CDSeqR: fast complete deconvolution for gene expression data from bulk tissues

Kai Kang [1,*,†], Caizhi David Huang [1,†], Yuanyuan Li [1], David M. Umbach[1], and Leping Li [1,*]

[1]Biostatistics and Computational Biology Branch, National Institute of Environmental Health

Sciences, Research Triangle Park, North Carolina, 27709, USA

[*]To whom correspondence should be addressed.

[†]These authors contribute equally.

Emails of corresponding authors: kangkai0714@gmail.com; li3@niehs.nih.gov

Abstract

Background: Biological tissues consist of heterogenous populations of cells. Because gene

expression patterns from bulk tissue samples reflect the contributions from all cells in the

tissue, understanding the contribution of individual cell types to the overall gene expression in

the tissue is fundamentally important. We recently developed a computational method, CDSeq,

that can simultaneously estimate both sample-specific cell-type proportions and cell-type-

specific gene expression profiles using only bulk RNA-Seq counts from multiple samples. Here

we present an R implementation of CDSeq (CDSeqR) with significant performance improvement

over the original implementation in MATLAB and an added new function to aid cell type

annotation. The R package would be of interest for the broader R community.

Result: We developed a novel strategy to substantially improve computational efficiency in

both speed and memory usage. In addition, we designed and implemented a new function for

annotating the CDSeq estimated cell types using single-cell RNA sequencing (scRNA-seq) data.

This function allows users to readily interpret and visualize the CDSeq estimated cell types. In

addition, this new function further allows the users to annotate CDSeq-estimated cell types

using marker genes. We carried out additional validations of the CDSeqR software using

synthetic, real cell mixtures, and real bulk RNA-seq data from the Cancer Genome Atlas (TCGA)

and The Genotype-Tissue Expression (GTEx) project.

Conclusions: The existing bulk RNA-seq repositories, such as TCGA and GTEx, provide enormous

resources for better understanding changes in transcriptomics and human diseases. They are

also potentially useful for studying cell-cell interactions in the tissue microenvironment. Bulk

level analyses neglect tissue heterogeneity, however, and hinder investigation of a cell-type-

specific expression. The CDSeqR package may aid *in silico* dissection of bulk expression data,

enabling researchers to recover cell-type-specific information.

Keywords: Deconvolution, tissue heterogeneity, gene expression, CDSeq.

Background

Many biological samples present heterogeneity; namely, their cellular composition varies

phenotypically and functionally. The cell-type proportions can exhibit high variability cross

samples from the same tissue type, potentially indicating the occurrence of various

physiological and pathological activities in the samples. Therefore, knowing the cellular

composition of heterogeneous samples is important to better understand the roles of distinct

cell populations. For example, dissection of tumor-infiltrating immune cells holds promise for

gaining deeper insights into the underlying mechanisms of cancers, for discovering predictive

biomarkers, as well as for the development of novel treatment strategies [1,2]. Although single-

cell RNA sequencing has become popular, in addition to its high cost and sparse read counts,

isolating cells from solid tissues especially frozen tissues remains challenging. Moreover, the

inevitable sparsity of RNA molecules sequenced from frozen samples further challenges

computational techniques. Therefore, bulk RNA-seq data are still routinely generated in many

research projects. The heterogeneous nature of bulk RNA-seq, however, hampers efforts to

study how individual cell types in the tissue microenvironment influence the underlying biology

of interest. Computational deconvolution methods [3,4,13–16,5–12] are complementary to

single-cell analysis and are very useful tools for extracting cell-type-specific signals from bulk

measurements.

This work describes an R package (CDSeqR) implementation of CDSeq (complete deconvolution

using sequencing data) [5] that we recently developed in MATLAB. CDSeq was designed to

simultaneously estimate the cell-type-specific gene expression profiles (GEPs) and the sample-

specific cell-type proportions using bulk RNA-seq data without the need of reference GEPs (i.e.

expression of pure cell lines or scRNA-seq data). Here, we not only implemented a user-friendly

R version for CDSeq but also substantially improved its computational efficiency in both speed

and memory usage. Specially, we designed a dimension Reduction-Recover approach that is

automatically parallelized to facilitate computation. In addition, we implemented a new

functionality for annotating the CDSeq-estimated cell types using scRNA-seq data. Moreover,

we employed a recently published deconvolution benchmarking pipeline [17] to thoroughly test

CDSeqR using both cell mixtures [18] and simulated data [19–21]. Throughout the manuscript,

we refer to "CDSeqR" as the package and "CDSeq" as the deconvolution procedure.

Implementation

Statistical model

CDSeq employs a hierarchical Bayesian modeling strategy to account for the mixing process of

observed RNA reads from different cell types. Specifically, the gene expression of any particular

cell type, in the form of read counts, is modeled by a Dirichlet multinomial random variable and

the bulk measure is therefore a weighted sum of all cell types (i.e., Dirichlet multinomial

random variables) constituting the bulk tissue. Then, CDSeq uses a Gibbs sampler [5,22] for

parameter estimation. A detailed description of the model and solver can be found in [5].

A dimension reduce-recover strategy for fast deconvolution

A practical challenge for our original MATLAB implementation of CDSeq was the high

computational demand, especially for large datasets. The Gibbs sampler employed for

parameter estimation requires storage of several large vectors whose sizes are data-dependent;

therefore, it can be computationally demanding especially for large datasets. We propose a

novel strategy for alleviating this issue. Our strategy, named dimension Reduce-Recover,

consists of two steps: dimension reduction and dimension recovery. This approach was based

on the following assumption: cell proportions in each sample are invariant with respect to the

genes used in deconvolution. Specifically, for a bulk RNA-seq sample, the proportions of cell

types can be estimated using multiple subsets of randomly selected genes. Therefore, for a bulk

RNA-Seq dataset, we should be able to obtain the estimated cell-type proportions for each

sample in the dataset regardless of the subset of genes considered. This idea allows us to

calculate multiple independent estimates of cell-type proportions using many subsets of

randomly selected genes processed in parallel. The final estimate of the cell-type proportions is

the average of the independent estimates. We then estimate the cell-type specific gene

expression profiles by post-multiplying the input data matrix by a generalized inverse of the

matrix of final estimated cell-type proportions (Supplementary Methods). We have carried out

thorough testing and demonstrated that this approach substantially speeds up computation

without sacrificing the performance (see Supplementary Note for details, and Supplementary

Fig. S9). We further evaluated the effects of the size of the gene list and the block number on

the performance when using the Reduce-Recovery strategy (Supplementary Fig. S9).

Cell type assignment function in CDSeqR

Bulk tissue RNA-seq samples usually present a great degree of heterogeneity. For example,

cancer cells in a tumor exhibit a spectrum of phenotypic and transcriptomic stages [23]. This

spectrum makes the assignment of identified cell types to known cell types challenging. In our

original MATLAB version, the cell-type assignment was based on correlation analysis using a

user-provided pure cell line GEPs. While this option remains available, the increasing number of

publicly available single cell data sets, e.g. [21,24]., provide alternative GEPs for cell-type

assignment. Thus, in CDSeqR, we designed and implemented a new function to perform cell-

type assignment for the downstream processing of CDSeq estimated cell-type-specific GEPs. In

addition, there may be cases where reliable reference datasets from either pure cell line or

single cell RNA-seq may not be available. Annotation of CDSeq estimated cell types using cell

type marker genes can also be performed in CDSeqR.

Specifically, this new function, *cellTypeAssignSCRNA*, embodies three approaches to annotate

the CDSeq-estimated cell types. First, it employs correlation analysis to measure the similarity

between the CDSeq-estimated cell-type-specific GEPs and the summarized cell-type specific

gene expression profiles from scRNA-seq data. When scRNA-seq reference data are provided,

cellTypeAssignSCRNA first sums up the read counts of all cells from the same cell type to form

the aggregated cell-type specific gene expression profiles for each cell type in the scRNA-seq

data. Next, *cellTypeAssignSCRNA* performs pair-wise correlation analysis between the CDSeq

estimated GEPs and the scRNA-seq GEPs and assign the CDSeq estimated cell type to the cell

type in the scRNA-seq data with which it has the highest correlation. A threshold for the

correlation can be set *a priori*. Any CDSeq estimated cell types that failed to achieve the

correlation threshold would be considered unannotated. Note that it is possible that more

than one CDSeq estimated cell types can match the same cell type.

Second, cell annotation can also be achieved by clustering both the user-provided scRNA-seq

reference data with the pseudo scRNA-seq data generated from the CDSeq estimated cell-type

specific gene expression profiles. Under the assumption that the total read count of each CDSeq

estimated cell type follows a negative binomial distribution, *cellTypeAssignSCRNA* generates the

total synthetic read count for each CDSeq cell type using the CDSeq estimated GEPs for the cell

using the R function *rnbinom (n, size, mu)* where *n* can be any integer greater than or equal to 1

(See Supplementary Figures S11-S16) and, by default, *mu* (mean) and *size* (dispersion) are

estimated from the reference scRNA-seq. These default parameters in *rnbinom* can be

replaced by user-provided parameters. Next, *cellTypeAssignSCRNA* generates the synthetic

single-cell read counts for each CDSeq cell type using the CDSeq-estimated GEPs and the R

function *rmultinom(n, size, prob)*, with *n* being the number of pseudo cells per CDSeq estimated

cell type (same as the n in *rnbinom*), *size* set equal to the total read count for the cell type as

generated by the preceding call to *rnbinom*, and *prob* provided by CDSeq-estimated cell-type-

specific gene expression profile expressed as a multinomial parameter vector (i.e., expression

levels expressed as proportions that sum to one). The resulting synthetic scRNA-seq data can

then subsequently be combined with user provided scRNA-seq data for clustering analysis and

cell type annotation using the Seurat package [25,26]. The clustering algorithm implemented in

Seurat is a graph-based approach based on the outcomes of principal components analysis. The

number of clusters cannot be set explicitly but is affected by a resolution parameter; the larger

the resolution parameter is the more clusters will be returned. The cell types identified by

CDSeq from bulk RNA-seq data were clustered with the individual cells from the scRNA-seq data.

We then assigned CDSeq-identified cell types to the cell type from the scRNA-seq data to which

the majority of the cells in the cluster belong (Fig 1).

Lastly, in the case where the reference data are not available, *cellTypeAssignSCRNA* carried out

clustering analysis of the pseudo single-cell data generated from the CDSeq-estimated GEPs

using Seurat [25,26] and identifies the marker genes in each cluster for cell type annotation.

The marker genes for each cluster are identified by comparing their expression levels in the

cluster with those in all other clusters. We show that this approach works reasonably well (Fig.

4 and Supplementary Fig. S17, S18, S19 and S21) using synthetic mixtures of human brain cells

[21].

Results

We validated CDSeqR using both synthetic and cell mixtures [5] with known cell-type

composition and cell-type-specific GEPs. For cell mixtures, the CDSeqR estimates using the

Reduce and Recovery strategy matched the known cell-type-specific GEPs and sample-specific

cell-type proportions (Fig. 2) while reducing computational time by about 96% (from about 120

min to 5 min) compared to the original implementation. In our previous work, we compared

CDSeqR with seven other deconvolution methods [5]. Here, we employed a recently published

benchmark pipeline [17] to simulate data for extensive comparisons with additional existing

deconvolution methods. In total, we compared CDSeqR with 14 competing deconvolution

algorithms [6,16,35,27–34] (Fig. 3 and Supplementary Fig. S6-S8) including linseed [6]. CDSeqR

software and linseed both provided accurate cell-type proportion using similar amounts of

computer time (Supplementary Fig. S1-S5). We further evaluated CDSeq and our new cell type

annotation function by examining the results of using different number of cell types in the

synthetic mixtures generated from scRNA-seq data (Supplementary Fig. S10-S16). In addition,

we examined CDSeqR's ability to detect immune cell subtypes in PBMC mixtures, a challenging

problem referred to as deep deconvolution [18,28]. Specifically, we generated synthetic

mixtures from 8 immune subtypes: B cells, Cytotoxic T cells, Helper T cells, Memory T cells,

Monocytes, Naïve Cytotoxic T cells, Naïve T cells, and Natural killer T cells using scRNA-seq [19]

and demonstrated that CDSeqR was able to identify all the immune cell subtypes and provided

accurate estimates of cell type proportions (Supplementary Fig. S21 and S22). We further

tested CDSeqR using GTEx [36] and TCGA [37] datasets and showed that the CDSeq identified

cell types were consistent with the published single-cell RNA-Seq results [20,21]

(Supplementary Fig. S23 and S24).

One input parameter for CDSeq function is the number of cell types to be deconvolved. The

choice for the input is data dependent. For example, for a large dataset (e.g., >50), specifying a

large number of cell type may help CDSeqR to detect all the major cell types due to the GEP

heterogeneity even for a same cell type. Fortunately, CDSeqR allows the user to specify a range

of possible cell type numbers as an input vector. For each choice in the vector, CDSeqR will

perform computation in parallel and estimate the number of cell types based on the posterior

distribution of the underlying model. In all *in silico* mixtures tested, CDSeqR provided accurate

estimates for the number of cell types in the synthetic data.

In addition, one may use the cell type information in scRNA-seq data from the same tissue type

as a guide. Here we showed that using synthetic mixture datasets generated from scRNA-seq

data, the newly implemented cell type annotation function can successfully uncover the cell

types (Fig. 4 and Supplementary fig. S10-24). Our simulation studies suggested that when the

specified cell type number is larger than the true value, the cell type annotation function is able

to identify and combine those cell types that are similar into one (Supplementary Fig. 10-16).

Another challenge for deconvolution is deep deconvolution [28], namely, to infer component

subtypes from bulk tissues. For example, researchers are often interested in uncovering

immune cell subtypes among major immune cell populations. In our previous work [18], we

demonstrated that CDSeq was able to estimate immune cell subtypes from PBMC (peripheral

blood mononuclear cell) data using microarray data. In this work, we further investigated

CDSeq's ability to infer immune cell subtypes using synthetic mixtures generated from scRNA-

seq data [19]. Using a deconvolution benchmarking pipeline [17], we created 100 synthetic

mixtures of various proportions of the 8 immune cell subtypes: B cells, Monocytes, Helper T

cells, Natural killer cells, Cytotoxic T cells, Memory T cells, Naïve Cytotoxic T cells, and Naïve T

cells. The highly-correlated GEPs of several of the cell types present major challenge for

deconvolution methods. To test and validate the performance of CDSeqR, we ran CDSeqR by

specifying a range of varying numbers of cell types from 2 to 40. CDSeqR can automatically

identify similar cell types and merge them into one. CDSeqR was able to identify all 8 immune

210   cell subtypes when the input number of the cell types was set to be greater than 10 (Fig 5;

211   Supplementary Fig. S21 and S22).

a

b

Besides the synthetic data, to further showcase the utility of CDSeqR and the newly

implemented cell annotation function, we carried out deconvolution analysis of the RNA-seq

data from human frontal cortex (209 samples) from the GTEx V8 [36]. We used publicly

available brain single-cell RNA-seq data [21] as the reference for cell annotation. We set the

number of cell types from 50 to 100 and ran CDSeqR with a dilution factor of 100 to facilitate

computation. The result demonstrates that setting the number of cell types to 100 enabled

detection of the major cell types in heterogenous brain samples whereas a smaller number (e.g.,

50) failed to identify oligodendrocyte progenitor cell, a known major cell type (Supplementary

Fig.S23). Setting the cell types to be 100 is reasonable as the brain is heterogenous and cell

states are known to represent a continuum. This notion is consistent with the finding that, in

brain prefrontal cortex [21,38], many of the major cell types consist of multiple subtypes. For

example, excitatory neurons have more than ten subtypes [21,38]. In a second example, we

deconvolved TCGA tumor samples without using any references. See Supplementary Fig.S24 for

details.

Discussion

CDSeq is a complete deconvolution method that uses gene expression data alone to estimate

both sample-specific cell-type proportions and cell-type-specific gene expression profiles from

RNA-seq data [5]. CDSeq was originally developed in MATLAB. In this work, we developed an R

package, CDSeqR, for a broader group of users. Moreover, in the R implementation, we

substantially improved CDSeq's computational efficiency in both speed and memory usage.

Specifically, we proposed a novel strategy – Reduce and Recover – to allow CDSeq to run on

multiple processors simultaneously (parallelization). We further validated our CDSeqR package

using data from both *in silico* and *in vitro* cell mixtures. We compared the performance of

CDSeqR with that of 14 competing deconvolution method and showed that cell-type

proportions estimated by CDSeqR are as or more accurate than those estimated by the

competing methods. However, unlike many competing methods CDSeqR does not require

reference GEPs for deconvolution and also provides cell-type-specific GEP estimates. We

provided recommendations for parameter settings in Supplementary Table S1 and the

parameters we used in our results in Supplementary Table S2.

In the R package, we also implemented a new cell-type assignment function. This new function

takes advantage of the publicly available scRNA-seq datasets and use them as a reference to aid

the annotation and visualization of the CDSeq estimated cell types. Specifically, CDSeqR

transforms its estimated cell-type-specific GEPs into pseudo single-cell read counts (see

Methods). Next, the two single-cell datasets (i.e. the external experimental scRNA-seq and the

pseudo-scRNA-seq generated from CDSeq estimates) are combined and clustered using existing

software such as Seurat [25,26]. Lastly, CDSeqR annotates the CDSeq cell types using either

clustering analysis or correlation analysis (See Methods). In the case where no reference scRNA-

seq dataset is available, CDSeqR identifies marker genes and uses them to aid cell type

annotation.

The ongoing discovery of new cell subtypes [21,23,39] suggest that cell types may be better

described as a continuum rather than as a sequence of discrete states. This recognition,

consequently, brings challenges to deconvolution algorithms, especially for those that rely

reference gene expression profiles [4,16,28,40]. The references will not fully capture the

heterogeneity and the continuum of states exhibited by cell types in bulk tissues. Compared to

existing deconvolution methods, CDSeq employs an unsupervised framework (does not require

a reference panel) and can discover cell types in the data. Nonetheless, CDSeqR can only

predict discrete cell types, not cell continuum. However, we showed that CDSeqR can do more

than detect only major cell types but also can help users identify immune subtypes.

Since cell types represent a continuum, it is difficult to assign a value to the number of cell

types present. This issue is analogous to determining the number of clusters from a clustering

analysis. Nonetheless, we suggest that, in practice, one may set the number of cell types to be a

vector that covers a range of plausible values. For example, set parameter cell_type_number =

seq(20,100,10)) will allow CDSeq to try the number of cell types from 20 to 100 with an

increment of 10. One can then visualize the clustering results with experimental scRNA-seq

data using the cell-type annotation function and also consider the values of log posterior

reported by CDSeq as a reference to determine the appropriate number of cell types.

Importantly, the underlying biology would need to be considered when determining the

number cell types in the data.

Conclusion

We developed an R package for our complete deconvolution method [5] and implemented new

functions to improve computational efficiency. Our method employs an unsupervised learning

framework and requires no reference profile for the deconvolution procedure. We provided

multiple ways to help identify CDSeq-estimated cell types after deconvolution. When a reliable

single cell reference dataset is available, one can annotate deconvolved cell types using

correlation analysis or clustering analysis. In the case where a single cell reference is not

available, CDSeqR will identify marker genes for each deconvolved cell type to help users

annotate the identities of those cell types. Our method is also able to infer the number of cell

types from bulk RNA-seq measurements. In summary, we believe that our CDSeqR package will

be a valuable tool for computationally deciphering sample heterogeneity using bulk RNA-Seq

data.

Abbreviations

TCGA: The Cancer Genome Atlas

GTEx: The Genotype-Tissue Expression (GTEx) project

Availability and requirements

Project name: CDSeq R package

Project home page: https://github.com/kkang7/CDSeq_R_Package

Operating system: Platform independent

Programming language: R, C++, C.

Other requirements: None

License: GPL-3

Any restrictions to use by non-academics: None

Declarations

303   Ethics approval and consent to participate

304   Not Applicable.

Consent for publication

307   Not Applicable.

Availability of data and materials

310   Source code are available on Github (https://github.com/kkang7/CDSeq_R_Package) and CRAN

311   (https://cran.r-project.org/web/packages/CDSeq/index.html).

Competing interests

314   The authors declare that they have no competing interests.

Funding

317   This work was supported by Intramural Research Program of the National Institutes of Health,

318   National Institute of Environmental Health Sciences (ES101765). The funding body plays no

319   roles in the design of the study and collection, analysis, and interpretation of data and in writing

320   the manuscript.

Authors' contributions

LL, KK and DU conceived the project. KK designed the new strategy for parallelization and

developed the new function for annotating CDSeq-estimated cell types. KK and DH

implemented the R package. KK, DH and YL performed numerical testing and validations. All

authors contributed to the writing of the manuscript. LL guided the research. All authors read

and approved the final manuscript.

Acknowledgements

The authors thank the NIEHS Office of Scientific Computing for computing support and the

NIEHS Epigenomics and DNA Sequencing Core Facility for RNA-seq analysis of the cell mixture

samples.

Reference

1.   Demaria O, Cornen S, Daëron M, Morel Y, Medzhitov R, Vivier E. Harnessing innate

immunity in cancer therapy. Nature. 2019.

2.   Zheng C, Zheng L, Yoo JK, Guo H, Zhang Y, Guo X, et al. Landscape of Infiltrating T Cells in

Liver Cancer Revealed by Single-Cell Sequencing. Cell. 2017;

3.   Shen-Orr SS, Tibshirani R, Khatri P, Bodian DL, Staedtler F, Perry NM, et al. Cell type--

specific gene expression differences in complex tissues. Nat Methods. 2010;7(4):287–9.

4.   Newman AM, Steen CB, Liu CL, Gentles AJ, Chaudhuri AA, Scherer F, et al. Determining

cell type abundance and expression from bulk tissues with digital cytometry. Nat

Biotechnol. 2019;

5.   Kang K, Przytycka TM, Meng Q, Shats I, Umbach DM, Li M, et al. CDSeq: A novel complete

deconvolution method for dissecting heterogeneous samples using gene expression data.

PLOS Comput Biol [Internet]. 2019 Dec 2; Available from:

https://doi.org/10.1371/journal.pcbi.1007510

6.   Zaitsev K, Bambouskova M, Swain A, Artyomov MN. Complete deconvolution of cellular

mixtures based on linearity of transcriptional signatures. Nat Commun. 2019;

7.   Shen-Orr SS, Gaujoux R. Computational deconvolution: extracting cell type-specific

information from heterogeneous samples. Curr Opin Immunol. 2013;25(5):571–8.

8.   Erkkilä T, Lehmusvaara S, Ruusuvuori P, Visakorpi T, Shmulevich I, Lähdesmäki H.

Probabilistic analysis of gene expression measurements from heterogeneous tissues.

Bioinformatics. 2010;

9.   Qiao W, Quon G, Csaszar E, Yu M, Morris Q, Zandstra PW. PERT: a method for expression

deconvolution of human blood samples from varied microenvironmental and

developmental conditions. PLoS Comput Biol. 2012;8(12):e1002838.

10.   Gong T, Szustakowski JD. DeconRNASeq: a statistical framework for deconvolution of

heterogeneous tissue samples based on mRNA-Seq data. Bioinformatics.

2013;29(8):1083–5.

11.   Zhong Y, Wan YW, Pang K, Chow LML, Liu Z. Digital sorting of complex tissues for cell

type-specific gene expression profiles. BMC Bioinformatics. 2013;

12.   Gaujoux R, Seoighe C. Semi-supervised Nonnegative Matrix Factorization for gene

expression deconvolution: a case study. Infect Genet Evol. 2012;12(5):913–21.

13.   Li Y, Xie X. A mixture model for expression deconvolution from RNA-seq in

heterogeneous tissues. BMC Bioinformatics. 2013;14(5):S11.

14.   Ahn J, Yuan Y, Parmigiani G, Suraokar MB, Diao L, Wistuba II, et al. DeMix: Deconvolution

for mixed cancer transcriptomes using raw measured data. Bioinformatics. 2013;

15.   Newman AM, Liu CL, Green MR, Gentles AJ, Feng W, Xu Y, et al. Robust enumeration of

cell subsets from tissue expression profiles. Nat Methods. 2015;

16.   Wang X, Park J, Susztak K, Zhang NR, Li M. Bulk tissue cell type deconvolution with multi-

subject single-cell expression reference. Nat Commun. 2019;

17.   Avila Cobos F, Alquicira-Hernandez J, Powell JE, Mestdagh P, De Preter K. Benchmarking

of cell type deconvolution pipelines for transcriptomics data. Nat Commun. 2020;

18.   Kang K, Meng Q, Shats I, Umbach DM, Li M, Li Y, et al. CDSeq: A novel complete

deconvolution method for dissecting heterogeneous samples using gene expression data.

PLoS Comput Biol. 2019;

19.   Zheng GXY, Terry JM, Belgrader P, Ryvkin P, Bent ZW, Wilson R, et al. Massively parallel

digital transcriptional profiling of single cells. Nat Commun. 2017;

20.   Puram S V., Tirosh I, Parikh AS, Patel AP, Yizhak K, Gillespie S, et al. Single-Cell

Transcriptomic Analysis of Primary and Metastatic Tumor Ecosystems in Head and Neck

Cancer. Cell. 2017;

21.   Mathys H, Davila-Velderrain J, Peng Z, Gao F, Mohammadi S, Young JZ, et al. Single-cell

transcriptomic analysis of Alzheimer's disease. Nature. 2019;

22.   Griffiths TL, Steyvers M. Finding scientific topics. Proc Natl Acad Sci. 2004;

23.   Pastushenko I, Brisebarre A, Sifrim A, Fioramonti M, Revenco T, Boumahdi S, et al.

Identification of the tumour transition states occurring during EMT. Nature. 2018;

24.   Han X, Zhou Z, Fei L, Sun H, Wang R, Chen Y, et al. Construction of a human cell landscape

at single-cell level. Nature. 2020;

25.   Butler A, Hoffman P, Smibert P, Papalexi E, Satija R. Integrating single-cell transcriptomic

data across different conditions, technologies, and species. Nat Biotechnol. 2018;

26.   Stuart T, Butler A, Hoffman P, Hafemeister C, Papalexi E, Mauck WM, et al.

Comprehensive Integration of Single-Cell Data. Cell. 2019;

27.   Chambers JM, Hastie TJ. Statistical models in S. Statistical Models in S. 2017.

28.   Newman AM, Liu CL, Green MR, Gentles AJ, Feng W, Xu Y, et al. Robust enumeration of

cell subsets from tissue expression profiles. Nat Methods. 2015;12(5):453.

29.   Du R, Carey V, Weiss ST. DeconvSeq: Deconvolution of cell mixture distribution in

sequencing data. Bioinformatics. 2019;

30.   Hao Y, Yan M, Heath BR, Lei YL, Xie Y. Fast and robust deconvolution of tumor infiltrating

lymphocyte from expression profiles using least trimmed squares. PLoS Comput Biol.

2019;

31.   Riplley B, Venables B, Bates DM, Firth D, Hornik K, Gebhardt A. Package "MASS". Support

Functions and Datasets for Venables and Ripley's MASS. Document freely available on

the internet at: http://www. r-project. org. 2018.

32.   Altboum Z, Steuerman Y, David E, Barnett-Itzhaki Z, Valadarsky L, Keren-Shaul H, et al.

Digital cell quantification identifies global immune cell dynamics during influenza

infection. Mol Syst Biol. 2014;

33.   Friedman J, Hastie T, Tibshirani R. Regularization paths for generalized linear models via

coordinate descent. J Stat Softw. 2010;

34.   Jew B, Alvarez M, Rahmani E, Miao Z, Ko A, Garske KM, et al. Accurate estimation of cell

composition in bulk expression through robust integration of single-cell information. Nat

Commun. 2020;

35. Dong M, Thennavan A, Urrutia E, Li Y, Perou CM, Zou F, et al. SCDC: bulk gene expression

deconvolution by multiple single-cell RNA sequencing references. Brief Bioinform. 2021;

36. Aguet F, Barbeira AN, Bonazzola R, Brown A, Castel SE, Jo B, et al. The GTEx Consortium

atlas of genetic regulatory effects across human tissues. Science (80-). 2020;

37. Weinstein JN, Collisson EA, Mills GB, Shaw KRM, Ozenberger BA, Ellrott K, et al. The

cancer genome atlas pan-cancer analysis project. Nature Genetics. 2013.

38. Gandal MJ, Zhang P, Hadjimichael E, Walker RL, Chen C, Liu S, et al. Transcriptome-wide

isoform-level dysregulation in ASD, schizophrenia, and bipolar disorder. Science (80-).

2018;

39. Trapnell C. Defining cell types and states with single-cell genomics. Genome Res.

2015;25(10):1491–8.

40. Hunt GJ, Freytag S, Bahlo M, Gagnon-Bartsch JA. Dtangle: Accurate and robust cell type

deconvolution. Bioinformatics. 2019;

41. Ding J, Adiconis X, Simmons SK, Kowalczyk MS, Hession CC, Marjanovic ND, et al.

Systematic comparison of single-cell and single-nucleus RNA-sequencing methods. Nat

Biotechnol. 2020;

42. McKenzie AT, Wang M, Hauberg ME, Fullard JF, Kozlenkov A, Keenan A, et al. Brain Cell

Type Specific Gene Expression and Co-expression Network Architectures. Sci Rep. 2018;

Figure legend

Figure 1. Schematic illustration of our cell-type assignment approach. It consists of five steps: 1)

generating synthetic single-cell read counts (gray rectangles) for the CDSeq-estimated cell-type-

specific GEPs (white rectangles); 2) combining the pseudo scRNA-seq data with user-provided

scRNA-seq data (colored rectangles), then performing clustering using Seurat; 3) visualizing the

result using tSNE plot to show the 2D embedding of the clustering outcomes with differently

colored circles denoting distinctive cell types in the single-cell data and gray squares denoting

the CDSeq-identified cell types; 4) annotating each cluster to the cell type to which the majority

of the cells in the cluster belong; 5) assigning the CDSeq-identified cell types accordingly as in

step 4.

Figure 2. Results of CDSeqR analysis of the *in vitro* cell mixtures. The mixtures comprise 4 four

cell types: cancer-associated fibroblast, lymphocytes, normal breast cells, tumor cells (see

Supplementary Methods for details). We ran CDSeqR on 32 bulk RNA-seq samples with known

cell proportions in each sample [18] using 7 randomly sampled gene subsets of size 500 (7 data

blocks, each of 500 genes). In the first row, each point represents a sample (n=32); in the

second row, each point represents a gene (n=~19,000). True and estimated GEPs are

normalized as RPKM. The line in each panel is the x=y line.

Figure 3. Comparisons with existing deconvolution methods using data generated from

benchmark pipeline [17]. We compared CDSeqR with 14 other deconvolution methods using

synthetic mixtures generated from three scRNA-seq datasets [20,21,41]. The results for the

PBMC dataset [41] are shown here. The X-axis represents different deconvolution methods

whereas the Y-axis denotes the correlation between the estimated cell type proportions by

each method and the true cell type proportions. We generated 10 sets of 100 mixtures. Each

dot in the box plots represents a deconvolution result from one of the 10 sets. CDSeqRR refers

to deconvolution with the Reduce-Recover strategy whereas CDSeq denotes deconvolution

without using Reduce-Recover option Additional results of the comparisons are available in

Supplementary Fig. S6-S8.

Figure 4. Annotation of CDSeq-identified cell types. CDSeqR was run with the Reduce-Recover

option using 800 genes per block and 10 blocks. A reference scRNA-seq dataset was provided

for cell type annotation using clustering analysis (a-b) and correlation analysis (c-d). (a) UMAP

embeddings of reference scRNA-seq data (color dots) and pseudo single-cell data generated

from the CDSeq-estimated cell-type specific gene expression profiles (color squares). Each

distinct color in the UMAP plot denotes a cell type provided with the scRNA-seq annotation

given in [21]. There are 7 major cell types provided with the scRNA-seq: excitatory neuron (Ex),

inhibitory neuron (In), oligodendrocyte (Oli), microglia (Mic), endothelial (Endo), astrocyte (Ast)

and oligodendrocyte progenitor cell (OPC). The deconvolution result used 7 as the number of

cell types and for each CDSeq-estimated cell type, it generated 10 pseudo cells which

correspond to a color square in the UMAP plot. The colors of the squares (i.e. CDSeq estimated

cell types) were determined based on its annotation result. (b) correlations between the

resulting CDSeqR estimated cell type proportions and true proportions; (c) correlations

between the CDSeqR estimated cell-type-specific GEPs and scRNA-seq GEPs; (d) correlation of

CDSeq-estimated cell type proportions with true proportions using correlation analysis (see

Methods for details). When reference for cell annotation is not provided, CDSeq will perform

clustering analysis on the pseudo single-cell data generated from the CDSeq-estimated cell-type

specific gene expression profiles and perform differential gene expression analysis to identify

the marker genes in each cluster using the Seurat software [25,26]. (e) Expression level of PLP1

(Oligodendrocyte marker [42]) in the clusters of CDSeq-estimated cell types (cell type number is

7); (f) Expression level of PLP1 in human brain prefrontal cortex scRNA-seq clusters [21]. See

Supplementary Figure S10-S20 for more details.

Figure 5. Results of deconvolution of PBMC immune cell subtype mixtures using Reduce-

Recover strategy. The number of cell types was set to be 20. (a) Correlation between the CDSeq

estimated cell-type-specific GEPs and true cell-type-specific GEPs; (b) Correlation between

CDSeq estimated sample-specific cell-type proportions and true cell type proportions.

Additional results for different specifications of the cell types are provided in Supplementary Fig.

S21 and S22.

Additional files

File name: Additional file 1

Title: Supplementary Note for CDSeqR

Description: Supplementary methods, tables and figures