CDSeqR: fast complete deconvolution for gene expression data from bulk tissues

Kai Kang [1,*,†], Caizhi David Huang [1,†], Yuanyuan Li [1], David M. Umbach[1], and Leping Li [1,*]

[1]Biostatistics and Computational Biology Branch, National Institute of Environmental Health Sciences, Durham, North Carolina, 27709, USA

[*]To whom correspondence should be addressed.

[†]These authors contribute equally.

Abstract

Background: Biological tissues consist of heterogenous populations of cells. Because gene

expression patterns from bulk tissue samples reflect the contributions from all cells in the

tissue, understanding the contribution of individual cell types to the overall gene expression in

the tissue is fundamentally important. We recently developed a computational method, CDSeq,

that can simultaneously estimate both sample-specific cell-type proportions and cell-type-

specific gene expression profiles using only bulk RNA-Seq counts from multiple samples. Here

we present an R implementation of CDSeq (CDSeqR) with significant performance improvement

over the original implementation in MATLAB and with a new function to aid interpretation of

deconvolution outcomes. The R package would be of interest for the broader R community.

Result: We developed a novel strategy to substantially improve computational efficiency in

both speed and memory usage. In addition, we designed and implemented a new function for

annotating CDSeq-estimated cell types using publicly available single-cell RNA sequencing

(scRNA-seq) data (single-cell data from 20 major organs are included in the R package). This

function allows users to readily interpret and visualize the CDSeq-estimated cell types. We

carried out additional validations of the CDSeqR software with *in silico* and *in vitro* mixtures and

with real experimental data including RNA-seq data from the Cancer Genome Atlas (TCGA) and

The Genotype-Tissue Expression (GTEx) project.

Conclusions: The existing bulk RNA-seq repositories, such as TCGA and GTEx, provide enormous

resources for better understanding changes in transcriptomics and human diseases. They are

also potentially useful for studying cell-cell interactions in the tissue microenvironment.

However, bulk level analyses neglect tissue heterogeneity and hinder investigation in a cell-

type-specific fashion. The CDSeqR package can be viewed as providing *in silico* single-cell

dissection of bulk measurements. It enables researchers to gain cell-type-specific information

from bulk RNA-seq data.

Keywords: Deconvolution, tissue heterogeneity, gene expression, CDSeq.

Background

Many biological samples present heterogeneity; namely, their cellular composition varies

phenotypically and functionally. The cell-type proportions can exhibit high variability cross

samples from the same tissue type, potentially indicating the occurrence of various

physiological and pathological activities in the samples. Therefore, knowing the cellular

composition of heterogeneous samples is important to better understand the roles of distinct

cell populations. For example, dissection of tumor-infiltrating immune cells holds promise for

gaining deeper insights into the underlying mechanisms of cancers, for discovering predictive

biomarkers, as well as for the development of novel treatment strategies [1,2]. Although single-

cell RNA sequencing has become popular, in addition to its high cost and sparse read counts,

isolating cells from solid tissues especially frozen tissues remains challenging. Moreover, the

inevitable sparsity of RNA molecules sequenced from frozen samples further challenges

computational techniques. Therefore, bulk RNA-seq data are still routinely generated in many

research projects. The heterogeneous nature of bulk RNA-seq, however, hampers efforts to

study how individual cell types in the tissue microenvironment in influence the underlying

biology of interest. Computational deconvolution methods [3–16] are complementary to single-

cell analysis and are very useful tools for extracting cell-type-specific signals from bulk

measurements.

This work describes an R package (CDSeqR) implementation of CDSeq (complete deconvolution

using sequencing data) that we recently developed in MATLAB. CDSeq [9] was designed for

simultaneously estimating cell-type-specific gene expression profiles (GEPs) and sample-specific

cell-type proportions using bulk RNA-seq data without providing reference GEPs (i.e. pure cell

line expressions or scRNA-seq data) to the deconvolution procedure. Here, we not only

implemented a user-friendly R version for CDSeq but also substantially improved its

computational efficiency in both speed and memory usage. Specially, we designed a dimension

Reduction-Recover approach that is automatically parallelized to facilitate computation. In

addition, we implemented a new function for assigning the CDSeq-estimated cell types using

publicly available scRNA-seq data. Furthermore, we thoroughly tested CDSeqR using both

simulated and real benchmark data [9].

Implementation

Statistical model

CDSeq employs a hierarchical Bayesian modeling strategy to account for the mixing process of

observed RNA reads from different cell types. Specifically, the gene expression of any particular

cell type, in the form of read counts, is modeled by a Dirichlet multinomial random variable and

the bulk measure is therefore a weighted sum of all cell types (i.e., Dirichlet multinomial

random variables) constituting the bulk tissue. Then, CDSeq uses a Gibbs sampler [9,17] for

parameter estimation. A detailed description of the model and solver can be found in [9].

A dimension reduce-recover strategy for fast deconvolution

A practical challenge for our original MATLAB implementation of CDSeq was the high

computational demand, especially for large datasets. The Gibbs sampler employed for

parameter estimation requires storage of several large vectors whose sizes are data-

dependent; therefore, it can be computationally demanding especially for large datasets. We

propose a novel strategy for alleviating this issue. Our strategy, named dimension Reduce-

Recover, consists of two steps: dimension reduction and dimension recovery. This approach

was based on the following assumption: cell proportions in each sample are invariant with

respect to the genes used in deconvolution. Specifically, for a bulk RNA-seq sample, the

proportions of cell types can be estimated using multiple subsets of randomly selected genes.

Therefore, for a bulk RNA-Seq dataset, we should be able to obtain the estimated cell-type

proportions for each sample in the dataset regardless of the subset of genes considered. This

idea allows us to perform multiple independent estimations of cell-type proportions using

many subsets of randomly selected genes processed in parallel. The final estimate of the cell-

type proportions is the average of the independent estimates. We then estimate the cell-type

specific gene expression profiles by post-multiplying the input data matrix by a generalized

inverse of the matrix of final estimated cell-type proportions (Supplementary Methods). We

have carried out thorough testing and demonstrated that this approach substantially speeds up

computation without sacrificing performance (see Supplementary Note for details).

A new cell type assignment function in CDSeqR

Deconvolution results from bulky tissue RNA-seq samples usually present a greater degree of

heterogeneity than those from cell mixtures or *in silico* experiments. We have found that, for

comprehensive cell-type discovery, the algorithm's parameter governing number of cell types

to be deconvolved must be set large. For example, cancer cells in a tumor exhibit a spectrum of

phenotypic and transcriptomic stages [18]. This spectrum makes the assignment of identified

cell types to known cell types challenging. In our original MATLAB version, the cell-type

assignment was based on correlation analysis using a user-provided pure cell line GEP. While

this option remains available, the increasing number of publicly available single cell data

provide alternative GEPs for cell-type assignment. Thus, in CDSeqR, we designed and

implemented a new function to perform cell-type assignment for the downstream processing of

cell-type-specific GEPs. The cell-type assignment function takes advantage of publicly available

scRNA-seq data such as in [19,20].

Specifically, we generated the synthetic scRNA-seq data in two steps. First, under the

assumption that the total read count of each CDSeq-estimated cell type followed a negative

binomial distribution, we randomly generated the total synthetic read count for each cell type

using the R function *rnbinom (n, size, mu)* with *n* set equal to 1 and, by default, *mu* set equal to

the maximum of all single-cell read counts in the single-cell data set and *size* set equal to *mu²*

(so that the negative binomial variance was $mu + mu^2/size = mu + 1$). These default parameters

in *rnbinom* can be replaced by user-provided parameters. Second, we generated the synthetic

single-cell read counts of every gene for each CDSeq-estimated cell type based its

corresponding CDSeq-estimated gene expression profile using the R function *rmultinom(n, size,*

prob), with *n = 1*, *size* set equal to the total read count for the cell type as generated by the

preceding call to *rnbinom*, and *prob* provided by CDSeq-estimated cell-type-specific gene

expression profile expressed as a multinomial parameter vector (i.e., expression levels

expressed as proportions that sum to one). The resulting synthetic scRNA-seq data are

subsequently combined with publicly available scRNA-seq data.

We then performed clustering analysis on the combined dataset using the Seurat package

[21,22]. The clustering algorithm implemented in Seurat is a graph-based approach based on

the outcomes of principal components analysis. The number of clusters cannot be set explicitly

but is affected by a resolution parameter; the larger the resolution parameter is the more

clusters will be returned. The cell types identified by CDSeq from bulk RNA-seq data were

clustered with the individual cells from the scRNA-seq data. We then assigned CDSeq-identified

cell types to the cell type from the scRNA-seq data to which the majority of the cells in the

cluster belong (Fig 1).

Figure 1. Schematic illustration of our cell-type assignment approach. It consists of five steps: 1)

generating synthetic single-cell read counts (gray rectangles) for the CDSeq-estimated cell-type-

specific GEPs (white rectangles); 2) combining the pseudo scRNA-seq data with experimental

scRNA-seq data with cell annotation (colored rectangles), then performing clustering using

Seurat; 3) visualizing the result using the tSNE plot to show the 2D embedding of the clustering

outcome with differently colored circles denoting distinctive cell types in the single-cell data

and gray squares denoting the CDSeq-identified cell types; 4) annotating each cluster to the cell

type to which the majority of the cells in the cluster belong; 5) assigning the CDSeq-identified

cell types accordingly as in step 4.

Results

We validated CDSeqR using both *in silico* and *in vitro* mixtures [9] where both cell-type

composition and cell-type-specific GEPs are known. For *in vitro* mixtures, the CDSeqR estimates

matched the known cell-type-specific GEPs and sample-specific cell-type proportions (Fig. 2)

while reducing computational time by about 96% (from about 120 min to 5 min). In our

previous work, we compared CDSeq with seven other deconvolution methods and illustrated its

advantages [9]. Here, we further compared CDSeqR with a recently developed complete

deconvolution method, linseed [10], that was not part of our previous comparison. CDSeqR

software and linseed both provided accurate cell-type proportion using similar amounts of

computer time; however, linseed cannot estimate cell-type-specific GEPs (Supplementary Fig.

S1-S5). We further tested CDSeqR using TCGA data and showed that CDSeqR-identified cell

types are consistent with single-cell RNA-Seq results (Puram et al., 2017) (Supplementary Fig.

S5).

Figure 2. Results of CDSeqR analysis of the *in vitro* cell mixtures. We ran CDSeqR on 32 bulk

RNA-seq samples with known cell proportions in each sample [23] using 7 randomly sampled

gene subsets of size 500 (7 data blocks, each of 500 genes). CDSeqR finished within 5 minutes

on an iMAC with 3.5GHz Intel Core i7 processor whereas the original CDSeq (MATLAB version)

took about 2 hours. In the first row, each point represents a sample (n=32); in the second row,

each point represents a gene (n=~19,000). True and estimated GEPs are normalized as RPKM.

The line in each panel is the x=y line.

One input parameter that CDSeq uses is the number of cell types to be deconvolved. We

suggest setting a large number of cell types when deconvolving real bulk RNA-seq samples. We

found that, when the number of cell types is set too small, the algorithm may fail to capture the

major cell types due to heterogeneity within those cell types [18]. The input for the appropriate

number of cell types is data-dependent. More tissue samples may require a larger number of

cell types to allow CDSeq to detect all the major cell types. The implementation allows one to

set the number of cell types to be a vector. Then, CDSeqR will perform computation in parallel

for each value in the vector and see which value yields the cell types that are in a better

agreement with the single-cell data. As an example, we showcased the usage of deconvolution

using CDSeqR and our new cell-type annotation function by deconvolving the GTEx

(www.gtexportal.org) V8 frontal cortex data (209 samples). We also used publicly available

brain single cell RNA-seq data to assign the CDSeq-estimated cell types [20]. The result

demonstrates that setting the number of cell types to 200 enabled detection of the major cell

types in heterogenous brain samples (Fig. 3). Although 200 may seem large, it may be justifiable

because the brain is highly heterogenous and cell states are known to represent a continuum.

This notion is consistent with the finding that, in brain prefrontal cortex [20,24], many of the

major cell types consist of multiple subtypes. For example, excitatory neurons have more than

ten subtypes [20,24].

Fig. 3. tSNE plot of the CDSeq-identified cell types in 209 GTEx frontal cortex RNA-seq bulk

tissue samples and annotated individual cells from scRNA-seq data [20]. In the tSNE plot, the

colored dots represent single cells of brain prefrontal cortex tissues from 48 individuals [20].

The colored squares denote the 200 CDSeq-identified cell types. As shown, CDSeq-estimated

cell types overlapped with all major clusters of single cells. CDSeqR identified the following cell

types: excitatory neurons (Ex), inhibitory neurons (In), Oligodendrocyte (Oli), microglia (mic),

oligodendrocyte progenitor cell (opc), astrocytes (ast), and endothelia (endo).

Discussion and Conclusions

CDSeq is a complete deconvolution method that uses gene expression data alone to estimate

both sample-specific cell-type proportions and cell-type-specific gene expression profiles [9].

CDSeq was originally developed in MATLAB. In this work, we developed an R package, CDSeqR,

for a broader group of users. Moreover, in the R implementation, we substantially improved

CDSeq's computational efficiency in both speed and memory usage. Specifically, we proposed a

novel strategy – Reduce and Recover – to allow CDSeq to run on multiple processors

simultaneously (parallelization). We further validated CDSeqR package using both *in silico* and

in vitro cell mixture data. We compared CDSeqR performance with another recently developed

complete deconvolution method and showed that, using similar amounts of computational

time, cell-type proportions estimated by CDSeqR are as accurate as those estimated by linseed;

but CDSeqR also provides cell-type-specific GEP estimates, whereas linseed does not.

In the R package, we also implemented a new cell-type assignment function. This new function

utilizes publicly available scRNA-seq datasets to help annotate and visualize CDSeq-estimated

cell types. In our R package, we provided publicly available scRNA-seq datasets for the major

human organs from the human cell landscape [19]; single cells in these data sets are already

annotated as to cell type. We transform the CDSeqR estimated cell-type-specific gene

expression profiles into "single-cell read counts" (synthetic scRNA-seq data). We then combine

our synthetic scRNA-seq data with experimentally obtained scRNA-seq as a single data matrix

for clustering. We identify the CDSeqR estimated cell types within a cluster by the cell type of

majority of the previously annotated single cells in that cluster.

As single-cell studies become popular, the complex nature of cell types is more clearly

recognized as new cell subtypes continue to be discovered [18,20,25]. Those findings suggest

that cell types may be better described as a continuum rather than as a sequence of discrete

states. This recognition, consequently, brings challenges to deconvolution algorithms, especially

for those that rely reference gene expression profiles [4,8,26,27]. The references will not fully

capture the heterogeneity and the continuum of states exhibited by cell types in bulk tissues.

Compared to existing deconvolution methods, CDSeq can mitigate such issues of heterogeneity

owing to its unsupervised framework (does not require a reference panel). We provide a guide

for users to assess the number of cell types input to CDSeq for identifying the major cell types

and their associated subtypes.

Since cell types represent a continuum, it is difficult to assign a value to the number of cell

types present. This issue is analogous to determining the number of clusters from a clustering

analysis. Nonetheless, we suggest that, in practice, one may set the number of cell types to be a

vector that covers a range of plausible values. For example, set parameter cell_type_number =

seq(20,100,10)) will allow CDSeq to try the number of cell types from 20 to 100 with an

increment of 10. One can then visualize the clustering results with experimental scRNA-seq

data using the cell-type annotation function and also consider the values of log posterior

reported by CDSeq as a reference to determine the appropriate number of cell types.

Complete deconvolution presents a different challenge – the assignment of biological identities

to the nominal cell types identified by the algorithm. CDSeqR employs a new approach to deal

with this challenge. Our approach takes advantage of the large amount of existing scRNA-seq

data. By converting CDSeqR-estimated gene expression profiles to "single cell read counts", one

can easily assign the identified cell types to existing known cell types based on publicly available

single-cell data.

In summary, we believe that our CDSeqR package will be a valuable tool for computationally

deciphering sample heterogeneity using bulk RNA-Seq data.

Availability and requirements

Project name: CDSeq R package

Project home page: https://github.com/kkang7/CDSeq_R_Package

Operating system: Platform independent

Programming language: R, C++, C.

Other requirements: None

License: GPL-3

Any restrictions to use by non-academics: None

Declarations

Ethics approval and consent to participate

Not Applicable.

Consent for publication

Not Applicable.

Availability of data and materials

Source code are available on Github.

Competing interests

The authors declare that they have no competing interests.

Funding

This work was supported by Intramural Research Program of the National Institutes of Health,

National Institute of Environmental Health Sciences (ES101765).

Authors' contributions

LL, KK and DU conceived the project. KK designed the new strategy for parallelization and

developed the new function for annotating CDSeq-estimated cell types. KK and DH

implemented the R package. KK, DH and YL performed numerical testing and validations. All

authors contributed to the writing of the manuscript. LL guided the research. All authors read

and approved the final manuscript.

Acknowledgements

The authors thank the NIEHS Office of Scientific Computing for computing support and the

NIEHS Epigenomics and DNA Sequencing Core Facility for RNA-seq analysis of the cell mixture

samples.

Reference

1.　Demaria O, Cornen S, Daëron M, Morel Y, Medzhitov R, Vivier E. Harnessing innate

immunity in cancer therapy. Nature. 2019.

2.　Zheng C, Zheng L, Yoo JK, Guo H, Zhang Y, Guo X, et al. Landscape of Infiltrating T Cells in

Liver Cancer Revealed by Single-Cell Sequencing. Cell. 2017;

3.　Shen-Orr SS, Tibshirani R, Khatri P, Bodian DL, Staedtler F, Perry NM, et al. Cell type--

specific gene expression differences in complex tissues. Nat Methods. 2010;7(4):287–9.

4.　Newman AM, Steen CB, Liu CL, Gentles AJ, Chaudhuri AA, Scherer F, et al. Determining

cell type abundance and expression from bulk tissues with digital cytometry. Nat

Biotechnol. 2019;

5.　Li Y, Xie X. A mixture model for expression deconvolution from RNA-seq in

heterogeneous tissues. BMC Bioinformatics. 2013;14(5):S11.

6.　Ahn J, Yuan Y, Parmigiani G, Suraokar MB, Diao L, Wistuba II, et al. DeMix: Deconvolution

for mixed cancer transcriptomes using raw measured data. Bioinformatics. 2013;

7.   Newman AM, Liu CL, Green MR, Gentles AJ, Feng W, Xu Y, et al. Robust enumeration of

cell subsets from tissue expression profiles. Nat Methods. 2015;

8.   Wang X, Park J, Susztak K, Zhang NR, Li M. Bulk tissue cell type deconvolution with multi-

subject single-cell expression reference. Nat Commun. 2019;

9.   Kang K, Przytycka TM, Meng Q, Shats I, Umbach DM, Li M, et al. CDSeq: A novel complete

deconvolution method for dissecting heterogeneous samples using gene expression

data. PLOS Comput Biol [Internet]. 2019 Dec 2; Available from:

https://doi.org/10.1371/journal.pcbi.1007510

10.   Zaitsev K, Bambouskova M, Swain A, Artyomov MN. Complete deconvolution of cellular

mixtures based on linearity of transcriptional signatures. Nat Commun. 2019;

11.   Shen-Orr SS, Gaujoux R. Computational deconvolution: extracting cell type-specific

information from heterogeneous samples. Curr Opin Immunol. 2013;25(5):571–8.

12.   Erkkilä T, Lehmusvaara S, Ruusuvuori P, Visakorpi T, Shmulevich I, Lähdesmäki H.

Probabilistic analysis of gene expression measurements from heterogeneous tissues.

Bioinformatics. 2010;

13.   Qiao W, Quon G, Csaszar E, Yu M, Morris Q, Zandstra PW. PERT: a method for expression

deconvolution of human blood samples from varied microenvironmental and

developmental conditions. PLoS Comput Biol. 2012;8(12):e1002838.

14.   Gong T, Szustakowski JD. DeconRNASeq: a statistical framework for deconvolution of

heterogeneous tissue samples based on mRNA-Seq data. Bioinformatics.

2013;29(8):1083–5.

15.   Zhong Y, Wan YW, Pang K, Chow LML, Liu Z. Digital sorting of complex tissues for cell

type-specific gene expression profiles. BMC Bioinformatics. 2013;

16. Gaujoux R, Seoighe C. Semi-supervised Nonnegative Matrix Factorization for gene

expression deconvolution: a case study. Infect Genet Evol. 2012;12(5):913–21.

17. Griffiths TL, Steyvers M. Finding scientific topics. Proc Natl Acad Sci. 2004;

18. Pastushenko I, Brisebarre A, Sifrim A, Fioramonti M, Revenco T, Boumahdi S, et al.

Identification of the tumour transition states occurring during EMT. Nature. 2018;

19. Han X, Zhou Z, Fei L, Sun H, Wang R, Chen Y, et al. Construction of a human cell landscape

at single-cell level. Nature. 2020;

20. Mathys H, Davila-Velderrain J, Peng Z, Gao F, Mohammadi S, Young JZ, et al. Single-cell

transcriptomic analysis of Alzheimer's disease. Nature. 2019;

21. Butler A, Hoffman P, Smibert P, Papalexi E, Satija R. Integrating single-cell transcriptomic

data across different conditions, technologies, and species. Nat Biotechnol. 2018;

22. Stuart T, Butler A, Hoffman P, Hafemeister C, Papalexi E, Mauck WM, et al.

Comprehensive Integration of Single-Cell Data. Cell. 2019;

23. Kang K, Meng Q, Shats I, Umbach DM, Li M, Li Y, et al. CDSeq: A novel complete

deconvolution method for dissecting heterogeneous samples using gene expression

data. PLoS Comput Biol. 2019;

24. Gandal MJ, Zhang P, Hadjimichael E, Walker RL, Chen C, Liu S, et al. Transcriptome-wide

isoform-level dysregulation in ASD, schizophrenia, and bipolar disorder. Science (80-).

2018;

25. Trapnell C. Defining cell types and states with single-cell genomics. Genome Res.

2015;25(10):1491–8.

26.   Newman AM, Liu CL, Green MR, Gentles AJ, Feng W, Xu Y, et al. Robust enumeration of

342   cell subsets from tissue expression profiles. Nat Methods. 2015;12(5):453.

343   27.   Hunt GJ, Freytag S, Bahlo M, Gagnon-Bartsch JA. Dtangle: Accurate and robust cell type

344   deconvolution. Bioinformatics. 2019;