Deep learning integration of molecular and interactome data for protein-compound

interaction prediction

Narumi Watanabe, Yuuto Ohnuki, Yasubumi Sakakibara

Department of Biosciences and Informatics, Keio University, Yokohama, Kanagawa 223-

8522, Japan

Corresponding Author

Yasubumi Sakakibara

3-14-1 Hiyoshi, Kohoku-ku, Yokohama, 223-8522, Japan

Phone/FAX: +81-45-566-1791

E-mail: yasu@bio.keio.ac.jp.

Abstract

Motivation: Virtual screening, which can computationally predict the presence or absence of

protein-compound interactions, has attracted attention as a large-scale, low-cost, and short-

term search method for seed compounds. Existing machine learning methods for predicting

protein-compound interactions are largely divided into those based on molecular structure

data and those based on network data. The former utilize information on proteins and

compounds, such as amino acid sequences and chemical structures, and the latter utilize

interaction network data, such as data on protein-protein interactions and compound-

compound interactions. However, few attempts have been made to combine both types of

data in molecular information and interaction networks.

Results: We developed a deep learning-based method that integrates protein features,

compound features, and heterogeneous interactome data to predict protein-compound

interactions. The interactome data consist of protein-protein interactions and compound-

compound interactions. The performance evaluations show that our deep learning framework

for integrating molecular structure data and interactome data outperforms state-of-the-art

machine learning methods for protein-compound interaction prediction tasks. This reveals

that protein-protein interaction and compound-compound interaction networks capture

different perspectives than amino acid sequence homology and chemical structure similarity,

and they have a synergistic effect in improving prediction accuracy. Furthermore,

experiments on three datasets of different difficulties show that this method is more robust

than existing methods in accurately predicting interactions between proteins and compounds

that are unseen in the training samples.

Keywords

Protein-compound interaction, Deep learning, Heterogeneous interaction network, Integration

Introduction

Most compounds that currently act as drugs bind to target proteins that can cause disease, and

these compounds can control their functions. Therefore, it is necessary to search for

compounds that can interact with the target protein when developing new drugs, and this

process must be performed efficiently. However, determining the interaction of a large

number of protein-compound pairs via experiments is expensive in terms of time and cost.

Virtual screening that can computationally classify the presence or absence of protein-

compound interactions has attracted attention as a large-scale, low-cost, short-term search

method for hit compounds. In particular, the method of using machine learning for virtual

screening is considered to be applicable to a wide variety of proteins and compounds.

Machine learning-based methods for predicting protein-compound interactions are

largely divided into those based on molecular structure data and those based on network data.

The former use protein and compound data represented in amino acid sequences and

chemical structure formulas, and they can be applied to proteins when a docking simulation

cannot be performed because the three-dimensional structure is unknown. In our previous

study [1-3], using positive interactions between drug compounds and their target proteins

downloaded from DrugBank (a database that contains information on existing drug

compounds) [4] and negative interactions consisting of randomly combined compounds and

proteins, we performed binary classification using a support vector machine (SVM). A

prediction accuracy of 85.1% was achieved. Based on this result, we developed COPICAT, a

comprehensive prediction system for protein-compound interactions, which enabled us to

search for lead compounds from a huge compound database, PubChem [5], consisting of tens

of millions of compounds.

Deep learning, a method developed in the field of machine learning, has been used in

a variety of fields in recent years because it has achieved high prediction accuracy in fields

such as image recognition, speech recognition, and compound activity prediction [6]. Deep

learning-based protein-compound interaction prediction methods have been developed based

on molecular structure data [7-10]. However, these existing deep learning-based methods

utilize only information based on amino acid sequences and chemical structures, so the

functional properties of proteins and compounds have not yet been incorporated into

prediction.

The other type of machine learning approach for protein-compound interaction

prediction is based on network data. An interaction network is commonly used to

comprehensively represent interactions between molecules. For example, the protein-protein

interaction network represents the relationships among physically interacting proteins. In the

protein-protein interaction network, a node is a protein, and an edge is drawn between a pair

of proteins that interact with each other.

Some previous studies incorporated data from multiple interaction networks to predict

molecular interactions. For instance, multi-modal graphs were proposed to handle three types

of interactions: protein-protein, protein-drug, and polypharmacy side effects. A deep learning

method, Decagon [11], for multi-modal graphs was proposed to predict polypharmacy side

effects. DTINet [12] and NeoDTI [13] were designed and developed as graph-based deep

learning frameworks to integrate heterogeneous networks for drug-target interaction

predictions and drug repositioning. In particular, NeoDTI exhibited a substantial performance

improvement over other state-of-the-art prediction methods based on multiple interaction

network data.

In addition to predicting protein-compound interactions, several studies have

predicted other types of molecular interactions. Protein-protein interactions induce many

biological processes within a cell, and experiential and computational methods have been

developed to identify various protein-protein interactions. High-throughput experimental

methods such as yeast two-hybrid screening were developed to discover and validate protein-

protein interactions on a large scale. Computational methods for protein-protein interaction

predictions employ various machine learning methods, such as SVM with feature extraction

engineering [14]. The recurrent convolutional neural network (CNN), which is a deep

learning method, was applied to sequence-based prediction for protein-protein interactions

[15]. Compounds that can interact with each other are often represented as compound-

compound interactions (also known as chemical-chemical interactions); interactive

compounds tend to share similar functions. Compound-compound interactions, called drug-

drug interactions, can be used to predict side effects based on the assumption that interacting

compounds are more likely to have similar toxicity [16]. A computational approach to

compound-compound interaction predictions has been studied with various machine learning

methods, including end-to-end learning with a CNN based on the SMILES representation

[17].

The purpose of this study is to improve prediction accuracy by integrating molecular

structure data and heterogeneous interactome data into a deep learning method for predicting

protein-compound interactions. In addition to the molecular information (amino acid

sequence and chemical structure) itself, protein-protein interaction network data with similar

reaction pathways or physical direct binding and compound network data linking compounds

with similar molecular activities are incorporated into the deep learning model as multiple-

interactome data. To the best of our knowledge, there are no deep learning-based solutions

for predicting protein-compound interactions that integrate multiple heterogeneous

interactome data along with the direct input of amino acid sequences and chemical structures.

This study proposes a method for predicting protein-compound (drug-target)

interactions by combining protein features, compound features, and network context for both

proteins and compounds. The network context comes in the form of protein-protein

interactions from the STRING database [18], and the compound-compound interactions come

from the STITCH database [19]. The protein-protein interaction network and compound-

compound interaction network are processed using node2vec [20] to generate feature vectors

for each protein node and each compound node in the interaction networks in an

unsupervised manner. Each network-based representation is then combined with additional

features extracted from a CNN applied to the amino acid sequence of a protein and from the

extended-connectivity fingerprint (ECFP) of a compound. The final combined protein

representations and compound representations are used to make a protein-compound

interaction prediction with an additional fully connected layer. The overall learning

architecture is illustrated in Figure 1.

In the performance evaluations, we demonstrate that integrating the molecular

structure data and multiple heterogeneous interactome data has a synergistic effect in

improving the accuracy of protein-compound interaction prediction. Furthermore,

performance comparisons with state-of-the-art deep learning methods based on molecular

information [10] and those based on interaction network data [13] as well as the traditional

machine learning methods SVM and random forest show that our model exhibits significant

performance improvements in the most important evaluation measures: AUROC, AUPRC, F-

measure and accuracy, while the other methods show low values of these measures. Finally,

we analyse whether protein-protein interactions capture a different perspective than amino

acid sequence homology and whether compound-compound interactions capture a different

perspective than chemical structure similarity.

Methods

1D-CNN for Encoding Protein Data

First, the protein data were applied to a one-dimensional convolutional neural network (1D-

CNN). For the protein input, a one-hot vector was used for the distributed representation of

an amino acid sequence of 20 dimensions at a height and width of 8,923 dimensions with the

maximum length of amino acid sequences.

An amino acid sequence is a linear structure (1-D grid). In this study, a filter (kernel)

with a one-dimensional convolution operation was applied to the linear structure. Here, a

"one-dimensional" convolutional operation for linear structures was interpreted as scanning

the input structure in only one direction along the linear structure with a filter of the same

height (dimension) as that of the distributed representation of the input.

One-Dimensional (1D) Convolutional Layer

We denote $A = [\boldsymbol{a}_1^{(1)}, \boldsymbol{a}_2^{(1)}, ..., \boldsymbol{a}_q^{(1)}]$ as an input vector sequence that corresponds to the one-hot vector representation of an amino acid sequence (as illustrated in Figure 1). For a filter function in the *l*-th hidden layer of the CNN, the input is the set of feature maps in the (*l*-1)-th hidden layer $\boldsymbol{x}_{i:i+r-1,j}^{(l-1)} = c_{i,j}^{(l-1)} \in \mathbb{R}^{m \times n}$, where *r* is the size of the filter, *m* is the size of the feature map, and *n* is the number of feature maps. The output of the *k*-th filter is a feature map of the *l*-th layer $c_i^{(l,k)} \in \mathbb{R}^m$, which is defined as follows:

$$c_i^{(l,k)} = f\left(\mathbf{W}^{(l,k)} c_{i,j}^{(l-1)} + \mathbf{b}^{(l,k)}\right),$$

where *f* is an activation function (leaky-ReLU), $\mathbf{W}^{(l,k)} \in \mathbb{R}^{m \times n \times d}$ is the weight matrix of the *k*-th filter in the *l*-th convolutional layer, and $\mathbf{b}^{(l,k)}$ is the bias vector. The average-pooling mechanism is applied to every convolution output. To obtain the final output $\boldsymbol{y} = \{y^{(t,1)}, y^{(t,2)}, ..., y^{(t,s)}\}$, global max-pooling is used as follows:

$$y^{(t,k)} = \max_i(c_i^{(t,k)}),$$

where *t* represents the last layer of the CNN and *s* represents the number of filters in the last layer.

Extended-Connectivity Fingerprint (ECFP) for Compound Data

The extended-connectivity fingerprint (ECFP, also known as the circular fingerprint or Morgan fingerprint) [21] is the most commonly used feature representation for representing a property of the chemical structure of a compound. This algorithm first searches the partial structures around each atom recurrently, then assigns an integer identifier to each partial structure and expresses this as a binary vector by using a hash function. Potentially, an infinite number of structures exist in the chemical space; consequently, the ECFP requires vectors with a large number of bits (usually 1,024 - 2,048 bits). In this study, we employed an

ECFP with 1024 bits as the feature representation for the chemical structure of a compound.

Feature Representation Learning for Protein-protein and Compound-Compound

Interactions

A protein-protein interaction network that connects physically interacting proteins and a

compound-compound interaction network that connects compounds with similar molecular

activities were input as multiple-interactome data. First, each network was represented as a

graph. A node is a protein in the protein-protein network and a compound in the compound-

compound network. An edge is drawn between a pair of proteins (compounds) that interact

with each other. By applying this graph to "node2vec" [20], the feature vector of each node

was obtained in an unsupervised manner; node2vec is a deep learning method that learns the

feature representation of nodes in a graph and obtains a feature vector for each node.

Node2vec is a graph embedding algorithm that can be applied to any type of graph, and it can

learn a feature vector such that nodes that are nearby on the graph are also close in the

embedded feature space. In other words, the inner product of the feature vectors of the nearby

nodes is high. It is known that the accuracy of the node classification task and the link

prediction task using the obtained feature representations of nodes is higher than that of the

existing methods.

The node2vec algorithm was applied to the protein-protein interaction network and

the compound-compound interaction network. Using a protein and a compound as vertices,

the interaction networks were converted into graphs with edge weights based on the

reliability of the experimental data and the similarity in molecular activity. Node2vec

(version 0.2.2) from the Python library, which implemented the node2vec algorithm, was

applied to the converted graph. The node2vec parameters used the default values (embedding

dimensions: 128; number of nodes searched in one random walk: walk_length=80; number of

random walks per node: num_walk=10; control of probability of revisiting a walk node: p=1;

control of the search speed and range: r=1; whether to reflect the graph weight:

weight_key=weight).

Let a protein-protein interaction network be expressed by a weighted graph

$G_{protein} = (V_{protein}, E_{protein})$ and a compound-compound interaction network by a

weighted graph $G_{compound} = (V_{compound}, E_{compound})$. By applying node2vec to these

graphs, the feature representations can be obtained and are denoted as $N_{protein} =$

$\text{node2vec}(G_{protein}) \in \mathbb{R}^d$ and $N_{compound} = \text{node2vec}(G_{compound}) \in \mathbb{R}^d$ for a dimension

of d.

Deep Learning Model Structure for Integrating Molecular Information and the

Interaction Network

The feature vectors obtained from the 1D-CNN for the amino acid sequence and node2vec

for the protein-protein interaction network were concatenated and fed to the final output

layer. Similarly, the feature vectors from the ECFP for the chemical structure and node2vec

for the compound-compound interaction network were concatenated and fed to the final

output layer.

We designed an output layer consisting of an element-wise product calculation

followed by a fully connected layer, which is an extension of cosine similarity. The

architecture is illustrated in Figure 2. First, the feature vectors for the proteins and

compounds were mapped onto the same latent space with a fixed dimension d by applying

fully connected layers. The similarity between the vector for proteins and the vector for

compounds on the latent space was calculated by the element-wise product calculation

method followed by a fully connected layer. When a pair of proteins and compounds was

input, if the similarity was higher than some predefined threshold (where the default was 0.5),

it was predicted that there was an interaction between the input pair. If the similarity was

lower, it was predicted that there was no interaction. This model is denoted as the "integrated

model".

More precisely, let $\boldsymbol{a}_{protein}$ denote the feature vector output by the 1D-CNN for an

amino acid sequence, and let $\boldsymbol{b}_{compound}$ denote the feature vector of the ECFP for the

chemical structure of a compound. Let $\boldsymbol{N}_{protein}$ and $\boldsymbol{N}_{compound}$ denote the feature

representations obtained from node2vec for the protein-protein interaction network and the

compound-compound interaction network. Two feature vectors $\boldsymbol{a}_{protein}$ and $\boldsymbol{N}_{protein}$ were

concatenated as one vector $\boldsymbol{v}_{protein}$ for the protein multi-modal feature. Two feature vectors

$\boldsymbol{b}_{compound}$ and $\boldsymbol{N}_{compound}$ were concatenated as one vector $\boldsymbol{v}_{compound}$ for the compound

multi-modal feature. The concatenated feature vectors $\boldsymbol{v}_{protein}$ and $\boldsymbol{v}_{compound}$ were mapped

onto the same latent space with a fixed dimension d by applying the fully connected layers f

and g. From this, the similarity between the two vectors for the latent space was calculated.

$\boldsymbol{v}_{protein} = \mathrm{concat}(\boldsymbol{a}_{protein}, \boldsymbol{N}_{protein}),$

$\boldsymbol{v}_{compound} = \mathrm{concat}(\boldsymbol{b}_{compound}, \boldsymbol{N}_{compound}),$

$(x_1, x_2, \dots, x_d) = f(\boldsymbol{v}_{protein}),$

$(y_1, y_2, \dots, y_d) = g(\boldsymbol{v}_{compound}),$

$\mathrm{output}_{integrated} = h(x_1 \cdot y_1, x_2 \cdot y_2, \dots, x_d \cdot y_d).$

As described above, to handle data from different modalities such as proteins and

compounds, we adopted a method of embedding data of different modalities into a common

latent space. Defining the similarity in the obtained latent space enables the measurement of

the similarity between the data for different modalities. Visual semantic embedding (VSE) is

a typical example of a method that handles data from different modalities and can associate

images with text data in acquiring these multi-modal representations [22]. VSE was

developed to generate captions from images (image captioning). The image feature and the

sentence feature are linearly transformed and embedded into a common latent space.

Single-Modality Models

To see the effect of integrating multi-modal features, two baseline models were constructed

for the performance comparison. One was based on molecular structure data and used only

amino acid sequence and chemical structure information, and the other was based on

interaction network data and used only protein-protein interaction and compound-compound

interaction information. The single-modality model based on molecular structure data,

denoted the "single-modality model (molecular)", is defined as follows:

$(x_1, x_2, \ldots, x_n) = f(\boldsymbol{a}_{protein})$,

$(y_1, y_2, \ldots, y_n) = g(\boldsymbol{b}_{compound})$,

$\text{output}_{molecule} = h(x_1 \cdot y_1, x_2 \cdot y_2, \ldots, x_n \cdot y_n)$,

and the single-modality model based on interaction network data, denoted the "single-

modality model (network)", is defined as follows:

$(x_1, x_2, \ldots, x_n) = f(\boldsymbol{N}_{protein})$,

$(y_1, y_2, \ldots, y_n) = g(\boldsymbol{N}_{compound})$,

$\text{output}_{network} = h(x_1 \cdot y_1, x_2 \cdot y_2, \ldots, x_n \cdot y_n)$.

Loss Function

For the similarity output x of the model, the output value was restricted to the range 0 to 1 by

the sigmoid function, and cross entropy was applied as the loss function $L(\theta)$ to calculate the

training error.

Hyperparameter Optimization

The hyperparameters, the number and size of the filters in the convolutional layers in the 1D-

CNN, and the number of units in the fully connected output layers were optimized by the

Bayesian optimization tool Optuna [23], which is an automatic hyperparameter optimization

software framework particularly designed for machine learning. For the hyperparameter

optimization, the validation dataset was obtained by dividing the training samples into a set

for training and a set for validation.

Regularization

Regularization is important for avoiding overfitting and improving the prediction accuracy in

deep learning for complex model architectures with a large number of parameters.

Regularization is especially important in our deep learning model, which integrates multiple

datasets of different modalities; hence, we employed several regularization methods.

We employed batch normalization [24], which allowed us to use much higher

learning rates and be less careful about initialization, after each convolutional layer. We also

inserted dropout [25] after the fully connected layers. Furthermore, we added an L2

regularization term to the training-loss function $L(\theta)$. When incorporating weight decay, the

objective function to be optimized is as follows:

$$L(\theta) + \lambda \frac{1}{2} \sum_{w} \|w\|^2,$$

where w refers to the parameters of the entire model, and the second term of the above

equation indicates taking the sum of the squared values of all the parameters and dividing by

2. λ is a parameter that controls the strength of regularization. Adding this term to the

objective function has the effect of preventing the absolute value of the network weight from

becoming too large, which helps prevent overfitting.

Comparison with State-of-the-Art Existing Methods

The prediction performance of the proposed models was compared with that of state-of-the-

art deep learning methods based on molecular structure data and interaction network data.

The first method was based on a graph CNN for protein-compound prediction [10]. It

employed a graph CNN for encoding chemical structures and a CNN for n-grams of amino

acid sequences. The second method was NeoDTI [13], which demonstrated superior

performance over other previous methods based on multiple-interaction-network data. We

also compared our method with the traditional machine learning methods SVM and random

forest [26] as the baseline prediction methods. These traditional methods require structured

data as input. For the protein information, the 3-mer (3-residue) frequency in the amino acid

sequence was used as the feature vector for 8,000 dimensions. For the compound

information, an ECFP with a length of 1,024 and a radius of 2 was used. The radial basis

function (RBF) was used as the kernel function of SVM, and all other parameters of SVM

and random forest used the default values. In implementing these machine learning methods,

sckit-learn (version 0.19.1) and chainer (version 5.0.0) were used.

Datasets

The protein-compound interaction data and compound-compound networks were retrieved

from the database STITCH [19], and the protein-protein networks were retrieved from the

database STRING [18].

Protein-Compound Interaction Data

Protein-compound interaction data can be obtained from the STITCH database [19]. STITCH

contains data on the interaction of 430,000 compounds with 9.6 million proteins from 2,031

species. The STITCH data sources consist of (1) structure-based prediction results, such as

the genome context and co-expression; (2) high-throughput experimental data; (3) automatic

text mining; and (4) information from existing databases. When a protein-compound dataset

is downloaded from STITCH, a score based on the reliability is created for each of the above

four items for each protein-compound pair. For the protein-compound interaction data used in

this study (as a "positive" example), the threshold value for the reliability score of item (2)

was set to 700, and the data with a reliability score of 700 or higher were extracted from

STITCH so that interologs were eliminated and the data were composed of only

experimentally reliable interactions; the data that did not meet this threshold were removed.

For the STITCH data, interactions with a confidence score of 700 or more were determined

based on the criterion that they were at least highly reliable [27]. Of the combinations of

proteins and compounds, only pairs not stored in the STITCH database were taken as

"negative" examples. In general, protein-compound pairs that are not stored in STITCH have

very low confidence, with a score of 150 or less for their interaction [28], so these are

considered to be non-interacting negative examples. The ratio of the positive and negative

examples was 1 to 2.

Protein-Protein Interaction Data

The protein-protein interaction information was obtained from the STRING database [18],

which contains data for protein-protein interactions covering 24.6 million proteins from 5,090

species. The STRING data sources consist of (1) experimental data; (2) pathway databases;

(3) automatic text mining; (4) co-expression information; (5) neighbouring gene information;

(6) gene fusion information; and (7) co-occurrence-based information. In particular, item (1)

is interaction data obtained from actual experiments, which include biochemical, biophysical,

and genetic experiments. These are extracted from databases organized by the BioGRID

database [29] and the IMEx consortium [30]. When the protein-protein interaction data from

STRING were downloaded, a score based on the reliability was created for each of the above

seven items for each protein-protein pair. Regarding the protein-protein interaction network,

the threshold value for the reliability score of item (1) was set to 150. Data that did not satisfy

this criterion were removed.

Compound-Compound Interaction Data

The compound-compound interaction data were also obtained from the STITCH database.

The compound-compound interaction data in STITCH are based on (1) the chemical

reactions obtained from the pathway databases; (2) structural similarity; (3) association with

previous literature; and (4) correspondence between the compounds based on molecular

activity similarity. For the similarity of the molecular activities in item (4), the activity data

obtained by screening the model cell line NCI60 were used. When the compound-compound

interaction data were downloaded from STITCH, a score based on the reliability was created

for each of the above four items for each compound pair. For the compound-compound

interaction data used in this study, the threshold value for the reliability score in item (4) was

set to 150. Data that did not satisfy this criterion were removed.

Construction of the Baseline, Unseen Compound-Test, and Hard Datasets for Evaluation

From the STITCH and STRING databases, a total of 22,881 protein-compound interactions,

175,452 protein-protein interactions and 69,231 compound-compound interactions were

downloaded. Using the downloaded dataset in which the protein-protein interaction,

compound-compound interaction and protein-compound interaction data were all available,

the three types of datasets below were constructed to perform five-fold cross validation.

In typical k-fold cross validation, all positive and negative examples are randomly

split into k folds. One of them is used as a test sample, and the remaining $k-1$ are used as

training samples; then, the k results obtained are averaged. We call the cross-validation

dataset the *baseline dataset*.

In this study, as more difficult and more practical tasks, we constructed two more

cross-validation datasets, called the *unseen compound-test dataset* and the *hard dataset*. In

the unseen compound-test dataset, we split the data into *k* folds so that none of the folds

contain the same compounds as the others. In the unseen compound-test dataset, the

compounds in the test sample do not appear in the training sample. In other words, the

interaction of new (unseen) candidate compounds with the target proteins must be accurately

predicted. In the hard dataset, we split the data into *k* folds so that none of the folds contain

the same proteins and compounds as the others. In the hard dataset, neither the proteins nor

the compounds in the test sample appear in the training sample. In other words, interactions

in which neither the proteins nor the compounds are found in the training sample must be

accurately predicted.

Results

The following measures were used for the performance evaluation criteria: AUROC (area

under the receiver operating characteristic curve), AUPRC (area under the precision-recall

curve), F-measure, accuracy, precision and recall.

$\text{Accuracy} = \dfrac{TP + TN}{TP + FP + FN + TN},$

$\text{Precision} = \dfrac{TP}{TP + FP},$

$\text{Recall} = \dfrac{TP}{TP + FN},$

$\text{F-measure} = \dfrac{2 \times \text{Recall} \times \text{Precision}}{\text{Recall} + \text{Precision}},$

where *TP* is the number of true positives, *TN* is the number of true negatives, *FP* is the

number of false positives, and *FN* is the number of false negatives.

Effectiveness of Integrating Molecular Structure Data and Interaction Network Data

The performance of our three models was evaluated to determine the effectiveness of

integrating the molecular structure data and the interaction network data. The results on the

three datasets are shown in Tables 1-3. In the tables, the mean and standard deviation (SD)

for the five folds are shown. Furthermore, the symbol "*" indicates that there was a

significant difference in the Wilcoxon signed-rank test, with p-value $p < 0.05$, in comparison

with the integrated model.

Table 1. Performance comparison of three proposed models with existing methods on the

baseline dataset.

	AUROC	AUPRC	F-measure	Precision	Recall	Accuracy
Integrated model (molecular+network)	**0.972**±0.004	**0.954**±0.005	**0.900**±0.006	**0.890**±0.005	**0.911**±0.013	**0.933**±0.004
Single-modality model (molecular)	0.956±0.004*	0.927±0.006	0.868±0.009	0.856±0.015	0.880±0.014	0.911±0.006
Single-modality model (network)	0.947±0.008*	0.920±0.010	0.853±0.015	0.868±0.011	0.839±0.021	0.904±0.009
Graph CNN [10]	0.917±0.006*	0.850±0.006	0.794±0.014	0.803±0.009	0.786±0.023	0.864±0.008
NeoDTI [13]	0.956±0.005*	0.905±0.016	0.872±0.006	0.881±0.007	0.870±0.013	0.917±0.004
SVM	0.805±0.009*	0.651±0.012	0.743±0.012	0.783±0.009	0.708±0.018	0.837±0.006
Random forest	0.873±0.009*	0.767±0.015	0.837±0.012	0.871±0.010	0.806±0.015	0.895±0.007

409   **Table 2.** Performance comparison on the unseen compound-test dataset.

	AUROC	AUPRC	F-measure	Precision	Recall	Accuracy
Integrated model (molecular+network)	**0.890**±0.039	**0.842**±0.050	**0.727**±0.085	0.842±0.036	**0.647**±0.114	**0.843**±0.038
Single-modality model	0.869±0.027	0.786±0.023	0.657±0.053	0.770±0.015	0.579±0.086	0.802±0.017

(molecular)						
Single-modality model (network)	0.831±0.053	0.759±0.055	0.661±0.073	0.797±0.040	0.569±0.093	0.809±0.030
Graph CNN [10]	0.804±0.037*	0.679±0.031	0.637±0.027	0.681±0.011	0.600±0.046	0.773±0.009
NeoDTI [13]	0.823±0.067	0.773±0.064	0.621±0.062	**0.867**±0.034	0.490±0.069	0.805±0.024
SVM	0.765±0.020*	0.603±0.029	0.689±0.029	0.761±0.030	0.630±0.041	0.810±0.016
Random forest	0.770±0.023*	0.635±0.026	0.697±0.036	0.837±0.020	0.600±0.052	0.828±0.014

411 **Table 3.** Performance comparison on the hard dataset.

	AUROC	AUPRC	F-measure	Precision	Recall	Accuracy
Integrated model (molecular+network)	**0.882**±0.035	**0.834**±0.041	**0.714**±0.064	0.843±0.037	**0.625**±0.089	**0.836**±0.030
Single-modality model (molecular)	0.851±0.023	0.770±0.023	0.662±0.038	0.789±0.033	0.572±0.042	0.806±0.020
Single-modality model (network)	0.780±0.051*	0.706±0.040	0.601±0.057	0.777±0.033	0.492±0.065	0.784±0.023
Graph CNN [10]	0.707±0.038*	0.563±0.083	0.427±0.132	0.637±0.108	0.327±0.121	0.719±0.043
NeoDTI [13]	0.790±0.039*	0.715±0.046	0.297±0.084	**0.892**±0.023	0.188±0.063	0.719±0.018
SVM	0.652±0.019*	0.500±0.023	0.481±0.044	0.820±0.038	0.343±0.045	0.755±0.012
Random forest	0.605±0.033*	0.452±0.046	0.364±0.075	0.815±0.116	0.236±0.055	0.728±0.026

Compared with the two single-modality models, the integrated model significantly

improved the prediction accuracy in all evaluation measures. For example, in terms of

AUPRC, which is a more informative evaluation index in an dataset that is imbalanced

between positive and negative samples, the integrated model showed significant

improvements of 3.0%, 7.1% and 8.3% over the single-modality model (molecular) and

3.7%, 10.9% and 18.1% over the single-modality model (network) in the baseline dataset, the

unseen compound-test dataset and the hard dataset, respectively. This demonstrates that

integrating multiple heterogeneous interactome data with molecular structure data brought a

synergistic effect in improving the accuracy of protein-compound interaction prediction.

Performance Comparison with Other Existing Methods

The prediction performance of our three models was compared with that of state-of-the-art

deep learning methods and traditional machine learning methods based on molecular

structure data and interaction network data. The results on the three datasets are shown in

Tables 1-3.

The integrated model yielded superior prediction performance compared with the

other existing methods. In the baseline dataset, the integrated model achieved significant

improvements compared with the graph CNN-based method [10], NeoDTI [13] and the

traditional machine learning methods SVM and random forest (Table 1). In fact, the

Wilcoxon signed-rank test [31] verification for the AUROC index showed that the

performance difference was statistically significant, with a p-value $p<0.05$, and hence proved

the superiority of the integrated model.

In the unseen compound-test dataset and the hard dataset, a more remarkable

difference in the performance of the integrated model was confirmed. We compared the

integrated model with the graph CNN-based method and NeoDTI in terms of AUROC,

AUPRC and F-measure. The integrated model greatly outperformed the others, with

significant improvements (10.7% in terms of AUROC, 24.0% in terms of AUPRC and 14.1%

in terms of F-measure on the unseen compound-test dataset, and 24.8% in terms of AUROC,

48.1% in terms of AUPRC and 67.2% in terms of F-measure on the hard dataset) over the

graph CNN-based method. In comparison with NeoDTI, significant improvements were also

confirmed: 8.1% in terms of AUROC, 8.9% in terms of AUPRC and 17.1% in terms of F-

measure on the unseen compound-test dataset, and 11.6% in terms of AUROC, 16.6% in

terms of AUPRC and 140.4% in terms of F-measure on the hard dataset. Based on the above

results, the integrated model can predict protein-compound interactions with stable accuracy,

regardless of the difficulty of the dataset and the types of proteins and compounds that make

up the test data, compared to other existing methods. This is due to the integrated model

using features based on sequence information and compound structure information and

features obtained from the interaction network as well as the effect of using the element-wise

product of the protein feature vector and the compound feature vector in the output layer.

The single-modality model also yielded superior prediction performance compared

with the existing methods using the same-modality input data. The graph CNN-based

prediction method [10] obtains a compound feature vector by converting the chemical

structure into a graph and applying it to the graph CNN, and it obtains a protein feature vector

by splitting the amino acid sequence into n-grams and applying it to the CNN. Therefore, the

graph CNN-based method can be defined as having the same molecular structure data-based

prediction model as the single-modality model (molecular). In the baseline dataset, the

unseen compound-test dataset and the hard dataset, the single-modality model (molecular)

outperformed the graph CNN-based prediction method. For example, in the hard dataset, the

single-modality model (molecular) achieved an improvement of 20.4% in terms of AUROC,

36.8% in terms of AUPRC and 55.0% in terms of F-measure on the hard dataset over the

graph CNN-based method (Table 3). From this result, in protein-compound interaction

prediction, it is sufficient to use the ECFP as a feature representation for the compound

structure, compared with the deep learning method in which the compound structure is

converted into a graph structure and a graph CNN is applied.

NeoDTI takes protein-protein interaction and compound-compound interaction

information as input and predicts whether an edge is drawn between the compound and

protein nodes by learning to reconstruct the network. Therefore, NeoDTI can be defined as an

interaction network-based prediction model, which is the same as the single-modality model

(network). The difference is that the single-modality model (network) first uses unsupervised

deep learning (node2vec) to automatically learn feature representations for nodes in the given

heterogeneous interaction networks and then applies supervised learning to predict protein-

compound interactions based on the learned features, while NetoDTI simultaneously learns

the feature representations of nodes and protein-compound interactions in a supervised

manner. In the three datasets, the prediction performance of the single-modality model

(network) was comparable to that of NetoDTI.

Discussion

To interpret the accuracy improvement obtained by integrating multiple interactome data

with molecular structure data, which was shown in the previous section, we analysed whether

the protein-protein interaction captured a different perspective than amino acid sequence

homology and whether the compound-compound interaction captured a different perspective

than chemical structure similarity. More concretely, we investigated the relationship between

the amino acid sequence homology and the similarity of proteins in the protein-protein

interaction network as well as the relationship between the chemical structure similarity and

the similarity in the compound-compound interaction network.

488   For every pair of proteins in the dataset used in the experiments, the amino acid

sequence similarity was calculated using DIAMOND, and the cosine similarity between two

vectors of the pair output by node2vec using the protein-protein interaction network was

calculated. All of the protein pairs were plotted with the amino acid sequence similarity on

the x-axis and the cosine similarity in the protein-protein interaction network on the y-axis.

The scatter plot is shown in Figure 3 (top). Similarly, for every pair of compounds, the

Jaccard coefficient of the ECFPs of the two compounds and the cosine similarity between the

two vectors output by node2vec using a compound-compound interaction network were

calculated. All of the compound pairs were plotted with the Jaccard coefficient on the x-axis

and the cosine similarity in the compound-compound interaction network on the y-axis, as

shown in Figure 3 (bottom). In both scatter plots, no clear correlation was observed. In fact,

the correlation coefficients for each scatter plot were 0.186 and 0.199, respectively. In other

words, it was confirmed that the amino acid sequence similarity and the similarity in the

protein-protein interaction network were not proportional. Similarly, it was confirmed that

the chemical structure similarity and the similarity in the compound-compound interaction

network were not proportional. Therefore, we concluded that the protein-protein interaction

network captured a different perspective than the amino acid sequence homology and

compensated for it. The compound-compound interactions captured a different perspective

than the chemical structure similarity and compensated for it.

For example, the protein "5-hydroxytryptamine (serotonin) receptor 6, G protein-

coupled (HTR6)" and the compound "Mesulergine" in the test sample in the "hard dataset"

have a positive interaction [32], and our model succeeded in correctly predicting it. However,

the single-modality model (molecular) and graph CNN-based method failed to predict the

positive interaction; that is, both predicted that the pair would not interact. The most similar

protein-compound pair in the training sample to the pair HTR6 and Mesulergine was the

protein "adrenoceptor alpha 2A (ADRA2A)" and the compound "Pergolide" [33]. The

protein ADRA2A and the compound Pergolide have a positive interaction in the training

sample. The sequence similarity score between HTR6 and ADRA2A is rather low at 100.5,

but the similarity of the two proteins in the protein-protein interaction network is relatively

high at 0.805. A part of the protein-protein interaction network around HTR6 and ADRA2A

is displayed in Figure 4 (left). Similarly, the Jaccard coefficient of the ECFPs between

Mesulergine and Pergolide is relatively low 0.273 (in general, compound pairs with a Jaccard

coefficient of ECFPs below 0.25 are considered not to have chemically similar structures

[34]), but the cosine similarity of the two compounds in the compound-compound interaction

network is high at 0.735. A part of the compound-compound interaction network around

Mesulergine and Pergolide is displayed in Figure 4 (right).

Conclusions

This study aimed to improve the performance of predicting protein-compound interactions by

integrating molecular structure data and interactome data. This was achieved by integrating

multiple heterogeneous interactome data into predictions of protein-compound interactions.

An end-to-end learning method was developed that combined a 1D-CNN for amino acid

sequences, an ECFP representation for compounds, and feature representation learning with

node2vec for protein-protein and compound-compound interaction networks. The proposed

integrated model exhibited significant performance differences with respect to the accuracy

measures in comparison to the current state-of-the-art deep learning methods. The

performance improvement was verified by the Wilcoxon signed-rank test as being

statistically significant. The results indicated that the proposed model was able to more

accurately predict the protein-compound interactions even in the hard dataset, where neither

the proteins nor the compounds in the test sample appear in the training sample.

An important future task is to integrate the gene regulatory network as additional

interactome data to further improve protein-compound interaction prediction. A large number

of gene expression profiles for various tissues and cell lines are available in public databases,

and gene regulatory networks can be effectively inferred from the gene expression profiles.

List of Abbreviations

SVM: Support Vector Machines

CNN: Convolutional Neural Network

ECFP: Extended-Connectivity Fingerprint

VSE: Visual Semantic Embedding

AUROC: Area Under the Receiver Operating characteristic Curve

AUPRC: Area Under the Precision-Recall Curve

SD: Standard Deviation

Declarations

Availability of Data and Materials

The source code for the implementation of this deep learning method, along with the dataset

for the performance evaluation, is available at https://github.com/Njk-901aru/multi_DTI.git.

Competing Interests

The authors declare that they have no competing interests.

Funding

This work was supported by MEXT KAKENHI Grant Number 221S0002, JSPS KAKENHI

Grant Numbers 22770047 and 24570062, the Model Plant Research Facility, NIBB

BioResource Center, the Functional Genomics Facility, NIBB Core Research Facilities, and

the Joint Usage/Research Program of the Center for Ecological Research, Kyoto University.

Authors' Contributions

NW; Implemented the software, analysed data, and co-wrote the paper. YO; analysed data

and compared with the existing methods. YS; designed and supervised the research, analysed

data, and co-wrote the paper. All authors read and approved the final manuscript.

Acknowledgements

Not applicable.

References

1.   Nagamine N, Sakakibara Y (2007) Statistical prediction of protein–chemical

interactions based on chemical structure and mass spectrometry data. Bioinformatics

23:2004-2012.

2.   Nagamine N, Shirakawa T, Minato Y, Torii K, Kobayashi H, Imoto M, Sakakibara Y

(2009) Integrating statistical predictions and experimental verifications for enhancing

protein-chemical interaction predictions in virtual screening. PLoS Comput Biol

5:e1000397.

3.   Sakakibara Y, Hachiya T, Uchida M, Nagamine N, Sugawara Y, Yokota M,

Nakamura M, Popendorf K, Komori T, Sato K (2012) COPICAT: a software system

for predicting interactions between proteins and chemical compounds. Bioinformatics

28:745-746.

4.   Wishart DS, Knox C, Guo AC, Cheng D, Shrivastava S, Tzur D, Gautam B, Hassanali

M (2008) DrugBank: a knowledgebase for drugs, drug actions and drug targets.

Nucleic Acids Res 36:D901-D906.

5.   Kim S, Thiessen PA, Bolton EE, Chen J, Fu G, Gindulyte A, Han L, He J, He S,

Shoemaker BA, Wang J, Yu B, Zhang J, Bryant SH (2016) PubChem substance and

compound databases. Nucleic Acids Res 44:D1202-D1213.

6.   LeCun Y, Bengio Y, Hinton G (2015) Deep learning. Nature 521:436-444.

7.   Tian K, Shao M, Wang Y, Guan J, Zhou S (2016) Boosting compound-protein

interaction prediction by deep learning. Methods 110:64-72.

8.   Öztürk H, Özgür A, Ozkirimli E (2018) DeepDTA: deep drug-target binding affinity

prediction. Bioinformatics (Oxford, England) 34:i821-i829.

9.   Lee I, Keum J, Nam H (2019) DeepConv-DTI: prediction of drug-target interactions

via deep learning with convolution on protein sequences. PLoS Comput Biol

15:e1007129.

10.   Tsubaki M, Tomii K, Sese J (2019) Compound–protein interaction prediction with

end-to-end learning of neural networks for graphs and sequences. Bioinformatics

35:309-318.

11.   Zitnik M, Agrawal M, Leskovec J (2018) Modeling polypharmacy side effects with

graph convolutional networks. Bioinformatics (Oxford, England) 34:i457-i466.

12.   Luo Y, Zhao X, Zhou J, Yang J, Zhang Y, Kuang W, Peng J, Chen L, Zeng J (2017)

A network integration approach for drug-target interaction prediction and

computational drug repositioning from heterogeneous information. Nat Commun

8:573.

13.   Wan F, Hong L, Xiao A, Jiang T, Zeng J (2019) NeoDTI: neural integration of

neighbor information from a heterogeneous network for discovering new drug–target

interactions. Bioinformatics 35:104-111.

14.   Hosur R, Peng J, Vinayagam A, Stelzl U, Xu J, Perrimon N, Bienkowska J, Berger B

(2012) A computational framework for boosting confidence in high-throughput

protein-protein interaction datasets. Genome Biol 13:R76.

15.   Chen M, Ju CJT, Zhou G, Chen X, Zhang T, Chang KW, Zaniolo C, Wang W (2019)

Multifaceted protein-protein interaction prediction based on Siamese residual RCNN.

Bioinformatics 35:i305-i314.

16.   Chen L, Lu J, Zhang J, Feng KR, Zheng MY, Cai YD (2013) Predicting chemical

toxicity effects based on chemical-chemical interactions. PLoS One 8:e56517.

17. Kwon S, Yoon S (2019) End-to-end representation learning for chemical-chemical

interaction prediction. IEEE/ACM Trans Comput Biol Bioinform 16:1436-1447.

18. Szklarczyk D, Morris JH, Cook H, Kuhn M, Wyder S, Simonovic M, Santos A,

Doncheva NT, Roth A, Bork P, Jensen LJ, von Mering C (2017) The STRING

database in 2017: quality-controlled protein-protein association networks, made

broadly accessible. Nucleic Acids Res 45:D362-D368.

19. Kuhn M, von Mering C, Campillos M, Jensen LJ, Bork P (2016) STITCH: interaction

networks of chemicals and proteins. Nucleic Acids Res 36:D684-D688.

20. Grover A, Leskovec J (2016) node2vec: scalable feature learning for networks. In:

Proceedings of KDD '16 (22nd ACM SIGKDD international conference on

knowledge discovery and data mining). ACM, New York, NY, USA, p 855-864.

21. Rogers D, Hahn M (2010) Extended-connectivity fingerprints. J Chem Inf Model

50:742-754.

22. Kiros R, Salakhutdinov R, Zemel RS (2014) Unifying visual-semantic embeddings

with multimodal neural language models. arXiv preprint arXiv:1411.2539.

23. Akiba T, Sano S, Yanase T, Ohta T, Koyama M (2019) Optuna: a next-generation

hyperparameter optimization framework. In: Proceedings of 25th ACM SIGKDD

international conference on knowledge discovery & data mining. ACM, New York,

NY, USA, p 2623–2631.

24. Ioffe S, Szegedy C (2015) Batch normalization: accelerating deep network training by

reducing internal covariate shift. arXiv preprint arXiv:150203167.

25. Srivastava N, Hinton G, Krizhevsky A, Sutskever I, Salakhutdinov R (2014) Dropout:

a simple way to prevent neural networks from overfitting. J Mach Learn Res 15:1929-

1958.

26. Bishop C (2006) Pattern recognition and machine learning. Springer-Verlag, Berlin,

Heidelberg.

27. Liu R, Hameed MDMA, Kumar K, Yu X, Wallqvist A, Reifman J (2017) Data-driven

prediction of adverse drug reactions induced by drug-drug interactions. BMC

Pharmacol Toxicol 18:44.

28. Kuhn M, Szklarczyk D, Franceschini A, von Mering C, Jensen LJ, Bork P (2011)

STITCH 3: zooming in on protein-chemical interactions. Nucleic Acids Res 40:D876-

D880.

29. Chatr-Aryamontri A, Oughtred R, Boucher L, Rust J, Chang C, Kolas NK, O'Donnell

L, Oster S, Theesfeld C, Sellam A, Stark C, Breitkreutz BJ, Dolinski K, Tyers M

(2019) The BioGRID interaction database: 2017 update. Nucleic Acids Res 45:D369-

D379.

30. Orchard S, Kerrien S, Abbani S, Aranda B, Bhate J, Bidwell S, Bridge A, Briganti L,

Brinkman FSL, Cesareni G, Chatr-Aryamontri A, Chautard E, Chen C, Dumousseau

M, Goll J, Hancock REW, Hannick LI, Jurisica I, Khadake J, Lynn DJ, Mahadevan U,

Perfetto L, Raghunath A, Ricard-Blum S, Roechert B, Salwinski L, Stümpflen V,

Tyers M, Uetz P, Xenarios I, Hermjakob H (2012) Protein interaction data curation:

the International Molecular Exchange (IMEx) consortium. Nat Methods 9:345-350.

31. Wilcoxon F (1945) Individual comparisons by ranking methods. Biom Bull 1:80-83.

32. Krogsgaard-Larsen N, Jensen AA, Schroder TJ, Christoffersen CT, Kehler J (2014)

Novel aza-analogous ergoline derived scaffolds as potent serotonin 5-HT6 and

dopamine D2 receptor ligands. J Med Chem 57:5823-5828.

33. Millan MJ, Maiofiss L, Cussac D, Audinot V, Boutin JA, Newman-Tancredi A (2002)

Differential actions of antiparkinson agents at multiple classes of monoaminergic

receptor. I. A multivariate analysis of the binding profiles of 14 drugs at 21 native and

cloned human receptor subtypes. J Pharmacol Exp Ther 303:791-804.

34.   Childs-Disney JL, Tran T, Vummidi BR, Velagapudi SP, Haniff HS, Matsumoto Y,

Crynen G, Southern MR, Biswas A, Wang ZF, Tellinghuisen TL, Disney MD (2018)

A massively parallel selection of small molecule-RNA motif binding partners informs

design of an antiviral from sequence. Chem 4:2384-2404.

Figure legends

Figure 1. Deep learning architecture that integrates molecular structure data and interactome

data to predict protein-compound interactions. It integrates graph-based and sequence-based

representations for the target protein and compound. The amino acid sequence of the protein

input was embedded into a one-hot vector of 20 dimensions in height. The ECFP

representation of the compound input was embedded into a 1024-dimensional vector. The

feature vectors were also extracted from the protein-protein and compound-compound

interaction network using node2vec, a feature representation learning method for graphs.

These feature vectors were combined as a protein vector and a compound vector. The

interaction was predicted in the output unit.

Figure 2. The output layer architecture. The integrated model predicts the protein-compound

interactions by embedding the protein and compound data from different modalities into a

common latent space. The feature vectors for the proteins and compounds are mapped onto

the same latent space by applying a fully connected layer. Then, their similarity in the latent

space is calculated with an element-wise product calculation followed by a fully connected

layer.

Figure 3. (Top) Relationship between the amino acid sequence similarity and the similarity

in protein-protein interaction network. (Bottom) Relationship between the chemical-structure

similarity and the similarity in compound-compound interaction network. The amino acid

sequence similarity was calculated using DIAMOND, and the chemical structure similarity

was calculated as the Jaccard coefficient of the ECFPs of the two compounds. The correlation

coefficients are 0.186 and 0.199, respectively.

Figure 4. (Left) Part of the protein-protein interaction network around ABL1 and YES1.

(Right) Part of the compound-compound interaction network around Crizotinib and Ceritinib.

Figure 1

Output

Protein vector

Compound vector

CNN

node2vec

node2vec

	M	R	E	...
	1	0	0	...
	...	...	...	...
	0	1	0	...
	0	0	1	...

One-hot embedding

1	0	1	0	0	1	...

ECFP

Protein-protein interaction

MREAAFMYST AVAIFLVILVAAL QGSA

Protein

CH₃

Compound

Compound-compound interaction

Figure 2

Figure 3

Figure 4