DRDOCK: A drug repurposing platform integrating automated docking, simulations and a log-odds-based drug ranking scheme

Kun-Lin Tsai[1] and Lee-Wei Yang[1,2]

[1]*Institute of Bioinformatics and Structural Biology, National Tsing-Hua University, Hsinchu 30013, Taiwan,*

[2]*Physics Division, National Center for Theoretical Sciences, Hsinchu 30013, Taiwan*

Abstract

Motivation

Drug repurposing, where drugs originally approved to treat a disease are reused to treat other diseases, has received escalating attention especially in pandemic years. Structure-based drug design, integrating small molecular docking, molecular dynamic (MD) simulations and AI, has demonstrated its evidenced importance in streamlining new drug development as well as drug repurposing. To perform a sophisticated and fully automated drug screening using all the FDA drugs, intricate programming, accurate drug ranking methods and friendly user interface are very much needed.

Results

Here we introduce a new web server, DRDOCK, **D**rug **R**epurposing **DO**cking with **C**onformation-sampling and pose re-ran**K**ing - refined by MD and statistical models, which integrates small molecular docking and molecular dynamic (MD) simulations for automatic drug screening of 2016 FDA-approved drugs over a user-submitted single-chained target protein. The drugs are ranked by a novel drug-ranking scheme using log-odds (LOD) scores, derived from feature distributions of true binders and decoys. Users can submit a selection of LOD-ranked poses for further MD-based binding affinity evaluation. We demonstrated that our platform can indeed recover one of the substrates for nsp16, a cap ribose 2'-O methyltransferase, and recommends XXX, could be repurposed for the COVID19 treatment. All the sampled docking poses and trajectories can be 3D-viewed and played via our web interface. This platform shall be easy-to-use for general scientists and medicinal researchers to carry out drug repurposing within a couple of days which should add value to our timely responses to, particularly, emergent disease outbreaks.

Availability and implementation

DRDOCK can be freely accessed from https://dyn.life.nthu.edu.tw/drdock/. (Due to the hardware upgrade, the service is NOT available before 2/15, 2021)

1 Introduction

In emergent diseases, re-use or recombination of old drugs, known as drug repurposing, can always be the first available remedy to respond to the diseases for their evidenced safety and preferred bioavailability (Ashburn et al., 2004; Barratt et al., 2012; Jin et al., 2014; Liu et al., 2018; Oliveira et al., 2018). In fact, statistics showed there are less and less new molecule entities (NMEs) (Avorn, 2015; Cleary et al., 2018; Paul et al., 2010) entering the market with an approval from FDA in the past decade for their inevitable side effects, unexpected low efficacy, long developmental time and accompanied high cost (Hughes et al., 2011; Mohs et al., 2017; Vohora et al., 2018).

Identification of drugs that could be repurposed for new targets requires an efficient and accurate high throughput drug screening and repurposing platforms, where the former uses all the available chemical leads, easily millions of them, and the latter uses FDA-approved drugs, or those that are still in the clinical trials (Ekins et al., 2007; March-Vila et al., 2017). One common practice uses small molecular docking (Forli et al., 2016; Gilson et al., 2007; Hsu et al., 2011; Kontoyianni M., 2017; Ma et al., 2011; Murgueitio et al., 2012), where different binding positions/orientations and configurations of a drug (termed "poses") are sampled in a protein and the resulting poses are rank-ordered by the docking scores or software-defined binding enthalpy. These docking simulations are performed in a vacuum with no dynamics involved, and, depending on the scoring functions, limited ligand entropy (Chang et al., 2007) change upon binding is considered.

The intrinsic protein dynamics (Eyal et al., 2015; Li et al., 2017; Yang et al., 2005; Yang et al., 2006; Yang et al., 2009; Zhang et al., 2020) has been proved crucial to modulation of ligand binding (Li et al., 2014; Yang et al., 2005) and used to assess the druggability of a protein target (Bakan et al., 2012; Lee et al., 2019). When excited by specific physicochemical perturbations, a small set of these intrinsic normal modes are recombined to drive protein conformational changes near the equilibrium state (Bakan et al., 2009; Yang et al., 2014). Given the modern computing power, molecular dynamics (MD) simulations have been largely used to describe the dynamic behavior of drugs-target interactions. The simulation trajectories of selected docking poses with the highest affinities (Alonso et al., 2006; Chang et al., 2016; Guterres et al., 2020) can be further analyzed for binding free energy evaluation at body temperature and room pressure, with neutralizing ions solvated in the explicit solvent (Guterres et al., 2020; Salmaso et al., 2018; Takemura et al., 2013).

On the other hand, most of the docking scoring functions are calibrated using a set of high qualities protein-ligand complex structures annotated by experimentally assayed binding affinities (Ballester et al., 2010; Cao et al., 2014; Huey et al., 2007; Koes et al., 2013;

Trott et al., 2009; Wang et al., 2002; Wang et al., 2011;). Due to the nature of structural biology, those experimentally "seen" in x-ray crystallography are usually stable co-crystallizer-protein complexes with relatively high affinity. Therefore, the scoring functions derived from these high-affinity ligands may fail to deprioritize low-affinity ligands that might only form transient binding with the target proteins since they are not included in the calibration process. This could introduce false positives of low-affinity drugs that are inappropriately prioritized in the docking process. If aforementioned simulation-based refinement and re-ranking are to be applied for only top-ranked drugs from the docking procedure, these wrongly prioritized low-affinity ones would result in a waste of computing resources. To best utilizing the computing resources and promote the success rate of drug repurposing, an accurate drug ranking method that is capable of distinguishing the effective drugs (true binders) from transient binders (decoys) is required.

In the past decades, there were web servers reported to provide small molecular docking and compound screening for drug discovery (Singh et al., 2020). SwissDock (Grosdidier et al., 2011), a reputed pioneer of docking web server, provides online computing resources for one-target-one-ligand docking service with limited acceptance for batched ligands-submission. iScreen (Tsai et al., 2011) provides cloud-computing resources for screening more than 20,000 traditional Chinese medicines (TCM) against a user-provided target by the docking program PLANTS (Korb et al., 2007; Korb et al., 2009). DockCoV2 (Chen et al., 2020), a target-centric drug repurposing database in response to the COVID-19 pandemic, deposits freely accessible simulated docking poses with no further MD-refinement for ~3000 administration-approved drugs against seven focused protein targets in SARS-CoV-2. Inverse docking web services, such as ACID (Wang et al., 2019) and idTarget (Wang et al., 2012), achieve drug repurposing by reverse screening, one drug against many drug targets, to fish promising targets to which the drug could bind. However, it does not allow to repurpose old drugs for newly emerged drug targets. ACFIS (Hao et al., 2016), another web service for *de novo* drug design, applies a fragment-based strategy by adding 2883 small fragments decomposed from compounds database, including FDA-approved drugs, to a core fragment derived from the input ligand in the user-provided protein-ligand complexed. This generates a set of new compounds with increased binding affinities to the target protein evaluated based on a few picosecond MD simulations. Despite these marked progress in making available customized online drug-screening services, there has not been a fully automated functional web server, allowing any uploaded PDB structure that can also be optionally relaxed by MD as a drug target over which several thousand of FDA-approved drugs are docked, followed by ≥10 nanosecond explicit-solvent MD simulations and trajectory-based binding affinity evaluation. To be responsive to emergent infectious diseases and diseases without gold standard therapeutics, the aforementioned online

service can be helpful to assess the binding affinity of all the FDA-approved drugs with essential genes in emergent pathogens, considering protein-drug dynamics in water at body temperature.

Here, we introduce DRDOCK, **D**rug **R**epurposing **DO**cking with **C**onformation-sampling and pose re-ran**K**ing, a new web server that integrates molecular docking and MD simulations for automatic virtual drug screening for drug repurposing of 2016 FDA-approved drugs. To improve the ranking accuracy of these drugs, we introduced a benchmark comprising drug-target pairs and an FDA-drug-specific metric to evaluate the goodness of any ranking method. With those, we developed two ranking methods, where in one of them, we developed the logarithm of odds (LOD) scores derived from pose features statistics (namely, pose affinity, distance to the binding pocket and entropic effect of poses) from true binders and decoys. Our web service implemented the LOD score, MD-based conformational sampling and MM/GBSA calculations to improve the screening accuracy in a relatively safe chemical space and therefore accelerate the drug repurposing.

2 Materials and methods

2.1 *In silico* FDA-approved drug library

2016 FDA approved drugs are collected and combined from the catalogs of MedChemExpress (MCE) FDA-Approved Drug Library (Cat. No.: HY-L022) and Enzo Life Sciences, Inc. Screen-Well® FDA Approved Drug Library (Version 1.5). The model 3D structures of drugs are built using BIOVIA Discovery Studio (Dassault Systèmes BIOVIA, Discovery Studio Modeling Environment, Release 2017, San Diego: Dassault Systèmes, 2016) with the protonation states of ionizable groups assigned at pH = 7. The input PDBQT files of drugs for docking are generated using AutoDock Tools (Morris et al., 2009), and the parameters required for MD simulations are assigned by Antechamber (Wang et al., 2006) based on GAFF2 (Wang et al., 2004) force field with am1-bcc (Jakalian et al., 2002) method for charges calculation.

2.2 Protein preprocessing

DRDOCK is designed for drug screening on a fully patched, single-chain protein target in the PDB format. The user-uploaded protein target is automatically processed and prepared for docking and MD simulations, including the prediction of protonation states of ionizable groups by using PROPKA3.1 (Olsson et al., 2011; Søndergaard et al., 2011), the flipping of the side-chain orientation of asparagine (Asn), glutamine (Gln), and histidine (His) for optimized hydrogen-bonding and the avoidance of NH2 clashes with surrounding toms adjusted by Reduce (Word et al., 1999), and automatic disulfide bonds detection (S-S distance < 2.5 Å). The input PDBQT file for docking is generated using AutoDockTools (Morris

et al., 2009), and the ff14SB force field (Maier et al., 2015) is used for MD simulations.

2.3 Benchmark set curated for the development of drug ranking methods

To develop the drug ranking methods and compare their performance, the complex structures for a set of known target proteins and FDA-approved drugs were extracted from the Protein Data Bank (PDB) (rcsb.org; Berman et al., 2000). We first collected 48 chemical IDs of FDA drugs that were newly approved during 2010-2016 gathered in the article published by Westbrook et al (2019) (the drugs reported to target the same target proteins were excluded for simplicity). Among these 48 approved drugs, 44 were included in our 2016 FDA-approved drug library. We then fetched the PDB IDs in which the structures were co-crystallized with one of the 44 drugs, eventually arrived in 20 drug-target complexes (see Supporting Info for details), listed in Table 1. We called the FDA-approved drug in the complex structure as "true binder".

Table 1. The collected 20 PDB complexes containing FDA-approved drugs used in this study.

PDB ID	Chain ID[2]	Seq. Length[3]	Target Name	Related diseases	Drug name	Chemical ID[1]	Binding Affinity[4]
				Training Set			
3g0b	A	740	Dipeptidyl peptidase 4	Diabetes	Alogliptin	T22	IC50: 7 nM[*]
4mxo	A	286	Proto-oncogene tyrosine-protein kinase Src	Chronic myeloid leukemia	Bosutinib	DB8	Kd: 0.73 nM[*]
4mkc	A	367	ALK tyrosine kinase receptor	Non-small cell lung cancers	Ceritinib	4MK	IC50: 0.2 nM[$]
5p9i	A	279	Tyrosine-protein kinase BTK	chronic lymphocytic leukemia	Ibrutinib	1E8	-
3wzd	A	309	Vascular endothelial growth factor receptor 2	Cancers	Lenvatinib	LEV	Kd: 2.1 nM[*]
2rgu	A	734	Dipeptidyl peptidase 4	Diabetes	Linagliptin	356	IC50: 0.1 nM[$]
2p16	A	234	Coagulation factor X	Thrombotic diseases	Apixaban	GG2	Ki: 0.08 nM[*]
4ag8	A	316	Vascular endothelial growth factor receptor 2	Cancers	Axitinib	AXI	Ki: 1.1 nM[*]
4xi3	A	243	Estrogen receptor	Breast cancer	Bazedoxifene acetate	29S	IC50: 0.6 nM[$]

PDB[1]	Chain[2]	Residues[3]	Protein	Disease	Drug	Chemical ID	Affinity[4]
5csw	A	282	Serine/threonine-protein kinase B-raf	Cancers	Dabrafenib	P06	IC50: 0.4 nM$^\$$
4tvj	A	368	Poly [ADP-ribose] polymerase 2	Cancers	Olaparib	09L	Kd: 0.28 nM$^\$$
2w26	A	234	Coagulation factor X	Thrombotic diseases	Rivaroxaban	RIV	Ki: 0.4 nM*
4rzv	A	281	Serine/threonine-protein kinase B-raf	Cancers	Vemurafenib	032	IC50: 4 nM$^\$$
3lxk	A	327	Tyrosine-protein kinase JAK3	Inflammatory diseases	Tofacitinib	MI1	Ki: 0.2 nM*
5ds3	A	271	Poly [ADP-ribose] polymerase 1	Cancers	Olaparib	09L	IC50: 0.9 nM$^\$$
2euf	B	308	Cyclin homolog	Cancers	Palbociclib	LQQ	IC50: 3.8 nM$^\$$
Test Set							
2wgj	A	306	Hepatocyte growth factor receptor	Cancers	Crizotinib	VGH	Ki: 2 nM$^\#$
6nec	A	314	Proto-oncogene tyrosine-protein kinase receptor	Thyroid and non-small cell lung cancer	Nintedanib	XIN	-
4zau	A	330	Epidermal growth factor receptor	Lung cancer	Osimertinib	YY3	IC50: 1.6 nM$^\$$
4bjc	A	240	Poly [ADP-ribose] polymerase tankyrase-2	Cancers	Rucaparib	RPB	IC50: 14 nM$^\#$

[1] The chemical ID for the access of the summary page of the drug in Protein Data Bank.
[2] The protein chain ID in the PDB entry used in this study.
[3] The number of protein residues solved in the crystal structure.
[4] The annotated experimental binding affinity associated with the PDB entry is from Binding MOAD (*), BindingDB ($^\$$), or PDBBind ($^\#$).

To generate the docking poses and their associated pose features (see the next section), each of the 20 complex structures (Table 1) was docked with our in-house built 2016 FDA-approved drugs by Autodock Vina (Trott et al., 2009). We defined the true binding pose of the true binder as the docking pose that among all has the shortest distance (measured from its mass center) to the mass center of the true binder's heavy atoms in their co-crystallized positions. The decoys (Graves et al., 2006) are defined as all the sampled poses of the 2016 FDA-approved drugs that are not the true binding pose.

2.4 Virtual drug screening and its resulting features

AutoDock Vina (Trott et al., 2009) was used for drug screening, where each of the 2016 FDA-approved drugs was docked into the target protein and allowed sampling for 20 poses. The docking box was set to cover the whole structure of the target protein with an additional 5 Å margin patched on each side of the docking box. The exhaustiveness was set to 50 to give accurate screening results within a reasonable time (~16hrs for the 2000+ drugs using 120 Intel Xeon E5606 CPU cores). The docking results were analyzed based on (A) the predicted binding affinity by AutoDock Vina, (B) the distance between the docking pose to the assigned target residues, and (C) the size of the poses cluster, as detailed below.

For Vina-predicted binding affinity, we used the original value (affinity) or the value divided by the square root of the number of drug heavy atoms (normalized affinity). The distance was measured as the closest distance between any heavy atoms of the drug pose to the center of mass (COM) of the assigned functional residues in a protein target (termed as "closest distance"), or the distance between COMs of a drug pose and assigned target residues (termed as "COM distance"). We also grouped similarly oriented poses into clusters. Clustering the docking poses into groups is to approximate the entropy contribution by the size of the clusters, where a large cluster suggested a less entropy loss during the drug binding process. To cluster the docking poses of each drug, we used the hierarchical clustering (Sokal and Michener, 1958) with a cutoff of 4 Å. Two types of distances were used - the distance between COMS of two poses (termed as "COM-based clustering") and the "adjacency" of docking poses (termed as "adjacency-based clustering", see below). In adjacency-based clustering, poses were clustered based on whether any of their heavy atoms come within 1 Å. The contact map of 20 poses x 20 poses was then used to identify the connected components, the "pose clusters" here, using an improved version of Tarjan's algorithm (Pearce, D.J., 2005) implemented in SciPy library (Virtanen et al., 2020). The three drug ranking algorithms introduced in the next section differ in their ways to integrate these aforementioned features, with an aim to prioritize the true binding pose/drug as front as possible among the 2015 competitors against the true binder's corresponding protein target.

2.5 *Ad hoc* method for drug ranking

The *ad hoc* ranking method is adapted and modified from our previous work (Liu et al., 2018), which is composed of two stages hierarchical classifying and sorting based on aforementioned three features (see Figure S1 for details) except that the cluster size here refers to the number of poses in a cluster that rank top 10 in affinity (out of 20) for that drug. In the first stage, a representative pose was chosen among the sampled 20 poses for

each drug. This was achieved by first applying a binary classification to group and prioritize those poses that were within 5 Å of the target site. Within each of the resulting two groups, a second binary classification was applied to each group where we prioritized the poses that belong to the largest clusters formed by the sampled 20 poses. Within each of the resulting four groups, the poses were then ordered based on the predicted binding affinity. The first pose in the top-ranked group was then chosen as the representative pose for that drug. The selected 2016 representative poses for 2016 drugs from the first stage were then used to determine the ranking of the drugs in the second stage. The drugs were again first binary-classified to prioritize the drugs that were within 5 Å of the target site. The drugs in each of the two groups were then ranked based on the predicted binding affinities.

2.6 Log-odds score (LOD score)

To develop the LOD score, the ranking of drugs is decided by a score based on the distance of pose features' statistics distributions, sampled within our benchmark set, from the true binders and the decoys. To get such statistics, we pooled all the generated poses from the 16 protein-drug complexes in the training set and derived the distribution of the true binding poses and decoys for each of the features associated with each pose. These distributions provided the statistical basis to annotate a sampled docking pose to be a true binder or decoy, based on its relative probability. Specifically, we calculated a log-odds (LOD) score for each of the sampled poses according to the following equation (Eq. 1):

$$LOD \ \ score = \sum_f log \frac{P_f^T(Q_f(x))}{P_f^F(Q_f(x))} \tag{1}$$

, where x represents a sampled docking pose; f represents one of the specified features we mentioned in section 2.4, e.g. the pose affinity, the pose's distance to the target site, and the size of poses cluster. $Q_f(x)$ is the value of feature f for the pose x is located. P_f^T and P_f^F are the probability distributions of feature f for docking poses sampled from the true binders and the decoys, respectively. Noted that $Q_f(x)$ are binned values and therefore different $Q_f(x)$ values within the same bin have the same P_f^T or P_f^F values. If there is no count for a bin, a small probability (10^{-7}) is assigned for that bin. The LOD score takes the idea of relative entropy, representing how more or less likely a given sampled pose can result from a true binder than from a decoy. A higher LOD score means the pose is more likely from a true binder. The 2016 drugs are rank-ordered based on their best LOD score among the 20 sampled poses.

2.7 Feature ranking score (FRS)

In the FRS method, the values *for a single feature* to all the poses of the 2016 drugs are sorted. A lower drug affinity and drugs' distances to target sites, or a larger size of pose clusters score correspond to a higher rank, starting from one. For each pose, the ranking for each of the three features is summed to obtain an FRS score such that

$$FRS = \sum_{f=1}^{3} [1 - \frac{(R_f - 1)}{N}] \qquad (2)$$

, where f represents one of the three features. R_f represents the ranking of a pose for the feature f. N is the total number of the sampled poses from all the 2016 drugs. The pose with the highest FRS in each drug is used as the representative pose for that drug, which is then sorted to obtain the final ranking for the 2016 drugs.

In the weighted FRS, the scores from different features are linearly combined such that

$$FRS = \sum_{f=1}^{3} w_f [1 - \frac{(R_f - 1)}{N}] \qquad (3)$$

, where w_f is the corresponding weight for the feature f.

To determine the weights associated with each feature, we constrained the range of values of the weights such that $0 < w_f < 1 \ \ and \ \ \sum_f w_f = 1$.

We then sought the set of $\{w_f\}$ that minimized the following average rank

$$\text{Rank}_{\text{avg}} = \frac{1}{16} \sum_{j=1}^{16} r_j^T , \qquad j \in \{ \ one \ of \ the \ 16 \ protein \ targets \ \} \qquad (4)$$

, where r_j^T is the rank of the true binder in jth target protein of the training dataset. To search for the optimal value of $\{w_f\}$, we applied two search methods: grid search and sampling search. Let the weights of the three features be w_1, w_2, and w_3. In the grid search method, we allowed two of the weights, said w_1 and w_2, to be any value in the set {0, 0.1, 0.2, ..., 0.9, 1}, and exhaustively searched the set of (w_1, w_2, 1-w_1-w_2) for the combination that minimized the loss function (Eq. 4). In the sampling search method (Weisstein, *MathWorld*), we sampled (w_1,w_2,w_3) according to the following equation (Eq. 5).

$$(w_1, w_2, w_3) = (0,0,1) + a(1,0,-1) + b(0,1,-1) \qquad (5)$$

, where a and b were sampled uniformly from 0 to 1, and we kept the set (w_1,w_2,w_3)

where $w_3 >= 0$. We sampled 10,000 sets of such (w_1,w_2,w_3) and chose the one that gave the smallest loss (Eq. 4).

2.8 Performance evaluation of the ranking methods

To use the testing set to evaluate a certain ranking method first parametrized over the training set, the total number "16" in Eq. (4) is replaced to "4" for the four drug-protein pairs in the test set (Table 1). We also defined the success rate of the true binders as the ratio of the training or test set being in the top 100 (~5%) or top 200 (~10%) among all the examined drugs.

2.9 Molecular dynamics (MD) simulations and MM/GBSA

While docking serves as a fast screening tool for *in silico* drug screening, as a trade-off, the lack of considering the solvation effect and molecular dynamics involved in the protein-ligand interaction introduces false positives (Pantsar et al., 2018). Explicit solvent MD simulations using classical force fields optimized for biological molecules are recognized to better describe the protein-ligand binding dynamics in a timescale allowed for weak binders to dissociate (Huang and Caflisch, 2011; Liu and Kokubo, 2017; Liu et al., 2018; Mollica et al., 2015). The resulting trajectories further allow accurate binding free energy evaluation by MM/GBSA, where the molecular mechanics of protein-ligand complexes and a continuum solvent model accounting for the solvation energy calculation are considered suitable to assess relative binding affinity for a set of drugs against the same pocket (Ahinko et al., 2018; Liu et al., 2018; Sun et al., 2014; Yang et al., 2011; Zhang et al., 2017).

The MD simulations for user-selected poses were performed using the OpenMM package (Eastman et al., 2017) in an explicit solvent. The simulation model of the protein target-drug binding pose complex was prepared using the LEaP program in AmberTools (Case et al., 2020). The complex was solvated using an explicit solvent of the TIP3P water model, with at least 10 Å of water layer patched on each side of the water box between the protein target and the box boundary. Sodium and chloride ions were used to neutralize the system to achieve a salt concentration of 100 mM. The system was first energy minimized for all the hydrogen, waters, and ions positions, leaving the remaining atoms restrained using a force constant of 10 kcal/mol/Å^2. This was followed by the energy minimization for atoms including also protein heavy atoms, leaving the protein C-alpha atoms and drug heavy atoms restrained using a force constant of 2 kcal/mol/Å^2. The system was then heated to 320 K in NVT ensemble for 1 ns and equilibrated for another 1 ns in NPT ensemble 310 K and 1 atm. The protein Cα atoms and drug heavy atoms were weakly restrained (0.1 kcal/mol/Å^2) during the NVT heating and NPT equilibration. The equilibrated system was then subject to a 10 ns simulation using the same condition as in the equilibration except for

the removal of all restraints, and the snapshots were sampled for every 0.1 ns, resulting in a trajectory composed of 100 frames. Langevin dynamics with a collision frequency of 2 ps^{-1} and a Monte Carlo Barostat with the volume rescaled every 25 time steps were applied for temperature and pressure controls, respectively. The particle mesh Ewald (PME) method was used to calculate the energy of non-bonded interaction with 10 Å as the distance cutoff. All the bonds involving hydrogens were constrained by SHAKE algorithm (Miyamoto and Kollman, 1992). The binding free energy approximated by the enthalpy contribution between the target protein and drugs for each sampled snapshot was calculated by MM/GBSA methods (Genheden et al., 2015; Greenidge et al., 2012; Kollman et al., 2000; Massova et al., 2000) with MMPBSA.py module (Miller et al., 2012) in the AmberTools (Case et al., 2020). The simulation results were summarized using the designed indicators, including the mean binding free energy from MM/GBSA calculation over sampled snapshots, the drug leaving time when the drug center of mass moving away from the target site more than 10 Å, and the largest distance of the drug COM to the target sites sampled during the simulations. A simulated drug got a higher rank if having a favorable mean binding free energy and staying long enough in the target site (or never leaving) during the 10 ns simulation. All the processing and analysis of the docking poses and MD trajectories were performed by ParmEd (http://parmed.github.io/ParmEd), Cpptraj (Roe et al., 2013), PyTraj (Nguyen et al., 2015), and MDAnalysis (Gowers et al., 2016; Michaud-Agrawal et al., 2011).

3 Website

3.1 Architecture

DRDOCK is composed of a central web server and distributed thread pools and data storage (Figure 1A). The web server plays as an interface to serve the web pages to the client browsers and receive the user requests. Once a service query is received, the web server processes the incoming query and sends compute-intensive tasks to the internal processing units-specific (CPUs and GPUs) thread pools. The web server dispatches the tasks to the specific type of thread pool through a job dispatcher hosted on a separate Redis server (https://redis.io/). The CPU thread pool is provided by an HPC cluster made of 11 nodes, each comprised of two CPUs of Intel(R) Xeon(R) X5660 (12 cores in total), for CPU-intensive tasks, such as docking and MM/GBSA calculations. The GPU thread pool equips with four GeForce GTX 980 Ti GPU cards and is responsible for carrying out MD simulations with AMBER ff14SB force field (Maier et al., 2015). The progress of the task is then reported to the web server through the internal LAN by HTTP(S). All the web server and threads can share the same files stored on a central Network Attached Storage (NAS). The portal webpage is programmed with Django Web framework (https://www.djangoproject.com/). The user-specific information and job configuration are stored using PostgreSQL (https://www.postgresql.org/).

3.2 Workflow

The workflow in DRDOCK can be summarized into four modules: structure preprocessing, docking/ranking 2016 FDA-approved drugs, 10 ns NPT MD simulation in water, and result rendering (Figure 1B). The user-submitted protein target in PDB format is first preprocessed before docking, including the determination of the pKa and protonation state of ionizable residues, optimizing the orientation of rotatable residue side-chains, and disulfide bond detection (Methods 2.2; see Supporting Results for more details). As an optional service, the user can choose to relax the target structure, without bound co-crystallizers, by 1 ns MD simulation in water before docking. The service then docks 2016 FDA-approved drugs to the target, and features inferred from docking poses (Methods 2.4) are used to calculate the LOD scores for drug ranking (Methods 2.6). Users then view the docking poses online on the results page and submit the interested docking poses for 10 ns NPT MD simulations of the protein-drug complexes in water. The resulting trajectories are used for assessing the drug binding stability (i.e., whether the drugs stay in the binding site through the simulation) and binding free energy by MM/GBSA (Methods 2.9). The trajectories are then updated to the results page for the playback of manipulatable 3D animations.

3.3 Result rendering

DRDOCK is designed for allowing real-time access to the latest calculation results while the entire drug screening is still in the process. The drugs and their docking poses shown in the results page are rank-ordered based on the LOD scores, described in the Methods. The drug name, 2D structure, drug properties, and external link to PubChem (Kim et al., 2019) can be viewed in each drug panel (Figure 1C, top). Docking poses for a drug can be selected by the switch at the top right (Figure 1C, top). Any docking pose can be further submitted for a 10 ns MD simulation (Figure 1C, and Figure S2B). When the simulation is finished, a superposed trajectory can be visualized in the embedded NGL viewer by clicking the "view trajectory" button (Figure 1C, bottom), and the corresponding features and the estimated binding free energies for each frame can be seen in the floated left panel (Figure 1C, bottom). For a better use of the computing resources, simulations for at most 20 selected poses can be submitted for each uploaded protein target. Finally, a complete list of rank-ordered drugs, all the docking poses, MD simulation trajectories, calculated features can be downloaded by clicking the "download" button (Figure 1C, and Figure S2B).

Figure 1. DRDOCK web service**. (A)** The architecture of DRDOCK. The central web server serves as the portal server serving the website and responds to any incoming requests. The CPU-intensive docking and GPU-intensive simulation jobs are sent from the web server separately to the corresponding thread pool on distributed machines through the job dispatcher. The progress of jobs is reported back to the web server through an internal LAN. All resulting files are kept in a central Network Attached Storage (NAS) that allows access from all the machines. A separated relational database hosted on the web server is used to save the user information and job configurations. **(B)** The workflow in DRDOCK. DRDOCK begins with preprocessing the user-submitted protein target. Users can choose to directly use the input structure for docking or optionally perform a one ns MD simulation to minimally relax the structure in water before docking. The preprocessed structure is then used to dock 2016 FDA-approved drugs, where the LOD scores calculated from the docking

poses are used for drug ranking. Users then view the docking poses on the online results page and pick interesting docking poses to simulate the dynamic protein-drug interaction in 10 ns NPT MD simulations with water. The resulting trajectory is used for binding free energy calculation by MM/GBSA and can be played on the online results page. **(C)** The functionality and info-display in the drug panel. The user can visualize the docking pose by clicking the eye-shape "view docking pose" button, and an extended space showing the binding mode of protein and drug will show up (top), clicking the "view docking features" button would render us a list of properties derived from the docking results (middle). Clicking the video-shape of "view trajectory" button pops open an NGL viewer (Rose et al., 2018) and plays the MD animation for the interacting drug-target complex if the pose were chosen for simulations. With this, MM/GBSA-estimated binding free energy is listed on the side, which is important for re-ranking the docking results. The pose and trajectory can be downloaded from the "download" button.

4 Results

We treat the drug screening problem as a ranking problem in order to reduce the disparity coming from different docking software used, different sampling depth and parameterization details of the drug force field etc. With this and through DRDOCK, given the consistency in an automated platform, the same drug on two different protein targets might be compared but more recommended comparison would be to examine the ranking of the drug in individual targets. Our goal here is to assess drug ranking methods based on how each method can prioritize the known true binders to the top of the 2016 FDA drugs, as high as possible.

We obtained a benchmark set of 20 drug-target complexes derived from a 2016 drug library (Westbrook et al., 2019; see Methods). We defined the co-crystallized drugs complexed with the corresponding target proteins as the true binders; for each target, there is only one true binder but 2015 decoy drugs (see also details on pose choice for the true binder). FDA drugs by design should target the best a single target of interest with the IC50 or Kd at nanomolar range and are not supposed to bind as well with other targets. For currently 2000+ FDA drugs that target nearly 900 protein targets (Santos et al., 2017), in average, more than 2 drugs "well bind" a single target. However, by how FDA drugs are designed and by the statistics where per drug targeting 0.5 protein in average, it should be reasonable to assume that the "cognate" or "native" drugs bind their designed targets the best or nearly the best, while the rest of the FDA drugs should not bind the same targets as well as the "native", hence our seemingly bold assumption of 1 true binder and 2015 hit decoys for each target. The 20 structures in benchmark set were randomly split into 16 and 4 respectively as the training set used for method calibration and the testing set for

evaluation of method performance. To get the atomic interactions of the drugs to the target proteins, each drug was docked or re-docked (for true binders) to the target proteins using a global search. At most 20 docked poses resulted for each drug and the features associated with the docking poses were calculated (Methods). We generated ~ 20 * 2016 * 20 poses for the 20 target proteins, where each pose was associated with the aforementioned three features (Methods).

Three drug ranking methods were evaluated using our benchmark set – using the LOD score, feature ranking score (FRS) and an *ad hoc* method modified from our previous study (Liu et al., 2018). To properly defined the LOD scores for our system, we needed to first identify relevant features that can render distinct probability distributions of true binders and decoys for that feature. Then, the most distinguishing features were used to derive the LOD scores, by summing which for each feature drugs are rank-ordered and the performance of the method is evaluated.

Feature ranking score (FRS) rates a pose by its ranking pertaining to each of examined features. As described in Eqs. 2 and 3, FRS is a sum of un-weighted (Eq. 2) or weighted (Eq. 3) ranking-normalized scores such that the highest rank in a certain feature gets the unity value while the lowest rank is nearly zero. To determine the weight of each feature in the linear combination, a grid-search method and a constrained sampling method are used to minimize the average rank of the true binders. The drugs are then ranked based on the pose with the highest FRS for each drug (Methods). As a comparison, the *ad hoc* approach was proposed (Liu et al., 2018) and its description can be found in Methods.

We quantified the difference between the distributions by Kolmogorov–Smirnov (K-S) test (Pratt, J.W., 2012) and Kullback–Leibler (K-L) divergence (Cover et al., 2006). A feature is considered "preferred" if it gives a large K-S statistics or K-L divergence (the "distance" between two distributions) between the distribution of true binders and that of decoys. The two distributions for each of the features are shown in Figures 2 to 4. For the binding affinity, the distributions of the original values between the true binders and decoys (K-S statistic: 0.775, K-L divergence: 2.981) were more different than that of the normalized affinity (K-S statistic: 0.188, K-L divergence: 0.273) (Figure 2). For the distance to the target sites, the true binders had shorter COM distances compared to that of decoys (K-S statistic: 0.828, K-L divergence: 2.415), and the difference was more pronounced than the distances measured using the closest drug heavy atoms (K-S statistic: 0.557, K-L divergence: 0.595) (Figure 3). Regarding the cluster size, the clusters grouped by adjacency-based clustering had stronger power to distinguish true binders from decoys (K-S statistic: 0.274, K-L divergence: 0.458) than that grouped by COM-based clustering (K-S statistic: 0.156, K-L divergence:

0.271) (Figure 4). Therefore, we used the regular affinity value as the measurement for the pose binding affinity, the COM-distance as the measurement for the pose distance to the target sites, and the cluster size resulted from the adjacency-based clustering as the measurement of the pose cluster size.

Figure 2. Difference in the distributions of the affinities between the "answer" poses (the true binder pose, left columns) and decoys (right columns) assessed by two different metric - Kolmogorov–Smirnov (K-S) test and Kullback–Leibler (K-L) divergence. Figures shows the original Vina predicted affinity values (top row) or normalized affinity by the square root of drug heavy atom number (bottom row). K-S statistic, the statistic in the Kolmogorov–Smirnov test, which tests against the null hypothesis that there is no difference between the distributions. p-value: the p-value in the distribution of the K-S statistic. The smaller the value, the more significant the difference. K-L divergence: Kullback–Leibler divergence, which measures the difference between the two distributions. The larger the value, the more different the two distributions. The results showed that the answer poses and decoys have more different distributions on the original affinity values than the normalized affinity values.

Figure 3. The comparison of the difference in the distribution of the distance to the target sites for the answer poses (left columns) and decoys (right columns) measured by the closest distance between any heavy atoms (top row) or by the distance from the center of mass (COM) of the drug. K-S statistic, the statistic in the Kolmogorov–Smirnov test. p-value: the p-value in the distribution of the K-S statistic. K-L divergence: Kullback–Leibler divergence. The results showed that the answer poses and decoys have more different distributions on using the closest distance as the distance measure than using COM distance.

Figure 4. The comparison of the difference in the distribution of the number of high-affinity poses (cluster size), defined as the top 10 highest affinity poses, in the cluster grouped by COM-based clustering (top row) or adjacency-based clustering (bottom row) for the answer poses (left columns) and decoys (right columns). K-S statistic, the statistic in the Kolmogorov–Smirnov test. p-value: the p-value in the distribution of the K-S statistic. K-L divergence: Kullback–Leibler divergence. The results showed that the answer poses and decoys have more different distributions on the number of high-affinity poses in the clustered grouped by adjacency-based clustering than COM-based clustering.

All the three drug ranking methods proceeded in two stages- a representative pose among the sampled poses was first chosen for each drug and the drugs were then ranked based on their representative poses. The performance of a method can be evaluated using two metrics - (A) the averaged ranking of true binders (Eq. 4) as well as (B) the percentage of true binders being prioritized to the top 5% or 10% of the examined drugs (Tables 2 and 3). To dissect the contribution of individual features, we computed the performance of the *ad hoc* method using only affinity, both affinity and distance, and all of the three features. The ranking based on affinity showed an average ranking of 164.44 and with 75% of the true binder drugs ranking in the top 10% of the 2016 FDA drugs (Table 2). When taking the distance and cluster size into account, the ranking was slightly improved and resulted in an

average rank of 153.81 and that 81.3% of the true binders are prioritized to the top 10%, suggesting the usefulness of adding the distance and cluster features. However, when looking at the Test Set results (Table 3), we found using all three features do not benefit the *ad hoc* results but using all three or just the "affinity + distance" benefit the FRS. Overall, the drug ranking predicted by the LOD scores suffer the least bias from the special case (see the results for 4zau) and showed a significant improvement in the average rank of the co-crystallized drugs in both training (Avg. rank: 110.5, Table 2) and testing dataset (Avg. rank: 26.75, while other methods rank >232, Table 3), which also reflected on the improved success rate of 100% (Table 3). The *ad hoc* method adopted a hierarchical strategy to rank features in different order, which could introduce biases. For a "loser" in the beginning hardly overcome the disadvantage for other outstanding features. On the contrary, the LOD score considered the three features altogether, and drugs getting a high score, suggesting relatively lower probability in the decoy set to have that feature value, in any of the three features were then possible to stood out and thus reducing the aforementioned problem.

For the FRS, our results showed that FRS performed the best when considering both the binding affinity and the distance to the active site, with an average ranking of 146.75 in the training set and 119.5 in the test set, both having 75% of the top 10% success rate (Table 2). We then compared the performance of the weighted FRS scores refined by the grid-search and the sampling method, which gave the weights of $(\alpha, \beta, \gamma) = (0.8, 0.2, 0)$ and $(0.72470771, 0.27438212, 0.00091017)$, where α, β, and γ were the weights for the binding affinity, distance to the active site, and cluster size, correspondingly. The learned weights suggested that the cluster size failed to prioritize these co-crystallized drugs by this method, which was consistent with the poor performance of FRS when considering all the three features (with equal weights) (Tables 2 and 3). The average rank of the weighted FRS (Avg. rank: 140.69 and 140.75) outperformed the equal weights FRS (Avg. rank: 163 to 266) in the training dataset, but did not show as competitive performance (Avg. rank: 190.5 and 167.0) compared to the equal weights FRS using affinity and distance features (Avg. rank: 119.5) in the testing dataset. *Our results suggested that the LOD score and the FRS based on affinity and distance features giving the best outcome to prioritize the co-crystallized drugs among the decoys*, from small molecule docking. Given that its best and consistent performance in both the training and testing dataset, the LOD score was chosen as the ranking method embedded in our DRDOCK.

Table 2. The predicted ranking of the answer drugs, the FDA-approved drugs bound in our collected 16 complexes, among the screened 2016 drugs, the average ranking, and the success rates by different ranking methods. The success rate was defined as the proportion of drugs in the 16 complexes that were ranked within the indicated top rank 100 (~5%) or

200 (~10%).

PDB ID	Drug name	Affinity[1]	Affinity + Distance[2]	Affinity +Distance +Clustering[3]	Ranking based on LOD score[4]	FRS rank (Affinity)[5]	FRS rank (Affinity +Distance)[5]	FRS rank (Affinity +Distance +Clustering)[5]	Weighted FRS rank (Grid)	Weighted FRS rank (Sampling)
3g0b	Alogliptin	1030	1050	1060	640	1109	1203	1272	1170	1181
4mxo	Bosutinib	731	688	668	374	723	549	513	631	572
4mkc	Ceritinib	78	61	54	5	69	3	130	5	5
5p9i	Ibrutinib	113	89	89	76	101	215	257	135	167
3wzd	Lenvatinib	22	16	12	4	18	13	10	9	10
2rgu	Linagliptin	232	187	175	319	198	210	205	169	175
2p16	Apixaban	45	45	47	3	45	14	530	9	13
4ag8	Axitinib	1	1	1	1	1	3	2	2	2
4xi3	Bazedoxifene	2	2	2	2	2	5	338	3	3
5csw	Dabrafenib	2	2	2	2	2	1	1	1	1
4tvj	Olaparib	8	8	8	1	8	2	2	1	1
2w26	Rivaroxaban	86	81	91	6	85	20	436	29	24
4rzv	Vemurafenib	1	1	1	1	1	1	1	1	1
3lxk	Tofacitinib	223	186	205	319	202	77	526	71	73
5ds3	Olaparib	4	4	4	3	4	1	1	1	1
2euf	Palbociclib	53	48	42	12	53	31	29	14	23
Avg. rank[6]		164.44	154.31	153.81	110.5	163.81	146.75	265.81	140.69	140.75
Success rate (< 100, ~ 5%)[7]		68.8% (11)	75.0% (12)	75.0% (12)	75.0% (12)	68.8% (11)	75.0% (12)	43.8% (7)	75.0% (12)	75.0% (12)
Success rate (< 200, ~ 10%)[7]		75.0% (12)	87.5% (14)	81.3% (13)	75.0% (12)	81.3% (13)	75.0% (12)	50.0% (8)	87.5% (14)	87.5% (14)

[1] The drugs were ranked by directly comparing the docking-predicted affinity values.

[2] The drugs were ranked by directly comparing the pose binding affinity and distance to the target sites.

[3] The drugs were ranked by directly comparing the pose binding affinity, distance to the target sites, and the size of the cluster the pose belonged to.

[4] The drugs were ranked based on the highest log of the odds ratio (LOD) score among the sampled poses derived from the distributions of true binders and decoys. The score represented the ratio of the probabilities that a sampled pose belonged to a true binder over decoys. The score shown in the table is the sum of the LOD scores derived from the distributions of affinity, cluster size, and distance to the target sites.

[5] The drugs were ranked based on the feature ranking scores (FRS) considering the annotated features.

[6] The average rank of true-binder drugs in the 16 complexes.

[7] The success rate was defined as the number of drugs that had predicted ranks within the indicated rank cutoff over a total of 16 drugs in the complexes. In the body of the table, the number in the parenthesis indicates the number of drugs that were succeeded prioritized within the rank cutoff.

Table 3. The predicted ranking of the answer drugs for the four protein targets in the testing set.

PDB ID	Drug name	Affinity[1]	Affinity + Distance[2]	Affinity +Distance +Clustering[3]	Ranking based on LOD score[4]	FRS rank (Affinity)[5]	FRS rank (Affinity +Distance)[5]	FRS rank (Affinity +Distance +Clustering)[5]	Weighted FRS rank (Grid)	Weighted FRS rank (Sampling)
2wgj	Crizotinib	41	38	39	2	41	1	339	1	1
6nec	Nintedanib	21	20	17	3	21	1	1	1	1
4zau	Osimertinib	585	738	712	86	585	470	301	739	650
4bjc	Rucaparib	284	249	244	16	284	6	6	21	16
Avg. rank[6]		232.75	261.25	253.0	26.75	232.75	119.5	161.75	190.5	167.0
Success rate (< 100, ~ 5%)[7]		50.0% (2)	50.0% (2)	50.0% (2)	100.0% (4)	50.0% (2)	75.0% (3)	50.0% (2)	75.0% (3)	75.0% (3)
Success rate (< 200, ~ 10%)[7]		50.0% (2)	50.0% (2)	50.0% (2)	100.0% (4)	50.0% (2)	75.0% (3)	50.0% (2)	75.0% (3)	75.0% (3)

[1, 2, 3, 4, 5, 6, 7] The definitions are the same as that in Table 2 and the average ranking and success rates by different ranking methods are also defined in the same way as Table 2.

5 Application

Coronavirus disease 2019 (COVID-19), an outbreak that began by the end of 2019, had progressed to a global pandemic in 2020 and severely impacted human society in whole aspects. Efforts for finding effective and safe treatment besides vaccines are still being made. In the host cell, the severe acute respiratory syndrome (SARS) coronaviruses, including SARS-CoV-2, the causality of COVID-19, methylated the 5' cap structure of newly

synthesized mRNAs to mimic the native host mRNAs and prevent their recognition and degradation by the host immune system (Daffis et al., 2012). The virus non-structural protein 16 (nsp16), which formed a complex with nsp10 (nsp16/10), was responsible for this methylation by transfer the methyl group from the methyl donor, S-adenosyl methionine (SAM), to the first nucleotide of the mRNA at 2'-O of the ribose sugar (Krafcikova et al., 2020; Viswanathan et al., 2020). The nsp16, a cap ribose 2'-O methyltransferase, thus became a potential drug target where peptides or drugs that could inhibit its enzyme activity could raise the instability of viral mRNAs and interferon (IFN)-mediated antiviral response (Wang et al., 2015), and, therefore, apply to COVID-19 treatment. Here, we used our webserver to screen drugs as the inhibitors for SARS-CoV2 nsp16. We used the nsp16 structure from SARS-CoV2 (PDB Code: 6wks, chain A) as the protein target submitted to our webserver. The position of the natural ligand, SAM (residue ID: 301), was chosen as the target site, of which the COM was used to calculate the distance from the docking poses that was used in LOD scores calculation and drug ranking. We then further submitted the top-ranked 20 drugs from the docking results to 10 ns MD simulations and got the corresponding MM/GBSA energies from the sampled snapshots.

Table 4 showed the top-ranked 20 drugs based on the LOD scores derived from the docking results and their corresponding indicators inferred from 10 ns MD simulations, including the mean binding free energy, the drug leaving time, and the largest distance of the drug to the target sites during the simulations (Methods 2.9). The natural ligand, S-adenosyl methionine (SAM), serving as a methyl donor for the mRNA substrate and belonging to one of the FDA-approved drugs included in our drug library, was ranked 17 at the docking stage, which demonstrated the robustness and accuracy of our drug ranking method based on the LOD score (Methods 2.6). Confirmed by the 10 ns simulation, SAM was further prioritized to rank 2 with the mean binding free energy of -31.0 kcal/mol and the longest distance of 1.43 Å to the target site, suggesting the high affinity and stable binding of the natural ligand with nsp16. Among the top 20 ranked drugs, several drugs failed to form tight interactions with the SAM binding pocket when examined by MD and finally left the binding pocket (distance > 10 Å from the target site) during the 10 ns simulations, including olaparib (docking rank: 2, MD rank: 15, drug leaving time: 6.9 ns), levosimendan (docking rank: 3, MD rank: 19, drug leaving time: 1.3 ns), and ataluren (docking rank: 4, MD rank: 17, drug leaving time: 4.2 ns), which suggested the limitation of docking scoring function with a fixed receptor at zero temperature (no kinetics) in vacuum. The re-evaluation of the binding by MD simulations in explicit-solvent could benefit the overall drug screening outcome.

Table 4. The top-ranked 20 drugs by the LOD score from nsp16's docking results.

Drug name	Docking rank[1]	LOD score[2]	Affinity (kcal/mol)[3]	Affinity rank[4]	MD rank[5]	Mean binding free energy (kcal/mol)[6]	Drug leaving time (ns)[7]	Longest distance to the target site (Å)[8]
ZZZ	1	5.31	-8.8	104	7	-18.64	-	2.97
Olaparib	2	5.13	-9.9	16	15	-20.86	6.9	12.18
Levosimendan	3	5.03	-7.9	378	19	-5.69	1.3	29.56
Ataluren	4	5.03	-7.9	379	17	-10.54	4.2	24.48
Nifuroxazide	5	5.03	-7.5	583	10	-16.46	-	1.75
Fenoterol	6	5.03	-7.4	646	4	-24.41	-	6.64
Duvelisib	7	4.6	-9.1	69	16	-14.58	5	10.41
Carprofen	8	4.49	-7.7	460	18	-6.41	2.1	22.85
Ergotamine	9	4.12	-10.5	4	8	-17.53	-	5.41
Sm13496	10	4.12	-10.4	6	5	-24.17	-	5.22
Raltegravir	11	3.73	-9.8	18	14	-11.62	9.2	14.09
Abemaciclib	12	3.73	-9.3	46	9	-16.68	-	5.21
XXX	13	3.73	-9.1	70	1	-35.56	-	3.33
Olmesartan	14	3.73	-9.1	71	20	-13.02	0.8	13.28
Dantrium	15	3.63	-7.9	380	12	-12.18	-	9.55
Tafamidis	16	3.63	-7.6	514	11	-13.38	-	7.74
S-adenosyl-methionine	17	3.63	-7.6	515	2	-31	-	1.43
YYY	18	3.63	-7.2	828	3	-25.34	-	3.47
Conivaptan	19	3.26	-10.6	3	6	-19.14	-	6.92
Eltrombopag	20	3.26	-10.3	7	13	-26.2	9.3	11.32

[1] The rank among 2016 drugs based on the log of the odds ratio (LOD) score (column 2).
[2] The log of the odds ratio (LOD) score used to rank the drugs based on the docking results. See Method 3.5.
[3] Docking affinity predicted by AutoDock Vina.
[4] The rank among 2016 drugs based on the docking affinity (column 4).
[5] The rank among the top 20 drugs subject to further 10 ns simulations. The drugs were ranked based on the average binding free energies (column 7) and drug leaving times (column 8).
[6] The average binding free energy by MM/GBSA method (Massova et al., 2000; Kollman et al., 2000) over the sampled snapshots during the simulations.
[7] The simulation time when the drug dissociated from the target site (the first time point when the distance of the drug to the target site was > 10 Å). -, the drugs did not dissociate during the whole 10 ns simulations.
[8] The longest distance of the drug to the target site sampled during the 10 ns simulations.

Our webserver also suggested several drugs that could potently bind and compete with SAM for its binding pocket, as reflected on their top-ranked LOD scores, favorable mean MM/GBSA binding free energies, and tight adhesion in the binding pocket suggested by the small departure of the drugs from the target site ("longest distance during simulation to the target site") (Methods 2.9). By considering both docking and MD simulation results, we highlighted three promising drugs, XXX (MD rank: 1, mean binding free energy: -35.56

kcal/mol, longest distance to target site: 3.33 Å, docking rank: 13), YYY (MD rank: 3, mean binding free energy: -25.34 kcal/mol, longest distance to target site: 3.47 Å, docking rank: 18), and ZZZ (MD rank: 7, mean binding free energy: -18.64 kcal/mol, longest distance to target site: 2.97 Å, docking rank 1), that could stably stay at the target site through the simulations (longest distance to the target site < 4 Å) and were ranked within top five per either the docking or MD results (Table 4). It would be worth examining whether their indication could also be extended to the treatment of viral infections. Other drugs top-ranked in Table 4 could also be promising candidates worth further assays for their possible inhibition of the nsp16 enzyme activity and application for viral suppression.

We hope our platform can provide a timely suggestion for promising drugs that can be reused in the outbreak of emergent diseases now and in the future and our benchmarking and ranking strategies can be of help to the medicinal chemists and careful researchers. Our rationales of making available this service are further discussed in the Supporting Information.

6 References

Ahinko, M., Niinivehmas, S., Jokinen, E., Pentikäinen, O.T., 2018. Suitability of MMGBSA for the selection of correct ligand binding modes from docking results. Chemical Biology & Drug Design 93, 522–538. doi:10.1111/cbdd.13446

Alonso, H., Bliznyuk, A.A., Gready, J.E., 2006. Combining docking and molecular dynamic simulations in drug design [WWW Document]. URL https://onlinelibrary.wiley.com/doi/full/10.1002/med.20067 (accessed 11.9.20).

Ashburn, T.T., Thor, K.B., 2004. Drug repositioning: identifying and developing new uses for existing drugs. Nature Reviews Drug Discovery 3, 673–683. doi:10.1038/nrd1468

Avorn, J., 2015. The $2.6 Billion Pill — Methodologic and Policy Considerations. New England Journal of Medicine 372, 1877–1879. doi:10.1056/nejmp1500848

Bakan, A., Bahar, I., 2009. The intrinsic dynamics of enzymes plays a dominant role in determining the structural changes induced upon inhibitor binding. Proceedings of the National Academy of Sciences 106, 14349–14354. doi:10.1073/pnas.0904214106

Bakan, A., Nevins, N., Lakdawala, A.S., Bahar, I., 2012. Druggability Assessment of Allosteric Proteins by Dynamics Simulations in the Presence of Probe Molecules. Journal of Chemical Theory and Computation 8, 2435–2447. doi:10.1021/ct300117j

Ballester, P.J., Mitchell, J.B.O., 2010. A machine learning approach to predicting protein–ligand binding affinity with applications to molecular docking. Bioinformatics 26, 1169–1175. doi:10.1093/bioinformatics/btq112

Barratt, M.J., Frail, D., 2012. Drug repositioning: Bringing new life to shelved assets and existing drugs. Wiley-Blackwell (an imprint of John Wiley & Sons Ltd), Chicester.

Berman, H.M., Westbrook J., Feng Z., Gilliland G., Bhat T.N., Weissig H., Shindyalov I.N., Bourne P.E., 2000. The Protein Data Bank. Nucleic Acids Research 28, 235–242. doi:10.1093/nar/28.1.235

Cao, Y., Li, L., 2014. Improved protein–ligand binding affinity prediction by using a curvature-dependent surface-area model. Bioinformatics 30, 1674–1680. doi:10.1093/bioinformatics/btu104

Case, D.A., Belfon, K., Ben-Shalom, I.Y., Brozell, S.R., Cerutti, D.S., Cheatham, T.E., III, Cruzeiro, V.W.D., Darden, T.A., Duke, R.E., Giambasu, G., Gilson, M.K., Gohlke, H. Goetz, A.W., Harris, R., Izadi, S., Kasavajhala, K., Kovalenko, A., Krasny, R., Kurtzman, T., Lee, T.S., LeGrand, S., Li, P., Lin, C., Liu, J., Luchko, T., Luo, R., Man, V., Merz, K.M., Miao, Y., Mikhailovskii, O., Monard, G., Nguyen, H., Onufriev, A., Pan, F., Pantano, S., Qi, R., Roe, D.R., Roitberg, A., Sagui, C., Schott-Verdugo, S., Shen, J., Simmerling, C.L., Skrynnikov, N., Smith, J., Swails, J., Walker, R.C., Wang, J., Wilson, L., Wolf, R.M., Wu, X., York, D.M. and Kollman, P.A., 2020. AMBER 2020, University of California, San Francisco.

Chang, C.-C., Khan, I., Tsai, K.-L., Li, H., Yang, L.-W., Chou, R.-H., Yu, C., 2016. Blocking the interaction between S100A9 and RAGE V domain using CHAPS molecule: A novel route to drug development against cell proliferation. Biochimica et Biophysica Acta (BBA) - Proteins and Proteomics 1864, 1558–1569. doi:10.1016/j.bbapap.2016.08.008

Chang, C.-E.A., Chen, W., Gilson, M.K., 2007. Ligand configurational entropy and protein binding. Proceedings of the National Academy of Sciences 104, 1534–1539. doi:10.1073/pnas.0610494104

Chen, T.-F., Chang, Y.-C., Hsiao, Y., Lee, K.-H., Hsiao, Y.-C., Lin, Y.-H., Tu, Y.-C.E., Huang, H.-C., Chen, C.-Y., Juan, H.-F., 2020. DockCoV2: a drug database against SARS-CoV-2. Nucleic Acids Research 49. doi:10.1093/nar/gkaa861

Cleary, E.G., Beierlein, J.M., Khanuja, N.S., Mcnamee, L.M., Ledley, F.D., 2018. Contribution of NIH funding to new drug approvals 2010–2016. Proceedings of the National Academy of Sciences 115, 2329–2334. doi:10.1073/pnas.1715368115

Cover, T.M., Thomas, J.A., 2006. CHAPTER 2 ENTROPY, RELATIVE ENTROPY, AND MUTUAL INFORMATION, in: Elements of Information Theory. Wiley, Hoboken, NJ.

Daffis, S., Szretter, K.J., Schriewer, J., Li, J., Youn, S., Errett, J., Lin, T.-Y., Schneller, S., Zust, R., Dong, H., Thiel, V., Sen, G.C., Fensterl, V., Klimstra, W.B., Pierson, T.C., Buller, R.M., Jr, M.G., Shi, P.-Y., Diamond, M.S., 2010. 2´-O methylation of the viral mRNA cap evades host restriction by IFIT family members. Nature 468, 452–456. doi:10.1038/nature09489

Degen, L., Matzinger, D., Merz, M., Appel-Dingemanse, S., Osborne, S., Lüchinger, S., Bertold, R., Maecke, H., Beglinger, C., 2001. Tegaserod, a 5-HT4 receptor partial agonist, accelerates gastric emptying and gastrointestinal transit in healthy male subjects. Alimentary Pharmacology & Therapeutics 15, 1745–1751. doi:10.1046/j.1365-2036.2001.01103.x

Eastman, P., Swails, J., Chodera, J.D., Mcgibbon, R.T., Zhao, Y., Beauchamp, K.A., Wang, L.-P., Simmonett, A.C., Harrigan, M.P., Stern, C.D., Wiewiora, R.P., Brooks, B.R., Pande, V.S., 2017. OpenMM 7: Rapid development of high performance algorithms for molecular dynamics. PLOS Computational Biology 13. doi:10.1371/journal.pcbi.1005659

Ekins, S., Mestres, J., Testa, B., 2007. In silico pharmacology for drug discovery: methods for virtual ligand screening and profiling. British Journal of Pharmacology 152, 9–20. doi:10.1038/sj.bjp.0707305

Eyal, E., Lum, G., Bahar, I., 2015. The anisotropic network model web server at 2015 (ANM 2.0). Bioinformatics 31, 1487–1489. doi:10.1093/bioinformatics/btu847

Forli, S., Huey, R., Pique, M.E., Sanner, M.F., Goodsell, D.S., Olson, A.J., 2016. Computational protein–ligand docking and virtual drug screening with the AutoDock suite. Nature Protocols 11, 905–919. doi:10.1038/nprot.2016.051

Genheden, S., Ryde, U., 2015. The MM/PBSA and MM/GBSA methods to estimate ligand-binding affinities. Expert Opinion on Drug Discovery 10, 449–461. doi:10.1517/17460441.2015.1032936

Gilson, M.K., Zhou, H.-X., 2007. Calculation of Protein-Ligand Binding Affinities. Annual Review of Biophysics and Biomolecular Structure 36, 21–42. doi:10.1146/annurev.biophys.36.040306.132550

Gowers, R., Linke, M., Barnoud, J., Reddy, T., Melo, M., Seyler, S., Domański, J., Dotson, D., Buchoux, S., Kenney, I., Beckstein, O., 2016. MDAnalysis: A Python Package for the Rapid Analysis of Molecular Dynamics Simulations. Proceedings of the 15th Python in Science Conference. doi:10.25080/majora-629e541a-00e

Graves, A.P., Brenk, R., Shoichet, B.K., 2006. Decoys for Docking. Journal of Medicinal Chemistry 48(11), 3714–3728. doi:10.1021/jm0491187.s001

Greenidge, P.A., Kramer, C., Mozziconacci, J.-C., Wolf, R.M., 2012. MM/GBSA Binding Energy Prediction on the PDBbind Data Set: Successes, Failures, and Directions for Further Improvement. Journal of Chemical Information and Modeling 53, 201–209. doi:10.1021/ci300425v

Grosdidier, A., Zoete, V., Michielin, O., 2011. SwissDock, a protein-small molecule docking web service based on EADock DSS. Nucleic Acids Research 39. doi:10.1093/nar/gkr366

Guterres, H., Im, W., 2020. Improving Protein-Ligand Docking Results with High-Throughput Molecular Dynamics Simulations. Journal of Chemical Information and Modeling 60, 2189–2198. doi:10.1021/acs.jcim.0c00057

Hao, G.-F., Jiang, W., Ye, Y.-N., Wu, F.-X., Zhu, X.-L., Guo, F.-B., Yang, G.-F., 2016. ACFIS: a web server for fragment-based drug discovery. Nucleic Acids Research 44. doi:10.1093/nar/gkw393

Hsu, K.-C., Chen, Y.-F., Lin, S.-R., Yang, J.-M., 2011. iGEMDOCK: a graphical environment of enhancing GEMDOCK using pharmacological interactions and post-screening analysis.

BMC Bioinformatics 12. doi:10.1186/1471-2105-12-s1-s33

Huang, D., Caflisch, A., 2011. Small Molecule Binding to Proteins: Affinity and Binding/Unbinding Dynamics from Atomistic Simulations. ChemMedChem 6, 1578–1580. doi:10.1002/cmdc.201100237

Huey, R., Morris, G.M., Olson, A.J., Goodsell, D.S., 2007. A semiempirical free energy force field with charge-based desolvation. Journal of Computational Chemistry 28, 1145–1152. doi:10.1002/jcc.20634

Hughes, J., Rees, S., Kalindjian, S., Philpott, K., 2011. Principles of early drug discovery. British Journal of Pharmacology 162, 1239–1249. doi:10.1111/j.1476-5381.2010.01127.x

Jakalian, A., Jack, D.B., Bayly, C.I., 2002. Fast, efficient generation of high-quality atomic charges. AM1-BCC model: II. Parameterization and validation. Journal of Computational Chemistry 23, 1623–1641. doi:10.1002/jcc.10128

Jin, G., Wong, S.T., 2014. Toward better drug repositioning: prioritizing and integrating existing methods into efficient pipelines. Drug Discovery Today 19, 637–644. doi:10.1016/j.drudis.2013.11.005

Kim, S., Chen, J., Cheng, T., Gindulyte, A., He, J., He, S., Li, Q., Shoemaker, B.A., Thiessen, P.A., Yu, B., Zaslavsky, L., Zhang, J., Bolton, E.E., 2018. PubChem 2019 update: improved access to chemical data. Nucleic Acids Research 47. doi:10.1093/nar/gky1033

Koes, D.R., Baumgartner, M.P., Camacho, C.J., 2013. Lessons Learned in Empirical Scoring with smina from the CSAR 2011 Benchmarking Exercise. Journal of Chemical Information and Modeling 53, 1893–1904. doi:10.1021/ci300604z

Kollman, P.A., Massova, I., Reyes, C., Kuhn, B., Huo, S., Chong, L., Lee, M., Lee, T., Duan, Y., Wang, W., Donini, O., Cieplak, P., Srinivasan, J., Case, D.A., Cheatham, T.E., 2000. Calculating Structures and Free Energies of Complex Molecules: Combining Molecular Mechanics and Continuum Models. Accounts of Chemical Research 33, 889–897. doi:10.1021/ar000033j

Kontoyianni M., 2017. Chapter 18 - Docking and Virtual Screening in Drug Discovery. In: Lazar I., Kontoyianni M., Lazar A. (eds) Proteomics for Drug Discovery. Methods in Molecular Biology, vol 1647. Humana Press, New York, NY

Korb, O., Stützle, T., Exner, T.E., 2007. An ant colony optimization approach to flexible protein–ligand docking. Swarm Intelligence 1, 115–134. doi:10.1007/s11721-007-0006-9

Korb, O., Stützle Thomas, Exner, T.E., 2009. Empirical Scoring Functions for Advanced Protein–Ligand Docking with PLANTS. Journal of Chemical Information and Modeling 49, 84–96. doi:10.1021/ci800298z

Krafcikova, P., Silhan, J., Nencka, R., Boura, E., 2020. Structural analysis of the SARS-CoV-2 methyltransferase complex involved in RNA cap creation bound to sinefungin. Nature Communications 11. doi:10.1038/s41467-020-17495-9

Lee, J.Y., Krieger, J.M., Li, H., Bahar, I., 2019. Pharmmaker: Pharmacophore modeling and hit

identification based on druggability simulations. Protein Science 29, 76–86. doi:10.1002/pro.3732

Li, H., Chang, Y.-Y., Lee, J.Y., Bahar, I., Yang, L.-W., 2017. DynOmics: dynamics of structural proteome and beyond. Nucleic Acids Research 45. doi:10.1093/nar/gkx385

Li, H., Sakuraba, S., Chandrasekaran, A., Yang, L.-W., 2014. Molecular Binding Sites Are Located Near the Interface of Intrinsic Dynamics Domains (IDDs). Journal of Chemical Information and Modeling 54, 2275–2285. doi:10.1021/ci500261z

Liu, K., Kokubo, H., 2017. Exploring the Stability of Ligand Binding Modes to Proteins by Molecular Dynamics Simulations: A Cross-docking Study. Journal of Chemical Information and Modeling 57, 2514–2522. doi:10.1021/acs.jcim.7b00412Liu, P.-F., Tsai, K.-L., Hsu, C.-J., Tsai, W.-L., Cheng, J.-S., Chang, H.-W., Shiau, C.-W., Goan, Y.-G., Tseng, H.-H., Wu, C.-H., Reed, J.C., Yang, L.-W., Shu, C.-W., 2018. Drug Repurposing Screening Identifies Tioconazole as an ATG4 Inhibitor that Suppresses Autophagy and Sensitizes Cancer Cells to Chemotherapy. Theranostics 8, 830–845. doi:10.7150/thno.22012

Ma, D.-L., Chan, D.S.-H., Leung, C.-H., 2011. Molecular docking for virtual screening of natural product databases. Chem. Sci. 2, 1656–1665. doi:10.1039/c1sc00152c

Maier, J.A., Martinez, C., Kasavajhala, K., Wickstrom, L., Hauser, K.E., Simmerling, C., 2015. ff14SB: Improving the Accuracy of Protein Side Chain and Backbone Parameters from ff99SB. Journal of Chemical Theory and Computation 11, 3696–3713. doi:10.1021/acs.jctc.5b00255

March-Vila, E., Pinzi, L., Sturm, N., Tinivella, A., Engkvist, O., Chen, H., Rastelli, G., 2017. On the Integration of In Silico Drug Design Methods for Drug Repurposing. Frontiers in Pharmacology 8. doi:10.3389/fphar.2017.00298

Massova, I., Kollman, P.A., 2000. Combined molecular mechanical and continuum solvent approach (MM-PBSA/GBSA) to predict ligand binding. Perspectives in Drug Discovery and Design 18, 113–135. doi:10.1023/A:1008763014207

Michaud-Agrawal, N., Denning, E.J., Woolf, T.B., Beckstein, O., 2011. MDAnalysis: A toolkit for the analysis of molecular dynamics simulations. Journal of Computational Chemistry 32, 2319–2327. doi:10.1002/jcc.21787

Miglianico, M., Eldering, M., Slater, H., Ferguson, N., Ambrose, P., Lees, R.S., Koolen, K.M.J., Pruzinova, K., Jancarova, M., Volf, P., Koenraadt, C.J.M., Duerr, H.-P., Trevitt, G., Yang, B., Chatterjee, A.K., Wisler, J., Sturm, A., Bousema, T., Sauerwein, R.W., Schultz, P.G., Tremblay, M.S., Dechering, K.J., 2018. Repurposing isoxazoline veterinary drugs for control of vector-borne human diseases. Proceedings of the National Academy of Sciences 115. doi:10.1073/pnas.1801338115

Miller, B.R., Mcgee, T.D., Swails, J.M., Homeyer, N., Gohlke, H., Roitberg, A.E., 2012. MMPBSA.py: An Efficient Program for End-State Free Energy Calculations. Journal of Chemical Theory and Computation 8, 3314–3321. doi:10.1021/ct300418h

Miyamoto, S., Kollman, P.A., 1992. Settle: An analytical version of the SHAKE and RATTLE algorithm for rigid water models. Journal of Computational Chemistry 13, 952–962. doi:10.1002/jcc.540130805

Mohs, R.C., Greig, N.H., 2017. Drug discovery and development: Role of basic biological research. Alzheimers Dementia: Translational Research Clinical Interventions 3, 651–657. doi:10.1016/j.trci.2017.10.005

Mollica, L., Decherchi, S., Zia, S.R., Gaspari, R., Cavalli, A., Rocchia, W., 2015. Kinetics of protein-ligand unbinding via smoothed potential molecular dynamics simulations. Scientific Reports 5. doi:10.1038/srep11539

Morris GM, Huey R, Lindstrom W, et al. AutoDock4 and AutoDockTools4: Automated docking with selective receptor flexibility. J Comput Chem. 2009; 30:2785-91.

Murgueitio, M.S., Bermudez, M., Mortier, J., Wolber, G., 2012. In silico virtual screening approaches for anti-viral drug discovery. Drug Discovery Today: Technologies 9. doi:10.1016/j.ddtec.2012.07.009

Nguyen, H., Roe, D.R., Swails, J., Case, D.A., 2015. pytraj (https://github.com/Amber-MD/pytraj)

Oliveira EAM, Lang KL., 2018. Drug Repositioning: Concept, Classification, Methodology, and Importance in Rare/Orphans and Neglected Diseases. Journal of Applied Pharmaceutical Science 157–165. doi:10.7324/japs.2018.8822

Olsson, M.H.M., Søndergaard, C.R., Rostkowski, M., Jensen, J.H., 2011. PROPKA3: Consistent Treatment of Internal and Surface Residues in Empirical pKa Predictions. Journal of Chemical Theory and Computation 7, 525–537. doi:10.1021/ct100578z

Pantsar, T., Poso, A., 2018. Binding Affinity via Docking: Fact and Fiction. Molecules 23, 1899. doi:10.3390/molecules23081899

Paul, S.M., Mytelka, D.S., Dunwiddie, C.T., Persinger, C.C., Munos, B.H., Lindborg, S.R., Schacht, A.L., 2010. How to improve R&D productivity: the pharmaceutical industrys grand challenge. Nature Reviews Drug Discovery 9, 203–214. doi:10.1038/nrd3078

Pearce, D.J., 2005. An Improved Algorithm for Finding the Strongly Connected Components of a Directed Graph.

Pratt, J.W., 2012. CHAPTER 7 Kolmogorov-Smirnov Two-Sample Tests, in: Concepts of Nonparametric Theory. Springer.

Roe, D.R., Cheatham, T.E., 2013. PTRAJ and CPPTRAJ: Software for Processing and Analysis of Molecular Dynamics Trajectory Data. Journal of Chemical Theory and Computation 9, 3084–3095. doi:10.1021/ct400341p

Rose, A.S., Bradley, A.R., Valasatava, Y., Duarte, J.M., Prlić, A., Rose, P.W., 2018. NGL viewer: web-based molecular graphics for large complexes. Bioinformatics 34, 3755–3758. doi:10.1093/bioinformatics/bty419

Pratt, J.W., 2012. CHAPTER 7 Kolmogorov-Smirnov Two-Sample Tests, in: Concepts of

Nonparametric Theory. Springer.

Salmaso, V., Moro, S., 2018. Bridging Molecular Docking to Molecular Dynamics in Exploring Ligand-Protein Recognition Process: An Overview. Frontiers in Pharmacology 9. doi:10.3389/fphar.2018.00923

Santos, R., Ursu, O., Gaulton, A., Bento, A.P., Donadi, R.S., Bologa, C.G., Karlsson, A., Al-Lazikani, B., Hersey, A., Oprea, T.I., Overington, J.P., 2017. A comprehensive map of molecular drug targets. Nature Reviews Drug Discovery 16, 19–34. doi:10.1038/nrd.2016.230

Singh, N., Chaput, L., Villoutreix, B.O., 2020. Virtual screening web servers: designing chemical probes and drug candidates in the cyberspace. Briefings in Bioinformatics. doi:10.1093/bib/bbaa034

Sokal, R.R., Michener, C.D., 1958. A statistical method for evaluating systematic relationships. University of Kansas Science Bulletin 38, 1409–1438.

Søndergaard, C.R., Olsson, M.H.M., Rostkowski, M., Jensen, J.H., 2011. Improved Treatment of Ligands and Coupling Effects in Empirical Calculation and Rationalization of pKa Values. Journal of Chemical Theory and Computation 7, 2284–2295. doi:10.1021/ct200133y

Stein, E.M., Dinardo, C.D., Pollyea, D.A., Fathi, A.T., Roboz, G.J., Altman, J.K., Stone, R.M., Deangelo, D.J., Levine, R.L., Flinn, I.W., Kantarjian, H.M., Collins, R., Patel, M.R., Frankel, A.E., Stein, A., Sekeres, M.A., Swords, R.T., Medeiros, B.C., Willekens, C., Vyas, P., Tosolini, A., Xu, Q., Knight, R.D., Yen, K.E., Agresta, S., Botton, S.D., Tallman, M.S., 2017. Enasidenib in mutant IDH2 relapsed or refractory acute myeloid leukemia. Blood 130, 722–731. doi:10.1182/blood-2017-04-779405

Sun, H., Li, Y., Tian, S., Xu, L., Hou, T., 2014. Assessing the performance of MM/PBSA and MM/GBSA methods. 4. Accuracies of MM/PBSA and MM/GBSA methodologies evaluated by various simulation protocols using PDBbind data set. Phys. Chem. Chem. Phys. 16, 16719–16729. doi:10.1039/c4cp01388c

Takemura, K., Burri, R.R., Ishikawa, T., Ishikura, T., Sakuraba, S., Matubayasi, N., Kuwata, K., Kitao, A., 2013. Free-energy analysis of lysozyme–triNAG binding modes with all-atom molecular dynamics simulation combined with the solution theory in the energy representation. Chemical Physics Letters 559, 94–98. doi:10.1016/j.cplett.2012.12.063

Trott, O., Olson, A.J., 2009. AutoDock Vina: Improving the speed and accuracy of docking with a new scoring function, efficient optimization, and multithreading. Journal of Computational Chemistry. doi:10.1002/jcc.21334

Tsai, T.-Y., Chang, K.-W., Chen, C.Y.-C., 2011. iScreen: world's first cloud-computing web server for virtual screening and de novo drug design based on TCM database@Taiwan. Journal of Computer-Aided Molecular Design 25, 525–531. doi:10.1007/s10822-011-9438-9

Virtanen, P., Gommers, R., Oliphant, T.E., Haberland, M., Reddy, T., Cournapeau, D., Burovski, E., Peterson, P., Weckesser, W., Bright, J., Walt, S.J.V.D., Brett, M., Wilson, J., Millman, K.J.,

Mayorov, N., Nelson, A.R.J., Jones, E., Kern, R., Larson, E., Carey, C.J., Polat, I., Feng, Y., Moore, E.W., Vanderplas, J., Laxalde, D., Perktold, J., Cimrman, R., Henriksen, I., Quintero, E.A., Harris, C.R., Archibald, A.M., Ribeiro, A.H., Pedregosa, F., Mulbregt, P.V., 2020. SciPy 1.0: fundamental algorithms for scientific computing in Python. Nature Methods 17, 261–272. doi:10.1038/s41592-019-0686-2

Viswanathan, T., Arya, S., Chan, S.-H., Qi, S., Dai, N., Misra, A., Park, J.-G., Oladunni, F., Kovalskyy, D., Hromas, R.A., Martinez-Sobrido, L., Gupta, Y.K., 2020. Structural basis of RNA cap modification by SARS-CoV-2. Nature Communications 11. doi:10.1038/s41467-020-17496-8

Vohora, D., Singh, G., 2018. Chapter 2 - Drug Discovery and Development: An Overview, in: Pharmaceutical Medicine and Translational Clinical Research. Academic Press.

Wang, F., Wu, F.-X., Li, C.-Z., Jia, C.-Y., Su, S.-W., Hao, G.-F., Yang, G.-F., 2019. ACID: a free tool for drug repurposing using consensus inverse docking strategy. Journal of Cheminformatics 11. doi:10.1186/s13321-019-0394-z

Wang, J.-C., Chu, P.-Y., Chen, C.-M., Lin, J.-H., 2012. idTarget: a web server for identifying protein targets of small chemical molecules with robust scoring functions and a divide-and-conquer docking approach. Nucleic Acids Research 40. doi:10.1093/nar/gks496

Wang, J.-C., Lin, J.-H., Chen, C.-M., Perryman, A.L., Olson, A.J., 2011. Robust Scoring Functions for Protein–Ligand Interactions with Quantum Chemical Charge Models. Journal of Chemical Information and Modeling 51, 2528–2537. doi:10.1021/ci200220v

Wang, J., Wang, W., Kollman, P.A., Case, D.A., 2006. Automatic atom type and bond type perception in molecular mechanical calculations. Journal of Molecular Graphics and Modelling 25, 247–260. doi:10.1016/j.jmgm.2005.12.005

Wang, J., Wolf, R.M., Caldwell, J.W., Kollman, P.A., Case, D.A., 2004. Development and testing of a general amber force field. Journal of Computational Chemistry 25, 1157–1174. doi:10.1002/jcc.20035

Wang, R., Lai, L., Wang, S., 2002. Further development and validation of empirical scoring functions for structure-based binding affinity prediction. Journal of Computer-Aided Molecular Design 16, 11–26. doi:10.1023/a:1016357811882

Wang, Y., Sun, Y., Wu, A., Xu, S., Pan, R., Zeng, C., Jin, X., Ge, X., Shi, Z., Ahola, T., Chen, Y., Guo, D., 2015. Coronavirus nsp10/nsp16 Methyltransferase Can Be Targeted by nsp10-Derived PeptideIn VitroandIn VivoTo Reduce Replication and Pathogenesis. Journal of Virology 89, 8416–8427. doi:10.1128/jvi.00948-15

Waterhouse, A., Bertoni, M., Bienert, S., Studer, G., Tauriello, G., Gumienny, R., Heer, F.T., de Beer, T.A.P., Rempfer, C., Bordoli, L., Lepore, R., Schwede, T., 2018. SWISS-MODEL: homology modelling of protein structures and complexes. Nucleic Acids Research 46. doi:10.1093/nar/gky427

Weisstein, E.W. "Triangle Point Picking." From MathWorld--A Wolfram Web Resource.

https://mathworld.wolfram.com/TrianglePointPicking.html

Westbrook, J.D., Burley, S.K., 2019. How Structural Biologists and the Protein Data Bank Contributed to Recent FDA New Drug Approvals. Structure 27, 211–217. doi:10.1016/j.str.2018.11.007

Word, J., Lovell, S.C., Richardson, J.S., Richardson, D.C., 1999. Asparagine and glutamine: using hydrogen atom contacts in the choice of side-chain amide orientation 1 1Edited by J. Thornton. Journal of Molecular Biology 285, 1735–1747. doi:10.1006/jmbi.1998.2401

Yang, L.-W., Eyal, E., Bahar, I., Kitao, A., 2009. Principal component analysis of native ensembles of biomolecular structures (PCA_NEST): insights into functional dynamics. Bioinformatics 25, 606–614. doi:10.1093/bioinformatics/btp023

Yang, L.-W., Kitao, A., Huang, B.-C., Gō, N., 2014. Ligand-Induced Protein Responses and Mechanical Signal Propagation Described by Linear Response Theories. Biophysical Journal 107, 1415–1425. doi:10.1016/j.bpj.2014.07.049

Yang, L.-W., Liu, X., Jursa, C.J., Holliman, M., Rader, A., Karimi, H.A., Bahar, I., 2005. iGNM: a database of protein functional motions based on Gaussian Network Model. Bioinformatics 21, 2978–2987. doi:10.1093/bioinformatics/bti469

Yang, L.-W., Rader, A.J., Liu, X., Jursa, C.J., Chen, S.C., Karimi, H.A., Bahar, I., 2006. o GNM: online computation of structural dynamics using the Gaussian Network Model. Nucleic Acids Research 34. doi:10.1093/nar/gkl084

Yang, T., Wu, J.C., Yan, C., Wang, Y., Luo, R., Gonzales, M.B., Dalby, K.N., Ren, P., 2011. Virtual screening using molecular simulations. Proteins: Structure, Function, and Bioinformatics 79, 1940–1951. doi:10.1002/prot.23018

Zhang, X., Perez-Sanchez, H., C. Lightstone, F., 2017. A Comprehensive Docking and MM/GBSA Rescoring Study of Ligand Recognition upon Binding Antithrombin. Current Topics in Medicinal Chemistry 17, 1631–1639. doi:10.2174/1568026616666161117112604

Zhang, Y., Doruker, P., Kaynak, B., Zhang, S., Krieger, J., Li, H., Bahar, I., 2020. Intrinsic dynamics is evolutionarily optimized to enable allosteric behavior. Current Opinion in Structural Biology 62, 14–21. doi:10.1016/j.sbi.2019.11.002

Supplementary Information

Contents

1. Supplementary methods

  Benchmark set curated for the development of drug ranking methods

2. Supplementary results and discussion

  DRDOCK – user submission

3. Supplementary tables

  Table S1 Supporting information of the collected 20 PDB complexes containing FDA-approved drugs used in this study.

4. Supplementary figures

  Figure S1 *Ad hoc* method for drug ranking.

  Figure S2 The user submission form and results page of DRDOCK.

5. References

1. Supplementary methods

Benchmark set curated for the development of drug ranking methods

To develop the drug ranking methods and compare their performance, the complex structures for a set of known target proteins and FDA-approved drugs were extracted from the Protein Data Bank (PDB) (rcsb.org; Berman et al., 2000). We first collected 48 chemical IDs of FDA drugs that were approved during 2010-2016 gathered in the article published by Westbrook et al (2019) (the drugs reported to target the same target proteins were excluded for simplicity). Among these 48 approved drugs, 44 were included in our 2016 FDA-approved drug library. We then fetched the PDB IDs in which the structures were co-crystallized with one of the 44 drugs. Those PDB IDs of the drug targets that were the same as the targets of the complexed drugs annotated in Westbrook's article (by matching the UniProt IDs) were retained. For those drugs of which any of the complexed targets of the found PDB IDs were matched to the annotated target, we compared their Enzyme Commission number (EC number) and kept those PDB IDs that shared the same EC number. This resulted in 86 PDB IDs composed of 26 drug targets for 33 out of the aforementioned 44 drugs. From these, we retained those protein structures solved by X-ray crystallography, without nonnative amino acids, and from Homo sapiens. We also eliminated those housing the drug binding sites occupied by ions and/or co-crystallizers that contact the FDA drugs of interest (within 5 Å), those containing missing residues within 5 Å of the bound drug that could impair the integrity of the binding site, those with documented low affinities (Kd, Ki, IC50 > 1000 nM), and those belonging to the membrane protein. This resulted in 40 PDB IDs composed of 24 non-redundant target protein-FDA drug pairs (10 targets have more than 2 PDB IDs) for 18 target proteins and 19 FDA drugs. For each target protein-FDA drug pair that had several PDB IDs, we followed the ordered criteria to choose one PDB ID as the representative: the target protein did not have mutated residues, having annotated binding affinity, having a higher resolution, and having higher binding affinity. This resulted in 20 non-redundant protein-drug complexes among which 16 were randomly assigned as the training set and the remaining four as the testing set (Table S1). We called the FDA-approved drug in the complex structure as "true binder".

2. Supplementary results and discussions

DRDOCK – user submission

DRDOCK requires users to submit a well-prepared single-chain protein structure in PDB format and the corresponding residues IDs of the target sites, such as active sites for enzymes, that are used to identify the closest docking poses the users should interest in (Figure S2A). Since the integrity of the protein structure is essential for meaningful MD simulations, the protein structure should be prepared for preventing any missing backbone heavy atoms (CA, C, N, O). The missing of any side-chain heavy atoms is allowed since they can be automatically patched according to pre-defined amino acid templates but may slightly distort the predicted binding poses in docking. DRDOCK requires the protein structure to only comprise 20 standard amino acids, of which the force constants and atom charges are already well developed and calibrated in AMBER ff14SB force field (Maier et al., 2015). For those structures containing some of the standard amino acid-derived residues, DRDOCK can tolerate that by mutating the residues back to their closest standard amino acids. Otherwise, the users should manually modify and mutate back those residues according to the original protein sequence. The most convenient way to achieve this is to submit the desired target protein structure with non-standard amino acids with its corresponding original peptide sequence to the SWISS-MODEL web server (Waterhouse et al., 2018) under the "template mode", which can automatically mutate any residue that is different from the original peptide sequence back and patch any missing heavy atoms, which is our recommended way to prepare a submission-ready target structure.

Discussions

Drug repurposing can usually serve as the first possible remedy in any emergent life-threatening infectious disease, before vaccines and any drug with high specificity can be made available. To promptly identify effective drugs from existing ones, a drug screening platform with both efficiency and accuracy is required (Park, 2019; Pulley et al., 2020; Pushpakom et al., 2018). Our web server aims to fulfill this prospect by providing an automatic drug screening platform for drug repurposing of 2016 FDA-approved drugs toward any protein target. Its easy-to-use interface removes the technical barrier of virtual screening and helps accelerate drug repurposing for abrupt outbreaks of emerging infectious diseases.

A general goal for virtual screening is to enrich the effective drugs for a given protein target to the top of a set of decoys (Graves et al., 2006) in a drug library. It is, therefore, more rationalized to use a scoring function trained based on both the true binders and decoys. However, there are difficulties when trying to include decoys in the calibration

process. First, the affinity of a decoy is too weak to be experimentally measured. Second, the atomic interaction between the protein and a decoy is not available without a solved complex structure. This results in that most scoring functions are calibrated using known protein-ligand complex structures with experimentally measured affinity while not taking decoys into account, although the evaluation of a ligand affinity based on the known atomic interaction is thought to be generally applied to either true binders and decoys. Here, we proposed a compromised way where we call a drug known to bind a protein target as the true binder and other drugs in the drug library as decoys for that target. A successful ranking method should prioritize the true binder on top of the decoys as much as possible. With this rationale, we defined a loss function as the total sum (or average if divided by the number of targets) of the rankings assigned by a ranking method for the true binders in the collected set of known protein-drug complexes. This loss function can be used to evaluate existed or search for improved ranking methods and is generally applicable to any set of protein-drug complexes.

To learn from both true binders and decoys, the atomic details of the proteins-drugs interaction are generated by docking software, Vina. The sampled docking poses form the statistical basis for us to distinguish the true binders from the decoys based on the different distributions of their pose features. The most distinguishable features include the affinity from Vina, the distance from pose COM to the target site, and the size of a pose cluster that inversely reflected the degree of entropy loss during the drug binding. A log-odds (LOD) score is designed as a quantitative tendency for describing a sampled pose is more likely true binders or decoys. We also propose a feature ranking score (FRS) that aims to avoid systematic bias when applying the method to different protein targets. Our results show that the LOD score had an outstanding improvement on the average ranking of the true binders consistent in both training and testing datasets, suggesting its general applicability. This also demonstrates that the incorporation of the decoys properties does help improve the correctness of the drug ranking methods.

While docking allows the screening of a huge drug library within a feasible time, the accuracy of predicted ligand binding affinity is hindered by its simplified scoring function, evaluating in a vacuum environment instead of water, and not taking the dynamics of protein-drug interaction into account (Pantsar et al., 2018). This is addressed by MD simulations with delicate force fields in explicit solvent. In DRDOCK, the pre-built parameters files of 2016 FDA-approved drugs and a straightforward user interface allow advanced binding free energy evaluation by MD simulations in just a few clicks. The double confirmations reduce the top-ranked decoys that are simply wasted if subject to experimental assays and shall help raise the success rate in drug repurposing.

3. Supplementary tables

Table S1. Supporting information of the collected 20 PDB complexes containing FDA-approved drugs used in this study.

PDB ID	UniProtKB ID	Target Name	Enzyme	Classification	Drug target site[1]	References
Training Set						
3g0b	P27487	Dipeptidyl peptidase 4	Yes	Serine protease	Catalytic site	Zhang et al., 2011
4mxo	P12931	Proto-oncogene tyrosine-protein kinase Src	Yes	Non-receptor tyrosine kinase	ATP binding site	Levinson et al., 2013
4mkc	Q9UM73	ALK tyrosine kinase receptor	Yes	Receptor tyrosine kinase	ATP binding site	Friboulet et al., 2014
5p9i	Q06187	Tyrosine-protein kinase BTK	Yes	Non-receptor tyrosine kinase	ATP binding site	Bender et al., 2017
3wzd	P35968	Vascular endothelial growth factor receptor 2	Yes	Receptor tyrosine kinase	ATP binding site	Okamoto et al., 2014
2rgu	P27487	Dipeptidyl peptidase 4	Yes	Serine protease	Catalytic site	Eckhardt et al., 2007
2p16	P00742	Coagulation factor X	Yes	Serine protease	Catalytic site	Pinto et al., 2007
4ag8	P35968	Vascular endothelial growth factor receptor 2	Yes	Receptor tyrosine kinase	ATP binding site	Mctigue et al., 2012
4xi3	P03372	Estrogen receptor	No	Nuclear receptors	Hormone binding site	Fanning et al., 2016
5csw	P15056	Serine/threonine-protein kinase B-raf	Yes	Serine/threonine protein kinase	ATP binding site	Waizenegger et al., 2016
4tvj	Q9UGN5	Poly [ADP-ribose] polymerase 2	Yes	Poly (ADP-ribose) polymerase	Nicotinamide pocket	Thorsell et al., 2016
2w26	P00742	Coagulation factor X	Yes	Serine protease	Catalytic site	Roehrig et al., 2005
4rzv	P15056	Serine/threonine-protein kinase B-raf	Yes	Serine/threonine protein kinase	ATP binding site	Karoulia et al., 2016
3lxk	P52333	Tyrosine-protein kinase JAK3	Yes	Non-receptor tyrosine kinase	ATP binding site	Chrencik et al., 2010
5ds3	P09874	Poly [ADP-ribose] polymerase 1	Yes	Poly (ADP-ribose) polymerase	Nicotinamide pocket	Dawicki-Mckenna et al., 2015
2euf	Q01043	Cyclin homolog	Yes	Cyclin-dependent kinase	ATP binding site	Lu et al., 2006
Test Set						
2wgj	P08581	Hepatocyte growth factor receptor	Yes	Receptor tyrosine kinase	ATP binding site	Cui et al., 2011
6nec	P07949	Proto-oncogene tyrosine-protein kinase receptor	Yes	Receptor tyrosine kinase	ATP binding site	Terzyan et al., 2019
4zau	P00533	Epidermal growth factor receptor	Yes	Receptor tyrosine kinase	ATP binding site	Yosaatmadja et al., 2015
4bjc	Q9H2K2	Poly [ADP-ribose] polymerase tankyrase-2	Yes	Poly (ADP-ribose) polymerase	Nicotinamide pocket	Haikarainen et al., 2013

[1] The functional site targeted by the drug.

4. Supplementary figures

Identify representative pose (stage 1)

Drug ranking (stage 2)

Figure S1. *Ad hoc* **method for drug ranking**. The poses and drugs were ordered in a hierarchical order-by-group manner in two stages. In the first stage, the sampled 20 poses for each drug were ordered and a representative pose was chosen as the top-ranked pose. This included two steps of hierarchical binary classifications, based on features of the pose's distance to the target site and the size of the pose cluster, and resulted in four groups of poses. Within each group, the poses were then sorted based on the pose affinity. In the second stage, the rankings of 2016 drugs were determined using the representative poses chosen in the first stage. The drugs were first classified and grouped into two based on

whether the docking pose was within 5 Å of the target site. The final drug rankings were then determined by ordering the drugs from high to low affinity in each of the groups.

Figure S2. The user submission form and results page of DRDOCK. **(A)** The job submission form in the main page of DRDOCK. The user is required to provide a well-prepared single-

chain protein structure ("PDB file"). The user can assign a specific chain ID, model number for NMR-resolved structures, a desired segment in the specified protein chain (in "Residues range"). Users are required to specify the IDs of residues that comprise a target site (e.g. enzyme active site residues). Lastly, the user should provide a valid email address for receiving the job status and results from DRDOCK. The orange fields are required while grey fields are optional. **(B)** The results page of DRDOCK. The drugs are rank-ordered based on our ranking algorithm that ranks docked poses as described in the Methods. The drug name, 2D structure, description, basic properties, and PubChem link are shown in the drug panel. The rank-ordered drug list in CSV format can be downloaded (the download button in the purple bar atop). To submit poses for MD simulations, click the flask icon to enter the simulation submission mode, where a submission panel and a "submit" button will show up in the functional bar atop (beneath the navigation bar). A checkmark also shows up and replaces the flask icon for chosen drugs. Users can also switch the docking poses to submit different poses for the same drug. Finally, click the "submit" button in the submission panel to submit all the checked poses to the web server. Users can browse the rank-ordered drugs based on the simulation results (see Methods) by toggling the "MD" at the upper right corner (highlighted in the black box in **Fig S2B**). See more functions in Figure 1C for visualizing the docking pose and playing the trajectory. Other details about DRDOCK, including that our file parser can allow several types of non-standard amino acids, can be found in **Supplementary methods**.

5. References

Bender, A.T., Gardberg, A., Pereira, A., Johnson, T., Wu, Y., Grenningloh, R., Head, J., Morandi, F., Haselmayer, P., Liu-Bujalski, L., 2017. Ability of Bruton's Tyrosine Kinase Inhibitors to Sequester Y551 and Prevent Phosphorylation Determines Potency for Inhibition of Fc Receptor but not B-Cell Receptor Signaling. Molecular Pharmacology 91, 208–219. doi:10.1124/mol.116.107037

Berman, H.M., Westbrook J., Feng Z., Gilliland G., Bhat T.N., Weissig H., Shindyalov I.N., Bourne P.E., 2000. The Protein Data Bank. Nucleic Acids Research 28, 235–242. doi:10.1093/nar/28.1.235

Chrencik, J.E., Patny, A., Leung, I.K., Korniski, B., Emmons, T.L., Hall, T., Weinberg, R.A., Gormley, J.A., Williams, J.M., Day, J.E., Hirsch, J.L., Kiefer, J.R., Leone, J.W., Fischer, H.D., Sommers, C.D., Huang, H.-C., Jacobsen, E., Tenbrink, R.E., Tomasselli, A.G., Benson, T.E., 2010. Structural and Thermodynamic Characterization of the TYK2 and JAK3 Kinase Domains in Complex with CP-690550 and CMP-6. Journal of Molecular Biology 400, 413–433. doi:10.1016/j.jmb.2010.05.020

Cui, J.J., Tran-Dubé Michelle, Shen, H., Nambu, M., Kung, P.-P., Pairish, M., Jia, L., Meng, J., Funk, L., Botrous, I., Mctigue, M., Grodsky, N., Ryan, K., Padrique, E., Alton, G., Timofeevski, S., Yamazaki, S., Li, Q., Zou, H., Christensen, J., Mroczkowski, B., Bender, S., Kania, R.S., Edwards, M.P., 2011. Structure Based Drug Design of Crizotinib (PF-02341066), a Potent and Selective Dual Inhibitor of Mesenchymal–Epithelial Transition Factor (c-MET) Kinase and Anaplastic Lymphoma Kinase (ALK). Journal of Medicinal Chemistry 54, 6342–6363. doi:10.1021/jm2007613

Dawicki-Mckenna, J.M., Langelier, M.-F., Denizio, J.E., Riccio, A.A., Cao, C.D., Karch, K.R., Mccauley, M., Steffen, J.D., Black, B.E., Pascal, J.M., 2015. PARP-1 Activation Requires Local Unfolding of an Autoinhibitory Domain. Molecular Cell 60, 755–768. doi:10.1016/j.molcel.2015.10.013

Eckhardt, M., Langkopf, E., Mark, M., Tadayyon, M., Thomas, L., Nar, H., Pfrengle, W., Guth, B., Lotz, R., Sieger, P., Fuchs, H., Himmelsbach, F., 2007. 8-(3-(R)-Aminopiperidin-1-yl)-7-but-2-ynyl-3-methyl-1-(4-methyl-quinazolin-2-ylmethyl)-3,7-dihydropurine-2,6-dione (BI 1356), a Highly Potent, Selective, Long-Acting, and Orally Bioavailable DPP-4 Inhibitor for the Treatment of Type 2 Diabetes†. Journal of Medicinal Chemistry 50, 6450–6453. doi:10.1021/jm701280z

Fanning, S.W., Mayne, C.G., Dharmarajan, V., Carlson, K.E., Martin, T.A., Novick, S.J., Toy, W., Green, B., Panchamukhi, S., Katzenellenbogen, B.S., Tajkhorshid, E., Griffin, P.R., Shen, Y., Chandarlapaty, S., Katzenellenbogen, J.A., Greene, G.L., 2016. Estrogen receptor alpha somatic mutations Y537S and D538G confer breast cancer endocrine resistance by stabilizing the activating function-2 binding conformation. eLife 5. doi:10.7554/elife.12792

Friboulet, L., Li, N., Katayama, R., Lee, C.C., Gainor, J.F., Crystal, A.S., Michellys, P.-Y., Awad,

M.M., Yanagitani, N., Kim, S., Pferdekamper, A.C., Li, J., Kasibhatla, S., Sun, F., Sun, X., Hua, S., Mcnamara, P., Mahmood, S., Lockerman, E.L., Fujita, N., Nishio, M., Harris, J.L., Shaw, A.T., Engelman, J.A., 2014. The ALK Inhibitor Ceritinib Overcomes Crizotinib Resistance in Non-Small Cell Lung Cancer. Cancer Discovery 4, 662–673. doi:10.1158/2159-8290.cd-13-0846

Graves, A.P., Brenk, R., Shoichet, B.K., 2006. Decoys for Docking. Journal of Medicinal Chemistry 48(11), 3714–3728. doi:10.1021/jm0491187.s001

Haikarainen, T., Narwal, M., Joensuu, P., Lehtiö, L., 2013. Evaluation and Structural Basis for the Inhibition of Tankyrases by PARP Inhibitors. ACS Medicinal Chemistry Letters 5, 18–22. doi:10.1021/ml400292s

Karoulia, Z., Wu, Y., Ahmed, T.A., Xin, Q., Bollard, J., Krepler, C., Wu, X., Zhang, C., Bollag, G., Herlyn, M., Fagin, J.A., Lujambio, A., Gavathiotis, E., Poulikakos, P.I., 2016. An Integrated Model of RAF Inhibitor Action Predicts Inhibitor Activity against Oncogenic BRAF Signaling. Cancer Cell 30, 485–498. doi:10.1016/j.ccell.2016.06.024

Levinson, N.M., Boxer, S.G., 2013. A conserved water-mediated hydrogen bond network defines bosutinib's kinase selectivity. Nature Chemical Biology 10, 127–132. doi:10.1038/nchembio.1404

Lu, H., Schulze-Gahmen, U., 2006. Toward Understanding the Structural Basis of Cyclin-Dependent Kinase 6 Specific Inhibition. Journal of Medicinal Chemistry 49, 3826–3831. doi:10.1021/jm0600388

Mctigue, M., Murray, B.W., Chen, J.H., Deng, Y.-L., Solowiej, J., Kania, R.S., 2012. Molecular conformations, interactions, and properties associated with drug efficiency and clinical performance among VEGFR TK inhibitors. Proceedings of the National Academy of Sciences 109, 18281–18289. doi:10.1073/pnas.1207759109

Okamoto, K., Ikemori-Kawada, M., Jestel, A., König, K.V., Funahashi, Y., Matsushima, T., Tsuruoka, A., Inoue, A., Matsui, J., 2014. Distinct Binding Mode of Multikinase Inhibitor Lenvatinib Revealed by Biochemical Characterization. ACS Medicinal Chemistry Letters 6, 89–94. doi:10.1021/ml500394m

Park, K., 2019. A review of computational drug repurposing. Translational and Clinical Pharmacology 27, 59. doi:10.12793/tcp.2019.27.2.59

Pantsar, T., Poso, A., 2018. Binding Affinity via Docking: Fact and Fiction. Molecules 23, 1899. doi:10.3390/molecules23081899

Pinto, D.J.P., Orwat, M.J., Koch, S., Rossi, K.A., Alexander, R.S., Smallwood, A., Wong, P.C., Rendina, A.R., Luettgen, J.M., Knabb, R.M., He, K., Xin, B., Wexler, R.R., Lam, P.Y.S., 2007. Discovery of 1-(4-Methoxyphenyl)-7-oxo-6-(4-(2-oxopiperidin-1-yl)phenyl)-4,5,6,7-tetrahydro- 1H-pyrazolo[3,4-c]pyridine-3-carboxamide (Apixaban, BMS-562247), a Highly Potent, Selective, Efficacious, and Orally Bioavailable Inhibitor of Blood Coagulation Factor Xa. Journal of Medicinal Chemistry 50, 5339–5356. doi:10.1021/jm070245n

Pulley, J.M., Rhoads, J.P., Jerome, R.N., Challa, A.P., Erreger, K.B., Joly, M.M., Lavieri, R.R., Perry, K.E., Zaleski, N.M., Shirey-Rice, J.K., Aronoff, D.M., 2020. Using What We Already Have: Uncovering New Drug Repurposing Strategies in Existing Omics Data. Annual Review of Pharmacology and Toxicology 60, 333–352. doi:10.1146/annurev-pharmtox-010919-023537

Pushpakom, S., Iorio, F., Eyers, P.A., Escott, K.J., Hopper, S., Wells, A., Doig, A., Guilliams, T., Latimer, J., Mcnamee, C., Norris, A., Sanseau, P., Cavalla, D., Pirmohamed, M., 2018. Drug repurposing: progress, challenges and recommendations. Nature Reviews Drug Discovery 18, 41–58. doi:10.1038/nrd.2018.168

Roehrig, S., Straub, A., Pohlmann, J., Lampe, T., Pernerstorfer, J., Schlemmer, K.-H., Reinemer, P., Perzborn, E., 2005. Discovery of the Novel Antithrombotic Agent 5-Chloro-N-({(5S)-2-oxo-3- [4-(3-oxomorpholin-4-yl)phenyl]-1,3-oxazolidin-5-yl}methyl)thiophene- 2-carboxamide (BAY 59-7939): An Oral, Direct Factor Xa Inhibitor. Journal of Medicinal Chemistry 48, 5900–5908. doi:10.1021/jm050101d

Terzyan, S.S., Shen, T., Liu, X., Huang, Q., Teng, P., Zhou, M., Hilberg, F., Cai, J., Mooers, B.H.M., Wu, J., 2019. Structural basis of resistance of mutant RET protein-tyrosine kinase to its inhibitors nintedanib and vandetanib. Journal of Biological Chemistry 294, 10428–10437. doi:10.1074/jbc.ra119.007682

Thorsell, A.-G., Ekblad, T., Karlberg, T., Löw, M., Pinto, A.F., Trésaugues, L., Moche, M., Cohen, M.S., Schüler, H., 2016. Structural Basis for Potency and Promiscuity in Poly(ADP-ribose) Polymerase (PARP) and Tankyrase Inhibitors. Journal of Medicinal Chemistry 60, 1262–1271. doi:10.1021/acs.jmedchem.6b00990

Waizenegger, I.C., Baum, A., Steurer, S., Stadtmu Ller, H., Bader, G., Schaaf, O., Garin-Chesa, P., Schlattl, A., Schweifer, N., Haslinger, C., Colbatzky, F., Mousa, S., Kalkuhl, A., Kraut, N., Adolf, G.R., 2016. A Novel RAF Kinase Inhibitor with DFG-Out-Binding Mode: High Efficacy in BRAF-Mutant Tumor Xenograft Models in the Absence of Normal Tissue Hyperproliferation. Molecular Cancer Therapeutics 15, 354–365. doi:10.1158/1535-7163.mct-15-0617

Westbrook, J.D., Burley, S.K., 2019. How Structural Biologists and the Protein Data Bank Contributed to Recent FDA New Drug Approvals. Structure 27, 211–217. doi:10.1016/j.str.2018.11.007

Yosaatmadja, Y., Silva, S., Dickson, J.M., Patterson, A.V., Smaill, J.B., Flanagan, J.U., Mckeage, M.J., Squire, C.J., 2015. Binding mode of the breakthrough inhibitor AZD9291 to epidermal growth factor receptor revealed. Journal of Structural Biology 192, 539–544. doi:10.1016/j.jsb.2015.10.018

Zhang, Z., Wallace, M.B., Feng, J., Stafford, J.A., Skene, R.J., Shi, L., Lee, B., Aertgeerts, K., Jennings, A., Xu, R., Kassel, D.B., Kaldor, S.W., Navre, M., Webb, D.R., Gwaltney, S.L., 2011. Design and Synthesis of Pyrimidinone and Pyrimidinedione Inhibitors of Dipeptidyl