Unravelling the Physiological Correlates of Mental Workload Variations in Tracking and Collision Prediction Tasks: Implications for Air Traffic Controllers

Alka Rachel John[1*], Avinash K Singh[1], Tien-Thong Nguyen Do[1], Ami Eidels[2], Eugene Nalivaiko[3], Alireza Mazloumi Gavgani[3], Scott Brown[2], Murray Bennett[2], Sara Lal[4], Ann M. Simpson[4], Sylvia M Gustin[5,6], Kay Double[7], Frederick Rohan Walker[3], Sabina Kleitman[8], John Morley[9], Chin-Teng Lin[1]

[1] Australian Artificial Intelligence Institute, Faculty of Engineering and Information Technology, University of Technology Sydney, Sydney, New South Wales, Australia

[2] School of Psychology, University of Newcastle, Callaghan, New South Wales, Australia

[3] School of Biomedical Sciences and Pharmacy and Centre for Advanced Training Systems, University of Newcastle, Callaghan, New South Wales, Australia

[4] School of Life Sciences, University of Technology Sydney, Sydney, New South Wales, Australia

[5] School of Psychology, University of New South Wales, Sydney, New South Wales, Australia

[6] Centre for Pain IMPACT, Neuroscience Research Australia

[7] Brain and Mind Centre and Discipline of Pharmacology, School of Medical Sciences, The University of Sydney, Sydney, New South Wales, Australia

[8] Faculty of Science, The University of Sydney, Sydney, New South Wales, Australia

[9] School of Medicine, Western Sydney University, Sydney, New South Wales, Australia

***Corresponding Author:** Alka Rachel John, alkarachel.john@student.uts.edu.au

Running head –Mental Workload in basic ATC tasks

Acknowledgements - This work was supported in part by the Australian Research Council

(ARC) under Discovery Grant DP180100670 and Discovery Grant DP180100656; in part by the

Australia Defence Innovation Hub under Contract P18-650825; U.S.   Office   of   Naval

Research Global through Cooperative Agreement under Grant ONRG-NICOP-N62909-19-1-

2058; and in part by the NSW Defence Innovation Network and NSW State Government of

Australia under Grant DINPP2019 S1-03/09.

Author Note

We have no known conflict of interest to disclose. Correspondence concerning this article should

be addressed to Alka Rachel John, Australian Artificial Intelligence Institute, Faculty of

Engineering and IT, University of Technology Sydney, NSW 2007, Australia. Email:

alkarachel.john@student.uts.edu.au

Abstract

Objective - We have designed tracking and collision prediction tasks to elucidate the differences in the physiological response to the workload variations in basic ATC tasks to untangle the impact of workload variations experienced by operators working in a complex ATC environment.

Background - Even though several factors influence the complexity of ATC tasks, keeping track of the aircraft and preventing collision are the most crucial.

Methods - Physiological measures, such as electroencephalogram (EEG), eye activity, and heart rate variability (HRV) data, were recorded from 24 participants performing tracking and collision prediction tasks with three levels of difficulty.

Results - The neurometrics of workload variations in the tracking and collision prediction tasks were markedly distinct, indicating that neurometrics can provide insights on the type of mental workload. The pupil size, number of blinks and HRV metric, root mean square of successive difference (RMSSD), varied significantly with the mental workload in both these tasks in a similar manner.

Conclusion - Our findings indicate that variations in task load are sensitively reflected in physiological signals, such as EEG, eye activity and HRV, in these basic ATC-related tasks.

Application - These findings have applicability to the design of future mental workload adaptive systems that integrate neurometrics in deciding not just 'when' but also 'what' to adapt. Our study provides compelling evidence in the viability of developing intelligent closed-loop mental workload adaptive systems that ensure efficiency and safety in ATC and beyond.

59   **Keywords:** Mental workload, EEG, pupil size, blink rate, RMSSD

60   **Précis:** This article identifies the physiological correlates of mental workload variation in basic
61   ATC tasks. The findings assert that neurometrics can provide more information on the task that
62   contributes to the workload, which can aid in the design of intelligent mental workload adaptive
63   system.

Introduction

People tend to avoid performing tasks that push their capabilities beyond their limits as they find it frustrating and stressful (Ahlstrom, 2010). However, not all work environments offer that luxury, which makes it crucial to establish good interaction between the human operator abilities and work environment (Wickens et al., 2015). Even though human operators can easily adapt to diverse work environments and perform several tasks and use different equipment simultaneously, poorly designed work environments cause an overload of sensory information resulting in excess workload. Air traffic controllers operate in such a complex environment to ensure a safe and efficient air traffic flow by organising traffic flow in a way that aircraft reach their destination in a well-organized and expeditious manner. However, as the air traffic increases, there is a growing need to study the mental factors that ensure the efficiency of air traffic controllers.

Mental workload is one of the most crucial factors that affects the efficiency of air traffic controllers as they operate in complex interactive work environments. Electroencephalogram (EEG) signal has been widely employed to estimate mental workload as the effects of task demand are clearly visible in EEG rhythm variations (Brookings et al., 1996, Gevins and Smith, 2003, Radüntz and Meffert, 2019). However, EEG features of the mental workload are found to be task-dependent, therefore, adding other modalities like eye activity data and heart rate data can help achieve far superior outcomes (Ke et al., 2014, Popovic et al., 2015).

Once the mental workload of the operator can be reliably assessed, it can be used to drive a

mental workload adaptive system (Prinzel et al., 2000; Schmorrowe et al., 2006). A mental

workload adaptive automation system should be able to conform to the variations in the mental

workload of the operator without them having to explicitly state their needs or triggering the

automation. When human operators and automation team up to achieve better performance and

efficiency, the operator expects automation to behave like a human coworker (Aricò et al., 2017).

Therefore, adaptive automation should be timely, stepping in at the right time and cognitively

empathetic with the operator, helping where it is needed, taking over the task that is currently

overwhelming the operator. However, currently, physiological correlates of the mental workload

are only used to decide "when" to adapt and not "what" to adapt, keeping the strategies

employed by the adaptive automation system still primitive. There is a need to develop

intelligent adaptive systems that can identify what form of automation to use depending on the

type of mental workload experienced by the operator. Nonetheless, there is still a dearth in

evidence that physiological metrics of mental workload can direct to the tasks contributing to

workload.

In this paper we investigated whether the multimodal physiological metrics of mental workload

can provide more information about the task contributing to the workload experienced by the

ATC operator. Even though several factors influence the complexity of ATC tasks (Mogford et

al., 1995, Cummings and Tsonis, 2005), such as environmental, display, traffic and

organisational factors, the main functions for ATC operator are tracking and collision prediction.

Therefore, we designed tracking and collision prediction tasks to elucidate the physiological

effects of workload variations in these basic ATC tasks. We formulated the following four

research hypotheses for our study:

H1. The three distinct levels of workload defined in both tracking and collision prediction tasks can yield significant performance degradation with the increasing levels of workload.

H2. Workload variation in tracking and collision prediction tasks can be reliably assessed using EEG, eye activity and HRV metrics.

H3. The performance in tracking and collision prediction tasks can be predicted based on the measured physiological signals.

H4. Physiological response to the workload variations in the tracking and collision prediction tasks will be distinct across tasks.

Methods

Participants

Twenty-four participants (age 25 ± 5, 17 males and 7 females, all right-handed) participated in this experiment after giving written informed consent. The experimental protocol was approved by the University of Technology Sydney Human Research Ethics Expedited Review Committee (ETH19-4197).

The EEG data were collected using SynAmps2 Express system (Compumedics Ltd., VIC, Australia) with 64 Ag/AgCl sensors system. Eye activity data was collected using Pupil Labs Pupil Core (Berlin, Germany). The Blood Volume Pulse (BVP) data was recorded using Empatica E4 (Empatica Srl, Milano, Italy). The real-time synchronisation of events from the task

140   scenario to the EEG, eye activity and BVP data was achieved by the Lab Streaming Layer

141   (Kothe, 2015).

Experimental Procedures

Our experimental design included two tasks – multiple objects tracking task (Innes et al., 2019)

and collision prediction task. As shown in Figure 1(A), in the tracking task, during the initial 3

seconds, participants look at a fixation cross on the screen followed by a freeze phase, where the

dots, some of which are blue, and the rest are red, remain stationary. The blue dots are the dots

that need to be tracked (hence, 'targets'). After three seconds of freeze, the blue targets also turn

red so that they are no longer distinctive from the other dots and all the dots start moving. The

participant is asked to keep track of the targets (dots that were initially blue) for 15 seconds.

After this time window all dots stop moving and the participants should indicate the target dots

by clicking on the dots that they have kept track of. The workload levels in this tracking task are

manipulated by varying the number of blue dots and the total number of dots (see Table 1).

As shown in Figure 1(B), in the collision prediction task, there is a fixation cross on the screen

for three seconds. Then there is a three-second-long freeze phase where the dots remain

stationary, after which all the dots start moving. The participant is required to predict the

trajectory of the dots and identify which pair of dots would collide. We have manipulated the

trajectory of the dots such that there will be only one collision in each trial. The participants were

asked to identify the pair of dots that would collide and click on both dots before the collision

happens. The levels of workload were manipulated by varying the number of dots (see Table 1).

Each participant had to perform 108 trials of each task with 36 trials of each workload level. The

type of workload condition in the trials was randomised to avoid any habituation or expectation

effects. All participants were trained in a training session to familiarise themselves with the

tasks. After the training, all participants performed the tasks for ~ 1.5 hours during which EEG,

eye activity and HRV data were collected.

Figure 1: The experimental design of the tasks. (A) the experimental design of the tracking task and (B) the design

of the collision prediction task. The number of dots shown in these diagrams is just for representation purposes.

Table 1: Workload Manipulations in the tracking and collision prediction tasks

TASK	WORKLOAD LEVEL	WORKLOAD MANIPULATION	
		Tracking Dots	Total Number of Dots
Tracking Task	Low	1	10
	Medium	3	12

		WORKLOAD MANIPULATION	
	High	5	15
		Total Number of Dots	
Collision	Low	6	
Prediction	Medium	12	
Task	High	18	

Data Analysis

Behavioural and Performance Data Analysis

For the tracking task, each participant's performance was evaluated by examining the tracking

accuracy.

$$Tracking\ Accuracy = \frac{Number\ of\ Correctly\ Tracked\ Dots}{Total\ Number\ of\ Dots\ to\ Track} \qquad (1)$$

In case of the collision prediction trials, the performance was determined using the time before

collision and collision miss proportion rate. The time before collision is the time period between

when the participant clicks on either one of the colliding dots and when the collision happens

(see Supplementary Figure 1). A collision miss was considered to happen when the participant

was unable to identify which pair of dots would collide and, hence, did not click on either of the

dots before the collision. The collision miss proportion rate for a particular workload level of the

collision prediction task is the ratio of the number of collision prediction misses to the total

number of collisions in that specific workload level.

$$Collision\ Prediction\ Miss\ Proportion\ Rate = \frac{Number\ of\ Missed\ Collision\ Predictions}{Total\ Number\ of\ Collisions} \qquad (2)$$

EEG Preprocessing

EEG data were preprocessed (see Supplementary Figure 2) using EEGLAB v2020.0 toolbox (Delorme and Makeig, 2004) in MATLAB R2019a (The Mathworks, Inc., Natick, MA, USA). EEG data were down-sampled to 250 Hz, and a band-pass filter of 2–45 Hz was applied. Channels with three seconds or more flat line were removed using the clean_flatline function. Noisy channels were identified and removed using the clean_channels function in EEGLAB. On an average 3±1 channels were removed and these channels were restored by interpolating the data from neighbouring channels using the spherical spline method from the EEGLAB toolbox. Continuous artifactual regions were removed using the EEGLAB function, pop_rejcont. Then window cleaning was performed using the clean_windows function in EEGLAB. After these artifact removal steps, two EEG datasets were extracted, one comprising tracking trials and one with the collision prediction trials. Each participant had 34±2 high workload, 35±1 medium workload and 34±1 low workload tracking trials, and 32±2 high workload, 33±2 medium workload and 33±1 low workload collision prediction trials.

Tracking and collision prediction datasets were decomposed using Independent Component Analysis (ICA), performed using EEGLAB's runica algorithm (Delorme and Makeig, 2004). Finally, we employed ICLabel (Pion-Tonachini et al., 2019), an automatic IC classifier to identify and reject components related to heart, line noise, eye, muscle, channel noise and other activities.

IC Clustering

EEGLAB STUDY structure (Delorme et al., 2011) was used to manage and process data recorded from multiple participants. A Study was created for each task, and each Study had one group (with 24 participants) with three conditions corresponding to the three levels of workload. For each participant, only those ICs that had a residual variance (RV) less than 15% and inside the brain volume were chosen, which was achieved using Fieldtrip extension (Oostenveld et al., 2011). The k-means clustering algorithm (Hartigan and Wong, 1979) was used to cluster independent components across all participants to clusters based on two equally weighted (weight = 1) criteria: (1) scalp maps and (2) their equivalent dipole model locations, which was performed using DIPFIT routines (Oostenveld and Oostendorp, 2004) in EEGLAB. Frontal and parietal brain regions have been reported to reflect the changes in workload (Brookings et al., 1996; Aricò et al., 2017), and as both our tasks also manipulate the visual load, we particularly focused on the frontal, parietal and occipital clusters of brain activity. Talairach coordinates (Lancaster et al., 2000) of the fitted dipole sources of these clusters were identified to select frontal, parietal and occipital clusters.

The grand-mean IC event-related spectral power changes (ERSPs) for each condition was subsequently calculated for each cluster. The three seconds of fixation phase in each tracking and collision prediction epoch was taken as the baseline to see the changes in power spectra during the task. ERSPs for frontal, parietal and occipital clusters for both tracking and prediction tasks were examined. To compare the ERSP of different workload conditions, permutation-based statistics, implemented in EEGLAB, was used with Bonferroni correction and significance level set to $p = .05$. Also, for the frontal, parietal and occipital cluster, each ICs' spectral powers were calculated using EEGLAB's spectopo function, which uses Welch's periodogram method (Welch, 1967) on each 2-s segment using a Hamming window with 25% overlap for a range of

frequencies from 2 to 45 Hz. For each IC, the power spectral density (PSD) at different

frequency bands were examined to identify the correlates of mental workload.

Eye Activity data

Pupil Core software, Pupil Capture provides the pupil size for the left and right eye separately

along with the associated confidence value, which represents the quality of the detection result.

All data points where the confidence of the pupil size was less than 0.8 were removed from the

data. The pupil size data was normalised using the baseline data (defined as the three seconds of

fixation period in each tracking and collision prediction epoch). The number of blinks during

each trial was also extracted from the pupil size measurement when the pupil size and confidence

of the measurement, reported by the Pupil Capture software, suddenly dropped to zero.

Heart Rate Variability

Inter-beat-interval (IBI) time series was computed from the Blood Volume Pulse (BVP) data of

each tracking and collision prediction trial. Root Mean Square of the Successive Differences

(RMSSD) was computed by detecting peaks of the BVP and calculating the lengths of the

intervals between adjacent beats.

$RMSSD = \sqrt{\frac{1}{N}\sum_{i=1}^{N}(IBI_{i-1} - IBI_i)^2}$ (3)

RMSSD data was also normalised by considering the three seconds of fixation period in each

tracking and collision prediction epoch as the baseline.

Statistical Analysis

Statistical analyses were carried out using the SPSS (IBM SPSS 26.0; Chicago, IL, U.S.A.)

statistical tool. In order to investigate the differences in the performance, EEG, eye activity and

HRV parameters across participants in the three workload levels of tracking and collision

prediction tasks, one-way repeated-measures analysis of variance (ANOVA) was conducted with

workload level as the within-subjects factor. Mauchly's test was implemented to test for

sphericity. We performed Greenhouse-Geisser correction if sphericity was not satisfied (p < .05).

If the main effect of the ANOVA was significant, post-hoc comparisons were made to determine

the significance of pairwise comparisons, using Bonferroni correction. Finally, multiple linear

regression was performed to relate EEG, eye activity and HRV metrics to the performance in the

tracking and collision prediction tasks. EEG power, eye activity and HRV metrics were all

entered as predictors using the enter method, and the performance in the task was the dependent

variable.

Results

Behavioural and Performance Measures

A repeated-measures ANOVA showed that tracking accuracy decreased significantly with

increasing levels of workload [$F(2, 54) = 239.910$, $p < .001$, $\eta_p^2 = .899$], as shown in Figure

2(A).

For the collision prediction task, the time before collision and collision prediction miss

proportion rate was considered. A repeated-measures ANOVA results showed that time before

collision decreased significantly with increasing workload [$F(1.497, 40.406) = 132.688$, $p < .001$,

$\eta_p^2 = .831$] and the collision prediction miss proportion increased with increasing levels of

workload [F(1.593, 43.009) = 116.338, p < .001, η_p^2 = .812], as shown in Figure 2(B1) and

2(B2).

A

B

271   Figure 2: (A) shows the tracking accuracy of all the participants in the tracking task for the three levels of workload.

272   (B) shows the performance of all participants in the collision prediction task for the three levels of workload. (B1)

273   shows the mean time before collision for all the participants in the low, medium, and high workload conditions. (B2)

274   shows the collision prediction miss proportion rate for the three levels of workload.

275   **EEG Results**

Independent Source Clusters

The frontal, parietal and occipital clusters for both tracking (refer Figure 3) and collision prediction task (see Figure 4) were selected based on the location of fitted dipole sources (Oostenveld and Oostendorp, 2004).

ERSP Changes with Mental Workload

Figures 5 illustrates frontal, parietal and occipital clusters' ERSP changes for three workload conditions: low, medium and high during the tracking task. Statistical analysis on ERSP changes of the frontal cluster (Figure 5(A)) revealed a significant increase in theta power with increasing levels of workload. However, no significant spectral power variations were observed at the parietal cluster. Figure 5(B) shows the ERSP changes at the occipital cluster, which revealed a significant decrease in alpha power with increasing levels of workload.

Figure 6 illustrates the frontal, parietal and occipital clusters' ERSP changes for three workload conditions in the collision prediction task. Statistical analysis on ERSP changes of the frontal cluster showed a significant increase in theta power with increasing levels of workload (Figure 6(A)). The ERSP changes at the parietal cluster (Figure 6(B)) revealed a significant increase in the theta power and a significant decrease in the alpha power with increasing level of workload. The ERSP changes at the occipital cluster (Figure 6(C)) revealed a significant increase in the delta and theta power with increasing workload.

Scalp map of the selected Frontal Cluster   Scalp map of the selected Parietal Cluster   Scalp map of the selected Occipital Cluster

Dipole locations of ICs in the Frontal Cluster   Dipole locations of ICs in the Parietal Cluster   Dipole locations of ICs in the Occipital Cluster

295   Figure 3. Frontal [Talairach coordinate: (-1, 41, 27)], Parietal [Talairach coordinate: (4, -51, 39)] and Occipital

296   [Talairach coordinate: (30, -70, 15)] clusters selected in the tracking task (A) spatial scalp maps; (B) dipole source

297   locations.

Scalp map of the selected Frontal Cluster   Scalp map of the selected Parietal Cluster   Scalp map of the selected Occipital Cluster

298   Dipole locations of ICs in the Frontal Cluster   Dipole locations of ICs in the Parietal Cluster   Dipole locations of ICs in the Occipital Cluster

299   Figure 4. Frontal [Talairach coordinate: (-10, 17, 46)], Parietal [Talairach coordinate: (5, -47, 47)] and Occipital

300   [Talairach Coordinate: (-3, -69, 20)] clusters selected in the collision prediction task (A) spatial scalp maps; (B)

301   dipole source locations.

B

B1

B2

B3

Figure 5: ERSP changes during the tracking task at the (A) Frontal and (B) Occipital Cluster. (A1) shows the ERSP

changes at the frontal cluster during high (first panel) and low (second panel) workload conditions and the third

panel shows the statistically significant difference between high and low workload conditions (p < .05). (A2) shows

the ERSP changes at the frontal cluster during high (first panel) and medium (second panel) workload conditions

and the third panel shows the statistically significant difference between high and medium workload conditions (p <

.05). (A3) shows the ERSP changes at the frontal cluster during medium (first panel) and low (second panel)

workload conditions and the third panel shows the statistically significant difference between medium and low

workload conditions (p < .05). (B1) shows the ERSP changes at the occipital cluster during high (first panel) and

low (second panel) workload conditions and the third panel shows the statistically significant difference between

high and low workload conditions (p < .05). (B2) shows the ERSP changes at the occipital cluster during high (first

panel) and medium (second panel) workload conditions and the third panel shows the statistically significant

difference between high and medium workload conditions (p < .05). (B3) shows the ERSP changes at the occipital

cluster during medium (first panel) and low (second panel) workload conditions and the third panel shows the

statistically significant difference between medium and low workload conditions (p < .05).

A

A1

Figure 6: ERSP changes during the collision prediction task at the (A) Frontal, (B) Parietal, (C) Occipital Cluster. (A1) shows the ERSP changes at the frontal cluster during high (first panel) and low (second panel) workload conditions and the third panel shows the statistically significant difference between high and low workload conditions ($p < .05$). (A2) shows the ERSP changes at the frontal cluster during high (first panel) and medium (second panel) workload conditions and the third panel shows the statistically significant difference between high and medium workload conditions ($p < .05$). (A3) shows the ERSP changes at the frontal cluster during medium (first panel) and low (second panel) workload conditions and the third panel shows the statistically significant difference between medium and low workload conditions ($p < .05$). (B1) shows the ERSP changes at the parietal cluster during high (first panel) and low (second panel) workload conditions and the third panel shows the statistically significant difference between high and low workload conditions ($p < .05$). (B2) shows the ERSP changes at the parietal cluster during high (first panel) and medium (second panel) workload conditions and the third panel shows the statistically significant difference between high and medium workload conditions ($p < .05$). (B3) shows the ERSP changes at the

parietal cluster during medium (first panel) and low (second panel) workload conditions and the third panel shows

the statistically significant difference between medium and low workload conditions (p < .05). (C1) shows the ERSP

changes at the occipital cluster during high (first panel) and low (second panel) workload conditions and the third

panel shows the statistically significant difference between high and low workload conditions (p < .05). (C2) shows

the ERSP changes at the occipital cluster during high (first panel) and medium (second panel) workload conditions

and the third panel shows the statistically significant difference between high and medium workload conditions (p <

.05). (C3) shows the ERSP changes at the occipital cluster during medium (first panel) and low (second panel)

workload conditions and the third panel shows the statistically significant difference between medium and low

workload conditions (p < .05).

Power Spectral Density Changes with Mental Workload

Figure 7(A1) illustrates that frontal theta PSD increased significantly with increasing levels of

workload in the tracking task [$F(2, 46) = 50.931$, $p < .001$, $\eta_p^2 = .822$]. As shown in Figure

7(A2), the results of one-way repeated-measures ANOVA showed that occipital alpha PSD

decreased significantly with increasing workload of the tracking task [$F(2, 46) = 24.780$, $p <$

$.001$, $\eta_p^2 = .693$].

For the collision prediction task, the frontal cluster's ICs showed significant increase in theta

PSD with increasing workload (Figure 7B(1)) according to the one-way repeated-measures

ANOVA [$F(2, 46) = 8.570$, $p = .001$, $\eta_p^2 = .271$]. However, the parietal cluster's IC's spectral

power showed a significant increase in the theta frequency band [$F(2, 46) = 47.764$, $p < .001$, η_p^2

$= .675$] and a significant decrease in the alpha band [$F(2, 46) = 38.639$, $p < .001$, $\eta_p^2 = .627$] with

increasing workload, as shown in Figure 7(B2) and Figure 7(B3). One-way repeated-measures

ANOVA results showed that occipital delta [$F(1.563, 35.951) = 35.321$, $p < .001$, $\eta_p^2 = .606$] and

theta [$F(2, 46) = 39.101$, $p < .001$, $\eta_p^2 = .630$] power increased significantly with increasing

workload in the collision prediction task, as shown in Figure 7(B4) and 7(B5).

Figure 7: (A) Normalized Power Spectral Density at the Frontal and Occipital ICs selected in the Frontal and

Occipital clusters for the tracking task. (A1) shows the normalised frontal theta PSD in the low, medium, and high

workload conditions. (A2) shows the normalised occipital alpha PSD for low, medium, and high workload condition

for the tracking task. (B) shows the normalized Power Spectral Density at the Frontal, Parietal and Occipital ICs

selected in the Frontal, Parietal and Occipital cluster for the collision prediction task. (B1) shows the mean frontal

theta PSD in the low, medium, and high workload conditions. (B2) shows the mean parietal theta PSD for the three

levels of workload. (B3) shows the mean parietal alpha power for different workload conditions and (B4) shows the

mean occipital delta PSD in the low, medium, and high workload conditions. (B5) shows the mean occipital theta

PSD for the three levels of workload condition in collision prediction task.

Eye activity changes with mental workload

As shown in Figure 8(A), pupil size increased with the increasing workload for both tracking

[$F(2, 38) = 13.205$, $p < .001$, $\eta_p^2 = .410$] and collision prediction tasks [$F(2, 46) = 9.276$, $p < .001$,

$\eta_p^2 = .287$]. The number of blinks during tracking and collision prediction tasks decreased with

the increasing workload, as shown in Figure 8(B). One-way repeated-measure ANOVA was

conducted to study the effect of workload variations on the number of blinks, which revealed

significant variations in the number of blinks during the tracking task for different workload

conditions [$F(2, 46) = 3.624$, $p = .035$, $\eta_p^2 = .136$]. The effect of workload on the number of

blinks in the collision prediction task was analysed using one-way repeated-measure ANOVA. It

showed a significant variation in the number of blinks [$F(2, 46) = 18.586$, $p < .001$, $\eta_p^2 = .447$].

Heart Rate Variability (RMSSD) changes with Mental Workload

Figure 8(C) shows the RMSSD decreased significantly with increasing workload conditions of

the tracking and collision prediction task. For the tracking task, there was a significant change in

the RMSSD for the different workload conditions, as shown by the one-way repeated-measures

ANOVA [$F(2, 34) = 10.171$, $p < .001$, $\eta_p^2 = .374$]. Results from one-way repeated-measures

ANOVA shows that in the collision prediction task, there was a significant change in the

RMSSD for different workload conditions [$F(2, 44) = 4.279$, $p = .022$, $\eta_p^2 = .201$].

A

A1

A2

B

B1

B2

C

C1

C2

Figure 8: (A) shows the normalized pupil size of all the participants shows a positive trend with the increasing

workload. (A1) Normalised pupil size in the three workload conditions of the tracking task. (A2) Normalised pupil

size during low, medium, and high workload conditions for the collision prediction task. (B) shows the negative

trend in the number of blinks with the increasing workload. (B1) Number of blinks during different workload

conditions of the tracking task. (B2) Number of blinks during the collision prediction task decreases with increasing

level of workload. (C) shows the declining trend in the normalized RMSSD of all the participants with the

increasing workload. (C1) Normalised RMSSD all the participants in the low, medium, and high workload

conditions of the tracking task. (C2) Normalised RMSSD during collision prediction task for the three levels of

workload.

Multiple Regression Results

Multiple regression was carried out to investigate whether EEG, eye activity and HRV metrics of

workload could significantly predict the performance in the tracking task. The results of the

regression indicated that the model explained 54.3% of the variance and that the model was a

significant predictor of the tracking performance, $F(3, 67) = 26.543$, $p < .001$. While EEG

metrics ($p = .001$) and eye activity ($p < .001$) contributed significantly to the model, HRV

metrics did not ($p = .125$). The final predictive model was:

$Performance\ in\ tracking\ task =$

$0.725 - 0.067 * EEG\ metrics - 0.089 * Eye\ related\ metrics - 0.152 * HRV\ metrics$

420   (4)

In order to determine whether EEG, eye activity and HRV metrics could significantly predict the

performance in collision prediction task, we conducted multiple regression analysis. The results

of the regression indicated that the model explained 61.7% of the variance and that the model

was a significant predictor of the performance in the collision prediction task, $F(3, 68) = 24.324$,

$p < .001$. While eye activity ($p = .02$) and EEG metrics ($p < .001$) contributed significantly to the

model, HRV metrics did not ($p = .443$). The final predictive model was:

$Performance\ in\ Collision\ Prediction\ task = 0.055 - 0.532 * EEG\ metrics - 0.276 *$

$Eye\ related\ metrics + 0.444 * HRV\ metrics$ (5)

Discussion

In this study, we designed two simplified tasks based on ATC: tracking and collision prediction

tasks. Although both these tasks represent the basic tasks that ATC operators routinely perform,

we considered them separately to untangle the differences in the physiological response to

workload variations in these tasks.

In order to study workload effects of increasing air traffic, the mental workload in both these

tasks was manipulated by varying the number of dots. It was observed that the performance in

the tracking and collision prediction task deteriorated significantly with increasing levels of

workload. Hence, we can confirm that the workload manipulation (by varying the number of

dots) in both tracking and collision prediction tasks was successful in eliciting significant

performance variations (H1).

In order to assess the mental workload, EEG, eye activity and BVP data were recorded while the

participants performed the tasks. The tracking task demands allocation of attentional resources to

keep track of one, three or five tracking dots moving randomly among distractor dots. Working

memory load is sensitive to increased allocation of attentional resources and is reflected by

increases in frontal theta power (Klimesch et al., 1998; Klimesch, 1999; Gevins and Smith,

2000). In the tracking task, we observed an increase in the frontal theta power, which confirms

that increased working memory load was experienced with increasing workload levels. Tracking

dots moving among distractor dots also entails working memory mechanisms related to relevant

item maintenance and increases in the memory load. This working memory mechanism was

reflected by a decrease in the alpha power (Gevins et al., 1997; Wilson, 2002 and Puma et al.,

2018). The alpha power is also known to decrease with increased memory load (Fournier et al.,

1999; Smith et al., 2001; Ryu and Myung, 2005) and task difficulty (Sterman and Mann, 1995;

Ota et al., 1996). Our findings also substantiate this working memory mechanism as the occipital

alpha power decreases with increasing workload levels in the tracking task.

In the collision prediction task, anticipating the trajectory of the dots and predicting whether the

dots would collide requires attention and internal concentration. Delta power is an indicator of

attention or internal concentration in mental tasks, and it has been reported to increase with the

increase in workload (Sterman and Mann, 1995; Harmony et al., 1996; Wilson, 2002). Our

results demonstrate an increase in the delta power at the occipital sites, which validates that there

is an increased allocation of attentional resources with increasing levels of workload in the

collision prediction task. Additionally, keeping a tab on the trajectory of six, 12 or 18 eight dots

adds to the memory load in the participants. Several studies have shown that theta power is

correlated with memory load (Jensen and Tesche, 2002; Jacobs et al., 2006) and working

memory capacity (Klimesch, 1996; Klimesch, 1999; Sauseng et al., 2010). In collision prediction

task, our results reveal a significant increase in the theta power at the frontal, parietal and

occipital clusters, confirming an increase in memory load with increasing levels of workload.

Furthermore, our results indicate that with increasing levels of workload, there is a decrease in

parietal alpha power. This observed alpha band desynchronisation with the increasing workload

is related to relevant item maintenance in the working memory (Sterman and Mann, 1995;

Gevins et al., 1997; Wilson, 2002; Puma et al., 2018) and is known to decrease with increased

memory load (Fournier et al., 1999; Smith et al., 2001; Ryu and Myung, 2005) and task

difficulty (Sterman and Mann, 1995; Ota et al., 1996). However, in the collision prediction task,

the most significant decrease in the parietal alpha power was observed a few seconds before the

collision. It might be related to the increase in the experienced time pressure (Slobounov et al.,

2000) as the participants attempt to identify and click on the colliding pair of dots before the

collision happens.

We also explored eye-related metrics and HRV metrics during workload variations. Eye activity

data was transformed to pupil size and blink rate. Pupil size increased significantly with the

increasing workload in both tracking and collision prediction tasks. The number of blinks also

reduced considerably with the increasing workload in both tasks. Pupil size is a reliable measure

of workload (Marquart et al., 2015) as it dilates with increasing workload. Recarte et al., 2008

show that blink inhibition happens in higher workload conditions and so, the blink rate is

inversely correlated with the attentional levels and workload experienced by the operator

(Brookings et al., 1996, Wilson, 2002, Widyanti et al., 2017). RMSSD was found to be

negatively correlated with the mental workload in both tasks. This decrease in RMSSD with the

increasing workload is widely reported in the literature (Mehler et al., 2011, Heine et al., 2017).

Our results show that EEG power spectra at the frontal, parietal and occipital areas, eye activity

and HRV metrics can reliably and accurately assess the mental workload of the participants in

both tasks. Hence, our second hypothesis (H2) is proved to be true for both tracking and collision

prediction tasks. Relating to our third hypothesis (H3), the multiple regression results showed

that the performance in the tracking and collision prediction tasks could be predicted from the

EEG, eye related and HRV metrics.

Our results also indicate that even though eye activity and HRV metrics are sensitive to task load

variations, they may not provide any valuable information on the task that causes the variations

in workload. However, the EEG measures were found to be not just sensitive to the workload

variations but also the task type. The increases in workload in the tracking task was reflected by

the increase in frontal theta power and decrease in occipital alpha power. No significant changes

were observed in the parietal theta, alpha, occipital delta, or theta power with the increasing

workload in the tracking task. In the collision prediction task, the increase in workload was

correlated with the increases in frontal theta, parietal theta, occipital delta and theta power and a

decrease in parietal alpha power. No significant variation was observed in the occipital alpha

power during the collision prediction task. The neurometrics correlated with the variations in the

workload of tracking and collision prediction tasks are different, which proves that our fourth

hypothesis (H4) is true. Therefore, neurometrics can help identify the task contributing to the

increase in workload in complex ATC environments at a time instant and define the strategies

that can be used by the workload adaptive system to mitigate this increase. These results provide

evidence that the use of EEG measures in a closed-loop adaptive system can not only aid the

decision of "when" but also "what" form of automation to deploy to mitigate the workload

variations in operators. Hence, the results presented here contribute to the development of

adaptive strategies essential for the design of intelligent closed-loop mental workload adaptive

ATC systems.

Conclusion

In order to elucidate the impact of basic task load variations that comprise the load variations in complex ATC tasks, we separately designed two basic ATC tasks: tracking and collision prediction tasks. EEG spectral power, eye and HRV correlates to mental workload variations for tracking and collision prediction tasks of air traffic controllers are successfully unravelled. The differences in neural response to increased workload in the tracking and collision prediction task indicate that these neural measures are sensitive to variations and type of mental workload and their potential utility in not just deciding "when" but also "what" to adapt, aiding the development of intelligent closed-loop mental workload aware systems. This investigation of physiological indices of workload variation in the basic ATC tasks has applicability to the design of future adaptive systems that integrate neurometrics in deciding the form of automation to be used to mitigate the variations in workload in complex ATC systems.

Key points:
- Workload variation in tracking and collision prediction tasks was reliably assessed using EEG, eye activity and HRV metrics.
- The performance in tracking and collision prediction tasks can be predicted based on the measured physiological signals.
- Neurometrics of the workload variations in the tracking and collision prediction tasks are distinct across tasks.

References

Ahlstrom, Ulf. "An eye for the air traffic controller workload." In *Journal if the Transportation Research Forum*, vol. 46, no. 3. 2010.

Aricò, Pietro, et al. "Human factors and neurophysiological metrics in air traffic control: a

critical review." *IEEE reviews in biomedical engineering* 10 (2017): 250-263.

Boksem, Maarten AS, Theo F. Meijman, and Monicque M. Lorist. "Effects of mental fatigue on

attention: an ERP study." *Cognitive brain research* 25, no. 1 (2005): 107-116.

Brookings, Jeffrey B., Glenn F. Wilson, and Carolyne R. Swain. "Psychophysiological responses

to changes in workload during simulated air traffic control." *Biological psychology* 42.3 (1996):

361-377.

Cummings, Mary L., and Chris Tsonis. "Deconstructing complexity in air traffic control."

Proceedings of the Human Factors and Ergonomics Society Annual Meeting. Vol. 49. No. 1.

Sage CA: Los Angeles, CA: Sage Publications, 2005.

Delorme, Arnaud, and Scott Makeig. "EEGLAB: an open source toolbox for analysis of single-

trial EEG dynamics including independent component analysis." *Journal of neuroscience*

methods 134, no. 1 (2004): 9-21.

Delorme, Arnaud, Tim Mullen, Christian Kothe, Zeynep Akalin Acar, Nima Bigdely-Shamlo,

Andrey Vankov, and Scott Makeig. "EEGLAB, SIFT, NFT, BCILAB, and ERICA: new tools for

advanced EEG processing." *Computational intelligence and neuroscience* 2011 (2011).

Gevins, Alan, and Michael E. Smith. "Neurophysiological measures of working memory and

individual differences in cognitive ability and cognitive style." *Cerebral cortex* 10.9 (2000): 829-

839.

Gevins, Alan, Michael E. Smith, Linda McEvoy, and Daphne Yu. "High-resolution EEG

mapping of cortical activation related to working memory: effects of task difficulty, type of

processing, and practice." *Cerebral cortex (New York, NY: 1991)* 7, no. 4 (1997): 374-385.

Gevins, Alan, and Michael E. Smith. "Neurophysiological measures of cognitive workload during human-computer interaction." *Theoretical Issues in Ergonomics Science* 4.1-2 (2003): 113-131.

Fournier, Lisa R., Glenn F. Wilson, and Carolyne R. Swain. "Electrophysiological, behavioral, and subjective indexes of workload when performing multiple tasks: manipulations of task difficulty and training." *International Journal of Psychophysiology* 31, no. 2 (1999): 129-145.

Harmony, Thalía, Thalía Fernández, Juan Silva, Jorge Bernal, Lourdes Díaz-Comas, Alfonso Reyes, Erzsébet Marosi, Mario Rodríguez, and Miguel Rodríguez. "EEG delta activity: an indicator of attention to internal processing during performance of mental tasks." *International journal of psychophysiology* 24, no. 1-2 (1996): 161-171.

Hartigan, John A., and Manchek A. Wong. "Algorithm AS 136: A k-means clustering algorithm." *Journal of the royal statistical society. series c (applied statistics)* 28, no. 1 (1979): 100-108.

Heine, Tobias, Gustavo Lenis, Patrick Reichensperger, Tobias Beran, Olaf Doessel, and Barbara Deml. "Electrocardiographic features for the measurement of drivers' mental workload." *Applied ergonomics* 61 (2017): 31-43.

Innes, Reilly J., Nathan J. Evans, Zachary L. Howard, Ami Eidels, and Scott D. Brown. "A broader application of the detection response task to cognitive tasks and online environments." *Human Factors* (2019): 0018720820936800.

Jacobs, Joshua, Grace Hwang, Tim Curran, and Michael J. Kahana. "EEG oscillations and recognition memory: theta correlates of memory retrieval and decision making." *Neuroimage* 32, no. 2 (2006): 978-987.

Jensen, Ole, and Claudia D. Tesche. "Frontal theta activity in humans increases with memory load in a working memory task." *European journal of Neuroscience* 15, no. 8 (2002): 1395-1399.

Ke, Yufeng, et al. "An EEG-based mental workload estimator trained on working memory task can work well under simulated multi-attribute task." *Frontiers in human neuroscience* 8 (2014): 703.

Keil, Andreas, Matthias M. Müller, Thomas Gruber, Christian Wienbruch, Margarita Stolarova, and Thomas Elbert. "Effects of emotional arousal in the cerebral hemispheres: a study of oscillatory brain activity and event-related potentials." *Clinical neurophysiology* 112, no. 11 (2001): 2057-2068.

Klimesch, Wolfgang. "Memory processes described as brain oscillations in the EEG-alpha and theta bands." *Psycoloquy* (1995).

Klimesch, Wolfgang. "Memory processes, brain oscillations and EEG synchronization." *International journal of psychophysiology* 24, no. 1-2 (1996): 61-100.

Klimesch, Wolfgang, et al. "Induced alpha band power changes in the human EEG and attention." *Neuroscience letters* 244.2 (1998): 73-76.

Klimesch, Wolfgang. "EEG alpha and theta oscillations reflect cognitive and memory performance: a review and analysis." *Brain research reviews* 29, no. 2-3 (1999): 169-195.

Kothe, Christian. "Lab streaming layer (LSL)." *https://github. com/sccn/labstreaminglayer. Accessed on October* 26 (2014): 2015.

Lancaster, Jack L., Marty G. Woldorff, Lawrence M. Parsons, Mario Liotti, Catarina S. Freitas, Lacy Rainey, Peter V. Kochunov, Dan Nickerson, Shawn A. Mikiten, and Peter T. Fox.

"Automated Talairach atlas labels for functional brain mapping." *Human brain mapping* 10, no. 3 (2000): 120-131.

Lin, Chin-Teng, Kuan-Chih Huang, Chih-Feng Chao, Jian-Ann Chen, Tzai-Wen Chiu, Li-Wei Ko, and Tzyy-Ping Jung. "Tonic and phasic EEG and behavioral changes induced by arousing feedback." *NeuroImage* 52, no. 2 (2010): 633-642.

Makeig, Scott, Marissa Westerfield, T-P. Jung, Sonia Enghoff, Jeanne Townsend, Eric Courchesne, and Terrence J. Sejnowski. "Dynamic brain sources of visual evoked responses." *Science* 295, no. 5555 (2002): 690-694.

Marquart, Gerhard, Christopher Cabrall, and Joost de Winter. "Review of eye-related measures of drivers' mental workload." *Procedia Manufacturing* 3 (2015): 2854-2861.

Mehler, Bruce, Bryan Reimer, and Ying Wang. "A comparison of heart rate and heart rate variability indices in distinguishing single-task driving and driving under secondary cognitive workload." (2011).

Mogford, Richard H., et al. *The Complexity Construct in Air Traffic Control: A Review and Synthesis of the Literature*. CTA INC MCKEE CITY NJ, 1995.

Onton, Julie, Arnaud Delorme, and Scott Makeig. "Frontal midline EEG dynamics during working memory." *Neuroimage* 27, no. 2 (2005): 341-356.

Oostenveld, Robert, and Thom F. Oostendorp. "Validating the boundary element method for forward and inverse EEG computations in the presence of a hole in the skull." *Human brain mapping* 17, no. 3 (2002): 179-192.

Oostenveld, Robert, Pascal Fries, Eric Maris, and Jan-Mathijs Schoffelen. "FieldTrip: open source software for advanced analysis of MEG, EEG, and invasive electrophysiological data." Computational intelligence and neuroscience 2011 (2011).

Ota, Toshio, Ryoichi Toyoshima, and Toshio Yamauchi. "Measurements by biphasic changes of

the alpha band amplitude as indicators of arousal level." *International journal of*

psychophysiology 24, no. 1-2 (1996): 25-37.

Pion-Tonachini, Luca, Ken Kreutz-Delgado, and Scott Makeig. "ICLabel: An automated

electroencephalographic independent component classifier, dataset, and website." *NeuroImage*

198 (2019): 181-197.

Popovic, Djordje, et al. "Sensitive, diagnostic and multifaceted mental workload classifier

(PHYSIOPRINT)." *International Conference on Augmented Cognition*. Springer, Cham, 2015.

Prinzel, Lawrence J., Frederick G. Freeman, Mark W. Scerbo, Peter J. Mikulka, and Alan T.

Pope. "A closed-loop system for examining psychophysiological measures for adaptive task

allocation." *The International journal of aviation psychology* 10, no. 4 (2000): 393-410.

Puma, Sébastien, et al. "Using theta and alpha band power to assess cognitive workload in

multitasking environments." *International Journal of Psychophysiology* 123 (2018): 111-120.

Radüntz, Thea, and Beate Meffert. "User experience of 7 mobile electroencephalography

devices: comparative study." *JMIR mHealth and uHealth* 7.9 (2019): e14474.

Recarte, Miguel Ángel, et al. "Mental workload and visual impairment: Differences between

pupil, blink, and subjective rating." *The Spanish journal of psychology* 11.2 (2008): 374.

Rouse, William B. "Adaptive aiding for human/computer control." *Human factors* 30, no. 4

(1988): 431-443.

Ryu, Kilseop, and Rohae Myung. "Evaluation of mental workload with a combined measure

based on physiological indices during a dual task of tracking and mental arithmetic."

International Journal of Industrial Ergonomics 35, no. 11 (2005): 991-1009.

Sauseng, Paul, Birgit Griesmayr, Roman Freunberger, and Wolfgang Klimesch. "Control

mechanisms in working memory: a possible function of EEG theta oscillations." *Neuroscience &*

Biobehavioral Reviews 34, no. 7 (2010): 1015-1022.

Schmorrow, Dylan, Kay M. Stanney, Glenn Wilson, and Peter Young. "Augmented cognition in

human–system interaction." *Handbook of human factors and ergonomics* (2006): 1364-1383.

Slobounov, S. M., K. Fukada, R. Simon, M. Rearick, and W. Ray. "Neurophysiological and

behavioral indices of time pressure effects on visuomotor task performance." *Cognitive Brain*

Research 9, no. 3 (2000): 287-298.

Smith, Michael E., Alan Gevins, Halle Brown, Arati Karnik, and Robert Du. "Monitoring task

loading with multivariate EEG measures during complex forms of human-computer interaction."

Human Factors 43, no. 3 (2001): 366-380.

Ullsperger, P., A-M. Metz, and H-G. Gille. "The P300 component of the event-related brain

potential and mental effort." *Ergonomics* 31, no. 8 (1988): 1127-1137.

Welch, Peter. "The use of fast Fourier transform for the estimation of power spectra: a method

based on time averaging over short, modified periodograms." IEEE Transactions on audio and

electroacoustics 15, no. 2 (1967): 70-73.

Widyanti, Ari, Nisha Faradila Sofiani, Herman Rahadian Soetisna, and Khoirul Muslim. "Eye

blink rate as a measure of mental workload in a driving task: convergent or divergent with other

measures?." *Eye* 8, no. 2 (2017).

Wilson, Glenn F. "An analysis of mental workload in pilots during flight using multiple

psychophysiological measures." *The International Journal of Aviation Psychology* 12, no. 1

(2002): 3-18.

Supplementary Material

Figure 1. A schematic diagram describing how time before collision was calculated in the collision prediction task

Figure 2. The EEG preprocessing and processing pipeline used for tracking and collision prediction tasks.