Effects of awareness and task relevance on neurocomputational models of mismatch

negativity generation

Running title: Mechanisms of vMMN: Adaptation or Prediction?

Schlossmacher, Insa[a,b], Lucka, Felix[c,d], Antje Peters[a,b], Bruchmann, Maximilian[a,b], and Straube,

Thomas[a,b]

[a]Institute of Medical Psychology and Systems Neuroscience, University of Münster, 48149

Münster, Germany

[b]Otto Creutzfeldt Center for Cognitive and Behavioral Neuroscience, University of Münster,

48149 Münster, Germany

[c]Centrum Wiskunde & Informatica, 1098XG, Amsterdam, The Netherlands

[d]Centre for Medical Image Computing, University College London, WC1E 6BT London,

United Kingdom

Corresponding author:

Insa Schlossmacher

Institute of Medical Psychology and Systems Neuroscience

University of Münster

Von-Esmarch-Strasse 52

48149 Münster

Germany

Phone: +49 251 83-52785

Fax: +49 251 83-56874

E-mail: insa.schlossmacher@uni-muenster.de

Abstract

Detection of regularities and their violations in sensory input is key to perception. Violations are indexed by an early EEG component called the mismatch negativity (MMN) – even if participants are distracted or unaware of the stimuli. On a mechanistic level, two dominant models have been suggested to contribute to the MMN: adaptation and prediction. Whether and how context conditions, such as awareness and task relevance, modulate the mechanisms of MMN generation is unknown. We conducted an EEG study disentangling influences of task relevance and awareness on the visual MMN. Then, we estimated different computational models for the generation of single-trial amplitudes in the MMN time window. Amplitudes were best explained by a prediction error model when stimuli were task-relevant but by an adaptation model when task-irrelevant and unaware. Thus, mismatch generation does not rely on one predominant mechanism but mechanisms vary with task relevance of stimuli.

Keywords: adaptation, computational modeling, inattentional blindness, MMN, prediction

1. Introduction

Detecting sudden changes in our environment is of fundamental importance for perceiving and responding to altered circumstances, i.e. by adjusting actions and updating the model of the world. A typical electrophysiological phenomenon associated with deviance detection is the so-called mismatch negativity (MMN), a negative-going event-related potential (ERP) over sensory cortices in response to infrequent (deviants) compared to frequent (standards) stimuli (Näätänen et al., 1978; Stefanics et al., 2014). It has been shown that the MMN can be observed regardless whether stimuli are task-relevant or not (Alho et al., 1989; Kuldkepp et al., 2013; Näätänen et al., 1978; Schlossmacher et al., 2020) and even if participants are unaware of the stimuli of interest (Jack et al., 2017; Koelsch et al., 2006; Schlossmacher et al., 2020; Strauss et al., 2015).

While the existence of the MMN is not contested, the mechanisms behind MMN generation have been a matter of great debate (Garrido et al., 2009b; May and Tiitinen, 2010; Näätänen et al., 2005; Winkler and Czigler, 2012). Over the years, several different mechanisms of varying complexity have been put forward. One candidate is adaptation (Jääskeläinen et al., 2004; May and Tiitinen, 2010). In this framework, the observed difference between deviants and standards stems from stimulus-specific adaptation to the standards. Rare stimuli activate so-called fresh-afferents and elicit a larger response compared to the adapted standards (May and Tiitinen, 2010). Differently to the adaptation hypothesis, the memory trace hypothesis implicated that the MMN to deviants represents change detection from the build-up memory trace of the standard stimulus (Näätänen, 1992; Schröger and Winkler, 1995). Over the years the memory-trace hypothesis has been refined to also include a model adjustment aspect that relates to the updating of a model of the sensory evidence in response to unpredicted events (Winkler et al., 1996; Winkler and Czigler, 1998). Recently, model adjustment has been linked with the concept of predictive processing which has been put forward with the rise of the

"Bayesian brain hypothesis" (Clark, 2013; Friston, 2005; Garrido et al., 2009b). The "Bayesian

brain" describes the supposition that neural information processing relies on Bayesian

principles using a generative model of the world that compares prior expectations with sensory

input (Clark, 2013; Friston, 2005). From this point of view, MMN can be conceptualized as a

prediction error that arises as a result of a comparison process between expected and presented

stimulus. During an oddball paradigm presentation of a deviant stimulus would thus lead to a

large prediction error as it violates the expectation of the more frequent standard (Stefanics et

al., 2014; Winkler and Czigler, 2012). Thus, the suggested mechanisms for MMN generation

differ considerably.

While in change detection schemes only the last stimulus would be relevant for the

current response, an adaptation model depends on the past stimulus sequence. Similarly to

adaptation, the stimulus history also plays an important role in the generation of a model of the

world under a prediction account. However, while prediction is an active process that is directed

in the future, adaptation is often seen as more passive (Näätänen et al., 2005). It is important to

note that both adaptation and prediction can be reconciled in the predictive processing

framework (Garrido et al., 2009b, 2009a; O'Shea, 2015). From this point of view, adaptation

could be considered a more low-level predictive process that contributes through synaptic

changes to the precision, while higher-level processes evidenced by prediction errors define the

flow of information between cortical areas (Garrido et al., 2009b, 2009a). Thus from this unified

perspective, observing adaptation or prediction as a mechanism in MMN generation does give

important insights on the level and complexity of processing.

Computational modeling offers a unique way to investigate the underlying mechanisms

by comparing predictors stemming from different models with single-trial ERP estimates

(Stefanics et al., 2016). In aware conditions, computational modeling approaches underscored

predictive processing as a promising mechanism during deviance processing across sensory

modalities (Lieder et al., 2013; Mars et al., 2008; Ostwald et al., 2012; Stefanics et al., 2018;

Weber et al., 2020). Unfortunately, until now most studies restricted their model space to two

or three models excluding e.g. adaptation (Mars et al., 2008; Ostwald et al., 2012; Stefanics et

al., 2018; Weber et al., 2020). However, there is evidence that under some conditions, e.g.

during sleep or at low levels in the cortical hierarchy, MMN responses can at least partly be

explained by adaptation (Ishishita et al., 2019; Parras et al., 2017; Strauss et al., 2015). Thus,

while evidence for adaptive processes during deviance detection has been found, it is unknown

whether and how experimental conditions, such as task relevance and awareness of stimuli alter

the dominant mechanism at play during MMN generation.

The current study addressed these questions by investigating models underlying visual

MMN under different task conditions including unawareness. One shortcoming of conventional

'blinding' techniques is to confound awareness of a stimulus with reporting it (Aru et al., 2012;

Tsuchiya et al., 2015). In order to address this issue, participants completed a visual

inattentional blindness (IB) paradigm (Pitts et al., 2012), drawing on the phenomenon that

otherwise perceivable stimuli remain undetected if participants perform a distractor task and

are uninformed about them (Hutchinson, 2019; Mack, 2003). This procedure allows

disentangling effects of awareness and task relevance on the MMN by avoiding a trial-by-trial

awareness report (Schlossmacher et al., 2020). In order to investigate how task conditions

influence mechanisms of mismatch generation, we compared different computational models

of single-trial amplitudes in the MMN time window during three experimental conditions ((A)

unaware, (B) aware: task-irrelevant, (C) aware: task-relevant). It has been shown that MMN

can be elicited during unawareness (Bekinschtein et al., 2009; Faugeras et al., 2012; Koelsch et

al., 2006; Strauss et al., 2015) and that MMN as well as related components like the N1 and

N2b are enhanced by attention (Auksztulewicz and Friston, 2015; Näätänen et al., 2011;

Sussman et al., 2003; Sussman, 2007). Based on these findings, we expect to observe a deviance

related response in all experimental conditions caused by both low-level adaptation and high-

level prediction to varying degrees. We expect that mechanisms in unaware and task-irrelevant

conditions rely on lower-level mechanisms like adaptation ,i.e. low-level predictions, while in

the task-relevant condition higher-level predictions are better suited than passive adaptation to

explain deviance processing. Consequently, we propose that the relative explanatory power of

predictive processing increases from unaware and task-irrelevant conditions to the task-relevant

condition.

2. Methods

2.1. Participants

The sample consisted of 31 participants (9 male) aged from 18 to 35 years ($M = 23.60$,

$SD = 4.02$). All had normal or corrected-to-normal vision and were right-handed. Participants

volunteered and were compensated with 9 € per hour. Before starting, participants were given

written instructions on the experimental task and given the opportunity to ask further questions.

The study was approved by the local ethics committee and all procedures were carried out in

accordance with the Helsinki declaration.

2.2. Apparatus

The experiment was run using MATLAB and the Psychophysics Toolbox (Brainard,

1997; Kleiner et al., 2007; Pelli, 1997). A G-Master GB2488HSU monitor at 60 Hz with a

resolution of 1920 × 1080 pixels was employed for stimulus display. The viewing distance

amounted to 60 cm. To respond, participants pressed the space bar and numeric keys of a

standard keyboard. A chin rest was used to prevent head movements during the experiment.

2.3. Experimental procedure and stimulus material

Unawareness of stimuli was achieved by using an inattentional blindness paradigm

(Mack, 2003; Pitts et al., 2012; Schlossmacher et al., 2020; Shafto and Pitts, 2015). In the

current design, participants were presented with shapes embedded in an array of white lines

presented in the background while the foreground consisted of a circling red dots that

occasionally decreased in luminance. The experimental procedure included three conditions:

(A) participants were either uninformed about the shapes and focused on the foreground task

(unaware), or (B) were informed about the shapes but still focused on the foreground task

(aware, task-irrelevant), or (C) focused on the shapes (aware, task-relevant).

Stimuli consisted of a 20 × 20 grid of white lines with a width of 0.45 degrees of visual

angle (°) each, spanning 10° × 10° in total and were presented on a black background (L_{white} =

0.35 cd/m^2, L_{black} = 327.43 cd/m^2; background stimuli, see Figure 1A). Line orientation was

chosen at random for each of the 400 lines comprised in the grid, i.e., a random pattern of lines

was used for every presentation. Shapes were constructed by orienting lines vertically and

horizontally to form a square and two rectangles centrally in the grid using 12 × 12, 8 × 16, and

16 × 8 lines, while all other lines were kept random (background stimuli, see Figure 1A). Each

shape remained 100 ms on the screen followed by a random pattern presented for 700 ms, after

which the next shape was presented. At all times, a red fixation cross of 0.9° × 0.9° was

presented centrally. Concurrently, 12 red dots were presented on three circular paths (four on

each circle) with a radius of 2.5°, 4.5°, and 6.5°, respectively (foreground stimuli; see Figure

1A for a stationary image of the dots). The dots, with radii of 0.32°, 0.41°, and 0.52°, rotated

with a constant angular velocity of 1.05 radians/s. On average, every 43 s (jitter: ± 0–10 s) a

randomly chosen dot slightly decreased in luminance for 500 ms (from L = 47.99 cd/m^2 to L =

16.30 cd/m^2; [204, 0, 0] to [114.75, 0, 0] in RGB). The rotation direction changed every 24 s

on average from clockwise to counterclockwise and vice versa (jitter: ± 0–10 s). Onsets of color

and rotation changes were further pseudorandomized in such a way that they never coincided

with a shape onset.

Shapes were presented in a standard oddball design. The standard stimulus was

presented in 80% of the cases and the deviant in 20%. Stimulus presentation was further

pseudorandomized that at least one standard stimulus was presented after each deviant.

Horizontal and vertical rectangles served as deviant and standard and were counterbalanced

across participants. On 22 randomly selected trials the shape presented was a square that served

Figure 1. Experimental setup. (A) Example stimuli. The red dots in the foreground circled around the fixation cross and served as the task in phase A and B. In the background of the top picture a horizontal rectangle is formed out of the white line segments, in the bottom picture all lines are random. (B) Schematic of the standard oddball paradigm. Note that for the conventional analysis the standard was always the stimulus before the deviant. ISI = inter-stimulus-interval.

as a target in phase C. In total, 1000 stimuli were presented during each phase. The run-time of

one phase amounted to 13.33 minutes (excluding breaks).

For all three experimental phases, the stimulus presentation was physically identical,

while the task differed. In phase A and B, participants were instructed to press the space bar

whenever they detected a luminance decrease in one of the dots. In phase C, participants' task

was to detect the squares. In phase A, participants were uninformed about the presence of the

background stimuli. The difficulty of the task was designed to elicit IB in almost all of the

participants. In phase B, the task was held constant, but all participants were informed about

the presence of the shapes. In phase C, awareness was held constant, but participants completed

a new task, which directed their attention to the shapes. Phase A was followed by either phase

B or phase C counterbalanced across participants. In order to accustom participants to the tasks,

phase A and phase C comprised a brief practice session in which the task difficulty was

gradually increased in three steps. In phase A, the target color started with an easy-to-spot

difference while only random patterns were presented until the target color used in the main

experiment was reached. In phase C, the duration of shapes started with a slower presentation

of 300 ms and accelerated until the shape duration of the main experiment of 100 ms was

reached. For an overview of the experimental procedure, see Table 1.

After completing each experimental phase, participants were given a questionnaire,

asking whether or not they perceived the shapes and to describe or sketch what they saw as detailed as possible. Then, participants were asked to rate nine different shapes made of line segments (including the three shapes shown during the experiment) on how confident they were of having seen the shape (confidence rating) and how often they saw the shape (frequency rating) on a 5-point scale. The awareness questionnaire and ratings relied on Pitts and colleagues (2012) as displayed in their appendix.

Table 1

Overview of the experimental procedure

Phase	Task	Shapes task-relevant
A	detect dot color	no
Awareness assessment & confidence/frequency ratings		
B	detect dot color	no
Awareness assessment & confidence/frequency ratings		
C	detect squares	yes
Awareness assessment & confidence/frequency ratings		

Note: Half of the participants completed the phases in the order ABC and the other half in the order ACB.

2.4. EEG recording and preprocessing

A 128-channel BioSemi active electrode system (BioSemi B.V., Amsterdam, Netherlands) was employed to collect electrophysiological data. Electrodes were placed using the equiradial system conforming with BioSemi electrode caps. Furthermore, vertical and horizontal eye movements were recorded with two electrodes attached above and below the left eye (VEOG) and two electrodes attached to the right and left outer canthi (HEOG). Instead of ground and reference, the BioSemi EEG system uses a CMS/DRL feedback loop with two additional electrodes (for more information see: http://www.biosemi.com/faq/cms&drl.htm). Electrical potentials were recorded with a sampling rate of 512 Hz and impedances were held below 20 kΩ. A build-in analog anti-aliasing low-pass filter of 104 Hz was applied prior to digitization.

Preprocessing of the EEG data was performed using the FieldTrip toolbox (Oostenveld

et al., 2010) in MATLAB. Offline filtering of the continuous data employed Butterworth filters

with half-power cut-offs if not specified otherwise. Data were band-stop filtered at 49–51 Hz

(roll-off: –24 dB/octave) and harmonic frequencies (up to 199–201 Hz) in order to minimize

line noise. Additionally, a 59-61 Hz band-stop filter accounting for the monitor refresh rate (60

Hz) was applied. A 0.1 Hz high-pass filter (roll-off: –12 dB/octave) removed slow drifts. Then,

the EEG signal was segmented into epochs of 200 ms before until 600 ms after stimulus onset.

Trials containing eye blinks, muscle artifacts, and electrode jumps were manually removed

based on visual inspection and bad channels were interpolated. Data were re-referenced from

the CMS/DRL to a common average reference. All trials were baseline-adjusted using the

average of a prestimulus interval from –200 to 0 ms.

For the oddball contrasts, trials of each subject were averaged separately for deviants

and standards. We used the standard stimuli prior to deviants for the standard average allowing

us to average equal amounts of stimuli per condition. This resulted in six waveforms

(deviant/standard in three phases) per participant. Furthermore, deviant and standard

waveforms were averaged across phases. Lastly, grand mean waveforms of the averaged data

were computed.

2.5. Statistical analysis

To test for the vMMN, statistical analysis employed a cluster-based permutation test

(Groppe et al., 2011; Maris and Oostenveld, 2007). In order to enhance its power, we chose a

time interval from 150 ms to 350 ms in posterior electrodes (Stefanics et al., 2014; see Figure

2). Hypotheses were directional, leading to a one-sided cluster-based permutation test. Clusters

were formed by two or more neighboring sensors (in time and space) whenever the t-values

exceeded the cluster threshold ($\alpha = .05$). The cluster mass, sum(t), was calculated by adding all

t-values within a cluster. The number of permutations was set to 5000, and the significance

value for testing the null hypothesis amounted to $\alpha = .05$. Prior to the analysis, ERPs were

down-sampled to 250 Hz and low-pass filtered at 25 Hz (roll-off: –24 dB/octave) to further

enhance statistical power (Luck, 2005). In order to quantify effect sizes of the significant

clusters, we averaged Cohen's *d* for each electrode and time point. After applying the cluster-

based permutation approach, cluster averages from significant clusters were computed and used

in the orthogonal planned comparisons.

Task performance was quantified as *d'* and reaction times of correct responses using the

method for paradigms with high event rates introduced by Bendixen and Andersen (2013). This

approach allows computing a false alarm rate for a continuous task with no clear distractor

events. Thus, we evaluated false alarms relative to the number of non-target time intervals of

the same length as the 2-seconds response interval for hits (Bendixen and Andersen, 2013). In

order to probe conscious shape perception we subtracted confidence ratings for shapes included

in the main experiment (hereinafter referred to as 'shown') from ratings for shapes not included

in the main experiment ('not shown'). In order to probe conscious perception of the oddball

sequence we subtracted frequency ratings of the deviant from the standard. Rating scores, RT,

d' and cluster averages were analyzed using repeated-measures ANOVAs and *t*-tests.

Whenever sphericity was violated, the Greenhouse-Geisser correction was applied and

corrected *p*-values as well as $\hat{\varepsilon}$-values are reported below. As some of our conclusions rely on

null effects, we additionally report Bayes Factors (BF), with BF_{01} denoting the evidence for the

null hypothesis and BF_{10} the evidence for the alternative hypothesis. Bayesian analysis relied

on the R package *BayesFactor* (Morey et al., 2018), which uses a Cauchy prior scaled with $r =$

$\frac{\sqrt{2}}{2}$ as default. We use the conventions from Jeffreys (1961) to interpret the results, that is we

considered a BF > 3 as substantial evidence for either hypothesis. The cluster-based

permutation was done using the FieldTrip toolbox (Oostenveld et al., 2010) in MATLAB. Other

statistical tests relied on the statistics program R (R Core Team, 2015).

2.6. Computational modeling approach

We based our computational modeling approach on Lieder et al. (2013), who used

individual single-trial estimates of the MMN and compared several different computational

models like adaptation, change detection, and predictive processing accounts. However, we

chose a different approach for model selection, first comparing all models with an intercept-

only null model and then comparing the winning model with all other models. Furthermore, in

order to account for the fitting of parameters in some of our models, we chose a 2-fold cross-

validation approach with 100 repetitions (Berrar, 2019). This entailed using 50% of artifact-

free single-trial vMMN estimates during the fitting procedure and using the remaining 50% to

test the model fit.

Individual single-trial amplitudes were extracted using the results of the cluster-based

permutation. Electrodes included in the significant vMMN cluster were averaged and an

individual difference wave was computed for each participant and phase. Then, the largest

negative peak of the difference wave during the time window of the significant cluster (150 –

350 ms) was determined. Last, single-trial estimates (y) were computed as the average

amplitude ± 25 ms around the peak. Only artifact-free trials were used for the single-trial

analysis.

We derived the single-trial trajectories of our predictors corresponding to four different

alternative models, namely (1) categorical oddball, (2) change detection, (3) adaptation, and (4)

precision-weighted prediction error. The categorical oddball predictor (CO) was always 1 if the

stimulus was an oddball, and 0 otherwise:

$$x_i = \begin{cases} 1, if\ s_i = deviant \\ 0, if\ s_i = standard \end{cases}$$ (3)

With x_i representing the predictor value in trial i, and s_i representing the stimulus type in trial

i. We included this predictor in order to validate the findings of our classical ERP analysis as it

most closely mimics the averaging procedure. The change detection predictor (CD) was 1 if the

stimulus was different from the one before, and 0 otherwise, thus standards after deviants were

also coded as changes:

$$x_i = \begin{cases} 1, if \ s_i \neq s_{i-1} \\ 0, if \ s_i = s_{i-1} \end{cases} \quad (4)$$

286 The adaptation predictor (A) was derived after Lieder et al. (2013). In this model, the response

287 to a stimulus decays and recovers exponentially as a function of the previous stimulus sequence.

$$x_{i,s} = \begin{cases} x_{i-1} \exp\left(-\frac{1}{\tau_{adapt}}\right), \ if \ s_i = s_{i-1} \\ 1 - (1 - x_{i-1}) \exp\left(-\frac{1}{\tau_{recover}}\right), \ else \end{cases} \quad (5)$$

Where for each stimulus s_i (here deviant and standard) a time course $x_{i,s}$ representing the decay

and recovery of the neuronal population was computed. The predictor x_i used in the final model

only included the values for the stimulus shown in the experimental sequence. The additional

parameters τ_{adapt} and $\tau_{recover}$ representing the rate of decay/recovery were fitted to the data using

a quasi-newton optimisation algorithm implemented in *fminunc* in Matlab. We substituted

values of tau that did not lie in the plausible range [0.1-200] (Lieder et al., 2013; Ulanovsky et

al., 2004) with values closest to the fitted τ. We minimized the negative log-likelihood,

including a parameter accounting for the observation noise similar to the HGF (see below). The

precision-weighted prediction error predictor (pwPE) was derived using the freely available

HGF toolbox (Mathys, 2011; Stefanics et al., 2018; Weber et al., 2020), which can be

downloaded from http://www.translationalneuromodeling.org/tapas. The model builds on a

process similar to Rescorla-Wagner models of reinforcement learning (Rescorla and Wagner,

1972) of the form:

$$prediction_i = prediction_{i-1} + learning \ rate \ \times \ prediction \ error \quad (6)$$

303 Where the prediction error is weighted by a learning rate, solving this for the pwPE gives

$$x_i = pwPE = prediction_i - prediction_{i-1} \quad (7)$$

Furthermore, a hierarchical process is assumed with levels modeled as Gaussian random walks;

for a description of the mathematical details of this model please refer to Mathys (2011). Here,

we used the absolute second level pwPE corresponding to beliefs about the stimulus probability

(Mathys, 2011) which has been shown to be relevant in mismatch processing (Stefanics et al.,

2018; Weber et al., 2020). We used the HGF function *tapas_fitModel* supplied with a

configuration files relying on *tapas_hgf_binary_config, tapas_gaussian_obs* and

tapas_quasinewton_optim_config (TAPAS release 3.2/HGF version 5.3). In the configuration

of the perceptual model, we diverged from the defaults in the following parameters. Following

Stefanics et al. (2018), we fitted a two-level HGF by setting the parameter κ_2 to zero, thereby

neglecting the environmental volatility as the oddball sequence in our experiment was highly

stable. Furthermore, we changed the starting value of ω which we decreased from -3 to -6 as

recommended by the HGF in order to not violate model assumptions while deriving the

trajectories (ω = -6 (var = 16)). All other parameters were left at their respective defaults,

namely $\mu_2^{(0)}$ = 0 (var = 0), $\sigma_2^{(0)}$ = 0.1 (var = 0), $\mu_3^{(0)}$ = 1 (var = 0), $\sigma_3^{(0)}$ = 1 (var = 0), ϑ = -6 (var

= 0), κ_1 = 1. Importantly, this entailed that the initial value corresponding to the belief about

the stimulus probability was set to a neutral point ($\mu_2^{(0)}$ = 0, i.e. both outcomes have the same

probability). For our observation model, we used *tapas_gaussian_obs* for continuous responses

as a basis, but fitted the single-trial EEG estimates to the absolute second level pwPE leaving

only ω as a free parameter. In order to accommodate the range of the single-trial estimates we

set ζ = 4.19 corresponding to the standard deviation of single-trial amplitudes derived by using

the procedure described above on the data reported in Schlossmacher et al. (2020). This

procedure allowed the HGF to fit the pwPE with an appropriate decay similar to the parameters

of the adaptation model.

All predictors were estimated based on the complete trial sequence (i.e., all deviants and

standard stimuli); however, the parameter estimation for the adaptation and pwPE model did

only take 50% of artifact-free trials into account. The remaining trials were used in the model

comparison step described in the following. Using a similar approach to Mars et al. (2008),

models were estimated by means of a two-level hierarchical general linear model with a random

intercept and constant slope on the group level of the form

$$y = X^{(1)}\theta^{(1)} + \epsilon^{(1)}, \tag{1}$$

$$\theta^{(1)} = \epsilon^{(2)}. \tag{2}$$

With y representing the concatenated single-trial estimates of all participants, $X^{(1)}$ the design matrix, $\theta^{(1)}$ the regression parameters, and ϵ a random error. The design matrix $X^{(1)}$ has $p + 1$ columns and t rows, with p being the number of participants and t being the length of the data vector y. $X^{(1)}_{i,j}$ is equal to 1 if data i is from participant j and $X^{(1)}_{\cdot,p+1}$ is equal to the predictor values of the tested mechanism (see below). $\theta^{(1)}$ is of the length $p + 1$, with the first p components representing the random intercepts for each participant j and $\theta^{(1)}_{p+1}$ representing the regression slope. Thus, we computed one model for each phase and potential mechanism that included the data of all participants. We specifically wanted to implement a constant slope to ensure that the effects have the 'right' direction, i.e., a negative sign of the slope (in the current study a higher pwPE value associated with a lower single-trial amplitude consistent with the MMN).

The null model consisted only of the random intercept (i.e. $X^{(1)}_{\cdot,p+1}$ was omitted), while the alternative models additionally included predictors representing different mechanisms of mismatch generation. We computed the null model and four alternative models using the R package *lme4* (Bates et al., 2015). We compared the models using the Akaike information criterion (AIC). First, we computed $\Delta AIC = AIC_{null} - AIC_i$ to compare alternative models to the null model for each random test set. Then, we compared the model with the lowest AIC, i.e., the winning model, to all other models to test whether it explained the data substantially better ($\Delta AIC = AIC_i - AIC_{min}$). In a last step, we averaged ΔAIC values to estimate model fit across all test sets and computed 95% confidence intervals. Interpretation of ΔAIC relied on the convention proposed by Burnham and Anderson (2004) with differences > 2 indicating substantial support for the model with the lower AIC.

2.7. Data and code availability statement

Data and code have been made available on the Open Science Framework accessible via

https://osf.io/bjna4/.

3. Results

Six participants reported awareness of the shapes during phase A and were thus excluded from the analysis. With regard to the remaining 25 participants, on average, 19.41% (SD = 9.80%) of trials were excluded from the analysis due to artifacts, and on average, 0.64 (SD = 1.00) electrodes were interpolated.

3.1. Behavioral Data

3.1.1. Task performance

Task performance quantified by d' did differ between phases ($F(2,48) = 5.28$, $p = .02$, $\hat{\varepsilon} = .70$, $BF_{10} = 6.52$) with significant better performance in phase B and C compared to phase A (all $p < 0.01$, all $BF_{10} > 6.06$), see Table 2. Comparing phase B and C, d' did not differ ($t(24) = -0.92$, $p = .37$, $BF_{01} = 3.25$). Reaction times did differ significantly between phases ($F(2,48) = 28.42$, $p < .001$, $\hat{\varepsilon} = .81$, $BF_{10} = 3.12 \times 10^7$) with faster reaction times in phase C compared to both phase A and B (all $p < .001$, all $BF_{10} > 7.90 \times 10^4$), while no difference was observed between phase A and B ($t(24) = 0.50$, $p = .62$, $BF_{01} = 4.24$), see Table 2.

Table 2

Behavioral data: Performance and ratings

	performance		ratings	
Phase	d'	RT	confidence	frequency
A	2.30 (0.87)	867 (141)	-0.02 (0.64)	-0.20 (0.82)
B	2.72 (0.88)	849 (120)	2.09 (0.91)	0.40 (0.76)
C	2.94 (0.71)	663 (63)	2.49 (0.80)	0.20 (0.50)

Note: Reaction time (RT) measured in ms. Mean rating score differences for confidence (shown – not shown) and frequency (standard – deviant) ratings. Standard deviations are provided in parentheses.

3.1.2. Confidence and frequency ratings.

Repeated-measures ANOVA of rating differences (shown – not shown) indicated a

significant main effect of phase for confidence ($F(2,48) = 84.59$, $p < .001$, $\hat{\varepsilon} = .73$, $BF_{10} =$

8.30×10^{16}), see Table 2. Participants could significantly better differentiate shown and not

shown shapes in phase C compared to phase B and in phase B and C compared to phase A (all

$p < .01$, all $BF_{10} > 7.76$).

In the frequency rating differences (standard – deviant) a significant main effect of phase

was found ($F(2,48) = 5.42$, $p = .008$, $BF_{10} = 9.38$), see Table 2. Participants could significantly

better differentiate the frequency of standard and deviant shapes in phase C and B compared to

phase A (all $p < .05$, all $BF_{10} > 1.94$), while no significant difference was observed between

Figure 2. Electrophysiological measures of deviance processing. (A) VMMN effect averaged over all three phases. Black electrodes and the time interval marked by dashed lines were included in the cluster-based permutation test. Significant clusters comprised the electrodes marked as bold and the time interval marked by the light yellow box. The shaded area around ERP waveforms depicts the 95%-bootstrap confidence interval. (B) Cluster averages of vMMN in phases A, B, and C. (C) Waveforms and topographies in phases A, B and C. Error bars depict standard error of the mean.

phase B and C ($t(24) = 1.22$, $p = .23$, $BF_{01} = 2.43$).

Importantly, *t*-tests in phase A showed no significant difference from zero for

confidence ($t(24) = -0.16$, $p = .88$, $BF_{01} = 4.69$) indicating that 'blind' participants could not

differentiate shown and not shown shapes. Additionally, frequency ratings did also indicate no

significant difference from zero in phase A, indicating that participants were unaware of the

oddball structure of the stimuli ($t(24) = -1.22$, $p = .23$, $BF_{01} = 2.43$).

3.2. EEG Data

3.2.1. Electrophysiological measures of deviance processing

Averaged over all phases a significant vMMN effect was found (maximal cluster:

$\text{sum}(t) = -3081.19$, $p < .001$, $d = -0.54$). This vMMN effect included the electrodes marked in

the right panel of Figure 2A and lasted from 150 to 350 ms. To further substantiate that vMMN

was indeed present in all phases we tested the cluster averages against zero in each phase. In

phase A ($t(24) = -2.25$, $p = .02$, $BF_{10} = 3.39$), B ($t(24) = -2.03$, $p = .03$, $BF_{10} = 2.35$) and C ($t(24)$

$= -3.71$, $p < .001$, $BF_{10} = 64.81$) a significant effect was observed, see Figure 2B. Furthermore,

a repeated measures ANOVA with the factor phase did not indicate a significant difference in

vMMN ($F(2,48) = 1.68$, $p = .20$, $BF_{01} = 1.69$). Testing cluster averages of the vMMN did not

reveal any effects of phase order in phases B ($t(23) = 0.58$, $p = .57$, $BF_{01} = 2.35$) and C ($t(23) =$

0.25, $p = .80$, $BF_{01} = 2.63$).

3.2.2. Computational modeling results

We computed the single-trial estimates in the vMMN time window around the

individual peak of each participant (phase A, M = 245.31 ms, SD = 59.46 ms, min = 156.25,

max = 347.66; phase B, M = 280.94 ms, SD = 61.11 ms, min = 160.16, max = 347.66; phase

C, M = 262.19 ms, SD = 54.75 ms, min = 167.97, max = 347.66). Estimated averaged θ values

for all modeled mechanisms were negative in all phases, indicating the higher the predictor the

more negative the single-trial amplitude.

In phase A, the single-trial vMMN estimates were substantially better explained by the

412 categorical oddball, precision-weighted prediction error, and adaptation model as compared to

413 the null model (all $\Delta AIC > 2$, see Figure 3B). Further, we obtained substantially more evidence

414 for the adaptation model compared to all other models (ΔAIC_{pwPE-A} = 6.15, 95% confidence

415 interval [5.32 6.98], ΔAIC_{CD-A} = 16.78 [15.75 17.79], ΔAIC_{CO-A} = 10.06 [9.16 10.95]). In phase

416 B, again, the categorical oddball, precision-weighted prediction error, and the adaptation model

417 were substantially better than the null model (all $\Delta AIC > 2$, see Figure 3B). Adaptation was the

418 best model, further evidenced by substantially more evidence for this model compared to all

419 other models (ΔAIC_{pwPE-A} = 6.15 [5.32 6.98], ΔAIC_{CD-A} = 16.78 [15.75 17.79], ΔAIC_{CO-A} =

420 10.06 [9.16 10.95]). In phase C, all four alternative models were substantially better than the

421 null model (all $\Delta AIC > 2$, see Figure 3B). The precision-weighted prediction error was the best

422 model, further evidenced by it being substantially better than all the other models (ΔAIC_{A-pwPE}

423 = 6.15 [5.32 6.98], $\Delta AIC_{CD-pwPE}$ = 16.78 [15.75 17.79], $\Delta AIC_{CO-pwPE}$ = 10.06 [9.16 10.95]).

424 Fitted values of ω, τ_{adapt} and $\tau_{recover}$ did not differ significantly between phases (all *ps*

425 > .05, all $BF_{10} < 3$) with the exception of $\tau_{recover}$ which was smaller in phase C compared to

426 phase A ($t(24) = 3.83$, $p < .001$, $BF_{10} = 41.89$) and B ($t(24) = 4.94$, $p < .001$, $BF_{10} = 511.33$).

427 Furthermore, we tested whether phase order influences the mechanisms by including it as a

428 factor with an interaction term in the models of phases B and C. Models including phase order

429 did not perform substantially better compared to their respective models without phase order

430 effects (all $\Delta AIC_{without-with} < 2$).

Figure 3. Example predictors and computational modeling results. (A) Example of single-trial predictors for one participant. The first 100 trials are depicted. (B) Alternative models compared to the null model in phase A, B and C using average ΔAIC. The bold line marks a ΔAIC of 2 which indicates substantial evidence for the alternative model after Burnham and Anderson (2004). Error bars represent 95% confidence intervals. pwPE = precision-weighted prediction error, A = adaptation, CD = change detection, CO = categorical oddball.

4. Discussion

In the present study, we investigated the influence of awareness and task relevance on

computational models of deviance processing during the visual MMN time window.

Experimental manipulations had the intended effects: Participants were engaged in the tasks in

all phases as evidenced by the task performance; inattentional blindness was successfully

elicited in uninformed participants; we observed a vMMN in all phases. This finding agrees

with the notion that the vMMN is a pre-attentive component that is elicited automatically.

Interestingly, a recent study found no vMMN to low-level visual features like orientation or

contrast (Male et al., 2020). In the light of this research, the vMMN observed here was probably

elicited by deviance in shapes that required some form of contour integration (Hess et al., 2003)

and thus more than low-level feature processing.

The predominant mechanism behind the vMMN did differ depending on experimental

conditions: When stimuli were task-irrelevant, both in unaware and aware conditions,

adaptation was identified as the main mechanism, while when stimuli were aware and task-

relevant vMMN resembled most closely a precision-weighted prediction error. Thus, there is

not only one predominant mechanism behind neuronal deviance processing but the relative

contribution of mechanisms differs dependent on task settings. Thus, using MMN terminology

(Kimura et al., 2009), we observed a 'genuine' MMN in the task-relevant condition while in

the nonconscious and task-irrelevant condition deviance signals were mainly caused by

refractoriness. Furthermore, we found that task relevance decreased the parameter indicating

recovery from adaptation that. However, as adaptation represented only the third best model

during task relevance, these results should be interpreted with caution.

In line with previous research, we found that vMMN was best explained by a prediction

error (Lieder et al., 2013; Stefanics et al., 2018; Weber et al., 2020). However, this did only

hold true in our task-relevant condition. Interestingly, two of these studies investigated MMN

(Stefanics et al., 2018; Weber et al., 2020) during a task setting similar to our phase B, where

we observed adaptation and not predictive processing. Since they did not include adaptation in

their model space, a direct comparison of studies is not possible. Lieder et al. (2013) found

MMN to be better explained by prediction than by adaptation in a passive auditory oddball

design with a simultaneous visual task, which allows only weak control for the role of

attentional focus. Another difference lies in the modality under investigation, which might have

influenced results.

Our findings that unaware and distracting conditions are stronger related to adaptation

as main mechanism of MMN generation fits some previous findings where mismatch

processing on lower levels of the hierarchy (Ishishita et al., 2019; Parras et al., 2017) or during

sleep (Strauss et al., 2015) has been shown to resemble adaptation. On the other hand, predictive

processing was found on higher levels of the neuronal hierarchy and during wakefulness (Parras

et al., 2017; Strauss et al., 2015). Thus, while both adaptation and prediction contribute to MMN

their relative weight changes under specific contextual settings and depending on the

hierarchical processing level similar to our findings. Besides, it has been shown that early

vMMN responses can be explained by adaptive processes, while later portions seem to rely on

memory-dependent comparison processes (Czigler et al., 2002; Kimura et al., 2009). The

observed increase of predictive activity in our task-relevant phase can also be related to studies

investigating effects of attention on MMN. While long considered a pre-attentive component

(Näätänen et al., 2001; Sussman et al., 2014), there have been studies showing a general

enhanced MMN for attended stimuli (Auksztulewicz and Friston, 2015; Sussman et al., 2003,

2014; Sussman, 2007; Woldorff et al., 1991); a finding that – while not statistically significant

– can also be seen descriptively in our phase C. Furthermore, additional components like the

N1 and the N2b have been found to be significantly enhanced in attended compared to

unattended conditions (Näätänen et al., 2011) which might reflect increased predictive activity.

This ties nicely into the observation of Auksztulewicz and Friston (2015) who found that

attention is linked to enhanced top-down precision of sensory signals consistent with the

predictive processing framework.

Importantly, we could show that awareness per se does not automatically elicit a

dominant prediction error signal. These results are highly relevant for studies investigating

MMN effects during sleep, under anesthesia, or in patients with disorders of consciousness

(Bekinschtein et al., 2009; Faugeras et al., 2012; Koelsch et al., 2006; Strauss et al., 2015). In

these studies, the MMN might be best explained by adaptive processes and not by predictive

ones. This would fit with the observation by Strauss and colleagues (2015) who, despite

observing a MMN during sleep, found that predictive processing was disrupted. Taking this up,

the current results have important implications for the "Bayesian brain hypothesis". From this

point of view, the hierarchical comparison process eliciting prediction errors should be

observable on all levels throughout the brain (Clark, 2013; Stefanics et al., 2014). Here,

however, we found MMN to most closely resemble adaptation during unawareness and task

irrelevance, while a dominant prediction error account required at least a specific amount of

attentional processing of stimuli. Thus, a prediction error might not be the best model under all

circumstances. Our data suggest a combination of adaptive and predictive accounts to explain

the MMN shaped by attentional conditions. The more relevant the oddball stimuli the stronger

is the relative contribution of predictive processes for the generation of the MMN.

As briefly sketched in the introduction, we would like to note that adaptation does not

necessarily contradict the predictive brain but might be a way to accomplish it on a mechanistic

level. From this point of view plastic changes in synaptic activity (i.e. adaptive processes) can

be seen as a way of how the brain encodes the precision of prediction errors during predictive

processing (Garrido et al., 2009a, 2009b). Adaptation can be linked to postsynaptic changes in

intrinsic connections i.e. within a cortical region, while model adjustment would be mediated

via extrinsic connections (Garrido et al., 2009a). Thus, adaptation might be considered a more

low-level predictive process related to precision that takes place within a cortical area while

higher-level processes evidenced by prediction errors allow more flexibility through extrinsic

connections. This line of argument supposes that predictive processing should be observed in

addition to adaptation, which was the case in the current study where both adaptation and

prediction were substantially better compared to a null model in all conditions. Furthermore, it

seems plausible that under conditions of unawareness and task irrelevance less extrinsic

network activity and thus more adaptation is observed as has been the case in the current study.

Lastly, it is important to point out possible limitations of our study. First, inattentional

blindness studies have the advantage of controlling for task relevance and awareness, but the

disadvantage that only delayed reports of awareness can be used. This opens the question

whether IB participants really experience blindness or rather inattentional amnesia, i.e.,

perceiving stimuli but swiftly forgetting them (Lamme, 2006; Wolfe, 1999). While we cannot

completely rule out this possibility, one study addressing this issue found that the inability to

report stimuli during IB stems from a perceptual deficit, not from memory failure (Ward and

Scholl, 2015). Furthermore, the experimental setup with three consecutive phases did not allow

a full counterbalancing of phase order, as the IB paradigm always has to begin with an

uninformed phase to prevent conscious perception of the critical stimuli. Thus, as phase A was

always the first phase, this could have potentially influenced the mechanisms observed in the

following phases. However, in the light of the current findings this seems not to have been a

large problem, as we observed the same mechanism in phases A and B, but different ones

between phase B and C, which were counterbalanced in their order. We used a standard oddball

paradigm with a rare deviant and frequent standard stimulus, which has been criticized as

physical stimulus features are entangled with expectedness. While we did counterbalance the

deviant across participants, a roving oddball paradigm (Baldeweg et al., 2004; Cowan et al.,

1993) or appropriate control conditions (Ruhnau et al., 2012; Schröger and Wolff, 1996; Wiens

et al., 2019) could alleviate this issue. The experimental tasks did manipulate attention in

different ways (i.e. paying attention to distributed dots vs. paying attention to a central shape)

which could potentially influenced our results. Consequently, substantiating the current

findings by using different types of awareness and task manipulations as well as different

oddball paradigms would be desirable.

Second, while we tried to best capture the different candidate mechanisms for MMN

there might be different models that could also be included in the model space. Nevertheless,

we tested four different models against a null model being able to cover the two most prominent

candidates namely adaptation and prediction. Furthermore, we only modeled a monotonic

relationship between predictors and EEG estimates. In addition, we used a random-intercept

with a constant slope in our model comparison. While this allowed controlling the direction of

the slope, not taking into account random effects on the level of the model might make the

model comparison vulnerable to outliers (Stephan et al., 2009). Refined models taking into

account interindividual variability and more complex coupling between EEG and predictors

might be even more appropriate.

Third, we derived single-trial amplitudes individually for each participant by extracting

the average amplitude around the negative peak of the difference wave. While this procedure

has the advantage of specifically targeting time points relevant for mismatch processing, it

might also result in different processes being covered in different participants. While individual

feature selection is common in single-trial computational modeling studies (Lieder et al., 2013;

Mars et al., 2008), other approaches taking all electrodes and time points into account would

also be informative (Ostwald et al., 2012; Stefanics et al., 2018; Weber et al., 2020).

Furthermore, we only focused on the vMMN time window and did not take into account other

effects elicited during oddball paradigms, like the P3 (Polich, 2007; Verleger, 2020). The P3

has been shown to be strongly modulated by task relevance, but not by awareness (Pitts et al.,

2012; Schlossmacher et al., 2020; Shafto and Pitts, 2015). As we were especially interested in

how mechanisms of mismatch processing vary under different task conditions, we did not

investigate the P3, which we did only expect to be elicited in our task-relevant phase

(Schlossmacher et al., 2020). However, investigating in what way mechanisms of mismatch

vary in this later time window depending on different task conditions including the question of

whether or not the oddball is a target stimulus seems promising in future studies.

5. Conclusion

564   In summary, this EEG study investigated specific neurocomputational models of

565   mismatch generation depending on task relevance and awareness of stimuli. A vMMN was

observed in all experimental conditions. However, single-trial computational modeling showed that the adaptation model provided the best evidence in unaware and task-irrelevant conditions while a precision-weighted prediction error was the best model during task relevance. This suggests that deviance processing does not rely on either adaptation or prediction alone, but is generated by both processes whose relative contributions are dependent on task settings.

6. Acknowledgements

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors. The authors declare no competing financial interests. We thank Marvin Jehn, Carolin Balloff, and Leona Rautenbach for their assistance in data collection.

References

Alho, K., Sams, M., Paavilainen, P., Reinikainen, K., Näätänen, R., 1989. Event-Related Brain Potentials Reflecting Processing of Relevant and Irrelevant Stimuli During Selective Listening. Psychophysiology 26, 514–528. https://doi.org/10.1111/j.1469-8986.1989.tb00704.x

Aru, J., Bachmann, T., Singer, W., Melloni, L., 2012. Distilling the neural correlates of consciousness. Neuroscience & Biobehavioral Reviews 36, 737–746. https://doi.org/10.1016/j.neubiorev.2011.12.003

Auksztulewicz, R., Friston, K., 2015. Attentional Enhancement of Auditory Mismatch Responses: a DCM/MEG Study. Cereb Cortex 25, 4273–4283. https://doi.org/10.1093/cercor/bhu323

Baldeweg, T., Klugman, A., Gruzelier, J., Hirsch, S.R., 2004. Mismatch negativity potentials and cognitive impairment in schizophrenia. Schizophrenia Research 69, 203–217. https://doi.org/10.1016/j.schres.2003.09.009

Bates, D., Mächler, M., Bolker, B., Walker, S., 2015. Fitting Linear Mixed-Effects Models Using lme4. Journal of Statistical Software 67, 1–48. https://doi.org/10.18637/jss.v067.i01

Bekinschtein, T.A., Dehaene, S., Rohaut, B., Tadel, F., Cohen, L., Naccache, L., 2009. Neural signature of the conscious processing of auditory regularities. PNAS 106, 1672–1677. https://doi.org/10.1073/pnas.0809667106

Bendixen, A., Andersen, S.K., 2013. Measuring target detection performance in paradigms with high event rates. Clinical Neurophysiology 124, 928–940. https://doi.org/10.1016/j.clinph.2012.11.012

Berrar, D., 2019. Cross-Validation, in: Ranganathan, S., Gribskov, M., Nakai, K., Schönbach, C. (Eds.), Encyclopedia of Bioinformatics and Computational Biology. Academic Press, Oxford, pp. 542–545. https://doi.org/10.1016/B978-0-12-809633-8.20349-X

Brainard, D.H., 1997. The Psychophysics Toolbox. Spatial vision 10, 433–6. https://doi.org/10.1163/156856897X00357

Burnham, K.P., Anderson, D.R., 2004. Multimodel Inference: Understanding AIC and BIC in Model Selection. Sociological Methods & Research 33, 261–304. https://doi.org/10.1177/0049124104268644

Clark, A., 2013. Whatever next? Predictive brains, situated agents, and the future of cognitive science. Behavioral and Brain Sciences 36, 181–204. https://doi.org/10.1017/S0140525X12000477

Cowan, N., Winkler, I., Teder, W., Näätänen, R., 1993. Memory prerequisites of mismatch negativity in the auditory event-related potential (ERP). Journal of Experimental Psychology: Learning, Memory, and Cognition 19, 909–921. https://doi.org/10.1037/0278-7393.19.4.909

Czigler, I., Balázs, L., Winkler, I., 2002. Memory-based detection of task-irrelevant visual changes. Psychophysiology 39, 869–873. https://doi.org/10.1017/S0048577202020218

Faugeras, F., Rohaut, B., Weiss, N., Bekinschtein, T., Galanaud, D., Puybasset, L., Bolgert, F., Sergent, C., Cohen, L., Dehaene, S., Naccache, L., 2012. Event related potentials elicited by violations of auditory regularities in patients with impaired consciousness. Neuropsychologia 50, 403–418. https://doi.org/10.1016/j.neuropsychologia.2011.12.015

Friston, K., 2005. A theory of cortical responses. Philosophical Transactions of the Royal Society B: Biological Sciences 360, 815–836. https://doi.org/10.1098/rstb.2005.1622

Garrido, M.I., Kilner, J.M., Kiebel, S.J., Stephan, K.E., Baldeweg, T., Friston, K.J., 2009a.
Repetition suppression and plasticity in the human brain. NeuroImage 48, 269–279.
https://doi.org/10.1016/j.neuroimage.2009.06.034
Garrido, M.I., Kilner, J.M., Stephan, K.E., Friston, K.J., 2009b. The mismatch negativity: A
review of underlying mechanisms. Clinical Neurophysiology 120, 453–463.
https://doi.org/10.1016/j.clinph.2008.11.029
Groppe, D.M., Urbach, T.P., Kutas, M., 2011. Mass univariate analysis of event-related brain
potentials/fields I: A critical tutorial review. Psychophysiology 48, 1711–1725.
https://doi.org/10.1111/j.1469-8986.2011.01273.x
Hess, R.F., Hayes, A., Field, D.J., 2003. Contour integration and cortical processing. Journal
of Physiology-Paris, Neurogeometry and visual perception 97, 105–119.
https://doi.org/10.1016/j.jphysparis.2003.09.013
Hutchinson, B.T., 2019. Toward a theory of consciousness: A review of the neural correlates
of inattentional blindness. Neuroscience & Biobehavioral Reviews 104, 87–99.
https://doi.org/10.1016/j.neubiorev.2019.06.003
Ishishita, Y., Kunii, N., Shimada, S., Ibayashi, K., Tada, M., Kirihara, K., Kawai, K., Uka, T.,
Kasai, K., Saito, N., 2019. Deviance detection is the dominant component of auditory
contextual processing in the lateral superior temporal gyrus: A human ECoG study.
Human Brain Mapping 40, 1184–1194. https://doi.org/10.1002/hbm.24438
Jääskeläinen, I.P., Ahveninen, J., Bonmassar, G., Dale, A.M., Ilmoniemi, R.J., Levänen, S.,
Lin, F.-H., May, P., Melcher, J., Stufflebeam, S., Tiitinen, H., Belliveau, J.W., 2004.
Human posterior auditory cortex gates novel sounds to consciousness. PNAS 101,
6809–6814. https://doi.org/10.1073/pnas.0303760101
Jack, B.N., Widmann, A., O'Shea, R.P., Schröger, E., Roeber, U., 2017. Brain activity from
stimuli that are not perceived: Visual mismatch negativity during binocular rivalry
suppression. Psychophysiol 54, 755–763. https://doi.org/10.1111/psyp.12831
Jeffreys, H., 1961. Theory of Probability. UK Oxford University Press, Oxford.
Kimura, M., Katayama, J., Ohira, H., Schröger, E., 2009. Visual mismatch negativity: New
evidence from the equiprobable paradigm. Psychophysiology 46, 402–409.
https://doi.org/10.1111/j.1469-8986.2008.00767.x
Kleiner, M., Brainard, D.H., Pelli, D.G., 2007. What's new in Psychtoolbox-3?, in:
Perception. Presented at the 30th European Conference on Visual Perception, Arezzo,
Italy, p. 14.
Koelsch, S., Heinke, W., Sammler, D., Olthoff, D., 2006. Auditory processing during deep
propofol sedation and recovery from unconsciousness. Clinical Neurophysiology 117,
1746–1759. https://doi.org/10.1016/j.clinph.2006.05.009
Kuldkepp, N., Kreegipuu, K., Raidvee, A., Näätänen, R., Allik, J., 2013. Unattended and
attended visual change detection of motion as indexed by event-related potentials and
its behavioral correlates. Frontiers in Human Neuroscience 7.
https://doi.org/10.3389/fnhum.2013.00476
Lamme, V.A.F., 2006. Towards a true neural stance on consciousness. Trends in Cognitive
Sciences 10, 494–501. https://doi.org/10.1016/j.tics.2006.09.001
Lieder, F., Daunizeau, J., Garrido, M.I., Friston, K.J., Stephan, K.E., 2013. Modelling Trial-
by-Trial Changes in the Mismatch Negativity. PLoS Computational Biology 9,
e1002911. https://doi.org/10.1371/journal.pcbi.1002911
Luck, S.J., 2005. An introduction to the event-related potential technique. MIT Press,
Cambridge Mass.
Mack, A., 2003. Inattentional Blindness Looking Without Seeing. Current Directions in
Psychological Science 12, 180–184. https://doi.org/10.1111/1467-8721.01256
Male, A.G., O'Shea, R.P., Schröger, E., Müller, D., Roeber, U., Widmann, A., 2020. The
quest for the genuine visual mismatch negativity (vMMN): Event-related potential

indications of deviance detection for low-level visual features. Psychophysiology 57, e13576. https://doi.org/10.1111/psyp.13576

Maris, E., Oostenveld, R., 2007. Nonparametric statistical testing of EEG- and MEG-data. J. Neurosci. Methods 164, 177–190. https://doi.org/10.1016/j.jneumeth.2007.03.024

Mars, R.B., Debener, S., Gladwin, T.E., Harrison, L.M., Haggard, P., Rothwell, J.C., Bestmann, S., 2008. Trial-by-Trial Fluctuations in the Event-Related Electroencephalogram Reflect Dynamic Changes in the Degree of Surprise. J. Neurosci. 28, 12539–12545. https://doi.org/10.1523/JNEUROSCI.2925-08.2008

Mathys, C., 2011. A Bayesian foundation for individual learning under uncertainty. Frontiers in Human Neuroscience 5. https://doi.org/10.3389/fnhum.2011.00039

May, P.J.C., Tiitinen, H., 2010. Mismatch negativity (MMN), the deviance-elicited auditory deflection, explained. Psychophysiology 47, 66–122. https://doi.org/10.1111/j.1469-8986.2009.00856.x

Morey, R.D., Rouder, J.N., Jamil, T., Urbanek, S., Forner, K., Ly, A., 2018. BayesFactor: Computation of Bayes Factors for Common Designs.

Näätänen, R., 1992. Attention and Brain Function. Psychology Press.

Näätänen, R., Gaillard, A.W.K., Mäntysalo, S., 1978. Early selective-attention effect on evoked potential reinterpreted. Acta Psychologica 42, 313–329. https://doi.org/10.1016/0001-6918(78)90006-9

Näätänen, R., Jacobsen, T., Winkler, I., 2005. Memory-based or afferent processes in mismatch negativity (MMN): A review of the evidence. Psychophysiology 42, 25–32. https://doi.org/10.1111/j.1469-8986.2005.00256.x

Näätänen, R., Kujala, T., Winkler, I., 2011. Auditory processing that leads to conscious perception: A unique window to central auditory processing opened by the mismatch negativity and related responses. Psychophysiology 48, 4–22. https://doi.org/10.1111/j.1469-8986.2010.01114.x

Näätänen, R., Tervaniemi, M., Sussman, E.S., Paavilainen, P., Winkler, I., 2001. 'Primitive intelligence' in the auditory cortex. Trends in Neurosciences 24, 283–288. https://doi.org/10.1016/S0166-2236(00)01790-2

Oostenveld, R., Fries, P., Maris, E., Schoffelen, J.-M., 2010. FieldTrip: Open source software for advanced analysis of MEG, EEG, and invasive electrophysiological data. Computational Intelligence and Neuroscience 2011. https://doi.org/10.1155/2011/156869

O'Shea, R.P., 2015. Refractoriness about adaptation. Front Hum Neurosci 9. https://doi.org/10.3389/fnhum.2015.00038

Ostwald, D., Spitzer, B., Guggenmos, M., Schmidt, T.T., Kiebel, S.J., Blankenburg, F., 2012. Evidence for neural encoding of Bayesian surprise in human somatosensation. NeuroImage 62, 177–188. https://doi.org/10.1016/j.neuroimage.2012.04.050

Parras, G.G., Nieto-Diego, J., Carbajal, G.V., Valdés-Baizabal, C., Escera, C., Malmierca, M.S., 2017. Neurons along the auditory pathway exhibit a hierarchical organization of prediction error. Nature Communications 8, 2148. https://doi.org/10.1038/s41467-017-02038-6

Pelli, D.G., 1997. The VideoToolbox software for visual psychophysics: transforming numbers into movies. Spatial vision 10, 437–42.

Pitts, M.A., Martínez, A., Hillyard, S.A., 2012. Visual Processing of Contour Patterns under Conditions of Inattentional Blindness. Journal of Cognitive Neuroscience 24, 287–303. https://doi.org/10.1162/jocn_a_00111

Polich, J., 2007. Updating P300: An integrative theory of P3a and P3b. Clinical Neurophysiology 118, 2128–2148. https://doi.org/10.1016/j.clinph.2007.04.019

R Core Team, 2015. R: A language and environment for statistical computing (Version 3.1.2). R Foundation for Statistical Computing: Vienna, Austria.

Rescorla, R.A., Wagner, A.R., 1972. A Theory of Pavlovian Conditioning: Variations in the Effectiveness of Reinforcement and Nonreinforcement, in: Black, A., Prokasy, W. (Eds.), Classical Conditioning II: Current Research and Theory. Appleton-Century-Crofts, New York, NY, pp. 64–99.

Ruhnau, P., Herrmann, B., Schröger, E., 2012. Finding the right control: The mismatch negativity under investigation. Clinical Neurophysiology 123, 507–512. https://doi.org/10.1016/j.clinph.2011.07.035

Schlossmacher, I., Dellert, T., Pitts, M., Bruchmann, M., Straube, T., 2020. Differential effects of awareness and task relevance on early and late ERPs in a no-report visual oddball paradigm. J. Neurosci. 40, 2906–2913. https://doi.org/10.1523/JNEUROSCI.2077-19.2020

Schröger, E., Winkler, I., 1995. Presentation rate and magnitude of stimulus deviance effects on human pre-attentive change detection. Neuroscience Letters 193, 185–188. https://doi.org/10.1016/0304-3940(95)11696-T

Schröger, E., Wolff, C., 1996. Mismatch response of the human brain to changes in sound location. NeuroReport 7, 3005–3008.

Shafto, J.P., Pitts, M.A., 2015. Neural Signatures of Conscious Face Perception in an Inattentional Blindness Paradigm. Journal of Neuroscience 35, 10940–10948. https://doi.org/10.1523/JNEUROSCI.0145-15.2015

Stefanics, G., Heinzle, J., Horváth, A.A., Stephan, K.E., 2018. Visual Mismatch and Predictive Coding: A Computational Single-Trial ERP Study. J. Neurosci. 38, 4020–4030. https://doi.org/10.1523/JNEUROSCI.3365-17.2018

Stefanics, G., Kremláček, J., Czigler, I., 2016. Mismatch negativity and neural adaptation: Two sides of the same coin. Response: Commentary: Visual mismatch negativity: a predictive coding view. Front Hum Neurosci 10. https://doi.org/10.3389/fnhum.2016.00013

Stefanics, G., Kremláček, J., Czigler, I., 2014. Visual mismatch negativity: a predictive coding view. Front. Hum. Neurosci 8, 666. https://doi.org/10.3389/fnhum.2014.00666

Stephan, K.E., Penny, W.D., Daunizeau, J., Moran, R.J., Friston, K.J., 2009. Bayesian model selection for group studies. NeuroImage 46, 1004–1017. https://doi.org/10.1016/j.neuroimage.2009.03.025

Strauss, M., Sitt, J.D., King, J.-R., Elbaz, M., Azizi, L., Buiatti, M., Naccache, L., Wassenhove, V. van, Dehaene, S., 2015. Disruption of hierarchical predictive coding during sleep. PNAS 112, E1353–E1362. https://doi.org/10.1073/pnas.1501026112

Sussman, E., Winkler, I., Wang, W., 2003. MMN and attention: Competition for deviance detection. Psychophysiology 40, 430–435. https://doi.org/10.1111/1469-8986.00045

Sussman, E.S., 2007. A New View on the MMN and Attention Debate. Journal of Psychophysiology 21, 164–175. https://doi.org/10.1027/0269-8803.21.34.164

Sussman, E.S., Chen, S., Sussman-Fort, J., Dinces, E., 2014. The Five Myths of MMN: Redefining How to Use MMN in Basic and Clinical Research. Brain Topogr 27, 553–564. https://doi.org/10.1007/s10548-013-0326-6

Tsuchiya, N., Wilke, M., Frässle, S., Lamme, V.A.F., 2015. No-Report Paradigms: Extracting the True Neural Correlates of Consciousness. Trends in Cognitive Sciences 19, 757–770. https://doi.org/10.1016/j.tics.2015.10.002

Ulanovsky, N., Las, L., Farkas, D., Nelken, I., 2004. Multiple Time Scales of Adaptation in Auditory Cortex Neurons. J. Neurosci. 24, 10440–10453. https://doi.org/10.1523/JNEUROSCI.1905-04.2004

Verleger, R., 2020. Effects of relevance and response frequency on P3b amplitudes: Review of findings and comparison of hypotheses about the process reflected by P3b. Psychophysiology 57, e13542. https://doi.org/10.1111/psyp.13542

Ward, E.J., Scholl, B.J., 2015. Inattentional blindness reflects limitations on perception, not
memory: Evidence from repeated failures of awareness. Psychon Bull Rev 22, 722–
727. https://doi.org/10.3758/s13423-014-0745-8
Weber, L.A., Diaconescu, A.O., Mathys, C., Schmidt, A., Kometer, M., Vollenweider, F.,
Stephan, K.E., 2020. Ketamine Affects Prediction Errors about Statistical Regularities:
A Computational Single-Trial Analysis of the Mismatch Negativity. J. Neurosci. 40,
5658–5668. https://doi.org/10.1523/JNEUROSCI.3069-19.2020
Wiens, S., Szychowska, M., Eklund, R., Berlekom, E. van, 2019. Cascade and no-repetition
rules are comparable controls for the auditory frequency mismatch negativity in
oddball tasks. Psychophysiology 56, e13280. https://doi.org/10.1111/psyp.13280
Winkler, I., Czigler, I., 2012. Evidence from auditory and visual event-related potential (ERP)
studies of deviance detection (MMN and vMMN) linking predictive coding theories
and perceptual object representations. International Journal of Psychophysiology,
Predictive information processing in the brain: Principles, neural mechanisms and
models 83, 132–143. https://doi.org/10.1016/j.ijpsycho.2011.10.001
Winkler, I., Czigler, I., 1998. Mismatch negativity: deviance detection or the maintenance of
the 'standard.' NeuroReport 9, 3809.
Winkler, I., Karmos, G., Näätänen, R., 1996. Adaptive modeling of the unattended acoustic
environment reflected in the mismatch negativity event-related potential. Brain
Research 742, 239–252. https://doi.org/10.1016/S0006-8993(96)01008-6
Woldorff, M.G., Hackley, S.A., Hillyard, S.A., 1991. The Effects of Channel-Selective
Attention on the Mismatch Negativity Wave Elicited by Deviant Tones.
Psychophysiology 28, 30–42. https://doi.org/10.1111/j.1469-8986.1991.tb03384.x
Wolfe, J.M., 1999. Inattentional amnesia. Fleeting memories 17.
800
801