Crowdsourced identification of multi-target kinase inhibitors for RET- and TAU-

based disease: the Multi-Targeting Drug DREAM Challenge

Short title: Crowdsourced identification of multi-target kinase inhibitors

Authors: Zhaoping Xiong*, Minji Jeon*, Robert J Allaway*, Jaewoo Kang, Donghyeon

Park, Jinhyuk Lee, Hwisang Jeon, Miyoung Ko, Hualiang Jiang, Minyue Zheng, Aik

Choon Tan, Xindi Guo, The Multi-Targeting Drug DREAM Challenge Community,

Kristen K Dang, Alex Tropsha, Chana Hecht, Tirtha K. Das, Heather A. Carlson, Ruben

Abagyan, Justin Guinney, Avner Schlessinger§, Ross Cagan§

*co-first authors

§corresponding authors

Affiliations:

RJA, JG, XG, NS, KKD: Sage Bionetworks, Seattle, WA

MJ, JK, DP, JL, MK: Department of Computer Science and Engineering, Korea

University, Seoul, Republic of Korea

JK, HJ: Interdisciplinary Graduate Program in Bioinformatics, Korea University, Seoul,

Republic of Korea

ACT: Department of Biostatistics and Bioinformatics, Moffitt Cancer Center, Tampa, FL,

USA

ZX: Shanghai Institute for Advanced Immunochemical Studies, ShanghaiTech

University, Shanghai 200031, China

HJ, MZ: Drug Discovery and Design Center, State Key Laboratory of Drug Research,

Shanghai Institute of Materia Medica, Chinese Academy of Sciences, 555 Zuchongzhi

Road, Shanghai 201203, China

AT: Laboratory for Molecular Modeling, Division of Chemical Biology and Medicinal

Chemistry, UNC Eshelman School of Pharmacy, University of North Carolina, Chapel

Hill, NC, USA.

HAC: Department of Medicinal Chemistry, University of Michigan, Ann Arbor, MI, USA

RA: Skaggs School of Pharmacy and Pharmaceutical Sciences, UC San Diego, San

Diego, CA, USA

AS, Department of Pharmacological Sciences, Icahn School of Medicine at Mount Sinai,

New York, NY, USA. avner.schlessinger@mssm.edu

CH, TD, RC: Department of Cell, Developmental, and Regenerative Biology, Icahn

School of Medicine at Mount Sinai, New York, NY, USA

RC: Corresponding author. Contact information: Institute of Cancer Sciences, University

of Glasgow; Garscube Estate, Switchback Road, Bearsden, Glasgow Scotland G61

ross.cagan@glasgow.ac.uk

Abstract

A continuing challenge in modern medicine is the identification of safer and more

efficacious drugs. Precision therapeutics, which have one molecular target, have been

long promised to be safer and more effective than traditional therapies. This approach

has proven to be challenging for multiple reasons including lack of efficacy, rapidly

acquired drug resistance, and narrow patient eligibility criteria. An alternative approach

is the development of drugs that address the overall disease network by targeting

multiple biological targets ('polypharmacology'). Rational development of these

molecules will require improved methods for predicting single chemical structures that

target multiple drug targets. To address this need, we developed the Multi-Targeting

Drug DREAM Challenge, in which we challenged participants to predict single chemical

entities that target pro-targets but avoid anti-targets for two unrelated diseases: RET-

based tumors and a common form of inherited Tauopathy. Here, we report the results of

this DREAM Challenge and the development of two neural network-based machine

learning approaches that were applied to the challenge of rational polypharmacology.

Together, these platforms provide a potentially useful first step towards developing lead

therapeutic compounds that address disease complexity through rational

polypharmacology.

Author Summary

Many modern drugs are developed with the goal of modulating a single cellular pathway

or target. However, many drugs are, in fact, 'dirty;' they target multiple cellular pathways

or targets. This phenomenon is known as multi-targeting or polypharmacology. While

some strive to develop 'cleaner' therapeutics that eliminate secondary targets, recent

work has shown that multi-targeting therapeutics have key advantages for a variety of

diseases. However, while multi-targeting drugs that affect a precisely-defined profile of

targets may be more effective, it is difficult to computationally predict which molecules

have desirable target profiles. Here, we report the results of a competitive

crowdsourcing project (the Multi-Targeting Drug DREAM Challenge), where we

challenged participants to predict chemicals that have desired target profiles for cancer

and neurodegenerative disease.

Introduction

Despite important advances in drug development, many diseases remain partly or

wholly resistant to drug-based treatments. In recent decades, the field has attempted to

address this by developing precision therapeutics with the goal of targeting critical

nodes in disease networks. However, this approach has proven to be challenging. Most

targeted therapeutics do not progress past preclinical research or clinical trials due to

poor efficacy or unacceptable toxicity [1,2]. Additional hurdles are encountered even

after clinical approval. For example, initial efficacy against melanoma by the BRAF

inhibitors dabrafenib or vemurafenib as single-agent therapeutics is generally followed

by emergent tumor resistance [3]. Further, based on biomarkers only a small number of

patients with metastatic tumors are eligible for these target-driven precision therapies,

and fewer still show sustained response [4].

An alternative to developing drugs with single targets is the development of

polypharmacology (multi-targeting) drugs. Many clinically approved drugs bind multiple

targets (http://ruben.ucsd.edu/dnet) [5,6], and in some cases the drug is improved by

these secondary activities. For example, vandetanib, a drug used in RET-dependent

medullary thyroid cancer (MTC), has a broad range of kinase targets that include RET,

VEGFR, etc. [7]; pre-clinical studies suggest that some of these secondary targets can

contribute to drug efficacy (*e.g.*, [8,9]). Developing optimized polypharmacology-based

drugs remains a challenge, however, as there are few roadmaps for predicting

structures that combine beneficial targets ('pro-targets') while avoiding liabilities ('anti-

targets') in a single molecule.

Current approaches to predict multi-target compounds range from 'physics-based'

methods that directly predict binding affinities, to 'omics-based' approaches utilizing

large datasets such as those including side-effects or gene expression profiles [10–14].

Notably, recent advances in machine learning architectures have allowed the

development of more effective methods relying on both physics-based and omics-based

approaches [15,16]. For example, a generative tensorial reinforcement learning

(GENTRL) model was used to design a small-molecule with optimal biological activity

for the discoidin domain receptor 1 (DDR1) with desirable pharmacokinetic properties in

just 21 days [17]. However, several limitations remain: current methods often (i) identify

frequent binders or obvious compounds, (ii) fail to discriminate activities among close

analogs, or (iii) identify small molecule inhibitors of 'promiscuous kinases' (e.g., DDR1

[18]) that are inherently easier to target. Notably, exploration of the full chemical

space—estimated between 10^{24} and 10^{60} structures—still remains a tremendous

challenge: known binders of, *e.g.*, the kinome together address a limited set of chemical

scaffolds [19].

Rational polypharmacology will require an improved ability to predict chemical

structures that specifically target optimized target sets. To identify better computational

strategies for this problem, we developed the Multi-Targeting Drug DREAM Challenge

[20]. In this challenge, we challenged participants to predict single chemical entities that

target pro-targets but avoid anti-targets for two unrelated diseases: RET-based tumors

and an inherited form of Tauopathy. Exploring each disease, we used a Drosophila

'dominant genetic modifier screen' to identify mediators of Drosophila RET^{M955T}-

mediated transformation and of Tau-mediated dysfunction [21,22]. The resulting

functional suppressors and enhancers of RET transformation provide a 'roadmap' for

the ideal profile of a lead polypharmacological therapeutic.

These data provide therapeutic roadmaps of suppressors (candidate 'pro-targets')

and enhancers (candidate 'anti-targets') for RET- and TAU-based disease. We publicly

posted this data, challenging the community to develop computational approaches with

improved ability to predict single chemical structures that successfully inhibit pro-targets

while avoiding anti-targets. Here, we report the development of two artificial neural

network-based machine learning approaches that were applied to the challenge of

rational polypharmacology. Together, these platforms provide a potentially useful first

step towards developing lead therapeutic compounds that address disease complexity

through polypharmacology.

Results

Rational development of drugs that act through polypharmacology will require identifying (i) pro-targets that, as a group, are predicted to be effective in addressing a disease network, and (ii) anti-targets that are predicted to act as liabilities either due to reduced disease efficacy or increased whole body toxicity. Our work in Drosophila [21–27] identified whole body pro-targets and anti-targets for RET-associated cancer and Tauopathy. To leverage this data, we established the Multi-targeting Drug DREAM challenge (www.doi.org/10.7303/syn8404040) designed to promote and assess novel rational approaches to polypharmacology (Figure 1).

Figure 1 - Multi-targeting drug DREAM Challenge overview. This challenge sought to identify new algorithms for the identification of multi-targeting drugs that bind disease-relevant targets and avoid disease-specific anti-targets. Participating teams used a broad array of different datasets and computational approaches to develop these methods. They were then asked to use these methods to predict small molecules that would bind to RET-driven cancer targets and anti-targets (Problem 1, P1) as well as Tauopathy targets and ant-targets (Problem 2, P2). A shortlist of these predicted molecules were then experimentally validated (Kd determination) as binders or non-binders of P1 and P2 proteins. Finally, the submitted compounds were scored using a combination of criteria including selectivity, novelty, patentability, and drug-like properties to identify the top performing teams.

Pro-targets and anti-targets

To ensure whole animal relevance, we used data from two Drosophila models. To

model RET-dependent oncogenic transformation, we used data from previous work that

screened Drosophila *GMR-RET^{M955T}* and *ptc>RET^{M955T}* cancer models [21,22]. Broad

genetic screening identified multiple key 'pro-targets' defined as 'dominant genetic

suppressors' of *GMR-RET^{M955T}*-mediated transformation including Drosophila orthologs

of BRAF, SRC, and S6K. Candidate 'anti-targets'—genetic loci that, when reduced,

acted as 'dominant genetic enhancers' of *RET^{M955T}*-mediated transformation—include

MKNK1, TTK, ERK8, PDK1, and PAK3. Given its central role, we also included RET as

a pro-target.

To provide a second independent test for compound predictions, we used data

recently generated in a screen of a previously-described inherited Drosophila

Tauopathy model [23–27]. Expressing the human disease isoform TAU^{R406W}

exogenously in a transgenic Drosophila line led to nervous system defects and animal

lethality [23–27]. Genetic screening of most of the Drosophila kinome identified several

dominant genetic suppressors of TAU^{R406W}. For example, reducing the activity of the

Drosophila orthologs of AURKA, PAK1, FGFR1, or STK11 suppressed TAU^{R406W}-

mediated fly lethality; these loci represent candidate therapeutic targets. Conversely,

reducing activity of PAK3, MAP3K7, or PIK3CA enhanced TAU^{R406W}-mediated lethality

(*unpublished data*), indicating they should be avoided by candidate therapeutics.

We used these two sets of data as benchmarks for computation-based compound

predictions: ideal therapeutic leads would inhibit most or all pro-targets while exhibiting

minimum activity against anti-targets.

Participation and Performance

The challenge had 190 registered participants. Of these registrants, 34 submitted

predictions, either as a part of one of 5 teams or as individuals. 10 prediction sets were

submitted for Problem 1, and 8 prediction sets were submitted for Problem 2. Each

prediction was scored using the rubric described in Table 1 (see Methods for additional

details).

Criteria	Points Awarded
Problem 1	
Binds RET[M918T)]	5
Binds BRAF, SRC, S6K	1, 3 or 9 if binding 1, 2 or 3 of these targets
Avoids MKNK1*	3
Avoids TTK, ERK8, PDK, PAK3	1, 2, 3, or 4 if it avoids 1, 2, 3, or 4 of these targets
Problem 2	
Binds AURKA*	5
Binds PAK1*	5
Binds FGFR1, LKB	1 or 3 if binding 1 or 2 of these targets
Avoids PAK3*	3
Avoids MAP3K7*	3
Avoids PIK3CA	1
Predicted to enter CNS	3
Both Problems	
Novelty	2
Ability to Patent	2
Drug-like molecule	3

Table 1 - Scoring guidelines for Problems 1 and 2. *Starred targets indicate that*

binding or avoiding that target was a requirement to receive target-based points.

Problem 1: Prediction of multi-targeting compounds for RET-driven cancers

Problem 1 asked participants to predict molecules that bound the RET^{M955T}-
associated cancer pro-targets RET[M918T], BRAF, SRC, S6K, and did not bind the
anti-targets MKNK1, TTK, ERK8, PDK1, and PAK3. Of the 10 prediction files submitted,
two of the predictions had the same top-ranked molecule and, therefore, 9 compounds
were selected by the challenge organizers for experimental evaluation. Supplemental
Figure 1A shows that while most of the submitted compounds had no similar molecule
submitted by another team (Tanimoto similarity >0.5), the few similar submitted
molecules were mostly predicted by the same method/team.

Binding evaluation revealed that the majority of predicted compounds (7/9) did not
bind any of the pro-targets at 10 µM or any of the anti-targets at 30 µM (Supplemental
Table 1). Two compounds were observed to significantly bind one or more pro-targets:
ZINC98209221 and ZINC40900273 (Figure 2, Table 2). ZINC98209221 was observed
to significantly bind all 4 pro-targets, while avoiding 2 of the 5 anti-targets. Of the
remaining 3 'bound' anti-targets, the K_d was larger than that of the pro-targets,
indicating that ZINC98209221 displayed a lower binding affinity for the Problem 1 anti-
targets as compared to the pro-targets. The other compound in Table 2,
ZINC40900273, only significantly bound one of 4 pro-targets (BRAF) but avoided all 5
anti-targets.

Submitter or Team	Chemical ID	Structure	InChIKey
Zhaoping Xiong	ZINC98209221		SMPGEBOIKULBCT-UHFFFAOYSA-N
DMIS_MTD	ZINC98209221		SMPGEBOIKULBCT-UHFFFAOYSA-N
UM-BISBII	ZINC40900273		KUQAFPIBXZKZON-UHFFFAOYSA-N

Table 2 - Compounds with activity against the Problem 1 targets. *"Submitter or*

Team" indicates the team that identified the compound as a solution to Problem 1.

"Chemical ID" is the ZINC identifier for the molecule. "Structure" is a two-dimensional

representation of the molecule. "InChIKey" is the hashed InChI for the molecule.

Strikingly, two teams identified the same molecule as a solution for Problem 1.

Figure 2 - Kd values of experimentally tested candidates from Problem 1. *A*

heatmap indicating the K_ds of all compounds tested in Problem 1. The best binder of the

pro-targets (ZINC98209221) was predicted by two different teams.

Problem 2: Prediction of multi-targeting compounds for Tauopathy

Problem 2 asked participants to predict compounds that bind the Tauopathy pro-

targets AURKA, PAK1, FGFR1, and STK11 and avoid the Tauopathy anti-targets PAK3,

MAP3K7, and PIK3CA. Eight compounds were selected for experimental testing.

Kinase binding assays indicated that 6 of 8 of the predicted compounds did not bind any

of the pro-targets or anti-targets at 30 µM (Supplemental Table 2). Two compounds

were observed to bind one or more pro-targets: ZINC3938668 and ZINC538658 (Figure

3, Table 3). Supplemental Figure 1B recapitulates the finding from Problem 1 in

Problem 2 - most of the submitted compounds had no similar molecule submitted

(Tanimoto similarity >0.5) and when similar molecules were submitted, they were

generally predicted within a single method and not across different teams.

Submitter or Team	Chemical ID	Structure	InChIKey
Zhaoping Xiong	ZINC3938668		OYONTEXKYJZFHA-SSHUPFPWSA-N
DMIS_MTD	ZINC18279871		LDEWQRSYYHTQRA-UHFFFAOYSA-N

Table 3 - Compounds with activity against the Problem 2 targets. *"Submitter or*

Team" indicates the team that identified the compound as a solution to Problem 2.

"Chemical ID" is the ZINC identifier for the molecule. "Structure" is a two-dimensional

representation of the molecule. "InChIKey" is the hashed InChI for the molecule.

Figure 3 - Kd values of experimentally tested candidates from Problem 2. *A*

heatmap indicating the K_ds of all compounds tested in Problem 1. ZINC3938668 and

ZINC538658 bind a subset of the pro-targets, and also both bind 2 of the three anti-

targets.

The molecule predicted by Zhaoping Xiong, ZINC3938668, bound 3 of 4 pro-targets

at 10 µM: AURKA, PAK1, and STK11. However, this molecule also bound 2 of 3 anti-

targets at 10 µM: PAK3 and MAP3K7. Similarly, the predicted molecule from team

DMIS-MTD, ZINC538658, bound 3 of 4 pro-targets at 10 µM: AURKA, FGFR1, and

STK11, and 2 of 3 anti-targets at 10 µM: PAK3 and MAP3K7.

Overall performance and methods summaries

To identify the top participants, we used the scoring algorithm described in Table 1.

This algorithm considered multiple factors including binding of targets and avoiding anti-

targets as well as fulfilling novelty, patentability, and drug-likeness criteria to derive a

numerical score. The top teams for both Problem 1 and Problem 2 were identical:

Zhaoping Xiong and DMIS_MTD, with 16 points each for Problem 1, and 11 and 9

points for Problem 2, respectively (Table 4). The remaining teams received points for

novelty, patentability, and drug-likeness criteria, but the compounds predicted by these

teams failed to meet binding criteria to receive points. Therefore overall top-performers

for the challenge were Zhaoping Xiong and DMIS_MTD, with overall scores of 28 and

25, respectively (Table 4).

Submitter or Team	Problem 1	Problem 2	Interactome	Final Points
Zhaoping Xiong	16	11	TRUE	28
DMIS_MTD	16	9	FALSE	25
Lasige-BioISI - Multi-target Drug Designing	7	7	TRUE	15
SuperModels	7	7	FALSE	14
Huiyuan Chen	7	7	FALSE	14
Masahiro Mochizuki	7	7	FALSE	14
David Koes	7	7	FALSE	14
Gregory Koytiger	7	7	FALSE	14
UM-BISBII	8		FALSE	8
Stratified	7		FALSE	7

Table 4 - Challenge scoreboard. *"Submitter or Team" indicates which team was*

scored. The "Problem 1" and "Problem 2" scores indicate each team's performance in

the two problems as scored using the criteria described in Table 1. "Interactome"

indicates whether the team participated in a text-mining exercise to facilitate team

interaction for bonus points. "Final Points" indicates the final score for each team.

Across the 10 participating teams a variety of approaches were employed to arrive

at a set of predicted compounds for Problems 1 and 2 (Table 5 and Supplemental

Methods). The majority of these methods utilized multiple steps including (i) combining

structure- and ligand-based approaches, (ii) applying one or more machine

learning/classification algorithms, (iii) use of other computational approaches such as

filtering, ligand docking, or creation and application of confidence scoring metrics to

identify compounds for the two problems, or (iv) manual selection of the top candidates.

Importantly, some teams used fully automated methods, while others used approaches

that required several manual curation steps. While the majority of teams utilized one or

more machine learning approaches, the two top-performing teams specifically relied on

neural network-based approaches to identify the best compounds for Problem 1 and 2

(Table 2 & 3). We therefore examined these two approaches more closely to identify

key similarities and differences.

Team	Computational Approach Used	Manual Selection of Top Candidates	Method Data Description
David Koes	neural network	yes	PDB
Team Stratified	ensemble gradient boosting	yes	pIC50
DMIS-MTD	neural network	yes	Cmap scores
UM-BISBII	dataset filtering		SEA-TC algorithm
Lasige-BioISI - Multi-target Drug Designing	random forest, support vector machine	yes	ChEMBL
Gregory Koytiger	neural network		ChEMBL, SwissProt
SuperModels	random forest, logistic regression	yes	ChEMBL, Klaeger et al, Eidogen, ExCAPE-DB
Zhaoping Xiong	neural network	yes	Merget and Fulle et al, Uniprot
Masahiro Mochizuki	random forest, logistic regression		unspecified kinase inhibition assay dataset
Huiyuan Chen	similarity calculations		Drugbank

Table 5 - Methods summary table. *"Computational Approach Used" describes the*

methods that were mentioned in each team's writeup (see Supplemental Methods).

"Manual Selection of Top Candidates" indicates whether a team described using a

manual curation step to produce their final set of predicted compounds. "Method Data

Description" highlights the data sources and data types used by each team.

Top performing teams

The two teams that were most effective at predicting binding of pro-targets and

avoidance of anti-targets both used artificial neural network approaches. Method 1

(Zhaoping Xiong) used features derived from the protein and small molecules. Method 2

(Team DMIS_MTD) relied on transcriptional responses in combination with chemical

features of the drug, with a post processing step that included docking.

Method 1 used a graph convolutional neural network deep learning approach

[28,29] to predict candidate bioactive compounds (Figure 4). Ligand-based models are

constrained when testing is done with just a few bioactive compounds. To build a more

generalizable and useful model, this approach incorporated key features of each target

kinase by converting the amino acid sequence into a 'word embedding' vector, then

trained together with graph convolutional neural fingerprints. In developing this method,

different combinations were used of extended connectivity fingerprints (ECFP4) of

compounds with known bioactivity data, neural fingerprints, and protein embeddings.

Testing on a 10% internal hold-out test set demonstrated that the combination of neural

fingerprints and protein embeddings performed the best, with an RMSE of 0.414

(Supplemental Table 3).

Figure 4 - *A schematic summarizing Zhaoping Xiong's method. The molecule is*

embedded with graph neural fingerprints and the target proteins are represented as

sequences and pretrained with a language model (doc2vec) model. These two

embeddings are fused together to classify the binding affinity as inactive, weak, or

potent.

The Method 1 researcher also made the observation that the majority of $-\log_{10} IC_{50}$

(pIC50) training data was centered around a pIC50 of 5, making prediction of more

extreme compound-target pIC50 values more challenging. To address this, the method

was developed as a classification problem in which the bioactivity of training data was

classified as "inactive" (pIC50 < 5), "weak" (5 <= pIC50 < 6) or "potent" (pIC50>=6). A

classification model trained on these data was then used to predict compound classes

for the targets/anti-targets posed by the Challenge. Finally, the top predictions were

manually selected based on predicted classes for the query targets and anti-targets.

Overall, this model performed best in the Challenge (Supplemental Figure 3).

Team DMIS-MTD based Method 2 on ReSimNet [30], a Siamese neural network

model that receives the structural information of two drugs and predicts their

transcriptional response similarity. ReSimNet was trained on the Connectivity Map

(CMap) dataset [31], which provides CMap scores of around 260,000 drug pairs from

2,400 unique drugs. The CMap score of a pair of drugs is computed based on the

similarity of the observed drug-induced gene expression profiles of the two drugs.

Trained on these CMap scores of observed drug pairs, ReSimNet predicts the CMap

scores of any drug pair that includes novel compounds.

Before utilizing ReSimNet to identify novel drug candidates, Team DMIS-MTD first

identified several prototype drugs with kinase inhibition profiles that satisfied most of the

Challenge's pro-target and anti-target conditions. They used the kinase inhibition

profiles from the *KI*nase *E*xperiment *O*mnibus (KIEO) database (http://kieo.tanlab.org),

which was constructed from experimental data on kinase inhibitors. The data was

curated from more than 600 published articles (Figure 5A). ReSimNet, trained on the

CMap dataset (Figure 5B), was used to predict the transcriptional response similarity

between a prototype drug and a novel compound from ZINC15 [32] (Figure 5C). Finally,

the top-ranking ZINC15 compounds were aggregated and filtered by Lipinski's rule, a

patent search through PubChem, and a protein-ligand docking algorithm (Figure 5D).

Figure 5 - *A schematic summarizing DMIS-MTD's method. The method was based on*

ReSimNet [30], a Siamese neural network model that predicts their transcriptional

response similarity of two compounds. (A) Several prototype drugs whose kinase

inhibition profiles satisfy most of the pro-target and anti-target conditions of the

challenge problem were identified using the KInase Experiment Omnibus (KIEO)

database. (B-C) ReSimNet, trained on the CMap dataset , was used to predict the

transcriptional response similarity between a prototype drug and a novel compound

from ZINC15. (D) Finally, the top-ranking ZINC15 compounds are aggregated and

filtered for compounds that fulfill Lipinski's rules, a patent search through PubChem, and

a protein-ligand docking algorithm.

Translation of hits to in vivo model systems

After identifying the best-binders in the competitive phase of the Challenge, we

assessed the *in vivo* translatability of the *in silico* predicted binders from Problem 1 that

were also found to bind the P1 targets *in vitro* (Table 2, Figure 2A). We obtained and

tested the compounds for their ability to rescue viability of transgenic flies that

expressed the oncogenic form of Drosophila RET in multiple tissues (*ptc>RET^{M955T}*) as

previously described [22,33].

Control transgenic *ptc>RET^{M955T}* (RET2B) flies fail to eclose to adulthood due to

expression of the transgene (0% adult viability; Supplemental Figure 4, Supplemental

Table 4). Feeding *ptc>RET^{M955T}* flies with food containing AD80 or APS6-45 (50 µM)—

experimental multi-targeting kinase inhibitors that reduce *ptc>RET^{M955T}* lethality

[22,33]—significantly increased survival to 27% and 22% mean eclosure, respectively

(Supplemental Figure 4, Supplemental Table 4). Feeding with ZINC98209221 or

ZINC40900273 (1, 10, or 50 µM final food concentrations) rescued to 1-1.5% of

animals, respectively (Supplemental Figure 4, Supplemental Table 4), a number that

failed to rise to statistical significance.

Ensemble modeling

As a proof-of-concept to identify candidates for future study, we devised a

"wisdom of the crowds" approach to identify consensus Problem 1 predictions of the

top-performing models by identifying the nexus of chemical space predicted by these

methods. Specifically, we obtained a larger list of top predictions from the two top-

performing teams using the same method and then determined the pairwise Tanimoto

similarity (Supplemental Figure 2A) between these two sets. Using this data, we

performed network analysis (Supplemental Figure 2B), which allowed us to identify

subclusters of structurally similar predicted molecules within the full set of top predicted

molecules. We further profiled these molecules using computationally generated

absorption, distribution, metabolism and excretion (ADME) metrics (Supplemental Table

5) to facilitate future prioritization of these molecules for medicinal chemistry and *in vivo*

screening.

Discussion

One approach to overcoming the limitations of precision medicine approaches in drug development is to develop new drugs with a goal of multi-targeting drugs that target multiple nodes in a disease network. Developing these drugs is a challenge, as both desired targets as well as toxic targets must be considered in the design process. One possible framework for identifying these drugs involves the use of predictive computational modeling strategies to perform virtual screening and identify compounds with a desirable target profile. Here, we described our efforts to identify better computational approaches for this pharmacologic problem.

To provide a disease context to this challenge, we used a set of previously identified pro-targets and anti-targets to design two challenge problems. Problem 1 asked teams to predict molecules that bound the RET^{M955T}-associated cancer targets RET[M918T], BRAF, SRC, S6K, and avoided binding to MKNK1, TTK, ERK8, PDK1, and PAK3. Problem 2 asked participants to predict compounds that bound the Tauopathy pro-targets, AURKA, PAK1, FGFR1, and STK11 and did not bind PAK3, MAP3K7, and PIK3CA. The teams collectively identified 3 compounds for Problem 1 and 2 compounds for Problem 2 that were observed to have any binding potency to the pro-targets. Furthermore, the same set of teams in both problems were successful, indicating that their methods were consistently best-performing. Both of the top-performing teams used neural networks based learning approaches. However, there were other teams that also employed a neural network based approach but did not successfully identify any binding compounds, suggesting that the specific approach may be critical for success. Other approaches (solely manual curation, random forest,

logistic regression) were unsuccessful in identifying binders, suggesting that these

methods may not be well-poised to perform well in this type of problem.

Another key finding was that most of the submitted methods, including the top-

performing methods, required a manual curation/selection step to select the top

performing compounds (Table 5). The decisions and criteria that are used in manual

selection can be difficult to define or reproduce using a decision tree or other algorithm.

A clear direction for future studies is to better define the nature and rationale for these

manual curation steps and devise strategies to automate these steps. The benefits of

such future work would likely be two-fold: it would increase the reproducibility of these

methods, and it could yield ensemble methods that are more successful in identifying

optimal compounds for a given set of targets and anti-targets.

The predominant limitation of this challenge was a relatively small participant pool,

which likely resulted in constrained space of methodology. Remarkably, the top-

performing methods predicted the identical compound (ZINC98209221) as the best

candidate for solving Problem 1, which is surprising given the size of the ZINC15

compound library. Furthermore, previous DREAM Challenges have consistently

demonstrated that a variety of methodologic approaches can perform well in many

different applications; therefore, it may be the case that methodologic approaches

beyond neural networks may indeed be applicable to the problems defined in this

challenge, but that the implementation may need to be altered to be successful.

The other key limitation of this study was the difficulty in translating computationally

predicted best binders to activity in an *in vivo* system. We tested the top prediction from

Problem 1 in the Drosophila RET^{M955} model system of RET-driven cancer but did not

observe bioactivity. There are multiple possible explanations for this, such as the
standard ADME challenges faced in drug development, as well as the differences
between the fly and human targets and networks [22,34]. To ameliorate this,
improvements could include increasing the scale of experimentally tested compounds to
identify a larger number of best binders, performing more stringent computational
filtering to eliminate compounds with poorer predicted bioavailability characteristics, and
performing standard medicinal chemistry and structure-activity relationship studies to
identify analogues with better *in vivo* performance.

In the Results, we described a proof-of-concept approach to use these methods to
identify molecular candidates for future experimental validation. By leveraging a
"wisdom of the crowds" approach, we identified consensus Problem 1 predictions of the
top-performing models by identifying the nexus of chemical space predicted by these
methods. We subsequently evaluated these molecules using computationally ADME
metrics to facilitate future prioritization of these molecules for medicinal chemistry and *in*
vivo screening. With this in mind, employing a tandem approach where that leverages
ensembled computational models to identify a general region of chemical space with an
appropriate polypharmacological profile, followed by more traditional drug optimization
approaches, may be a worthwhile future avenue to accelerate the development of multi-
targeting drugs.

Materials and Methods

Challenge infrastructure

Multi-targeting Drug DREAM Challenge participants were required to submit a prediction file following a pre-formatted YAML template that included each team's top 5 compound predictions for each of the two problems (RET^{M955T1}- and TAU^{R406W}-mediated phenotypes) (Figure 1). Each prediction included a compound name, vendor name and ID, a methods description, a rationale explaining why the approach was innovative, how the approach is generalizable, and why top predicted compounds are chemically novel. Participants were restricted to compounds that were available through a vendor listed on ZINC15 or other vendors for no more than $250 per mg. The full set of predictions and methods descriptions provided by the Multi-targeting Drug DREAM Challenge community is available as Supplementary Methods.

In vitro testing

Compounds were purchased and delivered to a contract research organization for experimental testing of binding to the target and anti-target kinases defined for Problems 1 (Figure 2) and 2 (Figure 3). Binding was evaluated using the DiscoverX KinomeScan profiling service. In brief, this method evaluated the ability of the predicted compounds to compete with a bead-immobilized ligand for the active sites of DNA-tagged kinases from Problem 1 and Problem 2. Kinases bound to the immobilized ligand were exposed to a broad range of concentrations of the prediction compounds (11 doses, 3-fold serial dilutions starting at 30 µM of compound). At each dose, the amount of drug bound to kinase was measured by eluting the non-bead-bound DNA-

tagged kinase and performing quantification by quantitative polymerase chain reaction

(qPCR).

Scoring Algorithm

Submissions were assessed using a point-based approach (Table 1). Points were

awarded for meeting multiple criteria, in which "binding" of a pro-target was a positive hit

at 10 μM and "non-binding" of an anti-target was defined as a negative result at 30 μM

(Supplemental Tables 1,2).

For problem 1, each of the compounds submitted were awarded points for binding

RET[M918T], BRAF, SRC, and/or S6K. Compounds were also awarded points for

avoiding MKNK1, TTK, ERK8, PDK1, and/or PAK3. For problem 2: E, each of the

compounds submitted were awarded points for binding AURKA, FGFR1, LKB1, and

PAK1 and avoiding the anti-targets PAK3, MAP3K7 (TAK1), and PIK3CA. In addition,

points were awarded for predictions for meeting other criteria including: novelty

(ECFP6-based Tanimoto coefficient <0.4 against all other ChEMBL compounds known

to be active against these targets), ability to patent (<2 hits in SciFinder database), and

drug-like features (adheres to ¾ of Lipinski's rule of 5). In addition, for Problem 2,

predictions predicted to enter the central nervous system (polar surface area <75) were

awarded additional points.

Chemical similarity calculations

Chemical similarity calculations and visualizations were performed in the R

programming language using rcdk, fingerprint, pheatmap and visNetwork packages.

SMILES strings for each structure were provided by each team, and then converted to a

binary fingerprint using the "standard" method provided by the fingerprint package (a

1024-bit "path based, hashed fingerprint"). These fingerprints were then used to

generate pairwise similarity matrices using the fingerprint::fp.sim.matrix with the method

parameter set to 'tanimoto'. Full R notebooks describing these analyses can be found at

https://github.com/Sage-Bionetworks-Challenges/Multi-Target-Challenge.

Ensemble method

Ensemble predictions were performed by generating lists of top predictions for each

top-performing team and assessing structural similarity as described above. We then

used the SwissADME [35] webapp to calculate the number of Lipinski violations, Ghose

violations, Veber violations, Egan violations, Muegge violations, PAINS alerts, Brenk

alerts, and Lead-likeness violations (Supplemental Table 5). For each compound and

we assigned a score of 1 for each value without a violation or alert, or a score of 0

otherwise. We then summed these values to create a composite score where a larger

score indicates fewer applicable violations/alerts to prioritize compounds for in vivo

screening.

In vivo validation

Female *UAS-RET^{M955T}* virgins were mated to *ptc-GAL4* males to generate *ptc>RET^{M955T}*

progeny. Progeny were grown at 25°C and compounds were tested by feeding larvae at

three doses: 10 µM, 5 µM, and 1 µM final food concentration. DMSO alone served as a

negative control and the experimental compounds AD80 and APS6-45 [22,33] served

as positive controls. Using survival to adulthood (eclosure), each condition was done in

quadruplicate, with 41-110 animals tested for each drug concentration.

Code availability

Zhaoping Xiong's top-performing method is available in a Github repository:

https://github.com/xiongzhp/FusedEmbedding. Instructions for running the method can

be found here:

https://github.com/xiongzhp/FusedEmbedding/blob/master/REPRODUCING.md.

Team DMIS-MTD's top-performing method is available at:

https://github.com/dmis-lab/ReSimNet

https://www.synapse.org/#!Synapse:syn20545440

Instructions for running this method can be found at:

https://github.com/dmis-lab/ReSimNet/blob/master/README.md.

A detailed description of the implementation and results of these two methods as well

as all other submitted methods can be found in the Supplemental Methods. Post

challenge analysis notebooks can be retrieved from:

https://github.com/Sage-Bionetworks-Challenges/Multi-Target-Challenge.

Acknowledgements

This work was supported by U54OD020353 (ORIP) to RC. RA was partially supported

by the NIH NIGMS R35GM131881 grant. The members of the Multi-targeting Drug

DREAM Challenge Community in addition to the article byline include: Joerg Kurt

Wegner, Janssen Pharmaceuticals; Huub Henkelsma, Gerard JP van Westen, Leiden

Academic Center for Drug Research; Brandon Bongers, Leiden University; Lindsey

Burggraaff; Leiden University, Jesper Van Engelen; Leiden University, Xuhan Liu,

Leiden University; Xuhan Liu; Marina Gorostiola Gonzalez; Marvin Steijaert; Hugo

Gutiérrez de Teran, Uppsala University; Holger Hoos; Anthe Janssen; Andre Falcao,

University of Lisbon; Samina Kausar, University of Lisbon; Miguel Rocha, Centre

Biological Engineering; Delora Baptista; Jorge Miguel Lourenço Ferreira, University of

Minho; Jinhyuk Lee; Hwisang Jeon; Miyoung Ko; Donghyeon Park, Korea University;

Gregory Koytiger, Immuneering Corporation; Team Stratified (4 anonymous members);

Masahiro Mochizuki, DeNA Co., Ltd.; David Koes, University of Pittsburgh; Huiyuan

Chen; Xengie Doan, Sage Bionetworks; Nasim Sanati, Sage Bionetworks

Contributions

RJA, JG, XG, NS, MJ, AT, HAC, RA, AS, ZX, HJ, MZ, AS, and RC wrote and edited the

manuscript. JG, XG, NS, KD, MJ, KJ, DP, JL, HJ, MK, ACT, AT, HAC, RA, AS, and RC

designed and implemented or competed in the competitive phase of the challenge. RJA,

XG, KD, RA, CH, TK, AS, and RC designed and implemented post-challenge

experiments and analyses. JG, KD, AS, RC were responsible for procuring funding for

this study and supervising the work.

Conflict of interest statement

Avner Schlessinger is co-founder of AIchemy, LLC.

References

1. Barton P, Riley RJ. A new paradigm for navigating compound property related drug
attrition. Drug Discovery Today. 2016. pp. 72–81. doi:10.1016/j.drudis.2015.09.010

2. Empfield JR, Clark MP. Reducing Drug Attrition. Springer; 2014.

3. Sullivan RJ, Flaherty KT. Resistance to BRAF-targeted therapy in melanoma. Eur J
Cancer. 2013;49: 1297–1304.

4. Marquart J, Chen EY, Prasad V. Estimation of the Percentage of US Patients With
Cancer Who Benefit From Genome-Driven Oncology. JAMA Oncol. 2018;4: 1093–
1098.

5. Allaway RJ, La Rosa S, Guinney J, Gosline SJC. Probing the chemical–biological
relationship space with the Drug Target Explorer. Journal of Cheminformatics.
2018. doi:10.1186/s13321-018-0297-4

6. Shi D, Khan F, Abagyan R. Extended Multitarget Pharmacology of Anticancer
Drugs. J Chem Inf Model. 2019;59: 3006–3017.

7. Davis MI, Hunt JP, Herrgard S, Ciceri P, Wodicka LM, Pallares G, et al.
Comprehensive analysis of kinase inhibitor selectivity. Nat Biotechnol. 2011;29:
1046–1051.

8. Vidal M, Wells S, Ryan A, Cagan R. ZD6474 suppresses oncogenic RET isoforms
in a Drosophila model for type 2 multiple endocrine neoplasia syndromes and
papillary thyroid carcinoma. Cancer Res. 2005;65: 3538–3541.

9. Vitagliano D, De Falco V, Tamburrino A, Coluzzi S, Troncone G, Chiappetta G, et
al. The tyrosine kinase inhibitor ZD6474 blocks proliferation of RET mutant
medullary thyroid carcinoma cells. Endocr Relat Cancer. 2011;18: 1–11.

10. Szalai B, Subramanian V, Holland CH, Alföldi R, Puskás LG, Saez-Rodriguez J.
Signatures of cell death and proliferation in perturbation transcriptomics data-from
confounding factor to effective prediction. Nucleic Acids Res. 2019;47: 10010–
10026.

11. Cichonska A, Ravikumar B, Allaway RJ, Park S, Wan F, Isayev O, et al.
Crowdsourced mapping of unexplored target space of kinase inhibitors. bioRxiv.
2020. p. 2019.12.31.891812. doi:10.1101/2019.12.31.891812

12. Thafar M, Raies AB, Albaradei S, Essack M, Bajic VB. Comparison Study of
Computational Prediction Tools for Drug-Target Binding Affinities. Front Chem.
2019;7: 782.

13. Pabon NA, Xia Y, Estabrooks SK, Ye Z, Herbrand AK, Süß E, et al. Predicting

protein targets for drug-like compounds using transcriptomics. PLoS Comput Biol.
2018;14: e1006651.

14. Douglass EF, Allaway RJ, Szalai B, Wang W, Tian T, Fernández-Torras A, et al. A
Community Challenge for Pancancer Drug Mechanism of Action Inference from
Perturbational Profile Data. bioRxiv. 2020. p. 2020.12.21.423514.
doi:10.1101/2020.12.21.423514

15. Lim H, Xie L. Omics Data Integration and Analysis for Systems Pharmacology.
Methods Mol Biol. 2019;1939: 199–214.

16. Schneider P, Walters WP, Plowright AT, Sieroka N, Listgarten J, Goodnow RA Jr,
et al. Rethinking drug design in the artificial intelligence era. Nat Rev Drug Discov.
2020;19: 353–364.

17. Zhavoronkov A, Ivanenkov YA, Aliper A, Veselov MS, Aladinskiy VA, Aladinskaya
AV, et al. Deep learning enables rapid identification of potent DDR1 kinase
inhibitors. Nat Biotechnol. 2019;37: 1038–1040.

18. Hanson SM, Georghiou G, Thakur MK, Miller WT, Rest JS, Chodera JD, et al.
What Makes a Kinase Promiscuous for Inhibitors? Cell Chem Biol. 2019;26: 390–
399.e5.

19. Rahman R, Ung PM-U, Schlessinger A. KinaMetrix: a web resource to investigate
kinase conformations and inhibitor space. Nucleic Acids Res. 2019;47: D361–
D366.

20. Schlessinger A, Abagyan R, Carlson HA, Dang KK, Guinney J, Cagan RL. Multi-
targeting Drug Community Challenge. Cell Chem Biol. 2017;24: 1434–1435.

21. Read RD, Goodfellow PJ, Mardis ER, Novak N, Armstrong JR, Cagan RL. A
Drosophila model of multiple endocrine neoplasia type 2. Genetics. 2005;171:
1057–1081.

22. Sonoshita M, Scopton AP, Ung PMU, Murray MA, Silber L, Maldonado AY, et al. A
whole-animal platform to advance a clinical kinase inhibitor into new disease space.
Nat Chem Biol. 2018. doi:10.1038/nchembio.2556

23. Beharry C, Alaniz ME, Alonso ADC. Expression of Alzheimer-like pathological
human tau induces a behavioral motor and olfactory learning deficit in Drosophila
melanogaster. J Alzheimers Dis. 2013;37: 539–550.

24. Blard O, Feuillette S, Bou J, Chaumette B, Frébourg T, Campion D, et al.
Cytoskeleton proteins are modulators of mutant tau-induced neurodegeneration in
Drosophila. Hum Mol Genet. 2007;16: 555–566.

25. Grammenoudi S, Anezaki M, Kosmidis S, Skoulakis EMC. Modelling cell and
isoform type specificity of tauopathies in Drosophila. SEB Exp Biol Ser. 2008;60:

39–56.

26. Pfleger CM, Wang J, Friedman L, Vittorino R, Conley LM, Ho L, et al. Grape-seed
polyphenolic extract improves the eye phenotype in a Drosophila model of
tauopathy. Int J Alzheimers Dis. 2010;2010. doi:10.4061/2010/576357

27. Williams DW, Tyrer M, Shepherd D. Tau and tau reporters disrupt central
projections of sensory neurons in Drosophila. J Comp Neurol. 2000;428: 630–640.

28. Li X, Li Z, Wu X, Xiong Z, Yang T, Fu Z, et al. Deep Learning Enhancing Kinome-
Wide Polypharmacology Profiling: Model Construction and Experiment Validation. J
Med Chem. 2019. doi:10.1021/acs.jmedchem.9b00855

29. Xiong Z, Wang D, Liu X, Zhong F, Wan X, Li X, et al. Pushing the Boundaries of
Molecular Representation for Drug Discovery with the Graph Attention Mechanism.
J Med Chem. 2019. doi:10.1021/acs.jmedchem.9b00959

30. Jeon M, Park D, Lee J, Jeon H, Ko M, Kim S, et al. ReSimNet: drug response
similarity prediction using Siamese neural networks. Bioinformatics. 2019;35:
5249–5256.

31. Subramanian A, Narayan R, Corsello SM, Peck DD, Natoli TE, Lu X, et al. A Next
Generation Connectivity Map: L1000 Platform and the First 1,000,000 Profiles. Cell.
2017;171: 1437–1452.e17.

32. Sterling T, Irwin JJ. ZINC 15--Ligand Discovery for Everyone. J Chem Inf Model.
2015;55: 2324–2337.

33. Dar AC, Das TK, Shokat KM, Cagan RL. Chemical genetic discovery of targets and
anti-targets for cancer polypharmacology. Nature. 2012;486: 80–84.

34. Ung PMU, Sonoshita M, Scopton AP, Dar AC, Cagan RL, Schlessinger A.
Integrated computational and Drosophila cancer model platform captures
previously unappreciated chemicals perturbing a kinase network. PLoS Comput
Biol. 2019;15: e1006878.

35. Daina A, Michielin O, Zoete V. SwissADME: a free web tool to evaluate
pharmacokinetics, drug-likeness and medicinal chemistry friendliness of small
molecules. Sci Rep. 2017;7: 42717.

 Supplemental Figure Legends

Supplemental Figure 1 - Chemical similarity comparison of all submitted Problem 1

and Problem 2 solutions.

Supplemental Figure 2 - (A) Similarity heatmap of top predicted compounds for

Problem 1 provided by the top-performing teams. Columns correspond to predictions

from Zhaoping Xiong, while rows correspond to predictions from DMIS-MTD. The

majority of compounds are relatively dissimilar from one another. (B) The similarity

matrix was converted into a network, where nodes are individual predicted compounds

and edges encode compound-compound Tanimoto similarities. Edge thickness

represents similarity (thicker edges = greater similarity). Edges representing similarity

below 0.4 were filtered out, and cluster subnetworks were identified (with each color

representing an individual subnetwork).

Supplemental Figure 3 - Recapitulating Zhaoping Xiong's three-class classification

model used for screening. (A) The distribution of pIC50; (B) The distribution of classes;

(C) The accuracy of the model across train, valid and test sets

Supplemental Figure 4 - RET2B and control *D. melanogaster* were treated with DMSO

(negative control), two candidate RET-targeting compounds identified using top

performing methods (ZINC4020 and ZINC9820) and two positive control multi-targeting

RET inhibitors previously demonstrated to rescue the RET2B model (AD80 [33], APS6-

45 [22]). Bars show the mean percent survival and error bars show the standard

deviation of four replicates per condition. A Mann-Whitney test was used to assess the

significance of changes to percent survival in the varying conditions. The RET2B Adult

panel (bottom right) indicates that higher concentrations of AD80 or APS6-45

significantly (p<0.05) rescue the RET2B model, while the two candidate ZINC molecules

have a minimal and non statistically-significant effect on percent survival to adulthood.

Supplemental Table Legends

Supplemental Table 1 - Problem 1 Results. "Submitter or Team" indicates which team was scored. "Chemical ID" indicates the ZINC or MolPort identifier for each predicted compound. "InChIKey" indicates the InChiKey for each predicted compound. Columns 4-12 indicate the experimentally-validated binding constant (K_d, nanomolar) for the pro-target or anti-target listed in the column header (>30000 nM indicates it was above the detection limit for the assay). Columns 13-16 indicate the status of the compound with respect to the challenge rules for novelty, drug-like properties, and likelihood to pass the CNS as defined in the challenge scoring rules. The final column indicates the number of points the prediction was given based on the defined scoring criteria.

Supplemental Table 2 - Problem 2 Results. "Submitter or Team" indicates which team was scored. "Chemical ID" indicates the ZINC or MolPort identifier for each predicted compound. "InChIKey" indicates the InChiKey for each predicted compound. Columns 4-10 indicate the experimentally-validated binding constant (K_d, nanomolar) for the pro-target or anti-target listed in the column header (>30000 nM indicates it was above the detection limit for the assay). Columns 11-14 indicate the status of the compound with respect to the challenge rules for novelty, drug-like properties, and likelihood to pass the CNS as defined in the challenge scoring rules. The final column indicates the number of points the prediction was given based on the defined scoring criteria.

Supplemental Table 3 - Zhaoping Xiong's method predictive performance on regression models. A summary of the performance of various model architectures tested by top performer Zhaoping Xiong using root-mean-square-error calculated using true pIC50 values.

Supplemental Table 4 - Top Problem 1 predictions fail to rescue the RET2B fly

model. The RET2B model was treated with two positive controls expected to rescue

this model (AD80 and APS6-45), a vehicle control (DMSO), and two test compounds

(ZINC4090, ZINC9820) predicted by the challenge results to rescue the RET2B model.

"tx": the treatment (compound and concentration) used; "genotype": WT or RET2B flies;

stage: class of counted animal - adult or pupae; "mean_percent_surv": the mean

percent survival across 4 replicates; "std_dev_survival": the standard deviation of the

percent survival across 4 replicates.

Supplemental Table 5 - *in silico* **chemical modeling of Problem 1 predictions from**

top performers. Additional hits from top performing teams were characterized using

SwissADME to identify compounds with preferred absorption, distribution, metabolism,

excretion, and other medicinal chemistry properties.

A. Selection of prototype drugs from KIEO

KIEO

Human curation

Search

Search result RET (M918T)
Sunitinib: POC 9.82
AST487: Kd 4.50
Sorafenib: Kd 7.4
Gefitinib: IC50 0.14

Prototype drug

B. Training ReSimNet on the Connectivity Map

Similarity score

Trained model

ReSimNet: neural network for transcriptional response similarity prediction

C. Rank compounds from ZINC using ReSimNet and prototype drugs

Prototype drug

ZINC15

Pairs

Predict

Similarity score

0.95

0.73

-0.84

Ranked candidates

Prediction of transcriptional response similarity between a prototype drug and a compound from ZINC15 using ReSimNet and rank aggregation

D. Post processing

✓ Lipinski's rules

✓ Patent search

✓ Docking algorithm