Statistical determinants of visuomotor adaption along different dimensions during naturalistic 3D reaches

E. Ferrea[1]*, J. Franke[1,2], P. Morel[1,4†], A. Gail[1,2,3†]

1 German Primate Center, Sensorimotor Group, Goettingen, Germany.
2 University of Goettingen, Georg-Elias-Mueller Institute of Psychology, Goettingen, Germany,
3 Bernstein Center for Computational Neuroscience, Goettingen, Germany.
4 Univ. Lille, Univ. Artois, Univ. Littoral Côte d'Opale, ULR 7369 - URePSSS - Unité de Recherche Pluridisciplinaire Sport Santé Société, Calais, France.

† equal contribution

*Corresponding author: eferrea@dpz.eu

Abstract

Neurorehabilitation in patients suffering from motor deficits relies on relearning or re-adapting motor skills. Yet our understanding of motor learning is based mostly on results from one or two-dimensional experimental paradigms with highly confined movements. Since everyday movements are conducted in three-dimensional space, it is important to further our understanding about the effect that gravitational forces or perceptual anisotropy might or might not have on motor learning along all different dimensions relative to the body. Here we test how well existing concepts of motor learning generalize to movements in 3D. We ask how a subject's variability in movement planning and sensory perception influences motor adaptation along three different body axes. To extract variability and relate it to adaptation rate, we employed a novel hierarchical two-state space model using Bayesian modeling via Hamiltonian Monte Carlo procedures. Our results show that differences in adaptation rate occur between the coronal, sagittal and horizontal planes and can be explained by the Kalman gain, i.e., a statistically optimal solution integrating planning and sensory information weighted by the inverse of their variability. This indicates

that optimal integration theory for error correction holds for 3D movements and explains adaptation rate

variation between movements in different planes.

Introduction

Studies of motor control and motor adaptation previously have been performed mostly in one or two-

dimensional settings[1-7]. It is unclear, how well these findings generalize to movements in 3D, since 3D

settings apply much less physical constraints on body pose and movements[8,9]. Unless movements are

constrained in a horizontal plane by a table or supported by an exoskeleton, gravity induces a force

anisotropy; unless movements are conducted in a frontoparallel plane, visual depth induces a perceptual

anisotropy. It is unknown, if and how differences in the way subjects plan movements and in the way

they perceive the environment and their own movement along different dimensions translate into motor

adaptation anisotropy. Here we directly compared adaptation in different dimensions in the context of

naturalistic movements in 3D.

Perceptual as well as other factors might contribute to adaptation anisotropies. Studies in 3D virtual

reality (VR) found that adaptation along a vertical axis entails a reduced learning rate relative to the other

two axes when a simultaneous triaxial perturbation was applied[10]. The authors proposed that their results

are a consequence of the higher weight given to proprioception when adjusting movements along the

vertical axis compared to sagittal or horizontal axis, considering/assuming that motor learning based on

proprioceptive feedback entails a lower learning rate than based on visual feedback. We will refer the

variability attributed to visual or proprioceptive feedback and affecting the estimate of the effector (hand)

position as "measurement variability"[11]. However, not only measurement variability matters. According

to optimal feedback control theory (OFC), the nervous system optimally (with respect to a specified goal)

combines sensory feedback (e.g. visual and proprioceptive) information with a forward prediction of the

body's state to control movements and to correct errors[12-15]. During motor adaptation, this forward model

is updated to reduce a sensory prediction error arising from a mismatch between its prediction and the

sensory feedback. Any variability in this closed-loop process thus should affect the observed rate of

adaptation. This includes variability in movement planning[11,16-21] which might result from the stochastic

nature of neuronal processes in sensorimotor transformations, referred to as "planning variability", and

which directly affects the reliability of the forward model prediction[22-26]. Here, we test the prediction of

optimal integration theory that planning and measurement variability between different dimensions

relative to the body determine the corresponding motor adaptation rates[16-19,27].

According to optimal integration theory, a statistically optimal solution for the update of the forward

model during adaptation is the Kalman filter[28], which is updated from the error proportionally to the

inverse of measurement variability and planning variability[11,29,30]. Higher variability in the forward model

(high planning variability) would increase the Kalman gain and allow faster corrections of the experienced

error, whereas a higher variability in the sensory feedback (high measurement variability) would decrease

the gain and therefore lead to slower adaptation. Previous studies found that human behavior approaches

that of an optimal learner[11,21,31] showing that adaptation rate positively correlates with the Kalman gain

calculated from the planning and measurement variabilities. Also, individual differences between subjects

in the rate of motor adaptation can be largely explained by individual differences in the Kalman gain[20], a

prediction which we here test in the context of 3D movements. To study adaptation in naturalistic 3D

movements, we leverage existing differences in planning and measurement variability in the different

planes of space (coronal, sagittal, horizontal) instead of experimentally inducing variability. From previous

work, we expect that the higher variability associated with depth perception reduces the rate of

adaptation [14,32]. At the same time, planning variability might be elevated along the vertical axis given the

stronger proprioceptive rather than visual component [33] due to the need of compensating gravitational

forces [34-36].

Current experiments and models propose that sensorimotor adaptation is supported by two learning

processes, which act on different timescales, one fast adapting and fast forgetting and one slow adapting

and slow forgetting[7,37]. To estimate adaptation rates separately for each learning process and link them

to Kalman gain, we will fit both fast- and slow-state processes during sensorimotor adaptation. Compared

to one-state models[22,23,26], two-state models explain motor adaptation as a combination of explicit and

implicit learning mechanisms, where explicit learning allows fast adaptation and implicit learning changes

performance more slowly[4,6,38]. Two-state models also better explain phenomena like savings, i.e.

improved learning due to repeated exposure[39-41], and anterograde interference, i.e. the negative influence

of past learning on future learning[2,42], that was found to be partially correlated with explicit learning[5].

Moreover, neurophysiological evidence of two-state learning dynamics was found in humans and

monkeys[43,44]. In a VR context, explicit learning was found to have a stronger influence on the final

adaptation level than in non-VR adaptation paradigm[8]. Given that two-state dynamics were found to

better model adaptive behaviours of visuomotor rotation paradigms, especially in VR settings, our method

will be focused on a two-state space model but the results will be also compared with a one-state model.

By considering the stochastic nature of error-based learning, we can independently estimate the

measurement and planning uncertainty from the empirical movement data during a 3D adaptation task

using stochastic modelling. Stochastic modeling has been shown to better identify the time course of the

hidden states[45]. Specifically, we use Bayesian inference via Hamiltonian Markov chain Monte Carlo

sampling (referred to as Hamiltonian Monte Carlo, HMC) to implement a novel multilevel hierarchical

version of the two-state space model fitting. Hierarchical modelling generally allows greater regularization

of the subjects' parameters and simultaneous estimates of the parameter distributions ultimately

resulting in less overfitting of the data[46]. We evaluated the hierarchical model and compared it to another

state-of-the-art model performing Bayesian inference via an expectation-maximization (EM) algorithm[45]

without a hierarchical structure. We show that HMC allows for a better extraction of data on the two

underlying motor learning states and the planning and measurement variabilities. Using hierarchical HMC

models, we confirm that two-state models better explain our experimental three-dimensional data than

single-state models. We, therefore, use the two-state hierarchical HMC model to test whether differences

in adaptation dynamics can be found between movements and perturbations of different directions

relative to the subject's own body and whether these differences comply with optimal integration theory.

110
111
Materials and Methods

Subjects

Data were collected from 26 healthy subjects (age range 20-32, 10 females, 16 males). The study was

performed under institutional guidelines for experiments with humans, adhered to the principles of the

Declaration of Helsinki, and was approved by the ethics committee of the Georg-Elias-Mueller-Institute

for Psychology at the University of Goettingen. All the subjects were right-handed, had normal or

corrected-to-normal vision and received financial compensation for their participation. Subjects gave

written consent to participate and received detailed written instructions for the task. They were asked to

paraphrase the instructions in their own words to make sure they understood the task. The experiment

was carried out in one single appointment that lasted between 2.5 and 3 hours, depending on the

subjects' freely chosen breaks among blocks (see later).

Virtual Reality Setup

Subjects sat in a darkened room at typical room temperature with no distracting noises. The 26

experiments were done individually at different times of the day and on different days. Subjects

performed the visuomotor task in a three-dimensional (3D) virtual reality with Wheatstone stereoscopic

view. Visual displays on two monitors were controlled by a customized C++ software similar to what was

described in previous studies [47,48]. The images of the two monitors (one for each eye, BenQ XL2720T, 27-

inch diagonal, 1920x1080, 60 Hz refresh rate, BenQ, Taepei, Taiwan) were reflected by two semi-

transparent mirrors. (75 x 75 mm, 70/30 reflection/transmission plate beamsplitter, covered from the

back to block transmission; stock #46-643, Edmund Optics Inc., Barrington, New Jersey, United States)

that were angled 45° relative to the two monitors on each side of the subject (Fig. 1A).

The two screens render a 3D view of virtual objects on a dark background. To accommodate test subject

ergonomics, we tilted the plane of view (mirrors and monitors) downward from horizontal by 30° towards

the frontal direction (virtual horizontal). This ensured that arm movements in the physical space could be

carried out in an ergonomic posture in front of the body while the virtual representation of the hand (the

cursor) was aligned with the actual hand position. The virtual cube that defined the subjects' workspace

was centered on and aligned with the axis of gaze. For the rest of the paper, we describe orientation

relative to the axes of this cube, i.e. relative to the virtual, not the physical horizontal and vertical.

To optimize the 3D perception of the virtual workspace for each subject, the inter-pupillary distance was

measured (range: 51 to 68 mm, mean = 59.48 mm) and the 3D projection was modified in the custom-

made software accordingly. This has been shown to benefit depth perception, reduce image fusion

problems and reduce fatigue in participants[49].

Subjects performed controlled physical arm movements to control cursor movements in the 3D

environment. For this, they moved a robotic manipulator (delta.3, Force Dimension, Nyon, Switzerland)

with their dominant hand to place the 3D cursor position into visual target spheres. The manipulator

captured the hand position at a sampling frequency of 2 kHz with a 0.02 mm resolution. Subjects could

neither see their hand nor the robot handle. Instead, a cursor (yellow sphere, 6 mm diameter) indicated

the virtual representation of the robot handle and therefore the hand position (Fig. 1B).

Behavioral task

Subjects performed a 3D center-out reaching task, i.e. started their reaches from a central fixation position

(indicated by sphere, semitransparent grey, 25 mm diameter) to one of eight potential target positions

(grey sphere, 8 mm diameter) arranged at the corners of a 10 cm-sided cube centered on the fixation

position (Fig. 1B-C). Each subject completed three blocks with breaks in between. One block consisted of

600 successful trials: 120 baseline trials, then 240 perturbed trials, and 240 washout trials again without

a perturbation (Fig. 1D). Each block lasted between 20 to 25 minutes, depending on the performance of

the subject. Breaks between blocks were adjusted according to the subject's needs and usually lasted

between 10 to 15 minutes for compensating potential fatigue/savings/anterograde interference effects

(see later). Before the actual experiment, a 10-minute training session was run to make subjects

comfortable with the three-dimensional environment and to ensure a correct understanding and

execution of the task.

At the beginning of each trial, subjects moved the cursor (co-localized with the physical hand position)

into the central fixation sphere and held the cursor there for 200 ms ("hold fixation"; Fig. 1B). After this

holding period, one of the eight potential targets was briefly highlighted by a spatial cue (semitransparent

grey sphere of 25 mm diameter, centered on the target). The corners of the cube, and hence also the

target, remained visible after the cue stimulus disappeared to allow precise localization of the target in

the 3D space. The size of the spatial cue corresponded to the eligible area in which the movement had to

end to be considered successful. The spatial cue remained visible for 300 ms and then disappeared

together with the fixation sphere. This disappearance served as a GO signal for the subjects. Subjects then

had 500 ms time to leave the fixation sphere and begin their hand movement towards the target. For

successful completion of the trial, it was sufficient that the cursor completely entered the target sphere,

without the need to stop inside the eligible area. Success or failure was indicated by sound signals: high-

pitch for success, low-pitch for failure. A trial was aborted if subjects had not left the starting sphere 500

ms after the GO signal, if the movement was stopped (speed below 3cm/s) at any point outside the target

area or lasted longer than 10 seconds. After each trial, subjects could immediately start a new trial by

moving the cursor back to the starting position.

Within each block, we consistently applied the same 2D visuomotor perturbation to the 3D position of

the cursor during all perturbation trials. Each perturbation affected the cursor position either within the

xy-, the yz- or the xz-plane, respectively. This means, for every perturbation, one out of the three

dimensions was left unperturbed, corresponding to the axis of rotation for the perturbation. In the

perturbed trials, the workspace was rotated by 30 degrees counterclockwise around either the x (rotation

in the sagittal plane), y (rotation in the horizontal plane) or z (rotation in the coronal plane) axes in each

of the three blocks (Fig. 1D). The rotation was applied in each block to one of the three planes. As proof

of concept, we verified that the projections of the trajectories on the perturbed planes look similar (Fig.

2A). The order of the blocks (perturbation planes) were controlled over the experiment using stratified

randomization between subjects, to prevent potential effects of fatigue, interference or savings between

blocks.

In the three blocks, the subjects conducted the same movements in terms of starting and end positions.

We chose the corners of a cube as targets since any movement from the center of the cube to a corner

always is a diagonal movement that is composed of equally large x-, y- and z-components. Therefore, the

same target movement can be subjected to perturbations in each of the three planes parallel to the

surfaces of the cube. This allowed us to compare perturbations in different body-centered dimensions

without changing movement start and end positions, thereby avoiding potentially confounding effects of

posture.

Within each block of trials, the order of the targets was pseudo-randomized such that all eight targets

were presented within each set of eight successful trials. These 8-trial sets counted as epochs and the

model fitting analysis was carried out on epochs rather than on single trials.

Data preprocessing

Data were stored for offline analysis performed in MATLAB® R2018a (MathWorks, Inc., Natick,

Massachusetts, United States). Data plots were generated with gramm, a MATLAB plotting library[50].

Trajectories were aligned in time to the start of the movement, defined as a speed increase above 3 cm/s,

to when the hand reached the target, and resampled in 50 time steps, so that each trajectory was

normalized in duration.

To calculate the spatial deviation of the hand position for each perturbed plane independent of target

direction, the trajectory of each trial was projected on the axis orthogonal to the center-to-target direction

and laying in the plane of the applied perturbation (Fig. 2B, perturbed dimension). To remove biases that

would result from curved trajectories independent of any perturbation, we computed the average

trajectory during baseline trials for each subject and block and subtracted these mean trajectories from

each trajectory in the according block. Figure 2C (middle and bottom panel) shows, for one example

subject, the average of the projected trajectories at baseline, during the first eight perturbation trials

(early adaptation) and the last eight perturbation trials (late adaptation) for all three perturbed planes.

While baseline-corrected trajectories are straight during baseline (by construction), the early adaptation

phase is characterized by curved trajectories with online movement corrections to reduce the target error

induced by the perturbed visual feedback. Later during adaptation trajectories on average were straight

again, i.e. the subject aimed at a direction suited to compensate the effect of perturbed feedback from

beginning of the movement. To quantify changes of the initial aiming direction over the course of

adaptation, we measure the deviation of the trajectory along the perturbed dimension at the moment

when half the distance along the center-to-target dimension is travelled (Fig. 2C) and quantify it as angle.

Fitting model and procedure

Existing Bayesian tools for fitting adaptation models[20,45] can only estimate parameters from single

experimental runs (changes over repeated trials in one task condition and one subject) despite the often

hierarchical nature of the experiment (repeated trials interleaved with multiple conditions, multiple

subjects).

To get more reliable estimates of subject-level and population-level learning parameters, we developed

a hierarchical-model version of single-state and two-state models of adaptation. Hierarchical models for

Bayesian inference allow to regularize the single subject fitted values by introducing a hyper-parameter

at the population level. For this, we used the probabilistic programming language Stan[51], through its

MATLAB interface. Stan allowed us to perform Bayesian inference with its implementation of a

Hamiltonian Markov chain Monte Carlo method using a NUTS sampler algorithm[52] for fitting the model

parameters to the empirical data.

The underlying trial-by-trial adaptation model for the movement angle corrections is the following. For

the trial n in subject j and perturbation plane p, the measured movement angle $y_{jp}(n)$ is:

237
$$y_{jp}(n) = x_{jp}(n) + \varepsilon_{u,jp}(n) \quad (1)$$

With $x_{jp}(n)$ being the hidden internal state (planning angle) and $\varepsilon_{u,jp}(n)$ the measurement noise of the

movement due to limited sensory accuracy of the agent, described by a normal distribution with zero

mean: $\varepsilon_{u,jp}(n)\sim N(0, \sigma_{u,jp})$. We refer to this term as measurement noise since it reflects the uncertainty

of estimating the position of the hand based on the sensory feedback with zero mean and standard

deviation $\sigma_{u,jp}$ from which we calculated the measurement variability by squaring the term $\sigma_{u,jp}$ ($\sigma^2_{u,jp}$).

We use this term to differentiate it from the uncertainty arising at the central brain level (planning noise;

see below). In our experimental paradigm/model, the measurement noise is also influenced and cannot

be disentangled from the execution noise that is added to the movement during conduction at the

"periphery", i.e., it includes any movement variability that is accessible to the central nervous

representations only via sensory feedback.

The internal state $x_{jp}(n + 1)$ in trial $n + 1$ depends on the state in the previous trial n, with retention **A**,

and the error e in the previous trial, with learning rate **B**. The error e is expressed as $e_{jp}(n) = p - y_{jp}(n)$,

where p is equal to thirty degrees during perturbed trials and zero degrees otherwise. The state update is

affected by a planning noise (or state update error) $\varepsilon_x(n)$, which gives us the following:

$$x_{jp}(n + 1) = A_{jp}x_{jp}(n) + B_{jp}e_{jp}(n) + \varepsilon_{x,jp}(n) \quad (2)$$

In the single-state model, A_{jp} and B_{jp} are positive scalars, and $\varepsilon_{x,jp}(n)\sim N(0, \sigma_{x,jp})$. $\sigma_{x,jp}$ is the standard

deviation of the internal state error and allows calculating the planning noise by squaring the term $\sigma_{x,jp}$

($\sigma^2_{x,jp}$). For the two-state model:

$$260 \qquad A_{jp} = \begin{bmatrix} a_{s,jp} & 0 \\ 0 & a_{f,jp} \end{bmatrix} \text{ with constraints } a_{s,jp} > a_{f,jp} > 0$$

$$261 \qquad B_{jp} = \begin{bmatrix} b_{s,jp} \\ b_{f,jp} \end{bmatrix} \text{ with constraints } b_{f,jp} > b_{s,jp} > 0$$

$$262 \qquad \varepsilon_{x,jp}(n) \sim N\left(\begin{bmatrix} 0 \\ 0 \end{bmatrix}, \begin{bmatrix} \sigma_{x,jp} & 0 \\ 0 & \sigma_{x,jp} \end{bmatrix} \right)$$

In our model, all subject and plane-level parameters: $\sigma_{u,jp}$, $a_{s,jp}$, $a_{f,jp}$, $b_{s,jp}$, $b_{f,jp}$, $\sigma_{x,jp}$ were drawn

from population-level normal distributions, e.g. for $a_{s,jp}$ we define $a_{s,jp} \sim N(\mu_{a_s,p}, \sigma_{a_s})$. Here, $\mu_{a_s,p}$ and

σ_{a_s} are population-level hyper-parameters, corresponding to the population (between-subject) average

of the slow retention for perturbation plane p and the population standard deviation of the slow

retention.

To keep the model simple, we did not include common per-subject offsets in the average hyper-

parameters across planes; in other words, the model we used did not take into account the fact that the

same subjects participated in experimental runs with different perturbed planes. A variation of the model

which permitted per-subject offsets yielded equivalent results (data not shown).

Bayesian inference requires priors for the hyper-parameters, which we chose wide to not constrain the

model. Retention average hyper-parameter ($\mu_{a_s,p}$, $\mu_{a_f,p}$ in the two-state model and $\mu_{A,p}$ in the single-

state model) priors were $\sim N(1,9)$, learning rate average ($\mu_{b_s,p}$, $\mu_{b_f,p}$ and $\mu_{B,p}$) priors were $\sim N(0,9)$, and

their population standard deviation hyper-parameter ($\sigma_{a_s}, \sigma_{a_f}, \sigma_{b_s}, \sigma_{b_f}$ and σ_A, σ_B) priors were half-

Cauchy distributions (location = 0, scale = 5)[53]. Priors of the population average and standard deviation

hyper-parameters of the measurement and planning noise ($\mu_{\sigma_x,p}, \mu_{\sigma_u,p}$ and $\sigma_{\sigma_x}, \sigma_{\sigma_u}$) were half-Cauchy

distributions (location = 0, scale = 15). The conclusions from the model fitting do not critically depend on

the exact choice of any of these parameters.

Steady-state Kalman gain

From the variances of the noise processes, we calculated the steady-state Kalman gain, as derived by

Burge and colleagues[11]. In short, by combining measurement and state-update equations of the Kalman

filter and assuming that a steady-state is reached, we can introduce the term $\sigma^2_{X_t^+}$ which consist on the

variance of the best estimates given the two noisy measurements (see Burge et al., 2008, for full formula

derivation):

$$\sigma^2_{X_t^+} = \frac{-\sigma_x^2 + \sqrt{(\sigma_x^2)^2 + 4\sigma_x^2\sigma_u^2}}{2} \quad (3)$$

The Kalman gain (K), weighting the contribution of planning and measurement variabilities in error

correction, is calculated as follows and indicates the amount of correction that should be attributed to

the error:

$$K = \frac{\sigma^2_{X_t^+} + \sigma_x^2}{\sigma^2_{X_t^+} + \sigma_u^2 + \sigma_x^2} \quad (4)$$

Validation of fitting procedure

To validate our hierarchical Bayesian fitting algorithm, we compared it to a non-hierarchical algorithm by

applying both to surrogate data sets. For this, we generated N = 100 artificial experimental runs using an

underlying two-state time course with the same number of baseline, perturbation, and washout trials as

in our experiment. For each simulation, each parameter was drawn from a random normal distribution

approaching the values we observed in our data: as~N(0.93,0.03), af~N(0.55,0.2), bs~N(0.06,0.04),

bf~N(0.18,0.08), planning variability~N(1.5,1), measurement variability~N(6,3). We then compared the

accuracy of parameter estimations from different fitting methods, namely an EM algorithm [45] and a non-

hierarchical and a hierarchical HMC algorithm.

To quantify whether our two-state hierarchical algorithm introduces spurious correlations among the

learning rates and the Kalman gain, we applied it to two versions of the surrogate datasets: One dataset

was built with 200 completely uncorrelated samples, whereas in a second data set we imposed bs equal

to the 0.3 times the Kalman gain calculated according to (4).

Results

The subjects performed the task (three conditions: baseline, perturbation and washout) with a high

success rate in all perturbed planes (number of correct trials/number of total trials > 99%). We used a

generalized linear mixed effect model (GLMM) with a binomial distribution to test the effect of the

perturbation in the different planes (fixed effect) on the success rate, with the subjects as random effect.

With the sagittal plane as intercept, there was no significant effect on the slope for the horizontal plane

(tstat = 1.5477, p = 0.1217) and no significant effect for the slope of the coronal plane (tstat = 1.3976, p =

0.16223). This means that we did not observe differences in performance among the three perturbation

planes.

The subjects showed stereotypical adaptation time courses (Figure 3A and supplementary figures 1-3)

during and after introduction of the perturbation with typical error correction profiles that compensate

for the applied rotation. To test differences among the three planes regarding the level of adaptation

reached by the subjects (Fig. 3A), a one-way between-subjects ANOVA was conducted to compare the

effects of the perturbed plane over the final adaptation level. The final adaptation level was calculated as

the average of the adaptation time course over the last 4 epochs of the perturbation period (Fig. 3B). We

found that the subjects adapt differently to the perturbations depending on the plane of rotation ($F_{(2,69)}$

= 30.77, p = 2.8 E-10). The final level of adaptation was significantly higher for perturbations in the coronal

plane compared to the sagittal plane (coronal-sagittal comparison, p = 7.6E-05, post-hoc multi-comparison

test corrected with Tukey's honestly significant difference) and horizontal plane (coronal-horizontal

comparison, p = 1.0 E-08) (Fig. 3B). Moreover, perturbations in the sagittal plane provoke stronger

adaptation than perturbations in the horizontal plane (sagittal-horizontal comparison, p = 0.004) (Fig. 3B).

To understand the underlying dynamic of the differences in adaptation, we modeled adaptation behavior

in the three different visuomotor perturbation planes with a two-state model, which separately identified

the slow and fast processes underlying adaptation. While our hierarchical Bayesian model fits data across

conditions and subjects (see Methods), Figure 3C shows the fitted curves for one example subject

performing three adaptation conditions.

Before comparing adaptation between the different planes, we evaluated whether in our three-

dimensional task, a two-state model fits the data better than a single-state model. The single-state model

shows larger root-mean-square residuals, i.e., larger difference between modeled and observed

adaptation trajectory (paired t-test, p = 6.6e-16). To take into account the number of free parameters when

comparing models, we additionally computed the widely applicable information criterion (WAIC), an

approximation of cross-validation for Bayesian procedures[54]. The two-state model shows a lower WAIC

compared to the single-state model (3.54E+04 and 3.58e+04, respectively), confirming the advantage on

using a two-stage model.

To validate our hierarchical fitting algorithm, we tested whether model parameters are better

reconstructed by our two-state Bayesian HMC hierarchical algorithm compared to a state-of-the-art EM

algorithm[45]. We also compared the HMC hierarchical model with the corresponding non-hierarchical HMC

model. For this, we generated multiple surrogate two-state adaptation datasets with randomly sampled

parameters (see Methods). We then tested how well the three algorithms retrieve the parameters of the

surrogate datasets. The hierarchical algorithm better reconstructs all parameters (error is smaller and

correlation is higher) (Fig. 4). We therefore decided to use a two-state model and independently fit the

parameters for each perturbation plane.

Optimal integration (OI) theory predicts that the rate of adaptation correlates with the weighing between

internal estimation and external sensory information for assessing the state of the system. A learner

optimally integrating these two types of information approximates a Kalman filter that combines them

depending on their respective variabilities. If planning (internal estimate) variability is high and

measurement (sensory information) variability low during adaptation, the experienced error will be given

credibility, and therefore faster learning will happen. In the opposite case, the learner tends to disregard

the experienced error and corrections would happen slowly.

We fitted all learning parameters of the two-state model and the measurement and planning variabilities

from our empirical data (Fig. 5A). To test if the above-mentioned mechanism of OI can explain the

observed differences between the perturbed planes in our experiment, we also correlated planning and

measurement variabilities with the slow learning rate bs for each experimental run in our dataset (Fig.

5B). Correlations between planning variability and the learning rate as well as between measurement

variability and learning rate were low (respective R2 : 0.13 and 0.11), but with a trend consistent to the

OI predictions, i.e., low measurement noise and high planning noise correlate with higher values of the

slow learning rate. When combining the contribution of the two noise parameters into an estimate of a

Kalman gain for each subject, the slow learning rate was explained much better (R2 between K and bs:

0.48), with a high Kalman gain being associated with high learning rate. Notably, this correlation between

Kalman gain (K) and slow learning rate (bs) is determined by the different levels for K and bs between the

perturbation planes. This means, the slow learning rate is mostly explained by the plane of the workspace

in which the perturbation is applied (R2 = 0.94), while it does not correlate with the Kalman gain variation

across the individual subjects within a perturbation condition. Last, the fast learning component shows a

correlation with the Kalman gain among perturbed planes (R2 between K and bf: 0.34).

A long washout plus additional waiting time between conditions prevented savings or anterograde effects

when switching between different planes of perturbation. To test for this, a forward stepwise linear

regression was used to identify possible predictors of the learning rates (bf or bs independently) out of

the order of execution (1st executed task, 2nd execution task or 3rd executed task) and perturbed axis.

At each step, variables were added based on p-values < 0.05. For both learning rates bs and bf, only the

perturbed axis was added to the model with p = 2.98E-44 and p = 8.22E-14 respectively. This means that

we did not observe a significant contribution of savings or anterograde effects on the learning rates.

Since the task uses multiple reach targets, one separate model could be fitted for each target unless one

assumes full generalization between sequentially visited targets. To avoid this pitfall and corresponding

increase in complexity, we fitted the model using epochs, motivated by the fact that in each epoch each

target was visited one time. When we also tested the model for the case where full generalization happens

between two consecutives targets, we found similar results as for the model trained on epochs (R2

between K and bs: 0.29, Supplementary Fig. 4).

We also validated the ability of our model to extract correlated learning parameters whenever present.

For this, we simulated an additional set of data where the slow learning rate bs was imposed to be 0.3

times the steady-state Kalman gain (see Methods). Figure 6A shows that we were able to reconstruct such

correlation with our model. Conversely, when no correlation between the slow learning rate and the

Kalman gain was introduced in the dataset, the model does not introduce spurious correlation. Figure 6

overall confirms the validity of our model for the study of correlations between model parameters.

Discussion

Discussion

We tested if observations and model assumptions about optimal integration (OI) theory for motor

learning, as previously derived from one- or two-dimensional highly confined reach tasks, also hold true

for largely unconstrained movements in three-dimensional space. We show that the rate of visuomotor

adaptation under 3D stereoscopic vision depends on the plane in which a 2D visuomotor rotation

perturbation is applied. Subjects adapted best to perturbations in the coronal plane followed by sagittal

and horizontal planes. The rates of slow and fast learning correlated well with the Kalman gain when

considering the variation across perturbation conditions, but not across subjects within a condition. We

could separately assess the within and across condition parameters with our novel hierarchical Bayesian

HMC fitting of the data. These results show that important aspects of OI theories of motor control derived

from 2D movements generalize to the largely unconstrained 3D movements studied here, at least at the

average population level, but do not extend to the individual subject level for any of the applied

perturbations[20].

A novel two-state hierarchical HMC algorithm for precise estimation of motor learning parameters

We developed a novel HMC Bayesian fitting procedure with a multilevel hierarchical structure to take into

account effects from multiple subjects performing a motor adaptation task in three different learning

conditions, i.e., when different planes relative to the body were perturbed. Naturally, such a hierarchical

approach shows lower goodness-of-fit to single-subject adaptation curves than algorithms that focus on

single-subject data since the hyper-parameter at the population level (i.e. all the samples coming from a

same distribution) act as regularization term. But multi-subject experiments are typically designed to

determine the effects of experimental variations on the motor learning behavior independent of test

subject. Hence, it is most important to best estimate the underlying learning parameters.

For the current experimental design, our procedure is better able to reconstruct actual model parameters

than a state-of-the-art EM fitting algorithm[45] or a non-hierarchical Bayesian HMC model, as revealed from

the surrogate testing. This is due to the low identifiability of such two-state models for relatively short

adaptation experiments comprising only a few dozen or even hundreds of trials per condition. The low

identifiability is a result of random fluctuations in the shape of the adaptation curve and is easily

associated with various learning parameters (see, for example, the outliers in Fig. 4). In the hierarchical

model, each parameter is sampled from a population-level distribution, the parameters of which are also

part of the model. This makes extreme values for the reconstructed parameter less likely.

Using our hierarchical model, we show that a two-state model fits the data significantly better than a

single-state model. The two-state model is well established for subjects performing in a 2D environment[7,37]

and better explains learning mechanisms such as savings and anterograde interference in 2D settings[38]. As

previously hypothesized[4,6], the fast learning process can be partly associated to an explicit process and the

slow learning process to an implicit process, both with anatomically distinct associated brain areas[6,19,43].

While it is plausible to assume that an interplay of explicit and implicit learning mechanisms is independent

of the dimensionality of the task, to our knowledge, the two-state model to date has not been

demonstrated for adaptation paradigms involving 3D movements. The fact that, in a 3D setting, we found

a two-state model to better fit the adaptation data than a single-state model without introducing

paradigms that explicitly enforce two-states dynamics (like re-learning after washout trials,[37]), might

indicate that the explicit learning component in our three dimensional-paradigm is more pronounced than

in classic two-dimensional paradigms. This finding is also in line with a recent study showing that VR

visuomotor rotation tasks have a stronger explicit component than non-VR tasks [8]. The results therefore

further strengthen the association between fast and slow states with explicit and implicit mechanisms.

Differences in estimated planning and measurement noises explain differences in learning rate

Motor learning studies are informative for motor rehabilitation protocols for patients that need to relearn

or re-adapt existing motor schemes. These patients will necessarily perform their movements in a three-

dimensional environment[55-58]. In our experiment, subjects adapted best to perturbations in the coronal

plane, followed by sagittal and horizontal planes. Differences in the slow and fast learning rates between

the planes were associated with different adaptation levels that were achieved during perturbation trials

in our data. In the following, we will discuss how these anisotropies in adaptation are related to

anisotropies in estimated planning and measurement noise, and, hence, could be explained by effects of

gravity and depth perception, respectively.

The slowest adaptation in the horizontal plane is likely explained by an anisotropy in planning variability

resulting from gravity. Previous studies suggested that movements along the vertical dimension have a

higher level of planning variability associated with gravity compensation[33-36]. Optimally combining

uncertainties on planning together with uncertainties on the estimation of the effector position here then

means that sensory measurements should be given more credibility in vertical movements due to the

higher planning variability. This leads to the prediction that adaptive corrections in the horizontal plane

arise slower than corrections in the sagittal or coronal plane, since the latter contain the vertical dimension

with the higher measurement credibility. Consistent with this view, perturbations in the horizontal plane

in our data were associated with the slowest adaptation rates and planning variability was lowest in the

horizontal plane, while measurement variability in the horizontal plane was close to the coronal plane

(Fig5B).

The fastest adaptation rates in the coronal plane are likely explained by anisotropies in measurement

variability resulting from visual depth perception. The coronal plane in our data yielded the lowest

estimate of measurement noise and, correspondingly, subjects adapted faster to perturbations in this

plane (Fig. 5B). In our model, measurement noise represents the reliability of the subject measurements

of the cursor position, i.e., the visual feedback about the movement, since the cursor determines the

motor goal. Subjects have to rely mainly on stereoscopy to estimate visual depth and visual localization is

less precise in depth[14,32]. Since depth is not perturbed by a rotation in the coronal plane, measurement

error is least in the coronal condition and adaptation should be fastest. On the other hand, visuomotor

rotations in the sagittal and horizontal planes both resulted in perturbations of cursor depth compared to

baseline. Corresponding to this, other studies also showed that subjects tend to adapt worse when the

measurement variability (or sensory nose) was increased by practically blurring the error feedback[11,13,21].

Optimal integration theory in 3D

Previous studies[11,20,21,26,31], provided evidence for the OI theory during visuomotor adaptation. They

showed that the planning component of motor noise correlates positively with the adaptation rate while

the measurement component correlates negatively, at least when the respective noise component is

experimentally kept constant. While the adaptation data from our 3D movements yielded similar trends,

the correlation of slow learning rate with either measurement- or planning-variability was weak. For an

optimal learner, the Kalman gain is indicative of the level of correction attributed to the experienced error

[11,21,31]. This Kalman gain positively correlates with the slow learning rate in our data, supporting the idea

that subjects optimally integrate the information relative to the internal state with experienced (visual)

feedback. However, and as opposed to what was suggested in previous studies[20,31], we observe the

correlation between Kalman gain and learning rates only across different perturbation conditions. Within

each perturbation condition and across individual subjects, there was no relationship between Kalman

gain and learning rates.

Conclusion

Here, we develop a novel HMC fitting procedure to correlate learning rates and noise levels estimated with

the same model and without the need to experimentally manipulating these error variabilities. By applying

this model to a sensorimotor adaptation task with naturalistic movements in 3D, we found that the rate

of adaptation with which subjects counteract applied visuomotor rotations, depends on the statistics of

the combined errors with which subjects plan and perceive movements. These errors differ between

different axes relative to the body, likely due to gravity compensation during planning- and perception-

induced anisotropies. This insight could be used in motor rehabilitation strategies by specifically targeting

the orientation of the body relative to the target while performing reaching movements to accelerate

learning.

Acknowledgments:

German Research Foundation (DFG, Germany, grant number FOR-1847-GA1475-B2), received by AG.

German Research Foundation (DFG, Germany, grant number SFB-889), received by AG.

Federal Ministry for Education and Research (BMBF, Germany, grant number 01GQ1005C), received by AG.

Federal Ministry for Education and Research (BMBF, Germany, grant numbers 01GQ0814), received by AG.

Figure Captions

Figure 1. Virtual reality setup with robotic manipulator for testing visuomotor rotation adaptation of
naturalistic reaches in different planes relative to the body. A) Schematic representation of the 3D virtual
reality setup. The two angled mirrors reflect the image from the two screens to the two eyes
independently providing stereoscopic vision. The mirrors are semitransparent to allow calibration of the
virtual reality space with the real hand position. During the experiments, transparency is blocked, so that
the subjects do not see the robotic manipulator and their hand, but only the co-registered cursor. B)
Spatial and temporal structure of the 3D reaching task. Following a brief holding period in the center of a
virtual cube, the subject has to reach to one of eight targets arranged at the corners of the cube. For
ergonomic reasons, the cube is orientated relatively to the slightly downward-tilted workspace and head

of the subject, not according to true horizontal. C) Example baseline trajectories of a single subject. D)
Time course of the perturbation experiment. Following a baseline phase of 120 trials, a 30-degree
visuomotor perturbation is applied for 240 trials, followed by a washout of 240 additional trials. In three
separate blocks for each subject, the perturbation is applied in the sagittal, coronal and horizontal plane,
respectively. Note that all reaches are conducted along a diagonal direction, i.e., each movement is
affected by either of the perturbations.

Figure 2. Quantification of adaptation level. A) Example trajectories from one subject. Each row/color of
the graph correspond to different planes of rotation. The trajectories are projected onto the plane which
is perpendicular to the axis of visuomotor rotation for representation and analysis of the data in each of
the three conditions (coronal, horizontal, sagittal). The trajectories show similarities across the three
planes. B) Within each plane, the trajectories are quantified along the two task relevant dimensions, the
center-to-target dimension and the dimension orthogonal to it in the same plane, which we refer to as
"perturbed" dimension. To compare data across tasks, each trajectory was resampled and rotated into
this reference frame. At half of the normalized trajectory, the adaptation angle was calculated and used
for model fitting. C) Examples of transformed trajectories from one subject during baseline, early
adaptation and late adaptation.

Figure 3. Visuomotor adaptation in three different planes relative to the body. A) Example of the time
course of adaptation for one example subject with perturbation applied to the sagittal plane. B) Final
adaptation level for each plane. C) Examples of data fitted with a one-state and a two-states learning
model, respectively. Black points represent the subject's data (average movement angle at half-trajectory
within 8-trial epochs; 105 epochs represent 360 concatenated baseline trials, 240 adaptation trials and
240 washout trials). The black dashed line shows the perturbation profile.

Figure 4. Comparison of hierarchical and non-hierarchical fitting algorithms. Parameter estimation
quality for our HMC hierarchical fitting procedure (orange), an HMC non-hierarchical fitting procedure
(red), and a EM fitting procedure (EM, blue; [45]). For each random parameter setting of the surrogate two-
state datasets, we represent the error in parameter reconstruction (estimated minus set parameter) for
each fitting procedure, including the distributions of the errors, average and 95% confidence intervals of
the squared error; and the correlation (average and 95% CI) between the estimated and set parameters.

Figure 5. Comparison of two-state model parameters between the perturbation planes. A) Estimated
fast and slow retention ($a_{f,jp}$, $a_{s,jp}$), learning rates ($b_{f,jp}$, $b_{s,jp}$), and measurement and planning
variabilities ($\sigma_{x,jp}$, $\sigma_{u,jp}$) for the sagittal (S), horizontal (H) and coronal (C) perturbation planes. Each color
represents one subjects. The error bars correspond to 95 % credible intervals (i.e., contain 95% of the
posterior probability) for the population average hyper-parameters $\mu_{a_s,p}$, $\mu_{a_f,p}$, $\mu_{b_s,p}$, $\mu_{b_f,p}$, $\mu_{\sigma_x,p}$, $\mu_{\sigma_u,p}$.
The steady-state Kalman gain K was computed from the posteriors of the measurement noise and
planning noise. B) Relationships between the slow learning rate bs and variability related parameters:
measurement noise variability, planning noise variability, and steady-state Kalman gain. Points
correspond to individual subjects' parameters in the different rotation planes (coded by color). The

correspondingly colored lines represent linear fits based on the across-subject parameter values within
each plane. The grey line corresponds to a linear fit based on subjects' parameters values across all planes.
The horizontal and vertical error bars correspond to 95 % credible intervals for the corresponding
parameter population average hyper-parameters.

Figure 6. Recovery of simulated correlations between model parameters by the HMC algorithm. A) A correlation
among bs and K was introduced in the surrogate data by setting bs equal to 0.3 times K (dashed black
line). B) When no correlation between bs and K was added to the surrogate data, the HMC fitting
algorithm did not introduce artificial spurious correlations.

Supplementary Figures

Supplementary Figure 1. Results of fitting the hierarchical HMC model to the adaptation profile of each
subject (n = 24) with perturbation applied to the Sagittal plane.

Supplementary Figure 2. Results of fitting the hierarchical HMC model to the adaptation profile of each
subject (n = 24) with perturbation applied to the horizontal plane.

Supplementary Figure 3. Results of fitting the hierarchical HMC model to the adaptation profile of each
subject (n = 24) with perturbation applied to the coronal plane.

Supplementary Figure 4. Similar to figure 5 but with the model applied on a trial base rather than epoch
base (no average over 8 consecutive trials). A) Example of single subject time course of adaptation with
2-state model fits. B) Extrapolated model parameter for all the subjects (different colors). C) Slow learning
rate (bs) vs Kalman gain relationship.

References

1   Krakauer, J. W. Motor learning and consolidation: the case of visuomotor rotation. *Adv Exp Med*
Biol **629**, 405-421, doi:10.1007/978-0-387-77064-2_21 (2009).
2   Leow, L. A., de Rugy, A., Marinovic, W., Riek, S. & Carroll, T. J. Savings for visuomotor adaptation
require prior history of error, not prior repetition of successful actions. *J Neurophysiol* **116**,
1603-1614, doi:10.1152/jn.01055.2015 (2016).
3   Mazzoni, P. & Krakauer, J. W. An implicit plan overrides an explicit strategy during visuomotor
adaptation. *J Neurosci* **26**, 3642-3645, doi:10.1523/JNEUROSCI.5317-05.2006 (2006).
4   McDougle, S. D., Bond, K. M. & Taylor, J. A. Explicit and Implicit Processes Constitute the Fast
and Slow Processes of Sensorimotor Learning. *J Neurosci* **35**, 9568-9579,
doi:10.1523/JNEUROSCI.5061-14.2015 (2015).
5   Morehead, J. R., Qasim, S. E., Crossley, M. J. & Ivry, R. Savings upon Re-Aiming in Visuomotor
Adaptation. *J Neurosci* **35**, 14386-14396, doi:10.1523/JNEUROSCI.1046-15.2015 (2015).

6   Taylor, J. A., Krakauer, J. W. & Ivry, R. B. Explicit and implicit contributions to learning in a
587   sensorimotor adaptation task. *J Neurosci* **34**, 3023-3032, doi:10.1523/JNEUROSCI.3619-13.2014
588   (2014).
589   7   Wolpert, D. M., Diedrichsen, J. & Flanagan, J. R. Principles of sensorimotor learning. *Nat Rev*
590   *Neurosci* **12**, 739-751, doi:10.1038/nrn3112 (2011).
591   8   Anglin, J. M., Sugiyama, T. & Liew, S. L. Visuomotor adaptation in head-mounted virtual reality
592   versus conventional training. *Sci Rep* **7**, 45469, doi:10.1038/srep45469 (2017).
593   9   Choi, W., Lee, J., Yanagihara, N., Li, L. & Kim, J. Development of a quantitative evaluation system
594   for visuo-motor control in three-dimensional virtual reality space. *Sci Rep* **8**, 13439,
595   doi:10.1038/s41598-018-31758-y (2018).
596   10   Lefrancois, C. & Messier, J. Adaptation and spatial generalization to a triaxial visuomotor
597   perturbation in a virtual reality environment. *Exp Brain Res* **237**, 793-803, doi:10.1007/s00221-
598   018-05462-2 (2019).
599   11   Burge, J., Ernst, M. O. & Banks, M. S. The statistical determinants of adaptation rate in human
600   reaching. *J Vis* **8**, 20 21-19, doi:10.1167/8.4.20 (2008).
601   12   Ernst, M. O. & Banks, M. S. Humans integrate visual and haptic information in a statistically
602   optimal fashion. *Nature* **415**, 429-433, doi:10.1038/415429a (2002).
603   13   Kording, K. P. & Wolpert, D. M. Bayesian integration in sensorimotor learning. *Nature* **427**, 244-
604   247, doi:10.1038/nature02169 (2004).
605   14   van Beers, R. J., Wolpert, D. M. & Haggard, P. When feeling is more important than seeing in
606   sensorimotor adaptation. *Curr Biol* **12**, 834-837, doi:10.1016/s0960-9822(02)00836-9 (2002).
607   15   Wolpert, D. M. & Ghahramani, Z. Computational principles of movement neuroscience. *Nat*
608   *Neurosci* **3 Suppl**, 1212-1217, doi:10.1038/81497 (2000).
609   16   Friston, K. What is optimal about motor control? *Neuron* **72**, 488-498,
610   doi:10.1016/j.neuron.2011.10.018 (2011).
611   17   Scott, S. H. Optimal feedback control and the neural basis of volitional motor control. *Nat Rev*
612   *Neurosci* **5**, 532-546, doi:10.1038/nrn1427 (2004).
613   18   Shadmehr, R. & Krakauer, J. W. A computational neuroanatomy for motor control. *Exp Brain Res*
614   **185**, 359-381, doi:10.1007/s00221-008-1280-5 (2008).
615   19   Shadmehr, R., Smith, M. A. & Krakauer, J. W. Error correction, sensory prediction, and
616   adaptation in motor control. *Annu Rev Neurosci* **33**, 89-108, doi:10.1146/annurev-neuro-
617   060909-153135 (2010).
618   20   van der Vliet, R. *et al.* Individual Differences in Motor Noise and Adaptation Rate Are Optimally
619   Related. *eNeuro* **5**, doi:10.1523/ENEURO.0170-18.2018 (2018).
620   21   Wei, K. & Kording, K. Uncertainty of feedback and state estimation determines the speed of
621   motor adaptation. *Front Comput Neurosci* **4**, 11, doi:10.3389/fncom.2010.00011 (2010).
622   22   Cheng, S. & Sabes, P. N. Modeling sensorimotor learning with linear dynamical systems. *Neural*
623   *Comput* **18**, 760-793, doi:10.1162/089976606775774651 (2006).
624   23   Cheng, S. & Sabes, P. N. Calibration of visually guided reaching is driven by error-corrective
625   learning and internal dynamics. *J Neurophysiol* **97**, 3057-3069, doi:10.1152/jn.00897.2006
626   (2007).
627   24   Korenberg, A. & Ghahramani, Z. A Bayesian view of motor adaptation. *Cahiers de Psychologie*
628   *Cognitive* **21** (2002).
629   25   Morel, P. D. & Baraduc, P. in *Cinquième conférence plénière française de Neurosciences*
630   *Computationnelles, "Neurocomp'10"* (Lyon, France, 2010).
631   26   van Beers, R. J. Motor learning is optimally tuned to the properties of motor noise. *Neuron* **63**,
632   406-417, doi:10.1016/j.neuron.2009.06.025 (2009).

27 Diedrichsen, J., Shadmehr, R. & Ivry, R. B. The coordination of movement: optimal feedback
control and beyond. *Trends Cogn Sci* **14**, 31-39, doi:10.1016/j.tics.2009.11.004 (2010).
28 Kalman, R. E. A New Approach to Linear Filtering and Prediction Problems. *Journal of Basic
Engineering* **82**, 35-45, doi:10.1115/1.3662552 (1960).
29 Baddeley, R. J., Ingram, H. A. & Miall, R. C. System identification applied to a visuomotor task:
near-optimal human performance in a noisy changing task. *J Neurosci* **23**, 3066-3075 (2003).
30 Ghahramani, Z., Wolptrt, D. M. & Jordan, M. I. in *Advances in Psychology* Vol. 119 (eds Pietro
Morasso & Vittorio Sanguineti) 117-147 (North-Holland, 1997).
31 He, K. *et al.* The Statistical Determinants of the Speed of Motor Learning. *PLoS Comput Biol* **12**,
e1005023, doi:10.1371/journal.pcbi.1005023 (2016).
32 Gepshtein, S. & Banks, M. S. Viewing geometry determines how vision and haptics combine in
size perception. *Curr Biol* **13**, 483-488, doi:10.1016/s0960-9822(03)00133-7 (2003).
33 Apker, G. A., Karimi, C. P. & Buneo, C. A. Contributions of vision and proprioception to arm
movement planning in the vertical plane. *Neurosci Lett* **503**, 186-190,
doi:10.1016/j.neulet.2011.08.032 (2011).
34 Le Seac'h, A. B. & McIntyre, J. Multimodal reference frame for the planning of vertical arms
movements. *Neuroscience letters* **423**, 211-215 (2007).
35 Papaxanthis, C., Pozzo, T. & McIntyre, J. Kinematic and dynamic processes for the control of
pointing movements in humans revealed by short-term exposure to microgravity. *Neuroscience*
135, 371-383 (2005).
36 Sciutti, A. *et al.* Visual gravity influences arm movement planning. *Journal of neurophysiology*
107, 3433-3445 (2012).
37 Smith, M. A., Ghazizadeh, A. & Shadmehr, R. Interacting adaptive processes with different
timescales underlie short-term motor learning. *PLoS Biol* **4**, e179,
doi:10.1371/journal.pbio.0040179 (2006).
38 Huberdeau, D. M., Krakauer, J. W. & Haith, A. M. Dual-process decomposition in human
sensorimotor adaptation. *Curr Opin Neurobiol* **33**, 71-77, doi:10.1016/j.conb.2015.03.003
(2015).
39 Avraham, G., Morehead, J. R., Kim, H. E. & Ivry, R. B. Re-exposure to a sensorimotor
perturbation produces opposite effects on explicit and implicit learning processes. *bioRxiv*
(2020).
40 Huang, V. S., Haith, A., Mazzoni, P. & Krakauer, J. W. Rethinking motor learning and savings in
adaptation paradigms: model-free memory for successful actions combines with internal
models. *Neuron* **70**, 787-801, doi:10.1016/j.neuron.2011.04.012 (2011).
41 Krakauer, J. W., Ghez, C. & Ghilardi, M. F. Adaptation to visuomotor transformations:
consolidation, interference, and forgetting. *J Neurosci* **25**, 473-478,
doi:10.1523/JNEUROSCI.4218-04.2005 (2005).
42 Sing, G. C. & Smith, M. A. Reduction in learning rates associated with anterograde interference
results from interactions between different timescales in motor adaptation. *PLoS Comput Biol* **6**,
doi:10.1371/journal.pcbi.1000893 (2010).
43 Della-Maggiore, V., Malfait, N., Ostry, D. J. & Paus, T. Stimulation of the posterior parietal cortex
interferes with arm trajectory adjustments during the learning of new dynamics. *J Neurosci* **24**,
9971-9976, doi:10.1523/JNEUROSCI.2833-04.2004 (2004).
44 Inoue, M. & Kitazawa, S. Motor Error in Parietal Area 5 and Target Error in Area 7 Drive
Distinctive Adaptation in Reaching. *Curr Biol* **28**, 2250-2262 e2253,
doi:10.1016/j.cub.2018.05.056 (2018).
45 Albert, S. T. & Shadmehr, R. Estimating properties of the fast and slow adaptive processes during
sensorimotor adaptation. *J Neurophysiol* **119**, 1367-1393, doi:10.1152/jn.00197.2017 (2018).

46   Browne, W. J. & Draper, D. A comparison of Bayesian and likelihood-based methods for fitting
multilevel models. *Bayesian analysis* **1**, 473-514 (2006).

47   Morel, P. *et al.* Long-term decoding of movement force and direction with a wireless
myoelectric implant. *J Neural Eng* **13**, 016002, doi:10.1088/1741-2560/13/1/016002 (2016).

48   Morel, P., Ulbrich, P. & Gail, A. What makes a reach movement effortful? Physical effort
discounting supports common minimization principles in decision making and motor control.
PLoS Biol **15**, e2001323, doi:10.1371/journal.pbio.2001323 (2017).

49   Rosenberg, L. *The effect of interocular distance upon operator performance using stereoscopic*
displays to perform virtual depth tasks. (1993).

50   Morel, P. Gramm: grammar of graphics plotting in Matlab. *The Journal of Open Source Software*
3, doi:10.21105/joss.00568 (2018).

51   Gelman, A., Lee, D. & Guo, J. Stan: A probabilistic programming language for Bayesian inference
and optimization. *Journal of Educational and Behavioral Statistics* **40**, 530-543 (2015).

52   Hoffman, M. D. & Gelman, A. The No-U-Turn sampler: adaptively setting path lengths in
Hamiltonian Monte Carlo. *J. Mach. Learn. Res.* **15**, 1593-1623 (2014).

53   Gelman, A. Prior distributions for variance parameters in hierarchical models (comment on
article by Browne and Draper). *Bayesian analysis* **1**, 515-534 (2006).

54   Vehtari, A., Gelman, A. & Gabry, J. Practical Bayesian model evaluation using leave-one-out
cross-validation and WAIC. *Statistics and computing* **27**, 1413-1432 (2017).

55   Holden, M. K. Virtual environments for motor rehabilitation: review. *Cyberpsychol Behav* **8**, 187-
211; discussion 212-189, doi:10.1089/cpb.2005.8.187 (2005).

56   Turolla, A. *et al.* Virtual reality for the rehabilitation of the upper limb motor function after
stroke: a prospective controlled trial. *J Neuroeng Rehabil* **10**, 85, doi:10.1186/1743-0003-10-85
(2013).

57   Deutsch, J. E., Merians, A. S., Adamovich, S., Poizner, H. & Burdea, G. C. Development and
application of virtual reality technology to improve hand use and gait of individuals post-stroke.
Restor Neurol Neurosci **22**, 371-386 (2004).

58   Pisella, L., Rode, G., Farne, A., Tilikete, C. & Rossetti, Y. Prism adaptation in the rehabilitation of
patients with visuo-spatial cognitive disorders. *Curr Opin Neurol* **19**, 534-542,
doi:10.1097/WCO.0b013e328010924b (2006).

A

RIGHT-EYE
MONITOR

PARALLEL HAPTIC
MANIPULATOR

ANGLED
MIRRORS

LEFT-EYE
MONITOR

B

Hold Fixation

Spatial Cue

Reach

C

z [mm]

y [mm]

x [mm]

D

120 trials
baseline

240 trials
perturbation

240 trials
washout

Horizontal

Coronal

Sagittal

Perturbed Planes

Figure 1

Figure 2

Figure 3

Figure 4

Figure 5

Figure 6

All Subjects Sagittal perturbation

Supplementary Figure 1

Supplementary Figure 2

Supplementary Figure 3

Supplementary Figure 4