Statistical determinants of visuomotor adaptation in a virtual reality three-dimensional environment

E. Ferrea[1]*, P. Morel[1,4]*, J. Franke[1,2], A. Gail[1,2,3]

1 German Primate Center, Sensorimotor Group, Goettingen, Germany,
2 University of Goettingen, Georg-Elias-Mueller Institute of Psychology, Goettingen, Germany,
3 Bernstein Center for Computational Neuroscience, Goettingen, Germany
4 Univ. Littoral Côte d'Opale, Univ. Lille, Univ. Artois, ULR 7369 - URePSSS - Unité de Recherche Pluridisciplinaire Sport Santé Société, F-59140 Dunkerque, France

*equal contribution

Corresponding author: eferrea@dpz.eu

Abstract

Recent advances in virtual reality (VR) technology allow motor control studies to investigate movement variety in a controlled 3D environment. However, visuomotor adaptation paradigms for arm reaches in a 3D space are still scarcely investigated. Elucidating these adaptations is important to further our understanding, predicting and hence, rehabilitating everyday movement behavior in humans suffering from motor deficits. We test how well optimal integration theory that was extrapolated from 1D and 2D settings extends to movements in 3D space; specifically, if and how a subject's variability in planning and sensory perception will influence motor adaptation. We test this hypothesis without introducing artificial (experimentally induced) variability. Instead, we exploit the natural anisotropy in sensory performance along different dimensions relative to the body. We use a virtual reality (VR) setup to compare the subject's adaptation of their 3D movements to perturbations applied separately in sagittal, coronal and horizontal planes. We found that subjects adapt best to perturbations in the coronal plane, i.e. when the depth component of the movement is unaffected, followed by sagittal then horizontal perturbations. To characterize how the adaptation rate selectively depends on planning and sensory uncertainty along different body axes, we developed a novel hierarchical two-state space model using Bayesian modeling via Hamiltonian Monte Carlo procedures to fit visuomotor adaptation profiles. Our

hierarchical model reconstructs learning parameters from surrogate data better than a state-of-the-art

expectation-maximization (EM) algorithm. Modeling revealed that differences in adaptation rate of

movement among the three planes are explained from the Kalman gain, i.e. the relative variability

associated with planning and sensory perception. The developed method allowed us to show that the

motor behavior is in line with optimal integration theory when considering adaptation rate variation

between the different planes.

39   Author Summary

The process of neurorehabilitation in human patients suffering from motor deficits could be considered

as a process of relearning or re-adapting motor skills. Virtual reality is already used to drive motor

rehabilitation. However, the majority of motor learning theories were developed under one or two-

dimensional experimental paradigms and it is assumed that the general findings apply to motor control

in three-dimensional movements. To test whether these theories are also compatible with more

naturalistic movements performed in a three-dimensional space, we used a new statistical method to

identify the dynamics of motor adaptation in virtual reality. We found that in a three-dimensional

environment, there are differences in how the subject will correct and adapt their movement based on

which orientation relative to the body the movement needs to be corrected. These differences come

from the statistical variability associated with unperturbed movements in the different directions. These

findings provide clues on how therapeutic regimens in virtual reality should be adapted, i.e. physical

reorientation of the body, to improve rehabilitation of certain movements.

53   Introduction

Research on visuomotor adaptation of limb movements is mostly performed in one or two-dimensional

reach-movement settings (Mazzoni and Krakauer 2006, Krakauer 2009, Wolpert, Diedrichsen et al. 2011,

Taylor, Krakauer et al. 2014, McDougle, Bond et al. 2015, Morehead, Qasim et al. 2015, Leow, de Rugy

et al. 2016). However, these theories, still need to be tested in less constrained 3D settings (Anglin,

Sugiyama et al. 2017). It is unknown, for example, if and how spatial anisotropy in sensory perception

translates into motor adaptation anisotropy. Here, we test the prediction of optimal integration (OI)

theory that natural variability in sensory measurement between different dimensions relative to the

body determines the corresponding motor adaptation rates (Scott 2004, Shadmehr and Krakauer 2008,

Diedrichsen, Shadmehr et al. 2010, Shadmehr, Smith et al. 2010, Friston 2011).

Virtual reality (VR) setups allow humans to perform a rich variety of movements in controlled 3D

experimental conditions (Choi, Lee et al. 2018) and can be flexibly used in laboratory settings to test

motor control theories. Among these theories, OI theory is the dominant principle to explain motor

adaptation. It proposes that the nervous system, according to a specified goal, optimally combines visual

and proprioceptive information with a forward prediction of the body's state (Wolpert and Ghahramani

2000, Ernst and Banks 2002, van Beers, Baraduc et al. 2002, Kording and Wolpert 2004) to control

movements and to correct errors. During motor adaptation, this forward model is updated to reduce the

sensory prediction error arising from a mismatch between its prediction and the sensory feedback.

Variability in sensory feedback or other variability in this closed-loop process thus affects the observed

rate of adaptation.

Variability arises due to the stochastic nature of neuronal processes in the sensorimotor transformations

(i.e., the planning and execution of the movement), referred to as "planning variability", and directly

affects the reliability of the forward model prediction (Korenberg and Ghahramani 2002, Cheng and

Sabes 2006, Cheng and Sabes 2007, van Beers 2009, Morel and Baraduc 2010). Other sources of

variability are directly attributed to the visual or proprioceptive feedback and affect the estimate of the

effector position (hereafter "measurement variability") (Kording and Wolpert 2004, Burge, Ernst et al.

2008, Wei and Kording 2010).

According to OI theory, during adaptation, a statistically optimal solution for the update of the forward

model is the Kalman filter (Kalman 1960), where corrections are weighed by the measurement

variability and planning variability (Ghahramani, Wolpert et al. 1997, Baddeley, Ingram et al. 2003,

Burge, Ernst et al. 2008). Higher variability in the forward model (high planning variability) would

increase the Kalman gain and allow faster corrections of the experienced error, whereas a higher

variability in the sensory feedback (high measurement variability) would determine a lower gain and

therefore a slower adaptation. Previous studies found that human behavior approaches that of an

optimal learner (Burge, Ernst et al. 2008, Wei and Kording 2010, He, Liang et al. 2016, van der Vliet,

Frens et al. 2018) showing that adaptation rate positively correlates with the Kalman gain calculated

from the planning and measurement variabilities. Recently, it was found that individual differences in

the rate of motor adaptation are largely explained by individual differences in the Kalman gain (van der

Vliet, Frens et al. 2018).

Here, we ask if adaptation in a three-dimensional space simulated in a virtual reality environment would

still reflect an optimal learner model. Importantly, we aim to confirm these models by leveraging the

existing differences in sensorimotor variabilities in the different planes of space, without needing to

introduce artificial variability (van Beers, Sittig et al. 1999, Wei and Kording 2010).

Current experiments and models propose that sensorimotor adaptation is supported by two learning

processes, which act on different timescales: one fast adapting and fast forgetting and one slow

adapting and slow forgetting (Smith, Ghazizadeh et al. 2006, Wolpert, Diedrichsen et al. 2011).

Compared to one-state models (Cheng and Sabes 2006, Cheng and Sabes 2007, van Beers 2009), two-

state models explain motor adaptation as a combination of explicit and implicit learning mechanisms,

where explicit learning allows fast adaptation and implicit learning changes performance more slowly

(Taylor, Krakauer et al. 2014, Huberdeau, Krakauer et al. 2015, McDougle, Bond et al. 2015). Two-stage

models better explain phenomena like savings (improved learning due to repeated exposure) (Krakauer,

Ghez et al. 2005, Huang, Haith et al. 2011, Avraham, Morehead et al. 2020) and anterograde

interference (negative influence of past learning on future learning, (Sing and Smith 2010, Leow, de

Rugy et al. 2016) that were found to be partially correlated with explicit learning (Morehead, Qasim et

al. 2015). Moreover, neurophysiological evidence of two-state learning dynamics was found in humans

and monkeys (Della-Maggiore, Malfait et al. 2004, Inoue and Kitazawa 2018). We fit fast- and slow-state

processes during sensorimotor adaptation (Smith, Ghazizadeh et al. 2006) to estimate the adaptation

rates. By considering the stochastic nature of error-based learning, we can independently estimate the

measurement and planning uncertainty from the empirical movement data during a 3D adaptation task,

with different perturbation planes oriented differently relative to the body. Stochastic modeling has

been shown to better identify the time course of the hidden states (Albert and Shadmehr 2018). We

used Bayesian inference via Hamiltonian Markov chain Monte Carlo sampling (referred to as

Hamiltonian Monte Carlo, HMC) to implement a novel multilevel hierarchical version of the two-state

space model fitting. We evaluated the hierarchical model and compared it to another state-of-the-art

model performing Bayesian inference via an expectation-maximization (EM) algorithm (Albert and

Shadmehr 2018) without a hierarchical structure. We show that HMC allows for a better extraction of

data on the two underlying motor learning states and the planning and measurement variabilities. Using

hierarchical HMC models, we confirm that two-state models better explain our experimental three-

dimensional data than single-state models. We, therefore, use the two-state hierarchical HMC model to

test whether differences in adaptation dynamics can be found between movements and perturbations

of different directions relative to the subject's own body and whether these differences comply with OI

theory.

Materials and Methods

Subjects

Data were collected from 26 healthy subjects (age range 20-32, 10 females, 16 males). The study was performed under institutional guidelines for experiments with humans, adhered to the principles of the Declaration of Helsinki, and was approved by the ethics committee of the Georg-Elias-Mueller-Institute for Psychology at the University of Goettingen. All the subjects were right-handed, had normal or corrected-to-normal vision and received financial compensation for their participation. Subjects gave written consent to participate and received detailed written instructions for the task. They were asked to paraphrase the instructions in their own words to make sure they understood the task. The experiment was carried out in one single appointment that lasted between 2.5 and 3 hours, depending on the subjects' freely chosen breaks among blocks (see later).

Virtual Reality Setup

Subjects sat in a darkened room (all distractions and light were removed). The temperature was ambient, there was no noise, the 26 experiments were done individually at different times of the day and on different days. Visual displays on two monitors were controlled by a customized C++ software similar to what was described in previous studies (Morel, Ferrea et al., 2016, Morel, Ulbrich et al., 2017). The images of the two monitors (one for each eye, BenQ XL2720T, 27-inch diagonal, 1920x1080, 60 Hz refresh rate, BenQ, Taepei, Taiwan) were reflected by two semi-transparent mirrors. (75 x 75 mm, 70/30 reflection/transmission plate beamsplitter, covered from the back to block transmission; stock #46-643, Edmund Optics Inc., Barrington, New Jersey, United States) that were angled 45° relative to the two monitors on each side of the subject (Fig. 1A). The two screens render a three-dimensional view of virtual objects on a dark background. To accommodate test subject ergonomy, we tilted the monitors downward by 30°. This ensured that arm movements in the physical space could be carried out in an

ergonomic posture in front of the body while the virtual representation (the cursor) of the hand was still

aligned with the actual hand position and the virtual cube centered on the axis of gaze.

In the rest of the paper, we describe orientation relative to the tilted head of the subject and workspace,

not according to true horizontal and vertical. To optimize the perception of the virtual workspace for

each subject, the inter-pupillary distance was measured (range:51 to 68 mm, mean = 59.48 mm) and the

3D projection was modified in the custom-made software accordingly. This has been shown to benefit

depth perception, reduce image fusion problems and reduce fatigue in participants (Rosenberg 1993).

Subjects performed controlled arm movements in the 3D environment. For this, they moved a robotic

manipulator (delta.3, Force Dimension, Nyon, Switzerland) with their dominant hand to place the 3D

cursor position into visual target spheres. The manipulator captured the hand position at (sampling

frequency = 2 kHz with a 0.02 mm resolution). Since subjects could neither see their hand nor the robot,

a cursor (yellow sphere, 6 mm diameter) indicated the virtual representation of the robot handle and

therefore the hand position (Fig1B).

Behavioral task

Subjects performed a reaching-out task from a central fixation point to one of eight potential target

positions (grey sphere, 25 mm diameter) arranged at the vertices of a 10 cm-sided cube centered on the

fixation point (Fig. 1B-C). Each subject completed three blocks with breaks in between. One block

consisted of 600 successful trials: 120 baseline trials, then 240 perturbed trials, and 240 washout trials

again without a perturbation (Fig. 1D). Each block lasted between 20 to 25 minutes, depending on the

performance of the subject. Breaks between blocks were adjusted according to the subject's needs and

usually lasted between 10 to 15 minutes. Before the actual experiment, a short training session was run

to make subjects comfortable with the three-dimensional environment and to ensure a correct

understanding and execution of the task.

At the beginning of each trial, subjects moved the cursor (co-localized with the hand position) into the

central fixation sphere (semitransparent grey, 25 mm diameter) and held the cursor there for 200 ms

("hold fixation"; Fig. 1B). After this holding period, one of the eight potential targets (grey, 8 mm

diameter) was briefly highlighted by a spatial cue (semitransparent grey sphere of 25 mm diameter,

centered on the target). The corners of the cube, and hence also the target, remained visible after the

cue stimulus disappeared to allow precise localization of the target in the 3D space. The size of the

spatial cue corresponded to the eligible area in which the movement had to end to be considered

successful. The spatial cue remained visible for 300 ms and then disappeared together with the fixation

sphere. This disappearance served as a GO signal for the subjects. Subjects then had 500 ms time to

leave the central fixation point and begin their hand movement towards the target. For successful

completion of the trial, it was sufficient that the cursor completely entered the target sphere, without

the need to stop inside the eligible area. Success or failure was indicated by sound signals: high-pitch for

success, low-pitch for failure. A trial was aborted if subjects had not left the starting point 500 ms after

the GO signal, if the movement was stopped (speed below 3cm/s) at any point outside the target area or

lasted longer than 10 seconds. After each trial, subjects could immediately start a new trial by moving

the cursor back to the starting position.

Within each block, we applied a 2D visuomotor perturbation to the 3D position of the cursor, i.e. a

perturbation which affected the cursor position sequentially to the xy-coordinate and then to the yz- or

xz-coordinates, respectively. For every perturbation, one out of the three dimensions was left

unperturbed, corresponding to the axis of rotation for the perturbation. In the perturbed trials, the

workspace was rotated by 30 degrees counterclockwise around either the x (rotation in the sagittal

plane), y (rotation in the horizontal plane) or z (rotation in the coronal plane) axes in each of the three

blocks (Fig. 1D). The rotation was applied in each block to one of the three planes. As proof of concept,

we verified that the projections of the trajectories on the perturbed planes look similar (Fig. 2A). The

order of the blocks (perturbation types) and thereby the rotated axes were controlled over the

experiment using stratified randomization between subjects. This should prevent potential effects of

fatigue or interference between blocks.

In both blocks, the subjects conducted the same movements in terms of starting and end positions. We

chose the corners of a cube as targets since any movement from the center of the cube to a corner

always is a diagonal movement that is composed of equally large x-, y- and z-components. Therefore,

the same target movement can be subjected to perturbations in each of the three planes parallel to the

surfaces of the cube. This allowed us to compare perturbations in different body-centered dimensions

without changing movement start and end positions, thereby avoiding potentially confounding effects

of posture.

Within each block of trials, the order of the targets was pseudo-randomized such that all eight targets

were presented within each set of eight successful trials. These 8-trial sets counted as epochs and the

model fitting analysis was carried out on epochs rather than on single trials.

Data preprocessing

Hand position data was acquired by sampling the manipulator position at 2 kHz and stored for offline

analysis performed in MATLAB® R2018a (MathWorks, Inc., Natick, Massachusetts, United States). Data

plots were generated with gramm, a MATLAB plotting library developed by the first co-author (Morel

2018). Trajectories were aligned in time from the start of the movement, defined as a speed increase

above 3 cm/s, to when the hand reached the target, and resampled in 50 time steps so that each

trajectory was normalized in duration.

To calculate the spatial deviation of the hand position for each perturbed plane independent of target

direction, the trajectory of each trial was projected on the axis orthogonal to the center-to-target

direction and laying in the plane of the applied perturbation (Fig. 2B, perturbed dimension). For each

subject, each trajectory and each specific block, the mean baseline trace was subtracted to each

trajectory to remove any trajectory bias (non-straight movements). Figure 2C (middle and bottom panel)

shows, for one example subject, the average of the projected trajectories at baseline, during the first 8

trials (early adaptation) and the last perturbation trials (late adaptation) for all three perturbed planes.

For our analysis, we considered the angle at half of the trajectory (Fig. 2C) that is indicative of the

intended direction, which we expect to change over the course of adaptation.

Fitting model and procedure

Existing tools for fitting adaptation models (Albert and Shadmehr 2018, van der Vliet, Frens et al. 2018)

can only estimate parameters from single experimental runs (changes over repeated trials in one task

condition and one subject) despite the often hierarchical nature of the experiment (repeated trials

interleaved with multiple conditions, multiple subjects). This is particularly problematic for two-state

models due to their low identifiability (see results).

To get more reliable estimates of subject-level and population-level learning parameters, we developed

a hierarchical-model version of single-state and two-state models of adaptation. For this, we used the

probabilistic programming language Stan (Gelman, Lee et al. 2015), through its MATLAB interface. Stan

allowed us to perform Bayesian inference with its implementation of a Hamiltonian Markov chain

Monte Carlo using a NUTS sampler algorithm (Hoffman and Gelman 2014).

The underlying trial-by-trial adaptation model for the movement angle corrections is the following. For

the trial n in subject j and perturbation plane p, the measured movement angle $y_{jp}(n)$ is:

$$y_{jp}(n) = x_{jp}(n) + \varepsilon_{u,jp}(n) \quad (1)$$

242   With $x_{jp}(n)$ being the hidden internal state (aiming angle) and $\varepsilon_{u,jp}(n)$ the measurement noise of the

243   movement due to limited sensory accuracy of the agent, described by a normal distribution with zero

244   mean: $\varepsilon_{u,jp}(n) \sim N(0, \sigma_{u,jp})$. The internal state depends on the previous state, with retention **A**, and

245   the error e at the previous trial, with learning rate **B**. The state update is affected by a planning noise (or

246   state update error) $\varepsilon_x(n)$, which gives us the following:

$$x_{jp}(n+1) = A_{jp}x_{jp}(n) + B_{jp}e_{jp}(n) + \varepsilon_{x,jp}(n) \quad (2)$$

250   In the single-state model, A_{jp} and B_{jp} are positive scalars, and $\varepsilon_{x,jp}(n) \sim N(0, \sigma_{x,jp})$. For the two-state

251   model:

$$A_{jp} = \begin{bmatrix} a_{s,jp} & 0 \\ 0 & a_{f,jp} \end{bmatrix} \text{ with constrains } a_{s,jp} > a_{f,jp} > 0$$

$$B_{jp} = \begin{bmatrix} b_{s,jp} \\ b_{f,jp} \end{bmatrix} \text{ with constrains } b_{f,jp} > b_{s,jp} > 0$$

$$\varepsilon_{x,jp}(n) \sim N\left(\begin{bmatrix} 0 \\ 0 \end{bmatrix}, \begin{bmatrix} \sigma_{x,jp} & 0 \\ 0 & \sigma_{x,jp} \end{bmatrix}\right)$$

In our mixed-model, all subject and plane-level parameters: $\sigma_{u,jp}$, $a_{s,jp}$, $a_{f,jp}$, $b_{s,jp}$, $b_{f,jp}$, $\sigma_{x,jp}$ were

drawn from population-level normal distributions, e.g. for $a_{s,jp}$ we define $a_{s,jp} \sim N(\mu_{a_s,p}, \sigma_{a_s})$. Here,

$\mu_{a_s,p}$ and σ_{a_s} are population-level hyper-parameters, corresponding to the population (between-

subject) average of the slow retention for perturbation plane p and the population standard deviation of

the slow retention.

To keep the model simple, we did not include common per-subject offsets in the average hyper-

parameters across planes; in other words, the model we used did not take into account the fact that the

same subjects participated in experimental runs with different perturbed planes. A variation of the

model which permitted per-subject offsets yielded equivalent results (data not shown).

Bayesian inference requires priors for the hyper-parameters, which were chosen wide to not constrain

the model. Retention average hyper-parameter ($\mu_{a_s,p}$, $\mu_{a_f,p}$ in the two-state model and $\mu_{A,p}$ in the

single-state model) priors were $\sim N(0,9)$, learning rate average ($\mu_{b_s,p}$, $\mu_{b_f,p}$ and $\mu_{B,p}$) priors were

$\sim N(1,9)$, and their population standard deviation hyper-parameter ($\sigma_{a_s}, \sigma_{a_f}, \sigma_{b_s}, \sigma_{b_f}$ and σ_A, σ_B) priors

were half-Cauchy distributions (location = 0, scale = 5) (Gelman 2006). Priors of the population average

and standard deviation hyper-parameters of the measurement and planning noise ($\mu_{\sigma_x,p}, \mu_{\sigma_u,p}$ and

$\sigma_{\sigma_x}, \sigma_{\sigma_u}$) were half-Cauchy distributions (location = 0, scale = 15). The conclusions from the model fitting

do not critically depend on the exact choice of any of these parameters.

Steady-state Kalman gain

From the variances of the noise processes, we calculated the steady-state Kalman gain, as derived by

Burge and colleagues (Burge, Ernst et al. 2008). In short, by introducing the term:

$\sigma_{X_t^+}^2 = \dfrac{-\sigma_x^2 + \sqrt{(\sigma_x^2)^2 + 4\sigma_x^2 \sigma_u^2}}{2}$ (4)

The Kalman gain (K) is calculated as follow:

$K = \dfrac{\sigma_{X_t^+}^2 + \sigma_x^2}{\sigma_{X_t^+}^2 + \sigma_u^2 + \sigma_x^2}$ (3)

Validation of fitting procedure

To validate our hierarchical Bayesian fitting procedure, we compared it to non-hierarchical fitting

procedures applied to surrogate data sets. For this, we generated N = 100 artificial experimental runs

using the two-state model with the same number of baseline, perturbation, and washout trials as in our

experiment. For each simulation, each parameter was drawn from a random normal distribution

approaching the values we observed in our data (table 1). We then compared the accuracy of parameter

estimations from different models, namely an EM algorithm (Albert and Shadmehr 2018) and a non-

hierarchical and a hierarchical HMC model.

Table 1

Random parameter distributions

$$a_s \sim N(0.93,0.03)$$

$$a_f \sim N(0.55,0.2)$$

$$b_s \sim N(0.06,0.04)$$

$$b_f \sim N(0.18,0.08)$$

$$\sigma_x \sim N(1.5,1)$$

$$\sigma_u \sim N(6,3)$$

Table 1. Distributions of parameters in the surrogate data approaching the values observed in the experiments.

Results

The subjects performed the task (three conditions: baseline, perturbation and washout) with a high success rate in all perturbed planes (number of correct trials/number of total trials during movement phase > 99%). A generalized linear mixed effect model with a binomial distribution was used to test the effect of the perturbation in the different planes (fixed effect) on the success rate with the subjects as random effect. With the sagittal plane as intercept, there was no significant effect on the slope for the horizontal plane (tstat = 1.5477, p = 0.1217) and no significant effect for the slope of the coronal plane (tstat = 1.3976, p = 0.16223).

To test differences among the level of adaptation reached by the subjects, a one-way between-subjects ANOVA was conducted to compare the effects of the perturbed plane over the final adaptation level (calculated as the average of the adaptation profile over the last 4 epochs). We found that the subjects adapt differently to the perturbations depending on the plane of rotation. The final level of adaptation

was significantly higher for perturbations in the coronal plane compared to the sagittal plane (pcor-sag =

7.6E-05) and horizontal plane (pcor-hor = 1.0 E-08) (Fig. 3A). Moreover, perturbations in the sagittal

plane provide stronger adaptation than perturbations in the horizontal plane (psag-hor = 0.004) (Fig.

3A).

To understand the underlying dynamic of the differences in adaptation, we modeled adaptation behavior

in the three different visuomotor perturbation planes with a two-state model, which separately

identified the slow and fast processes underlying adaptation. While our hierarchical Bayesian model fits

data across conditions and subjects (see Methods), Figure 3B shows the fitted curves for one example

subject performing one adaptation condition. We also evaluated whether in such a three-dimensional

task, a two-state model fits the data better than a single-state model. The single-state model shows

larger root-mean-square residuals when subtracting the modeled adaptation trajectory from the

observed trajectory (Fig. 3C, paired t-test, p = 6.6e-16). To take into account the number of free

parameters when comparing models, we additionally computed the widely applicable information

criterion (WAIC), an approximation of cross-validation for Bayesian procedures (Vehtari, Gelman et al.

2017). The two-state model shows a lower WAIC compared to the single-state model (3.54E+04 and

3.58e+04, respectively), confirming a better fit of the two-stage model.

To validate our new hierarchical fitting procedure, we tested whether model parameters are better

reconstructed by our two-state Bayesian HMC hierarchical model compared to a state-of-the-art EM

algorithm (Albert and Shadmehr 2018). We also compared the HMC hierarchical model with the

corresponding non-hierarchical HMC model. For this, we generated surrogate adaptation datasets from

multiple two-state models with randomly sampled parameters (see Methods) and used the three

algorithms to retrieve the randomly sampled parameters. The hierarchical model better reconstructs all

parameters (error is smaller and correlation is higher)(Fig. 4).

Optimal integration theory (OI) predicts that the rate of adaptation correlates with the weighing

between internal estimation and external sensory information for assessing the state of the system. A

learner optimally integrating these two types of information approximates a Kalman filter that combines

them depending on their respective uncertainties (variabilities). If planning (internal estimate) variability

is high and measurement (sensory information) variability low during adaptation, the experienced error

will be given credibility, and therefore faster learning will happen. In the opposite case, the learner

tends to disregard the experienced error and corrections would happen slowly. To test if this mechanism

can explain the observed differences between the perturbed planes in our experiment, we correlated

planning noise and measurement noise variabilities with the slow learning rate B_s for each experimental

run in our dataset (Fig. 5B).

Correlations between planning noise and the learning rate as well as between measurement noise and

learning rate were low (respective R^2 : 0.13 and 0.11), but with a trend consistent to the OI predictions,

i.e. low measurement noise and high planning noise correlate with higher slow learning rate. When

combining the contribution for each subject of the two noises into an estimate of a Kalman gain, the

slow learning rate was explained much better (R^2 between K and B_s : 0.48), with a high Kalman gain

being associated with high learning rate (Fig. 5B, right). Notably, this relationship between Kalman gain

(K) and slow learning rate (B_s) is only created by the different average values for K and B_s between the

perturbation planes. This means, the slow learning rate is mostly explained by the plane of the

workspace in which the perturbation is applied ($R^2 = 0.94$), while it does not correlate with the Kalman

gain variation across the individual subjects within a perturbation condition.

Discussion

Psychophysical experiments studying visuomotor adaptation to date mainly used one or two-

dimensional movement paradigms to derive theories for motor learning settings (Mazzoni and Krakauer

2006, Krakauer 2009, Wolpert, Diedrichsen et al. 2011, Taylor, Krakauer et al. 2014, McDougle, Bond et

al. 2015, Morehead, Qasim et al. 2015, Leow, de Rugy et al. 2016). Natural movement is rarely

constrained in this way and generalization of core theoretical concepts of motor control to

unconstrained three-dimensional movements has rarely been tested. Motor learning studies are

informative for motor rehabilitation protocols for patients that need to relearn or re-adapt existing

motor schemes and these patients will necessarily perform their movements in a three-dimensional

environment (Deutsch, Merians et al. 2004, Holden 2005, Pisella, Rode et al. 2006, Turolla, Dam et al.

2013). Therefore, we tested if observations and model assumptions about motor learning in one or two

dimensions still hold true for largely unconstrained movements in three-dimensional space. We show

that visuomotor adaptation under 3D stereoscopic vision depends on the plane in which a 2D

visuomotor rotation perturbation is applied. Subjects adapted best to perturbations in the coronal plane

followed by sagittal then horizontal. The rate of slow learning correlated well with the Kalman gain

variation across perturbation conditions, but not across subjects, as revealed by our novel hierarchical

Bayesian HMC modeling of the data. These results show that important aspects of OI theories of motor

control derived from 2D movements generalize to the largely unconstrained 3D movements studied here

but do not extend to the individual level for any of the applied perturbations.

A novel two-state hierarchical HMC algorithm for precise estimation of motor learning parameters

We developed a novel HMC Bayesian fitting procedure with a multilevel hierarchical structure to take

into account effects from multiple subjects performing a motor adaptation task in three different

learning conditions, i.e., different planes relative to the body were perturbed. Naturally, such a

hierarchical approach shows lower goodness-of-fit to single-subject adaptation curves than algorithms

that focus on single-subject data. But multi-subject experiments are typically designed to determine the

effects of experimental variations on the motor learning behavior independent of test subject. Hence, it

is most important to best estimate the underlying learning parameters.

For the current experimental design, our procedure is better able to reconstruct actual model

parameters than a state-of-the-art EM fitting algorithm (Albert and Shadmehr 2018) or a non-

hierarchical Bayesian HMC model, as revealed from the surrogate testing. This is due to the low

identifiability of such two-state models for relatively short adaptation experiments comprising only a few

dozen or even hundreds of trials per condition. The low identifiability is a result of random fluctuations

in the shape of the adaptation curve and are easily associated with various learning parameters (see, for

example, the outliers in Fig. 4). In the hierarchical model. Each parameter is sampled from a population-

level distribution, the parameters of which are also part of the model. This makes extreme values for the

reconstructed parameter less likely.

Comparison with single-state model

Using our hierarchical model, we show that a two-state model fits the data significantly better than a

single-state model. The two-state model is well established for subjects performing in a 2D environment

(Smith, Ghazizadeh et al. 2006, Wolpert, Diedrichsen et al. 2011) and better explains learning

mechanisms such as savings and anterograde interference in 2D settings (Huberdeau, Krakauer et al.

2015). As previously hypothesized (Taylor, Krakauer et al. 2014, McDougle, Bond et al. 2015), the fast

learning process is assumed to be associated to an explicit process and the slow learning process to an

implicit process, both with anatomically distinct associated brain areas (Della-Maggiore, Malfait et al.

2004, Shadmehr, Smith et al. 2010, Taylor, Krakauer et al. 2014). While it is plausible to assume that an

interplay of explicit and implicit learning mechanisms is independent of the dimensionality of the task, to

our knowledge, the two-state model to date has not been demonstrated for adaptation paradigms

involving 3D movements. The fact that, in a 3D setting, we found a two-state model to better fit the

adaptation data than a single-state model without introducing paradigms that manipulate explicit

learning mechanisms (like withholding the visual feedback (Wei and Kording 2010)), might indicate that

the explicit learning component in our three dimensional-paradigm is more pronounced than in classic

two-dimensional paradigms.

Differences in planning and measurement noises are related to learning rate

Differences in the slow and fast learning rates between the planes are associated with different

adaptation levels in our data. The coronal plane yielded the lowest measurement noise and subjects

adapted fastest to perturbations (Fig.5B). It is important to note that in our model, this measurement

noise represents the reliability of the subject measurements of the cursor position. This is likely due to

the fact that in our setup, subjects have to rely mainly on visual stereoscopy to estimate depth. Visual

localization is less precise in depth (van Beers, Wolpert et al. 2002, Gepshtein and Banks 2003) and

depth is not perturbed by a rotation in the coronal plane. On the other hand, rotations in the sagittal and

horizontal plane both resulted in cursor depth changes compared to baseline. Indeed, other studies also

showed that subjects tend to adapt worse when the sensory noise was increased by practically blurring

the error feedback (Kording and Wolpert 2004, Burge, Ernst et al. 2008, Wei and Kording 2010).

However, not all differences in the final adaptation or learning rates levels can simply be explained by

perceptual differences: we also found that perturbations in the horizontal plane were the most difficult

to learn, despite having measurement variability levels close to those of the coronal plane (Fig 5B-

measurement variability). In horizontal perturbations, subjects show the lowest level of planning

variability (Fig5B-planning variability). This could potentially be explained in our experiment by the

observation that in everyday life, humans tend to perform precise visually-guided upper-limb movement

more frequently in the horizontal plane (writing, typing, cooking). Our findings agree with other studies

that found that subjects adapt faster when state estimation uncertainty is increased (Burge, Ernst et al.

2008, Wei and Kording 2010).

When looking at all three planes of perturbation, the learning rate cannot be explained by the

measurement noise only or the planning noise only or by a linear combination of the two.

Optimal integration theory in 3D

Previous studies (Burge, Ernst et al. 2008, van Beers 2009, Wei and Kording 2010, He, Liang et al. 2016,

van der Vliet, Frens et al. 2018), provided evidence for the OI theory during visuomotor adaptation. They

showed that the planning component of motor noise correlates positively with the adaptation rate while

the measurement component correlates negatively, at least when the respective noise component

experimentally is kept constant. While the adaptation data from our 3D movements yielded similar

trends, the correlation of slow learning rate with either measurement- or planning-variability was weak.

For an optimal learner, the Kalman gain is indicative of the level of correction attributed to the

experienced error (Burge, Ernst et al. 2008, Wei and Kording 2010, He, Liang et al. 2016). This Kalman

gain positively correlates with the slow learning rate in our data, supporting the idea that subjects

optimally integrate the information relative to the internal state with experienced (visual) feedback.

However, and as opposed to what was suggested in previous studies (He, Liang et al. 2016, van der Vliet,

Frens et al. 2018), we observe the correlation between Kalman gain and slow learning rate only across

different perturbation conditions. Within each perturbation condition, there was no relationship

between Kalman gain and slow learning rate at the subject population level.

Conclusion

Here, we develop a novel HMC fitting procedure to correlate learning rates and noise levels estimated

with the same model and without the need to experimentally manipulating these error variabilities. By

applying this model to a sensorimotor adaptation task in 3D, we found that the rate of adaptation with

which subjects counteract applied visuomotor rotations, depends on the statistics of the combined

errors with which subjects plan and perceived movements, and these differ between different axes

relative to the body. This insight could be used in motor rehabilitation strategies by specifically targeting

the orientation of the body relative to the target while performing reaching movements to accelerate

learning.

Funding:

German Research Foundation (DFG, Germany, grant number FOR-1847-GA1475-B2). Received by AG.

German Research Foundation (DFG, Germany, grant number SFB-889). Received by AG.

Federal Ministry for Education and Research (BMBF, Germany, grant number 01GQ1005C). Received by

AG.

457
458

Figure Captions

Fig 1. A) Schematic representation of our virtual reality setup. The two angled mirrors reflect the image
from the two screens to the two eyes independently providing stereoscopic vision. The mirrors are
semitransparent to allow calibration of the virtual reality space with the real hand position. During the
experiments they were obscured from so that the subjects were not seeing the robotic manipulator or
their real hand but only the cursor overlapped it. B) Temporal structure of the task. Following a brief
holding period, the subject had to reach to one of eight targets arranged at the edges of a cube. The
cube is orientated relatively to the tilted head of the subject and workspace and not according to true
horizontal and vertical. C) The subjects reached from the center of the cube to one of the eight targets.
Here all baseline trajectories are simultaneously displayed. D) Temporal structure of each of the three
perturbation experiments. Following a baseline phase of 120 trials, a classical visuomotor perturbation
was applied for 240 trials followed by a washout of 240 additional trials. The rotation coordinate system
and the type of rotation are visualized below. The perturbation type was always a 30 degrees rotation of
the cursor around the sagittal, coronal or horizontal plane depending on the block. In the figure a
rotation in the horizontal plane is represented.

Fig 2. A) Example trajectories from one subject. Each row/color of the graph correspond to different
directions of rotations. The trajectories are projected on the plane perpendicular of the axis of rotation
for representation and analysis. The plot shows similarities across these trajectories when projected in

the plane of the applied perturbation. B) Transformation of the trajectories in the task relevant dimensions (perturbed dimension and center to target dimension). To compare data across tasks each trajectory was resampled and transformed in the new reference frame. At half of the trajectory the adaptation angle was calculated from the transformed dimensions and used for model fitting.C) examples of transformed trajectories from one subject during baseline, early adaptation and late adaptation

Fig 3. A) Final adaptation level for each plane. B) Examples of data fitted with one-state and two-states learning models. Black points represent the subject's data (average of angles at half-trajectory angle within 8-trial epochs) and the black dashed line the perturbation profile. Blue line: Single-state model. Orange line: two-state model (sum of the fast- and slow-states). Red lines: slow-state from the two-state model. Green lines: fast-state from the two-state model. C) Histogram of the RMSE values for all adaptation profiles (error between the actual data and the noiseless adaptation profiles) with the one-state and the two-states models.

Fig 4. Comparison of parameter estimation quality between our HMC hierarchical fitting procedure (orange), an HMC non-hierarchical fitting procedure (red) and a EM fitting procedure ((Albert and Shadmehr 2018) EM, blue). For each model parameter in randomly drawn two-state models we represent the error in parameter reconstruction (estimated parameter − drawn parameter) for each fitting procedure: histogram of the absolute error and average and 95% confidence intervals of the squared error. We also represent the correlation (average and 95%CI) between the estimated and drawn parameters.

Fig 5. Comparison of two-state model parameters between the perturbation planes. A) The colored lines represent the model parameter values obtained for all subjects (one line/color per subject : $\sigma_{u,jp}$, $a_{s,jp}$, $a_{f,jp}$, $b_{s,jp}$, $b_{f,jp}$, $\sigma_{x,jp}$) for the different perturbation planes. The error bars correspond to 95 % credible intervals (i.e. contain 95% of the posterior probability) for the population average hyper-parameters $\mu_{a_s,p}$, $\mu_{a_f,p}$, $\mu_{b_s,p}$, $\mu_{b_f,p}$, $\mu_{\sigma_x,p}$, $\mu_{\sigma_u,p}$. The steady-state Kalman gain K was computed from the posteriors of the measurement noise and planning noise. B) Relationships between the slow learning rate Bs and uncertainty related parameters: measurement noise variance, planning noise variance, and steady-state Kalman gain. Points correspond to individual subjects' parameters in the different rotation planes (coded by color). The correspondingly colored lines represent linear fits based on the subjects' parameter values within each plane. The grey line corresponds to a linear fit based on subjects' parameter values across all planes. The horizontal and vertical error bars correspond to 95 % credible intervals for the corresponding parameter population average hyper-parameters.

References

Albert, S. T. and R. Shadmehr (2018). "Estimating properties of the fast and slow adaptive processes during sensorimotor adaptation." J Neurophysiol **119**(4): 1367-1393.

Anglin, J. M., T. Sugiyama and S. L. Liew (2017). "Visuomotor adaptation in head-mounted virtual reality versus conventional training." Sci Rep **7**: 45469.

Avraham, G., J. R. Morehead, H. E. Kim and R. B. Ivry (2020). "Re-exposure to a sensorimotor perturbation produces opposite effects on explicit and implicit learning processes." bioRxiv.

Baddeley, R. J., H. A. Ingram and R. C. Miall (2003). "System identification applied to a visuomotor task: near-optimal human performance in a noisy changing task." J Neurosci **23**(7): 3066-3075.

Burge, J., M. O. Ernst and M. S. Banks (2008). "The statistical determinants of adaptation rate in human reaching." J Vis **8**(4): 20 21-19.

Cheng, S. and P. N. Sabes (2006). "Modeling sensorimotor learning with linear dynamical systems." Neural Comput **18**(4): 760-793.

Cheng, S. and P. N. Sabes (2007). "Calibration of visually guided reaching is driven by error-corrective learning and internal dynamics." J Neurophysiol **97**(4): 3057-3069.

Choi, W., J. Lee, N. Yanagihara, L. Li and J. Kim (2018). "Development of a quantitative evaluation system for visuo-motor control in three-dimensional virtual reality space." Sci Rep **8**(1): 13439.

Della-Maggiore, V., N. Malfait, D. J. Ostry and T. Paus (2004). "Stimulation of the posterior parietal cortex interferes with arm trajectory adjustments during the learning of new dynamics." J Neurosci **24**(44): 9971-9976.

Deutsch, J. E., A. S. Merians, S. Adamovich, H. Poizner and G. C. Burdea (2004). "Development and application of virtual reality technology to improve hand use and gait of individuals post-stroke." Restor Neurol Neurosci **22**(3-5): 371-386.

Diedrichsen, J., R. Shadmehr and R. B. Ivry (2010). "The coordination of movement: optimal feedback control and beyond." Trends Cogn Sci **14**(1): 31-39.

Ernst, M. O. and M. S. Banks (2002). "Humans integrate visual and haptic information in a statistically optimal fashion." Nature **415**(6870): 429-433.

Friston, K. (2011). "What is optimal about motor control?" Neuron **72**(3): 488-498.

Gelman, A. (2006). "Prior distributions for variance parameters in hierarchical models (comment on article by Browne and Draper)." Bayesian analysis **1**(3): 515-534.

Gelman, A., D. Lee and J. Guo (2015). "Stan: A probabilistic programming language for Bayesian inference and optimization." Journal of Educational and Behavioral Statistics **40**(5): 530-543.

Gepshtein, S. and M. S. Banks (2003). "Viewing geometry determines how vision and haptics combine in size perception." Curr Biol **13**(6): 483-488.

Ghahramani, Z., D. M. Wolpert and M. I. Jordan (1997). Computational models of sensorimotor integration. Advances in Psychology. P. Morasso and V. Sanguineti, North-Holland. **119**: 117-147.

He, K., Y. Liang, F. Abdollahi, M. Fisher Bittmann, K. Kording and K. Wei (2016). "The Statistical Determinants of the Speed of Motor Learning." PLoS Comput Biol **12**(9): e1005023.

Hoffman, M. D. and A. Gelman (2014). "The No-U-Turn sampler: adaptively setting path lengths in Hamiltonian Monte Carlo." J. Mach. Learn. Res. **15**(1): 1593-1623.

Holden, M. K. (2005). "Virtual environments for motor rehabilitation: review." <u>Cyberpsychol Behav</u> **8**(3):
187-211; discussion 212-189.
Huang, V. S., A. Haith, P. Mazzoni and J. W. Krakauer (2011). "Rethinking motor learning and savings in
adaptation paradigms: model-free memory for successful actions combines with internal models."
<u>Neuron</u> **70**(4): 787-801.
Huberdeau, D. M., J. W. Krakauer and A. M. Haith (2015). "Dual-process decomposition in human
sensorimotor adaptation." <u>Curr Opin Neurobiol</u> **33**: 71-77.
Inoue, M. and S. Kitazawa (2018). "Motor Error in Parietal Area 5 and Target Error in Area 7 Drive
Distinctive Adaptation in Reaching." <u>Curr Biol</u> **28**(14): 2250-2262 e2253.
Kalman, R. E. (1960). "A New Approach to Linear Filtering and Prediction Problems." <u>Journal of Basic</u>
<u>Engineering</u> **82**(1): 35-45.
Kording, K. P. and D. M. Wolpert (2004). "Bayesian integration in sensorimotor learning." <u>Nature</u>
427(6971): 244-247.
Korenberg, A. and Z. Ghahramani (2002). "A Bayesian view of motor adaptation." <u>Cahiers de Psychologie</u>
<u>Cognitive</u> **21**.
Krakauer, J. W. (2009). "Motor learning and consolidation: the case of visuomotor rotation." <u>Adv Exp</u>
<u>Med Biol</u> **629**: 405-421.
Krakauer, J. W., C. Ghez and M. F. Ghilardi (2005). "Adaptation to visuomotor transformations:
consolidation, interference, and forgetting." <u>J Neurosci</u> **25**(2): 473-478.
Leow, L. A., A. de Rugy, W. Marinovic, S. Riek and T. J. Carroll (2016). "Savings for visuomotor adaptation
require prior history of error, not prior repetition of successful actions." <u>J Neurophysiol</u> **116**(4): 1603-
1614.
Mazzoni, P. and J. W. Krakauer (2006). "An implicit plan overrides an explicit strategy during visuomotor
adaptation." <u>J Neurosci</u> **26**(14): 3642-3645.
McDougle, S. D., K. M. Bond and J. A. Taylor (2015). "Explicit and Implicit Processes Constitute the Fast
and Slow Processes of Sensorimotor Learning." <u>J Neurosci</u> **35**(26): 9568-9579.
Morehead, J. R., S. E. Qasim, M. J. Crossley and R. Ivry (2015). "Savings upon Re-Aiming in Visuomotor
Adaptation." <u>J Neurosci</u> **35**(42): 14386-14396.
Morel, P. (2018). "Gramm: grammar of graphics plotting in Matlab." <u>The Journal of Open Source</u>
<u>Software</u> **3**(23).
Morel, P. D. and P. Baraduc (2010). Dissociating the impact of sensory and motor noise in human
saccades. <u>Cinquième conférence plénière française de Neurosciences Computationnelles,</u>
<u>"Neurocomp'10"</u>. Lyon, France.
Pisella, L., G. Rode, A. Farne, C. Tilikete and Y. Rossetti (2006). "Prism adaptation in the rehabilitation of
patients with visuo-spatial cognitive disorders." <u>Curr Opin Neurol</u> **19**(6): 534-542.
Rosenberg, L. (1993). <u>The effect of interocular distance upon operator performance using stereoscopic</u>
<u>displays to perform virtual depth tasks</u>.
Scott, S. H. (2004). "Optimal feedback control and the neural basis of volitional motor control." <u>Nat Rev</u>
<u>Neurosci</u> **5**(7): 532-546.
Shadmehr, R. and J. W. Krakauer (2008). "A computational neuroanatomy for motor control." <u>Exp Brain</u>
<u>Res</u> **185**(3): 359-381.
Shadmehr, R., M. A. Smith and J. W. Krakauer (2010). "Error correction, sensory prediction, and
adaptation in motor control." <u>Annu Rev Neurosci</u> **33**: 89-108.
Sing, G. C. and M. A. Smith (2010). "Reduction in learning rates associated with anterograde interference
results from interactions between different timescales in motor adaptation." <u>PLoS Comput Biol</u> **6**(8).
Smith, M. A., A. Ghazizadeh and R. Shadmehr (2006). "Interacting adaptive processes with different
timescales underlie short-term motor learning." <u>PLoS Biol</u> **4**(6): e179.

Taylor, J. A., J. W. Krakauer and R. B. Ivry (2014). "Explicit and implicit contributions to learning in a
sensorimotor adaptation task." J Neurosci **34**(8): 3023-3032.
Turolla, A., M. Dam, L. Ventura, P. Tonin, M. Agostini, C. Zucconi, P. Kiper, A. Cagnin and L. Piron (2013).
"Virtual reality for the rehabilitation of the upper limb motor function after stroke: a prospective
controlled trial." J Neuroeng Rehabil **10**: 85.
van Beers, R. J. (2009). "Motor learning is optimally tuned to the properties of motor noise." Neuron
63(3): 406-417.
van Beers, R. J., P. Baraduc and D. M. Wolpert (2002). "Role of uncertainty in sensorimotor control."
Philos Trans R Soc Lond B Biol Sci **357**(1424): 1137-1145.
van Beers, R. J., A. C. Sittig and J. J. Gon (1999). "Integration of proprioceptive and visual position-
information: An experimentally supported model." J Neurophysiol **81**(3): 1355-1364.
van Beers, R. J., D. M. Wolpert and P. Haggard (2002). "When feeling is more important than seeing in
sensorimotor adaptation." Curr Biol **12**(10): 834-837.
van der Vliet, R., M. A. Frens, L. de Vreede, Z. D. Jonker, G. M. Ribbers, R. W. Selles, J. N. van der Geest
and O. Donchin (2018). "Individual Differences in Motor Noise and Adaptation Rate Are Optimally
Related." eNeuro **5**(4).
Vehtari, A., A. Gelman and J. Gabry (2017). "Practical Bayesian model evaluation using leave-one-out
cross-validation and WAIC." Statistics and computing **27**(5): 1413-1432.
Wei, K. and K. Kording (2010). "Uncertainty of feedback and state estimation determines the speed of
motor adaptation." Front Comput Neurosci **4**: 11.
Wolpert, D. M., J. Diedrichsen and J. R. Flanagan (2011). "Principles of sensorimotor learning." Nat Rev
Neurosci **12**(12): 739-751.
Wolpert, D. M. and Z. Ghahramani (2000). "Computational principles of movement neuroscience." Nat
Neurosci **3 Suppl**: 1212-1217.

A

PARALLEL HAPTIC
MANIPULATOR

RIGHT-EYE
MONITOR

ANGLED
MIRRORS

LEFT-EYE
MONITOR

B

Hold Fixation

Spatial Cue

Reach

C

D

120 trials
baseline

240 trials
perturbation

240 trials
washout

Perturbed Planes

Horizontal

Coronal

Sagittal

30°