Relating simulation studies by provenance — Developing a family of Wnt signaling models

Kai Budde[1*], Jacob Smith[2], Pia Wilsdorf[1], Fiete Haack[1], Adelinde M. Uhrmacher[1]

1 Institute for Visual and Analytic Computing, University of Rostock, Rostock, 18051, Germany
2 Faculty of Computer Science, University of New Brunswick, Fredericton, NB E3B 5A3, Canada

* kai.budde@uni-rostock.de

Abstract

For many cell-biological systems, a variety of simulation models exist. A new simulation model is rarely developed from scratch, but rather revises and extends an existing one.

A key challenge, however, is to decide which model might be an appropriate starting point for a particular problem and why. To answer this question, we need to identify and look at entities and activities that contributed to the development of a simulation model.

Therefore, we exploit the PROV Data Model (PROV-DM) and, building on previous work, continue developing a PROV ontology for simulation models. Based on a concrete case study of 19 Wnt/β-catenin signaling models, we identify crucial entities and activities as well as useful metadata to both capture the provenance information of individual simulation studies and relate these forming a family of models. The approach is implemented in *WebProv*, which allows one to insert and query provenance information.

Our specialization of PROV-DM contains the entities Research Question, Assumption, Requirement, Qualitative Model, Simulation Model, Simulation Experiment, Simulation Data, and Wet-lab Data as well as activities referring to building, calibrating, validating, and analyzing a simulation model. We show that most Wnt simulation models are connected to other Wnt models by using (parts of) these models. However, the overlap, especially regarding the Wet-lab Data used for calibration or validation of Simulation Models is small.

Making these aspects of developing a model explicit and queryable is a crucial step for assessing and reusing simulation models more effectively. The unambiguous specification of information helps to integrate a new simulation model within the family of existing ones. Our approach opens up a wealth of knowledge that may lead to the development of more robust and valid simulation models.

We hope that it becomes part of a standardization effort and that modelers adopt the benefits of provenance when considering or creating simulation models.

Author summary

We revise a provenance ontology for simulation studies of cellular biochemical models. Provenance information is useful for understanding the creation of a simulation model, because it does not only contain information about the entities and activities that have led to a simulation model but also the relations of these, which can be visualized. It provides additional structure as research questions, assumptions, and requirements are singled out and explicitly related along with data, qualitative models, simulation models, and simulation experiments through a small set of predefined but extensible activities.

We have applied our concept to a family of 19 Wnt signaling models and implemented a web-based tool (*WebProv*) to store the provenance information of these studies. The resulting provenance graph visualizes the story line within simulation studies and demonstrates the creation and calibration of simulation models, the successive attempts of validation and extension, and shows, beyond an individual simulation study, how the Wnt models are related. Thereby, the steps and sources that contributed to a simulation model are made explicit.

Our approach complements other approaches aimed at facilitating the reuse and assessment of simulation products in systems biology such as model repositories as well as annotation and documentation guidelines.

Introduction

Mechanistic, biochemical models are being implemented and questioned to deepen the understanding of biological systems. These models are usually the results of simulation studies that include phases of refinement and extension of simulation models together with the execution of diverse *in silico* (simulation) experiments.

A plethora of work has emerged over the last two decades to support the conduction and documentation of simulation studies (e.g., modeling and simulation life cycles [1], workflows [2], conceptual models [3]). Depending on the application domain, different modeling approaches have their own documentation guidelines [4–6]. In the case of systems biology, the "Minimum Information Requested in the Annotation of Biochemical Models (MIRIAM)" [7] and the "Minimum Information About a Simulation Experiment (MIASE)" [8] are two community standards used for documenting simulation models and corresponding simulation experiments. A recent perspective by Porubsky et al. (2020) [9] looks at all stages of a biochemical simulation study and at tools supporting their reproducibility. When looking at an entire simulation study and at the generation process of the included simulation model, these guidelines provide some indication about which information might be useful for documenting a complete simulation study as well as for establishing relationships between different simulation models.

This is of particular interest when several simulation models for a system under consideration exist, offering different perspectives on the system, answering different questions, or reflecting the data and information available at the time of generation. Model repositories such as BioModels [10,11], JWS Online [12], or the CellML Model Repository [13] provide different means to retrieve and use simulation models. For example, querying the BioModels database for biochemical and cellular simulation models that contain proteins such as Wnt, Janus kinase (Jak), or mitogen-activated protein kinase (MAPK), which are associated with corresponding signaling pathways, returns for Wnt a set of 22 simulation models, for Jak a set of 12 simulation models and for MAPK a set of 139 simulation models[1]. This already shows that MAPK is an

---

[1]As of January 2021 by looking at the results of the query `https://www.ebi.ac.uk/biomodels/search?query=wnt&domain=biomodels`, or exchanging "wnt" by "jak" or "mapk", respectively.

intensively studied signaling pathway. However, there is no way to easily compare these simulation models or to examine their relationships to each other. Tools such as BiVeS [14] are helpful to compare different versions of one particular simulation model, but comparing different models—even of the same system—will be a difficult task because the syntax of these models (e.g., the names of the species), as well as reactions, might be completely different. Instead of analyzing the similarities and differences in the specifications of simulation models to infer possible relationships between these simulation models, we will focus on context information, such as how a simulation model has been generated.

Particularly, larger models are usually not built from scratch [15]. In general, simulation models are the outcome of extensive as well as interactive model and data generation activities that include, in addition to executing various simulation experiments and successive model refinements, the adaptation of already existing models, for example, by composition or extension [15–17]. Therefore, the complexity of a model grows over time as researchers add parts to the model or refine it. Keeping track of these generation processes is the subject of provenance.

Provenance provides "information about entities, activities, and people involved in producing a piece of data or thing, which can be used to form assessments about its quality, reliability or trustworthiness" [18]. Thus, it can be applied to many fields of science, art, and technology, including biochemical and cellular simulation models. By exploiting standardized provenance data models, such as PROV-DM, this information is presented in a structured, queryable, and graphical form [19, 20]. In addition to providing crucial information about the generation of an individual simulation model and, thus, facilitating its reuse, provenance can be applied to reveal and exploit relationships between different simulation models.

In this publication, we will identify and structure relevant information needed for the provenance of simulation studies and elucidate how a family of simulation models can be established through relating the models to each other. As a case study, we will concentrate on 19 simulation studies of the Wnt/β-catenin signaling pathway. Among the different Wnt signaling pathways, the canonical Wnt or Wnt/β-catenin signaling pathway is the most intensively studied one, *in vitro* [21] as well as *in silico* [22]. This pathway is considered to be one of the key pathways in development and regeneration, including cell fate, cell proliferation, cell migration and adult homeostasis [23, 24]. In deregulated forms, it is involved in human cancers and developmental disorders [25, 26].

Our case study refers to the Wnt/β-catenin signaling pathway only, which we call Wnt throughout the text. We will present and use our web-based tool *WebProv* to store, present and query provenance information of these simulation studies. Different queries and analyses of the family of 19 Wnt simulation models will then be used for finding further insights into the family of Wnt signaling simulation models.

Materials and methods

Provenance of simulation models

Provenance data model

We consider the types and relations defined by the PROV data model: PROV-DM [18]. PROV-DM includes the following types: `entity`, `activity`, `agent` as well as the following relations: `WasGeneratedBy`, `Used`, `WasInformedBy`, `WasDerivedFrom`, `WasAttributedTo`, `WasAssociatedWith`, `ActedOnBehalfOf`. Provenance information is usually depicted as a directed, acyclic graph where the arrowheads show towards the sources or predecessors of an entity, activity, or agent—thus, depicting its origin. For our case study, we are only focusing on the types `entity` and `activity` as well as on

the relations `WasGeneratedBy` and `Used`. The reasons for our decision will be explained in the Results and discussion section.

Provenance ontology for simulation studies

Recently, Ruscheinski et al. (2018) [19] have applied PROV-DM for capturing provenance information of entire simulation studies and initiated a definition of a PROV-DM ontology for these studies. Important ingredients of this ontology have been identified to be "a) specific types of entities (e.g., data, theories, simulation experiments, and simulation models), b) specific roles between these entities (e.g., used as input, used for calibration, used for validation, used for adaptation, used for extension, used for composition), c) specific refinement of activities (i.e., successive refinement of activities down to a level where simulation experiment specifications define activities and thus are ready to be executed), and d) specific inference strategies (e.g., warnings if the same data has been used both by calibration and validation activities, or the option to reuse validation experiments among model descendants to check consistency)" [19]. The adaptation and application of this ontology for capturing the essential information of our case study is presented in the Results and discussion section.

Collecting provenance information

In order to gather all relevant information, the publications as well as the supporting materials—as they often contain model and experiment descriptions—were read thoroughly. Referenced publications were checked, as well, whenever they appeared to be important for the development of the simulation model. All information that resembled provenance entities were marked. While reading a study, a first sketch of a possible provenance graph was being made. Afterwards, a revision of all markings helped to finalize the graph and to remove duplicated entities. Often, authors described their simulation study chronologically, which made it easy to determine the path of its development, but sometimes, the connections of the entities had to be inferred from the context. In general, tracing the provenance of an entire simulation study in retrospective involved some interpretation of the results presented in the publication.

Implementing the PROV-DM ontology: WebProv

We have developed *WebProv*[2], a web-based tool that can be used to store, access, and display provenance information of simulation studies. It allows one to insert and query provenance information based on a web interface as frontend and a graph-based database as backend. The frontend uses Vue, a popular JavaScript reactivity system, along with D3.js, a JavaScript visualization library, to create the front-end visualizations and power the node/relationship editor. As scalability was not a concern when designing the tool, all graph data is sent to the frontend when the website is first opened, allowing the frontend to perform approximate string matching and explore the entire graph without additional queries to the database. Although this reduces the responsibilities of the back-end system, the backend still provides an interface for loading different types of nodes, updating data and importing/exporting JSON data from Neo4j. Furthermore, the backend allows one to load in a set of nodes and relationships from JSON into Neo4j on startup to initialize the database.

---

[2]The tool can be locally installed for testing and replicability purposes. Details about its installation, as well as the code are found on GitHub. An informative video showing the usage of *WebProv* is found on YouTube.

Provenance nodes   121

The main concept of *WebProv* is the Neo4j Provenance Node and the dependency graph   122
created from related Provenance Nodes using Neo4j relationships. A Provenance Node   123
represents an entity or activity and, therefore, must have a classification (e.g.,   124
Simulation Model or Building Simulation Model) which defines the types of relationships   125
that can be formed with other nodes depending on our PROV ontology. For example,   126
the entity Simulation Model can only be created by either the activity Building   127
Simulation Model or Calibrating Simulation Model (see the Results and discussion   128
section and Table 2 for all details). These classifications can be easily changed and   129
extended if needed. Additionally, `Study` nodes store information about a particular   130
study (a study reference as well as the name of the signaling pathway it is concerned   131
with) and group a set of Provenance Nodes together. Finally, `InformationField` nodes   132
allow us to attach zero or more key–value pairs to a Provenance Node to store further   133
information. In our case, we describe which information should be entered depending on   134
the entity type in the Results and discussion section.   135

Queries   136

WebProv allows two types of queries: text queries and queries in Cypher—Neo4j's query   137
language. The text query field will perform a fuzzy search of the data contained within   138
the nodes. If successful, a set of nodes are returned that contain the given phrase and   139
the user can choose to add any of these nodes to the graph. Alternatively, the Cypher   140
field passes the query as a string to the backend which forwards it to the Neo4j database.   141
Since arbitrary queries can be performed, when the results are returned, the frontend   142
attempts to parse the results using io-ts[3] as a Provenance Node. If successful, these   143
nodes are automatically shown on the graph. This method allows more complex queries,   144
in particular, subgraphs to be extracted. Thus, structural information can be accessed.   145

Wnt signaling models   146

A comprehensive list of published simulation studies that deal with or include the Wnt   147
signaling pathway is found in Table 1. Some of these Wnt models have already been   148
discussed in previous reviews [22, 27]. Out of the 31 simulation studies on Wnt, which   149
we have found, we have chosen to collect provenance information from 19 studies, shown   150
in bold in Table 1. We have included all Wnt simulation studies where simulation   151
models were stored in BioModels (6 studies) as well as all Wnt simulation studies   152
published by our group (4 studies). The remaining nine studies were selected randomly.   153
   All models include Wnt ligands and Wnt receptors (implicitly or explicitly) as well   154
as the Wnt signal transducer protein β-catenin. There are two exceptions: the   155
simulation model by Sick et al. 2006 [31] contains only Wnt and its antagonist Dkk and   156
the model by Rodríguez-González et al. (2007) [33] lacks β-catenin. The number of   157
species without considering compounds or different attributes or states, such as the   158
phosphorylation state, ranges from 2 (in [31]) to 30 (in [53]). The dimension of a system   159
may be higher if a model contains compounds or different states of the species. A   160
schematic representation of the Wnt signaling model including relevant species and   161
interactions from all 19 surveyed studies is shown in Fig 1.   162

---

[3]https://github.com/gcanti/io-ts

Table 1. Wnt simulation models (as of Feb. 1, 2021) with those included in this study printed in bold.

Study	BioModels	MA	SA	Scale	Add. Compartm.	Add. Pathways/Models
[28]	✓	ODE	det	SC	–	–
[29]	–	ODE	det	SC	–	–
[30]	–	ODE	det	SC	–	–
[31]	–	PDE	det	TOL	–	–
[32]	✓	ODE	det	SC	Nuc	MAPK/ERK
[33]	–	ODE	det	SC	–	Notch
[34]	✓	ODE	det	SC	–	–
[35]	–	ODE	det	SC	–	–
[36]	✓	ODE	det	SC	Nuc	Notch, MAPK/ERK
[37]	–	PDE	det&stoch	MC	–	E-cadherin
[38]	–	ODE	det	SC	–	–
[39]	–	ODE	det&stoch	MC	–	Cell cycle, E-cadherin
[40]	–	ODE	det	SC	–	–
[41]	–	ODE	det	SC	–	–
[42]	–	PDE	stoch	MC	–	–
[43]	–	ODE	det	SC	–	MAPK/ERK
[44]	–	PDE	det&stoch	MC	–	Notch
[45]	–	ODE	det	SC	–	–
[46]	✓	Rule	det&stoch	SC	Nuc	Cell cycle
[47]	–	ODE	det	SC	Nuc	–
[48]	–	ODE	det	SC	Nuc	Notch
[49]	–	ODE	stoch	SC	Nuc, GA	E-cadherin
[50]	–	ODE	det	SC	Nuc	–
[51]	–	Rule	stoch	SC	Nuc, Mem, LR	ROS
[52]	–	ODE	det	SC	Nuc	–
[53]	✓	ODE	det	SC	–	MAPK/ERK, PI3K/Akt
[54]	–	Bool	det	SC	–	PI3K/AKT, MAPK/ERK, Rho/Rac
[55]	–	ODE	det	SC	–	–
[56]	–	Rule	det	SC	Nuc, End, Mem, LR	–
[57]	–	Rule	stoch	SC	Nuc	ROS
[58]	–	ODE	det&stoch	MC	–	Cell cycle, Hippo

A list of published simulation studies of the Wnt signaling pathway is presented showing the references, the availability of the simulation models in BioModels, the modeling approaches (MA), the simulation approaches (SA), the scale of the models, additional compartments as well as additional pathways or sub-models included. The names of the authors of the studies printed in bold are: Lee et al. (2003) [28], Krüger and Heinrich (2004) [29], Cho et al. (2006) [30], Sick et al. (2006) [31], Kim et al. (2007) [32], Rodríguez-González et al. (2007) [33], van Leeuwen et al. (2007) [34], Wawra et al. (2007) [35], Goldbeter and Pourquié (2008) [36], van Leeuwen et al. (2009) [39], Mirams et al. (2010) [41], Kogan et al. (2012) [45], Mazemondet et al. (2012) [46], Wang et al. (2013) [48], Chen et al. (2014) [49], Haack et al. (2015) [51], Padala et al. (2017) [53], Haack et al. (2020) [56], and Staehlke et al. (2020) [57]. The BioModels IDs of the simulation models available in BioModels are: [28]: BIOMD0000000658, [32]: BIOMD0000000149, [34]: MODEL2001090001, [36]: BIOMD0000000201, [46]: MODEL1303140000, [53]: BIOMD0000000648. The modeling approaches (MA) are: ODE-based (ODE), PDE-based (PDE), rule-based or reaction-based (Rule), and Boolean network model (Bool). The simulation approaches (SA) are: det (deterministic), stoch (stochastic). The scale may be single cell (SC), multi cell (MC) or at a more abstract tissue/organ level (TOL). Every simulation model contains at least one compartment—usually the cytosol. We also denote additional compartments where reactions may take place and where some species may shuttle into or out of: Nucleus (Nuc), Membrane (Mem), Endosome (End), Golgi apparatus (GA), Lipid Raft (LR). Models without shuttling are considered to have only one compartment even though they describe processes in different places, for example, in the cytosol, nucleus and at the cell membrane.

(a)

Fig 1. Combined overview of all Wnt (sub-)models found within the 19 Wnt simulation studies. Depicted are the components (species, compartments, and reactions) of the central canonical Wnt signaling pathway (a) and its crosstalk with other signaling pathways (b). Note that the overview is a simplified and condensed representation. Interactions are simplified and some components of the submodels that do not directly affect the Wnt signaling pathway are omitted. Activated/phosphorylated proteins are indicated by (*). Inactive/unphosphorylated states of proteins have been omitted when possible. Submodels involving membrane-mediated processes, such as receptor/ligand interactions, destruction complex recruitment and endocytosis [31, 45, 51, 56], or cadherin-mediated cell adhesion [34, 39, 49] are incorporated in (a). Submodels involving crosstalk with ERK/FGF/PI3K/Akt [32, 36, 53], Notch [33, 36, 48], and ROS/Dvl-mediated pathways [51, 57] are shown in the lower panels of (b), respectively.

Results and discussion

In order to provide useful information about a set of simulation models as a kind of family, we need to answer the questions about which information regarding these models and their development processes are needed and how to describe them. Based on our earlier work on provenance of simulation models, we refine a specialization of the PROV Data Model (PROV-DM) and, thus, define a PROV ontology that is capable of both relating simulation models and reporting their generation processes. We also examine the level of detail, or granularity, that is necessary to capture relevant information of the provenance of simulation studies.

First, we will introduce and discuss our specialization of PROV-DM for cellular biochemical simulation models. Second, we will discuss our findings applying our specialization of PROV-DM and demonstrate the relationships as well as specific features of the provenance information of the 19 Wnt simulation studies covered in this publication.

Further steps towards a PROV-DM ontology for cellular biochemical simulation models

The specialization of PROV-DM, which has been introduced by Ruscheinski et al. (2018) [19], is being revised and refined. For capturing provenance information of simulation studies of cellular biochemical simulation models and relating these, we are defining and using a) specific types of entities and activities and b) specific relations with their roles and constraints. We have identified these types and relations as well as information that is useful for describing them in a succinct manner during the process of collecting provenance information of the studies containing cellular biochemical models. Our final set of entities, activities, and relations is shown in Table 2. Each entity and activity has already been mentioned for provenance, modeling or documentation purposes, or experiment design of simulation studies [1, 3–5, 8, 19, 20, 59–62], but they have not been used in this concrete combination.

In the following, we will describe these entities, activities, and relations and discuss the information that should be included in *WebProv*. For each provenance entity and activity, we will show examples of our specialization with provenance information obtained from the provenance graph of the simulation study by Lee et al. (2003) [28], shown in Fig 2.

Provenance entities

For every Provenance Node (entity or activity), we require the following details to be provided: a) (PROV-DM) Type, b) Study (Reference), c) Description.

The (PROV-DM) Type declares the type of entity or activity. The Study (Reference) contains the name of the study a Provenance Node belongs to. The Description contains some textual explanation of the Provenance Node. For some entities, we are asking for further information, as seen in Fig 3, which we will elaborate on.

Research Question [RQ]:
The research question (or research objective or problem formulation) determines the goal of the research presented in a publication. In the case of simulation studies, it typically forms the starting point in the modeling and simulation life cycle [1, 66] and is central to interpret its products such as simulation data or simulation model.

As for our provenance example shown in Fig 2, Lee et al. (2003) [28] questioned in RQ1 the necessity of "the two scaffold proteins, APC and Axin" (for Wnt signaling) and whether "their roles differ". This research question determines a minimum number of

Table 2. Entities, activities and allowed relations in our PROV-DM specialization.

Entity	*wasGeneratedBy* (Activity)
Research Question (`RQ`)	–
Assumption (`A`)	–
Requirement (`R`)	–
Qualitative Model (`QM`)	–
Simulation Model (`SM`)	`BSM` | `CSM`
Simulation Experiment (`SE`)	`CSM` | `VSM` | `ASM`
Simulation Data (`SD`)	`CSM` | `VSM` | `ASM`
Wet-lab Data (`WD`)	–

Activity	*used* (Entity)
Building Simulation Model (`BSM`)	`RQ` | `SM`, {`RQ` | `A` | `R` | `QM` | `SM` | `SE` | `SD` | `WD`}
Calibrating Simulation Model (`CSM`)	`SM`, {`A` | `R` | `SD` | `WD`}
Validating Simulation Model (`VSM`)	`SM`, {`A` | `R` | `SD` | `WD`}
Analyzing Simulation Model (`ASM`)	`SM`, {`A` | `SD` | `WD`}

Left column: Specified PROV-DM entity and activity types used for capturing provenance information of simulation studies. Right column: Relations of PROV-DM used for capturing provenance information of simulation studies as well as allowed connections of entities/activities from the first column. The PROV relation *wasGeneratedBy* connects `entities` with `activities`; *used* connects `activities` with `entities`. The entities Research Question, Assumption, Requirement, Qualitative Model, and Wet-lab Data are included in the provenance graph without their origins, thus without an activity generating them. The generation of the Simulation Model, Simulation Experiment, and Simulation Data are explicitly shown in the provenance graphs. For example, a Simulation Model can be created or updated based on a Building Simulation Model or Calibrating Simulation Model activity—the alternative is denoted by "|". Regarding the activities, each activity has at least one entity it depends on (Research Question or Simulation Model). Other entity types are optional and several or none of each of them may be used by one particular activity—denoted by {...} in the extended Backus–Naur form (EBNF).

model constituents and guides the modeler towards possible simulation experiments to be executed.

Assumption [`A`]:
We define assumptions of a simulation model to be all statements that refer to abstractions or specializations of the described model. Assumptions typically deal with the input of a model (e.g., *assume the concentration of x to be constant* or *let the initial value of y be ...*) and may set the boundaries of the system under consideration or partially explain the thoughts behind a simulation model—always with the research question in mind.

In order to facilitate the analysis of assumptions, we adopted the Systems Biology Ontology (SBO) [67] to categorize the assumptions. SBO provides "structured controlled vocabularies, comprised of commonly used modeling terms and concepts" [68] and is primarily used to "describe the entities used in computational modeling (in the domain of systems biology)" [67].

In the provenance example, three assumptions with three different categories could be identified. `A1`, for instance, reads "Dsh, TCF, and GSK3β are degraded very slowly,

Fig 2. Provenance graph of the study by Lee et al. (2003) [28]. Additionally, the entities used by Lee et al. (2003) from three other studies [63–65] are shown. The colors of the ellipses show different entity types, the borders of the rectangles visualize different activity types. The gray areas separate the individual studies.

Fig 3. UML class diagram of provenance entities in *WebProv*. We have identified the following entities to be useful for prociding provenance information of simulation studies in the field of systems biology: Research Question, Assumption, Requirement, Qualitative Model, Simulation Model, Simulation Experiment, Simulation Data, and Wet-lab Data. The requested information for each entity type is kept minimal for demonstration purposes and can easily be extended. The *Study (Reference)* contains information of the publication, for instance, "Lee et al. (2003)" and determines which study an entity belongs to. The *Description* contains a brief explanation of a particular entity and may be a cited text from the publication. Furthermore, entity references should ideally consist of a digital object identifier (DOI) to make the artifact associated with the particular entity unambiguously accessible. Additional information can always be entered in the "Further Information" part of *WebProv*.

we assume that their concentrations remain constant throughout the timecourse of a [226]
Wnt signaling event" [28] and was matched to ID 362 (Concentration conservation law) [227]
of SBO. [228]

Requirement [R]: [229]

Requirements (for a simulation model) define properties the results of a simulation need [230]
to show. These may be used for the purpose of calibrating or validating a simulation [231]
model. They also direct the modeler towards adaptation of a model if the requirements [232]
are not met. We do not consider other kinds of requirements (e.g., the need of using [233]
specific tools or approaches in conducting a simulation study). [234]

Typically, simulation data needs to be compared with real-world data—in our case [235]
wet-lab data. These real-world measurements determine the species of interest which [236]
should be part of the entity Requirement. Therefore, we record the main species [237]
considered by the requirement as well as its type (either qualitative or quantitative) and [238]
connect the Requirement to the wet-lab data it relates to. The list of main species will [239]
make it easier to compare, interrelate and reuse simulation models as they determine [240]
the focus of the model. [241]

We were able to identify one requirement R1 in the provenance example of Lee et al. [242]
(2003) [28]. The quantitative requirement that "Axin stimulates the phosphorylation of [243]
β-catenin by GSK3β at least 24,000-fold" actually refers to the wet-lab data WD1 [244]
obtained in another study by Dajani et al. (2003) [64]. Its main species are Axin, [245]
β-catenin, and GSK3β. [246]

Qualitative Model [QM]: [247]

We define the qualitative model to be a network diagram, such as a reaction scheme [248]
(chemical reaction network diagram), which contains the entities of the system (e.g., [249]
species) and their interactions. This diagram may be presented in a formal (e.g., using [250]
the Systems Biology Graphical Notation (SBGN) [69] or a Boolean network [251]
diagram [70]) or informal way. All textual descriptions of a simulation model that do [252]
not include quantitative information (e.g., reaction rate constants, initial values) can [253]
also be part of the qualitative model. It should be noted that the qualitative model is [254]
also called conceptual model [71] sometimes, whereas in other publications, the [255]
qualitative model forms part of the conceptual model [3]. [256]

We record a reference to the qualitative model, which, for example, could be a [257]
reference to a figure in the publication, or, ideally, a DOI. Furthermore, we denote a list [258]
of species and compartments used in the model. Multiple compartments require a [259]
shuttling of species from one compartment to another one and every compartment [260]
should, ideally, have an area (for the transfer rate or concentration in two-dimensional [261]
compartment) as well as a volume (for a three-dimensional compartment) [72]. [262]

In our provenance example of Lee et al. (2003) [28], QM1 contains a qualitative model [263]
in the form of a chemical reaction network diagram which can be directly accessed via a [264]
DOI. It represents reactions of the species Wnt, Dsh, GSK3, Axin, APC, β-catenin, and [265]
TCF within a cell extract. [266]

Simulation Model [SM]: [267]

The simulation model is the actual mathematical or computational model [73] that can [268]
be executed by a suitable tool. In most cases of our domain, the simulation model [269]
contains equations (for ODE/PDE systems) or, in some cases, reaction rules (for [270]
rule-based systems). An integral part of these quantitative simulation models are the [271]
parameter values as well as the initial condition. The simulation model could also be [272]
described in another form (e.g., in a quantitative process algebra [74, 75] or with a [273]
combination of multiple formalisms [76]. Formal approaches to describe a system [274]
through qualitative models (e.g., Boolean models [77] or Petri nets [78]) come with their [275]
own means of analysis and are assigned to the entity Simulation Model, as they are [276]
executable models. Usually, a parameter table complements the description of the [277]

simulation model and gives information about the parameter values and their origin. ²⁷⁸

A new Simulation Model entity is created whenever the reaction network changes or ²⁷⁹
after a simulation model has been calibrated, which typically means that the set of ²⁸⁰
parameter values and the initial condition have been (re-)defined. A validation activity ²⁸¹
(by itself) does not alter the simulation model, although a failed validation activity is ²⁸²
likely to induce a change of the simulation model (see, for instance, [56]). ²⁸³

Again, we are relying on a reference of the simulation model for accessing it. It ²⁸⁴
should be a link to the simulation model in Biomodels or a DOI to the description of ²⁸⁵
the simulation model. Ideally, it is presented in a structured and widely accepted format ²⁸⁶
such as SBML [79] or CellML [80]. ²⁸⁷

As for the provenance example, the calibrated simulation model of Lee et al. ²⁸⁸
(2003) [28], `SM2`, can be found in BioModels. ²⁸⁹

Simulation Experiment [`SE`]: ²⁹⁰
The simulation experiment is an execution of the simulation model. Ideally, it can be ²⁹¹
linked to a complete experiment specification (e.g., as a SED-ML [81] or SESSL [82] file ²⁹²
or simply as the execution code in a general purpose programming language) and to ²⁹³
documentation in a standard format that applies reporting guidelines such as MIASE ²⁹⁴
for simulation experiments [8]. Diverse simulation experiments might be applied to ²⁹⁵
serve the analysis, calibration, and validation of a simulation model. ²⁹⁶

To further structure the set of simulation experiments applied, we distinguish ²⁹⁷
simulation experiments whether they are used for optimization, sensitivity analysis, ²⁹⁸
perturbation, parameter scan, steady-state analysis, or time course analysis. This list is ²⁹⁹
neither complete nor are the categories disjoint, and, given a different set of simulation ³⁰⁰
studies, they will likely be subject to renaming, extension, and refinement. We have ³⁰¹
identified optimization experiments to be all experiments where an implicit or explicit ³⁰²
objective function is being used. This includes parameter estimation as well as manual ³⁰³
parameter fitting experiments. If these succeed, the Calibrating Simulation Model ³⁰⁴
activity will produce a new (calibrated) Simulation Model. In a sensitivity analysis, ³⁰⁵
more than one parameter value is being changed and some kind of sensitivity coefficient ³⁰⁶
is being calculated. As perturbations, we have interpreted experiments where the value ³⁰⁷
of one (or more) parameter is being changed to another (just one) value, for example, to ³⁰⁸
mimic a knock-out experiment. Parameter scans include the variation of at least one ³⁰⁹
parameter value within a given range. A steady-state analysis is aimed at identifying ³¹⁰
the steady state of a system. With time-course analysis, we refer to the analysis of ³¹¹
trajectories without varying parameter values. ³¹²

Eventually, an ontology about the various experiment types and analysis methods ³¹³
and their use in simulation studies will be crucial as simulation experiments play a ³¹⁴
central role in the provenance of simulation models. This would also help to exploit the ³¹⁵
provenance information effectively, for example, for automatically generating simulation ³¹⁶
experiments [83]. ³¹⁷

In the case of Lee et al. (2003) [28], different simulation experiments have been ³¹⁸
executed. For example, `SE1` contains a parameter scan in order to validate the ³¹⁹
simulation model. However, no further details are given in the paper, therefore, no ³²⁰
reference could be included in the entity (the reference is "not available"). ³²¹

Note that we have not included an entity Wet-lab Experiment. Our focus is on the ³²²
result of the Wet-lab Experiment (i.e., the Wet-lab Data) and its role within the ³²³
simulation study (e.g., being used in a Building Simulation Model, Calibrating ³²⁴
Simulation Model, or Validating Simulation Model activity). ³²⁵

Simulation Data [`SD`] and Wet-lab Data [`WD`]: ³²⁶
Data is the result of an experiment. In our case, it can either stem from wet-lab or ³²⁷
simulation experiments. It includes a reference to a plot or table or, ideally, to a ³²⁸
database containing the raw data. The simulation data are generated by simulation ³²⁹

experiments, therefore a link needs to be established. In case of a simulation experiment that serves the role of validation, information about the success of a validation facilitates to interpret the simulation model and further activities based on the simulation model. As no independent Wet-lab Experiment entity is supported, details about the wet-lab experiment can be summarized in the description of the Wet-lab Data. The type of the wet-lab experiment (*in vitro* or *in vivo*) as well as the used organism and organ/ tissue/ cell line are recorded.

In the provenance example, Lee et al. (2003) [28] have executed *in vitro* wet-lab experiments with an egg extract of Xenopus and have shown in WD1 that the "turnover of GSK3β, Dsh, and TCF is relatively slow". The data of this wet-lab experiment is not shown in the publication. The simulation data SD2 contains the results of the successful validation of the simulation model SM2. The simulation data is presented in Figure 2 of their publication. The way the provenance graph and the metadata of SD2 is visualized in *WebProv* can be seen in Fig 4.

Fig 4. Screenshot of WebProv. This screenshot shows the provenance graph of the study by Lee et al. (2003) [28] with additional entities from three other studies [63–65], which are automatically colored differently. The node SD2 has been clicked on, which opens a box on the right with the stored and editable metadata.

Provenance activities and relations

The provenance graph is formed by explicitly relating entities and activities. This is done by declaring which entities are being used or which entities are being generated by which activities. We currently distinguish four activities: building, calibrating, validating, and analyzing the simulation model.

Products of activities (i.e., entities) are connected to these activities via the relation *wasGeneratedBy*. For example, Simulation Experiments or Simulation Data may be the result of all but the Building Simulation Model activity. Activities are connected to entities via the relation *used*. For example, the Calibrating Simulation Model activity may use the Simulation Model as the object to be calibrated, some Simulation Data or Wet-lab Data for calibration, and Requirements to confirm the calibration results. All connections that we currently distinguish are shown in Table 2.

It should be noted that provenance activities in simulation studies can be defined at various levels of granularity. We have opted for a rather coarse-grained approach identifying only crucial activities of a simulation study without explicitly denoting how an activity has used a specific entity. Thus, we aggregate activities as much as possible and leave out intermediate steps, focusing on the entities and not on the activities. From the moment provenance information is recorded automatically during the course of a simulation study, a higher level of detail could be achieved and an abstraction-based filter could be applied to zoom out to reach our granularity [2].

Building Simulation Model [BSM]:
The Building Simulation Model activity, also called model derivation [84], can use all entities types, as any entity described above can contribute to the model building process, but it needs to have at least a link to a Research Question or Simulation Model. The only result of the building simulation activity is an entity Simulation Model. Not every update of a simulation model within a simulation study will be reflected in the provenance graph—only those changes to the model that are considered essential by the authors.

In our provenance graph of the study of Lee et al. (2003) [28], two Building Simulation Model activities are shown. BSM1 is using wet-lab data, the research question, the qualitative model, a requirement and assumptions to develop a "provisional reference state model", which forms the not yet calibrated simulation model in the study. The Building Simulation Model activity BSM2 is extending the simulation model SM2.

Calibrating Simulation Model [CSM]:
The calibration of a simulation model is used to determine parameter values. Sometimes, switching parts of a model on or off (e.g., individual rules or model components) or choosing between entire models can also be interpreted as a discrete parameter value to be determined using methods of model selection [85]. This activity uses a Simulation Model and typically needs reference data (Wet-lab Data or Simulation Data) for the parameter estimation procedure and produces a specification or documentation of a Simulation Experiment as well as a Simulation Data entity. If the calibration is successful, the result of this activity will always be a (calibrated) Simulation Model. Ideally, it also takes an explicit requirement into account, which, in some cases, if formally defined, can also be used for calibrating the simulation model [86, 87]. It may also use an Assumption.

In the case of the activity CSM1 of Lee et al. (2003) [28], several wet-lab data from their own experiments (WD1–WD5) as well as from Salic et al. (2000) [65] (WD1–WD3) are being used during the calibration of the model SM1 which produces a Simulation Experiment SE1, the corresponding Simulation Data SD1 as well as the calibrated Simulation Model SM2.

Validating Simulation Model [VSM]:
The validation of a simulation model is used to test its validity (with regard to some requirements). Unlike calibration activities, here, the result is typically a binary answer, yes or no, which may be determined based on a specific distance measure and error threshold. The activity uses a Simulation Model and traditionally relies on reference data (Wet-lab Data or Simulation Data) that has not been used for calibration. For example, the Simulation Data from other studies may be used for the intercomparison of simulation models when performing an equal simulation experiment. Additionally, the required behavior can be formally specified in a Requirement (e.g., in a temporal logic) and automatically be checked [88, 89]. The Validating Simulation Model activity may also use an Assumption. It produces at least one entity of type Simulation Experiment as well as the corresponding Simulation Data entity. The Simulation Data entity of validation experiments stores the information whether the validation has been successful or not.

In our provenance example of Lee et al. (2003) [28], the simulation model `SM2` is being validated in the activity `VSM1` by comparing it with their own *in vitro* measurements shown in `WD6` and `WD7`. Neither a distance measure nor an explicit requirement are mentioned.

Analyzing Simulation Model [`ASM`]:
Similar to validation and calibration experiments, this activity provides insights into the simulation model and thus also into the system under study. The activity uses a Simulation Model and creates a Simulation Experiment as well as resulting Simulation Data. The use of Assumptions, Simulation Data, or Wet-lab Data is optional and might give an indication about the purpose of an analysis. The Analyzing Simulation Model activity aggregates all simulation experiments that are not explicitly aimed at calibration and validation.

Lee et al. (2003) [28] analyze both the calibrated simulation model `SM2` as well as the extended simulation model `SM3` by applying parameter scans, perturbations, and sensitivity analyses which results in the Simulation Experiment `SE3`–`SE11` and Simulation Data `SD3`–`SD11`.

Extensibility of our approach

All of these entities, activities and relations show major steps of the development of a simulation model and, as we will see in the following section, help to interrelate different simulation studies. Still, PROV-DM would allow even more details. We have not yet considered the type `agent` of PROV-DM in our approach because this information appeared less relevant in the analyzed simulation studies. In the future, it could also be part of the provenance information to name the agent an entity is attributed to, the agent an activity is associated with, or to name the agent another agent acted on behave of [18]. This would particularly be of relevance if models are not only validated but also accredited, which typically involves a different group of people than those who have developed the simulation model [90].

We have also not included the direct connection between two activities or two entities, such as the possibility to have a model being derived from another model. Thus, we have not included the following relations: a) `WasInformedBy`, which relates an activity to another one and b) `WasDerivedFrom`, which describes a direct transformation (update) of an entity into a new one. However, these relations can partly be inferred via the existing relations. For example, a simulation model that has been generated by a Building Simulation Model activity that used another simulation model indicates that the former has been derived from the latter. Or a validation activity that failed and that is followed by a Building Simulation Model activity obviously holds some information for the latter.

Exploring the provenance information of and among the Wnt simulation models of 19 simulation studies

Based on the identified and also defined entities and activities from above, we have recorded the provenance information of the 19 studies shown in bold in Table 1 as well as the provenance information of entities from other publications that were used by the 19 studies[4]. The complete provenance information is presented in S1 Dataset. Screenshots and presentations with the provenance information may also be found on GitHub. We will now discuss the observations we have made during the process of capturing the provenance information and later show how the studies and simulation models relate to each other.

---

[4]The references to the additionally used studies is found in S1 Appendix.

Provenance of individual Wnt simulation models

It is important to remember that we have manually collected all provenance information (entities, activities and relations), as described in the Materials and methods section. Collecting this information based on publications only is a demanding task and requires some interpretation, as natural language descriptions tend to be ambiguous. Also, the nonlinearity of the text—it is not a lab protocol after all—makes it hard to identify the relations of the entities and activities as well as the order of their execution. This would likely hamper an effective use of text mining or machine learning methods to complement or replace the manual work. Therefore, provenance information should be directly collected during the simulation study and ideally without an intervention of the modeler.

The Research Question was usually found repetitively within the abstract and throughout the introduction and discussion sections. Sometimes, there was more than one research question to be answered. In this case, we have combined these into a single entity.

Many Assumptions were introduced by the word "assume" or its derivatives. Other expressions such as "hypothesis", "is believed", "consider", "approximate", "simplify", "suggest", "suppose", or "propose" were also used by the authors to mark an assumption. However, not every sentence containing one of these words was identified to be an assumption of the simulation model. Occasionally, there were also assumptions which did not use one of the key words from above. Furthermore, two out of 19 studies did not explicitly state assumptions ([29, 53]). Generally, identifying assumptions involves many uncertainties. On the one hand, the authors might not have stated all assumptions made during the derivation of the simulation model. On the other hand, we might have easily missed an assumption and also interpreted statements as assumptions that were not meant as such by the authors. As a consequence, the assumptions might look different if the authors had defined them themselves.

In order to further analyze the assumptions, we have categorized these using the Systems Biology Ontology (SBO) [67]. However, the assumptions could not always be unambiguously matched to an SBO vocabulary and some assumptions dealing with biological mechanisms are not covered by SBO. For example, an autocrine signaling assumed by Mazemondet et al. (2012) [46] cannot be expressed by SBO. Some assumptions also include more than one detail which is reflected by multiple SBO categories per assumption. In this case, the assumption entity is duplicated and every assumption entity will receive its own category. The categorization of 106 collected assumptions shows that the three most used categories of assumptions deal with kinetic constants (13 times), transport (9 times), and equivalence (8 times). The result of the categorization can be found in S1 Table.

In many cases, Requirements were not given explicitly in a formal way or even as textual descriptions. We could only identify Requirements in the publications of Lee et al. (2003) [28], Wang et al. (2013) [48], Chen et al. (2014) [49], and Haack et al. (2020) [56]. The lack of Requirements was especially obvious when calibration or validation experiments were being carried out without explicitly explaining the objective function.

In the surveyed publications, it was common to include a reaction scheme of the simulation model, which we referred to in the Qualitative Model entities. When recording all species, we disregarded di- or multimeric compounds established by monomers already mentioned. We also ignored different states of the species (e.g., phosphorylation states). In all provenance graphs but the one by Mirams et al. (2010) [41], at least one Qualitative Model was used by a Building Simulation Model activity to produce a first Simulation Model. Mirams et al. (2010) have directly worked with the simulation model SM2 from Lee et al. (2003) [28].

The Simulation Models were either part of the manuscript or, more often, part of the supporting material. In 13 out of 19 cases, it was a system of ordinary differential equations. There were two simulation studies using PDEs and four using a rule-based approach (see Table 1). Although the Wnt signaling pathway has also been used to illustrate features of rule-based modeling [91, 92], only few simulation models have been developed based on a rule-based approach. The reason for this might partly be because support for thorough experimentation with rule-based models including calibration and validation has only become available during the last decade [93–95].

We have categorized all 145 Simulation Experiments that we found regarding which experiment type they serve (see UML class diagram shown in Fig 3). The result of the categorization are shown in Fig 5 and the details in S2 Table. Most Simulation Experiments were parameter scans, followed by time course analyses and perturbations. None of the 19 simulation studies have used steady-state analysis alone without applying another type of experiment at the same time, which we then recorded because it was more specific. The detection of steady states is typically part of an optimization, parameter scan, perturbation, and sensitivity analysis, because steady-state values are often the starting and end point of each simulation and are used for calculations.

Fig 5. Categories of the simulation experiments conducted within the analyzed 19 Wnt signaling studies. All simulation experiments conducted within the 19 Wnt simulation studies have been categorized. Most simulation experiments were parameter scans.

Sometimes, simulation or wet-lab experiments have been conducted, however, the corresponding Simulation Data or Wet-lab Data is not shown, but briefly described, and are, thus, without references in the provenance graphs. Authors often refer to this by stating "data not shown". For example, Lee et al. (2003) [28] state that unpublished measurements showed that the "turnover of GSK3β, Dsh, and TCF is relatively slow". Usually, both Simulation Data and Wet-lab Data are shown in figures in the studies or published in tables or figures as part of the supplemental material. In recent years, more and more journals, such as PLOS Computational Biology, have been recommending (but not requiring) to adhere to checklists of the FAIRsharing [96] portal when reporting data, with FAIR standing for: findable, accessible, interoperable and reusable [97].

In the case of Simulation Data, the focus lies on FAIR simulation models and experiments as it should be possible to easily regenerate the data. This could be

achieved, for example, by publishing a COMBINE archive [60], which is a "single file   536
that aggregates all data files and information necessary to reproduce a simulation study   537
in computational biology" [98]. However, the publications we have analyzed date back   538
up to 17 years, so most data has not been published in a FAIR way.   539

When looking at Wet-lab Data, six out of 19 publications recorded own wet-lab data   540
[28, 31, 32, 45, 51, 57]. All other simulation studies either used wet-lab data from other   541
publications or did not explicitly refer to wet-lab data at all [29, 30, 33, 34, 39, 41, 53].   542
The latter could only be done because the authors relied on other Simulation Models   543
and the respective parameter and initial values. Interestingly, the wet-lab data obtained   544
either by the 19 Wnt signaling studies or by other studies which where used in the 19   545
studies stemmed from different organisms and cell lines. Besides human and murine cell   546
lines (each 11 studies), xenopus, rat, hamster, and kangaroo rat were used as a model   547
organisms. The experiments included, among others, (tumor) cell lines from the kidney   548
(BHK, HEK293, PtK2), bone (MG-63), cervix (HeLa), brain (neural progenitor cells),   549
and of fibroblasts (L cells, NIH/3T3). All different cell lines directly used in the studies   550
are presented by the colored rectangles in Fig 6. The cell lines and organisms that were   551
included in the simulation studies are shown in Table 3.   552

When looking at the CSM and VSM activities, we detect that only a few simulation   553
models were both calibrated and validated based on wet-lab data, namely those of Lee   554
et al. (2003) [28], Kogan et al. (2012) [45], and Haack et al. (2015) [51]. Some authors   555
just calibrated their simulation models ([33, 46, 48, 49, 53, 57]) and in two studies ([30, 56])   556
they were only validated (having assumed plausible ranges for parameter values). The   557
simulations models developed in [29, 32, 34–36, 39, 41] have neither been calibrated nor   558
validated explicitly, because they have used parameter values from other studies. Sick et   559
al. (2006) [31] have used arbitrary parameter values in their simulation models.   560

Some studies develop a story line where a simulation model has been successively   561
refined, extended, or composed ([28, 33, 34, 36, 41, 46, 48, 49, 51, 56]). These studies are   562
characterized by a Simulation Model being used by a Building Simulation Model   563
activity, both nodes of the same study.   564

Some simulation studies resulted in the development of multiple simulation models   565
that are neither extensions nor compositions but rather form a revision or alternative to   566
other simulation models developed in the same study: [33, 39, 41, 46, 48, 49]. This can be   567
seen in the provenance graph of a single study when the last simulation model is not   568
connected by a directed path to other simulation models of that study or when the   569
simulation models are part of disjoint branches of the provenance graph. For example,   570
in [46], the core model of the Wnt/β-catenin signaling pathway has been calibrated with   571
wet-lab data from Lee et al. (2003) [28], but this calibrated simulation model was not   572
used any longer and instead, a new calibration with wet-lab data from another study   573
took place. Two simulation studies ([35, 41]) show disconnected graphs. This shows that   574
these researchers considered, built, and analyzed multiple simulation models   575
independently of each other.   576

Beyond individuals: A family of Wnt simulation models   577

Whereas before we have looked at the properties of individual simulation studies, we are   578
now going to investigate the interrelations between the 19 Wnt/β-catenin signaling   579
simulation models. We will identify features that transform a set of simulation models   580
into a family.   581

Fig 6 shows an overview of all simulation studies considered in our research by   582
zooming out of the individual provenance graphs. All but two simulation models are   583
(indirectly) connected to the model proposed by Lee et al. (2003) [28], which was the   584
first validated simulation model of the canonical Wnt signaling pathway. This shows   585
that models are usually not built independently from one another, but are often   586

Table 3. Cell lines and organisms used building the simulation model.

Reference	Egg extract	Embryo	Fibroblasts L cells	Fibroblasts NIH/3T3 cells	Mammary gland (C57MG) cells	Osteoblast-like cells (MG-63)	Presomitic mesoderm (PSM) cells	Skin	Cervical cancer epithelial (HeLa S3) cells	Colon carcinoma RKO cells	Embryonic kidney epithelial (HEK 293) cells	Neural progenitor (ReNcell VM) cells	Baby hamster kidney (BHK) cells	Epithelial kidney cells (PtK2)	Pheochromocytoma cells	Not applicable
[28]	x															
[29]	x															
[30]	x															
[31]								x								
[32]	o										x					
[33]		x														x
[34]	x															
[35]	x				x						x					
[36]	x						x									
[39]	o															
[41]	x															
[45]	x		x													
[46]	x											x				
[48]	o						x									
[49]	x									x	x					
[51]	x		x	x							x	x	x	x		
[53]	o										x				x	
[56]	o		x	x					x		o	x	o	o		x
[57]				x												

The top row shows the origin of the cells used by the 19 studies. *Not applicable* means that the parameters values were obtained from theoretical calculations/considerations from a textbooks or without concrete reference to a wet-lab study. The colors denote the organisms of the cell line/organ used, with ■ Xenopus, ■ mouse, ■ human, ■ hamster, ■ kangaroo rat, and ■ rat. The "x" denotes *directly used*, the "o" denotes *indirectly used by using (parts of) a referenced simulation model.*

extensions or revisions of formerly published models or use the parts of the reactions or parameter values. The two exceptions not linked to Lee et al. (2003) [28] are the simulation models by Sick et al. (2006) [31] and by Rodríguez-González et al. (2007) [33]. Sick et al. (2006) use a reaction-diffusion system (Gierer-Meinhardt equations [99]) to model the interplay between Wnt and its antagonist Dkk with just two equations. Rodríguez-González et al. (2007) consider Wnt and Axin—two key players of the Wnt/β-catenin signaling pathway—but only in the context of the Notch signaling pathway and thus the model only contains a fragment of the canonical Wnt pathway.

We have also included the cell lines/tissue used for wet-lab experiments within each

study. As already seen in Table 3, we observe that different simulation studies use data or models obtained using other cell lines. This may be valid as the Wnt/β-catenin signaling pathway is evolutionarily conserved [23], which means that data can be shared, even though care must always be taken when using, for instance, parameter values determined with one cell line in a study that uses another cell line.

Fig 6. Provenance graph of all Wnt/β-catenin simulation studies considered here (black outlines) as well as additionally used studies (gray outlines). The colors indicate the cell lines used in wet-lab experiments of a study. Gray boxes represent pure Wnt/β-catenin simulation studies without acquiring wet-lab data. White boxes display publications used by some of the Wnt/β-catenin simulation studies that are either text books or simulation studies without published wet-lab data. The following cell lines/tissues were used: ■ Xenopus egg extract, ■ mouse embryo, ■ Fibroblasts L cells, ■ Fibroblasts NIH/3T3 cells, ■ mammary gland (C57MG) cells, ■ osteoblast-like cells (MG-63), ■ presomitic mesoderm (PSM) cells, ■ mouse skin, ■ cervical cancer epithelial (HeLa S3) cells, ■ colon carcinoma RKO cells, ■ embryonic kidney epithelial (HEK 293) cells, ■ neural progenitor (ReNcell VM) cells, ■ baby hamster kidney (BHK) cells, ■ epithelial kidney cells (PtK2), ■ pheochromocytoma cells. The references to the additionally used studies is found in S1 Appendix.

When looking at the same graph using a circular layout, we observe four clusters of two or more studies, as shown in S1 Figure. We have also colored the studies according to additional pathways they include and observe that the clusters separate the studies depending on these additional cellular mechanisms. The central cluster includes the Wnt model by Lee et al. (2003) [28] as well as the studies [30, 34, 35, 41]. A second cluster forms around the simulation studies [45, 46, 51, 56, 57] and either includes the same wet-lab data from [100, 101] or the Cell cycle [46] or ROS [51, 57]. A third cluster includes the pathways of Notch [33, 48] or Notch + MAPK/ERK [36]. Even though the algorithms locate [29] in the same cluster, it is content-wise rather part of the central cluster. A forth cluster forms around studies including MAPK/ERK [32] or MAPK/ERK + PI3K/Akt [53]. All other models are not part of a cluster and are either completely disconnected from the other studies [31] or include E-cadherin and the cell cycle [39] or just E-cadherin [49].

When comparing Fig 6 and S1 Figure, we find that the wet-lab data of just three studies, namely from [100–102] have been reused by simulation studies. On the one hand, this is surprising as wet-lab data could be reused for parameter estimation or model validation. On the other hand, when authors use parts or entire simulation models published by others, they do not necessarily recite the references that were used for obtaining the parameter and initial values that come with the model. Thus, a direct connection from the new simulation model to the wet-lab data used by another simulation study is not made.

Conclusion

Provenance of simulation models provides information about how a simulation model has been generated and about the steps and various sources that contributed to its generation. Here, we have developed a specialization of PROV-DM focusing on entities and activities. It builds on an earlier PROV-DM specialization in which Simulation Model, Simulation Experiment, Simulation Data, and Wet-lab Data have been identified as crucial entities of simulation studies [19]. Additionally, we have taken knowledge of modeling and simulation life cycles [1] into account and identified the Research Question, Assumptions, Requirements, the Qualitative Model to be important ingredients of the provenance of simulation models. We are also distinguishing between Building Simulation Model, Calibrating Simulation Model, Validating Simulation Model, and Analyzing Simulation Model activities and connect the entities and activities by using the relations *wasGeneratedBy* and *used*. In our definitions of the entities and activities, we have aimed at the minimal level of detail, or granularity, of the provenance graph to understand the course of a simulation study. We have also kept the necessary metadata of the entities and activities minimal to convey both the main idea of the simulation study and the content of each entity and activity. For storing, visualizing, and querying the provenance information, we have created the web-based tool *WebProv* that allows for each entity and activity to store (customized) metadata and references.

In order to examine our specialization of PROV-DM, the extensive analysis of 19 simulation studies of the canonical Wnt signaling pathway provided a suitable case study. We were able to explicitly show that most studies are connected to one or more other Wnt simulation studies, using (parts of) their simulation models, but also various data from wet-lab studies. Our result marks the outstanding role of the Wnt simulation model by Lee et al. (2003) [28] as the origin for most other models in our survey. Thus, a family of Wnt signaling models could be revealed.

In conclusion, provenance information provides added value to the existing list of documentation requirements and could complement and enrich the effort of "harmonizing semantic annotations for computational models in biology" [103].

Together with the exploitation of community standards and ontologies, the provenance information opens up further possibilities of reusing and analyzing simulation models, for example, to help with model selection, model merging, or model difference detection. Of course, to be fully accepted, our specialization of PROV-DM should be subject to a standardization initiative. We think that *WebProv*, or a similar tool, would be a valuable extension of model databases such as BioModels, as one could see where a simulation model comes from, whether there are other models connected to it, and in which way they are connected. This would help to quickly interpret the increasing number of published simulation models and find a suitable one for your research.

Supporting information

S1 Appendix.   Additional references for entities used by Wnt simulation studies. We show the references to additional studies that contain entities used by some of the 19 Wnt simulation studies.

S1 Dataset.   Complete provenance information of 19 Wnt simulation studies. This file contains the provenance information of the 19 analyzed simulation studies of the Wnt signaling pathway. It was exported from *WebProv* and may be imported into another instance of the tool.

S1 Figure.   Provenance graph of all 19 Wnt/β-catenin simulation studies and their depending studies using a circular layout. Studies which include additional pathways have been colored.

S1 Table.   Categorized assumptions. We present the results of the categorization of all assumptions found in the 19 simulation studies using SBO. We have have also added information about the key words that accompanied the assumptions.

S2 Table.   Categorized simulation experiments. We present the results of the categorization of the simulation experiments found in the 19 simulation studies using our categories.

Acknowledgments

We thank Nadja Schlungbaum for her excellent technical support.

References

1. Balci O. A life cycle for modeling and simulation. SIMULATION. 2012;88(7):870–883. doi:10.1177/0037549712438469.

2. Ruscheinski A, Wilsdorf P, Dombrowsky M, Uhrmacher AM. Capturing and Reporting Provenance Information of Simulation Studies Based on an Artifact-Based Workflow Approach. In: Proceedings of the 2019 ACM SIGSIM Conference on Principles of Advanced Discrete Simulation. SIGSIM-PADS '19. New York, NY, USA: Association for Computing Machinery; 2019. p. 185–196.

3. Wilsdorf P, Haack F, Uhrmacher A. Conceptual Models in Simulation Studies: Making it explicit. In: Proceedings of the 2020 Winter Simulation Conference. WSC '20. IEEE Press; 2020.

4. Monks T, Currie CSM, Onggo BS, Robinson S, Kunc M, Taylor SJE. Strengthening the reporting of empirical simulation studies: Introducing the STRESS guidelines. Journal of Simulation. 2018; p. 1–13. doi:10.1080/17477778.2018.1442155.

5. Erdemir A, Guess TM, Halloran J, Tadepalli SC, Morrison TM. Considerations for reporting finite element analysis studies in biomechanics. Journal of Biomechanics. 2012;45(4):625–633. doi:10.1016/j.jbiomech.2011.11.038.

6. Grimm V, Berger U, DeAngelis DL, Polhill JG, Giske J, Railsback SF. The ODD protocol: a review and first update. Ecological modelling. 2010;221(23):2760–2768. doi:10.1016/j.ecolmodel.2010.08.019.

7. Le Novère N, Finney A, Hucka M, Bhalla US, Campagne F, Collado-Vides J, et al. Minimum information requested in the annotation of biochemical models (MIRIAM). Nature biotechnology. 2005;23(12):1509. doi:10.1038/nbt1156.

8. Waltemath D, Adams R, Beard DA, Bergmann FT, Bhalla US, Britten R, et al. Minimum Information About a Simulation Experiment (MIASE). PLoS Computational Biology. 2011;7(4):e1001122. doi:10.1371/journal.pcbi.1001122.

9. Porubsky VL, Goldberg AP, Rampadarath AK, Nickerson DP, Karr JR, Sauro HM. Best Practices for Making Reproducible Biochemical Models. Cell Systems. 2020;11(2):109–120. doi:10.1016/j.cels.2020.06.012.

10. Malik-Sheriff RS, Glont M, Nguyen TVN, Tiwari K, Roberts MG, Xavier A, et al. BioModels — 15 years of sharing computational models in life science. Nucleic Acids Research. 2020;48(D1):D407–D415. doi:10.1093/nar/gkz1055.

11. Glont M, Nguyen TVN, Graesslin M, Hälke R, Ali R, Schramm J, et al. BioModels: expanding horizons to include more modelling approaches and formats. Nucleic Acids Research. 2018;46(D1):D1248–D1253. doi:10.1093/nar/gkx1023.

12. Olivier BG, Snoep JL. Web-based kinetic modelling using JWS Online. Bioinformatics. 2004;20(13):2143–2144. doi:10.1093/bioinformatics/bth200.

13. Lloyd CM, Lawson JR, Hunter PJ, Nielsen PF. The CellML Model Repository. Bioinformatics. 2008;24(18):2122–2123. doi:10.1093/bioinformatics/btn390.

14. Scharm M, Wolkenhauer O, Waltemath D. An algorithm to detect and communicate the differences in computational models describing biological systems. Bioinformatics. 2016;32(4):563–570. doi:10.1093/bioinformatics/btv484.

15. Cvijovic M, Almquist J, Hagmar J, Hohmann S, Kaltenbach HM, Klipp E, et al. Bridging the gaps in systems biology. Molecular Genetics and Genomics. 2014;289(5):727–734. doi:10.1007/s00438-014-0843-3.

16. Peng D, Warnke T, Haack F, Uhrmacher AM. Reusing simulation experiment specifications in developing models by successive composition - a case study to support developing models by successive extension. Simulation Modelling Practice and Theory. 2017;68:33–53. doi:10.1016/j.simpat.2016.07.006.

17. Peng D, Warnke T, Haack F, Uhrmacher AM. Reusing simulation experiment specifications to support developing models by successive extension. Simulation Modelling Practice and Theory. 2016;68:33–53. doi:10.1016/j.simpat.2016.07.006.

18. Belhajjame K, B'Far R, Cheney J, Coppens S, Cresswell S, Gil Y, et al. Prov-DM: The prov data model. World Wide Web Consortium (W3C); 2013.

19. Ruscheinski A, Gjorgevikj D, Dombrowsky M, Budde K, Uhrmacher AM. Towards a PROV Ontology for Simulation Models. In: International Provenance and Annotation Workshop. Springer; 2018. p. 192–195.

20. Ruscheinski A, Uhrmacher AM. Provenance in Modeling and Simulation Studies: Bridging Gaps. In: Proceedings of the 2017 Winter Simulation Conference. WSC '17. IEEE Press; 2017.

21. MacDonald BT, Tamai K, He X. Wnt/β-Catenin Signaling: Components, Mechanisms, and Diseases. Developmental Cell. 2009;17(1):9–26. doi:10.1016/j.devcel.2009.06.016.

22. Lloyd-Lewis B, Fletcher AG, Dale TC, Byrne HM. Toward a quantitative understanding of the Wnt/ β -catenin pathway through simulation and experiment. Wiley Interdisciplinary Reviews: Systems Biology and Medicine. 2013;5(4):391–407. doi:10.1002/wsbm.1221.

23. Steinhart Z, Angers S. Wnt signaling in development and tissue homeostasis. Development. 2018;145(11):dev146589. doi:10.1242/dev.146589.

24. Giles RH, van Es JH, Clevers H. Caught up in a Wnt storm: Wnt signaling in cancer. Biochimica et Biophysica Acta (BBA) - Reviews on Cancer. 2003;1653(1):1–24. doi:10.1016/S0304-419X(03)00005-2.

25. Clevers H, Nusse R. Wnt/β-catenin signaling and disease. Cell. 2012;149(6):1192–1205. doi:10.1016/j.cell.2012.05.012.

26. Logan CY, Nusse R. The Wnt Signaling Pathway in Development and Disease. Annual Review of Cell and Developmental Biology. 2004;20(1):781–810. doi:10.1146/annurev.cellbio.20.010403.113126.

27. Kofahl B, Wolf J. Mathematical modelling of Wnt/β-catenin signalling. Biochemical Society Transactions. 2010;38(5):1281–1285. doi:10.1042/BST0381281.

28. Lee E, Salic A, Krüger R, Heinrich R, Kirschner MW. The Roles of APC and Axin Derived from Experimental and Theoretical Analysis of the Wnt Pathway. PLoS Biology. 2003;1(1):e10. doi:10.1371/journal.pbio.0000010.

29. Krüger R, Heinrich R. Model reduction and analysis of robustness for the Wnt/β-catenin signal transduction pathway. Genome Informatics. 2004;15(1):138–148. doi:10.11234/gi1990.15.138.

30. Cho KH, Baek S, Sung MH. Wnt pathway mutations selected by optimal β-catenin signaling for tumorigenesis. FEBS Letters. 2006;580(15):3665–3670. doi:10.1016/j.febslet.2006.05.053.

31. Sick S, Reinker S, Timmer J, Schlake T. WNT and DKK determine hair follicle spacing through a reaction-diffusion mechanism. Science. 2006;314(5804):1447–1450. doi:10.1126/science.1130088.

32. Kim D, Rath O, Kolch W, Cho KH. A hidden oncogenic positive feedback loop caused by crosstalk between Wnt and ERK pathways. Oncogene. 2007;26(31):4571–4579. doi:10.1038/sj.onc.1210230.

33. Rodríguez-González J, Santillán M, Fowler A, Mackey MC. The segmentation clock in mice: interaction between the Wnt and Notch signalling pathways. Journal of theoretical biology. 2007;248(1):37–47. doi:10.1016/j.jtbi.2007.05.003.

34. van Leeuwen IMM, Byrne HM, Jensen OE, King JR. Elucidating the interactions between the adhesive and transcriptional functions of -catenin in normal and cancerous cells. Journal of Theoretical Biology. 2007;247(1):77–102. doi:10.1016/j.jtbi.2007.01.019.

35. Wawra C, Kühl M, Kestler HA. Extended analyses of the Wnt/β-catenin pathway: Robustness and oscillatory behaviour. FEBS Letters. 2007;581(21):4043–4048. doi:10.1016/j.febslet.2007.07.043.

36. Goldbeter A, Pourquié O. Modeling the segmentation clock as a network of coupled oscillations in the Notch, Wnt and FGF signaling pathways. Journal of Theoretical Biology. 2008;252(3):574–585. doi:10.1016/j.jtbi.2008.01.006.

37. Ramis-Conde I, Drasdo D, Anderson AR, Chaplain MA. Modeling the influence of the E-cadherin-β-catenin pathway in cancer cell invasion: a multiscale approach. Biophysical journal. 2008;95(1):155–165. doi:10.1529/biophysj.107.114678.

38. Goentoro L, Kirschner MW. Evidence that fold-change, and not absolute level, of β-catenin dictates Wnt signaling. Molecular cell. 2009;36(5):872–884. doi:10.1016/j.molcel.2009.11.017.

39. van Leeuwen IMM, Mirams GR, Walter A, Fletcher A, Murray P, Osborne J, et al. An integrative computational model for intestinal tissue renewal. Cell Proliferation. 2009;42(5):617–636. doi:10.1111/j.1365-2184.2009.00627.x.

40. Jensen PB, Pedersen L, Krishna S, Jensen MH. A Wnt Oscillator Model for Somitogenesis. Biophysical Journal. 2010;98(6):943–950. doi:10.1016/j.bpj.2009.11.039.

41. Mirams GR, Byrne HM, King JR. A multiple timescale analysis of a mathematical model of the Wnt/β-catenin signalling pathway. Journal of Mathematical Biology. 2010;60(1):131–160. doi:10.1007/s00285-009-0262-y.

42. Murray PJ, Kang JW, Mirams GR, Shin SY, Byrne HM, Maini PK, et al. Modelling Spatially Regulated β-Catenin Dynamics and Invasion in Intestinal Crypts. Biophysical Journal. 2010;99(3):716–725. doi:10.1016/j.bpj.2010.05.016.

43. Shin SY, Rath O, Zebisch A, Choo SM, Kolch W, Cho KH. Functional Roles of Multiple Feedback Loops in Extracellular Signal-Regulated Kinase and Wnt Signaling Pathways That Regulate Epithelial-Mesenchymal Transition. Cancer Research. 2010;70(17):6715–6724. doi:10.1158/0008-5472.CAN-10-1377.

44. Buske P, Galle J, Barker N, Aust G, Clevers H, Loeffler M. A Comprehensive Model of the Spatio-Temporal Stem Cell and Tissue Organisation in the Intestinal Crypt. PLoS Computational Biology. 2011;7(1):e1001045. doi:10.1371/journal.pcbi.1001045.

45. Kogan Y, Halevi-Tobias KE, Hochman G, Baczmanska AK, Leyns L, Agur Z. A new validated mathematical model of the Wnt signalling pathway predicts effective combinational therapy by sFRP and Dkk. Biochemical Journal. 2012;444(1):115–125. doi:10.1042/BJ20111887.

46. Mazemondet O, John M, Leye S, Rolfs A, Uhrmacher AM. Elucidating the Sources of β-Catenin Dynamics in Human Neural Progenitor Cells. PLoS ONE. 2012;7(8):e42792. doi:10.1371/journal.pone.0042792.

47. Schmitz Y, Rateitschak K, Wolkenhauer O. Analysing the impact of nucleo-cytoplasmic shuttling of β-catenin and its antagonists APC, Axin and GSK3 on Wnt/β-catenin signalling. Cellular Signalling. 2013;25(11):2210–2221. doi:10.1016/j.cellsig.2013.07.005.

48. Wang Hy, Huang Yx, Qi Yf, Zhang Y, Bao Yl, Sun Lg, et al. Mathematical models for the Notch and Wnt signaling pathways and the crosstalk between them during somitogenesis. Theoretical Biology and Medical Modelling. 2013;10(1):27. doi:10.1186/1742-4682-10-27.

49. Chen J, Xie ZR, Wu Y. Computational Modeling of the Interplay between Cadherin-Mediated Cell Adhesion and Wnt Signaling Pathway. PLoS ONE. 2014;9(6):e100702. doi:10.1371/journal.pone.0100702.

50. Tan C, Gardiner BS, Hirokawa Y, Smith DW, Burgess AW. Analysis of Wnt signaling β-catenin spatial dynamics in HEK293T cells. BMC Systems Biology. 2014;8(1):44. doi:10.1186/1752-0509-8-44.

51. Haack F, Lemcke H, Ewald R, Rharass T, Uhrmacher AM. Spatio-temporal Model of Endogenous ROS and Raft-Dependent WNT/Beta-Catenin Signaling Driving Cell Fate Commitment in Human Neural Progenitor Cells. PLoS Computational Biology. 2015;11(3):e1004106. doi:10.1371/journal.pcbi.1004106.

52. MacLean AL, Rosen Z, Byrne HM, Harrington HA. Parameter-free methods distinguish Wnt pathway models and guide design of experiments. Proceedings of the National Academy of Sciences. 2015;112(9):2652–2657. doi:10.1073/pnas.1416655112.

53. Padala RR, Karnawat R, Viswanathan SB, Thakkar AV, Das AB. Cancerous perturbations within the ERK, PI3K/Akt, and Wnt/β-catenin signaling network constitutively activate inter-pathway positive feedback loops. Molecular BioSystems. 2017;13(5):830–840. doi:10.1039/C6MB00786D.

54. Siegle L, Schwab JD, Kühlwein SD, Lausser L, Tümpel S, Pfister AS, et al. A Boolean network of the crosstalk between IGF and Wnt signaling in aging satellite cells. PLoS ONE. 2018;13(3):e0195126. doi:10.1371/journal.pone.0195126.

55. Cavallo JC, Scholpp S, Flegg MB. Delay-driven oscillations via Axin2 feedback in the Wnt/β-catenin signalling pathway. Journal of Theoretical Biology. 2020;507:110458. doi:10.1016/j.jtbi.2020.110458.

56. Haack F, Budde K, Uhrmacher AM. Exploring the mechanistic and temporal regulation of LRP6 endocytosis in canonical WNT signaling. Journal of Cell Science. 2020;133(15). doi:10.1242/jcs.243675.

57. Staehlke S, Haack F, Waldner AC, Koczan D, Moerke C, Mueller P, et al. ROS Dependent Wnt/β-Catenin Pathway and Its Regulation on Defined Micro-Pillars—A Combined In Vitro and In Silico Study. Cells. 2020;9(8):1784. doi:10.3390/cells9081784.

58. Ward D, Montes Olivas S, Fletcher A, Homer M, Marucci L. Cross-talk between Hippo and Wnt signalling pathways in intestinal crypts: Insights from an agent-based model. Computational and Structural Biotechnology Journal. 2020;18:230–240. doi:10.1016/j.csbj.2019.12.015.

59. Yilmaz L, Chakladar S, Doud K. The Goal-Hypothesis-Experiment Framework: A Generative Cognitive Domain Architecture for Simulation Experiment Management. In: Proceedings of the 2016 Winter Simulation Conference. WSC '16. IEEE Press; 2016. p. 1001—1012.

60. Bergmann FT, Adams R, Moodie S, Cooper J, Glont M, Golebiewski M, et al. COMBINE archive and OMEX format: one file to share all information to reproduce a modeling project. BMC Bioinformatics. 2014;15(1):369–377. doi:10.1186/s12859-014-0369-z.

61. Carusi A, Burrage K, Rodríguez B. Bridging experiments, models and simulations: an integrative approach to validation in computational cardiac electrophysiology. American Journal of Physiology-Heart and Circulatory Physiology. 2012;doi:10.1152/ajpheart.01151.2011.

62. Lorig F, Lebherz DS, Berndt JO, Timm IJ. Hypothesis-Driven Experiment Design in Computer Simulation Studies. In: Proceedings of the 2017 Winter Simulation Conference. WSC '17. IEEE Press; 2017.

63. Lee E, Salic A, Kirschner MW. Physiological regulation of β-catenin stability by Tcf3 and CK1ε. Journal of Cell Biology. 2001;154(5):983—-994. doi:10.1083/jcb.200102074.

64. Dajani R, Fraser E, Roe SM, Yeo M, Good VM, Thompson V, et al. Structural basis for recruitment of glycogen synthase kinase 3beta to the axin-APC scaffold complex. The EMBO Journal. 2003;22(3):494–501. doi:10.1093/emboj/cdg068.

65. Salic A, Lee E, Mayer L, Kirschner MW. Control of Beta-Catenin Stability: Reconstitution of the Cytoplasmic Steps of the Wnt Pathway in Xenopus Egg Extracts. Molecular Cell. 2000; p. 10. doi:10.1016/S1097-2765(00)80446-3.

66. Robinson S. Conceptual modelling for simulation Part I: definition and requirements. Journal of the Operational Research Society. 2008;59(3):278–290. doi:10.1057/palgrave.jors.2602368.

67. Courtot M, Juty N, Knüpfer C, Waltemath D, Zhukova A, Dräger A, et al. Controlled vocabularies and semantics in systems biology. Molecular Systems Biology. 2011;7(1):543. doi:10.1038/msb.2011.77.

68. Juty N, le Novère N. In: Dubitzky W, Wolkenhauer O, Yokota H, Cho KH, editors. Systems biology ontology. Springer-Verlag New York; 2013. p. 2063–2063.

69. Le Novère N, Hucka M, Mi H, Moodie S, Schreiber F, Sorokin A, et al. The Systems Biology Graphical Notation. Nature Biotechnology. 2009;27(8):735–741. doi:10.1038/nbt.1558.

70. Glass L, Kauffman SA. The logical analysis of continuous, non-linear biochemical control networks. Journal of Theoretical Biology. 1973;39(1):103–129. doi:10.1016/0022-5193(73)90208-7.

71. Torres NV, Santos G. The (Mathematical) Modeling Process in Biosciences; 2015.

72. Hofmeyr JHS. Kinetic modelling of compartmentalised reaction networks. Biosystems. 2020;197:104203. doi:10.1016/j.biosystems.2020.104203.

73. Fisher J, Henzinger TA. Executable cell biology. Nature Biotechnology. 2007;25(11):1239–1249. doi:10.1038/nbt1356.

74. Ciocchetta F, Hillston J. Bio-PEPA: A framework for the modelling and analysis of biological systems. Theoretical Computer Science. 2009;410(33-34):3065–3084. doi:10.1016/j.tcs.2009.02.037.

75. Boemo MA, Cardelli L, Nieduszynski CA. The Beacon Calculus: A formal method for the flexible and concise modelling of biological systems. PLoS computational biology. 2020;16(3):e1007651. doi:10.1371/journal.pcbi.1007651.

76. Karr JR, Takahashi K, Funahashi A. The principles of whole-cell modeling. Current opinion in microbiology. 2015;27:18–24. doi:10.1016/j.mib.2015.06.004.

77. Wang RS, Saadatpour A, Albert R. Boolean modeling in systems biology: an overview of methodology and applications. Physical Biology. 2012;9(5):055001. doi:10.1088/1478-3975/9/5/055001.

78. Chaouiya C. Petri net modelling of biological networks. Briefings in Bioinformatics. 2007;8(4):210–219. doi:10.1093/bib/bbm029.

79. Hucka M, Finney A, Sauro HM, Bolouri H, Doyle JC, Kitano H, et al. The systems biology markup language (SBML): a medium for representation and exchange of biochemical network models. Bioinformatics. 2003;19(4):524–531. doi:10.1093/bioinformatics/btg015.

80. Lloyd CM, Halstead MD, Nielsen PF. CellML: its future, present and past. Progress in biophysics and molecular biology. 2004;85(2-3):433–450. doi:10.1016/j.pbiomolbio.2004.01.004.

81. Köhn D, Le Novère N. In: Heiner M, Uhrmacher AME, editors. SED-ML—An XML Format for the Implementation of the MIASE Guidelines. vol. 5307. Springer Berlin Heidelberg; 2008. p. 176–190.

82. Ewald R, Uhrmacher AM. SESSL: A domain-specific language for simulation experiments. ACM Transactions on Modeling and Computer Simulation. 2014;24(2):1–25. doi:10.1145/2567895.

83. Wilsdorf P, Haack F, Budde K, Ruscheinski A, Uhrmacher AM. Conducting systematic, partly automated simulation studies—Unde Venis et Quo Vadis. AIP Conference Proceedings. 2020;2293(1):020001. doi:10.1063/5.0026939.

84. Vera J, Lischer C, Nenov M, Nikolov S, Lai X, Eberhardt M. Mathematical Modelling in Biomedicine: A Primer for the Curious and the Skeptic. International Journal of Molecular Sciences. 2021;22(2). doi:10.3390/ijms22020547.

85. Toni T, Welch D, Strelkowa N, Ipsen A, Stumpf MPH. Approximate Bayesian computation scheme for parameter inference and model selection in dynamical systems. Journal of The Royal Society Interface. 2009;6(31):187–202. doi:10.1098/rsif.2008.0172.

86. Palaniappan SK, Gyori BM, Liu B, Hsu D, Thiagarajan P. Statistical model checking based calibration and analysis of bio-pathway models. In: International Conference on Computational Methods in Systems Biology. Springer; 2013. p. 120–134.

87. Mitra ED, Suderman R, Colvin J, Ionkov A, Hu A, Sauro HM, et al. PyBioNetFit and the biological property specification language. IScience. 2019;19:1012–1036. doi:10.1016/j.isci.2019.08.045.

88. Jha SK, Clarke EM, Langmead CJ, Legay A, Platzer A, Zuliani P. A bayesian approach to model checking biological systems. In: International conference on computational methods in systems biology. Springer; 2009. p. 218–234.

89. Agha G, Palmskog K. A Survey of Statistical Model Checking. ACM Transactions on Modeling and Computer Simulation. 2018;28(1). doi:10.1145/3158668.

90. Balci O. Verification Validation and Accreditation of Simulation Models. In: Proceedings of the 29th Conference on Winter Simulation. WSC '97. USA: IEEE Computer Society; 1997. p. 135–141.

91. Boutillier P, Maasha M, Li X, Medina-Abarca HF, Krivine J, Feret J, et al. The Kappa platform for rule-based modeling. Bioinformatics. 2018;34(13):i583–i592. doi:10.1093/bioinformatics/bty272.

92. Groß A, Kracher B, Kraus JM, Kühlwein SD, Pfister AS, Wiese S, et al. Representing dynamic biological networks with multi-scale probabilistic models. Communications biology. 2019;2(1):1–12. doi:10.1038/s42003-018-0268-3.

93. Warnke T, Helms T, Uhrmacher AM. Reproducible and flexible simulation experiments with ML-Rules and SESSL. Bioinformatics. 2017;34(8):1424–1427. doi:10.1093/bioinformatics/btx741.

94. Thomas BR, Chylek LA, Colvin J, Sirimulla S, Clayton AHA, Hlavacek WS, et al. BioNetFit: a fitting tool compatible with BioNetGen, NFsim and distributed computing environments. Bioinformatics. 2015;32(5):798–800. doi:10.1093/bioinformatics/btv655.

95. Sorokin A, Sorokina O, Douglas Armstrong J. In: Hlavacek W, editor. RKappa: Software for Analyzing Rule-Based Models. Springer New York; 2019. p. 363–390.

96. Sansone SA, McQuilton P, Rocca-Serra P, Gonzalez-Beltran A, Izzo M, Lister AL, et al. FAIRsharing as a community approach to standards, repositories and policies. Nature Biotechnology. 2019;37(4):358–367. doi:10.1038/s41587-019-0080-8.

97. Wilkinson MD, Dumontier M, Aalbersberg IJ, Appleton G, Axton M, Baak A, et al. The FAIR Guiding Principles for scientific data management and stewardship. Scientific Data. 2016;3(1):160018. doi:10.1038/sdata.2016.18.

98. Scharm M, Waltemath D. A fully featured COMBINE archive of a simulation study on syncytial mitotic cycles in Drosophila embryos. F1000Research. 2016;5:2421. doi:10.12688/f1000research.9379.1.

99. Gierer A, Meinhardt H. A theory of biological pattern formation. Kybernetik. 1972;12(1):30–39. doi:10.1007/BF00289234.

100. Bafico A, Liu G, Yaniv A, Gazit A, Aaronson SA. Novel mechanism of Wnt signalling inhibition mediated by Dickkopf-1 interaction with LRP6/Arrow. Nature Cell Biology. 2001;3(7):683–686. doi:10.1038/35083081.

101. Hannoush RN. Kinetics of Wnt-driven β-catenin stabilization revealed by quantitative and temporal imaging. PLoS ONE. 2008;3(10). doi:10.1371/journal.pone.0003498.

102. Dequéant ML, Glynn E, Gaudenz K, Wahl M, Chen J, Mushegian A, et al. A Complex Oscillating Network of Signaling Genes Underlies the Mouse Segmentation Clock. Science. 2006;314(5805):1595—-1598. doi:10.1126/science.1133141.

103. Neal ML, König M, Nickerson D, Mısırlı G, Kalbasi R, Dräger A, et al. Harmonizing semantic annotations for computational models in biology. Briefings in Bioinformatics. 2019;20(2):540–550. doi:10.1093/bib/bby087.