Sensitive, reliable, and robust circRNA detection from RNA-seq with CirComPara2

Enrico Gaffo[1,*], Alessia Buratin[1,2], Anna Dal Molin[1], Stefania Bortoluzzi[1,3,*]

[1] Department of Molecular Medicine, University of Padova, Padova, Italy

[2] Department of Biology, University of Padova, Padova, Italy

[3] Interdepartmental Center For Innovative Biotechnologies, University of Padova, Padova, Italy

[*] corresponding authors

Tel: +39-049-827-6502

Fax: +39-049-827-6208

Email: stefania.bortoluzzi@unipd.it (S.B.), enrico.gaffo@unipd.it (E.G.)

Keywords: circRNAs, bioinformatics, transcriptomics, RNA-seq

Abstract

Current methods for identifying circular RNAs (circRNAs) suffer from low discovery rates and inconsistent performance in diverse data sets. Therefore, the applied detection algorithm can bias high-throughput study findings by missing relevant circRNAs. Here, we show that our bioinformatics tool CirComPara2 (https://github.com/egaffo/CirComPara2), by combining multiple circRNA detection methods, consistently achieves high recall rates without loss of precision in simulated and different real-data sets.

Main

Recent research uncovered that eukaryotic transcriptomes comprise thousands of stable circular RNAs (circRNAs), which can modulate cellular processes by encoding functional peptides and interacting with microRNA and RNA-binding proteins [1]. The regulatory role of circRNAs and their potential as biomarkers actuate the integration of circRNA in conventional transcriptome analysis, especially in cancer research and studies of pathological conditions.

CircRNAs originate by transcript back-splicing, a process where the molecule's 3' and 5' ends are covalently joined. Studies of circRNAs rapidly increased in pace with the development of bioinformatics approaches that identify the sequences spanning circRNA back-splice junctions from total RNA-seq data. To date, several methods for circRNA identification have been developed [2], but none clearly outperforms the others since they provide either highly sensitive or highly precise predictions [3–6]. CircRNA detection algorithms employ filtering procedures [3–6] that remove false-positive guesses (FPs) to improve precision, but that may also reject true circRNAs, thus increasing the number of false-negative predictions (FNs). Unlike FPs, FN errors cannot be amended with experimental validations and can cause overlooking circRNAs of interest, as suggested by the following analysis.

We analysed simulated RNA-seq data of 5,680 circRNAs from the whole human genome with nine circRNA discovery pipelines: circRNA_finder [7], CIRI2 [8], DCC [9], Findcirc [10], Segemehl [11], and CIRCexplorer2 [12] coupled to either BWA [13], Segemehl, STAR [14] and TopHat-Fusion [15]. On average,

49% of each method's FNs were above the overall circRNA median expression (Figure 1a), showing

that nearly half of the missed circRNAs had a considerable expression level. The methods' output was

further examined for the 1,945 circRNAs missed by one or more tools (the FN set) by inspecting each

algorithm for correct identification of the circRNAs in the FN set. Only 4% circRNAs in the FN set

were not discovered by any of the nine methods (Figure 1b), suggesting that the application of

multiple algorithms with dissimilar and possibly complementary features can improve the circRNA

detection rate.

However, combining predictions from different methods can worsen the overall precision if the

number of FPs is not controlled. Our former method CirComPara [16] combined four circRNA detection

tools and limited the number of FPs by excluding the circRNAs identified by single methods,

considering that circRNAs predicted by two or more algorithms help discard many FPs [5].

Interestingly, two or more methods detected 95% of the FNs in our simulation, with distinct circRNA

sets identified by different method combinations, whereas single tools (namely Segemehl,

CIRCexplorer2 on BWA, and CIRCexplorer2 on TopHat-Fusion) identified only 1% (Figure 1b).

This observation prompted us to implement CirComPara2, which integrates the nine circRNA

detection algorithms presented above. Although circRNA_finder and Segemehl can be enabled in

CirComPara2 by custom parameters, they are not considered in the default setting (Figure 1c)

because, in the simulated data analysis, a high number of FPs affected the conjoint predictions of

methods combinations that included circRNA_finder or Segemehl (Supplementary Figure S1). This

outcome agreed with the previous observation that certain method combinations do not ameliorate the

discovery of true circRNAs [5].

Besides, we assessed whether CirComPara2 achieved the optimal balance between the numbers of the

recovered FNs and the introduced FPs using the conjoint predictions of at least two methods or by a

different number of methods combined. The predictions based on all methods resulted in the highest

recall (0.99) but at the cost of the lowest precision (0.90; Figure 1d), indicating that the accumulation

of FPs outweighed the gained FNs. Next, subsetting predictions to the circRNAs commonly detected

by at least two tools showed a slightly reduced recall (0.98) with a substantially increased precision

(0.99). Instead, the conjoint predictions of three or more methods considerably decreased the recall

(0.96 to 0.68) with only a modest increase in precision (0.99 to 1.00). We calculated F_1-scores, which

provide single-value estimates accounting for and evenly weighing both recall and precision, to rank

the best performing method combinations. The highest F_1-score achieved by the conjoint predictions

of two or more methods (0.99; Figure 1d) indicated and confirmed the optimal trade-off between

recall and precision. Therefore, CirComPara2 was set to report the predictions common to at least two

methods.

Next, we compared the performances on the simulated data of CirComPara2 and the other nine

methods. CirComPara2 obtained the highest F_1-score (0.99) by achieving the highest recall (0.98)

while holding a precision comparable to the other algorithms (0.99 versus 0.92 to 1.00; Figure 2a)

confirming that CirComPara2 rectified the true circRNAs missed by the other methods. CirComPara2

maintained the highest F_1-score (0.98) even with a mostly incomplete gene annotation input (see

Methods), which for the annotation-based methods caused a dramatic reduction (up to -0.14) of the

recall (and of F_1-scores) (Supplementary Figure S2), indicating that CirComPara2 can leverage the

integrated annotation-independent algorithms, and suggesting that CirComPara2 can be efficient also

when applied to RNA-seq data of organisms with poor genome annotation.

CircRNA expression analysis usually involves downstream data cleaning to remove background noise

signals or mapping errors and poorly expressed circRNAs of little interest. Consequently, the

circRNAs with small back-splice junction read counts (BJRs) are routinely filtered out. As shown in

Figure 1a, FPs generally have small BJRs, suggesting that more reliable circRNAs can be retained by

simply filtering the expression abundance. Accordingly, all methods scored higher precision when the

minimum-BJR filter threshold increased but with a corresponding reduced recall, indicating that true

circRNAs (with low expression) were discarded as well (Supplementary Figure S3). CirComPara2

showed similar behaviour but maintained the highest recall compared to other methods at equal

precision (Figure 2b; Supplementary Table S1), suggesting that the circRNAs recovered by

CirComPara2 were true findings of considerable abundance, which may represent relevant circRNAs

in real experiments.

The gold standard for evaluating circRNA detection methods on real RNA-seq data is to treat

sequencing libraries with RNase R, which enriches the circRNA fraction by exploiting the circRNA

exonuclease degradation resistance derived by the lack of a single-stranded 3′ overhang [3,5,6,8,17].

CirComPara2 was then assessed on 142 public real RNA-seq data sets from six independent studies,

including human cell lines and various human, Rhesus macaque, and mice tissues (Supplementary

Table S2). Each sample matched ribosomal RNA-depleted and RNase R-treated libraries, which we

used as control samples (see Methods).

Performance of the methods agreed with the simulation analysis and previous benchmark study results

[3,5]: Segemehl showed high recall (median 0.75; Figure 2c), but the lowest precision (median 0.92), and

CIRCexplorer2 on BWA showed the most reliable predictions (median precision 0.97; Figure 2d) as

expected from annotation-based algorithms. Ranking the tools by their median F_1-score on the real-

data sets, CirComPara2 had the highest (0.91) and significantly different value (q < 0.001; Figure 2e),

substantially outperforming the method with the next best F_1-score, Segemehl (median 0.82;

Supplementary Table S3). CirComPara2's highest F_1-score resulted from its significantly larger recall

(median 0.86; q < 0.001; Figure 2c) and a negligible loss of precision compared to the other methods

(0.01 median reduction from the most precise method; Figure 2d). Notably, CirComPara2 had the

narrowest interquartile range for F_1-scores across the real-data sets (0.11; Figure 2e; Supplementary

Table S3), proving robustness in different scenarios. In light of the more challenging nature of real

compared to simulated data [4,17], these results confirmed the advantage of CirComPara2 over other

methods.

CirComPara2 implements a fully automated computational pipeline for circRNA detection and

quantification, from read pre-processing to circRNA annotation (Supplementary Figure S4), with a

modular and highly parallelised implementation that make it computationally efficient and resilient.

CirComPara2 is available as standalone software and Docker image to facilitate installation,

portability, and reproducibility.

Recently, large circRNA databases have been compiled using approaches similar to CirComPara2's

strategy [18]. For instance, circAtlas2.0 [19] retained circRNAs identified by at least two methods among

CIRI2, CIRCexplorer2, Findcirc and DCC; the same combination but replacing DCC with

circRNA_finder has been used in CircRic [20]. These two method combinations performed better on our

real-data sets than most of the algorithms except CirComPara2 (Supplementary Table S3), which

achieved similar precision and a slightly more than 0.2 better recall, proving the asset given by the

larger number of tools combined in CirComPara2. In light of the considerations above, CirComPara2

could provide comprehensive and reliable results to compile circRNA databases.

In conclusion, CirComPara2 mitigates the biases affecting single circRNA detection methods,

allowing inclusive and robust detection of circRNAs in diverse biological contexts, from non-model

organisms to human disease and cancer.

Materials and Methods

Simulated data set

CircRNA reads were simulated with the CIRI_simulator from the CIRI2 tool suite using the whole GRCh38 human genome and Gencode v29 gene annotation.

The parameters used in ciri_simulator were: -C 20 -LC 0 -R 1 -LR 1 -L 101 -E 1 -CHR1 0 -M 250 -M2 450 -PM 0 -S 70 -S2 0 -SE 0 -PSI 10.

A total of 10% (30% for the highly pruned annotation simulation) of the gene annotation for the simulated circRNA parent genes was removed from the annotation file and used as input to circRNA detection methods and to simulate linear transcript reads with Polyester (the reads_per_transcript parameter was set to 300). The linear transcript read files were then concatenated to the circRNA read files.

Code for generating the simulated data is available as a software tool *CCP_simulator* at https://github.com/egaffo/CCP_simulator. The parameter ANNOPARTS used in *CCP_simulator* for the two filters on gene annotation (standard and high pruning) was set to "85,4,5,1,0,0,0" and "60,15,10,2.5,6,3.5,3", respectively.

Real-data sets

Overall, 71 samples with matched rRNA depletion and rRNA depletion followed by RNase R treatment libraries from six studies (Supplementary Table S2), for a total of 142 samples processed, were retrieved from Gene Expression Omnibus (GEO) or the National Genomics Data Center (NGDC) databases.

True positive circRNAs were defined as those having higher circular-to-linear proportion in the matched circRNA enriched sample. To avoid detection bias caused by different sample sequencing depth, only circRNAs detected in the RNase R treated samples were considered.

Reads from PRJCA000751 were trimmed to 150bp in the preprocessing phase, as reported in the original work.

Method predictions in genomic scaffolds or from the mitochondrial genome were not considered.

CircRNAs predicted with a length shorter than the library read length or longer than the longest gene

expressed in the sample (computed as genes with TPM $\geq$ 1 computed by StringTie v2.1.4) were

filtered out.

CircRNA detection methods' parameters

The following genome and gene annotations from the Ensembl database were used in the analyses:

GRCh38 human genome and v97 gene annotation, Mmul 10 *Macaca mulatta* genome and v101 gene

annotation, and GRCm38 *Mus musculus* genome and v101 gene annotation.

CirComPara2 default parameters were set for the analyses, which are as follows:

adaptors from the Trimmomatic v0.39 TruSeq3-PE-2.fa file; PREPROCESSOR = "trimmomatic";

PREPROCESSOR_PARAMS = "MAXINFO:40:0.5 LEADING:20 TRAILING:20

SLIDINGWINDOW:4:30 MINLEN:50 AVGQUAL:26". For the PRJCA000751 data sets, the

CROP:150 option was appended to the parameter. STAR_PARAMS = '--runRNGseed 123 --

outSJfilterOverhangMin 15 15 15 15 --alignSJoverhangMin 15 --alignSJDBoverhangMin 15 --

seedSearchStartLmax 30 --outFilterScoreMin 1 --outFilterMatchNmin 1 --outFilterMismatchNmax 2

--chimSegmentMin 15 --chimScoreMin 15 --chimScoreSeparation 10 --chimJunctionOverhangMin

15'. CIRCRNA_METHODS = 'circexplorer2_bwa, circexplorer2_segemehl, circexplorer2_star,

circexplorer2_tophat, ciri, dcc, findcirc' ('circrna_finder' and 'testrealign' values were used in

additional runs to obtain CircRNA_finder and Segemhel predictions); CPUS = 12; BWA_PARAMS =

'-T 19'; SEGEMEHL_PARAMS = '-D 0'; BOWTIE2_PARAMS = '--reorder --score-min=C,-15,0 -q

--seed 123'; DCC_EXTRA_PARAMS = '-fg -M -F -Nr 1 1 -N'; TESTREALIGN_PARAMS = 'q

median_1'; FINDCIRC_EXTRA_PARAMS = '--best-qual 40 --filter-tags UNAMBIGUOUS_BP --

filter-tags ANCHOR_UNIQUE' (this setting implements the optimization suggested by Hansen [5]).

MIN_METHODS = 2; MIN_READS = 2; CIRC_MAPPING = "{'SE':

['STAR','TOPHAT','BOWTIE2'],'PE':['BWA','SEGEMEHL']}"; HISAT2_PARAMS = '--seed 123'.

Segemehl predictions reported in the sngl.bed and trns.txt files were merged to include spliced reads

spanning >20,000 bps, as CirComPara2 performs it.

Read alignment and circRNA detection methods' parameters were set as the value in the

corresponding CirComPara2 parameters. All other parameters not mentioned were left with default

values.

Details of the CirComPara2 method

CircRNA expression estimates in CirComPara2 are represented as the sum of all unique back-splice

junction reads (BJRs) identified by the circRNA methods. Then, the number of BJR fragments is

counted keeping track of the number of methods detecting each circRNAs. Finally, circRNAs with at

least two reads identified by two or more methods are reported. The MIN_METHODS and

MIN_READS options can be used to modify the required minimum reads and methods.

The CirComPara2 pipeline considers a preliminary alignment step that maps the reads linearly on the

genome. Linearly aligned reads are then used to characterise canonical gene and transcript expression

and count the linearly spliced reads spanning the back-splice junctions. Instead, linearly unmapped

reads are used as input to the circRNA detection methods.

Evaluation metrics and statistical tests

In evaluating method predictions, to compare samples with their matched control libraries, the

different sequencing depths of the control library and the biochemical variability of the

exoribonuclease in RNase R treatment have been adjusted by considering the proportion between the

expression of the predicted circRNAs and the linear transcripts sharing the back-spliced exons. In

each sample and for each method, we computed the circular-to-linear expression proportion (CLP) of

each predicted circRNA by counting the number of reads back-spliced (BS_{reads}) and linearly-spliced

(LS_{reads}) on the circRNA back-splice junctions, respectively. Then, the CLPs were calculated as

$BS_{reads}/(BS_{reads}+ LS_{reads})$. Szabo and Salzman [17] also suggested using the ratio between the expression of

circRNAs and their linear counterparts to overcome the evaluation issues deriving by RNase R treated

control samples.

Assuming that RNase R should degrade linear transcripts more than circRNAs regardless of its

efficiency in different samples, circRNAs with an equal or increased CLP in the control samples were

deemed true-positives (TPs); false-positives (FPs) otherwise. Only circRNAs detected in the control

libraries were considered to limit incorrect FP calls due to a lower sequencing depth of the control

sample.

The precision was defined as TP/(TP + FP). The recall was computed as TP/(TP + FN) and F_1-score

as (2 × Precision × Recall)/(Precision + Recall), where TP and FN denote the true-positive and false-

negative numbers.

Wilcoxon one-tailed paired tests were used to compare CirComPara2 greater recall and F_1-score or

lower precision with each method. Bonferroni multiple test correction was applied to compute

adjusted p-values (q-values). The q-values reported in the main text refer to the highest value among

the pairwise comparisons for recall and F_1-score, whereas to the lowest value for precision

comparisons.

Software versions

The software version of the circRNA detection methods and chimeric read aligners used in this study:

CIRCexplorer2 [12] v2.3.8, CircRNA_finder [7] v1.1, CIRI2 [8] v2.0.6, DCC v0.4.8 [9], Findcirc [10] v1.2,

Segemehl [11] v0.3.4 (used also by CIRCexplorer2), BWA MEM [13] v0.7.15 (used by CIRI2 and

CIRCexplorer2), STAR [14] v2.6.1e (used by circRNA_finder, DCC, and CIRCexplorer2), TopHat2 [15]

v2.1.0 (used for the TopHat-Fusion algorithm by CIRCexplorer2). CirComPara2 v0.1 was used to run

the analysis.

Key Points

● Current circRNA detection methods achieve either high precision or high recall.

● Current circRNA detection methods do not perform consistently across different data sets.

● Current circRNA detection methods can overlook circRNAs of interest.

● CirComPara2 achieves high detection recall with no loss of precision by combining seven

methods.

● CirComPara2 consistently outperforms other methods regardless of the biological context.

Funding

This work has been supported by the Italian Ministry of Education, Universities, and Research grant PRIN 2017 2017PPS2X4_003 (S.B.), AIRC, Milan, Italy Investigator Grant 2017 20052 (S.B.), and Fondazione Umberto Veronesi, Milan, Italy Fellowship 2020 (E.G.).

Acknowledgements

We thank Dr Geertruij te Kronnie for insightful suggestions and critical revision of the manuscript.

Author Contributions

Conceptualisation, E.G.; Data curation, E.G.; Formal Analysis, E.G. and A.B.; Funding Acquisition, E.G. and S.B.; Methodology, E.G. and A.B.; Project Administration, S.B.; Resources, S.B.; Software, E.G. and A.B.; Supervision, E.G. and S.B.; Visualization, E.G.; Writing – Original Draft, E.G., A.B. and S.B.; Writing – Review & Editing, E.G., A.B., A.D.M. and S.B. All authors have read and agreed to the published version of the manuscript.

Conflicts of Interest

The authors declare no conflict of interest.

 Figures

 Figure 1

Figure 1. CircRNAs overlooked by common detection methods and the CirComPara2 approach. a, The expression

level of predicted circRNAs. BJR: back-splice junction read counts; C2BW: CIRCexplorer2 on BWA; C2SE:

CIRCexplorer2 on Segemehl; C2ST: CIRCexplorer2 on STAR; C2TH: CIRCexplorer2 on TopHat-Fusion; CF:

circRNA_finder; CIRI: CIRI2; FC: Findcirc; SE: Segemehl; FP: false-positive; FN: false negative; TP: true positive. **b**,

Number of methods detecting circRNAs not detected by other methods and the number of the FNs detected. Colour refers

to the number of methods conjointly detecting circRNAs missed by other tools. The vertical bars show the number of FN

circRNAs detected by the methods indicated in the coloured dots below the bars. The bars denote disjoint circRNA sets. Grey dots indicate the methods failing to detect the circRNAs considered in the bar chart on the top. The horizontal bars on the right represent the overall number of FN circRNAs detected by the methods. The horizontal bar shows the percentage of detected FNs by grouping method combinations according to the number of combined methods. **c**, Workflow of the CirComPara2 strategy showing circRNA detection methods (coloured rounded corner boxes) with the respective chimeric read aligners (white boxes). The central Venn diagram represents the optimised combination of methods' prediction intersections implemented by CirComPara2 with circRNAs conjointly detected by two or more methods (grey filled intersections) retained as default. **d**, precision (red), recall (yellow) and F_1-score (green) for different numbers of methods considered by CirComPara2: ≥ 1 indicates the union of all single methods predictions, ≥ 2 indicates any pair of methods, and so on, up to 7, which indicates the conjoint predictions of all the methods considered. The grey filled parts in Venn diagrams show the intersections considered by the conjoint method combinations.

Figure 2. Performance of circRNA detection methods on simulated and real data sets. Simulated data (**a-b**): **a**, precision and recall of the circRNA detection methods (labels as in Figure 1), including CirComPara2 (CCP2; green dot); the dashed-line curves display plot areas for 0.85, 0.90, 0.95 and 0.98 F_1-scores. **b**, CircRNA detection methods' performance upon application of filters from 2 to 10 minimum circRNA raw expression estimates (BJR: back-splice junction read counts); dashed-line curves delimit F_1-scores plot areas from 0.92 to 0.98 with 0.01 increase steps; method colours as in (a). Real-data set benchmark density plot of (**c**) recall, (**d**) precision and (**e**) F_1-score; distribution quartiles are indicated by white vertical lines; each method contrasted with CirComPara2 Wilcoxon paired test, Bonferroni adjusted p-values are reported on the right of the plot.

References

1. Xiao, M.-S., Ai, Y. & Wilusz, J. E. Biogenesis and Functions of Circular RNAs Come into Focus. *Trends Cell Biol.* **30**, 226–240 (2020).

2. Chen, L. *et al.* The bioinformatics toolbox for circRNA discovery and analysis. *Brief. Bioinform.* (2020) doi:10.1093/bib/bbaa001.

3. Zeng, X., Lin, W., Guo, M. & Zou, Q. A comprehensive overview and evaluation of circular RNA detection tools. *PLoS Comput. Biol.* **13**, e1005420 (2017).

4. Chen, I., Chen, C.-Y. & Chuang, T.-J. Biogenesis, identification, and function of exonic circular RNAs. *Wiley Interdiscip. Rev. RNA* **6**, 563–579 (2015).

5. Hansen, T. B. Improved circRNA Identification by Combining Prediction Algorithms. *Front Cell Dev Biol* **6**, 20 (2018).

6. Hansen, T. B., Venø, M. T., Damgaard, C. K. & Kjems, J. Comparison of circular RNA prediction tools. *Nucleic Acids Res.* **44**, e58 (2016).

7. Westholm, J. O. *et al.* Genome-wide analysis of drosophila circular RNAs reveals their structural and sequence properties and age-dependent neural accumulation. *Cell Rep.* **9**, 1966–1980 (2014).

8. Gao, Y., Zhang, J. & Zhao, F. Circular RNA identification based on multiple seed matching. *Brief. Bioinform.* **19**, 803–810 (2018).

9. Cheng, J., Metge, F. & Dieterich, C. Specific identification and quantification of circular RNAs from sequencing data. *Bioinformatics* **32**, 1094–1096 (2016).

10. Memczak, S. *et al.* Circular RNAs are a large class of animal RNAs with regulatory potency. *Nature* **495**, 333–338 (2013).

11. Hoffmann, S. *et al.* A multi-split mapping algorithm for circular RNA, splicing, trans-splicing and fusion detection. *Genome Biol.* **15**, R34 (2014).

12. Zhang, X.-O. *et al.* Diverse alternative back-splicing and alternative splicing landscape of circular RNAs. *Genome Res.* **26**, 1277–1287 (2016).

13. Li, H. Aligning sequence reads, clone sequences and assembly contigs with BWA-MEM. (2013).

14. Dobin, A. *et al.* STAR: ultrafast universal RNA-seq aligner. *Bioinformatics* **29**, 15–21 (2013).

15. Kim, D. & Salzberg, S. L. TopHat-Fusion: an algorithm for discovery of novel fusion transcripts.

Genome Biol. **12**, R72 (2011).

16. Gaffo, E., Bonizzato, A., Kronnie, G. T. & Bortoluzzi, S. CirComPara: A Multi-Method

Comparative Bioinformatics Pipeline to Detect and Study circRNAs from RNA-seq Data.

Noncoding RNA **3**, (2017).

17. Szabo, L. & Salzman, J. Detecting circular RNAs: bioinformatic and experimental challenges.

Nature Reviews Genetics vol. 17 679–692 (2016).

18. Vromman, M., Vandesompele, J. & Volders, P.-J. Closing the circle: current state and

perspectives of circular RNA databases. *Brief. Bioinform.* (2020) doi:10.1093/bib/bbz175.

19. Wu, W., Ji, P. & Zhao, F. CircAtlas: an integrated resource of one million highly accurate

circular RNAs from 1070 vertebrate transcriptomes. *Genome Biol.* **21**, 101 (2020).

20. Ruan, H. *et al.* Comprehensive characterization of circular RNAs in ~ 1000 human cancer cell

lines. *Genome Med.* **11**, 55 (2019).