# MEG, myself, and I: individual identification from neurophysiological brain activity

Jason Da Silva Castanheira[1,*], Hector D Orozco[1,2,*], Bratislav Misic[1,†], Sylvain Baillet[1,†]

[1] Montreal Neurological Institute, McGill University, Montreal QC, Canada
[2] Department of Psychology, Neuroscience, and Behavior, McMaster University, Hamilton ON, Canada

[*] Contributed equally.
[†] Corresponding authors: bratislav.misic@mcgill.ca, sylvain.baillet@mcgill.ca.

## Abstract

Large, openly available datasets and current analytic tools promise the emergence of population neuroscience. The considerable diversity in personality traits and behaviour between individuals is reflected in the statistical variability of neural data collected in such repositories. This amount of variability challenges the sensitivity and specificity of analysis methods to capture the personal characteristics of a putative neural portrait. Recent studies with functional magnetic resonance imaging (fMRI) have concluded that patterns of resting-state functional connectivity can both successfully identify individuals within a cohort and predict some individual traits, yielding the notion of a *neural fingerprint*. Here, we aimed to clarify the neurophysiological foundations of individual differentiation from features of the rich and complex dynamics of resting-state brain activity using magnetoencephalography (MEG) in 158 participants. Akin to fMRI approaches, neurophysiological functional connectomes enabled the identification of individuals, with identifiability rates similar to fMRI's. We also show that individual identification was equally successful from simpler measures of the spatial distribution of neurophysiological spectral signal power. Our data further indicate that identifiability can be achieved from brain recordings as short as 30 seconds, and that it is robust over time: individuals remain identifiable from recordings performed weeks after their baseline reference data was collected. Based on these results, we can anticipate a vast range of further research and practical applications of individual differentiation from neural electrophysiology in personalized, clinical, and basic neuroscience.

## Introduction

Understanding the biological nature of individual traits and behaviour is an overarching objective of neuroscience research (*1–4*). The increasing availability of large, openly available datasets and advanced computational tools propels the field toward this aim (*5–7*). Yet, with bigger and deeper data volumes, neuroscientists are confronted to a paradox: while big-data neuroscience approaches the realm of population neuroscience, we remain challenged by understanding how interindividual data variability echoes the singularity of the self (*1, 3, 8, 9*).

This epistemological question has become particularly vivid with recent research showing that individuals can be identified from a cohort via their respective *neural fingerprints* derived from structural magnetic resonance imaging (MRI) (*10, 11*), functional MRI (fMRI) (*12–16*), electroencephalography (EEG) (*17–19*), or functional near-infrared spectroscopy (fNIRS) (*20*). Strikingly, neural fingerprints are associated with individual traits such as global intelligence, working memory, and attention abilities (*21–24*). Most published work so far is methodologically based on inter-individual similarity measures of functional connectivity—understood as statistical dependencies between ongoing signals across brain regions in task-free awake conditions (*25, 26*)—as defining features of neural fingerprints. Yet, the indirect coupling between hemodynamic and neural brain signaling interrogates the neurophysiological nature of brain fingerprints.

In electrophysiology, ongoing brain dynamics at rest are rich and complex (26) and have long been considered a nuisance, a by-product of neural noise (*28–30*). Recent experimental evidence, spurred by systems neuroscience models, indicates that spontaneous brain activity captured using electrophysiological techniques expresses similar resting-state connectomes as fMRI and influences conscious, sensory processes (*31–33*). Ongoing neurophysiological activity varies considerably between individuals and across the lifespan. One instance is the inter-individual variability of prominent features of human brain neurophysiological activity, such as the alpha rhythm (8-12 Hz) peak frequency (*34, 35*). Previous EEG fingerprinting work was restricted to scalp data, and therefore, provided limited neuroanatomical insight (*17–19*). Another distinctive aspect of electrophysiology is the contamination of recordings by artefacts of different natures including environment and instrument noise, muscle contractions, eye and head movements, which can be distinctive of individuals and can bias fingerprinting with non-neural signal features. Overall, the unique signature components of fast, neurophysiological brain dynamics across individuals remain unchartered.

Here we used resting state recordings of magnetoencephalography (MEG; 27) from a large cohort of participants to identify neurophysiological features of individual differentiation. We derived both measures of functional organization (i.e., functional connectivity) inspired by fMRI *neural fingerprinting* approaches, and spectral signal markers that are proper to the wider frequency spectrum of brain signaling accessible to neurophysiological data.

## Results

We used MEG data from 158 participants available from the Open MEG Archives (OMEGA; 6). Data collected on multiple days were available for a subset of these participants (N=47; mean duration between consecutive sessions: 201.7 days; Figure 1). The participants were both healthy and patient volunteers (ADHD and chronic pain) spanning in age from 18 – 73 years-old (see Supplemental Material). T1-weigthed structural MRI volumes were available from OMEGA for all participants and were used to produce source maps of resting-state brain activity (*36*). We derived several neurophysiological signal features from MEG brain source time series summarized within the Desikan-Killiany atlas—68 regions of interest (ROIs) parcellating the entire cortical surface (*37*). The MEG features comprised power-spectral-density estimates (PSD) within each of the 68 ROIs (*37*), and 68x68 functional connectomes (FC) between these ROIs. The approach is illustrated in Figure 1 and the FC and PSD methodological details are provided in Materials and Methods.

Participant identification was performed across pairs of MEG data segments taken from either the same (*within-session* identification) or a repeated session (*between-session* identification) using two distinct datasets (Figure 1a) and based either on FC or PSD features (referred as *connectome* and *spectral* fingerprinting, respectively). The *within-session* challenge with longer data segments was considered to assess the baseline performances of the MEG fingerprinting approaches proposed. The more challenging situations developed in the present report concern individual identification from shorter 30-s time segments within or between recording sessions. For each pair of participants, the Pearson's correlation coefficient between their respective features (i.e., FC or PSD) was the corresponding entry in the group correlation matrix (see Supplemental Material). The identification procedure for each individual proceeded via a lookup operation through the corresponding row of the correlation matrix; the index of the column featuring the largest correlation coefficient determined the predicted identity of the individual in the cohort. Thus, if a given individual's data features from the first dataset were most correlated to the data features from their second dataset, the individual would be correctly identified. Note that taking the maximum along the rows or columns simply switches which dataset is used for deriving the identification features (e.g., identifying individuals using dataset 1 from features derived from dataset 2; results for all possible combinations of datasets are in Supplemental Material). The overall accuracy of the identification procedure was computed as the proportion of participants correctly identified. We ran three types of identification challenges: *within-session* identification consisted of the personal differentiation between 158 participants (i.e., the datasets were from same-day recordings split in half); a *between-session* identification challenge for a subset of 47 participants for whom the datasets were from two separate days; and a *between-session* identification using considerably shortened data segments (30 seconds) (Figure 1a). We conducted the identification challenges using either broadband MEG data or band-limited versions within the typical frequency bands used in neurophysiology. We also derived a self-identifiability score for every participant, which indicates the saliency of the identification of any given individual in the tested cohort (see Material and Methods).

Figure 1: Identification analysis pipeline and definition of self-identifiability
**(a)** Schematic of exemplar MEG data divided into datasets used in each of the specified
identification challenges. i) *Within-session* challenge: the session data was split in half segments
of equal duration; ii) *Between-sessions* challenge: identification was performed using data
recorded on two separate days; iii) *Between-session shortened* challenge: data recorded on two
different days were split into three 30-s segments. **(b)** Schematic of the data analysis pipeline:
source modeling was first performed before extracting features from each region of the Desikan-
Killiany atlas (*37*). These features were vectorized and subsequently used to fingerprint
individuals, yielding a participant correlation matrix. **(c)** Features for the *between-session*
challenge from an exemplar subject. Left panel depicts AEC functional connectivity matrices
across two datasets; both matrices feature the Pearson correlation coefficients between all 68
regions of the Desikan-Killiany atlas (*37*). Right panel plots the power spectrum density
estimates from two regions of the atlas, across two datasets. **(d)** Self-identifiability was derived
for each participant as the z-score of their correlation to themselves, relative to the correlation
between themselves and the rest of the cohort. A participant with a high correlation to
themselves and low correlations to others was qualified as *highly identifiable*. An individual
highly correlated to both themselves and many others in the cohort was qualified as *less*
*identifiable*.

Within-session connectome and spectral data differentiate individuals
Within-session MEG connectome and spectral fingerprinting achieved 94.9% and 96.2%
participant identification accuracy, respectively (Figure 2). This outcome was robust to switching
datasets (Supplemental Material). While previous work (*12*) reported that data reduction
strategies improved identification performances, this was not the case with our data. Data
reduction strategies only marginally improved individual differentiation, as explained in
Supplemental Material.

We also ran the identification procedure for each of the typical frequency bands of
electrophysiology to understand whether the expression of certain ranges of brain rhythms
would be more specific of individual differentiation. We bandpass filtered MEG signals in the
delta (1-4Hz), theta (4-8Hz), alpha (8-13Hz), beta (13-30Hz), gamma (30-50Hz) and high gamma
(50-150Hz) frequency bands before running the same *within-session* fingerprinting procedure
using the resulting narrowband signals. Narrowband connectome fingerprinting yielded
identification accuracy scores of 98.7% for delta, 100% for theta, 99.4% for alpha, 100% for beta,
98.7% for gamma, and 94.9% for high gamma. Narrowband spectral fingerprinting produced
identification accuracies of 94.9% for delta, 95.6% for theta, 95.6% for alpha, 96.2% for beta,
96.2% for gamma, and 97.5% for high gamma. These results are summarized Figure 2a.

## MEG fingerprinting is robust against physiological, artefactual, and demographics confounds
We investigated the robustness of these results against variables of no interest and possible
confounds. We first processed each individual session's empty-room recordings in an identical
fashion to participants brain data. In particular, we produced pseudo brain maps of empty-room
sensor data using the same imaging kernels as those used for each session's participant brain
data. The implication is that imaging kernels designed based on information that are specific of
each participant, such as their respective head positions in the MEG sensor array and individual
anatomy brain features that constrain MEG source maps. We therefore tested whether such
individual information unrelated to brain activity contributed substantially to individual
identification from MEG source maps. We found that identification performances were
considerably reduced using empty-room data (<20% across all tested models; Figure 2). These
results based on source maps were corroborated by the low fingerprinting performances
obtained by using empty-room sensor data only (<5% across all tested models; Supplemental
Material).
158
We then performed Pearson correlation analyses between identification scores and recording
parameters, typical MEG artifacts and demographic variables. There was no association between
the duration of scans and self-identifiability for connectome (r=-0.02, p=0.75) and spectral
(r=0.02, p=0.8) fingerprinting (Supplemental Material). Further, none of the tested MEG artifacts
due to eye movements, heartbeats, and head motion were related to individual identifiability
from either connectome or spectral fingerprinting. Indeed, self-identifiability was not correlated
to motion (connectome: r=0.06, p=0.5; spectral: r= -0.01, p= 0.9), cardiac (connectome: r=0.05,
p=0.6; spectral: r= 0.07, p= 0.4), or ocular (connectome: r= -0.09, p = 0.3; spectral: r=-0.05,
p=0.5) artifacts (Figure 2b).
168
169    Lastly, we further hypothesized that fingerprinting performances may have been skewed by
170    sample heterogeneity in terms of data from healthy vs. patient participants. Yet, there was less
171    than 1% differences in identification accuracy after restricting fingerprinting to healthy
172    participant data (Supplemental Material). We also verified that participant demographics such as
173    age, sex, and handedness did not contribute to identifiability either (Supplemental Material).

174
Figure 2: Within-session identification is not related to recording artifacts
**(a)** Identification accuracy of connectome and spectral fingerprinting based on broadband and
narrowband brain signals. Horizontal grey bars indicate reference identification levels obtained
from empty-room data recorded on the same days as participants (see Methods). **(b)** Self-
identifiability was not related to typical confounds such head motion, eye movements and
heartbeats. Top row: using connectome fingerprinting; bottom row: spectral fingerprinting.

**MEG fingerprinting is robust over time**
We tested whether participants who underwent MEG sessions on separate days were
identifiable from datasets collected weeks to months apart (with a range of $1-1029$ days apart
and an average of 201.7 days, SD=210.1). We applied the above fingerprinting procedures
towards this *between-session* challenge on the subset of participants concerned (N=47).
Connectome fingerprinting decreased in performance compared to the identification accuracy
scores obtained from the *within-session* challenge (89.4%). Performance of connectome

fingerprinting from narrowband signals also decreased, with the greatest robustness obtained
from using signals in the beta and theta bands (Figure 3a and Supplemental Material). In
contrast, spectral fingerprinting was robust longitudinally, with identification accuracy scores of
97.9% (broadband) and >90% (narrowband) that were similar to those obtained in the *within-*
*session* challenge (Figure 3 and Supplemental Material). Self-identifiability scores were not
correlated with the number of days between MEG sessions (connectome: r= 0.09, p = 0.5;
spectral: r= 0.08, p=0.65).
195
We further challenged MEG individual differentiation between sessions days apart using shorter
data segments. We extracted three 30-s segments from the *between-session* data on each day
(Figure 1a) and ran the same fingerprinting procedures as above. Identification performance
from connectome fingerprinting remained high across all 30-s segments tested (Figure 3c) using
broadband MEG signals (identification accuracy 84.4%). Performance of spectral fingerprinting
was decreased (identification accuracy: 65.2% Figure 3c). We observed similar discrepancies in
performance robustness between connectome and spectral fingerprinting using narrowband
signals (Figure 3), especially in the delta, theta, and alpha bands. We report results obtained
from using sensor data only and for the *within-session shortened* challenge in Supplemental
Material.
206
207

Figure 3: Between-session identification accuracy
**(a)** Identification accuracy for connectome and spectral *between-session* fingerprinting.
Identification performances are similar to those from the *within-session* challenge. **(b)** Linear
regression analyses did not reveal an association between self-identifiability and the delay
between session recordings (connectome fingerprinting: r= 0.09, p = 0.5; spectral fingerprinting:
r= 0.08, p=0.65).  **(c)** *Between-session shortened* identification accuracy using 30-s data segments
collected days apart (average: 201.7 days). Each data point represents one combination of
datasets used for fingerprinting (see Methods for details) **(d)** Scatter plot of all identification
challenges (source and sensor level approaches) across frequency bands for both source and

220
221
Figure 4: Characteristic features of connectome and spectral fingerprinting
Intraclass correlation (ICC) for connectome and spectral *within-session* fingerprinting. **(a)** ICC for
connectome fingerprinting plotted for each tested frequency band, using network labels from
Yeo et al. (2011). The most prominent networks for connectome fingerprinting were the Visual,
Dorsal Attention and Limbic networks. **(b)** ICC for spectral fingerprinting plotted for each tested
frequency band and mapped using the Desikan-Killiany cortical parcellation (*37*). The most
salient features were the gamma and high-gamma band signals expressed in midline structures
and the beta band across the cortex.

Salient neurophysiological features for identification
We identified the features which were the most characteristic of individuals for MEG
fingerprinting. We derived measures of intraclass correlation (ICC) (*12*) to quantify how much
each feature, such as an edge of the FC connectome or the signal power in a frequency band
from an anatomical parcel, contributed to fingerprinting (see Methods). This metric was

reported in previous brain fingerprinting studies and captures the inter-rater reliability of each
participant as their own rater, to identify the neurophysiological signal features that are the
most consistent across individuals (*12*, *38*). We performed this analysis for both the broadband
connectome and the band-specific spectral fingerprinting *within-session* challenges. The data
show that the dorsal attention and visual networks were the most specific across individuals for
connectome fingerprinting, in all frequency bands (Figure 4). Beta-band connectivity of the
limbic network was particularly distinctive of individuals. For spectral fingerprinting, beta,
gamma, and high-gamma band signal power were the most salient identification features,
especially across medial regions (Figure 4b). Particularly, signals in the theta, alpha, beta, and
gamma bands discriminated individuals along midline, parietal, lateral temporal, and visual
areas. These results are consistent with our narrowband analysis (see Figure 2a), which
highlights beta activity as the most informative in identifying individuals.

## Neurophysiological identifying features are associated with demographics
Beyond identifying individuals in a cohort, we tested whether resting-state neurophysiological
features could also predict meaningful participant traits, using an exploratory partial-least-
squares (PLS) analysis (see Methods; (*39*)). Briefly, PLS explains the structure of the covariance
between two observation matrices – here a demographic matrix and a neurophysiological signal
matrix composed of ROI-specific connectome of spectral measures – with latent components.
PLS analysis of our data revealed three significant latent components, which were distinct for
connectome and spectral fingerprinting (Supplemental Material). The first latent component in
connectome fingerprinting was related to clinical population (r= 0.2, 95% CI [0.160, 0.3]) and
handedness (r= 0.2, 95% CI [0.1, 0.3]). This demographic profile was associated with reduced
beta-band functional connectivity over the frontal parietal network (Figure 5). For spectral
fingerprinting, the first salient latent component was related to a younger age (r= -0.3, 95% CI [-
0.1, -0.5]), female (r= 0.4, 95% CI [0.2, 0.5]) and clinical population (r= 0.5, 95% CI [0.2, 0.5]). This
demographic profile was associated with stronger expressions of broadband neurophysiological
signal power in superior parietal regions and the pericalcarine gyrus bilaterally, and reduced
neurophysiological signals in the isthmus cingulate (Figure 5).
263
264

265
Figure 5: Partial Least-Squares analysis relates demographics to connectome and spectral
features
(a) and (b) from left to right, depicts the design saliency patterns for the first latent variables and
their associated neural-data bootstrap ratios. Confidence Intervals (CI) were calculated through a
bootstrapping procedure, and as such may not necessarily be symmetric. Bootstrap ratios
computed for (a) connectome and (b) spectral features are plotted according to the resting-state
networks labelled according to Yeo et al. (2011) and the Desikan-Killiany parcellation (*37*),
respectively: Default Mode Network (DMN), Dorsal Attention (DA), Frontal-Parietal (FP), Limbic
(L), Somato-Motor (SM), Ventral Attention (VA), and Visual (VIS).

## Discussion
The recent leveraging of large, open fMRI datasets has brought empirical evidence that
individuals may be identified within a cohort from their brain imaging functional connectome,
inspiring the metaphor of a *neural fingerprint*. Unlike hand fingerprints, their cerebral
counterpart predicts task performance and a variety of traits (*14, 21–24*). These intriguing
findings require a better understanding of their neurophysiological foundations, which we
sought to characterize from direct neural signals captured at a large scale with MEG.
Our data show that individuals can be identified in a cohort of 158 unrelated participants from
their respective resting-state connectomes and spectral profiles in a range of fast brain signals.
MEG fingerprinting was successful using data lengths (30 seconds) much shorter than those
reported for fMRI fingerprinting (*14, 41*). Brain electrophysiological signals are rich, complex and
convey expressions of large-scale neural dynamics channeled by individual structural anatomy
and physiology (*42*). Indeed, we also showed that MEG fingerprinting is robust across time,
making individuals potentially identifiable from data collected days, months, or years apart.

Lastly, we characterized whether individual differences in resting-state neural dynamics are
demographically meaningful through an exploratory PLS analysis. We showed that both resting-
state functional connectomes and spectra predict latent demographic components. Recent
findings corroborate our results, demonstrating individual differences between functional
connectomes derived from resting-state electrophysiology (*43*). Future work will be required to
replicate and expand these findings in more samples of individuals.

## Connectome and spectral neurophysiological fingerprints
Our results highlight two sets of brain-wide electrophysiological features that contributed to
successful individual identification: connectome and spectral measures across the
neurophysiological frequency spectrum. Overall, connectome and spectral fingerprinting with
MEG performed equivalently to fMRI approaches, achieving overall identification rates above
90%, with robust individual identification over time and against noise (*12*, *14*, *44*).
We found that for connectome fingerprinting, the anatomical regions the most characteristic of
individuals differed between MEG and fMRI. While fMRI highlighted the default-mode network
and the fronto-parietal resting state networks, MEG connectome fingerprinting emphasized
functional connectivity within limbic and visual networks as contributing to individual specific
neurophysiological signatures. In contrast, both MEG and fMRI fingerprinting emphasize the
importance of the dorsal attention network (*14*). These observations are not mutually exclusive,
considering the different nature of brain signals captured by the respective modalities. One
possible interpretation—requiring further investigation— is that the fast neurophysiological
signals that contribute to identification with MEG have hemodynamic counterparts that are not
as salient in fMRI as the identifying networks reported so far. Nevertheless, our data indicate
that neurophysiological signals in the beta band contribute to the highest identification accuracy
amongst all other typical bands. This finding is compatible with previous work reporting that
correlated amplitude changes of MEG brain signals are related to the microstructure of white
matter tracts and reveal, with the same amplitude envelope correlation method as used here,
MEG resting-state brain networks that align with fMRI's (*45*, *46*). Beta-band activity also emerges
from recent literature as a signalling vehicle of re-afferent "top-down" communications in brain
circuits (*47*, *48*). One can therefore speculate that beta-band signals would convey
electrophysiological representations of internal cognitive models that are by essence intimately
specific of each individual (*27*).
Such brain signal amplitude signatures are further emphasized by the ability of simple spectral
brain maps to enable MEG fingerprinting. *Within-* and *between-session* spectral identification
were achieved with remarkable accuracy (>90%) with broadband MEG brain signals or restricted
to the typical bands of electrophysiology. Spectral identification based on signals from the faster
bands (gamma and high-gamma) was overall the most robust longitudinally and against using
shorter data segments. This observation is consistent with the width of (high) gamma frequency
bands spanning broader ranges (here between 30-50 Hz and 50-150 Hz) than slower bands such
as delta (1-4 Hz), theta (4-8 Hz) and alpha (8-12 Hz). The spectral estimates averaged across the
broader (high) gamma bands were therefore the most robust against using shorter data
segments. The reduced number of sliding time windows available over shorter data durations
increased the variance of the summary statistics extracted to derive the spectral fingerprints

from the signals defined over narrower bands. The higher frequency bands were less affected
because the larger number of frequency bins involved in the extraction of their summary power
statistics tended to compensate the higher empirical variance of spectral estimates from a lesser
number of observations over time. Connectome fingerprinting was more immune against using
shorter data durations. The underlying approach indeed did not require spectral transformations
but resorted to a bank of narrowband filters applied over the original duration of MEG
recordings, before the resulting filtered signals were segmented in shorter epochs for the
identification challenges. The consequence is that the number of data points used for all
narrowband signals was identical across all frequency bands, yielding moderate variability in
identification performances compared to those obtained with the spectral approach. Another
factor of robustness of the connectome approach is that connectivity weights between network
nodes may fluctuate very slowly over time in task free brain activity: Florin and Baillet (31)
reported fluctuation rates of 0.01Hz in MEG, indicating typical time cycles of 100s — a duration
substantially longer than the 30-s shortest time window used here. Over longer periods of time
though, such as in the *between-session* challenge, spectral fingerprinting outperformed its
connectome counterpart. We note a slight increase of spectral identification accuracy in the
*between-session* challenge (e.g., +1.6% for broadband fingerprinting) compared to *within-*
*session*, which was a statistical fluctuation due to using a smaller sample of participants.
349
On average across all source fingerprinting challenges reported herein, and despite successful
identification across lower frequency bands (delta 52.2%, theta 60.6%, alpha 65.3%),
performances were markedly better using high-frequency signal components (beta 81.9%;
gamma 81.7%; high gamma 76.2%). Gamma and faster activity have long been associated with
concurrent and colocalized hemodynamic fluctuations (*49, 50*). Because they may be seen as
dual manifestations of BOLD signaling used in fMRI fingerprinting, this may explain why these
signals contributed robustly to MEG brain fingerprinting in our data. However, gamma-band and
faster brain signals are on average weaker in amplitude and therefore may be masked by
contamination from artifacts and noise (*51–53*). The preprocessing applied to our data
attenuated such nuisance to a point where individuals were not identifiable from typical sources
of signal contamination such as individual head motion behavior.
361
Although a rhythm of prominent amplitude in humans during rest, alpha-band activity (8-12Hz)
was not particularly specific to identify individuals in the cohort. In that respect, our data is
aligned with previous MEG works on resting-state connectomes extracted from
neurophysiological MEG signals, which did not report on a salient role of alpha activity in driving
inter-regional connectivity (*31, 45*). We argue that the spatial topography of alpha resting
activity may be relatively stereotypical across individuals, involving thalamo-cortical loops that
project focally to the parieto-occipital junction, with limited variability across individuals (*6*). In
task, alpha activity has been related to attention orienting, alertness and anticipation, and the
registration of (multimodal) sensory information, thereby reflecting transient mental states (*41,*
*54–57*) rather than individual traits.
372

The data also indicates that MEG fingerprinting is robust against typical recording artefacts that
may be idiosyncratic of individuals and therefore, could have confounded identification. In
particular, session environmental conditions captured by empty-room MEG recordings were not
sufficient to identify individuals within or between sessions. The participant's anatomical and
head-position information embedded in their respective MEG source imaging kernels were also
not sufficient to identify individuals. Note that head position changed between sessions. Further
studies are required to clarify how these results may vary depending on the type of MEG source
modelling adopted. We anticipate little influence of the type of source model used though,
based on evidence that beamforming kernels are mathematically equivalently to other major
classes of linear source estimation kernels, such as weighted minimum-norm estimators (*58*).
Future work should corroborate these results with regards to fingerprinting. The choice of
connectivity measure to derive electrophysiological connectomes may also influence
identifiability (*59*). We look forward to current progress in electrophysiological brain
connectomics to put forward measures of network connectivity informed by mechanistic
principles and emerging as a standard metrics in the field to confirm and expand present
fingerprinting results (*60*).
389
While our present data show robust longitudinal fingerprinting performances, future work
involving more participants with multiple MEG visits is required to both replicate these
observations and investigate whether individual deviations from baseline fingerprints could be
early signals of asymptomatic neuropathophysiology (*27*). We hope the remarkable ability to
fingerprint individuals from the present electrophysiological features serves as a steppingstone
for future investigation, which may include multimodal non-invasive assessments based on MEG,
possibly combined with e.g., fMRI and/or EEG.

Neural fingerprints of individual traits
Our data suggests that individual differences in resting-state neurophysiological functional
connectivity and spectral power relate to latent demographic clusters. These observations are in
line with previous fMRI work that showed that connectomes are predictive of individual
differences in attention, working memory and intelligence. For instance, connectivity patterns
between the default mode and the dorsal attention networks predict attentional behaviour
during task and self-reported mind wandering (*22*, *61*, see *62 for review* ). Overall, a possible
conceptual framework is that task free neural dynamics are the signatures of an individual
scaffold of brain functions that is predictive of task behaviour. This view is also that of the
spontaneous trait reactivation hypothesis wherein the organization of the human cortex at rest
(manifested e.g., by functional connectivity) is a window into the self's unique traits and abilities
(*63*). Early evidence indeed suggests that functional connectomes are associated with
personality traits and even inter-personal closeness in social networks (*64*, *65*).
410
Yet, the mechanistic implementation of these intriguing observations remains elusive. Inter-
individual variability in the distribution of synaptic weights across the cerebrum, shaped through
lifetime experiences according to Hebbian principles, may account — at least in part — for
connectome fingerprinting (*63*). The heritability of the functional connectome has also been

discussed, especially for fronto-parietal networks (i.e., dorsal and ventral attention network and
the default mode network) (*66–68*). Heritability of brain spectral characteristics is also actively
discussed (*69–71*). This emerging literature and the empirical evidence of brain fingerprinting
certainly motivates more research on new, fascinating questions about the biological nature of
the self.

**Sampling population diversity for personalized interventions**
Robust individual signatures of brain activity may be transformative to neurophysiological
phenotyping and population neuroscience. With the increasing availability of multi-omic data
repositories, there is a research opportunity to span the diversity of statistical normative
characteristics of brain fingerprints across the population in relation to behaviour, environmental
and clinical variables (*1*, *3*, *27*). Our study highlights the utility of datasets of individuals who have
been scanned on multiple occasions to capture and characterize interindividual variability as
meaningful information. Ideally, large databanks of individual variants sampled across multiple
dimensions of socio-economic, age, and geographic factors enable normative modeling
approaches to establish the risk traits of developing syndromes of e.g., early cognitive decline,
neurodegeneration or mental illness. Previous work has shown that mental disorders may affect
the stability of individual fingerprints over time and therefore points at possible translational
applications of the approach (*15*, *72*). We may also foresee that changes over time or lack
thereof of a person's brain fingerprint may also constitute a new class of non-invasive markers of
responses to neurological and other treatment of a variety of chronic, neurodegenerative or
acute (e.g., stroke) conditions. Brain fingerprints derived from relatively short, task-free sessions
may play a leading role to realize this vision in practice.
Brain fingerprinting may also contribute to future endeavours in establishing how oscillatory
dynamics at rest support cognitive functions across the lifespan. MEG brain fingerprinting
presents several potential advantages in terms of safety, shorter scan time, and immediate
proximity of a care person during data collection, especially for special populations.
The methodological approaches proposed herein can, in principle, transfer to EEG fingerprinting
(*17–19*), which would be more readily available in clinics. Whether results would be as robust
with EEG than with MEG remains to be demonstrated. Indeed, EEG source mapping is more
prone to contamination from muscle artifacts and is more sensitive to approximations in the
biophysical modeling of head tissues, which may compromise further fingerprinting capabilities
(*27*).
447
In sum, our study extends the concept of neural or brain fingerprint to fast and large-scale
resting-state electrophysiological dynamics, which encapsulate meaningful individual differences
in both functional connectivity and neuroanatomical maps of power spectrum characteristics.
We are hopeful that the present contribution paves the way to replication and extension using
larger open datasets. Many fascinating outstanding questions remain about the biological nature
of inter-individual variability expressed via neural oscillations and brain network dynamics, and
more specifically how these differences associate with behavior and diseases natural history. The
research ahead is for future population neuroscience studies.
456

## Material and Methods

### The Open MEG Archives (OMEGA)

We used data from the Open MEG Archives (OMEGA; 6) consisting of resting-state MEG recordings acquired using the same MEG system (275 channels whole-head CTF; Port Coquitlam, British Columbia, Canada). The sampling rate was 2400 Hz, with an antialiasing filter applied at 600 Hz cut-off, and built-in third-order spatial gradient noise cancellation (see 6 for details on data acquisition).

We analysed MEG resting-state data from 158 unrelated OMEG participants (77 Females, 31.9 ± 14.7 years old). Recordings were approximately 5-min long. Supplementary Table 1 provides details on scanning procedures and Supplementary Table 2 on demographics. A subset of these individuals (N=47) had recordings over multiple visits (different days) and were used in the *between-session* fingerprinting challenge. The OMEGA data management protocol was approved by the research ethics board of the Montreal Neurological Institute.

### MEG data preprocessing and feature extraction

MEG data were preprocessed using Brainstorm (73; version Oct-12-2018) (following good-practice guidelines (*74*). Unless specified, all steps below were performed using the Brainstorm toolkit, with default parameters. Line noise artifact (60 Hz) along with its 10 harmonics were removed using a notch filter bank. Slow-wave and DC-offset artifacts were removed using a high-pass FIR filter with a 0.3-Hz cut-off. We derived Signal-Space Projections (SSPs) to remove cardiac and ocular artifacts. We used electro-cardiogram and -oculogram recordings to define signal projectors around identified artifact occurrences. We also applied SSPs to attenuate low-frequency (1-7 Hz) and high-frequency noisy components (40-400Hz) due to saccades and muscle activity, respectively. Bandpass filtered duplicates of the cleaned data were produced for each frequency band of interest (delta: 1-4Hz, theta: 4-8Hz, alpha: 8-13Hz, beta: 13-30Hz, gamma: 30-50Hz, and high gamma: 50-150Hz). Distinct brain source models were then derived for all narrowband versions of the MEG sensor data.

Each individual T1-weighted MRI data was automatically segmented and labelled with Freesurfer (*75*). Coregistration with MEG sensor locations was derived using dozens of digitized head points collected at each MEG session. We produced MEG forward head models for each participant using the overlapping spheres approach, and cortical source models with LCMV beamforming, all using Brainstorm with default parameters (2016 version for source estimation processes). We performed data covariance regularization. To reduce the effect of variable source depth, the estimated source variance was normalized by the noise covariance matrix. Elementary MEG source orientations were constrained normal to the surface at 15,000 locations of the cortex. Noise statistics for source modeling were estimated from two-minute empty-room recordings collected as close as possible in time to each participant's MEG session. Source timeseries were clustered into 68 cortical regions of interest (ROIs) defined from the Desikan-Killiany atlas (*37*) and dimension-reduced via the first principal component of all signals within each ROI. Connectome and spectral identification features were computed from ROI source timeseries. Individual functional connectomes were derived in all frequency bands from the amplitude

envelope correlation (AEC) approach (*76*). ROI timeseries were Hilbert transformed and all
possible pairs of resulting amplitude envelopes were used to derive the corresponding Pearson
correlation coefficients, yielding a 68x68 symmetric connectome array. We used Welch's
method to derive power spectrum density (PSD) estimates for each ROI (*77*), using time windows
of 2 seconds with 50% overlap sled over all ROI timeseries and averaged across all PSDs within
each ROI. The resulting frequency range of PSDs was 0-150Hz, with a frequency resolution of 0.5
Hz.

## Code Availability

505     The connectome and spectral features were then exported to Python (3.7.6) for subsequent
506     fingerprinting analyses. All codes for including preprocessing and data analysis can be found on
507     the project's GitHub (LINK).

## Data Availability

509     The power spectra and connectomes derived from the preprocessed OMEGA samples and used
510     to identify individuals in the present study are available upon request from corresponding
511     authors.

## Fingerprinting and self-identifiability

We used a fingerprinting approach directly adapted from fMRI connectome fingerprinting
methods (*12, 14*), which relies on correlational scoring of individuals between datasets. A given
*probe* participant is identified from a cohort by computing all Pearson correlation coefficients
between the spectral or connectome features of said probe at one timepoint (e.g., *dataset 1*)
and the entire cohort at a different timepoint (e.g., *dataset 2*). The entry presenting the highest
correlation to the probe determined the probe's estimated identity i.e., identified entry in the
cohort. This approach is applied between all pairs of participants in the cohort, yielding an
asymmetric correlation matrix spanning the cohort. We report scores of *identification accuracy*
*as* the ratio between the number individuals correctly identified with the described procedure
and the total number of individuals in the cohort. Identification accuracy scores are obtained
from identification challenges from dataset 1 to dataset 2 and vice-versa, *within-* and *between-*
*sessions*. Figure 1 details the definition of the dataset labels used, and Supplemental Material
contains the results from across all combinations of datasets/sessions.
Amico and Goñi (2018) proposed an identifiability score to quantify, for a given participant, the
reliability of its identification from others in the cohort. Here, we extend this notion with the
introduction of a *self-identifiability* measure, $I_{self}$. Let **A** be the correlation matrix spanning the
cohort (square, asymmetric) between dataset 1 and dataset 2, and N be the number of
participants to identify. We define $I_{self}$ as the z-score of participant $P_i$ 's correlation to themselves
between dataset 1 and dataset 2, with respect to $P_i$'s correlation to all other individuals in the
cohort, noted: $I_{self (i)} = (Corr_{ii} - \mu_{ij}) / \sigma_{ij}$ , where $Corr_{ii}$ is the $P_i$'s correlation between dataset 1 and
dataset 2, $\mu_{ij}$ is the mean correlation between participant $P_i$ in dataset 1 and all other individuals
in dataset 2 (i.e. the mean along the $i^{th}$ row of matrix **A**), and $\sigma_i$ is the empirical standard

deviation of inter-individual features correlations. Thus, if a participant is easily identifiable, its
self-identifiability increases; whereas small self-identifiability scores indicate a participant
particularly difficult to identify from the rest of the cohort.

Recording artifacts and self-identifiability
To investigate the effects of recording parameters and artifacts on fingerprinting, we related
each individual's self-identifiability to several possible confounds. The duration of each scan was
compared to self-identifiability to verify that longer recordings available from a subset of
individuals did not make them easier to identify. We also correlated the root mean square (RMS)
of signals that measured ocular, cardiac, and head movement artifacts over the duration of the
entire recording to participants' self-identifiability score. For cardiac artifacts for instance, we
derived the RMS of ECG recordings; for ocular artifacts we used the HEOG and VEOG electrode
recordings; and for motion artifact we extracted the RMS of all three head coil signals that
measured 3-D head movements. These derivations were conducted for both the connectome
and spectral broadband *within-session* fingerprinting challenge.

Fingerprinting across frequency bands
We replicated the above fingerprinting approach using data restricted to each frequency band of
interest (delta 1-4Hz, theta 4-8Hz, alpha 8-13Hz, beta 13-30Hz, gamma 30-50Hz, and high
gamma 50-150Hz). We report the identification accuracy obtained from each narrowband signal
in both the spectral and connectome fingerprinting challenges in Figure 2 and Figure 3, for the
*within-* and *between-session* fingerprinting challenges respectively.
We also performed fingerprinting tests based on sensor data only. We used the same
connectome and spectral approaches as the MEG source maps, considering the time series of
each of the 275 MEG channels instead of the 68 ROI time series derived from the brain map
parcels. We report the identification performances from both the sensor and source analyses in
Figure 3 and in Supplemental Material.

Between-session and shortened fingerprinting challenges
We verified the robustness of MEG fingerprinting with respect to 1) the ability to identify
participants over time and 2) from reduced data durations. We subdivided participants into
three additional challenges: the *within-session—shortened, between-session,* and *between-*
*session—shortened* challenge. First, we used the participant data described in the *within-session*
analysis and extracted connectome and spectral fingerprinting features over three 30-second
non-overlapping time segments. This duration was based on the length of the shortest recording
in the data sample (Figure 1aii). We applied the same fingerprinting procedure as described in
**Fingerprinting and self-identifiability** across all possible combinations of the three 30-second
datasets. Second, we assessed the stability of the fingerprinting outcomes using a subset of
participants with consecutive MEG sessions separated by several days (N=47; separated on
average by 201.7 days, see Supplemental Materials for details). Again, we applied the same
fingerprinting procedure as described in **Fingerprinting and self-identifiability** for this *between-*

*session* challenge. Lastly, we applied the same shortened analysis—described above—to the
subset of individuals with multiple scans (i.e., the between-sessions data). We report all possible
combinations of datasets (i.e., three 30s segments from day 1 and three 30s segments from day
2; see Figure 1a for example) in Figure 3.

## Empty-room fingerprinting

We tested whether environment and instrument noise daily conditions would bias individual
identification using empty-room recordings collected from each MEG session. The empty-room
data was processed identically to the participants data, using the same individual imaging
kernels, and were used to identify participants. We ran all possible combinations of empty-room
vs. participants datasets (e.g., empty-room 1 vs. participant dataset 1, empty-room 2 vs.
participant dataset 1, etc.) and computed the sample mean of the identification accuracies
across all dataset combinations. The identification accuracies obtained represent estimates of
baseline reference performances that can be compared to each form of fingerprinting based on
actual participant data (i.e., connectome or spectral, broadband or band-specific; see Figure 2
and Supplemental Material). In a similar fashion, we also used sensor-level empty-room
recordings of each participant for fingerprinting—attempting to identify individuals' recordings
from their empty-room features. The results of this analysis are reported in the Supplemental
Material.

## Most characteristic features for fingerprinting

We quantified the contribution of each feature (i.e., edges in the connectivity matrix or a
frequency band in an anatomical parcel) towards identifying individuals using Intraclass
Correlations (ICC). ICC is commonly used to measure the agreement between two observers
(e.g., ratings vs. scores). The stronger the agreement, the higher the ICC (*12*, *38*). ICC derives a
random effects model whereby each item is rated by different raters from a pool of potential
raters. We selected this measure to capture the inter-rater reliability of each participant as their
own rater to identify which edges (e.g., connections in FC) are the most consistent (i.e., which
features of a participant $P_i$ in dataset 1 are most like dataset 2). Here, the higher the ICC, the
more consistent a given feature was within individuals.  Additionally, we computed two other
measures of edgewise contribution proposed by Finn and colleagues (*14*): *group consistency* and
*differential power* (Supplemental Material). We applied all measures (i.e., ICC, group consistency,
and differential power) in the context of the broadband *within-session* fingerprinting challenge.
The source maps shown in Figure 4, Figure 5 and Supplemental material were generated using R
(V 3.6.3; *74*) with the *ggseg* package (*79*).

## Partial Least-Squares: MEG features of participant demographics

We conducted a Partial Least-Squares (PLS) analysis with the Rotman-Baycrest PLS toolbox (*80*).
PLS is a multivariate statistical method that relates two matrices of variables (e.g., neural activity
and participant demographics) by estimating a weighted linear combination of variables from
both data matrices to maximize their covariance. The associated weights can be interpreted

neural patterns (e.g., functional connections) and their associated demographic profiles. PLS
used singular value decompositions of the z-scored neural activity-demographics covariance
matrix. This decomposition yielded orthogonal latent variables (LV) associated to a pattern of
neural activity (i.e., functional connectivity or spectral power) and demographics. To assess the
significance of these multivariate patterns, we computed permutation tests (10,000
permutations). Each permutation shuffled the order of the observations (i.e., the rows) of the
demographic data matrix before running PLS on the resulting surrogate data under the null
hypothesis that there was no relationship between the demographic and neural data. A *p*-value
for the LVs was computed as the proportion of times the permuted singular values exceeded
that of the original data. We explored the first significant LV from the broadband connectome
and spectral fingerprinting features. We also assessed the contribution of each variable in the
demographics and neural activity matrices by bootstrapping observations with replacement
(10,000 bootstraps). We computed 95-% confidence intervals for the demographic weights and
bootstrap ratios for the neural weights. The bootstrap ratio was computed as the ratio between
each variable's weight and the bootstrap-estimated standard error.

## Author Contribution
All authors conceptualized the study, J.D.S.C. and H.D.O. preformed the analyses, S.B. and B.M.
provided guidance with data interpretation, J.D.S.C. wrote the first draft of the manuscript, all
authors contributed to the writing and editing of the manuscript.

## Competing Interests
The authors declare no competing financial interest.

## References

1.  J. Dubois, R. Adolphs, Building a Science of Individual Differences from fMRI. *Trends Cogn. Sci.* **20**,
425–443 (2016).

2.  M. B. Miller, J. D. Van Horn, Individual variability in brain activations associated with episodic
retrieval: a role for large-scale databases. *Int. J. Psychophysiol. Off. J. Int. Organ. Psychophysiol.* **63**,
205–213 (2007).

3.  J. D. Van Horn, S. T. Grafton, M. B. Miller, Individual Variability in Brain Activity: A Nuisance or an
Opportunity? *Brain Imaging Behav.* **2**, 327 (2008).

4.  T. Yarkoni, in *APA handbook of personality and social psychology, Volume 4: Personality processes*
*and individual differences.*, M. Mikulincer, P. R. Shaver, M. L. Cooper, R. J. Larsen, Eds. (American
Psychological Association, Washington, 2015; http://content.apa.org/books/14343-002), pp. 61–83.

5.  D. S. Marcus, J. Harwell, T. Olsen, M. Hodge, M. F. Glasser, F. Prior, M. Jenkinson, T. Laumann, S. W.
Curtiss, D. C. Van Essen, Informatics and data mining tools and strategies for the human connectome
project. *Front. Neuroinformatics*. **5**, 4 (2011).

6.    G. Niso, C. Rogers, J. T. Moreau, L.-Y. Chen, C. Madjar, S. Das, E. Bock, F. Tadel, A. C. Evans, P.
Jolicoeur, S. Baillet, OMEGA: The Open MEG Archive. *NeuroImage*. **124**, 1182–1187 (2016).

7.    R. A. Poldrack, K. J. Gorgolewski, Making big data open: data sharing in neuroimaging. *Nat. Neurosci.*
**17**, 1510–1517 (2014).

8.    R. B. Mars, R. E. Passingham, S. Jbabdi, Connectivity Fingerprints: From Areal Descriptions to Abstract
Spaces. *Trends Cogn. Sci.* **22**, 1026–1037 (2018).

9.    B. Mišić, O. Sporns, From regions to connections and networks: new bridges between brain and
behavior. *Curr. Opin. Neurobiol.* **40**, 1–7 (2016).

10.    S. A. Valizadeh, F. Liem, S. Mérillat, J. Hänggi, L. Jäncke, Identification of individual subjects on the
basis of their brain anatomical features. *Sci. Rep.* **8**, 5611 (2018).

11.    C. Wachinger, P. Golland, W. Kremen, B. Fischl, M. Reuter, BrainPrint: A discriminative
characterization of brain morphology. *NeuroImage*. **109**, 232–248 (2015).

12.    E. Amico, J. Goñi, The quest for identifiability in human functional connectomes. *Sci. Rep.* **8**, 8254
(2018).

13.    S. Bari, E. Amico, N. Vike, T. M. Talavage, J. Goñi, Uncovering multi-site identifiability based on
resting-state functional connectomes. *NeuroImage*. **202**, 115967 (2019).

14.    E. S. Finn, X. Shen, D. Scheinost, M. D. Rosenberg, J. Huang, M. M. Chun, X. Papademetris, R. T.
Constable, Functional connectome fingerprinting: identifying individuals using patterns of brain
connectivity. *Nat. Neurosci.* **18**, 1664–1671 (2015).

15.    T. Kaufmann, D. Alnæs, N. T. Doan, C. L. Brandt, O. A. Andreassen, L. T. Westlye, Delayed stabilization
and individualization in connectome development are related to psychiatric disorders. *Nat.*
*Neurosci.* **20**, 513–515 (2017).

16.    O. Miranda-Dominguez, B. D. Mills, S. D. Carpenter, K. A. Grant, C. D. Kroenke, J. T. Nigg, D. A. Fair,
Connectotyping: model based fingerprinting of the functional connectome. *PloS One*. **9**, e111048
(2014).

17.    M. Fraschini, A. Hillebrand, M. Demuru, L. Didaci, G. L. Marcialis, An EEG-Based Biometric System
Using Eigenvector Centrality in Resting State Brain Networks. *IEEE Signal Process. Lett.* **22**, 666–670
(2015).

18.    W. Kong, L. Wang, S. Xu, F. Babiloni, H. Chen, EEG Fingerprints: Phase Synchronization of EEG Signals
as Biomarker for Subject Identification. *IEEE Access*. **7**, 121165–121173 (2019).

19.    D. L. Rocca, P. Campisi, B. Vegso, P. Cserti, G. Kozmann, F. Babiloni, F. D. V. Fallani, Human Brain
Distinctiveness Based on EEG Spectral Coherence Connectivity. *IEEE Trans. Biomed. Eng.* **61**, 2406–
2412 (2014).

20.    J. de Souza Rodrigues, F. L. Ribeiro, J. R. Sato, R. C. Mesquita, C. E. B. Júnior, Identifying individuals
using fNIRS-based cortical connectomes. *Biomed. Opt. Express*. **10**, 2889–2897 (2019).

21.    A. S. Greene, S. Gao, D. Scheinost, R. T. Constable, Task-induced brain state manipulation improves
682            prediction of individual traits. *Nat. Commun.* **9**, 2807 (2018).

683    22.    M. D. Rosenberg, D. Scheinost, A. S. Greene, E. W. Avery, Y. H. Kwon, E. S. Finn, R. Ramani, M. Qiu,
684            R. T. Constable, M. M. Chun, Functional connectivity predicts changes in attention observed across
685            minutes, days, and months. *Proc. Natl. Acad. Sci. U. S. A.* **117**, 3797–3807 (2020).

686    23.    M. Yamashita, Y. Yoshihara, R. Hashimoto, N. Yahata, N. Ichikawa, Y. Sakai, T. Yamada, N.
687            Matsukawa, G. Okada, S. C. Tanaka, K. Kasai, N. Kato, Y. Okamoto, B. Seymour, H. Takahashi, M.
688            Kawato, H. Imamizu, A prediction model of working memory across health and psychiatric disease
689            using whole-brain functional connectivity. *eLife*. **7** (2018), doi:10.7554/eLife.38844.

690    24.    K. Yoo, M. D. Rosenberg, W.-T. Hsu, S. Zhang, C.-S. R. Li, D. Scheinost, R. T. Constable, M. M. Chun,
691            Connectome-based predictive modeling of attention: Comparing different functional connectivity
692            features and prediction methods across datasets. *NeuroImage*. **167**, 11–22 (2018).

693    25.    E. Bullmore, O. Sporns, The economy of brain network organization. *Nat. Rev. Neurosci.* **13**, 336–349
694            (2012).

695    26.    S. M. Smith, D. Vidaurre, C. F. Beckmann, M. F. Glasser, M. Jenkinson, K. L. Miller, T. E. Nichols, E. C.
696            Robinson, G. Salimi-Khorshidi, M. W. Woolrich, D. M. Barch, K. Uğurbil, D. C. Van Essen, Functional
697            connectomics from resting-state fMRI. *Trends Cogn. Sci.* **17**, 666–682 (2013).

698    27.    S. Baillet, Magnetoencephalography for brain electrophysiology and imaging. *Nat. Neurosci.* **20**,
699            327–339 (2017).

700    28.    E. Başar, *Chaos in Brain Function: Containing Original Chapters by E. Basar and T. H. Bullock and*
701            *Topical Articles Reprinted from the Springer Series in Brain Dynamics* (Springer Science & Business
702            Media, 1990).

703    29.    R. B. Stein, E. R. Gossen, K. E. Jones, Neuronal variability: noise or part of the signal? *Nat. Rev.*
704            *Neurosci.* **6**, 389–397 (2005).

705    30.    L. Q. Uddin, Bring the Noise: Reconceptualizing Spontaneous Neural Activity. *Trends Cogn. Sci.* **24**,
706            734–746 (2020).

707    31.    E. Florin, S. Baillet, The brain's resting-state activity is shaped by synchronized cross-frequency
708            coupling of neural oscillations. *NeuroImage*. **111**, 26–35 (2015).

709    32.    L. Iemi, N. A. Busch, A. Laudini, S. Haegens, J. Samaha, A. Villringer, V. V. Nikulin, Multiple
710            mechanisms link prestimulus neural oscillations to sensory responses. *eLife*. **8** (2019),
711            doi:10.7554/eLife.43620.

712    33.    J. Samaha, L. Iemi, S. Haegens, N. A. Busch, Spontaneous Brain Oscillations and Perceptual Decision-
713            Making. *Trends Cogn. Sci.* **24**, 639–653 (2020).

714    34.    S. Bodenmann, T. Rusterholz, R. Dürr, C. Stoll, V. Bachmann, E. Geissler, K. Jaggi-Schwarz, H.-P.
715            Landolt, The functional Val158Met polymorphism of COMT predicts interindividual differences in
716            brain alpha oscillations in young men. *J. Neurosci. Off. J. Soc. Neurosci.* **29**, 10855–10862 (2009).

35. S. Haegens, H. Cousijn, G. Wallis, P. J. Harrison, A. C. Nobre, Inter- and intra-individual variability in
alpha peak frequency. *NeuroImage*. **92**, 46–55 (2014).

36. S. Baillet, J. C. Mosher, R. M. Leahy, Electromagnetic brain mapping. *IEEE Signal Process. Mag.* **18**,
14–30 (2001).

37. R. S. Desikan, F. Ségonne, B. Fischl, B. T. Quinn, B. C. Dickerson, D. Blacker, R. L. Buckner, A. M. Dale,
R. P. Maguire, B. T. Hyman, M. S. Albert, R. J. Killiany, An automated labeling system for subdividing
the human cerebral cortex on MRI scans into gyral based regions of interest. *NeuroImage*. **31**, 968–
980 (2006).

38. P. E. Shrout, J. L. Fleiss, Intraclass correlations: Uses in assessing rater reliability. *Psychol. Bull.* **86**,
420–428 (1979).

39. A. R. McIntosh, B. Mišić, Multivariate Statistical Analyses for Neuroimaging Data. *Annu. Rev. Psychol.*
**64**, 499–525 (2013).

40. B. T. Yeo, Thomas, F. M. Krienen, J. Sepulcre, M. R. Sabuncu, D. Lashkari, M. Hollinshead, J. L.
Roffman, J. W. Smoller, L. Zöllei, J. R. Polimeni, B. Fischl, H. Liu, R. L. Buckner, The organization of the
human cerebral cortex estimated by intrinsic functional connectivity. *J. Neurophysiol.* **106**, 1125–
1165 (2011).

41. S. Noble, M. N. Spann, F. Tokoglu, X. Shen, R. T. Constable, D. Scheinost, Influences on the Test-
Retest Reliability of Functional Connectivity MRI and its Relationship with Behavioral Utility. *Cereb.*
*Cortex N. Y. N 1991*. **27**, 5415–5429 (2017).

42. J. Cabral, M. L. Kringelbach, G. Deco, Functional connectivity dynamically evolves on multiple time-
scales over a static structural connectome: Models and mechanisms. *NeuroImage*. **160**, 84–96
(2017).

43. M. Nentwich, L. Ai, J. Madsen, Q. K. Telesford, S. Haufe, M. P. Milham, L. C. Parra, Functional
connectivity of EEG is subject-specific, associated with phenotype, and different from fMRI.
*NeuroImage*. **218**, 117001 (2020).

44. C. L. Horien, X. Shen, D. Scheinost, R. T. Constable, The individual functional connectome is unique
and stable over months to years. *Neuroimage* (2019), doi:10.1016/j.neuroimage.2019.02.002.

45. M. J. Brookes, M. Woolrich, H. Luckhoo, D. Price, J. R. Hale, M. C. Stephenson, G. R. Barnes, S. M.
Smith, P. G. Morris, Investigating the electrophysiological basis of resting state networks using
magnetoencephalography. *Proc. Natl. Acad. Sci. U. S. A.* **108**, 16783–16788 (2011).

46. B. A. E. Hunt, P. K. Tewarie, O. E. Mougin, N. Geades, D. K. Jones, K. D. Singh, P. G. Morris, P. A.
Gowland, M. J. Brookes, Relationships between cortical myeloarchitecture and electrophysiological
networks. *Proc. Natl. Acad. Sci.* **113**, 13510 (2016).

47. G. Michalareas, J. Vezoli, S. van Pelt, J.-M. Schoffelen, H. Kennedy, P. Fries, Alpha-Beta and Gamma
Rhythms Subserve Feedback and Feedforward Influences among Human Visual Cortical Areas.
*Neuron*. **89**, 384–397 (2016).

48. B. Morillon, S. Baillet, Motor origin of temporal predictions in auditory attention. *Proc. Natl. Acad.*
*Sci.* **114**, E8913–E8921 (2017).

49. S. Haufe, P. DeGuzman, S. Henin, M. Arcaro, C. J. Honey, U. Hasson, L. C. Parra, Elucidating relations
between fMRI, ECoG, and EEG through a common natural stimulus. *NeuroImage*. **179**, 79–91 (2018).

50. N. K. Logothetis, J. Pauls, M. Augath, T. Trinath, A. Oeltermann, Neurophysiological investigation of
the basis of the fMRI signal. *Nature*. **412**, 150–157 (2001).

51. J. F. Nottage, J. Horder, State-of-the-Art Analysis of High-Frequency (Gamma Range)
Electroencephalography in Humans. *Neuropsychobiology*. **72**, 219–228 (2015).

52. E. M. Whitham, K. J. Pope, S. P. Fitzgibbon, T. Lewis, C. R. Clark, S. Loveless, M. Broberg, A. Wallace,
D. DeLosAngeles, P. Lillie, A. Hardy, R. Fronsko, A. Pulbrook, J. O. Willoughby, Scalp electrical
recording during paralysis: Quantitative evidence that EEG frequencies above 20Hz are
contaminated by EMG. *Clin. Neurophysiol.* **118**, 1877–1888 (2007).

53. S. Yuval-Greenberg, O. Tomer, A. S. Keren, I. Nelken, L. Y. Deouell, Transient induced gamma-band
response in EEG as a manifestation of miniature saccades. *Neuron*. **58**, 429–441 (2008).

54. Y. Bagherzadeh, D. Baldauf, D. Pantazis, R. Desimone, Alpha Synchrony and the Neurofeedback
Control of Spatial Attention. *Neuron*. **105**, 577-587.e5 (2020).

55. M. S. Clayton, N. Yeung, R. Cohen Kadosh, The many characters of visual alpha oscillations. *Eur. J.*
*Neurosci.* **48**, 2498–2508 (2018).

56. J. J. Foster, E. Awh, The role of alpha oscillations in spatial attention: limited evidence for a
suppression account. *Curr. Opin. Psychol.* **29**, 34–40 (2019).

57. T. Lennert, S. Samiee, S. Baillet, Coupled oscillations enable rapid temporal recalibration to
audiovisual asynchrony. *Commun. Biol.* **4**, 559 (2021).

58. J. C. Mosher, S. Baillet, R. M. Leahy, in *IEEE Workshop on Statistical Signal Processing, 2003* (2003),
pp. 294–297.

59. E. Sareen, S. Zahar, D. Van De Ville, A. Gupta, A. Griffa, E. Amico, "Exploring MEG brain fingerprints:
evaluation, pitfalls, and interpretations" (preprint, Neuroscience, 2021), ,
doi:10.1101/2021.02.15.431253.

60. S. Sadaghiani, M. J. Brookes, S. Baillet, "Connectomics of Human Electrophysiology" (preprint,
PsyArXiv, 2021), , doi:10.31234/osf.io/dr7zh.

61. M. D. Rosenberg, E. S. Finn, D. Scheinost, X. Papademetris, X. Shen, R. T. Constable, M. M. Chun, A
neuromarker of sustained attention from whole-brain functional connectivity. *Nat. Neurosci.* **19**,
165–171 (2016).

62. M. D. Rosenberg, E. S. Finn, D. Scheinost, R. T. Constable, M. M. Chun, Characterizing Attention with
Predictive Network Models. *Trends Cogn. Sci.* **21**, 290–302 (2017).

63.　T. Harmelech, R. Malach, Neurocognitive biases and the patterns of spontaneous correlations in the
human cortex. *Trends Cogn. Sci.* **17**, 606–615 (2013).

64.　H. Cai, J. Zhu, Y. Yu, Robust prediction of individual personality from brain functional connectome.
*Soc. Cogn. Affect. Neurosci.* **15**, 359–369 (2020).

65.　C. Parkinson, A. M. Kleinbaum, T. Wheatley, Similar neural responses predict friendship. *Nat.*
*Commun.* **9**, 332 (2018).

66.　D. C. Glahn, A. M. Winkler, P. Kochunov, L. Almasy, R. Duggirala, M. A. Carless, J. C. Curran, R. L.
Olvera, A. R. Laird, S. M. Smith, C. F. Beckmann, P. T. Fox, J. Blangero, M. E. Raichle, Genetic Control
over the Resting Brain. *Proc. Natl. Acad. Sci. U. S. A.* **107**, 1223–1228 (2010).

67.　M. S. Korgaonkar, K. Ram, L. M. Williams, J. M. Gatt, S. M. Grieve, Establishing the resting state
default mode network derived from functional magnetic resonance imaging tasks as an
endophenotype: A twins study. *Hum. Brain Mapp.* **35**, 3893–3902 (2014).

68.　O. Miranda-Dominguez, E. Feczko, D. S. Grayson, H. Walum, J. T. Nigg, D. A. Fair, Heritability of the
human connectome: A connectotyping study. *Netw. Neurosci. Camb. Mass*. **2**, 175–199 (2018).

69.　C. A. Hodgkinson, M.-A. Enoch, V. Srivastava, J. S. Cummins-Oman, C. Ferrier, P. Iarikova, S.
Sankararaman, G. Yamini, Q. Yuan, Z. Zhou, B. Albaugh, K. V. White, P.-H. Shen, D. Goldman,
Genome-wide association identifies candidate genes that influence the human
electroencephalogram. *Proc. Natl. Acad. Sci. U. S. A.* **107**, 8695–8700 (2010).

70.　E. Leppäaho, H. Renvall, E. Salmela, J. Kere, R. Salmelin, S. Kaski, Discovering heritable modes of MEG
spectral power. *Hum. Brain Mapp.* **40**, 1391–1402 (2019).

71.　E. Salmela, H. Renvall, J. Kujala, O. Hakosalo, M. Illman, M. Vihla, E. Leinonen, R. Salmelin, J. Kere,
Evidence for genetic regulation of the human parieto-occipital 10-Hz rhythmic activity. *Eur. J.*
*Neurosci.* **44**, 1963–1971 (2016).

72.　T. Kaufmann, D. Alnæs, C. L. Brandt, F. Bettella, S. Djurovic, O. A. Andreassen, L. T. Westlye, Stability
of the Brain Functional Connectome Fingerprint in Individuals With Schizophrenia. *JAMA Psychiatry*.
**75**, 749 (2018).

73.　F. Tadel, S. Baillet, J. C. Mosher, D. Pantazis, R. M. Leahy, Brainstorm: a user-friendly application for
MEG/EEG analysis. *Comput. Intell. Neurosci.* **2011**, 879716 (2011).

74.　J. Gross, S. Baillet, G. R. Barnes, R. N. Henson, A. Hillebrand, O. Jensen, K. Jerbi, V. Litvak, B. Maess,
R. Oostenveld, L. Parkkonen, J. R. Taylor, V. van Wassenhove, M. Wibral, J.-M. Schoffelen, Good
practice for conducting and reporting MEG research. *NeuroImage*. **65**, 349–363 (2013).

75.　B. Fischl, FreeSurfer. *NeuroImage*. **62**, 774–781 (2012).

76.　A. Bruns, R. Eckhorn, H. Jokeit, A. Ebner, Amplitude envelope correlation detects coupling among
incoherent brain signals. *Neuroreport*. **11**, 1509–1514 (2000).

77.  P. Welch, The use of fast Fourier transform for the estimation of power spectra: A method based on
time averaging over short, modified periodograms. *IEEE Trans. Audio Electroacoustics*. **15**, 70–73
(1967).

78.  R Core Team, *R: A Language and Environment for Statistical Computing* (R Foundation for Statistical
Computing, Vienna, Austria, 2020; https://www.R-project.org/).

79.  A. M. Mowinckel, D. Vidal-Piñeiro, *ggseg: Plotting Tool for Brain Atlases* (2021; https://CRAN.R-
project.org/package=ggseg).

80.  A. R. McIntosh, N. J. Lobaugh, Partial least squares analysis of neuroimaging data: applications and
advances. *NeuroImage*. **23 Suppl 1**, S250-263 (2004).

830
831

# Supplemental material

## MEG fingerprinting is robust against sample demographics

The OMEGA data repository contains 158 participants, with a subset (N=47) scanned at
multiple occasions several days apart. OMEGA consists essentially of data from healthy controls
with a 18-73-year age span (SD=14.7 years; Supplemental Table 1).
One potential confound that could have inflated our ability to fingerprint individuals is the
heterogeneity introduced by both healthy and clinical populations in the OMEGA cohort. To
address this concern, we ran a secondary analysis where we performed the fingerprinting
procedures described in the manuscript with only healthy controls (N=130). The results, reported
in Supplemental Table 2, demonstrated that fingerprint performances were not biased by the
patients/controls heterogeneity of the OMEGA sample. We observed a decrease of less than 1%
in performance relative to fingerprinting from the entire cohort. Further, there was no clear
relationship between self-identifiability and demographics (Figure S1)., using connectome (age: r=
0.08, p = 0.2; gender: t= -0.27, p = 0.7; handedness: t= -0.51, p = 0.6; clinical status: t= -0.87, p = 0.3;
two-tailed) and spectral fingerprinting (age: r= 0.10, p = 0.1; gender: t= 0.62, p = 0.5; handedness: t=
0.13, p = 0.8; clinical status: t= 0.84, p = 0.3; two-tailed).
849

850
**Figure S1: Self identifiability is not associated with demographics**
The plots depict demographic variables and corresponding self-identifiability scores across both
**(a)** connectome and **(b)** spectral broadband *within-session* fingerprinting. Demographic variables
included age, biological sex, dominant hand, and healthy vs. patient categories. There was no clear
relationship between demographics and self-identifiability — i.e., differences in demographics did
not drive self-identifiability.

857
858

Acquisition parameters did not affect both fingerprinting performances (Figure S2).
Participants with longer recordings (i.e., more data) were not more identifiable (connectome: r= -
0.02, p = 0.7; spectral: r= 0.02, p = 0.8). This observation is consistent with the *within- & between-*
*session shortened* fingerprinting results, which demonstrate individuals were identifiable from
shorter 30-second recordings (see below).
Taken together, these supplemental results demonstrate that MEG fingerprinting is robust
against data artifacts, heterogeneous sample demographics and acquisition parameters.
866

|  | Within-session data | Between-session data |
|---|---|---|
| Age | 31.9 ± 14.7 | 26.7 ± 11.6 |
| Gender | 77 Females | 24 Females |
| Dominant Hand | 147 Right, 8 Left, 1 Other | 44 Right, 3 Left |
| Clinical Status | 130 Healthy Controls<br>22 ADHD<br>6 Chronic Pain | 25 Healthy Controls<br>22 ADHD |

Supplemental table 1: OMEGA participant demographics

Demographic variables summarized for both subsets of the OMEGA data repository.

871
872

Figure S2: Recording duration did not affect self-identifiability

Scatter plots of self-identifiability vs. duration of data collections, for the broadband *within-session* challenge. There was no clear relationship between self-identifiability and the duration of the MEG recordings across participants.

877
878

| | All Participants | | Only Healthy Controls | |
| --- | --- | --- | --- | --- |
| | Dataset 1 to Dataset 2 | Dataset 2 to Dataset 1 | Dataset 1 to Dataset 2 | Dataset 2 to Dataset 1 |
| Connectome | 94.9% | 94.3% | 93.8% | 93.0% |
| Spectral | 96.2% | 96.2% | 95.3% | 95.3% |

Supplemental table 2. Fingerprinting performances of healthy controls

Identification performances of connectome and spectral broadband *within-session* fingerprinting obtained from for the entire repository (healthy controls and patients), and from healthy participants only. Each column reports fingerprinting performances from Dataset 1 to Dataset 2 and vice-versa (see Figure 1 for details). Overall, identification accuracy decreased slightly by ~0.9% when comprising healthy participants only. Consistent with our findings reported in Figure S2, clinical status did not play a major role in the identification of individuals.

888
889 **Figure S3: Identification accuracy from within-session datasets**
890 Results from MEG *within-session* fingerprinting. Identification accuracy for **(a)** connectome and **(b)**
891 spectral fingerprinting (broadband and narrowband data). The accuracy scores are reported for
892 identification from dataset 1 to dataset 2 and vice-versa, as explained in Methods.
893

894
895 **Figure S4: Example participant correlation matrix for fingerprinting**
896 Exemplar participant correlation matrix derived from *between-session* data used for
897 fingerprinting. The study-identity of participants was determined by the highest correlation
898 statistics taken across rows (e.g., to identify dataset-2 from dataset-1) or columns (to identify
899 dataset-1 from dataset-2).
900

**Data reduction from principal component analysis does not improve MEG fingerprinting**
**substantially**

Amico and Goñi (*1*) previously reported improvements to participant differentiation when
using data reduction techniques prior to identification, using e.g., principal component analysis
(PCA). We reproduced their approach, using PCA to reduce the dimensionality of the connectome
and spectral feature spaces prior to fingerprinting. Our results provided little support to PCA
reconstruction improving identification accuracy, as shown Figure S5 and in Supplemental Table
3. PCA increased self-identifiability by less than 1.5%. Data reduction had limited beneficial impact
possibly because of high fingerprinting performances at baseline (without data reduction). We
also emphasize that we conducted MEG source time series extraction via a PCA of all local time

series within each parcel. It is therefore likely that this dimension reduction procedure contributed
to improve signal-to-noise ratio and limited the impact of subsequent PCA of features.
913

|  | Original (un-reconstructed) | | PCA Reconstructed | |
| --- | --- | --- | --- | --- |
|  | Dataset 1 to Dataset 2 | Dataset 2 to Dataset 1 | Dataset 1 to Dataset 2 | Dataset 2 to Dataset 1 |
| Connectome | 94.9% | 94.3% | 96.2% | 96.2% |
| Spectral | 96.2% | 96.2% | 96.2% | 96.2% |

914
**Supplemental Table 3: Limited contribution of data reduction from principal component analysis**
**to MEG fingerprinting.**
Performances in identification accuracy for connectome and spectral broadband *within-session*
fingerprinting, for both original and PCA-reconstructed data (*1*). PCA data reduction improved
connectome fingerprinting performances only slightly (about 2%). It had virtually no effect on
spectral fingerprinting performances.
921

922
**Figure S5: Limited benefit of PCA reconstruction to identification accuracy**
PCA reconstruction as proposed by Amico and Goñi (2018) had limited effect on **(a)** connectome
and **(b)** spectral *within-session* fingerprinting. The original results (Figure 2) are plotted against

PCA-reconstructed results. From left to right, plots show *i)* PCA components plotted vs. their
respective fractions of signal variance explained, *ii)* identification accuracy across PCA
components, *iii)* average self-identifiability across PCA components, and *iv)* violin plots of self-
identifiability before and after PCA reconstruction. Overall, PCA reconstruction did not
substantially improve identification accuracy.
931
**Fingerprinting with 30-second data segments**
We challenged MEG fingerprinting using short 30-second data segments (i.e., shortened
*within-session* fingerprinting). We epoched participants' MEG recordings into three datasets of 30
second, where the first dataset was the first 30 seconds of the recording after having removed the
initial five seconds, the second dataset was the 30 seconds immediately following the first dataset,
and the last dataset was the last 30-second segment of the recording after having removed the
last ten seconds (Figure 1). Cropping the initial and last few seconds from recordings excluded
edge filtering and other session artifacts. The lengths of the short datasets and epochs were
determined from the participant with the shortest available recording. This procedure yielded
three data segments for fingerprinting purposes via 6 possible dataset pairs (i.e., dataset 1 and 2;
dataset 2 and 3; and dataset 1 and 3 and vice-versa). Results for all possible combinations of
datasets are reported in Figure S6.
Connectome fingerprinting successfully identified individuals across all possible
combinations of datasets (Figure S6). Identification from recordings collected closer in time (e.g.,
dataset-1 and dataset-2) outperformed identification from datasets collected further apart in time
(e.g., between dataset-1 and dataset-3). Overall, spectral fingerprinting yielded lower
identification accuracy than connectome fingerprinting, in particular from datasets further apart
in time.
In a similar fashion, we challenged MEG fingerprinting using short 30-second data
segments from different sessions (i.e., *between-session* fingerprinting). This yielded 6 epochs of
data for fingerprinting (i.e., three from both the first and second recording, see Figure 1a).
Identification results averaged across all possible data pairs are reported Figure 3c. Connectome
fingerprinting performances were greater than those from spectral fingerprinting. Identification
from slower frequency data components performed worse in comparison to higher bands – see
main article body for discussion.
957
958

**Figure S6: Identification accuracy from shortened within-session datasets**

Identification results from shortened *within-session* datasets (30 seconds) for **(a)** connectome and
**(b)** spectral broadband and narrowband fingerprinting. The accuracy scored are reported for
identification from all possible combinations of datasets, (i.e., dataset 1 to predict dataset 2,
dataset 3 to predict dataset 2, etc.; see Methods for details). Identification accuracy increased as
datasets were proximal in time (i.e., fingerprinting accuracy for dataset 1 to dataset 2 was greater
than for dataset 1 to dataset 3).

**Fingerprinting across recording sessions**

We also report fingerprinting accuracy performances from all possible pairs of datasets for
the *between-session* fingerprinting challenge in Figure S7. Overall, spectral fingerprinting
outperformed connectome fingerprinting, as discussed in the main text.

973
974 **Figure S7: Between-session identification accuracy**

975 Results from MEG *between-session* fingerprinting. Identification accuracy for both **(a) c**onnectome
976 and **(b)** spectral broadband and narrowband fingerprinting. The accuracy scores are reported for
977 identification from dataset 1 to dataset 2 and vice-versa (see Methods).
978
**Individuals cannot be identified from their respective imaging kernels**
We verified that the within-session identification of individuals was not possible from empty-room
data (i.e., with no participant under the MEG sensor array) processed through their respective
imaging kernel of beamformer weights. Indeed, these latter are defined from individual anatomy
and head position under the MEG sensor array, which may have been sufficient information to
drive identification. We therefore ran the same fingerprinting pipeline on each session's empty-
room data transformed through the corresponding individual's beamformer imaging kernel, which
was identical for each of the within-session data segments used. Note that for the between-
session challenges, the imaging kernels were adjusted to the respective individual head positions
measured during each session. These analyses demonstrated that the imaging kernel information
did not contribute substantially to MEG fingerprinting (overall performance was below 20% on
average, See Figure 2).
991
992 We also ran the MEG fingerprinting pipeline directly from the sensor data of the empty-room
993 recordings, without transformation through individual imaging kernels, to assess the floor level of
994 identification performances from non-brain data only. The data confirmed substantially lower
995 levels of identification (<5% accuracy on average; see Figure S8).
996
997

998
999 **Figure S8: Verification of failed fingerprinting from non-brain data (empty-room recordings)**
1000 Results for the empty-room sensor fingerprinting challenge. As expected, identification accuracies
1001 of connectome and spectral broadband and narrowband fingerprinting were substantially lower
1002 than from actual MEG data with individuals present.
1003
**Fingerprinting from scalp data only**
We also performed MEG fingerprinting from individual sensor data, with no MEG source
reconstruction to assess the added value of source modeling. We replicated the above MEG
fingerprinting pipelines from the *within-*, *within-shortened,* and *between- session* analyses.

Identification performances were less than with source modeling, especially from signal
components in higher frequency bands and for the *shortened* challenges (see Figure S9, S10, &
S11). Yet for other signal components and longer durations, individuals remain identifiable from
sensor-level data collected between sessions (>60% accuracy from broadband data), albeit with
lower accuracy than when using MEG source transformations, which explicitly account for
different head positions between sessions.
Taken together with the empty-room fingerprinting tests above, these results provide evidence
that brain signals, not environmental conditions, were crucial for individual identification.
1016
1017

1018
1019 **Figure S9: Within-session identification from MEG sensor data (no source modeling)**
1020 Results from MEG sensor data in the *within-session* fingerprinting challenge. The identification
1021 accuracy statistics are shown for both connectome and spectral broadband and narrowband
1022 fingerprinting. The average accuracy scores are reported across identifications from dataset-1 to
1023 dataset-2 and vice-versa (see Methods).
1024

1025
**Figure S10 Within-session identification from shortened (30-s) MEG sensor data (no source**
**modeling)**
Results from MEG sensor data in the *within-session shortened* fingerprinting challenge. The
identification accuracy statistics are shown for both connectome and spectral broadband and
narrowband fingerprinting. The average accuracy scores are reported across identifications from
all possible pairs of datasets (see Methods).

1032

1033
1034 **Figure S11: Between-session identification from MEG sensor data (no source modeling)**
1035 Results from MEG sensor data in the *between-session* fingerprinting challenge. The identification
1036 accuracy statistics are shown for both connectome and spectral broadband and narrowband
1037 fingerprinting. The average accuracy scores are reported across identifications from dataset-1 to
1038 dataset-2 and vice-versa (see Methods).
1039

**Salient neurophysiological features for fingerprinting**

We reported in the main manuscript intraclass correlations (ICC) to determine which
features contributed to individual identification the most. We also performed two additional
analyses, deriving *group consistency* and *differential power*. These two metrics were proposed by
Finn and colleagues (*2*) to identify the features which were the most consistent across their cohort,
vs. The features which were the most consistent within individuals but different across participant,
respectively (*2*). Differential power measures the empirical probability that a given feature is more
likely to have a higher edgewise product vector across individuals than within the same individual.
Taking the sum of the natural log of this probability across subjects yields differential power (*2*).
The higher the differential power, the better a feature discriminates between individuals. Results
for differential power are plotted in Figures S7 and S9. We found that the most discriminant
connectome features were the visual and limbic networks across frequency bands, while the most
discriminant spectral features remained along midline structures for fast oscillatory signal
components. Overall, these results confirmed the ICC analysis results, with the addition of the
contributions of spectral power in the beta and gamma band along the supplementary motor,
motor, and somatosensory cortices.

1056
**Figure S12: Differential power connectome fingerprinting**

Differential Power (DP) analysis for broadband connectome fingerprinting of the *within-session*
dataset (see Figure 1). Mean DP plotted within frequency bands and per resting-state network as
defined by (*3*): Default Mode Network (DMN), Dorsal Attention (DA), Frontal-Parietal (FP), Limbic
(L), Somato-Motor (SM), Ventral Attention (VA), and Visual (VIS). The higher the DP, the more the
corresponding functional connection was essential for fingerprinting. The outstanding
connections determined by DP for fingerprinting were the Visual network across all frequency
bands, and the Limbic network in the beta and gamma bands.

1065

Group consistency reflects edges that are consistent across individuals. Group consistency
was computed from the mean edgewise product vector across all subjects (*2*). Large values of
group consistency highlight features that are consistent both within participants and across the
cohort. Our analyses are shown Figures S8 and S10. The resulting most consistent connectome
features remained along the diagonal of the FC matrix (i.e., connections within the same networks)
specifically in the Dorsal Attention and Fronto-Parietal networks. The most consistent features for
spectral fingerprinting were in the lower frequency bands, specifically in the lateral frontal
cortices. This outcome was consistent with our ICC results (see Manuscript).

1074

1075
**Figure S13: Group consistency connectome fingerprinting**
Group Consistency (GC) analysis for broadband connectome fingerprinting of the *within-session*
dataset (see Figure 1). Mean GC plotted within frequency bands according to the labels from (*3*):
Default Mode Network (DMN), Dorsal Attention (DA), Frontal-Parietal (FP), Limbic (L), Somato-
Motor (SM), Ventral Attention (VA), and Visual (VIS). The higher the GC, the more consistent was
a functional connection within an individual and across the cohort. The most consistent
connections were those along the diagonal, specifically for the Dorsal Attention and Frontal-
Parietal networks across all frequency bands.

1084
**Figure S14: Differential power spectral fingerprinting**
Differential Power (DP) analysis for broadband spectral fingerprinting of the *within-session* dataset
(see Figure 1). Mean DP plotted within frequency bands according to the Desikan-Killiany atlas (*4*).

The higher the DP, the more a given frequency band and ROI distinguished between individuals.
The most characteristic regions and frequencies were medial structures for the beta band, and
temporal and central regions for gamma band signals.
1091

1092
**Figure S15: Group consistency spectral fingerprinting**
Group Consistency (GC) analyses for broadband spectral fingerprinting of the *within recording*
*session* dataset (see Figure 1). Mean GC plotted within frequency bands according to the Desikan-
Killiany atlas (*4*). The higher the GC, the more a given frequency band and ROI remained consistent
within individuals and across the cohort. The most stable frequencies were the lower bands (delta
and theta) and the most consistent regions across individuals were lateral frontal areas.
1099
**Partial Least Squares (PLS) analysis**
We tested whether differences in resting-state neurophysiological signals related to
meaningful demographic features using an exploratory Partial Least Squares (PLS) analysis. PLS is
a multivariate statistical method that relates two data matrices based on latent variables (LV) that
explain the highest covariance between the two datasets. Here, our two datasets consist of a
demographic matrix (i.e., age, gender, handedness, and clinical status) and a neurophysiological
data matrix (i.e., spectral power or functional connectome). Latent variables (which explain the
most covariance between both matrices), and their corresponding variance explained are plotted
in Figure S16. Significance of each latent variable was assessed via permutation tests. Permuting
the rows of the data allowed us to compute an associate p-value for each latent variable (see
Manuscript). We chose to explore the first significant latent variable which explained the most
variance for each neurophysiological signal feature (i.e., the first component for connectomes and
spectral data). The resulting weights associated to the latent neural and demographic components
are depicted Figure 5 along with their bootstrapped ratios. These results corroborate how
neurophysiological signals at rest, in addition to identifying individuals, carry meaningful
information about participant demographics.
1116

**(a) Functional connectivty**    **(b) Power spectral density**

**Figure S16: PLS latent variables**

Results for the PLS analysis conducted for both **(a)** connectome and **(b)** spectral fingerprinting features. Each plot depicts the latent components obtained for each of the PLS analyses, their corresponding variance explained, and permuted *p*-value (right axis). One significant latent variable explained 43.1% of the variance for connectome fingerprinting and two latent variables explained 44.7% and 28.3% of the variance for spectral fingerprinting, respectively. We explored in the main Manuscript only the first significant component for each method (i.e., the circled component).

## References

1.  E. Amico, J. Goñi, The quest for identifiability in human functional connectomes. *Sci. Rep.* **8**, 8254 (2018).

2.  E. S. Finn, X. Shen, D. Scheinost, M. D. Rosenberg, J. Huang, M. M. Chun, X. Papademetris, R. T. Constable, Functional connectome fingerprinting: identifying individuals using patterns of brain connectivity. *Nat. Neurosci.* **18**, 1664–1671 (2015).

3.  B. T. Yeo, Thomas, F. M. Krienen, J. Sepulcre, M. R. Sabuncu, D. Lashkari, M. Hollinshead, J. L. Roffman, J. W. Smoller, L. Zöllei, J. R. Polimeni, B. Fischl, H. Liu, R. L. Buckner, The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *J. Neurophysiol.* **106**, 1125–1165 (2011).

4.  R. S. Desikan, F. Ségonne, B. Fischl, B. T. Quinn, B. C. Dickerson, D. Blacker, R. L. Buckner, A. M. Dale, R. P. Maguire, B. T. Hyman, M. S. Albert, R. J. Killiany, An automated labeling system for subdividing the human cerebral cortex on MRI scans into gyral based regions of interest. *NeuroImage*. **31**, 968–980 (2006).