How human runners regulate footsteps on uneven terrain

Nihav Dhawale[1,2] and Madhusudhan Venkadesan[1]

[1]*Department of Mechanical Engineering & Materials Science,Yale University, USA*
[2]*National Centre for Biological Sciences, Tata Institute of Fundamental Research, India*

1 Abstract

Running was crucial for human evolution, especially for persistence hunting. But how people remain
stable on uneven natural terrain is not understood. In particular, we do not know how runners
manage competing demands on their attention, like seeking level ground areas to step on versus
seeking out prey. Previous work used step-like terrain with height variations but not the more
destabilizing combination of height and slope variations like a natural undulating terrain. So we
studied human runners on undulating uneven terrain and measured their energetics, kinematics, and
ground forces. Here we show that runners do not selectively land their feet on more level areas.
Instead, they remain stable using their body's mechanical response and possibly occasional feedback
corrections, with little increase in energy consumption relative to flat ground. These findings may
explain how persistence hunters can devote visual attention to tasks other than stability while running
on uneven ground.

Running on uneven terrain was needed for persistence hunting and played a key role in

human evolution [1, 2]. Visual guidance of foot placement may help avoid potentially destabi-

lizing areas of the ground [3, 4]. But vision is also needed to track subtle footprints, avoid large

obstacles, and continuously survey the landscape for prey. So there are potentially competing

demands on visual attention. Indeed, studies of people walking on uneven ground show subtle

interactions between gaze, stepping patterns, and terrain complexity that trade-off the use of

vision to guide the next step versus planning the overall path through uneven terrain [5, 6]. This

trade-off is probably more severe in running because there is lesser time to visually gather infor-

mation about the terrain for the oncoming step and use that to plan the step. Furthermore, in

persistence hunting, the runner should balance these demands on stability and attention against

running economy and metabolic energy consumption [7]. We currently do not know how people

negotiate stability on natural terrain and its impact on metabolic energy consumption.

Past studies of uneven terrain running have investigated running over step-like terrain com-

prised of piecewise flat blocks on the ground [8–12]. Such terrain are not representative of

the undulating unevenness of natural environments, but show how humans deal with height

variations on the ground. A key finding is that there is only a slight increase of around 5%

in metabolic energy consumption to run on these step-like, piecewise flat terrain [9]. That

naturally raises the question of how the runners remain stable.

Stability analysis has relied on interpreting data using models that approximate the runner

as a point-like mass on a massless leg, the widely used spring-legged inverted pendulum (SLIP)

model [8, 11, 13–15]. The main hypothesized strategies to aid stability include higher leg

retraction rates [16], wider lateral foot placement [9, 17], and the possible use of vision to guide

foot placement [18]. Point-mass models are appropriate to interpret stability for step-like terrain

because slope variations do not influence stability in point-mass models [19]. The point-mass

has no moment of inertia about its center, because of which the ground force is constrained

to point towards the center of mass, and the ground slope becomes immaterial. Theoretical

work using models that have a non-zero moment of inertia show that slope variations are far

more destabilizing [19], consistent with common experience among runners. So there is a need

for experiments on undulating terrain with slope variations to understand how natural terrain

affects stability.

Mathematical analysis of running finds two key strategies for remaining stable when both

the slope and height of the terrain randomly vary [19]. The first strategy is to selectively step

on flatter regions like local maxima and minima of an undulating terrain where the ground is

always level. Thus, the undulating terrain is effectively just height variations, and the previously

proposed stabilization mechanisms on step-like terrain become effective. The second strategy

is related to the mathematical result that step-to-step fluctuations in impulses arising from

tangential interactions of the foot with uneven ground are most destabilizing and could cause

the runner to fall. Thus controlling the body's mechanical state at touchdown to reduce the

horizontal impulse will aid stability. Although sensory feedback control is necessary for stability

according to the model, the combined effect of controlling the footstep location and reducing

the horizontal impulse allows for feedback acting slowly over multiple steps to suffice. However,

experimental tests of these hypothetical foot placement and horizontal impulse modulation

strategies are currently lacking.

The cumulative understanding of running from past experiments on flat and step-like terrain

and models on uneven terrain motivates this paper's two hypotheses. The first hypothesis

predicts that runners will land their feet on level ground areas to reduce destabilization by

randomly varying slopes. The second hypothesis predicts that runners will reduce tangential

impulses with the ground during stance. However, feedback control will probably be important

over several steps and often manifests as increased variability in step-to-step kinematic variables

Fig. 1. Uneven terrain experiments. a, We conducted human-subject experiments on flat and uneven terrain while recording biomechanical and metabolic data. The reflective markers and the outline of the force plate are digitally exaggerated for clarity. **b**, Footsteps were recorded to determine whether terrain geometry influences stepping location, illustrated here by a mean-subtracted contour plot of terrain height (units of mm) for an approximately 6 foot segment of uneven II overlaid with footsteps. Blue and red circles represent opposite directions of travel and marker transparency differentiates trials.

such as step length and width as found by previous studies [4, 9, 15]. So we studied human runners on uneven terrain that had slight but potentially destabilizing undulations and measured their energetics, kinematics, and foot contact forces (Fig. 1).

Results

We conducted overground running experiments with nine subjects who ran on three surfaces—flat, *uneven I*, and *uneven II*—while measuring ground reaction forces, oxygen consumption, and three-dimensional kinematics of the subject's hip and feet (Fig. 1a, Methods). We probed foot placement strategies by digitizing the uneven terrain and using those data in a stochastic analysis of the foot kinematics (Fig. 1b, 2). In addition, we estimated the tangential impulse that causes loss of forward momentum in early stance using the measured ground reaction forces (Fig. 3a,b), and recorded step kinematics and energetics that allow comparison with previously published studies on uneven terrain locomotion [9, 20–22].

Statistical tests used linear mixed models with a significance threshold of $\alpha = 0.05$. Post-hoc, pairwise comparisons with Tukey corrections were performed for the ANOVAs and ANCOVAs that passed the significance threshold (methods 1.4.2). We report statistically significant com-

Fig. 2. Foot placement on uneven terrain. Histogram of the interquartile range of heights (h_{IQR}) at footstep locations for the directed sampling scheme (blue), experiments (red, 5237 footsteps), and the blind sampling scheme (yellow) on **a**, uneven I and **b**, uneven II. Note that h_{IQR} varies over a greater range on uneven II.

parisons in the text and all comparisons in supplementary Tables S1,S2. Differences in the

mean between testing conditions are reported as mean $\pm$ standard error (S.E.) of the mean.

Descriptive statistics are reported as mean $\pm$ standard deviation (S.D.).

Nondimensionalization: We express lengths in units of leg length ℓ and speed in units of $\sqrt{g\ell}$,

[23] where g is acceleration due to gravity. Statistically significant post-hoc comparisons are ad-

ditionally reported in dimensional units using $g = 9.81\,\mathrm{m/s^2}$, and the mean of the measurements

across subjects, namely, $\ell = 0.89\,\mathrm{m}$ and $m = 66.1\,\mathrm{kg}$.

Foot placement on uneven terrain

To test whether real runners prefer to land on flatter patches, the measured footsteps were

compared against two extreme models, a null hypothesis of a *blind* runner and an alternative

hypothesis of a *directed* runner whose footsteps are selectively aimed at level parts of the terrain.

All participants were heel-strike runners on all terrain types as judged from the double peak

in the vertical ground reaction force profile. So their footsteps sample the terrain in heel-sized

patches. Therefore, we quantized the terrain into heel-size patches and used the interquartile

range of heights (h_{IQR}) in each patch as a measure of its unevenness.

The blind scheme uses a uniform random sample of heel-sized patches of the terrain to

obtain statistics of the terrain at landing locations. The directed scheme preferentially samples

more level patches using a Markov chain Monte Carlo (MCMC) model (methods 1.2.1). In this

model, each step is directed towards a patch of the lowest h_{IQR}, but within bounds defined by

the mean and standard deviation of the experimentally measured step length and width.

The experimentally measured stepping patterns are indistinguishable from the blind scheme

on both uneven I and II in terms of the terrain unevenness as quantified by h_{IQR} (human sub-

jects versus blind scheme in Fig. 2). However, the directed scheme finds substantially more

level landing patches, showing that it was possible for the runners to land on more level ground (directed scheme in Fig. 2). These trends are also borne out in a subject-wise analysis (supplementary Fig. S2,S3).

The directed scheme found more level patches at the cost of increased variability in step length and step width compared to the runners. The mean step length of the directed scheme was 0.3% and 0.02% lower than experimental data on uneven I and uneven II, respectively. However, the standard deviation of step length increased by 22% on uneven I and by 18% on uneven II compared to experimental measurements. The mean step width under the directed scheme was slightly different from the experimental data; higher by 3.7% on uneven I and lower by 7% on uneven II. In contrast, the standard deviation of step width for the directed scheme was higher than the experimental measurements by 97% on uneven I and by 79% on uneven II.

The overall statistics of the terrain location at foot landing may obscure step-to-step dependence of the foot landing on terrain features. So we used a second analysis of footstep patterns that estimated the foot landing probability $p_{i,j}$ in the $(i, j)^{\text{th}}$ foot-sized cell and correlated that with terrain unevenness as defined by the median and the interquartile range of the terrain height in that cell. Positive correlation with the median height would indicate stepping on local maxima that are flatter than the surrounding, and negative correlation with the interquartile range would indicate stepping on flatter regions with more uniform height. Neither correlation was significant (Table 1). Subject-wise landing probabilities also bear out the same results (supplementary fig S5). Taken together, these results indicate that the runners did not guide their footsteps towards flatter areas of the terrain.

Table 1. Correlation between landing probability and terrain unevenness. Details of the ANCOVAs on the linear mixed models from equation (12) showing denominator degrees of freedom, F-values, and p-values from the dataset of stepping probabilities and terrain height statistics of 1628 foot-sized terrain patches for all subjects on uneven I and uneven II.

dependent variable	DenDF	F-value	p-value
median terrain height	11.8	0.40	0.54
IQR terrain height	26.4	0.02	0.89

Fore-aft impulses

The fore-aft ground reaction force in stance initially decelerates the center of mass before accelerating it forward (Fig. 3a). We find that less than $6 \pm 1\%$ (mean $\pm$ S.D.) of the forward momentum is lost during the deceleration phase of stance and there is no dependence on ter-

¹²⁵ rain or subject (Fig. 3b). The low variability of the fore-aft impulse, just 1% of the forward

¹²⁶ momentum, suggests that it is tightly regulated across runners, terrain and steps.

Fig. 3. Regulation of fore-aft impulses. a, The fore-aft impulse J_y^* (grey shaded area) is found by integrating the measured fore-aft ground reaction force F_y (black curve) during the deceleration phase. **b**, Mean $\frac{J_y^*}{mv_y}$. **c**, Measured $\frac{J_y^*}{mv_y}$ (green circles) versus relative forward foot speed at landing (forward foot speed/center of mass speed) for each step recorded on all terrain types (total 1081 steps). The green line is the regression fit for the data. The dark and light grey lines are the predicted fore-aft impulse for the mean stiff and compliant jointed models, respectively. Per step model predictions in supplementary Fig. S6. **d**, Measured versus predicted fore-aft impulses for every step. The dotted line represents perfect prediction.

¹²⁷ Fore-aft impulses can be reduced by reducing forward foot speed at landing or by main-

¹²⁸ taining compliant joints at touchdown [19]. The regulation of foot speed is unlikely to be the

¹²⁹ primary determinant of the low variability in the collision impulse because the dimensionless

¹³⁰ forward foot speed at touchdown across all terrain varied by nearly 50% of its mean (0.4 ± 0.2,

¹³¹ supplementary Table S1), whereas fore-aft collision impulses varied only by 17% of the mean.

¹³² A statistical analysis lends further support and shows that the dimensionless fore-aft impulse

¹³³ depends significantly, but only weakly, on the dimensionless forward foot speed at landing (sup-

¹³⁴ plementary Table S2, $p = 0.001$, slope $= 0.01 \pm 0.003$).

¹³⁵ To further investigate this weak dependence of the retarding impulse on foot speed, we

¹³⁶ analysed the mechanics of foot landing and the resultant impulse using a four-link chain model

¹³⁷ of the leg and torso when the foot undergoes a rigid, inelastic collision with the ground (meth-

ods 1.3). The inertia of the leg's segments are represented by the three links and the torso, arms, and head by a single link attached to the top of the leg (Fig. 7, similar to [24]). The measured kinematics are fed through the model under two stiffness regimes; zero joint stiffness and infinite joint stiffness. Recall that only these two stiffness regimes are distinguishable in instantaneous collision models [24, 25], thus requiring no fitting parameters. By analyzing the collisional impulse for these two extremes of joint stiffness, we isolate the contributions to the fore-aft impulse arising from varying the joint stiffness versus varying the forward foot speed at landing.

The estimated fore-aft impulse at both joint stiffness extremes depends linearly on the forward foot speed (supplementary Fig. S6). The models at the two extremes of joint stiffness bound the experimental data, with the compliant model underestimating the measured fore-aft impulse while the stiff model overestimates it (Fig. 3c,d, supplementary Fig. S6). This is expected because the muscle contraction needed for weight support and propulsion would induce non-zero but non-infinite stiffness at the joints. But surprisingly, both models overestimate the dependence of the fore-aft impulse on foot speed, although the compliant model is closer to the data (Fig. 3c). The slope of measured speed-impulse data is $0.01 \pm 0.003, p = 0.001$ (supplementary Table S2) while that of the compliant jointed model is $0.0203 \pm 0.010, p < 0.0001$ and the stiff-jointed model is $0.056 \pm 0.005, p < 0.0001$ (supplementary Fig. S6). The compliant model's predictions resemble the data when the measured impulse is below 0.07 (Fig. 3d), which is the case for most steps (Fig. 3b). But the model underestimates the impulse on the occasional steps when runners experience more severe fore-aft impulses. Unlike the compliant model, the stiff model consistently over-estimates the measured fore-aft impulse over its entire range. Thus, we propose that maintaining low joint stiffness at landing helps maintain low fore-aft impulses despite variations in touchdown foot speed.

Leg retraction

Increased leg retraction rate results in reduced forward foot speed at touchdown, thereby altering the tangential impulse [16, 19]. The mean non-dimensional forward foot speed at landing is terrain-dependent and lower by 0.17 ± 0.04 ($p = 0.001$) on uneven I compared to flat ground, and by 0.15 ± 0.04 ($p = 0.002$) on uneven II compared to flat ground (Fig. 4a). For the mean subject, these correspond to reductions of 0.48 ± 0.11 m/s on uneven I and 0.42 ± 0.11 m/s on uneven II compared to flat ground. These differences indicate higher leg retraction rates on

Fig. 4. Energetics and stepping kinematics. a, Box plot of the mean forward foot speed at landing (units of froude number). **b**, Box plot of the median step width (normalized to leg length). **c**, Box plot of the step width variability. Central red lines denote the median, boxes represent the interquartile range, whiskers extend to 1.5 times the quartile range, and open circles denote outliers. **d**, Net metabolic rate normalized to subject mass. Whiskers represent standard deviation across subjects.

uneven terrain, as also reported in running birds [18, 26].

Leg retraction has been hypothesized to improve running stability in the context of point-

mass models by altering touchdown angle to aid stability [21, 27]. We find that touchdown

angle depends significantly but only weakly on forward foot speed at landing ($p \approx 0$, slope

$= 0.07 \pm 0.01$ rad). If the dimensionless forward foot speed at landing varied through its entire

observed range from -0.2 to 1.1, it would result in a change in landing angle of 0.08 rad or $5°$.

Stepping kinematics

Consistent with previous studies on step-like terrain, [9] we find that the median non-dimensional

step width is terrain dependent (Fig. 4b) and increased on uneven II versus flat ground by

0.004 ± 0.001 ($p = 0.03$). Step width variability, i.e. the interquartile range of step widths

within a trial, is also terrain dependent ($p = 0.05$, Fig. 4c) and greater on uneven II versus

level ground by 0.005 ± 0.002 ($p = 0.04$). For the mean subject, median step width increased

by 4 ± 1 mm and the step width variability (IQR) increased by 6 ± 2 mm.

Energetics

Despite the lack of guided foot placement on level ground and terrain-dependent increases in step width statistics and leg retraction rate, the approximately 5% increase in metabolic power consumption on the uneven terrain compared to flat we measured was not statistically significant. The statistical significance of the ANOVA, $p = 0.08$ (Fig. 4d), was just above our threshold of $\alpha = 0.05$. Our findings agree on the estimated increase of around 5% with running experiments on step-like terrain. [9] However, unlike our statistical results, Voloshina and Ferris [9] report statistical significance ($p < 0.05$).

Discussion

We find the surprising result that the runners do not use visual information about unevenness to guide their footsteps. Instead, the fore-aft collisions that they experience seem almost decoupled from the horizontal speed with which their foot lands on the ground. Using a model-based analyses of the data, we propose that low joint stiffness was probably the means to maintain low fore-aft impulses, which is known to weaken instabilities associated with the risk of falling by tumbling [19]. Taken together, these results suggest that runners rely on their body's passive mechanical response for remaining stable on uneven terrain. But that does not mean that sensory feedback is not used. We found changes in step width kinematics on the uneven terrain versus flat that were of similar magnitude to previous measurements comparing running on step-like terrain to level ground [9]. These suggest that subjects possibly combined open-loop strategies with step-to-step feedback-mediated stepping strategies that have been previously proposed [15, 28].

Fore-aft impulses have not been previously examined in the context of stability. A previous theoretical analysis hypothesized that reducing tangential collisions and maintaining low fore-aft impulses reduces the risk of falling by tumbling in the sagittal-plane [19]. Our data are consistent with this model. We find that only $6 \pm 1\%$ of the forward momentum was lost in stance although the forward foot speed at landing varied by nearly 50%. This reduction in variability is surprising because, all else held the same, speed and impulse are expected to be linearly related. This suggests that the fore-aft impulse is tightly regulated by other means. By examining the role of leg joint compliance using a model-based analysis of the data, we found that the measured fore-aft impulses were partly consistent with an idealized extreme of zero stiffness in the joints at the point of landing. However, joint stiffness in a real runner cannot be

too small because it is needed to withstand the torques for weight support and propulsion. Thus, we propose that the low variability in fore-aft impulses arises from active regulation of joint stiffness, but a causal relationship between the two remains to be established using methods such as leg EMG measurements [9].

Previous studies based on SLIP models cannot be compared with our results because SLIP models are energy conserving and unaffected by slope variations. However, previous experimental data that have been analyzed using SLIP models to infer leg forces and injury risk point to other benefits of decoupling fore-aft collisions from the foot speed. As we show, the runners appear to not be careful about where precisely they step and could thus encounter occasional sudden drops or step-ups on the terrain. So, being able to vary foot speed and leg retraction rates without affecting stability may allow the runner to maintain consistent leg forces and reduce discomfort or injury risk when sudden or large-obstacles are encountered [14, 26]. But caution is warranted in comparing our measurements with these past studies because of key differences in the nature of the terrain. As we previously noted, running over natural undulating terrain have not been studied previously and earlier work used step-like terrain. Furthermore, the peak-to-peak height variation of our terrain was less than 6% of the leg length, but previous studies used much larger step-like obstacles of 10% leg length or more. For example, we see no change in the variability of the leg landing angle between flat and uneven terrain trials (supplementary Table S1), which is expected if leg landing angle responded to variations in terrain height [14, 26]. So large step-like obstacles induce different swing-leg control strategies compared with undulating terrain with smaller height variations.

Variability in step-to-step kinematics were largely consistent with previous studies on step-like terrain with some notable differences. Studies of running birds hypothesize that crouched postures could aid stability on uneven terrain [18, 29], as do human-subject data on step-like terrain [9]. We find a slight decrease in the virtual leg length at touchdown on the most uneven terrain compared to flat, but the difference was only around 1% of the leg length (supplementary Table S1), whose effect on stability would be negligible. Human-subject experiments on step-like terrain report changes in step width and step length variability of 27% and 26%, respectively, and no changes to mean step length or step width between flat and step-like terrain [9]. Like those studies, we find increases in step width variability of 24% on uneven terrain compared to flat, and additionally find changes in median step width (13%) but not in step length variability (Fig. 4b, supplementary Table S1). The increase in median step width that

we measure could be due to the added stability challenges of running on terrain with slope variations in addition to height variations. Further experiments on terrain with similar height statistics but different slope statistics would be required to test this hypothesis.

Unlike studies on step-like terrain [9], we do not find a significant increase in metabolic power consumption on uneven terrain versus flat ground. Caution is needed in interpreting statistical significance when the p-values are at the cusp of significance. Further studies are needed to explain this variance of results between step-like versus undulating terrain, but it may indicate greater trial-to-trial variance on natural uneven terrain. Nevertheless, the magnitude of the estimated difference in metabolic energy consumption, of around 5%, is quite minor in our study as in previous work.

We find no evidence that subjects used visual information from the terrain geometry to plan footsteps despite predicted advantages to stability [19] and evidence from walking studies that highlight the role of vision in guiding step placement on natural, uneven terrain [5]. We speculate that foot placement strategies are used for obstacle avoidance [30] on more complex terrain while our terrain were designed to be undulating and obstacle-free. Our data thus suggests that terrain-guided foot placement strategies are not required for stability on gently undulating terrain but leaves open the possibility that there is a skill-learning component to such foot placement strategies which we could not measure since our volunteers were not experienced trail runners. Further experiments with runners of varying skill levels would be required to directly test this hypothesis.

The absence of terrain-guided foot placement in our experiment could also be the outcome of the need to reduce metabolic energy consumption. Aiming to land on flatter regions of the terrain would probably increase step length and step width variability as shown by the Markov chain model. These are known to increase metabolic energy consumption [31, 32]. The additional stability gains from the foot placement strategy may be marginal and not commensurate with the unfavorable increase in metabolic energy consumption. In this regime, foot placement could be dominated by step-to-step feedback control for stability as found in level treadmill experiments [15]. Experiments with runners on terrain with a wider range of unevenness properties would be required to investigate this hypothetical trade-off between stability and energy consumption.

Conclusions

Footsteps were not directed towards flatter regions of the terrain despite predicted benefits to stability. This suggests that the measured variability in step placement might arise from passive dynamics or step-to-step feedback control, as found in earlier studies on flat and step-like terrain. Instead we find evidence for a previously uncharacterized control strategy, where the destabilizing effects of careless stepping may be partly mitigated by the stabilizing influence of low tangential collisions coupled with the bodys mechanical response. This combination of feedback and body mechanics helps limit the reliance on visual guidance of footsteps. Importantly, the limited need for visual attention may explain how running hunters can track subtle footprints and hunt prey on uneven terrain without falling.

1 Methods

1.1 Protocol and experimental measurements

We conducted overground running experiments with 9 subjects (8 men, 1 woman; age 23–45 years, body mass 66.1 ± 8.5 kg, leg length 0.89 ± 0.04 m, reported as mean $\pm$ SD). All subjects were able-bodied, ran approximately 30 km per week, and had run at least one half-marathon or marathon within the previous year. Experiments were conducted at the National Centre for Biological Sciences, Bangalore, India with informed consent from the volunteers, and IRB approval.

Subjects ran back-and-forth on three 24 m long and 0.6 m wide tracks (Fig. 5a). In addition to a flat track, we used two custom-made uneven tracks, *uneven I* and *uneven II*, which had increasing unevenness. Uneven I and uneven II had peak-to-valley height differences (amplitude) of 18 ± 6 mm and 28 ± 11 mm (mean $\pm$ SD), respectively, and peak-to-peak horizontal separation (wavelength) of 102 ± 45 mm and 108 ± 52 mm, respectively (Fig. 5b,c,d). We recorded kinematics using an 8-camera motion capture system (Vicon Inc., Oxford, UK) at 300 frames per second and measured the ground reaction forces at 600 Hz using two force plates (AMTI Inc., model BP600900) embedded beneath the center of the track. Breath-by-breath respirometry was also recorded by a mobile gas analyser (Oxycon Mobile™, CareFusion Inc.).

A single trial consisted of a 3 minute period of standing when the resting metabolic rate was recorded followed by subjects running back-and-forth on the track for 8–10 minutes. Each subject ran on all three terrain with the order of presentation of the terrain types randomized.

305 We controlled the running speed using a moving light array in 24 m long LED strips laid on

306 either side of the track (Fig. 5a). Subjects were instructed to stay within the bounds of a 3 m

307 illuminated segment of the LED strip that travelled at 3 m/s. Running speed fluctuated within

308 a trial, however mean speed as well as speed variability were consistent across terrain types

309 (Table S1). Subjects were provided with standardized, commercially available running shoes.

Fig. 5. Details of the experiment design. a, Schematic of the running track, camera placement, force plate positions and the LED strip with a 3 m illuminated section. **b**, The terrain was designed so that the range of its height distribution h was comparable to ankle height $h_{\mathrm{pp}} \sim h_{\mathrm{f}}$ and peak-to-peak distances λ (along the length of the track) were comparable to foot length $\lambda \sim l_f$. **c**, Histograms of the mean subtracted heights h of the uneven terrain. **d**, Histograms of the peak-to-peak separation λ of the uneven terrain.

1.1.1 Uneven terrain

Terrain unevenness was heuristically specified so that peak-to-valley height variations were com-

parable to ankle height, and peak-to-peak horizontal distances were comparable to foot length

(Fig. 5b). Larger terrain height variations with similar (or smaller) peak-to-peak horizontal dis-

tances may elicit obstacle avoidance strategies which are not the subject of this paper. Smaller

peak-to-valley heights (say, comparable to the height of the heel pad) and smaller peak-to-peak

horizontal distances will likely be smoothed out by foot and sole compliance [33], whereas peak-

to-peak horizontal distances that are longer than a step length may make the slope variation

trivial.

The uneven terrain were constructed by Mars Adventures Inc. (Bangalore, India) by laying

fibre glass over heuristically created contours. Epoxy was used to harden the fibre glass sheets

into a stiff shell which was coated with a slurry of sand and epoxy to create a surface that

texturally resembles weathered rock. The terrain was then digitized using a dense arrangement

of reflective markers that were recorded by the motion capture system.

1.1.2 Kinematics

Foot kinematics were recorded using fiducial markers that were fixed to the shoes over the cal-

caneus, second distal metatarsal head, and below the lateral malleolus. Markers were attached

to the hip, over the left and right lateral superior iliac spine, and the left and right posterior

superior iliac spine. The mean position of the hip markers was used to estimate the center of

mass location.

Stance was defined as when the heel marker's forward velocity was minimized and its height

was within $15\,\mathrm{mm}$ of the marker's height during standing. The threshold of $15\,\mathrm{mm}$ was chosen

to account for terrain height variations so that stance may be detected even when the heel lands

on a local peak of the uneven terrain.

The distance d_{step} covered by the center of mass between consecutive touchdown events and

the time t_{step} between these events define the center of mass speed $v = d_{\mathrm{step}}/t_{\mathrm{step}}$. Leg angle at

touchdown was defined as the angle between the vertical and the line formed by joining the heel

marker to the center of mass. Virtual leg length at touchdown is defined as the distance between

the heel marker and the center of mass. Foot length l_f is defined as the average distance in the

horizontal plane between the toe and heel marker, across all subjects. Meander away from a

straight trajectory is defined as $(d - d_0)/d_0$, where d is the distance traversed by the center of

mass in the horizontal plane during a single run across the length of the track, while d_0 is the

length of the straight-line fit to the center of mass trajectory. The center of mass trajectory

during stance was fitted with a regression line in the horizontal plane and twice the distance of

nearest approach of the foot from this line is defined as the step width. This definition allows

for the runner's center of mass trajectory to meander while preserving a definition of step width

that is consistent with those previously used [32, 34]. Foot velocity/center of mass velocity at

landing were calculated by fitting a cubic polynomial to the heel marker trajectory/center of

mass trajectory in a $100\,\mathrm{ms}$ window before touchdown, and calculating the time derivative of the

fitted polynomial at the moment just prior to touchdown. Leg retraction rate ω is determined

using $\omega = v_f / ||\vec{l}||$, where v_f is the component of the foot's relative velocity with respect to the center of mass that is perpendicular to the virtual leg vector $\vec{l}$ (vector joining heel to center of mass).

Step width, step length and virtual leg length at touchdown are normalized by the subject's leg length, defined as the distance between the greater trochanter and lateral malleolus.

1.1.3   Kinetics

Force plate data were low-pass filtered using an 8th order, zero-phase, Butterworth filter with a cut-off frequency of 270 Hz. Touchdown on the force plates was defined by a threshold for the vertical force of four standard deviations above the mean unloaded baseline reading.

The forward collision impulse was reported as the decelerating portion of the fore-aft impulse J_y^* normalized by the aerial phase forward momentum (mv_y), where

$$J_y^* = \max_t \left| \int_0^t F_y(\tau) \, d\tau \right| \tag{1}$$

and F_y is the fore-aft component of the ground reaction force.

1.1.4   Energetics

Net metabolic rate is defined as the resting metabolic power consumption subtracted from the power consumption during running and normalized by the runner's mass. Metabolic power consumption is determined using measurements of the rate of O_2 consumption and CO_2 consumption using formulae from Brockway [35]. For running, this is calculated after discarding the first 3 minutes of the run to eliminate the effect of transients. The resting metabolic power consumption is calculated after discarding the first minute of the standing period of the trial. Data from each trial was visually inspected to ensure that the rate of O_2 consumption and CO_2 production had reached a steady state, seen as a plateau in the data trace.

1.2   Foot stepping analysis

1.2.1   Directed foot placement scheme

A Markov chain Monte Carlo model finds stepping locations with the lowest terrain unevenness subject to constraints of matching experimentally measured stepping kinematics. Starting from an initial position (x_i, y_i), the model finds the next stepping location (x_{i+1}, y_{i+1}) in the following

stages: *open-loop step*, *minimization step*, and a *noise process* given by,

open-loop step: $\hat{x}_{i+1} = x_i + (-1)^i s_w, \ \hat{y}_{i+1} = y_i + (-1)^j s_l.$ (2)

minimization: $(x'_{i+1}, y'_{i+1}) = \arg\min_{(x,y)} t(x,y),$ (3)

$$x \in [\hat{x}_{i+1} - \sigma_{sw}, \hat{x}_{i+1} + \sigma_{sw}],$$

$$y \in [\hat{y}_{i+1} - \sigma_{sl}, \hat{y}_{i+1} + \sigma_{sl}].$$

noise process: $x_{i+1} = x'_{i+1} + \eta_x, \ y_{i+1} = y'_{i+1} + \eta_y,$ (4)

where $\eta_x \sim v_M(1, 0, \sigma_{sw}), \ \eta_y \sim v_M(1, 0, \sigma_{sl}).$

In the open-loop stage, the model takes a step forward and sideways dictated by mean step

length s_l and mean step width s_w, respectively. The exponent j is either 0 or 1 and keeps track

of the direction of travel. The function $t(x, y)$ evaluates the interquartile range of heights of a

heel-sized patch centered around position (x, y). In the minimization step, the model conducts

a bounded search about $(\hat{x}_{i+1}, \hat{y}_{i+1})$ for the location that minimizes $t(x, y)$. The search region

is defined by the standard deviations of the measured step width σ_{sw} and step length σ_{sl}. To

simulate sensorimotor noise, the location of this minimum (x'_{i+1}, y'_{i+1}) is perturbed by random

variables η_x, η_y. The random variables are drawn from von Mises distributions with $\kappa = 1$,

centered about zero, and scaled so that the base of support for the distributions are $2\sigma_{sw}$ and

$2\sigma_{sl}$, respectively.

At the ends of the track, the x position of the runner is reset so that the runner is at the

center of the track, and the direction of travel is reversed (j value is toggled). We simulate

for 100,000 steps to ensure that reported terrain statistics at footstep locations as well as step

length and step width converge, i.e. errors between simulations in these parameters are less than

1% of their mean value.

1.2.2 Quantifying foot placement patterns

We define a foot placement index to estimate the probability that the runner's foot lands within

a foot-sized patch of the track. To calculate this index, we first divide the terrain into a grid

of 0.5 foot lengths × 1.0 foot lengths cells, with the longer side of the cell along the length of

the track (Fig. 6a). We count the number of footsteps $f_{i,j}$ in each cell $c_{i,j}$, where i indexes the

position of the cell along the length of the track and j indexes the position of cell transverse to

the track. We also define step length-sized neighborhoods that contain cell $c_{i,j}$ which are one

Fig. 6. Foot placement analysis. **a**, Red circles denote footstep locations (392 footsteps) in the 'x − y' plane for a representative trial on uneven II. The grid spacing is 190 mm along the length of the track and 95 mm along its width. Step length s_0 is shown for reference. T is the length of the capture volume and W is the width of the track. **b**, The probability of landing on a foot-sized region of the track is quantified by the foot placement index equation (5) shown as a heatmap with the colour bar at the top left.

step-length long and as wide as the track. Each such neighborhood has a cumulative footstep count S_i that depends on the longitudinal location i of the cell. The average across all such step length-sized neighborhoods that contain cell $c_{i,j}$ is S. This average S is used to normalize each $f_{i,j}$ to yield the foot placement index $p_{i,j}$ according to,

$$p_{i,j} = \frac{f_{i,j}}{S}. \tag{5}$$

The index $p_{i,j}$ measures the fraction of times a foot lands in cell $c_{i,j}$ compared to all other cells that are within a step length distance of it (Fig. 6b). If runners were perfectly periodic with no variation in footstep location from one run over the terrain to the next, $p_{i,j} = 1$ for cells on which subjects stepped and $p_{i,j} = 0$ otherwise. If, however, stepping location was the result of a uniform random process, $p_{i,j}$ would be a constant for every cell of the terrain.

Heatmaps of the foot placement index $p_{i,j}$ show that runners primarily run down the center of the track with a few preferred stepping locations (hot spots in the heatmap in supplementary Fig. S4). In certain heatmaps, such as subject 06 on uneven I, the runner appears to be

running diagonally (supplementary Fig. S4). This is due to a misalignment between the axes of

the motion capture reference frame and the track. We also report the total number of footsteps

recorded for each trial in supplementary Table S3.

To probe foot placement strategies we determine whether the foot placement index $p_{i,j}$

correlates with the median height or the interquartile range of heights within the cell $c_{i,j}$ (sup-

plementary Fig. S5). We test this hypothesis through the use of a statistical model described

in section 1.4.2.

1.3 Collision model

We model the leg in the sagittal plane as three rods; thigh, foot and shank, connected by hinge

joints that are either infinitely compliant or rigid. A fourth rod representing the torso sits on

top of the thigh. The rods are assumed to have a uniform mass distribution. Their masses and

lengths are expressed as fractions of the measured body mass and leg length using the ratios

found by Dempster [36]. The collision is assumed to be instantaneous and inelastic, with a

point-contact between the leg and the ground. The instantaneous collision assumption implies

that the ground reaction force dominates the collision, thus simplifying the model by ignoring

gravitational forces. Models with instantaneous and inelastic collisions are widely used to model

stance dynamics for walking [37, 38] and running [19, 39]. We use experimental data on center of

mass velocity and leg retraction rate just prior to landing along with the leg angle at touchdown

to compute a predicted collisional impulse. Because all our runner's were heel-strikers, we use

foot-strike index $s = 0.15$ for the collision calculations [24]. The ratio of the collisional impulse

to the measured whole body momentum just prior to landing is calculated for the model at the

two joint stiffness extremes and compared with experimental measurements of the normalized

fore-aft impulse.

Notation: Notation used in this section is as follows. Scalars are denoted by italic symbols

(e.g. I for the moment of inertia), vectors by bold, italic symbols ($\vec{v}$ for velocity), and points

or landmarks in capitalized non-italic symbols (such as center of mass G in Fig. 7a). Vectors

associated with a point, such as the velocity of center of mass G are written as $\vec{v}_{\mathrm{G}}$, with the

upper-case alphabet in the subscript specifying the point in the plane. Moment of inertia

variables are subscripted with '/A' representing the moment of inertia computed about point

A, such as $I_{/\mathrm{G}}$ representing the moment of inertia about the center of mass G. Position vectors

are denoted by $\vec{r}_{\mathrm{A/B}}$ which denotes the vector from point A to point B. Variables just before

$_{450}$ the collision with the terrain are denoted by the superscript '-', and just after the collision by

$_{451}$ the superscript '+'. Equations with variables that have no superscript are true at all instances

$_{452}$ in time.

Fig. 7. Model for estimating fore-aft collision impulses from kinematic data. **a**, A four link model of the foot (A-B), shank (B-C), thigh (C-D), and torso (D-N) moving with center of mass velocity $\vec{v}_{\mathrm{G}}^{-}$ and angular velocity $\vec{\Omega}^{-}$ collides with the ground at angle θ. G represents the center of mass. Leg length and body mass obtained from data and scaled according to Dempster [36] to obtain segment lengths and masses. Free-body diagrams show all non-zero external impulses: **b,** collisional impulse **J** acting at O, and panels **c, d, e,** show reaction impulses $\mathbf{R}_1$, $\mathbf{R}_2$, and $\mathbf{R}_3$ acting at B, C, and D respectively.

$_{453}$ **Rigid Joints:** Consider the L-shaped bar (Fig. 7a) falling with velocity $\vec{v}_{\mathrm{G}}^{-} = v_y^{-}\hat{\jmath} + v_z^{-}\hat{k}$ and

$_{454}$ rotational velocity $\vec{\Omega}^{-} = \omega^{-}\hat{\imath}$. Upon contact with the ground, the point O on the foot instantly

$_{455}$ comes to rest and the center of mass velocity undergoes an abrupt change, $\vec{v}_{\mathrm{G}}^{+} = v_y^{+}\hat{\jmath} + v_z^{+}\hat{k}$, $\vec{\Omega}^{+} =$

$_{456}$ $\omega^{+}\hat{\imath}$. Due to the instantaneous collision assumption, finite forces like the gravitational force do

$_{457}$ not contribute to the collisional impulse and hence the ground reaction force acting at point O

$_{458}$ contributes the only non-zero external impulse $\vec{J}$ on the body (Fig. 7b). The velocity of the

$_{459}$ leg and torso after the collision is obtained using angular momentum balance about the contact

$_{460}$ point and using the kinematic relation for rolling motion about O. These are written as,

$$M_b \vec{r}_{\mathrm{G/O}} \times \vec{v}_{\mathrm{G}}^{-} + I_{/\mathrm{G}}\vec{\Omega}^{-} = M_b \vec{r}_{\mathrm{G/O}} \times \vec{v}_{\mathrm{G}}^{+} + I_{/\mathrm{G}}\vec{\Omega}^{+}, \tag{6a}$$

$$\vec{v}_{\mathrm{G}} = \vec{v}_{\mathrm{O}} + \vec{\Omega} \times \vec{r}_{\mathrm{G/O}}, \tag{6b}$$

$$\text{where } \vec{v}_{\mathrm{O}}^{+} = 0. \tag{6c}$$

In the above equations, $M_b = M + M_t + M_s + m_f$ is the total mass of the runner. We solve for ω^+ in equation (6) and obtain the post-collision center of mass velocity $\vec{v}_{\text{G}}^+$ using equation 6b. From this, the collision impulse $\vec{J}$ and the normalized fore-aft collisional impulse $|J_y^*|/J_b$ are calculated using,

$$\vec{J} = M_b(\vec{v}_{\text{G}}^+ - \vec{v}_{\text{G}}^-), \tag{7a}$$

$$J_y^* = \vec{J} \cdot \hat{j}, \tag{7b}$$

$$\text{and } J_b = M_b(\vec{v}_{\text{G}}^- \cdot \hat{j}). \tag{7c}$$

Compliant joints: If the L-bar has compliant joints, then the post-collision velocities for each segment may vary. Therefore, we write additional angular momentum balance equations for each segment to solve for the post-collision state. Since the only non-zero external impulse acting on the shank, thigh, and torso segments is the reaction impulse $\vec{R}_1$ acting at B (Fig. 7c), the only non-zero external impulse on the thigh and torso portion of the leg is the reaction impulse $\vec{R}_2$ acting at C (Fig. 7d), and the only non-zero external impulse acting on the torso portion of the leg is the reaction impulse $\vec{R}_3$ acting at D (Fig. 7e), we write angular momentum balance equations for the entire body and these three segments as,

$$
\begin{aligned}
M_b \vec{r}_{\text{G/O}} \times v_{\text{G}}^- + I_{\text{/G}}\vec{\Omega}^- = {} & m_f \vec{r}_{\text{E/O}} \times \vec{v}_{\text{E}}^+ + I_{\text{/E}}\vec{\Omega}_{\text{E}}^+ + \\
& M_s \vec{r}_{\text{F/O}} \times \vec{v}_{\text{F}}^+ + I_{\text{/F}}\vec{\Omega}_{\text{F}}^+ + \\
& M_t \vec{r}_{\text{K/O}} \times \vec{v}_{\text{K}}^+ + I_{\text{/K}}\vec{\Omega}_{\text{K}}^+ + \\
& M \vec{r}_{\text{H/O}} \times \vec{v}_{\text{H}}^+ + I_{\text{/H}}\vec{\Omega}_{\text{H}}^+,
\end{aligned}
\tag{8a}
$$

$$
\begin{aligned}
M_s \vec{r}_{\text{F/B}} \times \vec{v}_{\text{F}}^- + M_t \vec{r}_{\text{K/B}} \times \vec{v}_{\text{K}}^- + & \\
M \vec{r}_{\text{H/B}} \times \vec{v}_{\text{H}}^- + (I_{\text{/F}} + I_{\text{/K}} + I_{\text{H}})\vec{\Omega}^- = {} & M_s \vec{r}_{\text{F/B}} \times \vec{v}_{\text{F}}^+ + I_{\text{/F}}\vec{\Omega}_{\text{F}}^+ + \\
& M_t \vec{r}_{\text{K/B}} \times \vec{v}_{\text{K}}^+ + I_{\text{/K}}\vec{\Omega}_{\text{K}}^+ + \\
& M \vec{r}_{\text{H/B}} \times \vec{v}_{\text{H}}^+ + I_{\text{/H}}\vec{\Omega}_{\text{H}}^+,
\end{aligned}
\tag{8b}
$$

$$
\begin{aligned}
M_t \vec{r}_{\text{K/C}} \times \vec{v}_{\text{K}}^- + M \vec{r}_{\text{H/C}} \times \vec{v}_{\text{H}}^- + & \\
(I_{\text{/K}} + I_{\text{/H}})\vec{\Omega}^- = {} & M_t \vec{r}_{\text{K/C}} \times \vec{v}_{\text{K}}^+ + I_{\text{/K}}\vec{\Omega}_{\text{K}}^+ + \\
& M \vec{r}_{\text{H/C}} \times \vec{v}_{\text{H}}^+ + I_{\text{/H}}\vec{\Omega}_{\text{H}}^+,
\end{aligned}
\tag{8c}
$$

$$
M \vec{r}_{H/D} \times \vec{v}_{\text{H}}^- + I_{\text{/H}}\vec{\Omega}^- = M \vec{r}_{H/D} \times \vec{v}_{\text{H}}^+ + I_{\text{/H}}\vec{\Omega}_{\text{H}}^+
\tag{8d}
$$

where $I_{/\mathrm{E}}, I_{/\mathrm{F}}, I_{/\mathrm{K}}, I_{/\mathrm{H}}$ are moments of inertia of the foot, shank, thigh, and torso segments, respectively about their centers. The linear and angular velocities of the foot $(\vec{v}_\mathrm{E}, \vec{\Omega})$, shank $(\vec{v}_\mathrm{F}, \vec{\Omega}_\mathrm{F})$, thigh $(\vec{v}_\mathrm{K}, \vec{\Omega}_\mathrm{K})$, and torso $(\vec{v}_\mathrm{H}, \vec{\Omega}_\mathrm{H})$ are related to the velocity of the contact point O as,

$$\vec{v}_\mathrm{E} = \vec{v}_\mathrm{O} + \vec{\Omega}_\mathrm{E} \times \vec{r}_{\mathrm{E/O}}, \tag{9a}$$

$$\vec{v}_\mathrm{F} = \vec{v}_\mathrm{O} + \vec{\Omega}_\mathrm{E} \times \vec{r}_{\mathrm{B/O}} + \vec{\Omega}_\mathrm{F} \times \vec{r}_{\mathrm{F/B}}, \tag{9b}$$

$$\vec{v}_\mathrm{K} = \vec{v}_\mathrm{O} + \vec{\Omega}_\mathrm{E} \times \vec{r}_{\mathrm{B/O}} + \vec{\Omega}_\mathrm{F} \times \vec{r}_{\mathrm{C/B}} + \vec{\Omega}_\mathrm{K} \times \vec{r}_{\mathrm{K/C}}, \tag{9c}$$

$$\vec{v}_\mathrm{H} = \vec{v}_\mathrm{O} + \vec{\Omega}_\mathrm{E} \times \vec{r}_{\mathrm{B/O}} + \vec{\Omega}_\mathrm{F} \times \vec{r}_{\mathrm{C/B}} + \vec{\Omega}_\mathrm{K} \times \vec{r}_{\mathrm{D/C}} + \vec{\Omega}_\mathrm{H} \times \vec{r}_{\mathrm{H/D}}, \tag{9d}$$

$$\text{where } \vec{v}_\mathrm{O}^- = \vec{v}_\mathrm{G}^- + \vec{\Omega}^- \times \vec{r}_{\mathrm{O/G}}, \tag{9e}$$

$$\text{and } \vec{v}_\mathrm{O}^+ = 0. \tag{9f}$$

Simultaneously solving equations (8)-(9) yields the post-collision velocities for each segment of the L-bar. From these, we calculate the normalized fore-aft collision impulse for the compliant model using equation (7).

1.4 Statistical methods

1.4.1 Sample size

Sample size could refer to the number of subjects or the number of foot steps that were used in the analyses. The number of subjects recruited was informed by typical participant numbers that were used in similar past studies [9, 15, 20]. There is an additional consideration for sufficiency of sample numbers for the foot placement analysis. The steps should densely sample the approximately 10 m long central region of the track, where the motion capture system was recording from. The 5237 recorded steps (2511 on uneven I, 2726 on uneven II) are sufficient to densely sample the measurement region assuming a heel-sized patch for each step.

1.4.2 Statistical analysis and reporting

A measure of central tendency and a measure of variability of the distributions of step width, step length, center of mass speed, forward foot speed at landing, fore-aft impulse, virtual leg length at touchdown, leg angle at touchdown, net metabolic rate, and meander are reported for each trial. For step width measures, the distribution of step widths within a trial deviated from normality and hence we report the median and the interquartile range of the distribution

for each trial instead of the mean and standard deviation, as is reported for all other variables (supplementary Fig. S1).

We use three different linear mixed models to determine (a) whether gait variables described above (and in supplementary Table S1) vary with terrain type, (b) whether leg angle at touchdown and decelerating fore-aft impulses covary with forward foot speed at touchdown, and (c) whether the foot placement index $p_{i,j}$ (equation (5)) correlates with the median height or the interquartile range of heights within the terrain region at landing. The statistical models are run using the `lmerTest` package in R [40]. We use a linear mixed-model fit by restricted maximum likelihood t-tests with Satterthwaite approximations to degrees of freedom. An ANOVA on the first model tests for the effect of the terrain factor, an ANCOVA on the second model tests for the effect of the terrain factor and the covariate forward foot speed, and an ANCOVA on the third model tests whether the probability of landing in a terrain patch $p_{i,j}$ significantly covaries with the height or unevenness of that terrain patch. Post-hoc pairwise comparisons, where relevant, are performed using the `emmeans` package in RStudio with p-values adjusted according to Tukey's method.

A measure of central tendency or variability within a trial is the dependent variable y for the first linear mixed model. There are 27 observations for the dependent variable y corresponding to each trial (9 subjects running on 3 terrain). Terrain is the fixed factor and subjects are random factors in the model given by,

$$y_{ij} = (\beta_0 + \mu_j) + \beta_i \text{terrain}_i + \epsilon_{ij}, \tag{10}$$

where $i = 1, 2$ and $j = 1 \ldots 9$. The intercept β_0 (value of y on flat terrain) and parameters β_i for uneven I and uneven II are estimated for this model. The random factor variables μ_j are assumed to be normally distributed about zero and account for inter-subject variability of the intercept. The model residuals are ϵ_{ij} which are also assumed to be normally distributed about zero. Detailed statistics for these tests are reported in supplementary Table S1.

The second linear mixed model uses stepwise data where each step is grouped by subject and terrain type. Each of the 1086 steps in this dataset contains a value for subject number, terrain type, touchdown leg angle, decelerating fore-aft impulse, and forward foot speed at touchdown.

The linear model for the dependent variable y (touchdown leg angle or fore-aft impulse) is,

$$y_{ij} = (\beta_0 + \mu_{1j}) + \beta_i \text{terrain}_i + (\beta_f + \mu_{2j} + \nu_i)\text{footspeed} + \epsilon_{ij} \tag{11}$$

where $i = 1, 2$ and $j = 1 \ldots 9$. Like in equation (10), the model estimates the intercept β_0, i.e. the value of y on flat terrain when foot speed $= 0$, β_i for terrain factor, and the slope β_f for the dependence of y on forward foot speed at touchdown. The variable μ_{1j} account for inter-subject variability of the intercept, and the variables μ_{2j} and ν_i account for inter-subject and terrain-specific variability of the slope β_f, respectively. The residuals ϵ_{ij} are assumed to be normally distributed. We report detailed statistics for this model in supplementary Table S2.

Using a dataset of 5237 steps from all subjects on uneven I and uneven II, we extract landing probabilities for 1628 terrain patches (as detailed in section 1.2.2). To test whether runners aimed for terrain regions with low unevenness, we use a linear mixed model of the form,

$$y_{kl} = (\mu_{1l} + \nu_{1k}) + (\mu_{2l} + \nu_{1k})\text{terr} + \epsilon_{kl} \tag{12}$$

where $k = 1, 2$ for the two uneven terrain and $l = 1 \rightarrow 9$ for the 9 subjects. The dependent variable y is the probability of landing in a foot-sized cell $p_{i,j}$ and the independent variable 'terr' refers to the median terrain height of the cell or the interquartile range of heights within the cell. The variables μ_{1l} accounts for subject-specific variability in the terrain-specific intercept ν_{1k}. The variables μ_{2l} accounts for subject-specific variability in the terrain-specific slope ν_{2k}. ANCOVAs on the model for both independent variables (the median terrain height and the interquartile range of heights within the cell) are summarized in Table 1.

Data availability statement: All data points are plotted in either the main text or the electronic supplementary material. Raw data are available on the Dryad repository associated with this paper.

Author Contributions: MV conceived the study. ND conducted the experiment. ND and MV performed the data analysis and wrote the paper.

Acknowledgements: Human Frontier Science Program and Wellcome Trust-DBT Alliance for funding.

Author Declaration: That authors declare that they have no conflict of interest.

References

[1] Carrier, D. R. The energetic paradox of human running and hominid evolution. *Current Anthropology* **25** (1984).

[2] Bramble, D. M. & Lieberman, D. E. Endurance running and the evolution of homo. *Nature* **432**, 345–352 (2004).

[3] Lee, D. N. & Lishman, R. Visual control of locomotion. *Scandinavian Journal of Psychology* **18**, 224–230 (1977).

[4] Warren Jr, W. H., Young, D. S. & Lee, D. N. Visual control of step length during running over irregular terrain. *Journal of Experimental Psychology: Human Perception and Performance* **12**, 259 (1986).

[5] Matthis, J. S., Yates, J. L. & Hayhoe, M. M. Gaze and the control of foot placement when walking in natural terrain. *Curr Biol* **28**, 1224–1233.e5 (2018).

[6] Thomas, N. D., Gardiner, J. D., Crompton, R. H. & Lawson, R. Keep your head down: Maintaining gait stability in challenging conditions. *Human Movement Science* **73**, 102676 (2020).

[7] Pontzer, H. Economy and endurance in human evolution. *Current Biology* **27**, R613–R621 (2017).

[8] Daley, M. A., Usherwood, J. R., Felix, G. & Biewener, A. A. Running over rough terrain: guinea fowl maintain dynamic stability despite a large unexpected change in substrate height. *Journal of Experimental Biology* **209**, 171–187 (2006).

[9] Voloshina, A. S. & Ferris, D. P. Biomechanics and energetics of running on uneven terrain. *Journal of Experimental Biology* **218**, 711–719 (2015).

[10] Müller, R., Häufle, D. F. B. & Blickhan, R. Preparing the leg for ground contact in running: the contribution of feed-forward and visual feedback. *Journal of Experimental Biology* **218**, 451–457 (2015).

[11] Müller, R., Birn-Jeffery, A. & Blum, Y. Human and avian running on uneven ground: a model-based comparison. *Journal of The Royal Society Interface* **13**, 20160529 (2016).

[12] Heim, S., Millard, M., Le Mouel, C. & Badri-Spröwitz, A. A little damping goes a long way: a simulation study of how damping influences task-level stability in running. *Biology Letters* **16**, 20200467 (2020).

[13] Seyfarth, A., Geyer, H., Günther, M. & Blickhan, R. A movement criterion for running. *Journal of biomechanics* **35**, 649–655 (2002).

[14] Birn-Jeffery, A. V. *et al.* Don't break a leg: running birds from quail to ostrich prioritise leg safety and economy on uneven terrain. *Journal of Experimental Biology* **217**, 3786–3796 (2014).

[15] Seethapathi, N. & Srinivasan, M. Step-to-step variations in human running reveal how humans run without falling. *eLife* **8**, e38371 (2019).

[16] Karssen, J. D., Haberland, M., Wisse, M. & Kim, S. The effects of swing-leg retraction on running performance: analysis, simulation, and experiment. *Robotica* **33**, 2137–2155 (2015).

[17] Mahaki, M., Bruijn, S. & Van Dieën, J. The effect of external lateral stabilization on the use of foot placement to control mediolateral stability in walking and running. *PeerJ* **7:e7939** (2019).

[18] Birn-Jeffery, A. V. & Daley, M. A. Birds achieve high robustness in uneven terrain through active control of landing conditions. *Journal of Experimental Biology* **215**, 2117–2127 (2012).

[19] Dhawale, N., Mandre, S. & Venkadesan, M. Dynamics and stability of running on rough terrains. *Royal Society Open Science* **6**, 181729 (2019).

[20] Donelan, J. M., Shipman, D. W., Kram, R. & Kuo, A. D. Mechanical and metabolic requirements for active lateral stabilization in human walking. *Journal of biomechanics* **37**, 827–835 (2004).

[21] Blum, Y., Lipfert, S., Rummel, J. & Seyfarth, A. Swing leg control in human running. *Bioinspiration & biomimetics* **5**, 026006 (2010).

[22] Arellano, C. J. & Kram, R. The energetic cost of maintaining lateral balance during human running. *Journal of Applied Physiology* **112**, 427–434 (2012).

[23] Alexander, R. & Jayes, A. A dynamic similarity hypothesis for the gaits of quadrupedal mammals. *Journal of zoology* **201**, 135–152 (1983).

[24] Lieberman, D. E. *et al.* Foot strike patterns and collision forces in habitually barefoot versus shod runners. *Nature* **463**, 531 (2010).

[25] Chatterjee, A. & Ruina, A. Two interpretations of rigidity in rigid-body collisions. *Journal of Applied Mechanics* **65**, 894–900 (1998).

[26] Blum, Y. *et al.* Swing-leg trajectory of running guinea fowl suggests task-level priority of force regulation rather than disturbance rejection. *PloS one* **9**, e100399 (2014).

[27] Seyfarth, A., Geyer, H. & Herr, H. Swing-leg retraction: a simple control model for stable running. *Journal of Experimental Biology* **206**, 2547–2555 (2003).

[28] Seipel, J. E. & Holmes, P. Running in three dimensions: Analysis of a point-mass sprung-leg model. *The International Journal of Robotics Research* **24**, 657–674 (2005).

[29] Blum, Y., Birn-Jeffery, A., Daley, M. A. & Seyfarth, A. Does a crouched leg posture enhance running stability and robustness? *Journal of Theoretical Biology* **281**, 97–106 (2011).

[30] Matthis, J. S. & Fajen, B. R. Visual control of foot placement when walking over complex terrain. *Journal of experimental psychology: human perception and performance* **40**, 106 (2014).

[31] Cavanagh, P. R. & Williams, K. R. The effect of stride length variation on oxygen uptake during distance running. *Medicine and science in sports and exercise* **14**, 30–35 (1981).

[32] Arellano, C. J. & Kram, R. The effects of step width and arm swing on energetic cost and lateral balance during running. *Journal of biomechanics* **44**, 1291–1295 (2011).

[33] Venkadesan, M., Mandre, S. & Bandi, M. M. *Bioinspired Legged Locomotion: Models, Concepts, Control and Applications, Chapter 7* (Butterworth-Heinemann, 2017).

[34] Donelan, J. M., Kram, R. & Kuo, A. D. Mechanical and metabolic determinants of the preferred step width in human walking. *Proceedings of the Royal Society of London B: Biological Sciences* **268**, 1985–1992 (2001).

[35] Brockway, J. Derivation of formulae used to calculate energy expenditure in man. *Human nutrition. Clinical nutrition* **41**, 463–471 (1987).

[36] Dempster, W. T. Space requirements of the seated operator, geometrical, kinematic, and mechanical aspects of the body with special reference to the limbs. Tech. Rep., Michigan State Univ East Lansing (1955).

[37] Donelan, J. M., Kram, R. & Kuo, A. D. Mechanical work for step-to-step transitions is a major determinant of the metabolic cost of human walking. *Journal of Experimental Biology* **205**, 3717–3727 (2002).

[38] Ruina, A., Bertram, J. E. & Srinivasan, M. A collisional model of the energetic cost of support work qualitatively explains leg sequencing in walking and galloping, pseudo-elastic leg behavior in running and the walk-to-run transition. *Journal of theoretical biology* **237**, 170–192 (2005).

[39] Srinivasan, M. & Ruina, A. Computer optimization of a minimal biped model discovers walking and running. *Nature* **439**, 72–75 (2006).

[40] Kuznetsova, A., Brockhoff, P. B. & Christensen, R. H. B. lmerTest package: Tests in linear mixed effects models. *Journal of Statistical Software* **82**, 1–26 (2017).

a

gas analyzer

reflective markers

force plate

uneven terrain

moving light array

b

foot length

step length

0.6 m

terrain height (mm)

25
15
5
-5
-15

a

F_z

force (bodyweight)

F_y J_y^*

mv_y

J_y^*

stance time (%)

b

fore-aft impulse: J_y^*/mv_y

flat   uneven I   uneven II

c

— mean stiff model
— mean compliant model
○ measured

fore-aft impulse

forward foot speed / CoM speed

d

◇ stiff model
□ compliant model

predicted fore-aft impulse

measured fore-aft impulse

a forward foot speed — p = 0.002, p = 0.001 comparing flat, uneven I, uneven II

b median step width (%LL) — p = 0.03 comparing flat, uneven I, uneven II

c IQR step width (%LL) — p = 0.04 comparing flat, uneven I, uneven II

d net metabolic rate (W/kg) — flat, uneven I, uneven II

a

3 m

LED strip

0.6 m   Track

force plates

24 m

b

h_f

l_f

$\lambda \gg l_f$
$h_{pp} \sim h_f$

$\lambda \sim l_f$
$h_{pp} \sim h_f$

$\lambda \ll l_f$
$h_{pp} \sim h_f$

λ

h

h_{pp}

c

fraction of terrain patches

0.06

0.04

0.02

-30   -10   10   30

h(mm)

d

fraction of terrain patches

1.0

0.8

0.6

0.4

0.2

uneven I
uneven II

0   100   200   300

λ(mm)

a

s_0

$W = 0.57$ m

$T = 10.07$ m

b

0   0.125   0.25   0.375

$W = 0.57$ m

$T = 10.07$ m

Figure S1. Subject-wise step width statistics. Step width is expressed as percent leg length (LL). Because the data are skewed, we report the median and interquartile range as measures of the central tendency and variability, respectively. Black dots represent medians, boxes show the interquartile range, lines extend to 1.5 times the quartile range, and grey circles represent outliers.

Figure S2. Subject-wise foot placement analysis on uneven I. Histograms of the interquartile range of heights (IQR) at the footstep locations for the directed sampling scheme (blue), each subject from the experiments (red), and the blind sampling scheme (yellow).

Figure S3. Subject-wise foot placement analysis on uneven II. Histograms of the interquartile range of heights (IQR) at the footstep locations for the directed sampling scheme (blue), each subject from the experiments (red), and the blind sampling scheme (yellow).

Figure S4. Subject-wise foot placement patterns. Heatmaps of the foot placement index for all subjects on each terrain. Each cell has an area of 190 mm × 95 mm, with the longer side of the rectangle along the length of the track. Colour bar for the heatmaps in the bottom left of the figure.

Figure S5. Subject-wise foot placement analysis. Foot placement index $p_{i,j}$ plotted against the median height of the terrain cell and the interquartile range of heights within the terrain cell at landing for all recorded steps on uneven I and uneven II.

Figure S6. Detailed results of the collision analysis. Measured $J_y^*/(mv_y)$ (blue circles: flat, red circles: uneven I, green circles: uneven II) and calculated $J_y^*/(mv_y)$ values for the collision model with a compliant leg (dark grey squares) and rigid leg (light gray diamonds) versus relative forward foot speed at landing (forward foot speed/centre of mass speed) for each step recorded on all terrain types (total 1081 steps). Solid lines are regression fits to the model. The intercept and slope of the fitted line for the compliant jointed model are 0.0252 ± 0.004 and 0.0203 ± 0.010, respectively ($R^2 = 0.57, p < 0.0001$), and the intercept and slope of the fitted line for the stiff jointed model are 0.120 ± 0.002 and 0.056 ± 0.005, respectively ($R^2 = 0.29, p < 0.0001$)

Table S1. Kinematic variables on different terrain types reported as mean $\pm$ SD, except for meander values which are reported as median $\pm$ interquartile range. For each variable, we show details of the ANOVAs performed on the linear model (from main text equation (10)), i.e. the F-value and p-value for the terrain factor. The denominator degrees of freedom for all ANOVAs was 16. Post-hoc comparisons when the ANOVAs reached the significance bound of $\alpha = 0.05$ are reported in the main text results section.

variable	flat	uneven I	uneven II	F-value	p-value
net metabolic rate (W/kg)	13.1 ± 0.5	13.7 ± 0.9	13.7 ± 0.8	2.97	0.08
median step width (%LL)	3.9 ± 1.9	4.1 ± 1.5	4.7 ± 2.0	4.53	0.03
IQR step width (% LL)	3.9 ± 1.4	4.3 ± 0.9	5.0 ± 1.2	3.65	0.05
mean step width (%LL)	4.2 ± 1.7	4.7 ± 1.6	5.2 ± 1.7	8.69	0.003
S.D. step width (% LL)	2.8 ± 0.8	3.4 ± 0.6	3.6 ± 0.6	5.54	0.01
mean step length (%LL)	128 ± 6	126 ± 9	125 ± 9	1.07	0.37
S.D. step length (%LL)	6 ± 1	7 ± 4	6 ± 1	0.64	0.54
mean meander ($\times 10^{-4}$)	3.21 ± 2.59	3.97 ± 1.65	4.88 ± 4.62	1.48	0.25
S.D. meander ($\times 10^{-4}$)	0.67 ± 0.53	1.33 ± 1.40	1.27 ± 2.78	1.58	0.23
mean fwd. foot speed (froude num.)	0.53 ± 0.17	0.36 ± 0.10	0.37 ± 0.12	13.08	0.0004
S.D. fwd. foot speed (froude num.)	0.17 ± 0.05	0.14 ± 0.05	0.18 ± 0.07	1.48	0.26
mean CoM speed (m/s)	3.24 ± 0.07	3.21 ± 0.07	3.18 ± 0.09	2.32	0.13
S.D. CoM speed (m/s)	0.11 ± 0.03	0.13 ± 0.04	0.12 ± 0.03	2.00	0.17
mean touchdown leg length (%LL)	120 ± 5	119 ± 4	119 ± 4	4.28	0.03
S.D. touchdown leg length (%LL)	1.1 ± 0.7	0.9 ± 0.3	1.3 ± 1.2	1.32	0.29
mean touchdown leg angle (rad)	0.20 ± 0.02	0.20 ± 0.02	0.21 ± 0.02	3.90	0.04
S.D. touchdown leg angle (rad)	0.03 ± 0.02	0.02 ± 0.003	0.03 ± 0.02	2.10	0.15

Table S2. Details of the ANCOVAs performed on the linear model (from main text equation (11)) showing the denominator degrees of freedom, F-value and p-value for the fixed terrain factor, and the estimated slopes β_f for the fixed forward foot speed effect.

dependent variable	factor	DenDF	F-value	p-value	β_f
touchdown leg angle	terrain	193	1.48	0.23	–
	fwd. foot speed	38	115.83	< 0.0001	0.07
fore-aft impulse	terrain	79	1.45	0.24	-
	fwd. foot speed	78	12.83	0.001	0.01

Table S3. Footstep counts for each subject on all terrain.

subject	flat	uneven I	uneven II
1	363	321	448
2	228	78	473
3	473	131	436
4	373	471	519
5	366	557	109
6	224	160	327
7	218	398	442
8	503	489	479
9	477	390	392