1 Selective attention and decision-making have separable neural bases in

2 space and time

Authors: Denise Moerel[1,2], Anina N. Rich[1,2,3,*], & Alexandra Woolgar[1,2,4,*]

[*] Equal contribution

1. School of Psychological Sciences, Macquarie University, Sydney, Australia

2. Perception in Action Research Centre, Macquarie University, Sydney, Australia

3. Macquarie University Performance and Expertise Research Centre, Sydney, Australia

4. MRC Cognition and Brain Sciences Unit, University of Cambridge, Cambridge, United

Kingdom

ABSTRACT

Attention and decision-making processes are fundamental to cognition. However, they are
usually experimentally confounded, making it difficult to link neural observations to specific
processes. Here we separated the effects of selective attention from the effects of decision-
making on human brain activity, using a two-stage task where the attended stimulus and
decision were orthogonal and separated in time. Multivariate pattern analyses of multimodal
neuroimaging data revealed the dynamics of perceptual and decision-related information
coding through time (magnetoencephalography (MEG)), space (functional Magnetic
Resonance Imaging (fMRI)), and their combination (MEG-fMRI fusion). Our MEG results
showed an effect of attention before decision-making could begin, and fMRI results showed
an attention effect in early visual and frontoparietal regions. Model-based MEG-fMRI fusion
suggested that attention boosted stimulus information in frontoparietal and early visual regions
before decision-making was possible. Together, our results suggest that attention affects
neural stimulus representations in frontoparietal regions independent of decision-making.

1. INTRODUCTION

Selective attention is a mechanism that prioritises relevant information from amongst competing sensory input. With clear behavioural benefits to attending to particular locations in space (Pestilli & Carrasco, 2005; Posner, 1980) or visual features (Sàenz et al., 2003; White & Carrasco, 2011), there is strong evidence that attention affects perception (Carrasco, 2011). However, in cognitive neuroscience experiments, attended information is also commonly the information that the participant makes a decision about, confounding the processes of selecting and maintaining relevant stimulus information with decision-making processes. In this study, we separate the effects of attention on the neural processing of information from the effects of decision-making and investigate the spatiotemporal correlates of each process separately.

According to the adaptive coding hypothesis (Duncan, 2001), single cells in frontoparietal cortex flexibly adapt their response to code different information as needed for the task, providing a potential source of bias for more selective brain regions (Desimone & Duncan, 1995). In humans, a network of frontoparietal regions, which we will refer to as the 'Multiple Demand' (MD) regions (Duncan, 2010; Duncan et al., 2020; Duncan & Owen, 2000), responds with a profile consistent with adaptive coding. Functional Magnetic Resonance Imaging (fMRI) studies in human participants show that the MD regions respond to a wide range of cognitively demanding tasks (Assem et al., 2020; Dosenbach et al., 2006; Duncan & Owen, 2000; Fedorenko et al., 2013).

More specific evidence for an adaptive response in MD regions comes from fMRI studies using multivariate pattern analyses (MVPA). These studies show that the MD regions code for a range of task-relevant information in different contexts (Woolgar et al., 2016). In addition, several studies have found stronger coding in the MD cortex for cued (i.e., attended, task-relevant) objects (Woolgar, Williams, et al., 2015) or features (Jackson et al., 2016; Jackson & Woolgar, 2018) relative to equivalent distractors. In parallel, recent magnetoencephalography (MEG) and electroencephalography (EEG) studies have shown the coding of a cued feature at a cued location is sustained over time, while information coding for distractor information is not sustained (Barnes et al., 2022; Battistoni et al., 2020; Goddard et al., 2022; Grootswagers et al., 2021; Kaiser et al., 2016; Moerel et al., 2022; Noah et al., 2023). What we do not know, however, is to what extent this difference in information coding between cued and distractor stimuli is driven by decision-making processes pertaining to the cued information.

Underscoring the importance of this confound, there is clear evidence that decisions can drive decoding in early visual areas (Löffler et al., 2019; Rens et al., 2017), and frontoparietal

cortex (Löffler et al., 2019), although these studies do not explicitly investigate the role of

attention, and the decision was not driven by visual information. Bode and colleagues (2012)

found perceptual decisions could be decoded from 140-180ms post-stimulus onwards from

pure noise images, slightly earlier than feature-based attention effects (Goddard et al., 2022).

Thus, decisions can be decoded in similar brain areas, with a time-course that could interact

with that of attention effects, further complicating the interpretation of the extant literature.

There is some evidence suggesting that attention effects can occur in the absence of decision-

making (Hon et al., 2006). However, this study did not investigate what information was coded

about the attended and unattended stimuli.

Here, we used MVPA of MEG and fMRI data to address 3 research questions. First, we

used MEG to ask whether attention affects the coding of stimulus information when it is

separated from decision-making processes in time, using a 2-stage task to dissociate the

coding of attended and unattended visual information from decision-related information.

Second, we used fMRI to ask what type of information the MD regions hold. Finally, we used

model-based MEG-fMRI to formally combine the data from the two imaging modalities and

examine the time-course with which the MD regions preferentially coded for cued compared

to distractor information during the first phase of the trial.

2. MATERIALS AND METHODS

2.1. MEG acquisition and analysis

2.1.1. Participants

The first part of this study consisted of a behavioural training session and a MEG session

carried out at Macquarie University (Sydney, Australia). We tested 31 healthy volunteers in

the behavioural training session. Of these, 21 performed well enough to participate in the MEG

session (at least 90% accuracy in the final run of the training session). The MEG data from 1

participant were excluded due to a failure to complete the experiment, resulting in a final MEG

sample of 20 participants (14 female/6 male, 18 righthanded/2 lefthanded, mean age = 25.8

years, SD = 5.1). Participants received $15 AUD for participation in the training session and

$30 AUD for participation in the MEG session. The study was approved by the Macquarie

University Human Research Ethics Committee, and all participants provided informed

consent.

 2.1.2. Stimuli and experimental procedure

 <u>MEG session</u>

Participants were instructed keep fixation at a central bullseye throughout the experiment and
were cued to attend to either blue or orange at the start of each block (32 trials). Figure 1
shows the stimuli and trial procedure. First, approximately equiluminant blue and orange
oriented lines within a circular window were overlaid at fixation for 150ms on a mid-grey
background (Figure 1A). Participants attended to the lines of the cued colour, while ignoring
the lines of the other colour. After a 500ms blank screen, a black comparison line was
presented for 200ms. The task was to determine which way the cued lines had to be rotated
to match the orientation of the comparison line. After the comparison line was presented, there
was a 500ms blank screen, and then the response screen, consisting of arrows showing either
a clockwise or an anti-clockwise rotation, was shown until a response was given. If participants
did not respond within 3 seconds, the next trial started. Participants pressed one of two buttons
to indicate whether the rotation shown on the response screen was correct or incorrect. We
used this response screen to separate the correct response button from the rotation direction
decision, ensuring that rotation direction decoding could not be driven by motor preparation.
The mapping of the buttons to indicate 'correct' or 'incorrect' was counterbalanced across
participants. Participants received feedback on every trial; at the end of each trial, the white
part of the fixation bullseye turned green (when correct) or red (when incorrect) for 250ms to
give feedback on accuracy.

The coloured oriented lines had a circular window of 3 degrees of visual angle (DVA),
a spatial frequency of 2 cycles/degree, were 2 possible colours (blue; RGB = 239, 159, 115
and orange; RGB = 72, 179, 217), and were phase randomised (Figure 1A). The comparison
line had a length of 0.8 DVA and a width of 0.1 DVA. The response mapping arrows were 1.5
DVA, and the central fixation bullseye had a diameter of 0.4 DVA. There were 4 possible
orientations for the cued, distractor, and comparison orientations, divided into 2 pairs: 22.5°
was paired with 112.5°, and 67.5° was paired with 157.5° (Figure 1B). When the cued
orientation was from one pair, the distractor and comparison orientation were always from the
other pair. This ensured that the two overlaid orientations were never the same. The
comparison orientation was always rotated 45° from the cued orientation, either in a clockwise
or an anti-clockwise direction.

A

B

	Cued orientation	Distractor orientation	Rotation direction	Comparison orientation
1	22.5°	67.5°	Clockwise	67.5°
2	22.5°	67.5°	Anti-clockwise	157.5°
3	22.5°	157.5°	Clockwise	67.5°
4	22.5°	157.5°	Anti-clockwise	157.5°
5	112.5°	67.5°	Anti-clockwise	67.5°
6	112.5°	67.5°	Clockwise	157.5°
7	112.5°	157.5°	Anti-clockwise	67.5°
8	112.5°	157.5°	Clockwise	157.5°
9	67.5°	22.5°	Anti-clockwise	22.5°
10	67.5°	22.5°	Clockwise	112.5°
11	67.5°	112.5°	Anti-clockwise	22.5°
12	67.5°	112.5°	Clockwise	112.5°
13	157.5°	22.5°	Clockwise	22.5°
14	157.5°	22.5°	Anti-clockwise	112.5°
15	157.5°	112.5°	Clockwise	22.5°
16	157.5°	112.5°	Anti-clockwise	112.5°

C

Cued & distractor orientation	Comparison orientation			Response screen
150ms	500ms	200ms	500ms	Until response

Figure 1. Stimuli and design. The stimulus, shown in **A**, consisted of oriented blue and orange lines within a circular window. Participants attended to the lines of one colour, while ignoring the lines of the other colour. **B** shows the 16 possible trial types, determined by a combination of cued orientation, distractor orientation, and rotation direction. The comparison orientation was not used in the analysis but is shown for completeness. The cued orientation, distractor orientation, and rotation direction are orthogonal dimensions in this design, only within the 2 pairs separately (top half and bottom half of the table). Decoding was done within each pair to ensure all of these factors are balanced. **C** shows an example of a trial sequence. Participants were cued to a particular colour for a block of 32 trials. On each trial, the cued and distractor oriented lines were shown for 150ms followed by 500ms delay, and then the comparison orientation was shown for 200ms. After another 500ms delay, the response screen appeared until a response ('correct' vs 'incorrect') was given, or until the 3s timeout. In this trial, for example, if the cued colour was blue, the participant would have to decide whether the blue lines need to rotate clockwise or anti-clockwise to match the comparison orientation. At the response screen, which in this trial shows clockwise, the correct response would be the button indicating 'correct'.

Cued orientation (4) x distractor orientation (2) x rotation direction (2) x response
screen (2) were counterbalanced within each block, and the cue colour was counterbalanced
over blocks. Participants were instructed which colour to attend at the start of each block of
32 trials, and the cue colour switched between blocks. Participants completed 16 experimental
runs, with 2 blocks per run (one block of 32 trials per cue colour). One participant completed
14 instead of 16 experimental runs. In addition to the feedback on every trial, participants
received feedback on their accuracy at the end of each block. The order of the trial types was
randomised within each block. To increase the number of correct trials, any trial on which the
participant made an error was presented again later in the block. This was done a maximum
of two times per block, and only if it was not the last trial in the block. We replaced error trials
with successful retakes in the analysis, thus increasing the number of correct trials available
for the decoding analysis. We did not record eye movements, but to influence decoding
accuracy, eye-movements during the trials would have to systematically vary between the
different conditions within each pair (see Figure 1B). This seems unlikely as all cued and
distractor orientations were presented at fixation with no variance between conditions.
158

<u>Training session</u>
Due to the challenging task, participants completed a separate behavioural training session
before doing the task in the MEG. The training session consisted of 3 parts. First, participants
practiced the rotation task without selection. Only lines of the cued colour were shown, and
the task was slower: the cued stimulus and comparison line were both presented for 500ms
instead of 150ms and 200ms respectively. Next, the selection element was introduced. Both
the cued and the distractor colour lines were shown, with the timing of the task again slowed
as in part 1 of the training. Finally, the task was presented at the same speed as used in the
MEG session: the cued stimulus was shown for 150ms and the comparison line was presented
for 200ms. Feedback was given at the end of each trial by the white part of the fixation bullseye
turning green (correct) or red (incorrect) for 250ms. At the end of each block, participants also
received feedback about their overall accuracy for that block.
Each run within the training session consisted of 2 blocks of 32 trials, one block per
cued colour. The number of runs per training part was adjusted flexibly depending on task
performance. When participants had finished at least 2 runs and achieved an average
accuracy of at least 90% for the previous run, they moved onto the next part of training.
Participants who were able to complete all 3 training steps within an hour-long session were
invited to participate in the MEG session.
177

2.1.3. MEG acquisition

Participants performed the task in a supine position. The MEG signal was continuously sampled at 1000Hz on a whole-head MEG system with 160 axial gradiometers inside a magnetically shielded room (Model PQ1160R-N2, KIT, Kanazawa, Japan). All MEG recordings were obtained at the KIT-Macquarie Brain Research Laboratory, National Imaging Facility, Sydney, Australia. Recordings were filtered online between 0.03Hz and 200Hz. To track head movements during the experiment, participants were fitted with a cap with 5 marker coils. We recorded the head shape of participants using a Polhemus Fastrak digitiser pen (Colchester, USA). The stimuli were projected onto the ceiling of the magnetically shielded room. To correct for delays in stimulus onsets of the projector compared to the triggers, photodiode responses were used to determine the onset of the trial. We adjusted the stimuli to correct for distortions introduced by the projector. The stimuli were presented using the Psychtoolbox extension in MATLAB (Brainard, 1997; Kleiner et al., 2007; Pelli, 1997). Participants used a 2-button response pad to respond on each trial.

2.1.4. Pre-processing

The data were pre-processed using the FieldTrip extension in MATLAB (Oostenveld et al., 2011). The recordings were sliced into 3100ms epochs; from 100ms before the onset of the first stimulus until 3000ms after stimulus onset. The signal was then down sampled to 200Hz. Error trials that had a successful retake were exchanged for the correct retake. To keep the counterbalancing of all conditions intact, we included the few error trials that did not have a successful retake in the analysis (0.33% of trials on average).

2.1.5. Decoding analysis

We used MVPA to determine whether there was information present in the pattern of activation for each timepoint about: 1) the cued orientation; 2) the distractor orientation; and 3) the rotation direction. Comparing the coding of the cued and distractor orientations allowed us to determine whether attended visual information was preferentially coded, while coding of the rotation direction reflected the decision participants had to make about the stimulus. Critically, the cued orientation, distractor orientation, and rotation direction were all orthogonal dimensions, allowing us to investigate the coding of each of these separately.

For each timepoint, we trained a Support Vector Machine (SVM) classifier on the activation across all 160 sensor channels to distinguish the conditions of interest. Classifier performance was determined using leave-one-run-out cross-validation. Data were split into a training dataset, containing the data from 15 runs, and a testing dataset, containing the data

from the left-out run. This was done 16 times, using a different testing run each time. The analysis was repeated for each point in time, resulting in a decoding accuracy over time. We used the CoSMoMVPA toolbox for MATLAB to conduct our MVPA analyses (Oosterhof et al., 2016).

Cued and distractor orientation: To examine whether there was information about the cued orientation, we trained a classifier to distinguish between the 4 possible cued orientations. These 4 orientations were divided into 2 pairs (see Figure 1B); 22.5° was paired with 112.5°, and 67.5° was paired with 157.5°. The classification of orientation was done within each pair separately, and the decoding accuracies were then averaged over pairs. This ensured that the cued orientation was orthogonal to the distractor orientation and comparison orientation. For example, in pair 1, cued orientation 22.5° and 112.5° occurred equally often with each of distractor orientations 67.5° and 157.5° (see Figure 1B). Cued and distractor orientations were also orthogonal to the rotation decision, so that only the orientation of the stimulus, and not the participant's decision about it, could drive the classifier. Because the decoding was done within a pair, theoretical chance level was 50%. The decoding analysis for the distractor orientation was the same, as the possible cued and distractor orientations were identical.

Rotation direction: We used coding of the rotation direction as a measure for coding of the decision participants had to make. To determine whether there was information about the rotation direction, we trained a classifier to distinguish between a clockwise and anti-clockwise rotation. The rotation direction was orthogonal to both the cued and distractor orientation conditions (e.g., a clockwise decision was equally associated with all 4 possible orientations). There were 2 possible rotation directions, giving a theoretical chance level of 50%.

2.1.6. Statistics

We used Bayesian statistics to determine the evidence for the coding of information under the null hypothesis (chance decoding) and the alternative hypothesis (above-chance decoding), for each time-point (Dienes, 2011; Jeffreys, 1998; Kass & Raftery, 1995; Rouder et al., 2009; Wagenmakers, 2007), using the Bayes Factor package in R (Morey & Rouder, 2018). To test whether the decoding accuracy was above chance, we used a half-Cauchy prior for the alternative, centred around $d = 0$, with the default width of 0.707 (Jeffreys, 1998; Rouder et al., 2009; Wetzels et al., 2011). To exclude irrelevant effect sizes, we excluded the $d = 0$ to 0.5 interval from the prior (Morey & Rouder, 2011; Teichmann et al., 2022), and used a point null at $d = 0$. To test whether there was stronger information coding for the cued compared to the distractor orientation, we calculated the difference between decoding accuracies for the

cued and distractor orientation. We used a half-Cauchy prior, centred around 0, with the same width and null interval described above, for the alternative hypothesis to capture directional effects (cued > distractor).

Bayes Factors (BFs) of <1 show evidence for the null hypothesis, while BFs of >1 show evidence for the alternative hypothesis. BFs between 1/3 and 3 are typically interpreted as showing insufficient evidence, BFs < 1/3 or BFs >3 as substantial evidence, and BFs < 1/10 or BFs >10 are interpreted as strong evidence (Wetzels et al., 2011). In this study, we defined the onset of strong evidence for above-chance decoding as the second consecutive timepoint with a BF >10, and the return to baseline decoding as the second consecutive timepoint with a BF<1/10.

2.2. fMRI acquisition and analysis

2.2.1. Participants

The second part of the study consisted of a behavioural training session and an fMRI session carried out at the MRC Cognition and Brain Sciences Unit (Cambridge, UK). 42 healthy volunteers participated in the initial training session. Of these, 27 volunteers performed well enough to participate in the fMRI session (at least 90% accuracy in the final run of the training session). The fMRI data from 3 participants were excluded due to excessive movement, failure to complete the experiment, or low task performance (accuracy < 80% in the fMRI session), resulting in a final fMRI sample of 24 participants (15 female/9 male, 23 righthanded/1 lefthanded, mean age = 27.33 years, SD = 5.53). One of these participants also participated in the MEG experiment and 23 of the participants were new recruits. Participants received £6 for participation in the training session and £20 for participation in the fMRI session, as well as £2.50 - £3 travel costs per session. All participants provided informed consent, and the study was approved by the Cambridge Psychology Research Ethics Committee.

2.2.2. Stimuli and experimental procedure

fMRI session

Participants performed the same task as in the MEG, except for the following 3 changes due to the lower temporal resolution of fMRI. First, the order of consecutive trial types was not fully randomised as it was in the MEG version, but was instead counterbalanced within each run, making sure each combination of cued orientation x distractor orientation x comparison orientation was equally likely to follow each other combination as well as itself. The order of the rotation direction was balanced separately within each run. Secondly, to keep the order of consecutive trial types intact, error trials were not repeated. Thirdly, participants did not

receive trial-wise feedback to avoid feedback of the previous trial influencing the signal of the
next trial. Participants still received feedback about their accuracy at the end of each block.
Participants completed 8 runs, with 4 blocks per run, and 32 trials per block. The total number
of blocks, and the number of trials per block stayed the same as the MEG experiment,
however, the blocks were divided into 8 runs of 4 blocks, instead of 16 runs of 2 blocks. One
participant completed 7 instead of 8 runs.

Training session

The training session was the same as described in the MEG experiment section.

2.2.3. fMRI acquisition

fMRI scans were acquired using a Siemens 3 Tesla Prisma-Fit scanner (Siemens Healthcare,
Erlangen, Germany), with a 32-channel head coil at the MRC Cognition and Brain Sciences
Unit, Cambridge, UK. We used a multi-band T2*-weighted echo planar imaging (EPI)
acquisition sequence with the following parameters: repetition time (TR) = 1208ms; echo time
(TE) = 30ms; flip angle = 67 degrees, field of view = 192 mm, multi-band acceleration factor =
2, no in-plane acceleration, in-plane resolution = 3 x 3 mm, 38 interleaved slices of 3 mm slice
thickness with 10% interslice gap. T1-weighted MPRAGE structural images were acquired at
the start of the session (resolution = 1 x 1 x 1 mm). The stimuli were presented on a NNL LCD
screen (resolution = 1920 x 1080, refresh rate = 60 Hz) using the Psychtoolbox extension in
MATLAB (Brainard, 1997; Kleiner et al., 2007; Pelli, 1997). Participants used a 2-button
response pad to respond on each trial. To get comfortable with performing the task in the MRI
scanner, participants completed 2 practice blocks of the task during the acquisition of the
structural scan at the start of the scanning session. Feedback about accuracy was given at
the end of each of these practice blocks.

2.2.4. Pre-processing and first-level model

The data were pre-processed using SPM 8 (Wellcome Department of Imaging Neuroscience)
in MATLAB. EPI images were converted to NIFTII format, spatially realigned to the first image
and slice-time-corrected (slice timing correction used the routine from SPM12 to allow for
multiband acquisitions). Structural scans were co-registered to the mean EPI image and
normalised to derive the normalisation parameters needed for the definition of the regions of
interest (ROIs).

To obtain activation patterns for the MVPA analysis, we estimated a General Linear
Model (GLM) for each participant. There were 16 regressors per run, reflecting a combination

of 4 cued orientations x 2 distractor orientations x 2 rotation directions (see Figure 1B). Whole

trials were modelled as a single events, lasting from the onset of the first stimulus until the

response was given, to account for trial-to-trial variability in response time (Woolgar et al.,

2014). Regressors were convolved with the hemodynamic response function of SPM8.

2.2.5. Regions of interest

13 frontal and parietal MD ROIs were taken from the parcellated map provided by Fedorenko

et al (2013), which is freely available online at imaging.mrc-

cbu.cam.ac.uk/imaging/MDsystem. The definition of the MD network is activation based, as

the map indexes regions that show a univariate increase in activation with increased task

demands, across a range of tasks. This is an updated definition of the MD system, with a high

degree of overlap with the previous definition, derived from meta-analytic data (Duncan &

Owen, 2000) that we used in previous work (Jackson et al., 2016; Jackson & Woolgar, 2018;

Woolgar, Williams, et al., 2015; Woolgar, Afshar, et al., 2015), and a more recent definition

derived from multimodal imaging (Assem et al., 2020). The ROIs comprised left and right

anterior inferior frontal sulcus (aIFS; center of mass (COM) = ±35 47 19, volume = 5.0 cm^3),

left and right posterior inferior frontal sulcus (pIFS; COM ±40 32 27, 5.7 cm^3), left and right

premotor cortex (PM; COM ±28 –2 56, 9.0 cm^3), left and right inferior frontal junction (IFJ;

COM ±44 4 32, 10.1 cm^3), left and right anterior insula/frontal operculum (AI/FO; COM ±34 19

2, 7.9 cm^3), left and right intraparietal sulcus (IPS; COM ±29 –56 46, 34.0 cm^3), and bilateral

anterior cingulate cortex (ACC; COM 0 15 46, 18.6 cm^3). Early visual cortex was defined as

area BA 17 (center of mass = –13, –81, 3/16, –79, 3, volume = 54 cm^3) from the Brodmann

template provided with MRIcro (Rorden & Brett, 2000). ROIs were deformed into native space

by applying the inverse of the normalisation parameters for each participant.

2.2.6. Decoding analysis

We used the same decoding analysis as described in the MEG experiment but in the MEG

experiment, we used MVPA to determine what information is present in the pattern of

activation for each *point in time*, whereas for the fMRI data, we determine what information is

present in the pattern of activation *for each ROI*. Within each ROI, we trained an SVM classifier

on the betas obtained from the GLM to distinguish the conditions of interest. The classifier

performance was determined by using a leave-one-run-out cross-validation. Decoding

accuracies were then averaged over hemispheres.

 2.2.7. Statistics

To test for an effect of attention, MD region, and the interaction between these factors, we

used a Bayesian analysis of variance (ANOVA) with attention (cued vs. distractor orientation)

and MD region (aIFS, pIFS, PM, IFJ, AI/FO, IPS, and ACC; data collapsed across

hemispheres) as within-subject factors, using the default Jeffries prior of medium width (1/2)

(Rouder et al., 2012). We conducted further Bayesian t-tests using the same parameters

described in the MEG experiment. To determine the contribution of individual MD regions and

V1 to the effect of attention on stimulus coding, we performed Bayesian tests of the difference

between decoding of the cued and distractor orientation per MD ROI and V1. In addition, we

performed Bayesian tests for the decoding of the cued orientation, distractor orientation, and

rotation direction against chance for the mean MD regions, per individual MD region and for

V1. We used the same parameters for these tests as described in the MEG section (2.1.6).

2.3. Model-based MEG-fMRI fusion

To gain insight into the coding of attended information, unattended information, and decision-

related information in both space and time simultaneously, we used model-based MEG-fMRI

fusion (Cichy et al., 2014, 2016; Hebart et al., 2018). This method uses Representational

Dissimilarity Matrices (RDMs) (Kriegeskorte et al., 2006, 2008) to abstract away from the

imaging modality, allowing us to compare the pattern similarity across neuroimaging

modalities. In addition, we can abstract away from the pattern of activation of specific

participants, comparing the representational similarity across different groups. Model-based

MEG-fMRI fusion further allows us to determine the match between the representational

structure for each timepoint (MEG), and each ROI (fMRI), which can be uniquely explained by

a theoretical model (Hebart et al., 2018) (see Figure 6A for an overview of this method). We

used 3 orthogonal models, coding for the *cued orientation*, *distractor orientation*, and *rotation*

direction.

The RDMs consisted of a 16 by 16 matrix comprising each combination of cued

orientation (4) x distractor orientation (2) x rotation direction (2) (see Figure 1B for an overview

of combinations). For each cell in the RDM, we used decoding accuracy as our measure of

dissimilarity, with greater decoding accuracy reflecting greater dissimilarity of activation

patterns (i.e., distinctiveness of patterns between the conditions). Decoding accuracies were

obtained for each cell in the RDM (i.e., pair of trial types) using the same cross-validation

procedure as described above and were z-scored per ROI and timepoint. For the MEG data,

we constructed an RDM at each timepoint. For each cell in the RDM, we obtained decoding

accuracies using a 25ms sliding window centred around each timepoint. For the fMRI data,

we constructed an RDM for the mean MD and V1 ROIs. The mean MD ROI was obtained by

calculating the RDM for each individual MD region and averaging across regions[1]. We did this

separately for each participant, and then averaged the RDMs over participants, resulting in a

single RDM per timepoint for MEG, and per ROI for fMRI. We constructed 3 model RDMs: for

the cued orientation, distractor orientation, and rotation direction (see Figure 6A). The cued

and distractor orientation models coded for: the same orientation (0), a difference of $45°$ (0.5),

or a difference of $90°$ (1); the rotation direction model coded for the same rotation (0) or a

different rotation (1).

We used commonality analysis to estimate the shared variance between 3 RDMs: the

MEG RDM for each point in time, the fMRI RDM for each ROI, and the model RDM. For each

timepoint, ROI, and model, we calculated the difference between two squared semi-partial

correlation coefficients, using Spearman correlation. Both semi-partial correlation coefficients

reflected the proportion of variance shared between MEG and fMRI; one with *all models*

partialled out from the MEG RDM, and the other with *all models except the model of interest*

partialled out from the MEG RDM. By comparing the variance when our model of interest was

included or not, we get a measure of the variance shared between MEG and fMRI that can be

uniquely explained by each model (Hebart et al., 2018). In this way we derive a time-course

of the model fit for each region.

2.3.1. Statistics

Because we averaged the RDMs over participants for both MEG and fMRI, we had a single

RDM for each timepoint for MEG, and a single RDM for each ROI for fMRI. To estimate the

null distribution, we computed 10,000 permutations by shuffling the rows and columns of the

group average MEG RDM and ran model-based MEG-fMRI fusion for each ROI using the

permuted MEG matrices. For each ROI, we then determined a cluster-inducing threshold for

each timepoint by choosing the 95^{th} percentile. We determined the largest maximum cluster

size in the null distribution. We did this over both ROIs to account for multiple comparisons

over our 2 ROIs. We compared the clusters in our fusion data to the maximum cluster size

obtained from the null distribution (equivalent to $p<0.05$, one-tailed, corrected for multiple

comparisons for the two ROIs and all the timepoints).

---

[1] We could instead have calculated the RDM by extracting the data from one large ROI including all MD regions; in practice this gave a similar RDM so was not considered further.

3. RESULTS

3.1. MEG results

3.1.1. Behavioural results for MEG session

Participants performed with high accuracy in the MEG session. The mean accuracy was 94.23% (SD = 3.90) before replacing error trials (see Methods), and 99.67% (SD = 0.56) after replacing error trials where possible, which means very few error trials were included in the analysis (0.33% of trials on average). The mean response time was 667ms (SD = 104ms).

3.1.2. Coding of the cued and distractor orientation over time

To examine the timepoints at which attended visual information was preferentially coded over unattended visual information, we compared the decoding accuracies for the same orientations when presented as the cued or distractor orientation for each point in time. Critically, the coding of the cued and distractor information could not be driven by decision-related information, as this was an orthogonal dimension in the design. The decoding accuracies for the cued and distractor orientations are shown in Figure 2. There was strong evidence for above-chance orientation decoding for the cued orientation starting at 85ms after stimulus onset, which was maintained until after the mean response time. The distractor stimulus orientation could be decoded with a very similar onset to the cued orientation, with strong evidence for above-chance coding from 90ms after stimulus onset. However, unlike the coding of the cued information, coding of the distractor orientation was not sustained over time, dropping back to chance within 420ms after stimulus onset. The difference between coding of the cued and distractor orientations, which reflects the attentional selection and maintenance of task-relevant information, was evident from 215ms after stimulus onset. This effect of attention, with stronger coding of the cued compared to distractor orientation, was maintained until after the mean response time.

Figure 2. Decoding accuracy of the cued and distractor orientation over time. Classifiers were trained to discriminate stimulus orientation when the orientation was either cued (blue) or not (light green). Theoretical chance is 50% decoding accuracy, and shaded areas around the plot lines show the 95% confidence intervals. The grey shaded areas show from left to right: 1) when the stimulus was on the screen (oriented lines in cued and distractor colours; labelled Stimulus), 2) when the comparison line was on the screen (labelled Comparison), and 3) when the response screen was shown (labelled Response screen). The response screen remained on until participants responded (or 3 secs). The vertical grey lines show the mean response time with 95% confidence intervals. Bayes factors are given below the plot on a logarithmic scale for the cued orientation (blue), the distractor orientation (light green) and the difference between the cued and distractor orientation (red). BFs below 1/10 are shown in grey, indicating strong evidence for the null hypothesis. BFs above 10 are shown in the plot colour (blue for the cued orientation, light green for the distractor orientation, and red for the effect of attention), indicating strong evidence for the alternative hypothesis. BF between 1/10

and 10 are shown in white. There was strong evidence for coding of the cued orientation from 85ms after the onset of the stimulus which was maintained until after the response was given. There was strong evidence for coding of the distractor orientation from 90ms after the onset of the stimulus, but this was not sustained over time. There was strong evidence for an effect of attention from 215ms after the onset of the stimulus until after the mean response time.

3.1.3. Coding of the rotation direction over time

To examine the time-course of decision-related information coding, we determined the coding of the rotation direction over time by training a linear classifier to distinguish between clockwise and anti-clockwise rotations. Participants had to actively manipulate the cued orientation in combination with the comparison orientation to determine the rotation. The decoding of the rotation direction over time is shown in Figure 3. We observed above-chance decoding of the rotation direction from 170ms after the onset of the comparison line, 820ms after the onset of the attended and unattended orientations, which was maintained until after the mean response time.

Figure 3. Decoding accuracy of the rotation direction over time. Classifiers were trained to discriminate the rotation direction, which could be clockwise or anti-clockwise. The rotation direction, about which participants had to make a decision, could be decoded from 170ms

479 after the onset of the comparison line (820ms after stimulus onset) and was maintained until
480 after the mean response time. Plotting conventions are as in Figure 2.
481

3.2. fMRI results

3.2.1. Behavioural results for fMRI session

Participants performed the task in the fMRI session with high accuracy (mean accuracy =
94.45%, SD = 4.91). Included participants all had a mean accuracy above 80%. The mean
response time was 658ms (SD = 140ms) from response screen onset.

3.2.2. Coding of the cued and distractor orientation in the MD regions and V1

To examine whether the effect of attention observed in the MEG data pertained to V1 and the
MD regions, we decoded the cued and distractor orientations for these ROIs. We were able
to separate these conditions due to the orthogonal design. The decoding accuracies for the
cued and distractor orientations, averaged across the MD regions and in V1, are shown in
Figure 4A. We used a Bayesian ANOVA with attention (orientation coding of cued vs.
distractor stimuli) and MD region (aIFS, pIFS, PM, IFJ, AI/FO, IPS, and ACC; data collapsed
across hemispheres) as within-subject factors. We found a main effect of attention (BF > 100),
no main effect of region (BF = 0.44), and an interaction between attention and region (BF =
9.60), justifying a further analysis of the effect of attention in individual MD regions (see Figure
4B). There was strong evidence for an effect of attention (cued > distractor coding) in aIFS,
pIFS, PM, IFJ, and IPS, and some evidence for an effect of attention in AI/FO and ACC (see
Figure 4B).

To determine whether the orientation coding for the cued and distractor orientations
was above chance, we performed Bayesian t-tests for the mean MD regions as well as the
individual MD regions. There was strong evidence for above-chance coding for the cued
orientation in the mean MD regions (mean accuracy = 55.62%, BF > 100), while decoding of
the distractor orientation was at chance (mean accuracy = 49.56%, BF < 0.01). There was
above-chance decoding for the cued orientation in all of the MD regions individually. Strong
evidence for chance level decoding for the distractor orientation was found for aIFS, pIFS,
PM, IFJ, AI/FO, and IPS (BF < 0.01). There was evidence for chance decoding for the
distractor orientation in ACC (BF = 0.20, and the 95% confidence intervals for this region
overlapped with chance, consistent with evidence for the null.

We also found an effect of attention in V1 (BF > 100), with stronger coding for the cued
orientations compared to the distractor orientations. V1 coded for the cued orientation (mean
accuracy = 66.34%, BF>100), while when these identical orientations were distractors there

was evidence for chance decoding (mean accuracy = 51.29%, BF = 0.28), and the 95%

confidence intervals overlapped with chance, consistent with evidence for the null.

Figure 4. Decoding accuracy of the cued and distractor orientation (A) averaged across the MD regions and in V1; and (B) in individual MD regions. In both **A** and **B**, classifiers were trained to discriminate stimulus orientation when the orientation was either cued (blue) or not (light green). Theoretical chance is 50%, and error bars indicate 95% confidence intervals. The Bayes factors for the decoding accuracies are shown below the plot in blue (cued orientation) and light green (distractor orientation), and the BFs for the difference (cued>distractor coding) are shown in red. All BFs are shown on a logarithmic scale. BFs > 10 are marked in the plot colour, BFs < 1/10 are marked in grey, and BFs in between this range are marked in white. In all of the MD regions, and in V1, there was strong evidence for coding of the cued orientation, but not for the distractor orientation. There was strong evidence for an effect of attention for most of the MD regions (aIFS, pIFS, PM, IFJ, AI/FO, and IPS) as well as average MD and V1.

3.2.3. Coding of the rotation direction in the MD regions and V1

To examine whether there was information about the rotation direction, which is our indicator of the decision, in the MD regions and V1, we trained a linear classifier to distinguish between a clockwise and anti-clockwise rotation direction. Since error trials were included in the

analysis to maintain the orthogonality of the different features, on a small number of trials (~6%), the decoded rotation direction does not reflect the decision of the participant, but the predominant influence should be the decision. Figure 5A shows the decoding accuracies for the rotation direction in the MD regions and V1. We used Bayesian t-tests to determine the evidence for chance versus above-chance decoding. We observed strong evidence for above-chance coding of rotation direction across the MD regions on average (mean accuracy = 52.43%, BF = 45.89), and in PM and IPS individually (Figure 5B). Although the average decoding accuracy found in V1 was similar to the MD regions, greater variance in V1 was reflected in an inconclusive BF (mean accuracy = 52.67%, BF = 1.85). There was substantial, but not strong, evidence for chance decoding in aIFS, pIFS, and IFJ, and insufficient evidence for rotation direction coding in the other MD regions.

Figure 5. Decoding accuracy of the rotation direction (decision) (A) averaged across the MD regions and in V1 and (B) in individual MD regions. In both **A** and **B**, classifiers were trained to discriminate the rotation direction, which could be clockwise or anti-clockwise. Plotting conventions are as in Figure 4. The rotation direction could be decoded from the MD regions (average, PM and IPS), while there was insufficient information for rotation direction coding in V1.

3.3. Model-based MEG-fMRI fusion results

We used model-based MEG-fMRI fusion to ask whether the MD regions coded attended information *before* a decision was made. The commonality coefficient shown in Figure 6A refers to the part of the variance that is shared between the MEG and fMRI RDMs which can be uniquely explained by our models for the cued orientation, distractor orientation, and rotation direction. In other words, it plots the dynamics with which the MD pattern, observed in fMRI and explained by each of our theoretical models, arises in the MEG data. We also ran the equivalent analysis for V1 (Figure 6C).

3.3.1. Cued orientation

In the MD regions, there was a significant cluster of commonality for the cued orientation from 555ms until 640ms after the onset of the stimulus (Figure 6B). Critically, this cluster occurred *before* the onset of the comparison line, and therefore before participants could make their decision. A second cluster started at 1140ms, 490ms after the onset of the comparison line and was maintained until after the average response time. In V1, cued orientation commonality coefficients were significant from 225ms until 505ms after the onset of the stimulus, and again from 1210ms, 560ms after the onset of the comparison line, until after the mean response time (Figure 6C).

3.3.2. Distractor orientation

There were no significant clusters of commonality for the distractor orientation in the MD region or V1.

3.3.3. Rotation direction

We observed a cluster of significant commonality for the rotation direction, which is an index of the decision participants had to make, in the MD regions starting from 1140ms, 490ms after the onset of the comparison line, which lasted until after the participant responded. V1 showed a similar pattern over time, with a significant rotation direction cluster from 1160ms, 510ms after comparison line onset.

Figure 6. Model-based MEG – fMRI fusion methods (A) and results over time for the MD regions (B) and V1 (C). A gives an overview of the model-based MEG – fMRI fusion method. We used RDMs to abstract away from the imaging modality. Each cell in the RDM corresponds to the dissimilarity between 2 specific trial types. A trial type is a combination of the cued orientation, distractor orientation, and rotation direction. Trial types 1-16 in the RDMs correspond to the 16 trial types listed in Figure 1B. We created an RDM for each region of interest (V1 and mean MD regions) for the fMRI data, for each time-point in the MEG data, and for the 3 models (cued orientation, distractor orientation, and rotation direction). We then determined commonality: the part of the variance that is shared between the MEG RDM for each timepoint and the fMRI RDM for each ROI, that can be uniquely explained by each theoretical model. This results in a time-course of commonality coefficients for each ROI and model. Note that the ROIs are plotted by projecting a 3D region onto the cortical surface. **B** and **C** show the time-course of commonality for the MD regions and V1 respectively. The different lines depict the commonality explained by the model for the cued orientation (blue), the distractor orientation (light green), and the rotation direction (orange). Significant timepoints (equivalent to p<0.05, one-tailed) were obtained with a cluster-corrected randomisation test, corrected for multiple comparisons across ROIs and timepoints, and are shown at the bottom of the plots. Plotting conventions are as in Figure 2 and 3 except that the dots in the bottom of this plot show significant time-points, not Bayes Factors.

4. DISCUSSION

A wealth of fMRI, M/EEG and non-human primate studies have shown preferential coding of cued compared to distractor information (Barnes et al., 2022; Battistoni et al., 2020; Bode & Haynes, 2009; Goddard et al., 2022; Grootswagers et al., 2021; Harel et al., 2014; Jackson et al., 2016; Kaiser et al., 2016; Li et al., 2007; Moerel et al., 2022; Rao et al., 1997; Sigala et al., 2008; Stiers et al., 2010; Stokes et al., 2013; Waskom et al., 2014; Woolgar, Afshar, et al., 2015; Woolgar, Williams, et al., 2015). However, most paradigms manipulate attention by requiring participants to respond to the cued (but not the distractor) stimulus, which means they cannot distinguish between preferential coding of cued information due to attentional selection and maintenance of relevant information, and coding due to decision-making processes performed on the attended information. We used MEG, fMRI, and model-based MEG-fMRI fusion to distinguish between these explanations. Our MEG data showed that attention affects stimulus processing around 215ms after stimulus onset, before participants had the necessary information to make an explicit decision in our task. Then, when the comparison line was presented, the decision about the rotation direction could be decoded approximately 170ms later. Our fMRI data showed the MD regions coded attended visual information, and did so more strongly than distracting visual information, even though the decision made was orthogonal to the stimulus itself. The orthogonal decision representation was also present in the MD system, specifically in PM and IPS. We also found an effect of attention in V1, with stronger coding of the cued compared to distractor orientations, in line with previous studies (Jackson et al., 2016; Jehee et al., 2012; Pratte et al., 2013). Our model-based MEG-fMRI fusion analysis showed evidence for the coding of attended orientation information in the MD regions *before* participants could make a decision. These data are consistent with the interpretation of previous results as effects of attention on the processing of visual stimuli, with a stronger coding of attended compared to unattended visual information in the brain. This could be driven by an enhancement of the attended visual information, a suppression of the unattended visual information, or both.

The finding that the MD regions preferentially code for attended information over unattended information, even when the decision is orthogonal, is in line with the finding of Hon and colleagues (2006), who used univariate analyses to show that the average MD response reflected changes in cued information when no decision was needed, or when the decision was unrelated to the cued information. Our results take the inference beyond simple activation changes and confirm that decision-making processes are not required for the prioritisation of cued over distractor information.

Our results also show that, in addition to coding the attended information, MD regions

also code for decision-related information. The PM and IPS, which are part of the MD network,

held information about the rotation direction, which was the decision participants had to make.

The time-course with which this information emerged, from about 170ms after the onset of the

comparison line, fits well with a previous study which found a perceptual decision on a pure

noise image could be decoded around 140-180ms (Bode et al., 2012). The fast time-course

suggests the coding of rotation direction information could reflect the accumulation of decision-

related information before the participant is able to respond. This is in line with the description

of decision-making as the accumulation of evidence towards one of two decision alternatives

until a decision boundary is reached (Gold & Shadlen, 2007; Heekeren et al., 2008; Ratcliff &

McKoon, 2007). We cannot comment on the exact delay between the onset of decision

information coding and the response, as our task involved a delayed response - participants

could only generate a response (which was again orthogonal to the decision) after the

response screen came on.

In addition to separating the effects of attention and decision-making, our study adds

to the literature by combining neuroimaging techniques, giving us resolution in both space and

time for a single paradigm. Our MEG data show that the effect of attention emerges *before*

participants have all of the information needed to make a decision, while our fMRI data show

that the MD regions code both attended visual information and the decision participants have

to make about the stimulus. Moreover, we formally related the two results using model-based

MEG-fMRI fusion in order to estimate the time-course of response in the MD network and V1

separately. The data suggest that visual information arises first in V1, but that both V1 and the

MD regions code for information about the attended orientation *before* participants can begin

to make a decision. Orthogonal decision-related signals in MD cortex arose only after the

comparison line was presented. The MEG-fMRI fusion method is an exciting step towards

resolving neural processes in both time and space, but is limited in sensitivity since it is only

able to pick up effects that are present in both the MEG data and the fMRI data (see Cichy &

Oliva (2020) for an overview of possible limitations). For instance, although our MEG data

revealed transient coding of unattended information, this was not evident in the fusion results,

presumably because the much slower time resolution of fMRI obscured its detection. This

highlights the utility of considering the data from each neuroimaging technique separately, as

well as together.

Our findings emphasise the adaptable response of the MD regions, in line with the

literature in non-human primates showing the same neural populations can simultaneously

encode multiple task parameters (Aoi et al., 2020; Fusi et al., 2016; Rigotti et al., 2013). For

example, Aoi and colleagues (2020) show that a single neural population in monkey prefrontal
cortex can maintain information about relevant and irrelevant sensory information, as well as
the saccade response, over the course of a trial. Another line of evidence for the flexible
response of the MD regions comes from fMRI studies in humans. These studies show that
multivariate patterns of activity code for a range of information in different tasks (Woolgar et
al., 2016), with single MD voxels re-used to code multiple task features between tasks
(Jackson & Woolgar, 2018). In addition, Woolgar and colleagues (2015) found stronger visual
object coding in the MD regions for cued relative to distractor objects, and Jackson and
colleagues (2016) reported stronger MD coding of cued compared to distractor features of the
same object. Moreover, MD coding of cued information can be selectively impaired by non-
invasive stimulation of the right dorsolateral prefrontal cortex, one of the nodes in the MD
network (Jackson et al., 2021). Our study also provides evidence for a multi-faceted response
of the MD regions, although we cannot determine whether this is driven by the same
population of neurons within those brain areas. The multifaceted MD response observed in
our study, reflecting relevant visual information as well as decisions about this information, is
consistent with the proposal that these regions play a key role in associating different types of
information by integrating information over multiple sources (Duncan, et al., 2020). The MD
system is well placed to achieve this, being widely distributed and strongly interconnected
across the cortex (Assem et al., 2020; Duncan et al., 2020). In addition, our results emphasise
an explicit role of the MD regions in selective attention, with preferential coding of the
information that is task relevant separately from functional decisions.

In summary, our MEG results show that attention affects the representation of visual
stimuli in advance of decision-making processes, while the fMRI results show that the MD
regions code for attended visual information as well as decisions about this information. The
MEG-fMRI fusion results show the spatio-temporal unfolding of these processes, suggesting
that the MD regions represent information about the attended stimulus before participants can
begin to make a decision. These results emphasise a key role for the MD regions in selective
attention and are consistent with the proposal that these regions integrate different types of
information for decision-making. Our multimodal data demonstrate that selective attention and
decision-making have separable bases in neural coding.

5. ACKNOWLEDGEMENTS
This work was supported by the Australian Research Council (ARC) Centre of Excellence in
Cognition and its Disorders (CE110001021), International Research Training Program
Scholarships from Macquarie University awarded to DM, an ARC Discovery Project

(DP170101840) awarded to ANR and AW, and by the Medical Research Council (UK)

intramural funding (SUAG/093/G116768) awarded to AW. The authors acknowledge the

facilities and scientific and technical assistance of the National Imaging Facility, a National

Collaborative Research Infrastructure Strategy (NCRIS) capability, at Macquarie University.

For the purpose of open access, the authors have applied a Creative Commons Attribution

(CC BY) licence to any Author Accepted Manuscript version arising from this submission.

6. REFERENCES

Aoi, M. C., Mante, V., & Pillow, J. W. (2020). Prefrontal cortex exhibits multidimensional

dynamic encoding during decision-making. *Nature Neuroscience*, *23*(11), 1410–

1420. https://doi.org/10.1038/s41593-020-0696-5

Assem, M., Glasser, M. F., Van Essen, D. C., & Duncan, J. (2020). A Domain-General

Cognitive Core Defined in Multimodally Parcellated Human Cortex. *Cerebral Cortex*,

30(8), 4361–4380. https://doi.org/10.1093/cercor/bhaa023

Barnes, L., Goddard, E., & Woolgar, A. (2022). Neural Coding of Visual Objects Rapidly

Reconfigures to Reflect Subtrial Shifts in Attentional Focus. *Journal of Cognitive

Neuroscience*, *34*(5), 806–822. https://doi.org/10.1162/jocn_a_01832

Battistoni, E., Kaiser, D., Hickey, C., & Peelen, M. V. (2020). The time course of spatial

attention during naturalistic visual search. *Cortex*, *122*, 225–234.

https://doi.org/10.1016/j.cortex.2018.11.018

Bode, S., & Haynes, J.-D. (2009). Decoding sequential stages of task preparation in the

human brain. *NeuroImage*, *45*(2), 606–613.

https://doi.org/10.1016/j.neuroimage.2008.11.031

Bode, S., Sewell, D. K., Lilburn, S., Forte, J. D., Smith, P. L., & Stahl, J. (2012). Predicting

Perceptual Decision Biases from Early Brain Activity. *Journal of Neuroscience*,

32(36), 12488–12498. https://doi.org/10.1523/JNEUROSCI.1708-12.2012

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*(4), 433–436.

https://doi.org/10.1163/156856897X00357

Carrasco, M. (2011). Visual attention: The past 25 years. *Vision Research*, *51*(13), 1484–

1525. https://doi.org/10.1016/j.visres.2011.04.012

Cichy, R. M., & Oliva, A. (2020). A M/EEG-fMRI Fusion Primer: Resolving Human Brain

Responses in Space and Time. *Neuron*, S0896627320305183.

https://doi.org/10.1016/j.neuron.2020.07.001

Cichy, R. M., Pantazis, D., & Oliva, A. (2014). Resolving human object recognition in space

and time. *Nature Neuroscience*, *17*(3), 455–462. https://doi.org/10.1038/nn.3635

Cichy, R. M., Pantazis, D., & Oliva, A. (2016). Similarity-Based Fusion of MEG and fMRI

Reveals Spatio-Temporal Dynamics in Human Cortex During Visual Object

Recognition. *Cerebral Cortex*, *26*(8), 3563–3579.

https://doi.org/10.1093/cercor/bhw135

Desimone, R., & Duncan, J. (1995). Neural Mechanisms of Selective Visual Attention.

Annual Review of Neuroscience, *18*(1), 193–222.

https://doi.org/10.1146/annurev.ne.18.030195.001205

Dienes, Z. (2011). Bayesian Versus Orthodox Statistics: Which Side Are You On?

Perspectives on Psychological Science, *6*(3), 274–290.

https://doi.org/10.1177/1745691611406920

Dosenbach, N. U. F., Visscher, K. M., Palmer, E. D., Miezin, F. M., Wenger, K. K., Kang, H.

C., Burgund, E. D., Grimes, A. L., Schlaggar, B. L., & Petersen, S. E. (2006). A Core

System for the Implementation of Task Sets. *Neuron*, *50*(5), 799–812.

https://doi.org/10.1016/j.neuron.2006.04.031

Duncan, J. (2001). An adaptive coding model of neural function in prefrontal cortex. *Nature*

Reviews Neuroscience, *2*(11), 820–829. https://doi.org/10.1038/35097575

Duncan, J. (2010). The multiple-demand (MD) system of the primate brain: Mental programs

for intelligent behaviour. *Trends in Cognitive Sciences*, *14*(4), 172–179.

https://doi.org/10.1016/j.tics.2010.01.004

Duncan, J., Assem, M., & Shashidhara, S. (2020). Integrated Intelligence from Distributed

Brain Activity. *Trends in Cognitive Sciences*, *24*(10), 838–852.

https://doi.org/10.1016/j.tics.2020.06.012

Duncan, J., & Owen, A. M. (2000). Common regions of the human frontal lobe recruited by

diverse cognitive demands. *Trends in Neurosciences*, *23*(10), 475–483.

https://doi.org/10.1016/S0166-2236(00)01633-7

Fedorenko, E., Duncan, J., & Kanwisher, N. (2013). Broad domain generality in focal regions

of frontal and parietal cortex. *Proceedings of the National Academy of Sciences*,

110(41), 16616–16621. https://doi.org/10.1073/pnas.1315235110

Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: High dimensionality for higher

cognition. *Current Opinion in Neurobiology*, *37*, 66–74.

https://doi.org/10.1016/j.conb.2016.01.010

Goddard, E., Carlson, T. A., & Woolgar, A. (2022). Spatial and Feature-selective Attention

Have Distinct, Interacting Effects on Population-level Tuning. *Journal of Cognitive*

Neuroscience, *34*(2), 290–312. https://doi.org/10.1101/530352

Gold, J. I., & Shadlen, M. N. (2007). The Neural Basis of Decision Making. *Annual Review of*
Neuroscience, *30*(1), 535–574.
https://doi.org/10.1146/annurev.neuro.29.051605.113038
Grootswagers, T., Robinson, A. K., Shatek, S. M., & Carlson, T. A. (2021). The neural
dynamics underlying prioritisation of task-relevant information. *Neurons, Behavior,*
Data Analysis, and Theory, 2020.06.25.172643. https://doi.org/10.51628/001c.21174
Harel, A., Kravitz, D. J., & Baker, C. I. (2014). Task context impacts visual object processing
differentially across the cortex. *Proceedings of the National Academy of Sciences*,
111(10), E962–E971. https://doi.org/10.1073/pnas.1312567111
Hebart, M. N., Bankson, B. B., Harel, A., Baker, C. I., & Cichy, R. M. (2018). The
representational dynamics of task and object processing in humans. *Elife*, *7*, e32816.
Heekeren, H. R., Marrett, S., & Ungerleider, L. G. (2008). The neural systems that mediate
human perceptual decision making. *Nature Reviews Neuroscience*, *9*(6), 467–479.
https://doi.org/10.1038/nrn2374
Hon, N., Epstein, R. A., Owen, A. M., & Duncan, J. (2006). Frontoparietal Activity with
Minimal Decision and Control. *Journal of Neuroscience*, *26*(38), 9805–9809.
https://doi.org/10.1523/JNEUROSCI.3165-06.2006
Jackson, J. B., Feredoes, E., Rich, A. N., Lindner, M., & Woolgar, A. (2021). Concurrent
neuroimaging and neurostimulation reveals a causal role for dlPFC in coding of task-
relevant information. *Communications Biology*, *4*(1), 1–16.
https://doi.org/10.1038/s42003-021-02109-x
Jackson, J. B., & Woolgar, A. (2018). Adaptive coding in the human brain: Distinct object
features are encoded by overlapping voxels in frontoparietal cortex. *Cortex*.
https://doi.org/10.1016/j.cortex.2018.07.006
Jackson, J., Rich, A. N., Williams, M. A., & Woolgar, A. (2016). Feature-selective Attention in
Frontoparietal Cortex: Multivoxel Codes Adjust to Prioritize Task-relevant
Information. *Journal of Cognitive Neuroscience*, *29*(2), 310–321.
https://doi.org/10.1162/jocn_a_01039
Jeffreys, H. (1998). *The Theory of Probability*. OUP Oxford.
Jehee, J. F. M., Ling, S., Swisher, J. D., Bergen, R. S. van, & Tong, F. (2012). Perceptual
Learning Selectively Refines Orientation Representations in Early Visual Cortex.
Journal of Neuroscience, *32*(47), 16747–16753.
https://doi.org/10.1523/JNEUROSCI.6112-11.2012
Kaiser, D., Oosterhof, N., & Peelen, M. (2016). The Neural Dynamics of Attentional
Selection in Natural Scenes. *The Journal of Neuroscience : The Official Journal of the*

Society for Neuroscience, *36*, 10522–10528.

https://doi.org/10.1523/JNEUROSCI.1385-16.2016

Kass, R. E., & Raftery, A. E. (1995). Bayes Factors. *Journal of the American Statistical*

Association, *90*(430), 773–795. https://doi.org/10.1080/01621459.1995.10476572

Kleiner, M., Brainard, D., & Pelli, D. (2007). What's new in Psychtoolbox-3? *Perception 36*

ECVP Abstract Supplement.

Kriegeskorte, N., Goebel, R., & Bandettini, P. (2006). Information-based functional brain

mapping. *Proceedings of the National Academy of Sciences*, *103*(10), 3863–3868.

https://doi.org/10.1073/pnas.0600244103

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis—

Connecting the branches of systems neuroscience. *Frontiers in Systems*

Neuroscience, *2*. https://doi.org/10.3389/neuro.06.004.2008

Li, S., Ostwald, D., Giese, M., & Kourtzi, Z. (2007). Flexible Coding for Categorical Decisions

in the Human Brain. *Journal of Neuroscience*, *27*(45), 12321–12330.

https://doi.org/10.1523/JNEUROSCI.3795-07.2007

Löffler, A., Haggard, P., & Bode, S. (2019). Decoding Changes of Mind in Voluntary Action—

Dynamics of Intentional Choice Representations. *Cerebral Cortex*.

https://doi.org/10.1093/cercor/bhz160

Moerel, D., Grootswagers, T., Robinson, A. K., Shatek, S. M., Woolgar, A., Carlson, T. A., &

Rich, A. N. (2022). The time-course of feature-based attention effects dissociated

from temporal expectation and target-related processes. *Scientific Reports*, *12*(1),

6968. https://doi.org/10.1038/s41598-022-10687-x

Morey, R. D., & Rouder, J. N. (2011). Bayes factor approaches for testing interval null

hypotheses. *Psychological Methods*, *16*(4), 406–419.

https://doi.org/10.1037/a0024377

Morey, R. D., & Rouder, J. N. (2018). *BayesFactor: Computation of Bayes Factors for*

Common Designs. https://CRAN.R-project.org/package=BayesFactor

Noah, S., Meyyappan, S., Ding, M., & Mangun, G. R. (2023). Time Courses of Attended and

Ignored Object Representations. *Journal of Cognitive Neuroscience*, *35*(4), 645–658.

https://doi.org/10.1162/jocn_a_01972

Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J.-M. (2011). FieldTrip: Open Source

Software for Advanced Analysis of MEG, EEG, and Invasive Electrophysiological

Data. *Computational Intelligence and Neuroscience*, *2011*, 1–9.

https://doi.org/10.1155/2011/156869

Oosterhof, N. N., Connolly, A. C., & Haxby, J. V. (2016). CoSMoMVPA: Multi-Modal

Multivariate Pattern Analysis of Neuroimaging Data in Matlab/GNU Octave. *Frontiers*

in Neuroinformatics, *10*. https://doi.org/10.3389/fninf.2016.00027

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: Transforming

numbers into movies. *Spatial Vision*, *10*(4), 437–442.

Pestilli, F., & Carrasco, M. (2005). Attention enhances contrast sensitivity at cued and

impairs it at uncued locations. *Vision Research*, *45*(14), 1867–1875.

https://doi.org/10.1016/j.visres.2005.01.019

Posner, M. I. (1980). Orienting of attention. *Quarterly Journal of Experimental Psychology*,

32(1), 3–25. https://doi.org/10.1080/00335558008248231

Pratte, M. S., Ling, S., Swisher, J. D., & Tong, F. (2013). How attention extracts objects from

noise. *Journal of Neurophysiology*, *110*(6), 1346–1356.

https://doi.org/10.1152/jn.00127.2013

Rao, S. C., Rainer, G., & Miller, E. K. (1997). Integration of What and Where in the Primate

Prefrontal Cortex. *Science*, *276*(5313), 821–824.

https://doi.org/10.1126/science.276.5313.821

Ratcliff, R., & McKoon, G. (2007). The Diffusion Decision Model: Theory and Data for Two-

Choice Decision Tasks. *Neural Computation*, *20*(4), 873–922.

https://doi.org/10.1162/neco.2008.12-06-420

Rens, N., Bode, S., Burianová, H., & Cunnington, R. (2017). Proactive Recruitment of

Frontoparietal and Salience Networks for Voluntary Decisions. *Frontiers in Human*

Neuroscience, *11*. https://doi.org/10.3389/fnhum.2017.00610

Rigotti, M., Barak, O., Warden, M. R., Wang, X.-J., Daw, N. D., Miller, E. K., & Fusi, S.

(2013). The importance of mixed selectivity in complex cognitive tasks. *Nature*,

497(7451), Article 7451. https://doi.org/10.1038/nature12160

Rorden, C., & Brett, M. (2000). *Stereotaxic Display of Brain Lesions* [Research article].

Behavioural Neurology. https://doi.org/10.1155/2000/421719

Rouder, J. N., Morey, R. D., Speckman, P. L., & Province, J. M. (2012). Default Bayes

factors for ANOVA designs. *Journal of Mathematical Psychology*, *56*(5), 356–374.

https://doi.org/10.1016/j.jmp.2012.08.001

Rouder, J. N., Speckman, P. L., Sun, D., Morey, R. D., & Iverson, G. (2009). Bayesian t

tests for accepting and rejecting the null hypothesis. *Psychonomic Bulletin & Review*,

16(2), 225–237. https://doi.org/10.3758/PBR.16.2.225

Sàenz, M., Buracâs, G. T., & Boynton, G. M. (2003). Global feature-based attention for
motion and color. *Vision Research*, *43*(6), 629–637. https://doi.org/10.1016/S0042-
6989(02)00595-3

Sigala, N., Kusunoki, M., Nimmo-Smith, I., Gaffan, D., & Duncan, J. (2008). Hierarchical
coding for sequential task events in the monkey prefrontal cortex. *Proceedings of the*
National Academy of Sciences, *105*(33), 11969–11974.
https://doi.org/10.1073/pnas.0802569105

Stiers, P., Mennes, M., & Sunaert, S. (2010). Distributed task coding throughout the multiple
demand network of the human frontal–insular cortex. *NeuroImage*, *52*(1), 252–262.
https://doi.org/10.1016/j.neuroimage.2010.03.078

Stokes, M. G., Kusunoki, M., Sigala, N., Nili, H., Gaffan, D., & Duncan, J. (2013). Dynamic
Coding for Cognitive Control in Prefrontal Cortex. *Neuron*, *78*(2), 364–375.
https://doi.org/10.1016/j.neuron.2013.01.039

Teichmann, L., Moerel, D., Baker, C. I., & Grootswagers, T. (2022). An empirically-driven
guide on using Bayes Factors for M/EEG decoding. *Aperture Neuro*, *1*(8), 1–10.
https://doi.org/10.1101/2021.06.23.449663

Wagenmakers, E.-J. (2007). A practical solution to the pervasive problems ofp values.
Psychonomic Bulletin & Review, *14*(5), 779–804.
https://doi.org/10.3758/BF03194105

Waskom, M. L., Kumaran, D., Gordon, A. M., Rissman, J., & Wagner, A. D. (2014).
Frontoparietal Representations of Task Context Support the Flexible Control of Goal-
Directed Cognition. *Journal of Neuroscience*, *34*(32), 10743–10755.
https://doi.org/10.1523/JNEUROSCI.5282-13.2014

Wetzels, R., Matzke, D., Lee, M. D., Rouder, J. N., Iverson, G. J., & Wagenmakers, E.-J.
(2011). Statistical Evidence in Experimental Psychology: An Empirical Comparison
Using 855 t Tests. *Perspectives on Psychological Science*, *6*(3), 291–298.
https://doi.org/10.1177/1745691611406923

White, A. L., & Carrasco, M. (2011). Feature-based attention involuntarily and
simultaneously improves visual performance across locations. *Journal of Vision*,
11(6), 15–15. https://doi.org/10.1167/11.6.15

Woolgar, A., Afshar, S., Williams, M. A., & Rich, A. N. (2015). Flexible Coding of Task Rules
in Frontoparietal Cortex: An Adaptive System for Flexible Cognitive Control. *Journal*
of Cognitive Neuroscience, *27*(10), 1895–1911.
https://doi.org/10.1162/jocn_a_00827

Woolgar, A., Golland, P., & Bode, S. (2014). Coping with confounds in multivoxel pattern

analysis: What should we do about reaction time differences? A comment on Todd,

Nystrom & Cohen 2013. *NeuroImage*, *98*, 506–512.

https://doi.org/10.1016/j.neuroimage.2014.04.059

Woolgar, A., Jackson, J., & Duncan, J. (2016). Coding of Visual, Auditory, Rule, and

Response Information in the Brain: 10 Years of Multivoxel Pattern Analysis. *Journal*

of Cognitive Neuroscience, *28*(10), 1433–1454.

https://doi.org/10.1162/jocn_a_00981

Woolgar, A., Williams, M. A., & Rich, A. N. (2015). Attention enhances multi-voxel

representation of novel objects in frontal, parietal and visual cortices. *NeuroImage*,

109, 429–437. https://doi.org/10.1016/j.neuroimage.2014.12.083