MinION barcodes: biodiversity discovery and identification by everyone, for everyone

Amrita Srivathsan[1], Leshon Lee[1], Kazutaka Katoh[2,3], Emily Hartop[4,5], Sujatha Narayanan Kutty[1,6], Johnathan Wong[1], Darren Yeo[1], Rudolf Meier[1,7]

[1] Department of Biological Sciences, National University of Singapore, Singapore

[2] Research Institute for Microbial Diseases, Osaka University, Japan

[3] Artificial Intelligence Research Center, AIST, Tokyo, Japan

[4] Zoology Department, Stockholms Universitet, Stockholm, Sweden

[5] Station Linné, Öland, Sweden

[6] Tropical Marine Science Institute, National University of Singapore, Singapore

[7] Museum für Naturkunde, Leibniz Institute for Evolution and Biodiversity Science, Center for Integrative Biodiversity Discovery, Berlin, Germany

Abstract

Background

DNA barcodes are a useful tool for discovering, understanding, and monitoring biodiversity which are critical tasks at a time of rapid biodiversity loss. However, widespread adoption of barcodes requires cost-effective and simple barcoding methods. We here present a workflow that satisfies these conditions. It was developed via "innovation through subtraction" and thus requires minimal lab equipment, can be learned within days, reduces the barcode sequencing cost to <10 cents, and allows fast turnaround from specimen to sequence by using the portable, real-time sequencer MinION.

Results

We describe cost-effective and rapid procedures for barcoding individual specimens with MinION sequencing. We illustrate how tagged amplicons can be obtained and sequenced with the portable, real-time MinION sequencer in many settings (field stations, biodiversity labs, citizen science labs, schools). We also provide amplicon coverage recommendations that are based on several runs of the latest generation of MinION flow cells ("R10.3") which suggest that each run can generate barcodes for >10,000 specimens. Next, we present a novel software, ONTbarcoder, which overcomes the bioinformatics challenges posed by MinION reads. The software is compatible with Windows 10, Macintosh, and Linux, has a graphical user interface (GUI), and can generate thousands of barcodes on a standard laptop within hours based on only two input files (FASTQ, demultiplexing file). We document that MinION barcodes are virtually identical to Sanger and Illumina barcodes for the same specimens (>99.99%) and provide evidence that MinION flow cells and reads have improved rapidly since 2018.

Conclusions

We propose that barcoding with MinION is the way forward for government agencies, universities, museums, and schools because it combines low consumable and capital cost with scalability. Small projects can use the flow cell dongle ("Flongle") while large projects

28   can rely on MinION flow cells that can be stopped and re-used after collecting sufficient data

29   for a given project.

1. Background

DNA sequences have been used for identification and taxonomic purposes for decades [1-3], but for most of this time they have been akin to mobile phones in the 1990s: of limited value due to sparse signal coverage and high cost. Obtaining barcodes was too complicated and expensive despite the development of effective DNA extraction protocols [4], fast Sanger sequencing protocol [5], and the establishment of the Canadian Centre for DNA Barcoding (CCDB), which is the primary sequencing facility for the International Barcode of Life Consortium (iBOL: https://ibol.org/resources/sequencing-facility/). After 15 years and the investment of >200 million USD in facilities and barcoding, ca. 8 million animal barcodes are available for searches in the database "BOLD Systems" of which ca. 6 million sequences can be downloaded as "public data" (April 2021: [6]). Combined with barcodes from NCBI, they are now a valuable resource for the global biodiversity community.

However, the cost of barcodes has remained high (http://ccdb.ca/pricing/) and the most widely used approach to large-scale barcoding still relies on sending specimens from all over the world to the CCDB in Guelph (Canada). For example, >85% of all arthropod barcodes in BOLD Systems were generated by the CCDB with more than >60% of the voucher specimens remaining in the centre (https://www.boldsystems.org/index.php/Taxbrowser_Taxonpage?taxid=20). Unfortunately, this model for barcoding interferes with real-time biodiversity monitoring and specimen accessibility. We therefore here argue that barcoding has to be decentralized. We show that this can be achieved through "innovation through subtraction," which yields simplified and cost-effective solutions for generating barcode amplicons in molecular laboratories with very basic equipment. Combined with the use of MinION sequencers, these simplifications allow for generating barcodes almost anywhere by biologists and citizen scientists alike.

A decentralized model for monitoring the world's biodiversity is necessary given the scale, urgency, and importance of the task at hand. For example, even if there were only 10 million

species of metazoan animals on the planet [7] and a new species was discovered with every

50[th] specimen that is processed, species discovery with barcodes will require the

sequencing of 500 million specimens [8]. Yet, species discovery is only a small part of the

biodiversity challenge in the 21[st] century. Biodiversity loss is now considered by the World

Economic Forum as one of the top three global risks based on likelihood and impact for the

next 10 years [9] and Swiss Re estimates that 20% of all countries face ecosystem collapse

as biodiversity declines [10]. This implies that biodiversity discovery and monitoring will

require in the future completely different scales than in the past. The old approaches thus

need rethinking because all countries will need real-time distributional and abundance

information in order to develop effective conservation strategies and policies. In addition,

they will need information on how species interact with each other and the environment [11].

Barcodes were initially intended as an identification tool for biologists [1]. Thus, most

projects focused on taxa with a large following in biology (e.g., birds, fish, butterflies) [12]

Yet, despite targeting taxa with well-understood diversity, the projects struggled with

barcoding >75% of the described species in these groups [12]. When the pilot barcoding

projects ran out of tissues from identified specimens, they started targeting unidentified

specimens; i.e., DNA barcoding morphed into a technique that was used for biodiversity

discovery ("dark taxa": [12, 13]). This shift towards biodiversity discovery was gradual and

incomplete because the projects used a "hybrid approach" that started with sorting

specimens to "morphospecies" before barcoding one or a few specimens for each

morphospecies/sample (e.g., [14-20]). However, this approach is not ideal for biodiversity

discovery and monitoring because morphospecies sorting is labour-intensive and of

unpredictable quality because it is heavily dependent on the taxonomic expertise of the

sorters [21, 22]. This is why it is preferable to reverse the workflow [23] by barcoding all

specimens first and assessing congruence with morphology afterwards [24, 25]. This

approach has the additional benefit that it yields quantitative data and corroborated species-

level units. However, it requires efficient and low-cost barcoding methods that are also

suitable for biodiverse countries with limited science funding.

Fortunately, such cost-effective barcoding methods are now becoming available. This is

partially due to the replacement of Sanger sequencing with second- and third-generation

sequencing technologies that have lower sequencing costs [23, 26-33]. These changes

mean that the widespread application of the reverse workflow is now feasible for tackling the

species-level diversity of those metazoan clades that are so specimen- and species-rich that

they have been neglected in the past [33, 34]. Many of these clades have high spatial

species turnover, requiring many localities in each country to be sampled and large numbers

of specimens to be processed [32]. Such intensive processing is best achieved close to the

collecting locality to avoid the delays and costs of shipping samples across continents. This

is now feasible because biodiversity discovery can be readily pursued in decentralized

facilities at varied scales. Indeed, accelerated biodiversity discovery is a rare example of a

big science initiative that allows for meaningful engagement of students and citizen

scientists, which can enhance significantly biodiversity education and appreciation [35-38].

This is especially so when stakeholders not only barcode, but also image specimens,

determine species abundances, and map distributions of newly discovered species. All of

which can be based on specimens collected in the citizens' own backyard.

But can such decentralized biodiversity discovery really be effective? Within the last five

years, students and interns in the laboratory of the corresponding author at the National

University of Singapore barcoded >330,000 specimens. After analyzing the first >140,000

barcoded specimens for selected taxa representing different ecological guilds, the alpha and

beta diversity of Singapore's arthropod fauna was analyzed based on ~8,000 putative

species which revealed that some habitats were unexpectedly species-rich and harboured

unique faunas (e.g., mangroves, freshwater swamp: [32, 39]). Barcodes even helped with

the conservation of charismatic taxa when they were used to identify the larval habitats for

more than half of Singapore's damsel- and dragonfly species [40] and facilitated species

interaction research and biodiversity surveys based on eDNA [41, 42]. Biodiversity

appreciation by the public was fostered by featuring newly discovered species and their

species interactions on "Biodiversity of Singapore" (BOS >15,000 species:

https://singapore.biodiversity.online/), dozens of new species have been described, and the

descriptions of another 150 species are being finalized [43-51].

Barcoding metazoan specimens require the successful completion of three steps: (1)

obtaining DNA template, (2) amplifying *COI* via PCR, and (3) sequencing the *COI* amplicon.

Many biologists learn these techniques in university for a range of different genes – from

those that are easy to amplify (short fragments of ribosomal and mitochondrial genes with

well-established primers) to those are difficult (long, single-copy nuclear genes with few

known primers). Fortunately, amplification of short mitochondrial markers like *COI* does not

require the same level of care as nuclear markers. Learning how to barcode efficiently is

hence an exercise of unlearning unnecessary procedures. Note that this unlearning comes

with cost savings which are particularly vital for boosting biodiversity research where it is

most needed: in biodiverse countries with limited science funding. Our manuscript therefore

has a more comprehensive Methods section than most publications, because we do not only

describe which methods we used for our experiments, but also why certain alternative

methods were avoided. In addition, we provide videos that illustrate the techniques

(https://www.youtube.com/channel/UC1WowokomhQJRc71FmsUAcg).

Simplified laboratory techniques for obtaining barcode amplicons are important, but they

need to be complemented with efficient and cost-effective sequencing techniques.

Therefore, we here also test the capabilities of the latest flow cells used in Oxford Nanopore

Technologies (ONT) instruments. They have the advantage of being inexpensive and

yielding data quickly by passing single-stranded DNA through a nanopore and using the

current fluctuations for reconstructing the DNA sequence [52]. ONT's MinION is especially

suitable for decentralized barcoding because it is small and inexpensive. However, its use

for barcoding has been unpopular because of low sequence read accuracy (85% - 95%: [52,

53]). This meant that the data had to be analyzed with complex bioinformatics pipelines that

are not suitable for widespread use.

Recently, three significant changes occurred. Firstly, ONT released a low-cost and capacity

flow cell (Flongle) that only has 126 pores (126 channels) instead of the customary 2048

(512 channels) of a full MinION flow cell. We here test whether Flongle is a promising tool for

small barcoding projects that need quick turnaround times for a few hundred specimens.

Secondly, ONT released a new flow cell chemistry for full flow cells ("R10.3") where the

nanopores have a dual instead of a single reader-head. Dual reading has altered the read

error profile by giving better resolution to homopolymers and improved consensus accuracy

[54, 55]. Lastly, ONT released high accuracy (HAC) basecalling

(https://nanoporetech.com/about-us/news/new-research-algorithms-yield-accuracy-gains-

nanopore-sequencing). All three innovations are here tested using six different amplicon

pools of very different sizes (191 - 9,932 specimens). Overall, we find that the innovations

were very effective at improving read quality and quantity. This meant that we could develop

and release a new bioinformatics software, "ONTbarcoder," which is fast and user-friendly in

that it has a GUI, is compatible with all major operating systems, and does not require the

installation of third-party software.

Results

Performance of new flow cells and high-accuracy basecalling

We used six pools of amplicons to test the new ONT products. The pools contained

amplicons for 191 - 9,932 specimens and were run for 15-49 hours (Table 1). The amplicons

were tagged with a 13-bp index to facilitate demultiplexing reads to specimen specific bins.

Basecalling the fast5 files using Guppy in MinIT under the high accuracy (HAC) model was

still very slow and took 12 days for the largest dataset (*Palaearctic Phoridae (658 bp)* (Table

1). However, it yielded good quality reads that could be demultiplexed at high rates for the

four R10.3 MinION datasets (= 30-49%). The only exception was the *Palaearctic Phoridae*

(313 bp) dataset (15.5%). Flongle datasets showed overall also lower demultiplexing rates

(17-21%).

Table 1. Datasets generated in this study and the results of barcoding using ONTbarcoder at
200X coverage (Consensus by Length) and 100X coverage (Consensus by Similarity).
175

Dataset Name	Flow cell details Run time/Guppy version	Raw reads/reads passing length threshold/reads of suitable length/ demultiplexed	Demultiplexing rate/# QC_compliant barcodes /# Filtered barcodes with 1N/# Filtered barcodes with >1N /# Unreliable barcodes
MinION R10.3 Datasets			
Mixed Diptera (658 bp, N=511)	R10.3: reused flow cell: 71 pores according to QC, but 500+ active during run Runtime: 27.5 hrs Guppy: 4.2.3+f90bd04	3,864,000/3,425,357/3,560,389/1,544,758	43.39%/495/2/5/8 Total success rate= 502/511 (98.2%)
Afrotropical Phoridae (658 bp, N=4,275)	R10.3: new flow cell: QC: 1,101 pores Runtime: 49.5 hrs Guppy: 4.0.11+f1071ce	6,838,903/5,465,164/5,474,306/2,681,029	48.97%/3,722/121/59/247 Total success rate= 3905/4275 (91.3%)
Palaearctic Phoridae (658 bp, N=9,932)	R10.3: new flow cell: QC: 1,239 pores Runtime: 47.5 hrs Guppy: 4.2.3+f90bd04	16,595,984/15,658,174/16,100,505/5,012,489	31.13%/8,026/108/231/780 Total success rate= 8,365/9,932 (84.2%)
Palaearctic Phoridae (313 bp, N=9,929)	R10.3: new flow cell: QC: 1,297 pores Runtime: 37 hrs Guppy: 4.2.3+f90bd04	13,690,869/13,221,764/10,366,455/12,983,260/2,015,135	15.52%/8,705/118/112/899 Total success rate= 8,935/9,929 (90%)
Flongle Datasets			
Mixed Diptera Subsample (658 bp, N=257)	Flongle: new QC: 81 pores Runtime: 24 hrs Guppy: v 4.0.11+f1071ce	294,896/222,189/190,952/33,270	17.42%/185/35/20/9 Total success rate= 240/257 (93.4%)
Chironomidae (313 bp, N=191)	Flongle: new QC: 74 pores Runtime: 15 hrs Guppy: 4.2.3+f90bd04	560,062/525,087/504,621/108,574	21.52%/178/1/2/6 Total success rate= 181/191 (94.8%)

We then investigated barcode accuracy (Figure 1) by directly aligning the MinION barcodes

with Sanger and Illumina barcodes for the same specimens. We find that MinION barcodes

are virtually identical (>99.99% identity, Table 2). We furthermore established that the

number of ambiguous bases ("N") is very low for barcodes obtained with R10.3 (<0.01%).

Indeed, more than 90% of all barcodes are entirely free of ambiguous bases. In comparison,

Flongle barcodes have a slightly higher proportion of ambiguous bases (<0.06%). They are

concentrated in ~20% of all sequences so that 80% of all barcodes again lack Ns. This

means that MinION barcodes well exceed the Consortium for the Barcode of Life (CBOL)

criteria for "barcode" designation with regard to length, accuracy, and ambiguity

(Ratnasingham and Hebert 2013).

Table 2. Quality assessment of barcodes generated by ONTbarcoder at 200X read
coverage (Consensus by Length) and 100X coverage (Consensus by Similarity). The
accuracy of MinION barcodes is compared with the barcodes obtained for the same
specimens using Illumina/Sanger sequencing. Errors are defined as sum of substitution or
indel errors. Denominators are the total number of nucleotides assessed.
193

Dataset	No. of comparison barcodes	No. of barcodes with errors/No. of errors/% identity	# of Ns/%Ns
R10.3: Mixed Diptera: Sanger barcodes available	476	2/10/99.997%	19 (0.006%)
R10.3: Afrotropical Phoridae: Illumina barcodes available*	3316	23/48/99.995%	284 (0.011%)
Flongle-Mixed Diptera Subsample: Sanger barcodes available	231	5/8/99.994%	91 (0.058%)

194
*5 barcodes with very high distances from reference were excluded for R10.3: Afrotropical Phoridae dataset as

they likely represent lab contamination (see Srivathsan, Hartop et al. (2019)

Rarefaction at different read coverage levels reveals that 80-90% of high-quality barcodes

are obtained within a few hours of sequencing. In addition, the number of barcodes

generated by MinION exceeded or was comparable to what could be obtained with Sanger

or Illumina (Figure 1). We also determined the coverage needed for obtaining reliable

barcodes. For this purpose, we plotted the number of barcodes obtained against coverage

(Figure 2). This revealed that the vast majority of specimens yield high-quality barcodes at

coverages between 25x and 50x when R10.3 reads are used. Increasing coverage beyond

50x only leads to modest improvements in quality and few additional barcodes. The

coverage needed for obtaining Flongle barcodes was somewhat higher, but the main

difference between the R9.4 technology of the Flongle flow cell and R10.3 of the MinION

flow cell was that more barcodes retained ambiguous bases even at high coverage for R9.4

data. The differences in read quality between R9.4 and R10.3 became even more obvious

when the read bins for the "Mixed Diptera Subsample" were analyzed based an identical

numbers of R10.3 and R9.4 reads. The barcodes based on Flongle and R10.3 data are

compatible, but the R10.3 barcodes are ambiguity-free while some of the corresponding

Flongle barcodes retain 1-2 ambiguous bases.

Overall, these results imply that 100x raw read coverage is sufficient for obtaining barcodes

with either R10.3 or R9.4 flow cells. Given that most MinION flow cells yield >10 million

reads of an appropriate length, one could, in principle, obtain 100,000 barcodes in one flow

cell. However, this would require that all amplicons are represented by similar numbers of

copies and that all reads could be correctly demultiplexed. In reality, only 30-50% of the

reads can be demultiplexed and the number of reads per amplicon fluctuates widely (Figure

3). Very-low coverage bins tend to yield no barcodes or barcodes of lower quality (errors or

Ns). These low-coverage barcodes can be improved by collecting more data, but this comes

at a high cost and increased risk of a small number of contaminant reads yielding barcodes.

For example, we observed that some "negative" PCR controls yielded low-quality barcodes

for 4 of 106 negatives in the Palaearctic Phoridae (313 bp) and 1 of 105 negatives in the

Palaearctic Phoridae (658 bp) datasets.

To facilitate the planning of barcode projects, we illustrate the trade-offs between barcode

yield, sequencing time, and amount of raw data needed for six amplicon pools (Figure 4:

191-9,932 specimens). These standard curves can be used to roughly estimate the number

of raw reads needed to achieve a specific goal for a barcoding project of a specific size (e.g.,

obtaining 80% of all barcodes for a project with 1000 amplicons). Note that the number of

raw reads is displayed in real-time in MinKNOW so that the run can be terminated when the

target number of reads has been reached. The number of recoverable barcodes in Figure 4

was set to the number of all error-free, filtered barcodes obtained in an analysis of all data.

We would argue that this is a realistic estimate of recoverable barcodes given the saturation

plots in Figure 1 that suggest that most barcodes with significant amounts of data have been

called at 200x coverage. Note, however, that Figure 4 can only provide very rough guidance

on how many reads are needed because, for example, the demultiplexing rates differ

between flow cells and different amplicon pools have very different read abundance

distributions (see Figure 3).

We further compared the barcodes obtained with ONTbarcoder with those obtained via the

recent software NGSpeciesID [56]. NGSpeciesID often provides multiple consensus

barcodes for the same set of reads for a specimen. We here only compare the consensus

barcodes supported by the highest number of reads. When compared to Illumina or Sanger

reference barcodes, the barcodes obtained via ONTbarcoder have fewer errors (Table 3: 25-

118 erroneous barcodes for NGSpeciesID vs 5-28 erroneous barcodes for ONTbarcoder). In

addition, NGSpeciesID also yielded consensus barcodes for negative controls because it

performs no quality control based on length, translation or other criteria. Most of the

corresponding read sets yielded no barcodes with ONTbarcoder due to rigorous quality

checks and low read count filters. For example, NGSpeciesID formed 32 negative

consensus barcodes for Afrotropical Phoridae 658 dataset (demultiplexed by minibar) with

30 being represented by <5 sequences.

255
Table 3. Comparison of barcodes obtained by ONTbarcoder with NGSpeciesID
(green=highest number of correct and lowest number of errors for datasets). NGSpeciesID
was applied once to the demultiplexed reads obtained with ONTbarcoder and once to those
obtained with minibar. Barcode calling was done using all demultiplexed reads as well as
200X subset. ONTbarcoder was run at 200X read coverage (Consensus by Length) and

100X coverage (Consensus by Similarity). The accuracy of MinION barcodes is only
compared to reference barcodes obtained with Illumina/Sanger sequencing. Errors are
defined as sum of substitution and indel errors.

	ONTBarcoder 200X	ONTBarcoder dem[1] + NGSpeciesID All reads	ONTBarcoder dem[1] + NGSpeciesID 200X	minibar + NGSpeciesID All reads	minibar + NGSpeciesID 200X
Mixed Diptera Subsample Flongle					
Identical+compatible[2] (# of reference barcodes)	**226** (240)	72 (241)	73 (241)	121 (239)	122 (239)
Incorrect, (1/2/3/4/5+) errors	**5 (3/1/1/0/0)**	169 (83/60/13/6/7)	168 (88/55/13/7/5)	118 (29/21/8/4/56)	119 (31/20/8/4/56)
# reads demultiplexed/reads of length 658±50	33,270/32,978			19,511/15,935	
Mixed Diptera R10.3					
Identical+compatible[2] (# of reference barcodes)	**473** (475)	173 (478)	353 (478)	418 (478)	453 (478)
Incorrect, with (1/2/3/4/5+) errors	**2 (0/0/1/0/1)**	305 (126/97/48/17/17)	125 (91/24/5/1/4)	60 (45/9/3/0/3)	25 (20/2/0/0/3)
# reads demultiplexed/reads of length 658±50	1,544,768/1,532,408			1,540,751/1,378,910	
Afrotropical Phoridae R10.3					
Identical+compatible[2] (# of reference barcodes)	**3293** (3321)	2832 (3339)	3111 (3341)	3193 (3340)	3245 (3340)
Incorrect, (1/2/3/4/5+) errors	**28 (15/5/0/0/8)**	507 (362/90/19/12/24)	230 (172/31/5/3/19)	147 (90/27/3/1/26)	95 (50/13/12/1/27)
# reads demultiplexed/reads of length 658±50	2,681,029/2,668,933			3,117,597/2,782,367	

264   [1] dem=demultiplexing
265   [2] Identical barcodes match perfectly with references, and there are no ambiguities while
266   compatible barcodes match with reference with at 100% identity but contain ambiguities.
267   NGSpeciesID does not introduce N's in barcodes and thus these two categories were
268   grouped for this comparison.
269

Figure 1. Rapid recovery of accurate MinION barcodes over time (in hours, x-axis) (filtered barcodes: dark green = barcodes passing all 4 QC criteria, light green = one ambiguous base; lighter green = more than 1N, no barcode = white with pattern, 1 mismatch = orange, >1 mismatch = red). The solid black line represents the number of barcodes available for comparison. White dotted line represents the amount of raw reads collected over time, blue represents number of demultiplexed reads over time (plotted against Z-axis)

Coverage

Figure 2. Relationship between barcode quality and coverage. Subsetting the data to 5-200X
coverage shows that there are very minor gains to barcode quality after 25-50X coverage.
(filtered barcodes: dark green = barcodes passing all 4 QC criteria, light green = one
ambiguous base; lighter green = more than 1N, no barcode = white with pattern, 1 mismatch
= orange, >1 mismatch = red).

279 Figure 3. Read bin size distribution for six amplicon pools (color-coding as in Figs 1-2). Due
280 to the very generous coverage for the "Mixed Diptera" dataset, we also use grey to show the
281 bin size distribution after dividing the bin read totals by 5.

Figure 4. Relationship between barcoding success and number of raw reads for six amplicon

pools (191-9932 specimens; barcoding success rates 84-97%). Percentage of barcodes

recovered is relative to the final estimate based on all data.

Discussion

Democratization of Barcoding

Biodiversity research needs new scalable techniques for large-scale species discovery and

monitoring. This task is particularly urgent and challenging for invertebrates that collectively

make up most of the terrestrial animal biomass. We argued earlier that this is likely to be a

task that requires the processing of at least 500 million specimens from all over the world

with many tropical countries with limited research funding requiring much of the biodiversity

discovery work. Pre-sorting these specimens into putative species-level units with DNA

sequences is a promising solution as long as obtaining and analyzing the data are

sufficiently straightforward and cost-effective. We believe that the techniques described in

this manuscript will help with achieving these goals.

We here show that sequencing barcode amplicons with MinION is a particularly attractive

option. Firstly, MinION library preparation can be learned within hours and an automated

library preparation instrument is available and eventually expected to also generate ligation-

based libraries ("VolTRAX"). Secondly, MinION flow cells can accommodate projects of

varying scales. Flongle can be used for amplicon pools with a few hundred products, while

an R10.3 flow cell can accommodate projects with up to 10,000 specimens. The collection of

data on MinION flow cells can be stopped whenever the software controlling the run

("MinKNOW") indicates that a sufficiently high number of reads have been acquired. Flow

cells can then be washed and re-used again although the remaining capacity declines over

time so that we have only re-used flow cells up to four times.

Traditionally, the main obstacles to using MinION for barcoding have been poor read quality

and high cost. Both issues are fading into the past. The quality of MinION reads has

improved to such a degree that the laptop-version of our new software "ONTbarcoder" can

generate thousands of very high quality barcodes within hours. There is also no longer a

need to "polish" reads or to rely on external data or algorithms. The greater ease with which

MinION barcodes can be obtained is due to several factors. Firstly, each flow cell now yields

a much larger numbers of reads. Secondly, R10.3 reads have a different error profile which

allows for reconstructing higher-quality barcodes. Thirdly, high accuracy basecalling has

improved raw read quality and thus demultiplexing rates. Lastly, we can now use parameter

settings for MAFFT that are designed for MinION reads. These changes mean that even

low-coverage bins can yield very accurate barcodes; i.e., both barcode quality and quantity

are greatly improved.

We had previously tested MinION for barcoding in 2018 and 2019 and here re-sequenced

some of the same amplicon pools. This allowed for a precise assessment of the

improvements. In 2018, sequencing the 511 amplicons of the *Mixed Diptera* sample required

one flow cell and we obtained 488 barcodes of which only one lacked ambiguous bases. In

2021, we sequenced on a used flow cell (R10.3) with only ~500 pores, and we obtained 502

barcodes with >98% (496) being free of ambiguous bases. The results obtained for the 2019

amplicon pools were also better. In 2019, one flow cell (R9.4) allowed us to obtain 3,223

barcodes from a pool of amplicons obtained from 4,275 specimens of *Afrotropical Phoridae*.

Resequencing weak amplicons increased the total number of barcodes by approximately

500 to 3,762 [33]. Now, one R10.3 flow cell yielded 3,905 barcodes (+143) for the same

amplicon pool, while retaining an accuracy of >99.99% and reducing the ambiguities from

0.45% to 0.01%. If progress continues at this pace, we predict that MinION will be the default

barcoding tool for most users. This, too, is because all barcoding steps can now be carried

out in one laboratory with a modest set of equipment (see Table 4). With MinION being

readily available, there is no longer the need to outsource sequencing and/or to wait until

enough barcode amplicons have been prepared for an Illumina or PacBio/Sequel flow cell

[57]. This eases biodiversity discovery and allows many biologists, government agencies,

students, and citizen scientists from around the globe to get involved in biodiversity

discovery.

Table 4. Equipment required for MinION barcoding

Required (<500 specimens)	
1	MinION sequencer (preferably Mk1C for basecalling) with Flongle adapter
2	Thermocycler(s)
3	Gel Electrophoresis setup
4	Magnetic Separation Rack

5	Qubit for DNA quantification
6	<u>Standard equipment</u>: Vortex, Mini-centrifuge, pipettes, freezer, fridge
7	Standard laptop or PC
Required (>500 specimens)	
1	Multichannel pipette(s)
Optional but highly desirable	
1	Hula Mixer

This raises the question of how much it costs to sequence a barcode with MinION. There is

no straightforward answer because the cost depends on user targets. For example, a user

who wants to sequence a pool of 5000 barcodes may want an 80% success rate in order to

identify the dominant species in a sample of nuisance midges that occur in mixed-species

swarms [58]. Based on Figure 4, only ca. 1.5 million raw MinION reads would be needed. On

average, MinION flow cells yield >10 million reads and cost USD 475-900 depending on how

many cells are purchased at the same time. Add the library cost of ca. USD 100 and the

overall sequencing cost of the project is USD 180-235. This experiment would be expected

to yield 4000 barcodes for the 5000 amplicons (4-6 cents/barcode). Given the low cost of 1

million MinION reads ($50-90), we predict that most users will opt for sequencing at a

greater depth since this will likely yield several hundred additional barcodes. This will

increase the sequencing cost per barcode, because the first 1.5 million reads already

recovered barcodes for all strong amplicons. Additional reads will predominantly strengthen

read coverage for these amplicons and relatively few reads will be added to the read bins

that were too weak to yield barcodes at low coverage; i.e., there are diminishing returns for

additional sequencing.

Overall, we thus predict that most users will only multiplex 10,000 amplicons in the same

MinION flow cell so that the sequencing cost per specimen would be 0.06-0.10 USD

depending on flow cell cost. Large-scale biodiversity projects can reduce the cost further by

switching to sequencing with PromethION, a larger ONT sequencing instrument that can

accommodate up to 48 flow cells. PromethION flow cells have 6 times the number of pores

for twice the cost so that this switch reduces the sequencing cost by 60% (flow cell capacity:

60,000 barcodes). At the other end of the scale are those users who occasionally need a few

hundred barcodes. They can use Flongle flow cells, which are comparatively expensive

(0.50 USD) because each flow cell costs $70 and requires a library that is prepared with half

the normal reagents (ca. $50).

ONTbarcoder for large-scale species discovery with MinION

We here introduce ONTbarcoder, which runs on a regular laptop using either Windows10,

Linux, or Macintosh OS and has a GUI. ONTbarcoder has been extensively tested (>4000

direct comparisons to Sanger and Illumina barcodes) and is designed to yield thousands of

barcodes rapidly without impairing accuracy even when encountering low-coverage

amplicons. Accuracy is ensured by applying 4 QC criteria related to length and translatability

of the barcode. Speed is maintained through the parallelization of most steps on UNIX

systems (Mac and Linux; parallelization is restricted to demultiplexing in Windows).

ONTbarcoder furthermore allows for updating the parameter file for alignment. This is

advisable because MinION continues to evolve quickly. We expect flow cell capacity to

increase further and basecalling to improve (see [59]). For example, a new basecaller

("*bonito*") developed by ONT has shown promise by improving raw read accuracy

(https://nanoporetech.com/about-us/news/new-research-algorithms-yield-accuracy-gains-

nanopore-sequencing). This basecaller is now also available in MinKNOW and our

preliminary tests (Flongle: *Mixed Diptera Subsample, Chironomidae*; R10.3: *Palaearctic*

Phoridae, 313 bp; bonito version=0.3.6*)* confirm that it yields reads of similar quality as HAC

(unpublished data). We expect these regular changes to ONT software to further improve

the suitability of ONT sequencers for barcoding.

ONTbarcoder evolved from miniBarcoder, which yielded high quality barcodes based on four

different tests covering >8000 barcodes [31, 33, 54, 60], but had two drawbacks that have

been fixed in ONTbarcoder. Firstly, we dropped the translation-based error correction that

tended to increase the number of Ns. This step used to be essential because indel errors

were prevalent in consensus barcodes obtained with older flow cell models. Secondly,

ONTbarcoder can be installed by unzipping a file and is easy to maintain on different

operating systems. Until now, external dependencies meant that several software packages

had to be installed and that only some operating systems were compatible. This has been a

major drawback of all MinION bioinformatics pipelines and led Watsa et al. [35] to

recommend that bioinformatics training is needed before MinION barcoding could be used in

schools (e.g., training in UNIX command-line). With ONTbarcoder, such training will no

longer be needed.

MinION has been used for barcoding fungi, animals, and plants and alternative pipelines

have been developed [36, 54, 56, 60-66], but there is one fundamental difference between

these studies/pipelines and the vision presented here. These studies tended to show that

MinION sequencing can be done in the field. Thus only a very small number of specimens

were analysed (<150 with the exception of >500 in Chang, Ip et al [60]). The potential use in

the field is an attractive feature for time-sensitive samples that could degrade before

reaching a lab. However, it is unlikely to help substantially with tackling large-scale

biodiversity discovery and monitoring because obtaining few MinION barcodes per flow cell

is too expensive. Additionally, the bioinformatic pipelines that were developed for these

small-scale projects were not suitable for large-scale, decentralized barcoding. For example,

some used ONT's commercial barcoding kit that only allows for multiplexing up to 96

samples in one flow cell [64, 66]; i.e., each amplicon has very high read coverage which

influenced the design of the analysis pipelines (e.g. coverage recommendations for ONTrack

is 1000x: Maestri, Cosentino et al.[64]). The high coverage requirements also meant that the

pipelines were only tested for small numbers of samples (<60: Menegon, Cantaloni et al.

2017, Maestri, Cosetino et al. 2019, Seah, Lim et al. 2020, Sahlin, Lim et al. 2021 [56, 61,

64, 66]) which are unlikely to represent the complexities of large, multiplexed amplicon pools

(e.g., nucleotide diversity, uneven coverage).

This concern is confirmed by our test of the most recently introduced bioinformatics pipeline

(NGSpeciesID [56]). It requires minibar/qcat and nanofilt, isONclust SPOA, Parasail, and

optionally, Medaka [63, 67, 68] and often yields multiple consensus barcodes for the same

set of reads because it relies on an intermediate clustering step. To assess the performance

of NGSpeciesID, we used the consensus barcode with the highest coverage and only

compared the results for those barcodes for which we had reference barcodes obtained with

Sanger and Illumina (Table 3). We find that under optimal settings, NGSpeciesID yields 3-23

times the number of erroneous barcodes than ONTbarcoder (Table 3). One reason is that

NGSpeciesID does not use ambiguity codes in consensus sequences; i.e., ONTbarcoder will

place an "N" when the evidence is ambiguous while NGSpeciesID will opt for one of the

nucleotides. In addition, NGSpeciesID does not use barcode length or translatability as QC

criteria. This has the downside that the software is more likely to yield erroneous barcodes.

For example, NGSpeciesID proposes consensus barcodes for very small read sets for which

ONTbarcoder proposes no barcodes because they failed the QC or did not meet the

minimum read threshold. An upside of not using barcode length and translatability as QC is

that NGSpeciesID can propose consensus barcodes for genes that are non-coding (e.g.,

ITS) or have high length variability (e.g., ribosomal genes). However, the user should be

aware that 3-5% of these barcodes will include errors if the results for *COI* also hold for other

genes (see Table 3).

Biodiversity monitoring with MinION barcodes

Despite the widespread use of metabarcoding for analyzing samples consisting of hundreds

or thousands of specimens [69, 70], large-scale barcoding of individual specimens remains

essential for discovering and describing species. It associate barcodes with individual

voucher specimens, which can be used for further research. This is essential for taxonomic

research, which is the only way to fix systematic errors caused by *COI* which lumps recently

diverged species and splits species with deep allopatric splits [71]. High quality barcode

databases are also important for the analysis of metabarcoding data because they facilitate

the identification of numts, heteroplasmy, contaminants and errors. Furthermore, large-scale

barcoding will also be critical for developing AI-assisted biodiversity monitoring of

invertebrates using images [72]. Such monitoring requires neural networks that are trained

with large numbers of images. These images are best obtained from specimens that were

identified/grouped into species based on barcodes barcodes. It appears likely that AI-

assisted biodiversity monitoring will be the method of choice in the future because it can has

the potential to quickly identify and count common species and highlight which specimens

may belong to new/rare species [73].

Conclusions

Many biologists would like to have ready access to barcodes without having to send

specimens halfway around the world or run large, complex, and expensive molecular

laboratories. Many have been impressed by MinION's low cost, portability, and its ability to

deliver real-time sequencing, but they were worried about high cost and complicated

bioinformatics pipelines. We here demonstrate that these concerns are no longer justified.

MinION barcodes obtained by R10.3 flow cells are virtually identical to barcodes obtained

with Sanger and Illumina sequencing. Barcoding with MinION is now also cost-effective and

the new "ONTbarcoder" software makes it straightforward to analyze the data on a standard

laptop. Add the simplified and cheaper methods for obtaining amplicons and biodiversity

discovery will become more scalable and accessible to all.

Methods

MinION and Flongle sequencing were here tested for six amplicon pools (Table 5). For two

of the pools, *Mixed Diptera* (N=511) and *Afrotropical Phoridae* (N=4,275), we already had

amplicons and comparison barcodes that were obtained with Sanger, Illumina, and older

versions of MinION flow cells that used a different chemistry (see below). These two pools

were here used to assess the accuracy of barcodes generated using the new MinION flow

cell using the R10.3 chemistry. Two additional datasets were used to test the capacity of

R10.3 flowcells for mini- and full length barcodes by sequencing barcodes of different

lengths for the same specimens and obtained with the same DNA template (*Palaearctic*

Phoridae, 658 and 313 bp for ca. 9,930 specimens). Lastly, we tested the performance of

Flongle flow cells using a *Chironomidae* dataset (313 bp mini-barcodes for 191 specimens)

and a *Mixed Diptera Subsample* (full-length barcodes for 257 specimens) of the

aforementioned *Mixed Diptera* amplicon pool for which we had Sanger barcodes for

comparison.

The methods for obtaining the reference barcodes with Sanger and Illumina are described in

Srivathsan et al. [31, 33]. Briefly, for Sanger sequencing (Mixed Diptera sample set), the

same PCR products sequenced with MinION were individually cleaned using SureClean

Plus (Bioline, London) and subjected to cycle sequencing using BigDye™. The products

were precipitated using PureSeq (Aline BioSciences, Woburn) and analysed in ABI 3730xl

96 capillary sequences. The resulting chromatograms were edited using Sequencer v4

(GeneCodes, Ann Arbor). For Illumina sequencing of products of the Afrotropical Phoridae

dataset, an independent PCR was conducted using the DNA extract for the same specimens

to amplify a short 313-bp fragment of COI using 9-bp tagged versions of the primers

described by Leray et al. [74]. The products were pooled and sequenced using HiSeq2500

(250 bp PE sequencing). The data processing followed Wang et al.'s protocol. [23] for

obtaining a set of consensus barcodes.

Table 5. Datasets used in the study and the corresponding experimental details.

Dataset Name	Number of specimens	Fragment size, primer information	Extraction/PCR setup	PCR cleanup	ONT Library Preparation kit/Flow cell used
R10.3 Datasets					
Mixed Diptera	511 (257 mixed	658 bp	Extraction Method:	Ampure	SQK-

(see Srivathsan et al. 2018) - Sanger barcodes available	Diptera, 254 Dolichopodidae) 17 negatives	HCO2198, LCO1490 [75]	QuickExtract PCR Mix: Total volume: 20 µl 10× buffer: 2 µl dNTPs (2.5 mM): 1.5 µl Taq polymerase: 0.2 µl BSA (1 mg/ml): 2 µl Primer (5 µM): 2 µl each DNA:2 µl	beads (Beckman Coulter)	LSK110/FLO-MIN111
Afrotropical Phoridae (see Srivathsan et al. 2019) - Illlumina mini-barcodes available	4275 (Phoridae) 45 negatives	658 bp HCO2198, LCO1490 [75]	Extraction Method: QuickExtract PCR Mix: Total volume: 15.16 µl Mastermix (CWBio): 10 µl 25mM MgCl2: 0.16 µl BSA (1mg/ml): 2 µl Primer (10µM): 1 µl each DNA: 1 µl	Sera-Mag beads (GE Healthcare Life Sciences) in PEG	SQK-LSK109/FLO-MIN111
Palaearctic Phoridae (658)	9,929 (Phoridae) 105 negatives	658 bp jgHCO2198, LCO1490 [75, 76]	Extraction Method: HotSHOT PCR Mix: Total volume: 16 µl Mastermix (CWBio): 7 µl BSA (1mg/ml): 1 µl Primer (10µM): 1 µl each DNA: 6 µl	Ampure beads (Beckman Coulter)	SQK-LSK110/FLO-MIN111
Palaearctic Phoridae (313)	9,932 (Phoridae) 106 negatives	313 bp m1COIintF, jgHCO2198 [74, 76]	Extraction Method: HotSHOT PCR Mix: Total volume: 14 µl Mastermix (CWBio): 7 µl BSA (1mg/ml): 1 µl Primer (10µM): 1 µl each DNA: 4 µl	Ampure beads (Beckman Coulter)	SQK-LSK110/FLO-MIN111
Flongle Datasets					
Mixed Diptera subsample (see Srivathsan et al. 2018) - Sanger barcodes available	257 7 negatives	See "Mixed Diptera" entry for R10.3	See "Mixed Diptera" entry for R10.3	Ampure beads (Beckman Coulter)	SQK-LSK109/Flongle
Chironomidae	191 (Chironomidae) 1 negative	313 bp m1COIintF, jgHCO2198 [74,76]	Extraction Method: HotSHOT PCR Mix: Total volume: 14 µl Mastermix (CWBio): 7 µl BSA (1mg/ml): 1 µl Primer (10µM): 1 µl each DNA: 4 µl	Ampure beads (Beckman Coulter)	SQK-LSK109/Flongle

1: DNA extraction

For all newly barcoded specimens, we used DNA template obtained with 10-15 µL HotSHOT

per specimen [77], but other buffers like PBS could have also been used (see [78]). Small

specimens were submerged within the well of a microplate while larger specimens were

placed head-first into the well. Note that the specimen need not be entirely submerged in

HotSHOT. The placement of 95 specimens takes approximately 17 minutes and the DNA is

obtained within 20 minutes in a thermocycler via two heating steps [77]

(https://www.youtube.com/watch?v=y1qGzL5PraQ&t=3s). After neutralization, >20 µl of

template is available for amplifying *COI* and the voucher can be recovered. The advantages

of HotSHOT is low cost and speed. The disadvantages are fast degeneration of the leftover

template within days. Some alternatives to DNA extraction with HotSHOT are described in

Table 6. We consider them too costly or time-consuming given that *COI* is a mitochondrial

gene and thus naturally enriched. Indeed, the small mitochondrial genome (16 kbp) usually

contributes 0.5-5% of the DNA in a genomic extraction [79, 80]. Therefore obtaining

sufficient template for DNA barcoding should take <20 minutes, does not require DNA

purification, and should cost essentially nothing as long as the specimens contain DNA of

reasonable quality (e.g., <20 year old Malaise trap samples).

Table 6. Alternative DNA extraction methods

Commonly used alternative DNA extraction methods	advantages	disadvantages
"directPCR": "contaminating" a PCR reaction with the DNA of the target organism by adding the entire specimen or a tissue sample into the PCR reagent mix (Wong, Tay et al. 2014).	• No cost • No waiting time obtaining for template	• time-consuming when subsampling is needed (antenna, leg) • low success rate for heavily sclerotized specimens • no DNA template left after PCR
Commercial DNA extraction buffers: e.g., QuickExtract: 10 µl sufficient for obtaining DNA template from most insect specimens (Srivathsan, Hartop et al. 2019)	• long shelf life of buffers • template stays viable for weeks • additional DNA can be obtained through re-extraction of specimen	• moderate costs (<0.20 USD) • DNA in leftover template degrades within weeks/months
Commercial DNA extraction kits: e.g., DNeasy Blood & Tissue Kits:	• template is stable	• high cost (>1 USD) • time-consuming

522
523

2: Amplification of COI via PCR

Obtaining amplicons for DNA barcodes does not require high-fidelity polymerases, which are mostly needed for amplifying low copy-number nuclear genes based on low-concentration template. Standard polymerases are sufficient. We exclusively used CWBio 2x master mix in 14-16 ul PCR reactions (see Table 5 for details). The set-up of one plate requires <15 minutes (https://www.youtube.com/watch?v=NxYOvZGhD0E&t=5s). In order to save time, only a small number of reactions per microplate need to be checked via gel electrophoresis (N=8-12, including the negative control). Running out additional amplicons is not necessary because failed amplicons do not add to the MinION sequencing cost and can be recovered via re-sequencing [33] or re-amplification.

Amplicon sequencing with all second and third generation sequencing technologies (including MinION) involves amplicon pools. This means that the amplicon for each specimen has to be tagged/indexed/barcoded with short DNA sequences at the 5' ends of the amplicons. This allows for the assignment of each read obtained during sequencing to a specific specimen during the "demultiplexing" bioinformatics step. We use 13 bp tags that are distinct (>4bp from each other including insertions/deletions) and lack homopolymers (see supplementary materials). This tag length is a compromise given that longer tags have the disadvantage of reducing PCR success rates [33] while having the advantage of increasing the proportion of reads that can be demultiplexed with confidence.

Numerous dual-PCR tagging techniques for amplicons have been described in the literature [29, 64, 81, 82], but we only use single-PCR tagging [28]. It is here described for a microplate with 96 templates, but the same principle can be applied to strip tubes or partial microplates. What is needed is a 96-well primer plate where each well contains a differently tagged reverse primer. This "primer plate" can yield 96 unique combinations of primers once the 96 reverse primers are combined with one forward primer (f-primer x 96 differently tagged r-primers = 96 unique combinations). This also means that if one purchases 105

differently tagged forward primers, one can individually tag 10,800 specimens (105 x 96=

10,800 amplicons). This is the number of amplicons that we consider appropriate for a

MinION flow cell (R10.3; see Results). In the laboratory we assign the tag combinations as

follows. For each plate with 96 PCR reactions, we add the same f-primer to a tube with the

PCR master mix to be used for the entire plate. We then dispense the "f-primed" master mix

into the 96-wells. Afterwards, we use a multichannel pipette to add the DNA template and

the tagged r-primers from the r-primer plate into the PCR plate. All 96 samples in the plate

now have a unique combination of tagged primers because they only share the same tagged

forward primer. This makes tracking of tag combinations simple because each PCR plate

has its own tagged f-primer, while the r-primer is consistently tied to well position. Each plate

has a negative control that is used to detect contamination. The tagging information for each

plate is recorded in the demultiplexing file that is later used to demultiplex the reads obtained

during sequencing (see supplement for an example).

We prefer single-PCR tagging over two-PCR tagging [29, 64, 81, 82] because it is cheaper

(requires half the amount of primer), less error-prone (fewer PCR reactions and cycles), and

saves time (no need to clean-up the first-round amplicons). The only downsides of single-

PCR tagging are an initially higher investment in primers and the need to manage the primer

stock more carefully because it is used for a longer time. Long-term storage should thus be

at -80°C and the number of freeze-thaw cycles should be kept low (<10).

3. Amplicon sequencing

PCR is followed by pooling, purification of the amplicons via the removal of unused PCR

reagents, the adjustment of DNA concentration, and sequencing. We only pool 1 μl of each

PCR product. The pools were cleaned using SPRI bead-based clean-up with Ampure

(Beckman Coulter) beads, but Kapa beads (Roche) or the more cost-effective Sera-Mag

beads (GE Healthcare Life Sciences) in PEG [83] are also viable options [33]. For barcodes

longer than 300 bp, we recommend the use of a 0.5X ratio for Ampure beads since it

removes a larger proportion of primers and primer dimers. However, this ratio is only suitable

if yield is not a concern (e.g., pools consisting of many and/or high concentration amplicons).

Increasing the ratio to 0.7-1X will improve yield but render the clean-up less effective. The

pooling and clean-up of three 96-well plates takes about 40 minutes

(https://www.youtube.com/watch?v=YKVWEvcSw6A), but the time per plate is lower when

large numbers of amplicons are pooled. Amplicon pools containing large numbers of

amplicons may require multiple rounds of clean-up, but only a small subset of the initial pool

has to be purified because most library preparation kits require only small amounts of DNA.

We confirm the success of the clean-up procedures via gel electrophoresis, which should

show only one strong band of expected length. After the clean-up, the pooled DNA

concentration is measured in order to use an appropriate amount of DNA for library

preparation. We use Qubit, but less precise techniques are probably also suitable.

Obtaining a cleaned amplicon pool according to the outlined protocol is not time consuming,

but many studies retain "old Sanger sequencing habits". For example, they use gel

electrophoresis for each PCR reaction to test whether an amplicon has been obtained.

Afterwards, they clean and measure all amplicons – one at a time – for normalization (often

with very expensive techniques: Ampure beads: [64]; TapeStation, BioAnalyzer, Qubit:[66]).

This is presumably done to obtain a pool of amplicons where each has equal representation.

However, reads are cheap while the clean-up and measurement of many amplicons is

expensive and unnecessary because weak products that failed to yield a barcode in the first

sequencing run can be re-sequenced [33].

4. Library preparation and sequencing

We prepare our MinION libraries using ligation-based kits and 200 ng of DNA for full flow

cells and 100 ng for Flongle (see Table 6 for details). We generally follow kit instructions, but

exclude the FFPE DNA repair mix in the end-repair reaction, as this is mostly needed for

formalin-fixed, paraffin-embedded samples. The reaction volumes for the R10.3 flow cell

libraries consist of 45 μl of DNA, 7 μl of Ultra II End-prep reaction buffer (New England

Biolabs), 3 μl of Ultra II End Prep enzyme mix (New England Biolabs) and 5 μl of molecular

grade water. For the Flongle, only half of the reagents are used to obtain a total volume of

30 μl. We further modify the Ampure ratio to 1x for all steps as DNA barcodes are short

whereas the recommended ratio in the manual is for longer DNA fragments. The libraries for

the experiments in this study were loaded and sequenced on a MinION Mk 1B. Data capture

involved a MinIT or a Macintosh computer that meets the IT specifications recommended by

ONT. The bases were called using Guppy (versions provided in Table 1), under the high-

accuracy model in MinIT taking advantage of its GPU.

We here only used MinION and Flongle flow cells for barcoding. This preference was based

on four considerations: (1) Scaling; i.e., ability to accommodate projects of different sizes, (2)

turnaround times, (3) cost, and (4) amplicon length. Flongle can be used for small amplicon

pools (<300 products) because it has low fixed costs per experiment (library and flow cell:

ca. $120 USD) and the turnaround time is fast, so the MinION Flongle is arguably the best

sequencing option for small barcoding projects with > 50 barcodes. Full MinION flow cells

also have fast turnaround times, but the minimum run cost is closer to 1000 USD for most

users (flow cell cost drops with bulk purchase), so this option only becomes more cost-

effective than Flongle when >1800 amplicons are sequenced. As illustrated in the Results

section of the manuscript, one MinION flow cell can comfortably sequence 10,000

amplicons.

Alternatives to MinION/Flongle are sequencing barcode amplicons with Sanger, Illumina

(Wang, Srivathsan et al. 2018), or PacBio (e.g., Sequel: Hebert, Braukmann et al. [29]).

Sanger sequencing has fast turnaround times but high sequencing cost per amplicon ($3-4

USD). PacBio's Sequel flow cells have a similar capacities as full MinION flow cells [29] and

the consumable costs are also similar for most users who have to outsource Sequel

sequencing due to the high instrument cost for PacBio. However, Sequel does not allow for

flexible scaling like Flongle/MinION and most users will have to wait several weeks until the

data are returned from the service provider. By far the most cost-effective sequencing

method for barcodes is Illumina's NovaSeq sequencing. However, the fixed costs for library

and lanes are high (3000-4000 USD), but each flow cell yields 800 million reads which can

comfortably sequence 800,000 barcodes at a cost of < $0.01 USD per barcode. Note that

Illumina reads are only suitable for generating mini-barcodes of up to 420 bp length (using

250bp PE sequencing using SP flow cell). "Full-length" *COI* barcode (658 bp) can only be

obtained by sequencing two amplicons per specimen.

5. Bioinformatics: Development and application of ONTbarcoder

One of the most significant barriers to widespread barcoding with MinION has been complex

bioinformatics pipelines that were needed for fixing the high error rates of ONT reads.

However, after obtaining data from a new R10.3 flow cell, we noticed major improvements in

read quality, the total number of raw reads, and the number of demultiplexed reads. This led

to the development of "ONTbarcoder", which has a graphical user interface (GUI) and is

suitable for all major operating systems (Linux, Mac OS, Windows10). The use of the

software is illustrated in a video tutorial:

https://www.youtube.com/channel/UC1WowokomhQJRc71FmsUAcg.

ONTbarcoder. ONTbarcoder (available at: https://github.com/asrivathsan/ONTbarcoder) has

three modules. (a) The first is a demultiplexing module which assigns reads to specimen-

specific bins. (b) The second is a barcode calling module which reconstructs the barcodes

based on the reads in each specimen bin. (c) The third is a barcode comparison module that

allows for comparing barcodes obtained via different software and software settings.

a. Demultiplexing. In order to obtain barcodes three pieces of information and two files have

to be provided to ONTbarcoder via the GUI: (1) primer sequence, (2) expected fragment

length, and (3) demultiplexing information (=tag combination for each specimen). The latter

is summarized in a demultiplexing file (see supplementary information for format). The only

other required file is the FASTQ file obtained from MinKNOW/Guppy after basecalling.

Demultiplexing by ONTbarcoder starts by analyzing the read length distribution in the

FASTQ file. Only those reads that meet the read length threshold are demultiplexed

(default= 658 bp corresponding to metazoan COI barcode). Technically, the threshold

should be the amplicon length plus the length of both tagged primers, but ONT reads have

indel errors such that they are occasionally too short or too long. We therefore advise to

specify the amplicon length without primer&tag as threshold. ONTbarcoder will split reads

that are twice the expected fragment length into two parts whose lengths are determined

based fragment size, primer and tag lengths, and a window to account for indel errors

(default=100 bp).

Once all reads with a suitable length for demultiplexing have been identified, ONTbarcoder

finds the primers via sequence alignment of the primer sequence to the reads (using python

library *edlib*). Up to 10 deviations from the primer sequence are allowed because this step is

only needed for determining the primer location and orientation within the read. For

demultiplexing based on the tags, the flanking region of the primer sequence is retrieved

whereby the number of retrieved bases is equal to the user-specified tag length. The flanking

sequences are then matched against the tags from the user-provided tag combinations

(demultiplexing file). In order to account for sequencing errors, not only exact matches are

accepted, but also matches that differ by up to 2 bps from the tag sequence

(substitutions/insertions/deletions). Note that accepting tag variants does not lead to

demultiplexing error because all tags differ by >4 bp. All reads with the same tag

combination thus identified belong to the same specimen and are pooled into the same bin.

To increase efficiency, demultiplexing is parallelized and the search space for primers and

tags are restricted to the beginning and end of the reads (window is user-specified).

b. Barcode calling: Barcode calling uses the reads within each specimen-specific bin to

reconstruct the barcode sequence. The reads are aligned to each other and a consensus

sequence is called. Barcode calling is done in three phases: "Consensus by Length",

"Consensus by Similarity" and "Consensus by barcode comparison". The user can opt to

only use some of these methods.

"Consensus by Length" is the main barcode calling mode and relies on efficient alignment in

order to provide reasonable speed for thousands bins each containing many reads.

ONTbarcoder delivers speed by using an iterative approach that gradually increases the

number of reads ("coverage") per bin that is used during alignment. However, reconstructing

barcodes based on few reads could lead to errors which are weeded out by ONTbarcoder by

applying four Quality Control (QC) criteria. The first three QC criteria are applied immediately

after the consensus sequence has been called: (1) the barcode must be translatable, (2) it

has to match the user-specified barcode length, and (3) the barcode has to be free of

ambiguous bases ("N"). To increase the chance of finding a barcode that meets all three

criteria, we subsample the reads in each bin by read length (thus the name "Consensus by

Length"); i.e., initially only those reads closest to the expected length of the barcode are

used. For example, if the user specified coverage=25x for a 658 bp barcode, ONTbarcoder

would only use the 25 reads that have the closest match to 658 bp. The fourth QC measure

is only applied to barcodes that have already met the first three QC criteria. A multiple

sequence alignment (MSA) is built for the barcodes obtained from the amplicon pool, and

any barcode that causes the insertion of gaps in the MSA is rejected. Note that if the user

suspects that barcodes of different length are in the amplicon pool, the initial analysis should

use the dominant barcode length. The remaining barcodes can then be recovered by re-

analyzing all data or only the failed read bins ("remaining", see below) and bins that yielded

barcodes that had to be "fixed". These bins can be reanalyzed using a different pre-set

barcode length.

"Consensus by Similarity". Barcodes that failed the QC during the "Consensus by Length"

stage are often very close to the expected length and have few ambiguous bases, and/or

cause few gaps in the MSA. These "preliminary barcodes" can be improved through

"Consensus by Similarity". This method eliminates outlier reads from the read pool in the

bins. Such reads can differ considerably (see below) from the signal of the consensus

barcode and ONTbarcoder identifies them by sorting all reads by similarity to the preliminary

barcode. Only the top 100 reads (this default can be changed) that differ by <10% from the

preliminary barcode are retained and used for calling the barcodes again using the same

techniques described "Consensus by Length" (including the same QC criteria). This

improvement step converts many preliminary barcodes found during "Consensus by Length"

into barcodes that pass all four QC criteria by filling/removing indels or resolving an

ambiguous base.

"Consensus by barcode comparison". The remaining preliminary barcodes that still failed to

convert into QC-compliant barcodes tend to be based on read bins with low coverage, but

some can yield good barcodes after subjecting them to a further improvement step that fixes

the remaining errors. ONTbarcoder identifies these errors by finding the 20 most similar QC-

compliant barcodes that have already been reconstructed for the other amplicons. The 21

sequences are aligned and ONTbarcoder finds the errors because they cause insertions and

deletions in the MSA. Insertions are deleted, gaps are filled with ambiguous bases ("N"), but

mismatches are retained. The number and kinds of "fixes" are recorded and added to the

FASTA header of the barcode. Large number of fixes imply that the barcode should not be

used (see below). "Rare taxa are disadvantaged by this method, but the barcode for very

few if any will ever reach the "Consensus by barcode comparison" stage because most/all

will be resolved earlier. We added "consensus by barcode comparison" because it helps with

resolving weak barcodes for specimens that represent abundant species.

Output. ONTbarcoder produces a summary table (Outputtable.csv) and FASTA files that

contain the different classes of barcodes. Each barcode header contains information on

coverage used for barcode calling, coverage of the specimen bin, length of the barcode,

number of ambiguities and number of indels fixed. Five sets of barcodes are provided, here

discussed in the order of barcode quality: (1) "QC_compliant": The barcodes in this set

satisfy all four QC criteria without correction and are the highest quality barcodes. (2)

"Filtered_barcodes": this file contains the barcodes that are translatable, have <1%

ambiguities and have up to 5 indels fixed during the last step of the bioinformatics pipeline.

These filtering thresholds were calibrated based on two datasets for which we have

Sanger/Illumina barcodes and the resulting barcodes are found to be highly accurate. Note

that the file with filtered barcodes also includes the QC_compliant barcodes and that all

results discussed in this manuscript are based on filtered barcodes given that they are of

much higher quality than the average barcode in BOLDSystems (assessment in Srivathsan,

Baloğlu et al [31]).

The remaining files include barcodes of lesser and/or suspect quality. (3)

"Fixed_barcodes_XtoY": these files contain barcodes that had indel errors fixed and are

grouped by the number of errors fixed. Only the barcodes with 1-5 errors overlap with

Filtered barcodes file, if they have <1% ambiguities. (4) "Allbarcodes": this file contains all

barcodes in sets (1)-(3). (5) "Remaining": these are barcodes that fail to either translate or

are not of predicted length. Note that all barcodes should be checked via BLAST against

comprehensive databases in order to detect lab contamination. There are several online

tools available for this and we recommend the use of GBIF sequence ID tool

(https://www.gbif.org/tools/sequence-id) which gives straightforward output including a

taxonomic summary.

The output folder also includes the FASTA files that were used for alignment and barcode

calling. The raw read bins are in the "demultiplexed" folder, while the resampled bins (by

length, coverage, and similarity) are in their respective subfolders named after the search

step. Note that the raw reads are encoded to contain information on the orientation of the

sequence and thus cannot be directly used in other software without modifications (see

ONTbarcoder manual on Github). Lastly, for each barcode FASTA file (1-5), there are

folders with the files that were used to call the barcodes. This means that the user can, for

example, reanalyze those bins that yielded barcodes with high numbers of ambiguous

bases. Lastly a "runsummary.xlsx" document allows the user to explore the details of the

barcodes obtained at every step of the pipeline.

Algorithms. ONTbarcoder uses the following published algorithms. All alignments utilize

MAFFTv7 (Katoh and Standley 2013). The MinION reads are aligned using an approach

similar to lamassemble [84] with parameters optimized for nanopore data by "last-train" [85]

which accounts for strand specific error biases. The MAFFT parameters can be modified in

the "parfile" supplied with the software which helps with adjusting the values given the

rapidly changing nanopore technology. All remaining MSAs in the pipeline (e.g., of

preliminary barcodes) use MAFFT's default settings. All read and sequence similarities are

determined with the *edlib* python library under the Needle-Wunsch ("NW") setting, while

primer search is using the infix options ("HW"). All consensus sequences are called from

within the software. This is initially done based on a minimum frequency of 0.3 for each

position. This threshold was empirically determined based on datasets where MinION

barcodes can be compared to Sanger/Illumina barcodes. The threshold is applied as follows.

All sites where >70% of the reads have a gap are deleted. For the remaining sites,

ONTbarcoder accepts those consensus bases that are found in at least >30% of the reads.

If no base/multiple bases reach this threshold, an "N" is inserted. To avoid reliance on a

single threshold, ONTbarcoder allows the user to change the consensus calling threshold

from 0.2 to 0.5 for all barcodes that fail the QC criteria at 0.3 frequency. However, barcodes

called at different frequencies are only accepted if they pass the first three QC criteria and

are identical. If no such barcode is found, the 0.3 frequency consensus barcode is used for

further processing.

c. Barcode comparison. Many users may want to call their barcodes under different settings

and then compare barcode sets. The ONTbarcoder GUI simplifies such comparisons. A set

of barcodes can be dragged into the window and the user can select a barcode set as the

reference. The barcode comparisons are conducted using *edlib* library. The barcodes in the

sets are compared and classified into three categories: "identical" where sequences are a

perfect match and lack ambiguities, "compatible" where the sequences only differ by

ambiguities, and "incorrect" where the sequences differ by at least one base pair. Several

output files are provided. A summary sheet, a FASTA file each for "identical", "compatible",

and the sequences only found in one dataset. Lastly, there is a folder with FASTA files

containing the different barcodes for each incompatible set of sequences. This module can

be used for either comparing set(s) of barcodes to reference sequences, or for comparing

barcode sets against each other. It furthermore allows for pairwise comparisons and

comparisons of multiple sets in an all-vs-all manner. This module was here used to get the

final accuracy values presented in Table 2.

Quality of Flongle and MinION barcodes

We first used ONTbarcoder to analyze the data for all six datasets by analyzing all

specimen-specific read bins at different coverages (5-200x in steps of 5x). This means that

the barcodes for a bin with 27 reads were called five times at 5x, 10x, 15x, 20x, and 25x

coverages while bins with >200x were analyzed 40 times at 5x increments. Instead of using

conventional rarefaction via random subsampling reads, we used the first reads provided by

the flow cell because this accurately reflects how the data accumulated during the

sequencing run and how many barcodes would have been obtained if the run had been

stopped early. This rarefaction approach also allowed for mapping the barcode success

rates against either coverage or time.

In order to obtain a "best" estimate for how many barcodes can be obtained, we also carried

out one analysis at 200x coverage with the maximum number of "Comparison by Similarity"

reads set to 100. All analyses produced a "filtered" set of barcodes (barcodes with <1% Ns

and up to 5 fixes) that were used for assessing the accuracy and quality via comparison with

Sanger and Illumina barcodes for *Mixed Diptera (MinION R10.3)*, *Afrotropical Phoridae*

(MinION R10.3), and *Mixed Diptera Subsample (Flongle R9.4).* For the comparisons of the

barcode sets obtained at the various coverages, we used MAFFT and the

assess_corrected_barcode.py script in miniBarcoder (Srivathsan et al. 2019).

6. Bioinformatics: Application of minibar and NGSpeciesID

We compared the barcodes obtained with ONTbarcoder with those obtained with the

recently published NGSpeciesID [56]. This comparison was carried out for the datasets that

have the reference barcodes obtained with Sanger and Illumina (*Mixed Diptera (MinION*

R10.3), *Afrotropical Phoridae (MinION R10.3)*, and *Mixed Diptera Subsample (Flongle*

R9.4)). Two comparisons were made. Firstly, we used the same demultiplexed reads that

were used for calling the barcodes using ONTbarcoder. Secondly, we demultiplexed the

data using *minibar* (git commit: 938ae51) and applied NGSpeciesID (Git commit: 24afc6c)

for consensus barcode calling. This approach allowed for software comparisons for

consensus calling and demultiplexing. *minibar* was run using the parameters (-e 2 -E 10 -T),

i.e. maximum number of errors in tag region was set to 2, in primer alignment was set to 10

and primer and tags were trimmed from the sequences. NGSpeciesID was run with both full

datasets as well as by subsampling the data to 200 reads (--sample_size 200) to keep it

comparable with our analysis using ONTbarcoder. Other parameters settings were: intended

target length = 658 (--m) and maximum deviation from target length = 50 (--s). Lastly, for the

R10.3 datasets, the medaka model was specified by using –model r103_min_high_g345,

which was the only available for R10.3.

Acknowledgements

We would like to thank John T. Longino and Michael Branstetter for providing valuable comments on the manuscript. For the Palaearctic phorid samples, we would like to thank Dave Karlsson, the Swedish Insect Inventory Project, and the crew at Station Linné that sorted out the phorids. We would also like to thank Wan Ting Lee for help with molecular work, and the numerous staff, students and interns who have contributed to the establishment of the pipeline in the NUS laboratory. We would also like to acknowledge Suphavilai Chayaporn and Niranjan Nagarajan from Genome Institute of Singapore for their help with basecalling using bonito. This work was supported by a Ministry of Education grant on biodiversity discovery (R-154-000-A22-112).

Declarations: Software and test dataset availability

ONTbarcoder is available at https://github.com/asrivathsan/ONTbarcoder, which also contains the link to download the raw data and demultiplexing files. The manual for the software is included in the repository https://github.com/asrivathsan/ONTbarcoder/blob/main/ONTBarcoder_manual.pdf. The videos tutorials can be found in the YouTube channel Integrative Biodiversity Discovery: https://www.youtube.com/channel/UC1WowokomhQJRc71FmsUAcg. The datasets have been uploaded to NCBI, under BioProject: PRJNA745481, SRA accession numbers: SRR15185964, SRR15098600, SRR15098599, SRR15188571, SRR15188570, SRR15188569. The datasets, demultiplexing files and reference barcodes are also available via doi:10.5281/zenodo.5115258.

Literature cited

1. Hebert PDN, Cywinska SL, Ball SL, DeWaard JR: **Biological identifications through DNA Barcodes**. *Proc Biol Sci* 2003, **270**(1512):313-321.
2. Tautz D, Arctander P, Minelli A, Thomas RH, Vogler AP: **A plea for DNA taxonomy**. *Trends in Ecology & Evolution* 2003, **18**(2):70-74.

3.   Meier R: **DNA sequences in taxonomy - Opportunities and challenges**. In: *The New*
Taxonomy Systematics Association Special Volume. Edited by Wheeler QD. New York: CRC
Press; 2008: 95-128.
4.   Ivanova NV, DeWaard JR, Hebert PD: **An inexpensive, automation-friendly protocol for**
recovering high-quality DNA. *Molecular Ecology Notes* 2006, **6**(4):998-1002.
5.   Ivanova NV, Borisenko AV, Hebert PD: **Express barcodes: racing from specimen to**
identification. *Molecular ecology resources* 2009, **9 Suppl s1**:35-41.
6.   Meier R, Blaimer B, Buenaventura E, Hartop E, Von Rintelen T, Srivathsan A, Yeo D: **A re-**
analysis of the data in Sharkey et al.'s (2021) minimalist revision reveals that BINs do not
deserve names, but BOLD Systems needs a stronger commitment to open science. *BioRxiv*
2021, **doi**:10.1101/2021.1104.1128.441626.
7.   Stork NE, McBroom J, Gely C, Hamilton J: **New approaches narrow global species estimates**
for beetles, insects, and terrestrial arthropods. *PNAS* 2015, **112**(24):7519-7523.
8.   Yeo D, Srivathsan A, Meier R: **Longer is Not Always Better: Optimizing Barcode Length for**
Large-Scale Species Discovery and Identification. *Systematic Biology* 2020, **69**(5):999-1015.
9.   **World Economic Forum. The Global Risks Report 2020.**
[https://www.weforum.org/reports/the-global-risks-report-2020]
10. Re S: **Biodiversity and Ecosystem Services A business case for re/insurance**. In. Zurich: Swiss
Re Management Ltd.; 2020.
11. Abrego NT, Roslin T, Huotari Y, Ji NM, Schmidt NM, Wang J, Yu D, Ovaskainen O: **Accounting**
for species interactions is necessary for predicting how arctic arthropod communities
respond to climate change. *Ecography* 2021, **doi**:10.1111/ecog.05547.
12. Kwong S, Srivathsan A, Meier R: **An update on DNA barcoding: low species coverage and**
numerous unidentified sequences. *Cladistics* 2012, **28**(6):639-644.
13. **Dark taxa: GenBank in a post-taxonomic world** [https://iphylo.blogspot.com/2011/04/dark-
taxa-genbank-in-post-taxonomic.html]
14. Barrett RDH, Hebert PD: **Identifying spiders through DNA barcodes**. *Canadian Journal of*
Zoology 2005, **83**:481-491.
15. Hendrich L, Pons J, Ribera I, Balke M: **Mitochondrial Cox1 sequence data reliably uncover**
patterns of insect diversity but suffer from high lineage-idiosyncratic error rates. *PLoS One*
2010, **5**(12):e14448.
16. Hebert PD, DeWaard JR, Zakharov EV, Prosser SWJ, Sones JE, McKeown JTA, Mantle B, La
Salle J: **A DNA 'Barcode Blitz': Rapid Digitization and Sequencing of a Natural History**
Collection. *PLoS One* 2013, **8**(7):e68535.
17. Ng'endo RN, Osiemo ZB, Brandl R: **DNA Barcodes for Species Identification in the**
Hyperdiverse Ant Genus Pheidole (Formicidae: Myrmicinae). *Journal of Insect Science* 2013,
13:27.
18. Hebert PD, Ratnasingham S, Zakharov EV, Tefler AC, Levesque-Beaudin M, Milton A,
Pedersen S, Jannetta P, DeWaard JR: **Counting animal species with DNA barcodes: Canadian**
insects. *Philosophical Transactions of the Royal Society B: Biological Sciences* 2016,
371:20150333.
19. Thormann B, Ahrens D, Armijos DM, Peters MK, Wagner T: **Exploring the leaf beetle fauna**
(Coleoptera: Chrysomelidae) of an Ecuadorian mountain forest using DNA barcoding. *PLoS*
One 2016, **11**(2):e0148268.
20. Knox MA, Hogg ID, Pilditch CA, Garcia-R JC, Hebert PDN, Steinke D: **Contrasting patterns of**
genetic differentiation for deep-sea amphipod taxa along New Zealand's continental
margins. *Deep Sea Research Part I: Oceanographic Research Papers* 2020, **162**:103323.
21. Krell FT: **Parataxonomy vs. taxonomy in biodiversity studies – pitfalls and applicability of**
'morphospecies' sorting. . *Biodiversity and Conservation* 2004, **13**(4):795-812.

22.   Stribling JB, Pavlik KL, Holdsworth SM, Leppo EW: **Data quality, performance, and**
uncertainty in taxonomic identification for biological assessments. *Journal of the North*
American Benthological Society 2008, **27**(4):906-919.
23.   Wang WY, Srivathsan A, Foo M, Yamane SK, Meier R: **Sorting specimen-rich invertebrate**
samples with cost-effective NGS barcodes: Validating a reverse workflow for specimen
processing. *Molecular ecology resources* 2018, **18**(3):490-501.
24.   Puillandre N, Modica MV, Zhang Y, Sirovich L, Boisselier MC, Cuaud C, Holford M, Samadi S:
Large-scale species delimitation method for hyperdiverse groups. *Molecular Ecology* 2012,
21:2671-2691.
25.   Hartop E, Srivathsan A, Ronquist F, Meier R: **Large-scale Integrative Taxonomy (LIT):**
resolving the data conundrum for dark taxa. . *BioRxiv* 2021,
doi:10.1101/2021.1104.1113.439467.
26.   Shokralla S, Gibson JF, Nikbakht H, Janzen D, Hallwachs W, Hajibabaei M: **Next-generation**
DNA barcoding: using next-generation sequencing to enhance and accelerate DNA barcode
capture from single specimens. *Molecular ecology resources* 2014, **14**(5):892-901.
27.   Shokralla S, Porter TM, Gibson JF, Dobosz R, Janzen D, Hallwachs W, Golding GB, Hajibabaei
M: **Massively parallel multiplex DNA sequencing for specimen identification using an**
Illumina MiSeq platform. *Scientific Reports* 2015, **5**:9687.
28.   Meier R, Wong W, Srivathsan A, Foo M: **$1 DNA barcodes for reconstructing complex**
phenomes and finding rare species in specimen-rich samples. *Cladistics* 2016, **32**:100-110.
29.   Hebert PD, Braukmann TWA, Prosser SWJ, Ratnasingham S, deWaard JR, Ivanova NV, Janzen
D, Hallwachs W, Naik S, Sones JE *et al*: **A Sequel to Sanger: amplicon sequencing that scales.**
BMC Genomics 2018, **19**:219.
30.   Krehenwinkel H, Kennedy SR, Rueda A, Lam A, Gillespie RG: **Scaling up DNA barcoding –**
Primer sets for simple and cost efficient arthropod systematics by multiplex PCR and
Illumina amplicon sequencing. *Methods in Ecology and Evolution* 2018, **9**(11):2181-2193.
31.   Srivathsan A, Baloglu B, Wang W, Tan WX, Bertrand D, Ng AHQ, Boey EJH, Koh JJY, Nagarajan
N, Meier R: **A MinION-based pipeline for fast and cost-effective DNA barcoding.** *Molecular*
ecology resources 2018, **18**(5):1035-1049.
32.   Yeo D, Srivathsan A, Puniamoorthy J, Foo M, Grootaert P, Chan L, Guenard B, Damken C,
Wahab RA, Ang YC *et al*: **Mangroves are an overlooked hotspot of insect diversity despite**
low plant diversity. *BMC Biology* 2021, **doi**:10.1186/s12915-12021-01088-z.
33.   Srivathsan A, Hartop E, Puniamoorthy J, Lee WT, Kutty SN, Kurina O, Meier R: **Rapid, large-**
scale species discovery in hyperdiverse taxa using 1D MinION sequencing. *BMC Biology*
2019, **17**(1):96.
34.   Ponder W, Lunney D: **The Other 99% - the Conservation and Biodiversity of Invertebrates.**
Sydney: Transactions of the Royal Zoological Society of New South Wales; 1999.
35.   Watsa M, Erkenswick GA, Pomerantz a, Prost S: **Portable sequencing as a teaching tool in**
conservation and biodiversity research. *PLoS Biology* 2020, **18**(4):e3000667.
36.   Pomerantz A, Peñafel A, Arteaga A, Bustamante L, Pichardo F, Coloma LA, Barrio-Amorós CL,
Salazar-Valenzuela D, Prost S: **Real-time DNA barcoding in a rainforest using nanopore**
sequencing: opportunities for rapid biodiversity assessments and local capacity building.
2018 2018, **7**(4):giy033.
37.   Marshall SA: **Field photography and the democratization of arthropod taxonomy** *American*
Entomologist 2008, **54**(4):207-210.
38.   Dunn RR, Beasley DE: **Democratizing evolutionary biology, lessons from insects.** *Current*
Opinion in Insect Science 2016, **18**:89-92.
39.   Baloglu B, Clews E, Meier R: **NGS barcoding reveals high resistance of a hyperdiverse**
chironomid (Diptera) swamp fauna against invasion from adjacent freshwater reservoirs.
Front Zool 2018, **15**:31.

40. Yeo D, Puniamoorthy J, Ngiam RWJ, Meier R: **Towards holomorphology in entomology:**
rapid and cost-effective adult–larva matching using NGS barcodes. *Systematic Entomology*
2018.
41. Lim NK, Tay YC, Srivathsan A, Tan JW, Kwik JT, Baloglu B, Meier R, Yeo DC: **Next-generation**
freshwater bioassessment: eDNA metabarcoding with a conserved metazoan primer
reveals species-rich and reservoir-specific communities. *Royal Society open science* 2016,
3(11):160635.
42. Srivathsan A, Nagarajan N, Meier R: **Boosting natural history research via metagenomic**
clean-up of crowdsourced feces. *PLoS Biology* 2019, **17**(11):e3000517.
43. Grootaert P: **Revision of the genus Thinophihis Wahlberg (Diptera: Dolichopodidae) from**
Singapore and adjacent regions: A long term study with a prudent reconciliation of a
genetic to a classic morphological approach. *Raffles Bulletin of Zoology* 2018, **66**:413-473.
44. Tang CF, Grootaert P, Yang D: **Protomedetera, a new genus from the Oriental and**
Australasian realms (Diptera, Dolichopodidae, Medeterinae). *ZooKeys* 2018, **743**:137-151.
45. Tang CF, Yang D, Grootaert P: **Revision of the genus Lichtwardtia Enderlein in Southeast**
Asia, a tale of highly diverse male terminalia (Diptera, Dolichopodidae). *ZooKeys* 2018,
798:63-107.
46. Grootaert P: **Species turnover between the northern and southern part of the South China**
Sea in the Elaphropeza Macquart mangrove fly communities of Hong Kong and Singapore
(Insecta: Diptera: Hybotidae). *European Journal of Taxonomy* 2019, **554**:1-27.
47. Samoh AC, Satasook C, Grootaert P: **NGS-barcodes, haplotype networks combined to**
external morphology help to identify new species in the mangrove genus Ngirhaphium
Evenhuis & Grootaert, 2002 (Diptera: Dolichopodidae: Rhaphiinae) in Southeast Asia.
Raffles Bulletin of Zoology 2019, **67**:640-659.
48. Ismay B, Ang YC: **First records of Pseudogaurax Malloch 1915 (Diptera: Chloropidae) from**
Singapore, with the description of two new species discovered with NGS barcodes. *Raffles*
Bulletin of Zoology 2019, **67**:412-420.
49. Wang WY, Yamada A, Eguchi K: **First discovery of the mangrove ant Pheidole sexspinosa**
Mayr, 1870 (Formicidae: Myrmicinae) from the Oriental region, with redescriptions of the
worker, queen and male. *Raffles Bulletin of Zoology* 2018, **66**:652-663.
50. Wang WY, Yong GWJ, Jaitrong W: **The ant genus Rhopalomastix (Hymenoptera: Formicidae:**
Myrmicinae) in Southeast Asia, with descriptions of four new species from Singapore
based on morphology and DNA barcoding. *Zootaxa* 2018, **4532**(3):301-340.
51. Wang WY, Yamada A, Yamane S: **Maritime trap-jaw ants (Hymenoptera, Formicidae,**
Ponerinae) of the Indo-Australian region - redescription of Odontomachus malignus Smith
and description of a related new species from Singapore, including first descriptions of
males. *ZooKeys* 2020, **915**:137-174.
52. Wick RR: **Performance of neural network basecalling tools for Oxford Nanopore**
sequencing. *Genome biology* 2019, **20**:129.
53. Silvestre-Ryan J, Holmes I: **Pair consensus decoding improves accuracy of neural network**
basecallers for nanopore sequencing. *Genome biology* 2021, **22**:38.
54. Chang JJM, Ip YCA, Ng CSL, Huang D: **Takeaways from Mobile DNA Barcoding with**
BentoLab and MinION. *Genes* 2020, **11**:1121.
55. Vereecke N, Bokma J, Haesebrouck F, Nauwynck H, Boyen F, Pardon B, Theuns S: **High**
quality genome assemblies of Mycoplasma bovis using a taxon-specific Bonito basecaller
for MinION and Flongle long-read nanopore sequencing. *BMC Bioinformatics* 2020, **21**:517.
56. Sahlin K, Lim MCW, Prost S: **NGSpeciesID: DNA barcode and amplicon consensus**
generation from long-read sequencing data. *Ecology and evolution* 2021, **11**(3):1392-1398.
57. Ho JKI, Puniamoorthy J, Srivathsan A, Meier R: **MinION sequencing of seafood in Singapore**
reveals creatively labelled flatfishes, confused roe, pig DNA in squid balls, and phantom
crustaceans. *Food Control* 2020, **112**:107144.

58.   Cranston PS, Ang A, Heyzer A, Lim RBH, Wong WH, Woodford JM, Meier R: **The nuisance**
midges (Diptera: Chironomidae) of Singapore's Pandan and Bedok reservoirs. *Raffles*
Bulletin of Zoology 2013, **61**:779-793.
59.   Xu Z, Mai Y, Liu D, He W, Lin X, Xu C, Zhang L, Meng X, Mafofo J, Zaher WA *et al*: **Fast-Bonito:**
A Faster Basecaller for Nanopore Sequencing. *BioRxiv*
2020:doi:10.1101/2020.1110.1108.318535.
60.   Chang JJM, Ip YCA, Bauman AG, Huang D: **MinION-in-ARMS: Nanopore Sequencing to**
Expedite Barcoding of Specimen-Rich Macrofaunal Samples From Autonomous Reef
Monitoring Structures. *Frontiers in Marine Science* 2020, **7**:448.
61.   Menegon M, Cantaloni C, Rodriguez-Prieto A, Centomo C, Abdelfattah A, Rossato M,
Bernardi M, Xumerle L, Loader S, Delledonne M: **On site DNA barcoding by nanopore**
sequencing. *PlOS One* 2017, **12**(10):e0184741.
62.   Wurzbacher C, Larsson E, Bengtsson-Palme J, den Wyngaert SV, Svantesson S, Kristiansson E,
Kagami M, Nilsson RH: **Introducing ribosomal tandem repeat barcoding for fungi.** *Molecular*
ecology resources 2018, **19**(1):118-127.
63.   Krehenwinkel H, Pomerantz A, Henderson JB, Kennedy SR, Lim JY, Swamy V, Shoobridge JD,
Graham N, Patel NH, Gillespie RG *et al*: **Nanopore sequencing of long ribosomal DNA**
amplicons enables portable and simple biodiversity assessments with high phylogenetic
resolution across broad taxonomic scale. *GigaScience* 2019.
64.   Maestri S, Cosetino E, Paterno M, Freitag H, Garces JM, Marcolungo L, Alfano M, Njunjić I,
Schilthuizen M, Slik F *et al*: **A Rapid and Accurate MinION-Based Workflow for Tracking**
Species Biodiversity in the Field. *Genes* 2019, **10**(6):468.
65.   Knot IE, Zouganelis GD, Weedall GD, Wich SA, Rae R: **DNA Barcoding of Nematodes Using**
the MinION. *Frontiers in Ecology and Evolution* 2020, **8**:100.
66.   Seah A, Lim MCW, McAloose D, Prost S, Seimon TA: **MinION-Based DNA Barcoding of**
Preserved and Non-Invasively Collected Wildlife Samples. *Genes* 2020, **11**(4):445.
67.   Daily J: **Parasail: SIMD C library for global, semi-global, and local pairwise sequence**
alignments. *BMC Bioinformatics* 2016, **17**:81.
68.   Sahlin K, Medvedev P: **De Novo Clustering of Long-Read Transcriptome Data Using a**
Greedy, Quality Value-Based Algorithm. *Journal of Computational Biology* 2020, **27**(4):472-
484.
69.   Elbrecht V, Leese F: **Can DNA-Based Ecosystem Assessments Quantify Species Abundance?**
Testing Primer Bias and Biomass—Sequence Relationships with an Innovative
Metabarcoding Protocol. *PLoS One* 2015, **10**(7):e0130324.
70.   Buchner D, Beermann AJ, Leese F, Weiss M: **Cooking small and large portions of**
"biodiversity-soup": Miniaturized DNA metabarcoding PCRs perform as good as large-
volume PCRs. *Ecology and evolution* 2021, **11**(13):9092-9099.
71.   Hickerson MJ, Meyer CP, Moritz: **DNA Barcoding Will Often Fail to Discover New Animal**
Species over Broad Parameter Space. *Systematic Biology* 2006, **55**(5):729-739.
72.   Valan M, Makonyi K, Maki A, Vondráček D, Ronquist F: **Automated Taxonomic Identification**
of Insects with Expert-Level Accuracy Using Effective Feature Transfer from Convolutional
Networks. *Systematic Biology* 2019, **68**(6):876-895.
73.   Wührl I, Pylatiuk C, Giersch M, Lapp F, von Rintelen T, Balke M, Schmidt S, Cerretti P, Meier
R: **DiversityScanner: Robotic discovery of small invertebrates with machine learning**
methods. *BioRxiv* 2021, **doi**:10.1101/2021.1105.1117.444523.
74.   Leray M, Yang JY, Meyer CP, Mills SC, Agudelo N, Ranwez V, Boehm JT, Machida RJ: **A new**
versatile primer set targeting a short fragment of the mitochondrial COI region for
metabarcoding metazoan diversity: application for characterizing coral reef fish gut
contents. *Front Zool* 2013, **10**:34.

75.   Folmer O, Black M, Hoeh W, Lutz R, Vrijenhoek R: **DNA primers for amplification of**
mitochondrial cytochrome c oxidase I from diverse metazoan invertebrates. *Mol Marina*
Biol Technol 1994, **3**(5):294-299.
76.   Geller J, Meyer C, Parker M, Hawk H: **Redesign of PCR primers for mitochondrial**
cytochrome c oxidase subunit I for marine invertebrates and application in all-taxa biotic
surveys. *Molecular ecology resources* 2013, **13**(5):851-861.
77.   Truett G, Heeger P, Mynatt R, Truett A, Walker J, Warman MJB: **Preparation of PCR-quality**
mouse genomic DNA with hot sodium hydroxide and tris (HotSHOT). *Biotechniques* 2000,
29(1):52-54.
78.   Thongjued K, Chotigeat S, Bumrungsri P, Thahakiatkrai P, Kitpipit T: **A new cost-effective and**
fast direct PCR protocol for insects based on PBS buffer. *Molecular ecology resources* 2019,
19(3):691-701.
79.   Arribas P, Andújar C, Hopkins K, Shepherd M, Vogler AP: **Metabarcoding and mitochondrial**
metagenomics of endogean arthropods to unveil the mesofauna of the soil. *Methods in*
Ecology and Evolution 2016, **7**(9):1071-1081.
80.   Crampton-Platt A, Yu DW, Zhou X, Vogler AP: **Mitochondrial metagenomics: letting the**
genes out of the bottle. *GigaScience* 2016, **5**(1):s13742-13016-10120-y.
81.   Zizka VM, Elbrecht V, Macher JN, Leese F: **Assessing the influence of sample tagging and**
library preparation on DNA metabarcodin. *Molecular ecology resources* 2019, **19**(4):893-
899.
82.   Valentini A, Miquel C, Nawaz MA, Bellemain E, Coissac E, Pompanon F, Gielly L, Cruaud C,
Nascetti G, Wincker P *et al*: **New perspectives in diet analysis based on DNA barcoding and**
parallel pyrosequencing: the trnL approach. *Molecular ecology resources* 2009, **9**(1):51-60.
83.   Rohland N, Reich D: **Cost-effective, high-throughput DNA sequencing libraries for**
multiplexed target capture. *Genome research* 2012, **22**:939-946.
84.   Frith MC, Mitsuhashi S, Katoh K: **lamassemble: Multiple Alignment and Consensus**
Sequence of Long Reads. In: *Multiple Sequence Alignment.* Edited by Katoh K. New York:
Humana; 2020: 135-145.
85.   Hamada MY, Ono Y, Asai K, Frith MC: **Training alignment parameters for arbitrary**
sequencers with LAST-TRAIN. *Bioinformatics* 2017, **33**(6):926-928.

1114