PhyloCSF++: A fast and user-friendly implementation of PhyloCSF with annotation tools

Christopher Pockrandt [1,2]*, **Martin Steinegger** [3]* **and Steven L. Salzberg** [1,2,4,5]

[1] Center for Computational Biology, Johns Hopkins University, Baltimore, MD 21211, USA

[2] Department of Biomedical Engineering, Johns Hopkins University, Baltimore, MD 21205, USA

[3] School of Biological Sciences, Seoul National University, Seoul, Republic of Korea

[4] Department of Biostatistics, Johns Hopkins University, Baltimore, USA,

[5] Department of Computer Science, Johns Hopkins University, Baltimore, MD 21211, USA

*The authors contributed equally. To whom correspondence should be addressed.

Abstract

Summary: PhyloCSF++ is an efficient and parallelized C++ implementation of the popular PhyloCSF method to distinguish protein-coding and non-coding regions in a genome based on multiple sequence alignments. It can score alignments or produce browser tracks for entire genomes in the wig file format. Additionally, PhyloCSF++ annotates coding sequences in GFF/GTF files using precomputed tracks or computes and scores multiple sequence alignments on the fly with MMseqs.

Availability: PhyloCSF++ is released under the AGPLv3 license. Binaries and source code are available at `https://github.com/cpockrandt/PhyloCSFpp`. The software can be installed through bioconda. A variety of tracks can be accessed through `ftp://ftp.ccb.jhu.edu/pub/software/phylocsf++/`.

Contact: pockrandt@jhu.edu, martin.steinegger@snu.ac.kr

1 Introduction

Two decades after the first human genome was sequenced, previously unknown genes in human are still being found [7]. For many less-studied organisms the situation is even more uncertain, as their protein-coding gene catalogues remain sparse.

An established method that uses evolutionary conservation to detect protein-coding regions is PhyloCSF [4]. It takes a multiple sequence alignment (MSA) and a phylogenetic tree of related species as input and computes a score, based on codon substitution rates and codon frequencies, reflecting the likelihood for the region to be coding or non-coding. As examples of its recent application, PhyloCSF scores (available as genomic tracks) were used to identify 133 novel protein coding genes in human [5] and to investigate the conservation of the newly emerged ORF10 in *SARS-CoV2* [2]. Currently, there are tracks available for *H.sapiens*, *M.musculus*, *G.gallus*, *C.elegans*, *D.melanogaster*, *A.gambiae* and *SARS-CoV-2*.

Here we present the free open-source software PhyloCSF++, a fast multi-threaded implementation of PhyloCSF that additionally to scoring alignments directly produces genome tracks, and allows users to annotate GFF files with PhyloCSF scores. We used PhyloCSF++ to generate tracks

for 5 additional species and made them available for the UCSC genome browser [3][1].

2 Methods

The original PhyloCSF tool was developed in OCaml and requires older versions of the OCaml compiler and libraries. No binary version (ideally with statically linked libraries) is available, which makes it challenging for users to compile and run the original implementation of PhyloCSF. Computing tracks and posterior probabilities requires additional scripts [5] and coding, and multi-threading is not supported.

PhyloCSF is a valuable method that after 10 years still plays an important role in the discovery of novel genes, hence we created PhyloCSF++, a new implementation of the algorithm in C++ that is more efficient and that adds parallelization. Multi-threading allows one to process large MSAs of eukaryotic genomes. It can be installed on any UNIX system with $gcc \geq 4.9$ and *cmake*, and only depends on the GNU

---

[1] `ftp://ftp.ccb.jhu.edu/pub/software/phylocsf++/hub.txt`

Fig. 1. PhyloCSF++ (a) The command *build-tracks* of PhyloCSF++ takes a whole-genome MSA of related species as input and produces six tracks, one for each reading frame. Additionally, a confidence track is outputted. Each track is stored as wig file and consists of normalized posterior probability scores within the range ±15 for each codon of the input MSA. Positive scores indicate coding and negative scores indicate non-coding regions. (b) The command *annotate-with-tracks* scores coding sequences (CDS) from a GFF file using PhyloCSF tracks. (c) Alternatively, CDS can be scored without tracks using MMSeqs [8] and a set of genome sequences. MMSeqs will perform a search and generate a MSA of all CDS, which then will be scored by PhyloCSF++. (d) Comparison of PhyloCSF and PhyloCSF++ tracks. Both produce nearly equal scores with a Pearson correlation coefficient of 0.999. (e) Speed comparison for generating tracks of PhyloCSF (blue) and PhyloCSF++ single threaded (dark green) and multi threaded (green) for the first 50 alignments of the 100way alignment of chr22 of GRCh37 with the 100vertebrates model in seconds.

scientific library [1]. Statically linked binaries are available for download, or can be installed via bioconda.

3 Results

Score computation. PhyloCSF++ offers all three PhyloCSF modes (fixed, mle and omega) that compute the likelihood of a region to be coding or non-coding. All three modes are faster than PhyloCSF and fully parallelized. In a benchmark on alignments from a 100-way multiz alignment of hg19 on the 100vertebrates model, PhyloCSF++ was faster by a factor of 1.1, 1.3 and 2.0 for all three modes with a single thread compared to PhyloCSF on a consumer laptop (see Fig. 1e). The maximum likelihood estimation as well as the omega mode (that only requires a phylogenetic tree and no training data) have randomized algorithms and can lead to minor differences in computed scores compared to the reference implementation.

Track building. In contrast to the original implementation of PhyloCSF, PhyloCSF++ offers a direct way to build tracks. For *C. elegans* we recomputed the tracks and got effectively the same scores for all codons and all frames, with a Pearson correlation coefficient of 0.999. Fig. 1d shows a dot plot of 10^6 sampled positions across all frames. Small differences are due to randomization in initializing the HMM for computing posterior probabilities.

GFF annotation with tracks. To simplify the evaluation of PhyloCSF scores, the tracks can be used to annotate CDS features in a GFF file. For each CDS feature and its corresponding transcript, PhyloCSF scores as well as confidence scores are computed by taking the mean over all codons.

GFF annotation with MMseqs. If tracks or a whole-genome MSA are not available, a GFF file can be annotated by aligning only the CDS to a set of reference genomes on the fly using MMseqs. MMseqs computes and chains MSAs directly for the transcripts of interest without the need for a whole-genome multiple sequence alignment, which would require a much greater computing resource than aligning only the CDS.

Tracks. We generated new tracks for the following species: rat (rn6), fugu (fr3), stickleback (gasAcu1), tarsier (tarSyr2) and yeast (sacCer3). Each

of these tracks is available for download and also accessible through the UCSC genome browser.

Conclusion

PhyloCSF++ was developed to make the discovery of novel genes for many species faster and easier. Additional features to the original PhyloCSF software allow users to directly build tracks from whole-genome MSAs. Furthermore, PhyloCSF++ can directly annotate GFF files using computed tracks, or if no whole-genome MSAs are available, quickly compute MSAs using MMseqs.

In summary, we hope that the software will prove helpful to detect novel protein sequences in already well-studied genomes and also prove useful for the large and growing number of new genomes [6].

Funding

This work was supported in part by grant IOS-1744309 from the National Science Foundation, and grant R01-HG006677 from the U.S. National Institutes of Health. Martin Steinegger acknowledges support from the National Research Foundation of Korea grant [2019R1A6A1A10073437, NRF-2020M3A9G7103933]; and the Creative-Pioneering Researchers Program through Seoul National University.

References

[1] M. Galassi et al. Gnu scientific library reference manual, 1996.

[2] I. Jungreis et al. SARS-CoV-2 gene content and COVID-19 mutation impact by comparing 44 sarbecovirus genomes. Sept. 2020.

[3] W. J. Kent et al. The human genome browser at UCSC. *Genome Res.*, 12(6):996–1006, June 2002.

[4] M. F. Lin et al. PhyloCSF: a comparative genomics method to distinguish protein coding and non-coding regions. *Bioinformatics*, 27(13):i275–82, July 2011.

[5] J. M. Mudge et al. Discovery of high-confidence human protein-coding genes and exons by whole-genome PhyloCSF helps elucidate 118 GWAS loci. *Genome Res.*, 29(12):2073–2087, Dec. 2019.

[6] A. Rhie et al. Towards complete and error-free genome assemblies of all vertebrate species. May 2020.

[7] S. L. Salzberg. Open questions: How many genes do we have? *BMC Biol.*, 16(1):94, Aug. 2018.

[8] M. Steinegger et al. MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. *Nat. Biotechnol.*, 35(11):1026–1028, Nov. 2017.