Community Evaluation of Glycoproteomics Informatics Solutions Reveals High-Performance Search Strategies of Serum *N*- and *O*-Glycopeptide Data

Rebeca Kawahara[1], Anastasia Chernykh[1], Kathirvel Alagesan[2], Marshall Bern[3], Weiqian Cao[4], Robert J. Chalkley[5], Kai Cheng[6], Matthew S. Choo[7], Nathan Edwards[8,9], Radoslav Goldman[8,9,10], Marcus Hoffmann[11], Yingwei Hu[12], Yifan Huang[13], Jin Young Kim[14], Doron Kletter[3], Benoit Liquet-Weiland[15,16], Mingqi Liu[4], Yehia Mechref[13], Bo Meng[17], Sriram Neelamegham[6], Terry Nguyen-Khuong[7], Jonas Nilsson[18], Adam Pap[19,20], Gun Wook Park[14], Benjamin L. Parker[21], Cassandra L. Pegg[22], Josef M. Penninger[23,24], Toan K. Phung[22], Markus Pioch[11], Erdmann Rapp[11,25], Enes Sakalli[23], Miloslav Sanda[8,10], Benjamin L. Schulz[22], Nichollas E. Scott[26], Georgy Sofronov[15], Johannes Stadlmann[23], Sergey Y. Vakhrushev[27], Christina M. Woo[28], Hung-Yi Wu[28], Pengyuan Yang[4], Wantao Ying[17], Hui Zhang[12], Yong Zhang[17], Jingfu Zhao[13], Joseph Zaia[29], Stuart M. Haslam[30], Giuseppe Palmisano[31], Jong Shin Yoo[14,32], Göran Larson[33], Kai-Hooi Khoo[34], Katalin F. Medzihradszky[5,19], Daniel Kolarich[2], Nicolle H. Packer[1,2,35], and Morten Thaysen-Andersen[1,35]*

[1]Department of Molecular Sciences, Macquarie University, Sydney, NSW, Australia

[2]Institute for Glycomics, Griffith University Gold Coast Campus, QLD, Australia

[3]Protein Metrics Inc., Cupertino, CA, United States of America

[4]Institutes of Biomedical Sciences, and the NHC Key Laboratory of Glycoconjugates

Research, Fudan University, Shanghai, China

[5]UCSF, School of Pharmacy, Department of Pharmaceutical Chemistry, San Francisco, CA,

United States of America

[6]State University of New York, Buffalo, NY, United States of America

[7]Analytics Group, Bioprocessing Technology Institute, Agency for Science, Technology and

Research, Singapore

[8]Clinical and Translational Glycoscience Research Center (CTGRC), Georgetown University,

Washington, DC, United States of America

[9]Department of Biochemistry and Molecular & Cellular Biology, Georgetown University,

Washington, DC, United States of America

[10]Department of Oncology, Georgetown University, Washington, DC, United States of

America

[11]Max Planck Institute for Dynamics of Complex Technical Systems, Bioprocess

Engineering, Magdeburg, Germany

[12]Department of Pathology, The Johns Hopkins University, Baltimore, MD, United States of

America

[13]Department of Chemistry and Biochemistry, Texas Tech University, TX, United States of

America

[14]Research Center of Bioconvergence Analysis, Korea Basic Science Institute, Republic of

Korea

[15]Department of Mathematics and Statistics, Macquarie University, Sydney, NSW, Australia

[16]CNRS, Laboratoire de Mathématiques et de leurs Applications de PAU, E2S-UPPA, Pau,

France

[17]State Key Laboratory of Proteomics, Beijing Institute of Lifeomics, Beijing Proteome

Research Center, National Center for Protein Sciences (Beijing), Beijing, China

[18]Proteomics Core Facility, Sahlgrenska academy, University of Gothenburg, Gothenburg,

Sweden

[19]BRC, Laboratory of Proteomics Research, Szeged, Hungary

[20]Doctoral School in Biology, Faculty of Science and Informatics, University of Szeged,

Szeged, Hungary

[21]Department of Anatomy and Physiology, University of Melbourne, Melbourne, VIC,

Australia

[22]School of Chemistry and Molecular Biosciences, University of Queensland, QLD, Australia

[23]IMBA, Institute of Molecular Biotechnology of the Austrian Academy of Sciences, Vienna,

Austria

[24]Department of Medical Genetics, Life Sciences Institute, University of British Columbia,

Vancouver, BC, Canada

[25]glyXera GmbH, Magdeburg, Germany

[26]Deparment of Microbiology and Immunology, University of Melbourne, Melbourne, VIC,

Australia

[27]Copenhagen Center for Glycomics, Department of Cellular and Molecular Medicine,

University of Copenhagen, Copenhagen, Denmark

[28]Department of Chemistry and Chemical Biology, Harvard University, Cambridge, MA,

United States of America

[29]Department of Biochemistry, Boston University Medical Campus, Boston, MA, United

States of America

[30]Department of Life Sciences, Imperial College London, London, UK

[31]Instituto de Ciências Biomédicas, Departamento de Parasitologia, Universidade de São

Paulo, São Paulo, SP, Brazil

[32]Graduate School of Analytical Science and Technology, Chungnam National University,

Daejeon, Republic of Korea

[33]Department of Laboratory Medicine, Sahlgrenska Academy, University of Gothenburg,

Gothenburg, Sweden

[34]Institute of Biological Chemistry, Academia Sinica, Taipei, Taiwan

[35]Biomolecular Discovery Research Centre, Macquarie University, Sydney, NSW, Australia

Running title: High-performance search strategies of serum glycoproteomics data

Keywords: Glycoproteomics, glycopeptide, *N*-glycosylation, *O*-glycosylation, informatics,

software, search engine, mass spectrometry

*Corresponding author:

Dr Morten Thaysen-Andersen, PhD

Department of Molecular Sciences

Biomolecular Discovery Research Centre

Faculty of Science & Engineering

Macquarie University - Sydney

NSW-2109, Australia

Abstract

Glycoproteome profiling (glycoproteomics) is a powerful yet analytically challenging

research tool. The complex tandem mass spectra generated from glycopeptide mixtures

require sophisticated analysis pipelines for structural determination. Diverse software aiding

the process have appeared, but their relative performance remains untested. Conducted

through the HUPO Human Proteome Project – Human Glycoproteomics Initiative, this

community study, comprising both developers and users of glycoproteomics software,

evaluates the performance of informatics solutions for system-wide glycopeptide analysis.

Mass spectrometry-based glycoproteomics datasets from human serum were shared with all

teams. The relative team performance for *N*- and *O*-glycopeptide data analysis was

comprehensively established and validated through orthogonal performance tests. Excitingly,

several high-performance glycoproteomics informatics solutions were identified. While the

study illustrated that significant informatics challenges remain, as indicated by a high

discordance between annotated glycopeptides, lists of high-confidence (consensus)

glycopeptides were compiled from the standardised team reports. Deep analysis of the

performance data revealed key performance-associated search variables and led to

recommendations for improved "high coverage" and "high accuracy" glycoproteomics search

strategies. This study concludes that diverse software for comprehensive glycopeptide data

analysis exist, points to several high-performance search strategies, and specifies key

variables that may guide future software developments and assist informatics decision-

making in glycoproteomics.

Introduction

Protein glycosylation, the attachment of complex carbohydrates (glycans) to discrete sites on proteins, plays diverse roles in biology[1]. Glycoproteomics, the system-wide analysis of intact glycopeptides, has evolved from proteomics and glycomics by the recognised benefits of concertedly studying glycan structures, modification sites and protein carriers at scale within a single experiment[2, 3].

Facilitated by recent advances in separation science, mass spectrometry (MS) and informatics, glycoproteomics has matured over past decades and is now ready to tackle biological questions and generate new insights into the heterogeneous glycoproteome in biological systems[4-7]. While glycoproteomics studies now routinely report thousands of *N*- and *O*-glycopeptides[8], accurate identification of glycopeptides from large volumes of mass spectral data remains a bottleneck. The annotation process of glycopeptide MS/MS data is highly error-prone due to the challenging task of correctly assigning both the glycan composition, modification site(s) and peptide carrier[9-11]. As a result, glycopeptides reported in glycoproteomics papers are frequently misidentified or suffer from ambiguous annotation even in studies attempting to control the false discovery rate (FDR) of assignments.

Diverse fragmentation modes including resonance-activation collision-induced dissociation (CID), beam-type CID (higher-energy collisional dissociation, HCD) and electron-transfer dissociation (ETD) have proven valuable for glycoproteomics[12-15]. When applied in concert, now possible, for example, on Orbitrap Tribrid mass spectrometers, these fragmentation strategies provide complementary structural information of glycopeptides. Briefly, HCD-MS/MS informs on the peptide carrier and produces useful diagnostic glycan fragments enabling glycopeptide classification and deduction of generic glycan compositions, ETD-MS/MS reveals in favourable cases the modification site and peptide identity, while resonance-activation CID-MS/MS informs primarily on the glycan composition, sequence

and topology[16, 17]. Hybrid-type fragmentation strategies including ETciD and EThcD are

becoming popular given their ability to generate information-rich glycopeptide spectra

containing multiple fragment types[18]. Accurate mass measurements (<5-10 ppm) at high

resolution of precursor and product ions available on most contemporary instruments are

essential in glycoproteomics. Despite these exciting advances, unambiguous glycopeptide

identification remains challenging. Informatics advances are therefore required to ensure

accurate glycoproteome profiling to further the field[19].

Glycoproteomics has experienced the development of diverse commercial and academic

software showing promise for precise annotation and identification of glycopeptides from

MS/MS data[20, 21]. While some of these tools are already well-established and widely applied

in glycoproteomics[22], the relative performance of software available to the community remain

untested leaving a critical knowledge gap that hinders rapid progress in the field.

Facilitated by the HUPO Human Proteome Project – Human Glycoproteomics Initiative

(HPP-HGI), we here perform a comprehensive community-based evaluation of existing

informatics solutions for large-scale glycopeptide analysis. While informatics challenges

undoubtedly still exist in glycoproteomics, our study highlights that several computational

tools, some already demonstrating high performance, others considerable potential, are

available to the community. Importantly, key performance-associated search parameters and

high-performance search strategies were identified, findings that may aid software developers

and users to improve the challenging glycoproteomics data analysis in the immediate future.

162
Results

Study design and overview

Two glycoproteomics data files (File A-B) of human serum were acquired (**Figure 1a**). A

synthetic *N*-glycopeptide was included as a positive control. File A-B were generated using

HCD-ETciD-CID-MS/MS and HCD-EThcD-CID-MS/MS, respectively, to accommodate

most search engines. Serum is a well-characterised biospecimen displaying profound

heterogeneity of *N*- and *O*-glycoproteins[23-25]. Thus, File A-B displayed characteristics (file

size, complexity, type) similar to data typically encountered in glycoproteomics[26-29].

File A-B were shared with all 22 participating teams who classified themselves as developers

(9 teams) or users (13 teams) of glycoproteomics software (**Figure 1b**, **Extended Data**

Figure 1a-b). All teams identified *N*- and *O*-glycopeptides from File A-B and reported their

approaches and identifications in a standardised reporting template. Most developers (five

teams) and users (eight teams) were experienced in glycoproteomics (>10 years). Participants

were from North and South America, Europe, Asia, and Oceania, (**Extended Data Figure**

1c-d).

Only File B was processed by all teams (**Extended Data Figure. 1e**). While most

participants reported on spectra acquired with multiple fragmentation methods, a few teams

used only HCD- or EThcD-MS/MS for the identifications (**Extended Data Figure 1f-g**).

Participants used diverse search engines (**Figure 1b**, **Extended Data Figure 1h**). Some

search engines were used as stand-alone tools or with other software while others were

applied with pre-/post-processing tools to aid the identification (**Extended Data Figure 1i**).

The developers used 9 different glycopeptide-centric search engines including Team 1: IQ-

GPA v2.5[30], Team 2: Protein Prospector v5.20.23[31], Team 3: glyXtool[MS] v0.1.4[32], Team 4:

Byonic v2.16.16[33], Team 5: Sugar Qb[34], Team 6: Glycopeptide Search v2.0alpha[35], Team 7:

GlycopeptideGraphMS v1.0[36]/Byonic[33], Team 8: GlycoPAT v2.0[37], Team 9: GPQuest v2.0[38].

Amongst the 13 users, 10 teams (~75%) used Byonic (Team 10, 11, 13, 15-18, 20-22), while

only few teams used Protein Prospector (Team 12), SugarQB/Sequest HT (Team 14), and

Mascot (Team 19) (**Supplementary Table 1**).

File A/B contained 8,737/9,776 HCD-MS/MS scans of which 5,485/6,148 (~63%) spectra contained glycopeptide-specific oxonium ions (e.g. *m/z* 204.0867) used for ETciD-/EThcD-/CID-MS/MS triggering (**Extended Data Figure 2a-b**). Amongst all potential glycopeptide MS/MS spectra (File A/B, 16,445/18,444, considering all fragmentation modes), 3,402/4,982 (20.7%/27.0%) non-redundant (unique) glycopeptide-to-spectrum matches (glycoPSMs) were collectively reported by participants. Most teams reported on HCD- and EThcD-MS/MS data, while only few teams used CID- and ETciD-MS/MS. Similar charge distribution (most frequently quadruply-charged precursors) was observed for glycopeptides reported from different fragmentation modes (**Extended Data Figure 2c-d**).

A wealth of data was collected via a comprehensive reporting template. The team reports covered intricate details of the employed search strategies and identified glycopeptides (**Figure 1c**). Details of the applied search settings were captured including permitted peptide modifications, mass tolerance, post-search filtering criteria (**Supplementary Table 1**), and glycan search space (**Supplementary Table 2**). The search settings (SS1-SS13, **Table 1**) varied considerably across teams.

Additionally, diverse output data arising from the glycopeptide identifications were captured (**Supplementary Table 3**). The output data also varied across teams (**Supplementary Table 4**). Analysis of key search output variables (SO1-SO9, **Table 1**) revealed that the reported *N*- and *O*-glycopeptides, as expected, showed different characteristics (e.g. LC retention time, glycan mass) while other characteristics (e.g. observed precursor *m/z*) were similar between the two analyte classes (**Extended Data Figure 3**). Analysis of SO1-SO9 data also demonstrated that some teams reported highly discrepant output. For example, and without being able to link these observations to performance, the developers of Glycopeptide Search (Team 6) and GlycopeptideGraphMS (Team 7) reported glycopeptides with unusually low (z = ~3+) and high (~5.5+) charge states relative to other teams (~4.5+) (**Extended Data Figure**

3c). These output data comparisons may be valuable for developers to better understand,

further develop, and ultimately improve their software.

The team performance was assessed using orthogonal performance tests that served to

comprehensively evaluate the glycopeptide identification accuracy (specificity) and

glycoproteome coverage (sensitivity), two key performance characteristics in

glycoproteomics (**Figure 1d**). Six (N1-N6) and five (O1-O5) performance tests were

carefully designed to assess the relative performance for *N*- and *O*-glycopeptide data analysis

across teams (**Table 1**, **Supplementary Table 5-15**). Firstly, the ability to detect the

synthetic *N*-glycopeptide in the datasets was assessed (N1). Further, the glycan compositions

(N2, O1) and source glycoproteins (N3, O2) of reported glycopeptides were compared to the

established serum glycome and against known serum glycoproteins[4, 23, 39-42]. To validate the

use of literature to score teams, we performed manual site-specific glycoprofiling of four

serum glycoproteins i.e. alpha-1-antitrypsin (A1AT), ceruloplasmin (CP), haptoglobin (HP)

and immunoglobulin G1 (IgG1) and showed an excellent agreement (R^2 = 0.85-0.99) with

relevant literature of healthy human serum[43-46] (**Extended Data Figure 4**). The

glycoproteome coverage was simply the reported non-redundant glycopeptides (N4, O3).

Finally, the ability to identify glycopeptides commonly reported by most teams ("consensus

glycopeptides") (N5, O4) and free of NeuGc and multi-Fuc features (N6, O5) was also

scored. We ensured that NeuGc and multi-Fuc glycopeptides, unexpected glycofeatures in

human serum[23, 47-49], were indeed absent or rarely detected in File A-B (discussed below)

allowing these to be deemed putative false positives for the purpose of scoring teams

(**Extended Data Figure 5**).

The performance tests were used to score and rank teams (**Figure 1e**, **Supplementary Table**

16). The developer and user groups were not compared since they received different study

instructions. The team scoring was validated using an independent glycoprotein-centric site-

specific profiling test (**Supplementary Table 17**). Finally, performance data from both team-

wide and search engine-centric approaches revealed performance-associated search variables

and led to improved glycoproteomics search strategies (**Supplementary Table 18-19**).

Overview of the reported glycopeptides

The below analyses were carried out using data reported from File B processed by all teams.

The total *N*-glycoPSMs (49-2,122) and source glycoproteins (9-168) reported by the 22 teams

varied dramatically (**Figure 2a**, **Supplementary Table 3**). In line with literature of human

serum *N*-glycosylation[23, 24], the reported *N*-glycopeptides carried mainly complex-type *N*-

glycans (92.6%, average across teams) while relatively few oligomannosidic (6.4%) and

truncated ($Hex_{<4}HexNAc_{<4}$) (1.0%) *N*-glycopeptides were reported. The applied *N*-glycan

search space spanned an equally wide range (23-381 compositions) comprising mostly

complex-type *N*-glycans (89.1%) and the less heterogeneous oligomannosidic (5.9%) and

truncated (5.0%) *N*-glycans. No associations were found between the size of the *N*-glycan

search space and reported *N*-glycoPSM counts (Pearson R^2 = 0.115). Unexpected glycan

compositions including NeuGc- and multi-Fuc-containing complex-type *N*-glycans, which

are negligible features of human serum glycoproteins[23,47-49], were not only included in the

glycan search space (up to 26.5% and 28.9%, respectively), but also reported (up to 20.6%

and 5.0%) by some teams. The absence of NeuGc and rarity of multi-Fuc glycopeptides in

the shared data was supported by a lack of diagnostic fragment ions for NeuGc (*m/z*

290/308), scarcity of antenna Fuc ions (*m/z* 512/803) and the frequent mis-annotation of

MS/MS spectra claimed to correspond to NeuGc and multi-Fuc glycopeptides (**Extended**

Data Figure 5). While only infrequently detected, multi-Fuc glycopeptides were, however,

evidently present in our data as supported by manual spectral annotation (**Extended Data**

Figure 5d).

Collectively, 2,556 unique *N*-glycopeptides (defined herein as unique peptide sequences and glycan compositions), covering 320 different source *N*-glycoproteins and 424 different *N*-glycan compositions were reported across teams (**Figure 2b**, **Supplementary Table 6-7**, **9**). Of these, only 43 *N*-glycopeptides (1.7%), 26 source *N*-glycoproteins (8.1%) and 28 *N*-glycan compositions (6.6%) were commonly reported by at least 75% of teams (see **Extended Data Figure 6a** for an example of congruent spectral annotation across teams). Most glycopeptides, however, were commonly reported by only few teams likely due to frequent mis-annotation of the spectral data (**Extended Data Figure 6b**).

Significantly fewer, but equally discrepant, *O*-glycopeptides (5-578 *O*-glycoPSMs) were reported by participants (**Figure 2c**, **Extended Data Figure 3i**). As expected, most reported *O*-glycopeptides carried $\text{Hex}_1\text{HexNAc}_1\text{NeuAc}_{1\text{-}2}$[40, 50]. The applied *O*-glycan search space also varied dramatically (3-223 glycan compositions). Similar to the *N*-glycopeptide analysis, no association was observed between the *O*-glycan search space and reported *O*-glycoPSM counts (Pearson R^2 = 0.118). Instead, many other associations were identified (discussed below). While seven teams included NeuGc in the applied *O*-glycan search space (up to 9.0%), only four teams reported NeuGc *O*-glycopeptides (up to 7.3%). In addition, 12 teams included multi-fucosylated glycans in the *O*-glycan search space (up to 43.5%); 11 of those teams reported multi-fucosylated *O*-glycopeptides (average of 28.6%, up to 61.8%). Both NeuGc and multi-fucosylated *O*-glycans are negligible features of human serum *O*-glycoproteins as supported by literature[40, 50] and our own analyses (see above). The reported multi-fucosylated *O*-glycan compositions could, in principle, in some cases arise from multiple discrete *O*-glycans residing on the same peptide. Since *O*-glycosylation sites were inconsistently and/or ambiguously reported by most teams (see below) we were not able to assess this aspect further.

Collectively, 1,192 unique *O*-glycopeptides covering 231 different source *O*-glycoproteins

and 288 different *O*-glycan compositions were identified, but surprisingly few *O*-

glycopeptides were commonly reported across teams. Only 3 *O*-glycopeptides (0.3%), 6

source *O*-glycoproteins (2.6%) and 7 *O*-glycan compositions (2.4%) were commonly

reported by at least half the teams (**Figure 2c**). Most *O*-glycopeptides were reported by a

single or few teams.

Despite the discrepant reporting, high-confidence lists spanning 163 *N*- and 23 *O*-

glycopeptides commonly reported by teams could be generated. Importantly, these consensus

glycopeptides mapped to expected serum glycoproteins e.g. α-2-macroglobulin (UniProtKB,

P01023) and haptoglobin (P00738) and carried expected serum *N*-glycans e.g.

$Hex_5HexNAc_4Fuc_{0-1}NeuAc_2$ (GlyTouCan IDs, G09675DY/G22754FQ) and *O*-glycans e.g.

$Hex_1HexNAc_1NeuAc_{1-2}$ (G65285QO/G84906ML) that were biosynthetically related

(**Extended Data Figure 7**), devoid of NeuGc and poor in multi-Fuc further supporting their

correct identification. These high-confidence glycopeptides form an important reference to

future studies of the human serum glycoproteome and have therefore been made publicly

available (GlyConnect Reference ID 2943).

High-performance informatics solutions for N-glycoproteomics

The relative team performance for *N*-glycoproteomics was comprehensively assessed using

six independent performance tests (N1-N6) (**Table 1**, **Supplementary Table 5-10**). Amongst

these performance tests, N1 scored the ability to accurately identify a synthetic *N*-

glycopeptide in the sample (**Extended Data Figure 8**). Similar to the other performance

tests, N1 was used to establish the relative team performance. Founded on a "ground truth",

the N1 data including the 12 manually annotated spectra all corresponding to the synthetic *N*-

glycopeptide are particularly informative and may aid developers train algorithms and

improve software to better annotate *N*-glycopeptide spectral data. The N1 data also supported

observations made across the entire dataset (**Extended Data Figure 2**) confirming that

glycopeptides were preferentially identified in charge state 4+ using HCD- and EThcD-

MS/MS even when high-quality MS/MS data from other charge states and fragmentation

modes were available.

In line with literature[2, 8], most teams employed HCD- and/or EThcD-MS/MS for

glycopeptide identification. While these two fragmentation modes displayed similar

performance in tests scoring the glycan composition (N2, O1) and glycoproteome coverage

(N4, O3), higher scores were achieved for EThcD- relative to HCD-based identifications in

the source glycoprotein tests (N3, O2) (**Extended Data Figure 9**). Importantly, accurate

glycosylation site localisation, not tested with this study (discussed below), is a recognised

strength of EThcD-MS/MS data[5, 12].

The performance tests were used to score and rank developers and users (**Figure 3a**). At a

glance, the scorecard pointed to considerable team-to-team variations in the performance

profiles suggesting that the applied software and search strategies exhibit markedly different

strengths and weaknesses for *N*-glycoproteomics. As an example, IQ-GPA (Team 1) and

GlycoPAT (Team 8) performed well (relative to other developers) in the *N*-glycan

composition test (N2), while Protein Prospector (Team 2) and Byonic (Team 4) performed

well in tests scoring the source *N*-glycoproteins (N3) and *N*-glycoproteome coverage (N4).

Overall, Protein Prospector (Team 2, overall score 0.682), Byonic (Team 4, 0.676) and

GlycoPAT (Team 8, 0.647) were found to be high-performance software solutions for *N*-

glycoproteomics. Notably, our scoring did not separate these three developers by any

significant margin, but their overall performance was slightly higher than IQ-GPA (Team 1,

0.621) and glyXtool[MS] (Team 3, 0.580) and substantially higher than other software (score

range 0.296-0.366).

Supporting our scoring method, an independent assessment method based on the match

between reported and actual site-specific *N*-glycoforms of four serum glycoproteins (A1AT,

CP, HP, IgG1, thus founded on a "ground truth") recapitulated the scoring profile across

teams ($R^2 = 0.82$) (**Extended Data Figure 10**). Further supporting the top ranking of Byonic

and Protein Prospector, the best performing user teams employed Byonic (Team 11, 13, 15,

score range 0.687-0.777) and Protein Prospector (Team 12, 0.709). Their overall performance

scores were marginally higher than seven other Byonic users (Team 10, 16-18, 20-22, 0.593-

0.679), but markedly higher than teams using SugarQb (Team 14, 0.172) and Mascot (Team

19, 0.413). Despite the similar overall performance amongst most user teams, not least the 10

Byonic users, their performance profiles differed markedly across the six performance tests.

We then explored the scorecard for software-independent performance-associated variables

including the search settings (SS1-SS13) and search output (SO1-9) using seven different

statistical methods (**Figure 3b**). Many statistically strong relationships were found revealing

key performance-associated variables that either positively or negatively correlated with the

glycopeptide identification efficiency. As an example, the use of decoy/contaminant

databases (SS13) showed associations with performance in the synthetic *N*-glycopeptide test

(N1) and high *N*-glycoproteome coverage (N4). Search strategies that allowed for a relatively

high diversity and number of non-glycan variable peptide modifications (SS8, SS10) and few

glycans per peptide (SS9) were also associated with high *N*-glycoproteome coverage (N4).

As expected, allowing multiple missed peptide cleavages (SS7) and variable non-glycan

modifications (SS10) in the search strategy correlated with higher glycopeptide FDRs as

indicated by higher rates of NeuGc and multi-Fuc identifications (low N6 scores)

(**Supplementary Table 18**).

The association analyses also identified many interesting relationships between the search

output and performance (**Figure 3b**). Intuitively, teams that reported many *N*-glycoPSMs

(SO9) performed well in the synthetic *N*-glycopeptide test (N1), had a higher *N*-

glycoproteome coverage (N4) and identified more consensus *N*-glycopeptides (N5). Further,

teams that reported glycopeptides featuring a relatively high glycan mass (SO8) more often

identified the correct glycan composition (N2), while teams that reported glycopeptides

exhibiting relatively high molecular masses (SO5) more often identified the correct source *N*-

glycoproteins (N3). Glycopeptides displaying relatively high molecular masses (large glycans

and/or peptides) are less likely to be incorrectly identified due to fewer theoretical

glycopeptide candidates (fewer potential false positives) in the higher mass range. In

addition, early LC retention time (SO1), high charge (SO3), high glycopeptide mass (SO5),

high actual mass error (low mass accuracy, SO6) and high glycan mass (SO8) were search

output linked to high *N*-glycoproteome coverage (N4). Teams reporting *N*-glycopeptides with

high molecular masses (SO5) more often identified consensus glycopeptides (N5). Finally,

low actual mass error (SO6) was, as expected, associated with better identification accuracy.

High-performance informatics solutions for O-glycoproteomics

Protein Prospector (Team 2) displayed the highest performance in tests scoring the source *O*-

glycoproteins (O2) and consensus *O*-glycopeptides (O4) (**Figure 3c**, **Supplementary Table**

16). Conversely, IQ-GPA (Team 1) and glyXtool^MS (Team 3) were the best performing

software in tests scoring the *O*-glycan compositions (O1) and *O*-glycoproteome coverage

(O3), respectively. Overall, Protein Prospector (Team 2, overall score 0.613) and glyXtool^MS

(Team 3, 0.522) were found to be high-performance software for *O*-glycoproteomics.

Amongst the users, four Byonic teams (Team 13, 15, 17, 18, overall score range 0.473-0.701)

were ranked in the high-performance band.

Correlation analyses showed that accurate identification of the *O*-glycan compositions (O1)

associated with approaches using a focused (narrow) *O*-glycan search space (SS2) and

permitting only few missed peptide cleavages (SS7) (**Figure 3d**, **Supplementary Table 18**).

In addition, search strategies permitting incorrect precursor selection (SO4) were commonly

used by teams scoring well in the *O*-glycan composition test (O1). Interestingly, employing a

broad *O*-glycan search space (SS2) was associated with accurate identification of source *O*-

glycoproteins (O2), high *O*-glycoproteome coverage (O3), and better identification of

consensus *O*-glycopeptides (O4). Further, teams reporting identifications with low mass error

(SO6) scored well in the *O*-glycan composition test (O1), but, notably, at the cost of lower *O*-

glycoproteome coverage (O3) and fewer consensus *O*-glycopeptides (O4).

Search engine-centric analysis

We then explored the impact of different search strategies on the glycoproteomics data output

for the popular Byonic search engine used by 11 teams. The Byonic teams employed highly

diverse search strategies; except for the common use of decoy/contaminant databases (SS13)

and monoisotopic correction (SS14), the search settings varied considerably across these

teams (**Figure 4a**). Undoubtedly, this search diversity and different output filtering methods

used by the Byonic teams (e.g Byonic score >100, PEP-2D < 0.001, FDR < 1%) contributed

to the dramatic variation in reported glycopeptides (**Figure 4b**, **Supplementary Table 1**).

Unsurprisingly, therefore, the relative specificity (accuracy) and sensitivity (coverage) scores

(established from N1-N6/O1-O5) showed different performance profiles of the Byonic teams

particularly for the *O*-glycopeptide analysis (**Figure 4c**, **Supplementary Table 16**). Teams

achieving better-than-average sensitivity scores (e.g. Team 15, 17), typically under-

performed with respect to specificity. Other teams achieved higher-than-average specificity

scores at the cost of sensitivity (e.g. Team 18, 22), confirming the intuitive reciprocal

relationship between these performance metrics.

The individual search variables were then investigated through a series of controlled (in-

house) searches using Byonic. For this purpose, the search settings were systematically varied

from the "Default" search strategy used by most teams while keeping other parameters

constant. Several search settings showed performance gains in terms of improved specificity

(e.g. literature-guided narrow glycan search space, SS1-SS2) or sensitivity (e.g. decoy

database disabled, SS13), but often at the expense of other performance characteristics

(**Figure 4d-e**, **Supplementary Table 19a**). While reduced sensitivity (glycoproteome

coverage) may be an acceptable compromise for higher specificity (identification accuracy),

the opposite arguably does not hold true. Thus, the significant sensitivity gains and

concomitant loss in specificity achieved by disabling the decoy database (SS13), did not

benefit the data analysis. Instead, increasing the permitted glycans per peptide (SS9),

tightening the allowed mass error (SS11-SS12) and relaxing the protease specificity

benefitted both specificity and sensitivity. Search settings that showed cost-less performance

gains were combined for subsequent rounds of iterative searches. Importantly, these efforts

led to improved "high accuracy", "high coverage" and "balanced" (accuracy><coverage)

search strategies for *N*- and *O*- glycoproteomics (**Figure 4f**). None of the Byonic teams had

utilised these combinations of search settings. When assessed using the independent

glycoprotein-centric scoring method, these three recommended search strategies showed

improved performance (specificity, sensitivity) relatively to the Default strategy and

strategies used by Byonic teams (**Supplementary Table 19b**). Notably, the high coverage

searches dramatically expanded the search time, a metric here not considered beyond

logistical constraints.

Finally, we explored the performance of different fragmentation methods by systematically

varying the spectral input (HCD/EThcD/CID) in Byonic while keeping search settings and

output filtering constant. Highest performance was achieved when HCD and EThcD were

jointly searched (**Supplementary Table 19c**). Our analysis also suggested that low-

resolution CID data do not benefit the Byonic search performance when used alone or with

HCD/EThcD data, an observation supported by the Byonic team comparison

(**Supplementary Table 19d**).

Discussion

This is the first community-driven study aiming to objectively discern the performance of

current informatics solutions for glycoproteomics data analysis. Excitingly, several high-

performance glycoproteomics software and search strategies were identified. Amongst the 9

developer teams, Protein Prospector (Team 2) was identified as the top performing software

for both *N*- and *O*-glycoproteomics. Byonic (Team 4) also displayed high-performance for *N*-

glycopeptide data analysis, and while this developer only demonstrated moderate

performance for *O*-glycoproteomics, four Byonic user teams (Team 13, 15, 17, 18) displayed

the highest performance for *O*-glycopeptide data analysis. Protein Prospector[51] and Byonic[33],

developed 10-20 years ago, have pioneered the glycopeptide informatics field and are search

engines already commonly used in glycoproteomics[8, 31, 33].

Protein Prospector is an academic (free) tool recognised for its ability to identify modified

peptides and modification site(s) from LC-MS/MS data using a probability-difference based

scoring system[31]. Protein Prospector is often a preferred search engine in studies addressing

the challenging site annotation of *O*-glycopeptides in particular when ET(hc)D-MS/MS data

are available[5]. However, Protein Prospector does not estimate the FDR of the glycan

components of glycopeptides, which it regards as non-descript PTMs with an exact mass, and

the software may appear less user-friendly than competing tools.

Facilitated by a user-friendly interface, precise spectral annotation and useful output reports

of identified glycopeptides/proteins, the commercial Byonic search engine has gained

considerable popularity (as illustrated herein) as it enables relatively straightforward

identification of peptides with known and unknown modifications including glycosylation

from different MS/MS data. Byonic features useful fine control options that enable tailored

glycopeptide searches and post-search filtering of output based on prior knowledge. Byonic

scores and annotates multiple types of glycopeptide fragments to deduce the peptide carrier,

glycan and modification site, but the FDRs, calculated identically for non-glycosylated

peptides and glycopeptides, primarily addresses the correctness of the peptide rather than the

glycan and the site localisation[33].

Notably, GlycoPAT[37] (Team 8) and glyXtool[MS 32] (Team 3) were in our study also identified

as high-performance *N*- and *O*-glycoproteomics software, respectively. Furthermore, IQ-

GPA[30] (Team 1) demonstrated merit for both *N*- and *O*-glycopeptide data analysis. While all

three software handle high-resolution HCD-, ETciD-, and EThcD-MS/MS data, IQ-GPA and

GlycoPAT also identify glycopeptides based on high-resolution CID-MS/MS data and apply

post-search filtering based on advanced peptide and glycan decoy methods to estimate both

peptide and glycan FDRs of glycopeptide candidates. The software glyXtool[MS] instead uses

oxonium ions, Y_1-ions (peptide-HexNAc), other glycopeptide-specific fragments, and

peptide-specific b-/y-ions to control FDR. Excitingly, these three academic tools were

recently developed (< 5 years ago), and thus, hold a considerable potential in the field.

We used both team-wide and search engine-centric approaches to uncover performance-

associated search variables for glycoproteomics data analysis. The team-wide correlation

analyses revealed many search settings and search output linked to performance. Backed by

robust statistics, these "universal" relationships existing across search engines will widely

benefit glycoproteomics software developers and users aiming to improve *N*- and *O*-

glycopeptide data analysis (**Table 2**). This knowledge may aid tackling existing challenges in

glycoproteomics, amongst the most critical, reducing the FDR of glycopeptide candidates

carrying glycans with similar (e.g. NeuAc-R *versus* Fuc_2-R, $\Delta m = 1.0204$ Da) or identical

(e.g. $NeuAc_1Hex_1$-R *versus* $NeuGc_1Fuc_1$-R, $\Delta m = 0$ Da) masses. Our study indeed confirms

that glycopeptides displaying such "difficult-to-identify" features (NeuAc, NeuGc, multi-Fuc,

Met oxidation, Cys carbamidomethylation) are frequently mis-annotated with current search

engines (**Extended Data Figure 5**). We therefore recommend that efforts should be invested

in improving tools to allow for accurate identification of such challenging glycopeptides.

Meanwhile, our search engine-centric approach involving systematic Byonic searches

revealed search settings impacting the performance of this widely used search engine and

highlighted that specificity (accuracy) and sensitivity (coverage) are competing performance

characteristics challenging to achieve in a single search. This suggests that glycoproteomics

data may benefit from being interrogated using multiple orthogonal search strategies that are

subsequently combined or by approaches that strike a balance between accuracy and

coverage. To this end, we here recommend a set of improved "high accuracy", "high

coverage" and "balanced" search strategies that should be selected (and further

tailored/optimised) according to the sample and research question being investigated (**Figure**

4f).

Although not a focus here, our study also showed that the search strategy dramatically

impacts the search time. While the spectral input type and data output filtering represent other

critical variables that also need further exploration, our study indicates that HCD- and EThcD

are currently the most informative spectral types in glycoproteomics, and that knowledge-

guided filtering and curation of data output is critically required to lower FDRs.

The study also highlighted the significant informatics challenges still associated with large-

scale glycopeptide data analysis as illustrated by the discrepant reporting of glycopeptides

across teams. Notably, high discordance of reported glycopeptides was even found between

participants using the same software, confirming that search variables other than the search

engine also substantially impact the glycopeptide data analysis. While the 10 Byonic user

teams reported a marginally higher rate of consensus glycopeptides, their spread in terms of

search output data, reported glycoPSMs and overall performance scores was of similar

magnitude as the variance observed amongst other user teams. Whilst the (self-reported) team

experience in glycoproteomics was not found to be an accurate predictor of team scoring and

ranking, the variability in the spectral data input, search settings and, importantly, at the post-

search filtering stage were identified as key factors contributing to the discrepant reports.

Concertedly, these observations point to the importance of using both the most informative

spectral data, powerful search engines, tailored search settings and knowledge-driven post-

search filtering to achieve high-performance glycoproteomics data analysis.

Despite the considerable team-to-team variation, this study produced consensus lists of 163

N-glycopeptides and 23 *O*-glycopeptides from serum glycoproteins commonly reported by

teams. Importantly, these high-confidence glycopeptides carried biosynthetically-related

glycans that were devoid of NeuGc and poor in multi-Fuc features in line with literature[23, 40]

and mapped to known high-abundance serum proteins[4, 23, 39, 41, 42]. The consensus lists have

been made publicly available (GlyConnect ID 2943) as they form an important reference for

future studies of the human serum glycoproteome.

The study design including the sample type/preparation and data collection method was

chosen to mimic conditions typically encountered in glycoproteomics while also aiming to

accommodate most informatic solutions and appeal to users in the field. Multiple orthogonal

performance tests and separate validation were applied to ensure a fair and holistic scoring of

search engines and teams. Despite these efforts, it cannot be ruled out that some software or

users may have been unintentionally disadvantaged and/or excluded by the chosen

experimental design and scoring system. The team scoring and ranking should be viewed in

light of these constraints and limitations common to most community-based comparison

studies founded on communal data.

In addition to reporting on the peptide and glycan components of identified glycopeptides,

teams were requested to report on site(s) of modification where possible. Since most tryptic

N-glycopeptides only comprise a single sequon, site localisation is primarily a challenge

related to *O*-glycoproteomics[5, 16]. Most teams indeed returned data of the *O*-glycosylation

site(s), but due to highly discrepant and often inconclusive reporting of sites and a paucity of

literature on serum *O*-glycosylation sites, we were unable to score glycosylation site

localisation.

Most software currently available for glycoproteomics data analysis participated in this study.

However, several glycopeptide search engines e.g. pGlyco[52], MSFragger-Glyco[53], O-Pair

Search[54], and StrucGP[55] were unfortunately not represented due to LC-MS/MS data

incompatibility or due to their development after the study period. Thus, this study is

essentially a snapshot of the performance of software available at the time the data analysis

was performed. Highlighting the rapid progress in glycoproteome informatics, most of the

software solutions participating in this study have been improved and new versions released

after the evaluation period. For example, GPQuest v2.0, GlycoPAT v1.0 and Protein

Prospector v5.20.23 tested herein have been superseded by more recent versions i.e. GPQuest

v2.1, GlycoPAT v2.0 and Protein Prospector v.6.2.2. Thus, a limitation of this study is that

newer tools are available at the time of publication that were not compared in our analysis.

Follow-up studies comparing the performance of these latest glycoproteomics software

upgrades and informatics solutions not included in this study are therefore warranted. Beyond

testing the ability of participants to identify the peptide and glycan components of

glycopeptides from glycoproteomics data, such future comparative studies should ideally also

test the ability to accurately quantify (relative, absolute) and report on modification sites of

identified glycopeptides and could explore other relevant parameters not addressed herein

including the use of alternative proteases, TMT-labelling, and stepped-HCD-MS/MS data

amongst other experimental conditions gaining popularity in glycoproteomics.

In summary, this community study has documented that the field has several high-

performance informatics solutions available for glycoproteomics data analysis and has

elucidated key performance-associated search strategies that will serve to guide developers

and users of glycoproteomics software.

Acknowledgements

Drs Rosa Viner and Sergei Snovida (Thermo Fisher Scientific) are thanked for providing high-quality LC-MS/MS data. Dr Krishnatej Nishtala is thanked for aiding the data analysis. Drs Catherine Hayes, Julien Mariethoz and Frederique Lisacek are thanked for informatics assistance. RK was supported by an Early Career Fellowship (Cancer Institute NSW ECF181259). DK was supported by an Australian Research Council Future Fellowship (FT160100344). GP was funded by FAPESP (n° 2018/15549-1). MTA was supported by a Macquarie University Safety Net Grant. DK and NHP were supported by the Australian Research Council Centre of Excellence in Nanoscale Biophotonics (CE140100003).

Author Contributions Statement

Conception: NHP, MTA. Design: RK, DK, KK, GL, KFM, GP, JZ, JSY, SMH, NHP, MTA. Data acquisition: All participants (Team 1-22). Data analysis: RK, AC, BLP, GS, MTA. Data interpretation: RK, AC, MTA. Creation of new software used in the work: All developers (Team 1-9). Manuscript writing/editing: RK, AC, DK, KK, GL, KFM, GP, JZ, JSY, SMH, NHP, MTA. All authors have approved the manuscript.

Competing Interests Statement

All authors responsible for the study conception/design, data analysis/interpretation, and manuscript writing/editing declare no conflict of interest. Participants (Team 1-22) declare a perceived or real financial or academic conflict of interest in the study outcomes, which was mitigated by excluding participants from the analysis and interpretation of data returned by participants and from manuscript editing.

 Tables

Table 1. Overview of the symbols used in this study to refer to the key search settings (SS1-
SS13), search output (SO1-SO9) and performance tests (N1-N6, O1-O5) applied to establish
the relative team performance for glycopeptide data analysis. [#]Average of output data
reported by each team. AA, amino acid residues. While reported glycoPSMs were considered
search output (SO9), unique glycopeptides (site-localisation not considered) were used to
score the glycoproteome coverage (N4, O3).

	Search settings	**Range or definition of category** (team count)
SS1	*N*-glycan search space	23 - 381 unique glycan compositions
SS2	*O*-glycan search space	3 - 223 unique glycan compositions
SS3	Search engine(s) applied	Byonic (11), Protein Prospector (2), GlycoPAT (1), GlycopeptideGraphMS (1), glyXtool^{MS} (1), GPQuest (1), Other (5)
SS4	Type of search engine	Academic/open access/in-house = 0 (7), Commercial = 1 (15)
SS5	Spectral calibration post-acquisition	No = 0 (18), Yes = 1 (4)
SS6	Protease specificity	Non-tryptic (*N*- or *O*-ragged or non-specific) = 0 (8), Tryptic = -1 (14)
SS7	Missed peptide cleavages permitted	0 - 2 missed cleavages
SS8	Variable peptide modification(s) (non-glycan)	0 - 14 non-glycan modification types
SS9	Maximum glycans per peptide	1 - 5 glycans/peptide
SS10	Maximum other variable modifications	0 - 5 variable modifications/peptide
SS11	Precursor ion mass error permitted	Low (<5 ppm) = 0 (6), Medium (5-10 ppm) = 1 (14), High (>10 ppm) = 2 (2)
SS12	Product ion mass error permitted	Low (<5 ppm) = 0 (0), Medium (5-10 ppm) = 1 (9), High (>10 ppm) = 2 (13)
SS13	Peptide/protein FDR (decoy/contaminant database)	No decoy/contaminant = 0 (3), Only decoy or contaminant = 1 (9), Both decoy and contaminant = 2 (10)
	Search output	**Range** (*N*- or *O*-glycosylation)
SO1	Glycopeptide LC retention time[#]	41.7 - 57.2 min (NG) 26.2 - 55.8 min (OG)
SO2	Glycopeptide *m/z* (observed)[#]	*m/z* 712.9 - 1199.4 (NG) *m/z* 619.6 - 1229.0 (OG)
SO3	Glycopeptide charge state (observed)[#]	z = 3.9 - 4.3 (NG) z = 3.1 - 5.4 (OG)
SO4	Monoisotopic correction (off-by-X, positive values)[#]	0 - 2.1 Da (NG) 0 - 2.0 Da (OG)
SO5	Glycopeptide mass ([M+H], observed)[#]	3144.6 - 4913.0 Da (NG) 1892.9 - 6057.1 Da (OG)
SO6	Glycopeptide actual mass error (observed, positive values)[#]	0.5 - 2.8 ppm (NG) 1.1 - 5.9 ppm (OG)
SO7	Glycopeptide length[#]	16.9 - 26.8 AA (NG) 14.5 - 38.9 AA (OG)

SO8	Glycan mass (calculated from reported glycopeptides)[#]	1880.8 - 2410.1 Da (NG) 195.8 - 2216.8 Da (OG)
SO9	Reported GlycoPSMs	49 - 2122 glycoPSMs (NG) 5 - 578 glycoPSMs (OG)
	Performance tests	**Description of scoring method**
N1	Synthetic *N*-glycopeptide	Identification accuracy (specificity, %) multiplied by coverage (sensitivity, %) of a synthetic *N*-glycopeptide (**Supplementary Table 5**)
N2	*N*-glycan composition	Pearson correlation (R^2) between the expected[23] and observed *N*-glycan distribution in human serum (**Supplementary Table 6**)
N3	Source *N*-glycoprotein	Specificity and sensitivity of reported source glycoproteins relative to expected serum glycoproteins[23, 39] (**Supplementary Table 7**)
N4	*N*-glycoproteome coverage	Unique *N*-glycopeptides (unique peptide sequence and *N*-glycan composition) (**Supplementary Table 8**)
N5	Commonly reported 'consensus' *N*-glycopeptides	Proportion of reported glycopeptides of the consensus glycopeptides commonly reported by >50% teams (**Supplementary Table 9**)
N6	NeuGc and multi-Fuc *N*-glycopeptides (absence)	Proportion of reported glycoPSMs not containing NeuGc and multi-Fuc of all reported glycoPSMs. Only applicable if NeuGc/Fuc ≥2 glycans were included in glycan search space (**Supplementary Table 10**)
O1	*O*-glycan composition	Pearson correlation (R^2) between the expected[40] and observed *O*-glycan distribution in human serum (**Supplementary Table 11**)
O2	Source *O*-glycoprotein	Specificity and sensitivity of reported source glycoproteins relative to expected serum glycoproteins[4, 41, 42] (**Supplementary Table 12**)
O3	*O*-glycoproteome coverage	Unique *O*-glycopeptides (unique peptide sequence and *O*-glycan composition) (**Supplementary Table 13**)
O4	Commonly reported 'consensus' *O*-glycopeptides	Proportion of reported glycopeptides of the consensus *O*-glycopeptides commonly reported by >30% teams (**Supplementary Table 14**)
O5	NeuGc and multi-Fuc *O*-glycopeptides (absence)	Proportion of reported glycoPSMs not containing NeuGc and multi-Fuc containing glycoPSMs of all reported glycoPSMs. Only applicable if NeuGc/Fuc ≥2 glycans were included in glycan search space (**Supplementary Table 15**)

Table 2. Overview of software-independent search variables important for high-performance glycoproteomics data analysis (see **Figure 3b,d, Table 1**, **Supplementary Table 18** for study variables and associations). Only search variables closely associated with high performance (≥3 statistical tests) have been included. ‡Software-independent search settings that may guide improved glycoproteomics search strategies. ^Search output expected from high-performance glycoproteomics data analysis. This information may also aid post-search filtering of glycopeptide data. The possible compromise of selected search strategies on the overall glycoproteomics performance is indicated. NA, not applicable.

Performance area	Related test	High-performance search settings‡	High-performance search output (expected)^	Strategy may compromise
Efficient *N*-glycopeptide analysis (all-round performance)	Overall score (N1-N6)	• Use decoy/contaminant protein database to establish peptide/protein FDR (SS13)	• High *m/z* (SO2) • High monoisotopic correction (SO4) • High glycopeptide mass (SO5) • High glycoPSM count (SO9)	NA
Accurate *N*-glycan identification	N2	NA	• High glycan mass (SO8)	*N*-glyco-proteome coverage
Accurate source *N*-glycoprotein identification	N3	NA	• Late LC retention time (SO1) • High glycopeptide mass (SO5)	*N*-glyco-proteome coverage
High *N*-glycoproteome coverage	N4	• Allow diversity of variable non-glycan peptide modifications (SS8) • Allow few glycans per peptide (SS9) • Allow multiple variable non-glycan modifications per peptide (SS10) • Use decoy/contaminant protein database to establish peptide/protein FDR (SS13)	• Late LC retention time (SO1) • High charge stage (SO3) • High glycopeptide mass (SO5) • High actual mass error (SO6) • High glycan mass (SO8) • High glycoPSM count (SO9)	*N*-glycopeptide identification accuracy, search time
Reduce NeuGc and multi-Fuc FDR	N6	• Allow few missed peptide cleavages (SS7) • Allow few variable non-glycan modifications per peptide (SS10)	• Low actual mass error (SO6)	*N*-glyco-proteome coverage

Efficient *O*-glycopeptide analysis (all-round performance)	Overall score (O1-O5)	• Use broad glycan database (SS2) • Allow few missed peptide cleavages (SS7) • Allow multiple variable non-glycan modifications per peptide (SS10)	• Large peptides (SO7) • High glycoPSM count (SO9)	Search time
Accurate *O*-glycan identification	O1	• Use focused (narrow) glycan database (SS2) • Allow few missed peptide cleavages (SS7)	• High monoisotopic correction (SO4) • Low actual mass error (SO6)	*O*-glyco-proteome coverage
Accuracy source *O*-glycoprotein identification	O2	• Use broad glycan database (SS2) • Use full trypsin specificity (SS6) • Allow few missed cleavages (SS7) • Allow few glycans per peptide (SS9) • Allow multiple variable non-glycan modifications per peptide (SS10)	• High glycoPSM count (SO9)	*O*-glyco-proteome coverage, search time
High *O*-glycoproteome coverage	O3	• Use broad glycan database (SS2)	• High actual mass error (SO6) • High glycoPSM count (SO9)	*O*-glycopeptide identification accuracy, search time

Figure Legends/Captions

Figure 1. Study overview. **a**. Two glycoproteomics data files of human serum (File A-B) were generated and shared with participants. **b**. Participants comprising both developers (orange) and users (blue, team identifiers indicated) employed diverse search engines to complete the study. **c**. Teams returned a common reporting template capturing details of the applied search strategy including key search settings (SS1-SS13) and search output (SO1-SO9, **Table 1**) and identified glycopeptides. **d**. Complementary performance tests (N1-N6, O1-O5, **Table 1**) were used to comprehensively evaluate the ability of teams to identify *N*- and *O*-glycopeptides. **e**. The performance profiles were used to separately score and rank the developers and users. Diverse team-wide and search engine-centric (Byonic-focused) approaches were employed to identify performance-associated variables and high-performance search strategies.

Figure 2. Overview of the glycopeptides reported across teams. Team 8-9 did not perform *O*-glycopeptide analysis. **a,c.** Distribution of the reported glycoPSMs (bars), unique source glycoproteins (dots) and applied glycan search space (mirror, see also **Supplementary Table 2-3**) across teams. **b,d.** Proportion of glycopeptides, source glycoproteins and glycan compositions commonly reported by teams. The high-confidence 'consensus' glycopeptides have been made publicly available (GlyConnect Reference ID 2943).

Figure 3. Team scoring/ranking and identification of performance-associated variables. **a,c.** Heatmap representation of normalised scores (range 0-1) from the glycopeptide performance tests (N1-N6, O1-O5, **Table 1**). Team 8-9 did not return *O*-glycopeptide data. See **Supplementary Table 5-16** for performance data. [#]The top third performing teams (white bold) were placed in a high-performance band. Team scoring was validated using an independent assessment method (**Extended Data Figure 10**). *Performance could not be

determined. **b,d.** Many study variables (search settings and search output) showed

associations (negative or positive) with performance. See **Table 1** for variables. See

Supplementary Table 18 for statistics.

Figure 4. Search engine-centric (Byonic-focused) analysis of search strategies for high-

performance glycoproteomics data analysis. **a**. Overview of the search settings employed by

Byonic teams. Default: Search strategy used by most teams (yellow). Custom: Variations

from the Default search strategy (green). [#]Data of SS14, a setting not included in the team

reports, were adopted from SO4 data. **b**. The glycoproteome coverage (unique glycopeptides,

File B) varied amongst Byonic teams. **c**. Specificity (accuracy) and sensitivity (coverage)

scores for i) *N*-glycopeptides and ii) *O*-glycopeptides for Byonic teams. **d-e**. Controlled (in-

house) searches for *N*- and *O*-glycopeptides using Byonic (File B). Individual search settings

were systematically varied (iteration level 1) and output assessed for performance gains

(specificity, sensitivity). Search settings showing performance gains (shaded

circles/diamonds) without unacceptable costs in specificity (SS13) or search time (SS8/SS10,

SS9) (grey stars) were collectively tested for synergy (iteration level 2-3, dark green). **f**.

Recommended Byonic-centric search strategies for "high accuracy", "high coverage" and

"balanced" (accuracy><coverage) glycoproteomics data analysis. ^The recommended search

strategies showed relative performance gains as determined using an independent

glycoprotein-centric score (**Supplementary Table 19b**). Search time and glycoproteome

coverage (unique glycopeptides) are also indicated.

References

1.   Varki, A. Biological roles of glycans. *Glycobiology* **27**, 3-49 (2017).

2.   Thaysen-Andersen, M., Packer, N.H. & Schulz, B.L. Maturing Glycoproteomics
Technologies Provide Unique Structural Insights into the N-glycoproteome and Its
Regulation in Health and Disease. *Mol Cell Proteomics* **15**, 1773-1790 (2016).

3.   Chandler, K.B. & Costello, C.E. Glycomics and glycoproteomics of membrane
proteins and cell-surface receptors: Present trends and future opportunities.
Electrophoresis **37**, 1407-1419 (2016).

4.   Ye, Z., Mao, Y., Clausen, H. & Vakhrushev, S.Y. Glyco-DIA: a method for
quantitative O-glycoproteomics with in silico-boosted glycopeptide libraries. *Nature*
Methods **16**, 902-910 (2019).

5.   Pap, A., Klement, E., Hunyadi-Gulyas, E., Darula, Z. & Medzihradszky, K.F. Status
Report on the High-Throughput Characterization of Complex Intact O-Glycopeptide
Mixtures. *Journal of The American Society for Mass Spectrometry* **29**, 1210-1220
(2018).

6.   Blazev, R. et al. Integrated glycoproteomics identifies a role of N-glycosylation and
galectin-1 on myogenesis and muscle development. *Mol Cell Proteomics* (2020).

7.   Kawahara, R. et al. The complexity and dynamics of the tissue glycoproteome
associated with prostate cancer progression. *Mol Cell Proteomics* (2020).

8.   Chernykh, A., Kawahara, R. & Thaysen-Andersen, M. Towards structure-focused
glycoproteomics. *Biochemical Society Transactions*, 1-25 (2020).

9.   Lee, L.Y. et al. Toward Automated N-Glycopeptide Identification in
Glycoproteomics. *J Proteome Res* **15**, 3904-3915 (2016).

10. Darula, Z. & Medzihradszky, K.F. Carbamidomethylation Side Reactions May Lead

to Glycan Misassignments in Glycopeptide Analysis. *Anal Chem* **87**, 6297-6302

(2015).

11. Riley, N.M., Malaker, S.A. & Bertozzi, C.R. Electron-Based Dissociation Is Needed

for O-Glycopeptides Derived from OpeRATOR Proteolysis. *Anal Chem* **92**, 14878-

14884 (2020).

12. Riley, N.M., Malaker, S.A., Driessen, M.D. & Bertozzi, C.R. Optimal Dissociation

Methods Differ for N- and O-Glycopeptides. *J Proteome Res* **19**, 3286-3301 (2020).

13. Woo, C.M. et al. Development of IsoTaG, a Chemical Glycoproteomics Technique

for Profiling Intact N- and O-Glycopeptides from Whole Cell Proteomes. *J Proteome*

Res **16**, 1706-1718 (2017).

14. Fang, P. et al. Multilayered N-Glycoproteome Profiling Reveals Highly

Heterogeneous and Dysregulated Protein N-Glycosylation Related to Alzheimer's

Disease. *Anal Chem* **92**, 867-874 (2020).

15. Woo, C.M. et al. Mapping and Quantification of Over 2000 O-linked Glycopeptides

in Activated Human T Cells with Isotope-Targeted Glycoproteomics (Isotag). *Mol*

Cell Proteomics **17**, 764-775 (2018).

16. Darula, Z. & Medzihradszky, K.F. Analysis of Mammalian O-Glycopeptides-We

Have Made a Good Start, but There is a Long Way to Go. *Mol Cell Proteomics* **17**, 2-

17 (2018).

17. Wu, S.W., Pu, T.H., Viner, R. & Khoo, K.H. Novel LC-MS(2) product dependent

parallel data acquisition function and data analysis workflow for sequencing and

identification of intact glycopeptides. *Anal Chem* **86**, 5478-5486 (2014).

18.   Reiding, K.R., Bondt, A., Franc, V. & Heck, A.J.R. The benefits of hybrid
698   fragmentation methods for glycoproteomics. *TrAC Trends in Analytical Chemistry*
699   **108**, 260-268 (2018).

700   19.   Thaysen-Andersen, M., Kolarich, D. & Packer, N.H. Glycomics & Glycoproteomics:
701   From Analytics to Function. *Mol Omics* (2020).

702   20.   Hu, H., Khatri, K. & Zaia, J. Algorithms and design strategies towards automated
703   glycoproteomics analysis. *Mass Spectrom Rev* **36**, 475-498 (2017).

704   21.   Abrahams, J.L. et al. Recent advances in glycoinformatic platforms for glycomics and
705   glycoproteomics. *Curr Opin Struct Biol* **62**, 56-69 (2020).

706   22.   Cao, W. et al. Recent advances in software tools for more generic and precise intact
707   glycopeptide analysis. *Mol Cell Proteomics* (2020).

708   23.   Clerc, F. et al. Human plasma protein N-glycosylation. *Glycoconj J* **33**, 309-343
709   (2016).

710   24.   Dotz, V. & Wuhrer, M. N-glycome signatures in human plasma: associations with
711   physiology and major diseases. *FEBS Lett* **593**, 2966-2976 (2019).

712   25.   Hoffmann, M., Marx, K., Reichl, U., Wuhrer, M. & Rapp, E. Site-specific O-
713   Glycosylation Analysis of Human Blood Plasma Proteins. *Mol Cell Proteomics* **15**,
714   624-641 (2016).

715   26.   Parker, B.L. et al. Terminal Galactosylation and Sialylation Switching on Membrane
716   Glycoproteins upon TNF-Alpha-Induced Insulin Resistance in Adipocytes. *Mol Cell
717   Proteomics* **15**, 141-153 (2016).

718   27.   Zhang, Y. et al. Systems analysis of singly and multiply O-glycosylated peptides in
719   the human serum glycoproteome via EThcD and HCD mass spectrometry. *J
720   Proteomics* **170**, 14-27 (2018).

721   28.   Yu, Q. et al. Electron-Transfer/Higher-Energy Collision Dissociation (EThcD)-

722   Enabled Intact Glycopeptide/Glycoproteome Characterization. *J Am Soc Mass*

723   *Spectrom* **28**, 1751-1764 (2017).

724   29.   Darula, Z., Pap, A. & Medzihradszky, K.F. Extended Sialylated O-Glycan Repertoire

725   of Human Urinary Glycoproteins Discovered and Characterized Using Electron-

726   Transfer/Higher-Energy Collision Dissociation. *J Proteome Res* **18**, 280-291 (2019).

727   30.   Park, G.W. et al. Integrated GlycoProteome Analyzer (I-GPA) for Automated

728   Identification and Quantitation of Site-Specific N-Glycosylation. *Sci Rep* **6**, 21175

729   (2016).

730   31.   Baker, P.R., Trinidad, J.C. & Chalkley, R.J. Modification site localization scoring

731   integrated into a search engine. *Mol Cell Proteomics* **10**, M111 008078 (2011).

732   32.   Pioch, M., Hoffmann, M., Pralow, A., Reichl, U. & Rapp, E. glyXtool(MS): An

733   Open-Source Pipeline for Semiautomated Analysis of Glycopeptide Mass

734   Spectrometry Data. *Anal Chem* **90**, 11908-11916 (2018).

735   33.   Bern, M., Kil, Y.J. & Becker, C. Byonic: advanced peptide and protein identification

736   software. *Curr Protoc Bioinformatics* **Chapter 13**, Unit13 20 (2012).

737   34.   Stadlmann, J., Hoi, D.M., Taubenschmid, J., Mechtler, K. & Penninger, J.M. Analysis

738   of PNGase F-Resistant N-Glycopeptides Using SugarQb for Proteome Discoverer 2.1

739   Reveals Cryptic Substrate Specificities. *Proteomics* **18**, e1700436 (2018).

740   35.   Pompach, P., Chandler, K.B., Lan, R., Edwards, N. & Goldman, R. Semi-automated

741   identification of N-Glycopeptides by hydrophilic interaction chromatography, nano-

742   reverse-phase LC-MS/MS, and glycan database search. *J Proteome Res* **11**, 1728-

743   1740 (2012).

744   36.   Choo, M.S., Wan, C., Rudd, P.M. & Nguyen-Khuong, T. GlycopeptideGraphMS:

745   Improved Glycopeptide Detection and Identification by Exploiting Graph Theoretical

746   Patterns in Mass and Retention Time. *Anal Chem* **91**, 7236-7244 (2019).

747   37.   Liu, G. et al. A Comprehensive, Open-source Platform for Mass Spectrometry-based

748   Glycoproteomics Data Analysis. *Mol Cell Proteomics* **16**, 2032-2047 (2017).

749   38.   Toghi Eshghi, S., Shah, P., Yang, W., Li, X. & Zhang, H. GPQuest: A Spectral

750   Library Matching Algorithm for Site-Specific Assignment of Tandem Mass Spectra to

751   Intact N-glycopeptides. *Anal Chem* **87**, 5181-5188 (2015).

752   39.   Sun, S. et al. Site-Specific Profiling of Serum Glycoproteins Using N-Linked Glycan

753   and Glycosite Analysis Revealing Atypical N-Glycosylation Sites on Albumin and

754   alpha-1B-Glycoprotein. *Anal Chem* **90**, 6292-6299 (2018).

755   40.   Yabu, M., Korekane, H. & Miyamoto, Y. Precise structural analysis of O-linked

756   oligosaccharides in human serum. *Glycobiology* **24**, 542-553 (2014).

757   41.   Darula, Z., Sarnyai, F. & Medzihradszky, K.F. O-glycosylation sites identified from

758   mucin core-1 type glycopeptides from human serum. *Glycoconj J* **33**, 435-445 (2016).

759   42.   Yang, W., Ao, M., Hu, Y., Li, Q.K. & Zhang, H. Mapping the O-glycoproteome using

760   site-specific extraction of O-linked glycopeptides (EXoO). *Mol Syst Biol* **14**, e8486

761   (2018).

762   43.   Kolarich, D., Weber, A., Turecek, P.L., Schwarz, H.-P. & Altmann, F.

763   Comprehensive glyco-proteomic analysis of human α1-antitrypsin and its charge

764   isoforms. *PROTEOMICS* **6**, 3369-3380 (2006).

765   44.   Harazono, A. et al. Site-specific N-glycosylation analysis of human plasma

766   ceruloplasmin using liquid chromatography with electrospray ionization tandem mass

767   spectrometry. *Analytical Biochemistry* **348**, 259-268 (2006).

768   45.   Huffman, J.E. et al. Comparative performance of four methods for high-throughput

769   glycosylation analysis of immunoglobulin G in genetic and epidemiological research.

770   *Mol Cell Proteomics* **13**, 1598-1610 (2014).

771   46.   Pompach, P. et al. Site-specific Glycoforms of Haptoglobin in Liver Cirrhosis and

772   Hepatocellular Carcinoma. *Molecular & Cellular Proteomics* **12**, 1281-1293 (2013).

773   47.   Pavic, T. et al. N-glycosylation patterns of plasma proteins and immunoglobulin G in

774   chronic obstructive pulmonary disease. *J Transl Med* **16**, 323 (2018).

775   48.   Zaytseva, O.O. et al. Heritability of Human Plasma N-Glycome. *J Proteome Res* **19**,

776   85-91 (2020).

777   49.   Gudelj, I. et al. Changes in total plasma and serum N-glycome composition and

778   patient-controlled analgesia after major abdominal surgery. *Sci Rep* **6**, 31234 (2016).

779   50.   Gizaw, S.T., Gaunitz, S. & Novotny, M.V. Highly Sensitive O-Glycan Profiling for

780   Human Serum Proteins Reveals Gender-Dependent Changes in Colorectal Cancer

781   Patients. *Anal Chem* **91**, 6180-6189 (2019).

782   51.   Chalkley, R.J. et al. Comprehensive analysis of a multidimensional liquid

783   chromatography mass spectrometry dataset acquired on a quadrupole selecting,

784   quadrupole collision cell, time-of-flight mass spectrometer: II. New developments in

785   Protein Prospector allow for reliable and comprehensive automatic analysis of large

786   datasets. *Mol Cell Proteomics* **4**, 1194-1204 (2005).

787   52.   Liu, M.Q. et al. pGlyco 2.0 enables precision N-glycoproteomics with comprehensive

788   quality control and one-step mass spectrometry for intact glycopeptide identification.

789   *Nat Commun* **8**, 438 (2017).

790   53.   Polasky, D.A., Yu, F., Teo, G.C. & Nesvizhskii, A.I. Fast and comprehensive N- and

791   O-glycoproteomics analysis with MSFragger-Glyco. *Nat Methods* **17**, 1125-1132

792   (2020).

793   54.   Lu, L., Riley, N.M., Shortreed, M.R., Bertozzi, C.R. & Smith, L.M. O-Pair Search

794   with MetaMorpheus for O-glycopeptide characterization. *Nat Methods* **17**, 1133-1138

795   (2020).

796   55.   Shen, J. et al. StrucGP: de novo structural sequencing of site-specific N-glycan on

797   glycoproteins using a modularization strategy. *Nat Methods* **18**, 921-929 (2021).

Online Methods

Key methodological details are provided below. Please consult the **Extended methods** for an

exhaustive description of methods employed.

Study design and participants

Nine developer and 13 user teams completed the study (**Supplementary Table 1**). Teams

received two glycoproteomics data files (File A-B) and reported identified *N-* and *O-*

glycopeptides using a common reporting template (PXD024101, PRIDE). User teams were

free to use any search engine(s) at their disposal including manual annotation/filtering of

search output. Developers returned the identified glycopeptides directly from their own

software without manual post-search filtering. The relative team performance was therefore

compared within (not between) the developer and user groups.

Study sample

A synthetic *N*-glycopeptide (52 fmol) from human vitamin K-dependent protein C

(EVFVHP$\underline{N}$YSK, $Hex_5HexNAc_4NeuAc_2$) was spiked into human serum (product #31876,

Thermo Fisher Scientific), the mixture digested using trypsin, and glycopeptides enriched.

Mass spectrometry

The enriched glycopeptide mixture was analysed twice using two similar LC-MS/MS

acquisition methods generating File A-B. For both files, peptides were separated using C_{18}

reversed-phase nanoLC and detected on a Thermo Scientific™ Orbitrap Fusion™ Lumos™

Tribrid™ mass spectrometer using high-resolution MS1 and data-dependent HCD-MS/MS

acquisition. Product-dependent (oxonium ion) triggered ETciD-/CID-MS/MS (Orbitrap) and

EThcD-/CID-MS/MS (Orbitrap/ion trap) events of glycopeptide precursors were scheduled

for File A-B, respectively. Participants received File A-B as .raw/.mgf files.

Search instructions and reporting template

Teams used a fixed protein search space (human proteome, 20,231 UniProtKB reviewed

sequences), but could freely choose the glycan search space. Teams were instructed neither to

include xylose nor any glycan substitutions in the glycan search space. The participants

reported their team details, identification strategy and identified glycopeptides in a common

reporting template. All reports were carefully checked for compliance to the study guidelines

to enable fair comparisons between teams.

Compilation and comparison of team data

Data from the returned reports were compiled (**Supplementary Table 1-2**) including the

reported glycopeptides (**Supplementary Table 3**). Unique identifiers (IDs) for the reported

glycopeptides and their glycan compositions and source glycoproteins were generated to

enable team-to-team comparisons using pivot tables in Excel.

Glycoprofiling of select serum N-glycoproteins

The site-specific *N*-glycosylation of select glycoproteins including human alpha-1-antitrypsin

(A1AT, P01009), ceruloplasmin (CP, P00450), haptoglobin (HP, P00738) and

immunoglobulin G1 (IgG1, P01857) was profiled using AUC-based MS1 quantitation.

Search engine-centric analysis and optimisation of Byonic search strategies

Deep search engine-centric analyses were performed through a series of controlled in-house

searches using Byonic v3.9.4 (Protein Metrics Inc., CA, USA). Search settings or spectral

data input were systematically varied and the output scored. Search settings leading to

relative performance gains were iteratively used for additional searches.

Performance testing of teams and software

Relative performance for glycopeptide data analysis was determined via three different

methods. In short, teams were comprehensively scored and ranked based on overall

performance scores established from multiple complementary performance tests (N1-N6, O1-

O5). The performance tests included the synthetic *N*-glycopeptide test (N1), the glycan

composition test (N2, O1), the source glycoprotein test (N3, O2), the glycoproteome

coverage test (N4, O3), the commonly reported (consensus) glycopeptide test (N5, O4), and

the NeuGc/multi-Fuc glycopeptide test (N6, O5). The team scoring was validated using an

independent glycoprotein-centric assessment method that scored the quantitative match of

glycoPSMs reported by teams to the actual site-specific *N*-glycosylation of selected

glycoproteins (A1AT, CP, HP, IgG1). For the search engine-centric analysis of the Byonic

search strategies, performance was evaluated based on relative specificity and sensitive

scores derived from the performance tests (N1-N6, O1-O5).

Statistical analysis

Scores from each performance test (N1-N6, O1-O5) and the overall team performance scores

were tested for associations with the search settings (SS1-SS13) and search output (SO1-

SO9) using seven statistical methods[56]. Only strong associations observed across at least

three different statistical methods were considered. Further, unpaired two-sided t-tests were

applied as indicated. The confidence interval was 95% and statistical significance indicated

as $*p < 0.05$, $**p < 0.01$ and $***p < 0.001$. Pearson correlations were used to quantitatively

compare the observed site-specific *N*-glycan distribution of four glycoproteins in the sample

to the literature and to validate the team scoring via the glycoprotein-centric scores.

Data Availability Statement

This study contains extended data figures and other supplementary information. Multiple

figures/tables have associated raw data (**Figure 1-4**, **Table 1-2**, **Extended Data Figure 1-4**,

8-10). The supporting information includes: 1) **Extended Data Figure 1-10,** 2)

Supplementary information containing **Extended methods** (pdf) and 3) **Supplementary**

Table 1–19 (Microsoft Excel). Further, the LC-MS/MS raw data (File A-B), reporting

template, and deidentified but otherwise unredacted team reports are available via

ProteomeXchange (PXD024101). Username: reviewer_pxd024101@ebi.ac.uk, Password:

YLk2wW1P. The consensus glycopeptides are available via the GlyConnect resource of the

Glycomics@ExPASy collection hosted at SIB - Swiss Institute of Bioinformatics

(GlyConnect Reference ID 2943).

Code Availability Statement

Developers (Team 1-9) used their own software to complete this study. All participants

including the developers detailed how software were handled and how data were generated.

Additionally, developers detailed in their reports how their software could be tested and data

validated by the study committee. While the codes for the developer software

(commercial/academic origins) have not been released as part of this work, all team reports

underpinning this study have been released (see Data Availability Statement).

891 **Methods References**

893   56.   Efron, B. & Hastie, T. Computer Age Statistical Inference: Algorithms, Evidence, and

894   Data Science. (Cambridge University Press, 2016).

a

File A

b

File B

c

File A

d

File B

⬚ Total HCD-MS/MS spectra
■ Total 204-containing MS/MS spectra
■ Total reported glyco-PSMs (all teams)

a Undetectable NeuGc glycopeptides in human serum

b Example of correctly and incorrectly annotated sialoglycopeptide

c Antenna-Fuc (and thus multi-Fuc) are rarely detected

d Example of correctly and incorrectly annotated multi-Fuc glycopeptides

e Example of correctly and incorrectly annotated sialoglycopeptides

a Example of an HCD-MS/MS spectrum correctly annotated by most teams

b Example of an HCD-MS/MS spectrum incorrectly annotated by several teams

a

- **37** (A) hgi
- **2** (B) VN
- **0** (AB)

b

- **20** (A) hgi
- **9** (B) VN
- **0** (AB)

a

File A

HCD-MS/MS (#5552)
m/z 856.85 (4+)

ETciD-MS/MS (#5553)
m/z 856.85 (4+)

CID-MS/MS (#5554)
m/z 856.85 (4+)

File B

HCD-MS/MS (#5425)
m/z 1142.13 (3+)

EThcD-MS/MS (#5429)
m/z 1142.13 (3+)

CID-MS/MS (#5430)
m/z 1142.13 (3+)

HCD-MS/MS (#5888)
m/z 856.85 (4+)

EThcD-MS/MS (#5890)
m/z 856.85 (4+)

CID-MS/MS (#5891)
m/z 856.85 (4+)

HCD-MS/MS (#5919)
m/z 693.27 (5+)

EThcD-MS/MS (#5922)
m/z 693.27 (5+)

CID-MS/MS (#5923)
m/z 693.27 (5+)

Relative Intensity

* Oxonium ions and B-ions
* Y-ions (peptide + glycan fragment)
* Peptide backbone fragments (b-/y-/c-/z-ions)
* Unfragmented precursor

c

EVFVHP**N**YSK
(P04070)

b

■ Correct identification   ■ Incorrect identification
■ MS/MS type not included in search   □ Not reported by team

d

Team	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
Sensitivity (%)	50	67	13	38	0	0	0	33	0	25	29	33	33	0	75	27	18	38	0	25	17	40
Specificity (%)	100	50	100	100	0	0	0	100	0	100	100	100	100	0	100	100	100	100	0	100	100	100
Score (0-100)	50	34	13	38	0	0	0	33	0	25	29	33	33	0	75	27	18	38	0	25	17	40