Structure Can Predict Function in the Human Brain: A Graph Neural Network Deep Learning

Model of Functional Connectivity and Centrality based on Structural Connectivity

Josh Neudorf, Shaylyn Kress, and Ron Borowsky*

Cognitive Neuroscience Lab, Department of Psychology, University of Saskatchewan,

Saskatoon, Saskatchewan, Canada

* Corresponding author

E-mail: ron.borowsky@usask.ca (RB)

Abstract

Although functional connectivity and associated graph theory measures (e.g., centrality; how centrally important to the network a region is) are widely used in brain research, the full extent to which these functional measures are related to the underlying structural connectivity is not yet fully understood. The most successful recent methods have managed to account for 36% of the variance in functional connectivity based on structural connectivity. Graph neural network deep learning methods have not yet been applied for this purpose, and offer an ideal model architecture for working with connectivity data given their ability to capture and maintain inherent network structure. This model applied here to predict functional connectivity and centrality from structural connectivity accounted for 72% of the variance in functional connectivity, double that of the previous best model, and 91% of the variance in functional centrality. Regions of particular importance to the model's performance as determined through lesioning are discussed, whereby regions with better structure-function coupling have a higher impact on model performance. Future research on models of patient, demographic, or behavioural data can also benefit from this graph neural network method as it is ideally-suited for capturing connectivity and centrality in brain networks. These prediction results have set a new benchmark for prediction of functional connectivity from structural connectivity, and models like this may ultimately lead to a way to predict functional connectivity in individuals who are unable to do fMRI tasks (e.g., non-responsive patients).

Keywords: functional connectivity, resting state fMRI, structural connectivity, DTI, deep learning, centrality

Structure Can Predict Function in the Human Brain: A Graph Neural Network Deep Learning

Model of Functional Connectivity and Centrality based on Structural Connectivity

There is now widespread usage of functional connectivity and associated graph theory measures (e.g., centrality; how centrally important to the network a particular region is). Investigating to what extent the structural connectivity as measured by diffusion tensor imaging (DTI) can explain functional connectivity as measured by resting state functional magnetic resonance imaging (rsfMRI) is an important step towards understanding to what extent there is a structural basis for these functional measures (the importance of this problem has recently been highlighted; Suárez et al., 2020). Some of the first steps towards understanding the relationship between structure and function showed moderate correspondence when examining direct structural connections, accounting for approximately 50% of the variance (Honey et al., 2009), or looking at a subset of connections (62%; Hagmann et al., 2008). However, when examining all functional connections, structural connectivity accounts for only 9% of the variance using linear regression by one account (Rosenthal et al., 2018). Novel graph theory measures calculated using structural connectivity have accounted for 23% of the variance in functional connectivity (Goñi et al., 2014), a combination of vector encodings of structural connectivity and deep learning with a fully connected network (FCN) have accounted for 36% of the variance in functional connectivity (Rosenthal et al., 2018), and simulated fMRI activation using a hybrid approach with both DTI and electroencephalography (EEG) data has accounted for 53% of the variance in functional connectivity (Schirner et al., 2018). Still, there remains a large amount of variance unaccounted for if we are to determine the extent to which measures of centrality based on functional connectivity offer insight into the properties of the underlying structural network.

There is a general consensus in the neuroscience community that rsfMRI functional connectivity measures represent the effective connectivity between regions in the brain. Effective connectivity describes the meaningful result of communication between regions that are sparsely connected by direct and indirect structural connections (white matter tracts). To support this view researchers have noted that patterns of connectivity seem to occur between regions that are expected to function together based on previous research and neuroanatomy (see van den Heuvel and Hulshoff Pol, 2010 for a review). To the extent that modern methods allow the effects of physiological factors (e.g., respiration and cardiac function) to be accounted for, the neuronal basis of the BOLD signal can be increased relative to noise (e.g., Birn et al., 2008; Chang et al., 2009; Falahpour et al., 2013; Golestani et al., 2015; Kassinopoulos and Mitsis, 2019; Salas et al., 2021), but co-occurring increases and decreases of this signal have yet to be robustly linked to the organization of the underlying structural network. Searching for the upper limit in predicting functional connectivity from structure remains an important goal for investigating to what extent the rsfMRI functional connectivity represents the 'effective' connectivity of the structural network.

One issue with structural connectivity is that DTI tractography data is sparse, meaning the majority of values are zeros. On the other hand, functional connectivity data has many more non-zero values, even when thresholded. This difference occurs in part because many routes of communication between brain regions are indirect rather than direct, and is one reason functional connectivity has been widely used. Measures of indirect ('effective') connectivity are available using graph theory, including shortest path length, communicability (Estrada and Hatano, 2008), and novel measures designed for brain research (e.g., search information and path transitivity;

Goñi et al., 2014), but research is still investigating the extent to which these measures represent how information is communicated between brain regions.

Research employing graph theory measures of centrality, which describe a region's importance to the network, has become common for both structural and functional connectivity. Some common centrality measures include degree centrality (number of connections to a region), eigenvector centrality (number of connections to a region weighted by the centrality of its neighbours), and PageRank centrality (a variant of eigenvector centrality developed for use in ranking web pages, with the advantage that it addresses the issue of eigenvector centrality sometimes being excessively high when a low degree node is connected to a high centrality node; Page et al., 1999). Figure 1 depicts an example graph with labels showing which node has the highest centrality for each of these measures. This example graph more closely resembles the sparse (few connections) structural connectivity network than the highly connected functional connectivity network. The interpretation of centrality for structural connectivity is more straightforward than for functional connectivity, as functional connectivity is already loosely interpreted as 'effective' connectivity (taking indirect structural connections into account). Functional connectivity centrality has been used to demonstrate age and sex related differences (Zuo et al., 2012), differences between patient and control groups (for patients with schizophrenia, Chen et al., 2015; bipolar disorder, Deng et al., 2019, Zhou et al., 2017; retinitus pigmentosa, Lin et al., 2021; and diabetic optic neuropathy, Xu et al., 2020), and differences related to genotype (Wink et al., 2018). Structural connectivity centrality has also been used to demonstrate differences between patient and control groups (e.g., Long et al., 2020; Raizman et al., 2020; Turkiewicz et al., 2021; Yu et al., 2016), and to demonstrate a relationship between structural centrality and functional complexity suggesting that regions integrating information

from many sources have more complex functional activity (Neudorf et al., 2020). An important

question that remains to be answered is to what extent can variance in functional connectivity

centrality measures be accounted for by structural connectivity.

Figure 1. An example graph illustrating degree centrality, eigenvector centrality, and PageRank

centrality.

The problem of developing a deep learning approach to using brain connectivity for

prediction has been a focus of recent research. In a graph neural network approach to deep

learning, the structure of the connectivity data as a network (graph) is maintained, making this

method ideal for prediction problems related to connectivity data. One implementation of this

model architecture (not using additional global values in this case), Graph Nets (Battaglia et al.,

2018), trains a small fully connected network (FCN) update function to update the value of each

edge based on the value of the edge and the values of the 2 connected nodes, and another

trainable FCN that updates the value of each node using the value of the node and the aggregated

value of connected edges (see Figure 2). Any number of updates can be performed, each using

the updated values from the last step, before calculating the loss function and training the update

functions (message passing). Graph neural network approaches to deep learning have been consistently outperforming other models of deep learning in prediction with brain connectivity data. Some applications of a graph neural network method to brain connectivity data include demonstrations of sex prediction from functional connectivity (88% accuracy; Arslan et al., 2018), a similarity metric learning model for predicting the similarity between two functional connectivity networks (63% accuracy; Ktena et al., 2017), prediction of Alzheimer's disease from functional connectivity that outperformed previous methods (80% to 81% accuracy; Bi et al., 2020; Parisot et al., 2018), and prediction of Autism Spectrum Disorder outperforming previous methods (61% to 70% accuracy; Arya et al., 2020; Parisot et al., 2018; Zhang and Wang, 2020).

Figure 2. Depiction of Graph Nets update functions, where e_k' refers to the updated edge value, and where v_i and v_i' refer to the node being updated and then its updated value. Adapted from Battaglia et al. (2018).

Considering the ultimate goal of relating DTI structural connectivity to resting state functional connectivity, a graph neural network deep learning approach has not yet been established, but based on past successes predicting other measures using brain connectivity this

type of model is a promising candidate. This research uses a Graph Nets (Battaglia et al., 2018)

deep learning model to determine to what extent structural connectivity can predict functional

connectivity, as well as functional connectivity derived centrality measures.

Methods

Dataset

High quality DTI and resting state fMRI data for 998 subjects were obtained from the

Human Connection Project (HCP) database (Van Essen et al., 2013; please see this paper for

ethics statements). The HCP preprocessed rsfMRI data was used, which has been FSL FIX

(Salimi-Khorshidi et al., 2014) preprocessed, along with the DTI preprocessed data (see HCP

preprocessing pipelines for more information on preprocessing steps, Glasser et al., 2013). Each

of the 4 rs- fMRI sessions was z-score standardized for each voxel independently from each

other session. Each voxel within each session was also bandpass filtered to keep frequencies

between 0.01 Hz and 0.1 Hz (see Hallquist et al., 2013).

Connectivity Measures

The Pearson correlation coefficient was then calculated for each voxel using the 4800

total time points (all 4 sessions concatenated), as a measure of functional connectivity. DSI

Studio's (http://dsi-studio.labsolver.org) deterministic tracking algorithm that uses quantitative

anisotropy (Yeh et al., 2013) as the termination index was used to produce structural connectivity

matrices of streamline count for the AAL 90 region atlas (Tzourio-Mazoyer et al., 2002). For

reconstruction in DSI Studio the Generalized Q-sampling (Yeh et al., 2010) method was used,

and tracking was performed using a fiber count of 1 million fibers, maximum angular deviation

of 75 degrees, and a minimum and maximum fiber length of 20 mm and 500 mm respectively. A

whole brain seed was then used to calculate the structural connectivity matrix as the count of connections between each combination of the 90 AAL atlas regions.

Graph theory centrality measures of degree centrality, eigenvector centrality, and PageRank centrality were calculated using the NetworkX python library (Hagberg et al., 2008; using functions *degree*, *eigenvector_centrality*, and *pagerank*). These measures were calculated using a thresholded functional connectivity matrix, with the lower threshold set to the critical correlation coefficient for R with p = .0001 (see Zuo et al., 2012). Likewise, the DTI structural connectivity matrix was used to calculate degree, eigenvector, and PageRank centrality for each atlas region. The structural and functional centrality measures were then z-score standardized and rescaled to have values between -1 and 1.

Model Architecture

The Graph Nets (Battaglia et al., 2018) python library, which relies on Tensorflow (Abadi et al., 2015), was used with a message passing design, using 10 message passing steps (as in the default model defined by Battaglia et al., 2018; accessible at https://github.com/albertotono/graph_nets). Following Battaglia et al., (2018) two latent layers were used with 16 nodes in each layer for the update functions. Seventy percent of the data was used as a training set, with 10 percent used for validation during training and 20 percent saved for testing (as done previously; e.g., Wang et al., 2020). The Adam (Kingma and Ba, 2017) optimizer was used with default values (learning rate = .001, β_1 = .9, β_2 = .999, and $\varepsilon = 1 * 10^{-7}$). Training was performed using batch gradient descent, with a batch size of 24 used for training the edge prediction model, and a batch size of 32 used for the centrality prediction models (a batch size of 32 was also tried for the edge prediction model but this produced unstable loss during training, so the batch size was adjusted to 24). The loss function used was the mean

squared error (MSE) of the functional measures compared to the predicted values. One epoch

was completed when enough batches were completed to randomly sample as much unique test

data as possible (21 batches for size of 32, and 29 batches for size of 24). For the edge prediction

models, structural connectivity values were given as the input edges, all input nodes were

initialized with a value of 1.0, and functional connectivity measures were compared to the output

edges to calculate loss (see Figure 3a). For the centrality prediction models, structural

connectivity values were given as the input edges, structural centrality measures were given as

the input nodes, and functional centrality measures were compared to the output nodes to

calculate loss (see Figure 3b). In order to encourage the model to find an effective solution in as

few steps as possible, the loss was calculated as the mean MSE for all 10 message passing steps.

A Nvidia GTX 1080 graphical processing unit (GPU) was used for the centrality prediction

models and required approximately 24 hours to run 3000 epochs. A Nvidia GTX 3090 GPU was

used for the edge prediction model and required approximately 96 hours to run 5000 epochs.

Figure 3. Depiction of the steps in the (a) edge prediction model, and (b) centrality prediction

model, where ϕ^e represents the FCN update function for edges taking an edge and 2 connected

nodes as input, ϕ^v represents the FCN update function for nodes taking a node and the

aggregated value of connected edges as input, and $\rho^{e \rightarrow v}$ represents the aggregation of edge

values. Adapted from Battaglia et al. (2018).

Results

Edges

The edge prediction model was trained for 5000 epochs, and there was no evidence for overfitting of the model to the training set, as the validation set decreased its loss along with the training set (Figure 4). Figure 5 depicts the empirical versus the predicted mean values of functional connectivity, accounting for 72.4% of the variance in the 201 subject test group. The structural connectivity of each individual atlas region was iteratively lesioned, and this lesioned network was given to the previously trained model as input. The MSE loss was then calculated to determine the importance of each region to model performance (see Figure 6). The top 10 regions that impacted the model performance the most included the LH superior frontal lobe, LH insula, LH lingual gyrus, LH inferior, middle, and superior occipital lobe, RH calcarine cortex, RH supplementary motor area, RH precentral gyrus, and RH middle cingulate cortex. These examples include many regions that would be considered more unimodal than transmodal, including the occipital and motor regions. Numerous studies have demonstrated that the coupling of structure and function is greater for unimodal than for transmodal regions (e.g., Margulies et al., 2016; Preti and Van De Ville, 2019; Suárez et al., 2020), so we investigated whether the lesion impact on the model performance was related to structure-function coupling, calculated as the mean R^2 between structural and functional connectivity of each region. The structure-function coupling was positively related to lesion loss ($R(88) = .335$, $p = .001$), indicating that more highly coupled regions were more important for model performance (see Figure 7).

Figure 4. Edge prediction model MSE loss for training and validation sets as a function of the number of training epochs.

Figure 5. Predicted rsfMRI functional connectivity as a function of empirical rsfMRI functional connectivity ($R^2 = .724$).

Figure 6. Axial slices of functional connectivity loss (MSE) related to lesioning structural connectivity to each atlas region, where dark blue indicates a lesser effect on the model performance and dark red indicates a greater effect. Larger sphere size also indicates greater effect of lesion on model performance.

Figure 7. Lesioned functional connectivity loss as a function of structure-function coupling ($R(88) = .335$, $p = .001$).

Using the predicted functional connectivity, measures of centrality for degree, eigenvector, and PageRank were calculated by unstandardizing first before following the same thresholding and centrality calculation as described in the Methods. The mean predicted values for degree centrality accounted for 88.5% of the variance in the empirical data (see Figure 8), for eigenvector centrality accounted for 91.0% of the variance in the empirical data (see Figure 9), and for PageRank centrality accounted for 86.8% of the variance in the empirical data (see Figure 10). These results demonstrate that the model has accounted for a large amount of variance in connectivity as well as centrality, but in order to determine if even better performance could be produced, a model designed to directly predict centrality was utilized.

Figure 8. Degree centrality measures calculated from the predicted functional connectivity values as a function of empirical degree centrality ($R^2 = .885$).

Figure 9. Eigenvector centrality measures calculated from the predicted functional connectivity values as a function of empirical eigenvector centrality ($R^2 = .910$).

Figure 10. PageRank centrality measures calculated from the predicted functional connectivity values as a function of empirical PageRank centrality ($R^2 = .868$).

Degree Centrality

The degree prediction model was trained for 3000 epochs, and there was no evidence for overfitting of the model to the training set, as the validation set decreased its loss along with the training set (Figure 11). Figure 12 depicts the empirical versus the predicted mean values of functional degree centrality, accounting for 68.0% of the variance in the 201 subject test group. The previous calculation of degree centrality from the predicted functional connectivity performed better than this alternative model, accounting for 88.5% of the variance.

Figure 11. Degree centrality model MSE loss for training and validation sets as a function of the number of training epochs.

Figure 12. Predicted rsfMRI functional connectivity degree centrality as a function of empirical rsfMRI functional connectivity degree centrality (R^2 = .680).

Eigenvector Centrality

The eigenvector prediction model was trained for 3000 epochs, and there was no evidence for overfitting of the model to the training set, as the validation set decreased its loss along with the training set (Figure 13). Figure 14 depicts the empirical versus the predicted mean values of functional eigenvector centrality, accounting for 65.4% of the variance in the 201 subject test group. The previous calculation of eigenvector centrality from the predicted functional connectivity performed better than this alternative model, accounting for 91.0% of the variance.

Figure 13. Eigenvector centrality model MSE loss for training and validation sets as a function of the number of training epochs.

Figure 14. Predicted rsfMRI functional connectivity eigenvector centrality as a function of empirical rsfMRI functional connectivity eigenvector centrality ($R^2 = .654$).

PageRank Centrality

The eigenvector prediction model was trained for 3000 epochs, and there was no evidence for overfitting of the model to the training set, as the validation set decreased its loss along with the training set (Figure 15). Figure 16 depicts the empirical versus the predicted mean values of functional PageRank centrality, accounting for 66.0% of the variance in the 201 subject test group. The previous calculation of PageRank centrality from the predicted functional connectivity performed better than this alternative model, accounting for 86.8% of the variance.

Figure 15. PageRank centrality model MSE loss for training and validation sets as a function of the number of training epochs.

Figure 16. Predicted rsfMRI functional connectivity PageRank centrality as a function of empirical rsfMRI functional connectivity PageRank centrality ($R^2 = .660$).

Discussion

Resting state fMRI has been used to calculate functional connectivity networks in brain research for many years, and graph theory measures such as centrality have been calculated for these functional networks, yet a clear relationship between the physical structural connectivity derived values and what is assumed to be the 'effective' functional connectivity has been elusive. The most successful previous effort to predict functional connectivity from structural connectivity have been able to account for 36% of the variance in functional connectivity, and the importance of continuing efforts to improve model prediction performance has been recently highlighted (Suárez et al., 2020). However, by using the Graph Nets (Battaglia et al., 2018) deep learning model architecture, which is well suited to modeling network datasets, functional connectivity was predicted from structural connectivity, accounting for 72% of the variance. This prediction benchmark surpasses previous models which have used structural connectivity to

predict functional connectivity with deep learning (36%, Rosenthal et al., 2018), as well as

methods using a hybrid simulation approach with both structural connectivity and EEG data

(53%, Schirner et al., 2018). In addition, functional centrality was predicted from structural

connectivity and centrality data accounting for up to 91% of the variance. These results set an

important benchmark in what should be a continuing effort in the network neuroscience

community to determine the extent to which functional connectivity and graph theory measures

such as centrality can be derived from structural connectivity, and therefore to what extent we

can infer functional connectivity from structural connectivity.

The regions of the brain that are particularly important for the performance of the model

were highlighted by iteratively lesioning each region. Common regions with the highest

importance to the model performance included the superior frontal lobe, occipital regions,

middle cingulate cortex, insula, precentral gyrus, and supplementary motor area. The majority of

these regions would be considered as highly unimodal (occipital and motor regions), which has

previously been shown to coincide with higher structure-function coupling (e.g., Margulies et al.,

2016; Preti and Van De Ville, 2019; Suárez et al., 2020). In order to test whether the structure-

function coupling may affect how important a region is to model performance, structure-function

coupling was compared to lesion loss. Indeed, higher structure-function coupling was associated

with that region being more important for model performance, indicating that part of what makes

a region more important to the model is the extent to which structure and function are related.

Future Directions

The graph neural network deep learning model architecture is one that is designed with

networks in mind, and maintains the structure of the brain connectivity data, whereas other

commonly used deep learning approaches do not. We have demonstrated here that this is an

effective deep learning model for use with structural and functional connectivity data. Future research predicting patient, demographic, or behavioural data should also make use of this method in order to improve on past deep learning attempts. Prediction of task activation from structural connectivity has also been explored in recent research (e.g., Ekstrand et al., 2020; Osher et al., 2016; Wu et al., 2020), and this model could also lead to improvements in task activation prediction.

As this model is further developed to account for variance in functional connectivity, this approach may also lead to predictive functional mapping for patients who are unable to follow fMRI instructions. Alternatively, there may be an upper limit on the amount of information about structural connectivity that is contained in functional connectivity measures. This upper limit may exist due to a number of factors. Neuromodulation selectively inhibits and excites neurons throughout the brain network, leading to dynamic patterns of functional connectivity, so although the underlying structure does not change during MRI imaging, the functional connectivity is in constant flux (Bell and Shine, 2016; Shine, 2019). The low spatial resolution of the atlas used also means that the precise structural connectivity patterns between neurons cannot be measured. In addition, functional boundaries can vary across individuals and between sessions (Gordon et al., 2017; Laumann et al., 2015; Mueller et al., 2013; Salehi et al., 2020; Suárez et al., 2020; Wang et al., 2015), so the use of atlases is a source of error for this reason as well. The temporal dynamics also differ from one region to the next, affecting the calculation of functional connectivity (Gollo et al., 2015; Keitel and Gross, 2016; Murray et al., 2014; Shafiei et al., 2019; Suárez et al., 2020). Depending on how unimodal or transmodal a region is, there may be a higher (unimodal) or lower (transmodal) degree of coupling between structure and function (Margulies et al., 2016; Preti and Van De Ville, 2019; Suárez et al., 2020). Additional atlases

should be used to predict function from structure in order to determine whether there is

consistency (or lack thereof) across them. Based on our deep learning model results, there is

clearly much more variance in functional connectivity that can be accounted for by structural

connectivity using a graph neural network approach, and future research should continue to

develop further graph theory and simulation methods able to explicitly define the nature of the

relationship between the two.

Conclusion

Our graph neural network deep learning model provides a new benchmark for prediction

of rsfMRI functional connectivity (72% of variance) and functional centrality (91% of variance)

from DTI structural connectivity, which far exceeds the performance of the non graph neural

network models previously reported by others (36%). This research has not only brought us

closer to finding the upper limit on prediction of connectivity and centrality of function from

structural connectivity, it has opened new doors for understanding the structure-function network

relationships in the human brain.

Acknowledgements

This research was supported by the Natural Sciences and Engineering Research Council of Canada through Alexander Graham Bell Canada Graduate Scholarships to Josh Neudorf and Shaylyn Kress, and Discovery Grant 18968-2013-22 to the senior author Ron Borowsky. The authors affirm that there are no conflicts of interest to disclose.

Data were provided [in part] by the Human Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience at Washington University.

References

Abadi, M., Agarwal, A., Barham, P., Brevdo, E., Chen, Z., Citro, C., Corrado, G.S., Davis, A., Dean, J., Devin, M., Ghemawat, S., Goodfellow, I., Harp, A., Irving, G., Isard, M., Jia, Y., Jozefowicz, R., Kaiser, L., Kudlur, M., Levenberg, J., Mane, D., Monga, R., Moore, S., Murray, D., Olah, C., Schuster, M., Shlens, J., Steiner, B., Sutskever, I., Talwar, K., Tucker, P., Vanhoucke, V., Vasudevan, V., Viegas, F., Vinyals, O., Warden, P., Wattenberg, M., Wicke, M., Yu, Y., Zheng, X., 2015. TensorFlow: Large-Scale Machine Learning on Heterogeneous Distributed Systems 19.

Arslan, S., Ktena, S.I., Glocker, B., Rueckert, D., 2018. Graph Saliency Maps Through Spectral Convolutional Networks: Application to Sex Classification with Brain Connectivity, in: Stoyanov, D., Taylor, Z., Ferrante, E., Dalca, A.V., Martel, A., Maier-Hein, L., Parisot, S., Sotiras, A., Papiez, B., Sabuncu, M.R., Shen, L. (Eds.), Graphs in Biomedical Image Analysis and Integrating Medical Imaging and Non-Imaging Modalities, Lecture Notes in Computer Science. Springer International Publishing, Cham, pp. 3–13. https://doi.org/10.1007/978-3-030-00689-1_1

Arya, D., Olij, R., Gupta, D.K., Gazzar, A.E., Wingen, G., Worring, M., Thomas, R.M., 2020. Fusing Structural and Functional MRIs using Graph Convolutional Networks for Autism Classification, in: Medical Imaging with Deep Learning. Presented at the Medical Imaging with Deep Learning, PMLR, pp. 44–61.

Battaglia, P.W., Hamrick, J.B., Bapst, V., Sanchez-Gonzalez, A., Zambaldi, V., Malinowski, M., Tacchetti, A., Raposo, D., Santoro, A., Faulkner, R., Gulcehre, C., Song, F., Ballard, A., Gilmer, J., Dahl, G., Vaswani, A., Allen, K., Nash, C., Langston, V., Dyer, C., Heess, N., Wierstra, D., Kohli, P., Botvinick, M., Vinyals, O., Li, Y., Pascanu, R., 2018. Relational inductive biases, deep learning, and graph networks. ArXiv180601261 Cs Stat.

Bell, P.T., Shine, J.M., 2016. Subcortical contributions to large-scale network communication. Neurosci. Biobehav. Rev. 71, 313–322. https://doi.org/10.1016/j.neubiorev.2016.08.036

Bi, X., Liu, Z., He, Y., Zhao, X., Sun, Y., Liu, H., 2020. GNEA: A Graph Neural Network with ELM Aggregator for Brain Network Classification [WWW Document]. Complexity. https://doi.org/10.1155/2020/8813738

Birn, R.M., Smith, M.A., Jones, T.B., Bandettini, P.A., 2008. The respiration response function: The temporal dynamics of fMRI signal fluctuations related to changes in respiration. NeuroImage 40, 644–654. https://doi.org/10.1016/j.neuroimage.2007.11.059

Chang, C., Cunningham, J.P., Glover, G.H., 2009. Influence of heart rate on the BOLD signal: The cardiac response function. NeuroImage 44, 857–869. https://doi.org/10.1016/j.neuroimage.2008.09.029

Chen, C., Wang, H.-L., Wu, S.-H., Huang, H., Zou, J.-L., Chen, J., Jiang, T.-Z., Zhou, Y., Wang, G.-H., 2015. Abnormal Degree Centrality of Bilateral Putamen and Left Superior Frontal Gyrus in Schizophrenia with Auditory Hallucinations: A Resting-state Functional Magnetic Resonance Imaging Study. Chin. Med. J. (Engl.) 128, 3178–3184. https://doi.org/10.4103/0366-6999.170269

Deng, W., Zhang, B., Zou, W., Zhang, X., Cheng, X., Guan, L., Lin, Y., Lao, G., Ye, B., Li, X., Yang, C., Ning, Y., Cao, L., 2019. Abnormal Degree Centrality Associated With Cognitive Dysfunctions in Early Bipolar Disorder. Front. Psychiatry 10. https://doi.org/10.3389/fpsyt.2019.00140

Ekstrand, C., Neudorf, J., Kress, S., Borowsky, R., 2020. Structural connectivity predicts functional activation during lexical and sublexical reading. NeuroImage 218, 117008. https://doi.org/10.1016/j.neuroimage.2020.117008

Estrada, E., Hatano, N., 2008. Communicability in complex networks. Phys. Rev. E 77, 036111. https://doi.org/10.1103/PhysRevE.77.036111

Falahpour, M., Refai, H., Bodurka, J., 2013. Subject specific BOLD fMRI respiratory and cardiac response functions obtained from global signal. NeuroImage 72, 252–264. https://doi.org/10.1016/j.neuroimage.2013.01.050

Glasser, M.F., Sotiropoulos, S.N., Wilson, J.A., Coalson, T.S., Fischl, B., Andersson, J.L., Xu, J., Jbabdi, S., Webster, M., Polimeni, J.R., Van Essen, D.C., Jenkinson, M., 2013. The minimal preprocessing pipelines for the Human Connectome Project. NeuroImage, Mapping the Connectome 80, 105–124. https://doi.org/10.1016/j.neuroimage.2013.04.127

Golestani, A.M., Chang, C., Kwinta, J.B., Khatamian, Y.B., Jean Chen, J., 2015. Mapping the end-tidal CO_2 response function in the resting-state BOLD fMRI signal: Spatial specificity, test–retest reliability and effect of fMRI sampling rate. NeuroImage 104, 266–277. https://doi.org/10.1016/j.neuroimage.2014.10.031

Gollo, L.L., Zalesky, A., Hutchison, R.M., van den Heuvel, M., Breakspear, M., 2015. Dwelling quietly in the rich club: brain network determinants of slow cortical fluctuations. Philos. Trans. R. Soc. B Biol. Sci. 370, 20140165. https://doi.org/10.1098/rstb.2014.0165

Goñi, J., Heuvel, M.P. van den, Avena-Koenigsberger, A., Mendizabal, N.V. de, Betzel, R.F., Griffa, A., Hagmann, P., Corominas-Murtra, B., Thiran, J.-P., Sporns, O., 2014. Resting-brain functional connectivity predicted by analytic measures of network communication. Proc. Natl. Acad. Sci. 111, 833–838. https://doi.org/10.1073/pnas.1315529111

Gordon, E.M., Laumann, T.O., Gilmore, A.W., Newbold, D.J., Greene, D.J., Berg, J.J., Ortega, M., Hoyt-Drazen, C., Gratton, C., Sun, H., Hampton, J.M., Coalson, R.S., Nguyen, A.L., McDermott, K.B., Shimony, J.S., Snyder, A.Z., Schlaggar, B.L., Petersen, S.E., Nelson, S.M., Dosenbach, N.U.F., 2017. Precision Functional Mapping of Individual Human Brains. Neuron 95, 791-807.e7. https://doi.org/10.1016/j.neuron.2017.07.011

Hagberg, A.A., Schult, D.A., Swart, P.J., 2008. Exploring Network Structure, Dynamics, and Function using NetworkX 5.

Hagmann, P., Cammoun, L., Gigandet, X., Meuli, R., Honey, C.J., Wedeen, V.J., Sporns, O., 2008. Mapping the Structural Core of Human Cerebral Cortex. PLOS Biol. 6, e159. https://doi.org/10.1371/journal.pbio.0060159

Hallquist, M.N., Hwang, K., Luna, B., 2013. The nuisance of nuisance regression: Spectral misspecification in a common approach to resting-state fMRI preprocessing reintroduces noise and obscures functional connectivity. NeuroImage 82, 208–225. https://doi.org/10.1016/j.neuroimage.2013.05.116

Honey, C.J., Sporns, O., Cammoun, L., Gigandet, X., Thiran, J.P., Meuli, R., Hagmann, P., 2009. Predicting human resting-state functional connectivity from structural connectivity. Proc. Natl. Acad. Sci. 106, 2035–2040. https://doi.org/10.1073/pnas.0811168106

Kassinopoulos, M., Mitsis, G.D., 2019. Identification of physiological response functions to correct for fluctuations in resting-state fMRI related to heart rate and respiration. NeuroImage 202, 116150. https://doi.org/10.1016/j.neuroimage.2019.116150

Keitel, A., Gross, J., 2016. Individual Human Brain Areas Can Be Identified from Their Characteristic Spectral Activation Fingerprints. PLOS Biol. 14, e1002498. https://doi.org/10.1371/journal.pbio.1002498

Kingma, D.P., Ba, J., 2017. Adam: A Method for Stochastic Optimization. ArXiv14126980 Cs.

Ktena, S.I., Parisot, S., Ferrante, E., Rajchl, M., Lee, M., Glocker, B., Rueckert, D., 2017. Distance Metric Learning Using Graph Convolutional Networks: Application to Functional Brain Networks, in: Descoteaux, M., Maier-Hein, L., Franz, A., Jannin, P., Collins, D.L., Duchesne, S. (Eds.), Medical Image Computing and Computer Assisted Intervention − MICCAI 2017, Lecture Notes in Computer Science. Springer International Publishing, Cham, pp. 469–477. https://doi.org/10.1007/978-3-319-66182-7_54

Laumann, T.O., Gordon, E.M., Adeyemo, B., Snyder, A.Z., Joo, S.J., Chen, M.-Y., Gilmore, A.W., McDermott, K.B., Nelson, S.M., Dosenbach, N.U.F., Schlaggar, B.L., Mumford, J.A., Poldrack, R.A., Petersen, S.E., 2015. Functional System and Areal Organization of a Highly Sampled Individual Human Brain. Neuron 87, 657–670. https://doi.org/10.1016/j.neuron.2015.06.037

Lin, Q., Zhu, F.-Y., Shu, Y.-Q., Zhu, P.-W., Ye, L., Shi, W.-Q., Min, Y.-L., Li, B., Yuan, Q., Shao, Y., 2021. Altered brain network centrality in middle-aged patients with retinitis pigmentosa: A resting-state functional magnetic resonance imaging study. Brain Behav. 11, e01983. https://doi.org/10.1002/brb3.1983

Long, X., Little, G., Treit, S., Beaulieu, C., Gong, G., Lebel, C., 2020. Altered brain white matter connectome in children and adolescents with prenatal alcohol exposure. Brain Struct. Funct. 225, 1123–1133. https://doi.org/10.1007/s00429-020-02064-z

Margulies, D.S., Ghosh, S.S., Goulas, A., Falkiewicz, M., Huntenburg, J.M., Langs, G., Bezgin, G., Eickhoff, S.B., Castellanos, F.X., Petrides, M., Jefferies, E., Smallwood, J., 2016. Situating the default-mode network along a principal gradient of macroscale cortical organization. Proc. Natl. Acad. Sci. 113, 12574–12579. https://doi.org/10.1073/pnas.1608282113

Mueller, S., Wang, D., Fox, M.D., Yeo, B.T.T., Sepulcre, J., Sabuncu, M.R., Shafee, R., Lu, J., Liu, H., 2013. Individual Variability in Functional Connectivity Architecture of the Human Brain. Neuron 77, 586–595. https://doi.org/10.1016/j.neuron.2012.12.028

Murray, J.D., Bernacchia, A., Freedman, D.J., Romo, R., Wallis, J.D., Cai, X., Padoa-Schioppa, C., Pasternak, T., Seo, H., Lee, D., Wang, X.-J., 2014. A hierarchy of intrinsic timescales across primate cortex. Nat. Neurosci. 17, 1661–1663. https://doi.org/10.1038/nn.3862

Neudorf, J., Ekstrand, C., Kress, S., Borowsky, R., 2020. Brain Structural Connectivity Predicts Brain Functional Complexity: Diffusion Tensor Imaging Derived Centrality Accounts for Variance in Fractal Properties of Functional Magnetic Resonance Imaging Signal. Neuroscience 438, 1–8. https://doi.org/10.1016/j.neuroscience.2020.04.048

Osher, D.E., Saxe, R.R., Koldewyn, K., Gabrieli, J.D.E., Kanwisher, N., Saygin, Z.M., 2016. Structural Connectivity Fingerprints Predict Cortical Selectivity for Multiple Visual Categories across Cortex. Cereb. Cortex 26, 1668–1683. https://doi.org/10.1093/cercor/bhu303

Page, L., Brin, S., Motwani, R., Winograd, T., 1999. The PageRank Citation Ranking: Bringing Order to the Web. [WWW Document]. URL http://ilpubs.stanford.edu:8090/422/ (accessed 9.23.19).

Parisot, S., Ktena, S.I., Ferrante, E., Lee, M., Guerrero, R., Glocker, B., Rueckert, D., 2018. Disease prediction using graph convolutional networks: Application to Autism Spectrum

Disorder and Alzheimer's disease. Med. Image Anal. 48, 117–130.
https://doi.org/10.1016/j.media.2018.06.001

Preti, M.G., Van De Ville, D., 2019. Decoupling of brain function from structure reveals regional
behavioral specialization in humans. Nat. Commun. 10, 4747.
https://doi.org/10.1038/s41467-019-12765-7

Raizman, R., Tavor, I., Biegon, A., Harnof, S., Hoffmann, C., Tsarfaty, G., Fruchter, E., Tatsa-
Laur, L., Weiser, M., Livny, A., 2020. Traumatic Brain Injury Severity in a Network
Perspective: A Diffusion MRI Based Connectome Study. Sci. Rep. 10, 9121.
https://doi.org/10.1038/s41598-020-65948-4

Rosenthal, G., Váša, F., Griffa, A., Hagmann, P., Amico, E., Goñi, J., Avidan, G., Sporns, O.,
2018. Mapping higher-order relations between brain structure and function with
embedded vector representations of connectomes. Nat. Commun. 9, 1–12.
https://doi.org/10.1038/s41467-018-04614-w

Salas, J.A., Bayrak, R.G., Huo, Y., Chang, C., 2021. Reconstruction of respiratory variation
signals from fMRI data. NeuroImage 225, 117459.
https://doi.org/10.1016/j.neuroimage.2020.117459

Salehi, M., Greene, A.S., Karbasi, A., Shen, X., Scheinost, D., Constable, R.T., 2020. There is no
single functional atlas even for a single individual: Functional parcel definitions change
with task. NeuroImage 208, 116366. https://doi.org/10.1016/j.neuroimage.2019.116366

Salimi-Khorshidi, G., Douaud, G., Beckmann, C.F., Glasser, M.F., Griffanti, L., Smith, S.M.,
2014. Automatic Denoising of Functional MRI Data: Combining Independent
Component Analysis and Hierarchical Fusion of Classifiers. NeuroImage 90, 449–468.
https://doi.org/10.1016/j.neuroimage.2013.11.046

Schirner, M., McIntosh, A.R., Jirsa, V., Deco, G., Ritter, P., 2018. Inferring multi-scale neural
mechanisms with brain network modelling. eLife 7, e28927.
https://doi.org/10.7554/eLife.28927

Shafiei, G., Zeighami, Y., Clark, C.A., Coull, J.T., Nagano-Saito, A., Leyton, M., Dagher, A.,
Mišić, B., 2019. Dopamine Signaling Modulates the Stability and Integration of Intrinsic
Brain Networks. Cereb. Cortex 29, 397–409. https://doi.org/10.1093/cercor/bhy264

Shine, J.M., 2019. Neuromodulatory Influences on Integration and Segregation in the Brain.
Trends Cogn. Sci. 23, 572–583. https://doi.org/10.1016/j.tics.2019.04.002

Suárez, L.E., Markello, R.D., Betzel, R.F., Misic, B., 2020. Linking Structure and Function in
Macroscale Brain Networks. Trends Cogn. Sci. 24, 302–315.
https://doi.org/10.1016/j.tics.2020.01.008

Turkiewicz, J., Bhatt, R.R., Wang, H., Vora, P., Krause, B., Sauk, J.S., Jacobs, J.P., Bernstein,
C.N., Kornelsen, J., Labus, J.S., Gupta, A., Mayer, E.A., 2021. Altered brain structural
connectivity in patients with longstanding gut inflammation is correlated with
psychological symptoms and disease duration. NeuroImage Clin. 102613.
https://doi.org/10.1016/j.nicl.2021.102613

Tzourio-Mazoyer, N., Landeau, B., Papathanassiou, D., Crivello, F., Etard, O., Delcroix, N.,
Mazoyer, B., Joliot, M., 2002. Automated Anatomical Labeling of Activations in SPM
Using a Macroscopic Anatomical Parcellation of the MNI MRI Single-Subject Brain.
NeuroImage 15, 273–289. https://doi.org/10.1006/nimg.2001.0978

van den Heuvel, M.P., Hulshoff Pol, H.E., 2010. Exploring the brain network: A review on
resting-state fMRI functional connectivity. Eur. Neuropsychopharmacol. 20, 519–534.
https://doi.org/10.1016/j.euroneuro.2010.03.008

Van Essen, D.C., Smith, S.M., Barch, D.M., Behrens, T.E.J., Yacoub, E., Ugurbil, K., 2013. The WU-Minn Human Connectome Project: An overview. NeuroImage, Mapping the Connectome 80, 62–79. https://doi.org/10.1016/j.neuroimage.2013.05.041

Wang, D., Buckner, R.L., Fox, M.D., Holt, D.J., Holmes, A.J., Stoecklein, S., Langs, G., Pan, R., Qian, T., Li, K., Baker, J.T., Stufflebeam, S.M., Wang, K., Wang, X., Hong, B., Liu, H., 2015. Parcellating cortical functional networks in individuals. Nat. Neurosci. 18, 1853–1860. https://doi.org/10.1038/nn.4164

Wang, X., Liang, X., Jiang, Z., Nguchu, B.A., Zhou, Y., Wang, Y., Wang, H., Li, Y., Zhu, Y., Wu, F., Gao, J.-H., Qiu, B., 2020. Decoding and mapping task states of the human brain via deep learning. Hum. Brain Mapp. 41, 1505–1519. https://doi.org/10.1002/hbm.24891

Wink, A.M., Tijms, B.M., ten Kate, M., Raspor, E., de Munck, J.C., Altena, E., Ecay-Torres, M., Clerigue, M., Estanga, A., Garcia-Sebastian, M., Izagirre, A., Martinez-Lage Alvarez, P., Villanua, J., Barkhof, F., Sanz-Arigita, E., 2018. Functional brain network centrality is related to APOE genotype in cognitively normal elderly. Brain Behav. 8. https://doi.org/10.1002/brb3.1080

Wu, D., Fan, L., Song, M., Wang, H., Chu, C., Yu, S., Jiang, T., 2020. Hierarchy of Connectivity–Function Relationship of the Human Cortex Revealed through Predicting Activity across Functional Domains. Cereb. Cortex 30, 4607–4616. https://doi.org/10.1093/cercor/bhaa063

Xu, Q.-H., Li, Q.-Y., Yu, K., Ge, Q.-M., Shi, W.-Q., Li, B., Liang, R.-B., Lin, Q., Zhang, Y.-Q., Shao, Y., 2020. Altered Brain Network Centrality in Patients with Diabetic Optic Neuropathy: A Resting-State FMRI Study. Endocr. Pract. 26, 1399–1405. https://doi.org/10.4158/EP-2020-0045

Yeh, F., Wedeen, V.J., Tseng, W.I., 2010. Generalized $ q$-Sampling Imaging. IEEE Trans. Med. Imaging 29, 1626–1635. https://doi.org/10.1109/TMI.2010.2045126

Yeh, F.-C., Verstynen, T.D., Wang, Y., Fernández-Miranda, J.C., Tseng, W.-Y.I., 2013. Deterministic Diffusion Fiber Tracking Improved by Quantitative Anisotropy. PLoS ONE 8. https://doi.org/10.1371/journal.pone.0080713

Yu, Z., Tao, L., Qian, Z., Wu, J., Liu, H., Yu, Y., Song, J., Wang, S., Sun, J., 2016. Altered brain anatomical networks and disturbed connection density in brain tumor patients revealed by diffusion tensor tractography. Int. J. Comput. Assist. Radiol. Surg. 11, 2007–2019. https://doi.org/10.1007/s11548-015-1330-y

Zhang, W., Wang, Y., 2020. Deep Multimodal Brain Network Learning for Joint Analysis of Structural Morphometry and Functional Connectivity, in: 2020 IEEE 17th International Symposium on Biomedical Imaging (ISBI). Presented at the 2020 IEEE 17th International Symposium on Biomedical Imaging (ISBI), pp. 1–5. https://doi.org/10.1109/ISBI45749.2020.9098624

Zhou, Q., Womer, F.Y., Kong, L., Wu, F., Jiang, X., Zhou, Y., Wang, D., Bai, C., Chang, M., Fan, G., Xu, K., He, Y., Tang, Y., Wang, F., 2017. Trait-Related Cortical-Subcortical Dissociation in Bipolar Disorder: Analysis of Network Degree Centrality. J. Clin. Psychiatry 78, 584–591. https://doi.org/10.4088/JCP.15m10091

Zuo, X.-N., Ehmke, R., Mennes, M., Imperati, D., Castellanos, F.X., Sporns, O., Milham, M.P., 2012. Network Centrality in the Human Functional Connectome. Cereb. Cortex 22, 1862–1875. https://doi.org/10.1093/cercor/bhr269