Hyperbolic disc embedding of functional human brain connectomes using resting state fMRI

Wonseok Whi[1,2], Seunggyun Ha[3], Hyejin Kang[4*], Dong Soo Lee[1,2,5*]

[1]Department of Molecular Medicine and Biopharmaceutical Sciences, Seoul National University, Seoul, Korea

[2]Department of Nuclear Medicine, Seoul National University and Seoul National University Hospital, Seoul, Korea

[3]Division of Nuclear Medicine, Department of Radiology, Seoul St. Mary's Hospital, The Catholic University of Korea, Seoul, Korea

[4]Biomedical Research Institute, Seoul National University Hospital, Seoul, Korea

[5]Medical Research Center, Seoul National University, Seoul, Korea

* Correspondence to H. K. (hkang211@snu.ac.kr) or D.S.L. (dsl@snu.ac.kr)

Abstract

The brain presents a real complex network of modular, small-world, and hierarchical nature, which are features of non-Euclidean geometry. Using resting-state functional magnetic resonance imaging (rs-fMRI), we constructed a scale-free binary graph for each subject, using internodal time-series correlation of regions-of-interest (ROIs) as a proximity measure. The resulted network could be embedded onto manifolds of various curvature and dimensions. While maintaining the fidelity of embedding (low distortion, high mean average precision), functional brain networks were found to be best represented in the hyperbolic disc. Using $\mathbb{S}^1/\mathbb{H}^2$ model, we reduced the dimension of the network into 2-D hyperbolic space and were able to efficiently visualize the internodal connections of the brain, preserving proximity as distances and angles on the hyperbolic discs. Each individual disc revealed decentralized nature of information flow and anatomic relevance. Using the hyperbolic distance on the $\mathbb{S}^1/\mathbb{H}^2$ model, we could detect the anomaly of network in autistic spectrum disorder (ASD) subjects. This procedure of embedding grants us a reliable new framework for studying functional brain networks and the possibility of detecting anomalies of the network in the hyperbolic disc on an individual scale.

Keywords: functional brain network, hyperbolic geometry, hyperbolic embedding, $\mathbb{S}^1/\mathbb{H}^2$

model

Introduction

Significant progress has been achieved over the last decades in unveiling the structure and

mechanism of the human brain, which is one of the most complicated systems of nature.

Especially, studies on the network geometry, which offer a new perspective on the framework

of structural brain networks[1,2], or connectomes, have revealed that structural brain networks

share certain topological properties such as modularity[3], small-world[4], and heavy-tailed

degree distribution[5].

However, Euclidean geometry, which serves as a standard framework of

investigation in our physical reality, does not seem to suffice in explaining the observed

connectivity between the brain regions, functional as well as structural. Instead, an increasing

amount of evidence suggests that the geometry of negative curvature i.e. hyperbolic geometry

serves as the more appropriate explanatory platform of the above-mentioned topologic

features of the structural brain networks that dominates the formation of the network and the

probability of connections between the brain regions[6,7].

Since the functional brain network was closely related to the connectomes[8-10], we

assume that the functional brain network best fits with the hyperbolic geometry, which is

regarded as the geometric representation of high-dimensional tree or tree-like graphs with

hierarchies[11]. However, real complex graphs could also have a cycle or torus-like structures

therein in any dimensions and necessitated the trial-fitting to spherical space of positive

curvatures. As hyperbolic and spherical spaces with various curvatures and Euclidean space

can be combined to represent real complex graphs with the product of spaces, any real

complex graphs can now be tested for their feasibility of fitting to the model of a product of

spaces with various negative and/or positive curvatures. The only reserve is to find the model

space of appropriate dimension and curvature to fit the real complex networks.

By this means, we later show that we successfully embedded the functional brain

graphs observed on resting-state functional MRI (rs-fMRI) to be fit to the 2-dimensional

hyperbolic plane (disc) with better fidelity compared with other product manifolds of low

dimension. In this study, we used a purely geometric $\mathbb{S}^1/\mathbb{H}^2$ model, which is well known to

reveal the hidden geometry of many other real complex networks of non-Euclidean nature,

such as internet connection[12], world trade web[13] or even the structural brain network[6,7].

When we adopted the binary graph obtained by rs-fMRI as an input to the $\mathbb{S}^1/\mathbb{H}^2$

model, we could fit the nodes to their optimal positions on the hyperbolic disc proposed by

Papadopoulos et al.[14] and further publicized as *Mercator*[15]. The position of the nodes could be

used to calculate the hyperbolic distance between each node, which serves as a unique

variable for determining the connection probability between the nodes on this disc[16]. We used

the distance matrix for comparison of the proximity between brain region pairs across the

individuals with autism spectrum disorder (ASD) and control group to see if the method is

applicable to real cases of diseased subjects.

Results

Distribution of time-series correlation in rs-fMRI

We used the pre-defined parcellation of the whole brain into 274 regions of interest (ROIs)

and computed the time-series correlation between the ROIs. The distribution of the value of

coefficients is shown in (**Fig. 1a**). Overall, a positive correlation was dominant among edges

from the healthy young adults, while a small portion of edges showed a negative correlation.

Detailed visualization of correlation matrix from a representative case is shown in (**Fig. 1b**).

We regarded that a certain degree of anticorrelation between brain regions also suggested

connection and took the absolute value of the correlation coefficient for thresholding the

network.

Determining the threshold of correlation for binary network composition

To form the binarized adjacency matrix for each fMRI image, we applied various threshold

values to correlation matrix in order to choose binary network that satisfies scale-free

property. The chosen threshold yielded degree distribution which fit well to linear plot on

log-log relations between degree and degree frequency and included most of the nodes within

the largest connected component of the resulting binary network. After we investigated the

degree distribution of the graph and the average size of the largest connected component, we

chose the threshold for individuals and finally entire population. When we applied a higher

threshold, more nodes without any connection were excluded from the component. On the

other hand, when we lowered the threshold, the network lost its scale-freeness, which make

the later embedding procedure theoretically inappropriate.

Since we wanted to retain as many nodes as possible in every case, we applied the

highest threshold possible while the scale-freeness of the network is valid. These procedures

are shown in (**Fig. 2**) for three cases of control subjects from Autism Brain Imaging Data

Exchange (ABIDE) II dataset. In a threshold value of 0.35 (**Fig. 2a**), in which most of the

nodes are preserved, the degree distribution forms a peaked curve, which violates the

scale-freeness of the network. While, in a higher threshold value of 0.45 (**Fig. 2c**), 4.8% of

nodes, an average of 13 nodes per network is excluded from the largest component, which is

considered inappropriate for a whole-brain analysis. Therefore, after searching the entire

population of 180 subjects, the threshold value was determined as 0.40 (**Fig. 2b**). For the

human connectome project (HCP) dataset, the threshold value was set to 0.36, which resulted

from a similar procedure.

Embedding of the graphs into spaces of various curvatures/dimensions

To find the most natural way of embedding brain graphs into manifolds, we compared the

average distortion (D_{avg}) and mean average precision (mAP) of embedding between the target

manifolds. Ten representative data in the HCP dataset and ABIDE dataset were used for

embedding. The target manifolds were hyperbolic, spherical (with unit curvatures, i.e. -1 and

1, respectively), and Euclidean manifolds of 10 and 2 dimensions, plus the single dimension

of a spherical manifold $\mathbb{S}^1$ (i.e., circle).

Among the low dimensions, embedding to the 2-dimensional hyperbolic space of

$\mathbb{H}^2$ had significantly higher mean average precision (mAP) than embedding to $\mathbb{E}^2$ and $\mathbb{S}^1$.

For ABIDE II dataset, embedding to 10-dimensional hyperbolic space of $\mathbb{H}^{10}$ tended to have

lower distortion than embedding to $\mathbb{E}^{10}$. For both datasets, embedding to the 2-dimensional

hyperbolic space of $\mathbb{H}^2$ had significantly lower distortion than embedding to $\mathbb{E}^2$ and $\mathbb{S}^1$

(**Table 1-2, Fig. 3a-b**). Notably, for both datasets, embedding to the 2-dimensional hyperbolic

space of $\mathbb{H}^2$ had significantly lower distortion than embedding to $\mathbb{E}^2$ and $\mathbb{S}^1$ (**Fig. 3c-d**).

Embedding graphs into the 2-D hyperbolic disc

For each subject, we embedded the largest component of the binary graph to a hyperbolic plane according to the $\mathbb{S}^1/\mathbb{H}^2$ model. Results of the embedding (in the ROI scope) of the representative cases are shown in (**Fig. 4**). Color denotes the anatomic lobe, while the lobes within the right and left cerebral hemispheres and cerebellum are marked with circular, square, and triangular markers, respectively. The results of embedding in the voxel scale are shown in (**Supplementary Fig. 1**).

Every embedding result revealed vacant space in the center of the disk. ROIs from the bilateral insula, subcortical, and cerebellum had narrow angular distributions. ROIs from more large anatomic lobes (frontal, temporal, parietal) were located with relatively broader distributions. And ROIs from the same lobes of contralateral sides (for example, right and left frontal lobes) had similar distributions of angles.

To assess the validity of embedding, we compared the absolute value of original correlation coefficients used for thresholding with connection probability between the edges, which resulted in hyperbolic distances computed on the $\mathbb{S}^1/\mathbb{H}^2$ model (**Fig. 5**). The two measures, which are commonly scaled from 0 to 1, tended to show similar patterns for each of the subjects. We discussed the similarity and difference between the two measures in (**Supplementary Note 1**).

To investigate if the embedding results are compatible with other established

methods of functional segregation, we made use of network components calculated by

independent component analysis (ICA) and plotted the composing voxels of each

independent component in colors in the $\mathbb{S}^1/\mathbb{H}^2$ disc (**Supplementary Fig. 2**). To remove the

arbitrariness of rotation by the constant angle in the embedded disks, we adjusted the angular

position of the embedded disks in order for the mean angle of the visual network (VN) to

have a value of 0 (**Supplementary Fig. 3**). However, rotational symmetry should be

considered to see the distribution of each component and belonging voxels thereof.

We assessed the reproducibility of the embedding process by measuring the

coefficient of variance for the hyperbolic distance matrices in one representative case (**Fig. 6**,

Supplementary Fig. 4). Most of the nodes had relatively low arbitrariness of position in

repeated embedding procedure. Meanwhile, outermost positioned nodes, which represents

low popularity, tended to have a position with higher variability (**Supplementary Note 2**).

Detection of abnormal functional pathway on hyperbolic disc in the ASD subjects

Among the variable patterns of functional brain networks embedded on $\mathbb{S}^1/\mathbb{H}^2$ model from

ASD group subjects, one subject of autism spectrum disorder showed a longer hyperbolic

distance of node pairs connecting the bilateral frontoparietal cortices and bilateral basal

ganglia, which represents the cortico-striatal pathway, compared to the control group of 134

healthy young adults (**Fig. 7a**) ($P < 0.05$). This tendency was not prominent when the

comparison analysis was conducted on correlation matrices of a subject and 134 controls.

Notably, a subject with Asperger's syndrome showed a shorter hyperbolic distance of

the edges of node pairs, which connect bilateral posterior superior temporal sulcus (pSTS)

and basal ganglia, and the correlation study showed a similar pattern (**Fig. 7b**) ($P < 0.05$).

Discussion

Neuroscientific work in the past decades has provided the perspective that the brain is a

complex network that is composed of interactions between regions[17], and rs-fMRI has

emerged as an efficient tool in exploring the connection[18]. However, it still remains unclear

how each region of the brain is connected functionally in a multiplex way and organized in

higher order to perform its complicated function at rest with activation whose amplitude was

smaller than when related with tasks. Preceding work by Allard et al.[7,19] implemented

hyperbolic geometry model to enlighten this question by providing a map of structural

connectomes, while exploiting this geometry's expansive space able to contain brain

connectome's high-order and high-dimensional correlational structure. One of the major

advantages of this model is that it implements 2-dimensional hyperbolic space to embed the

network, which is makes it easy to visualize brain connectomes and to understand of how the brain regions are working in a multiplex connected fashion.

Meanwhile, not much work has attempted to yield deep insight of this subtle correlative works of multiple nodes of an individual brain from the norms made of many subjects as represented by an individual functional map to define an unheralded disease-specific anomaly of a single affected subject. Since many neurologic disorders are classified as a group of similar clinical manifestations[20] with unclear neurologic pathophysiology, changing the scope into connectomes of affected individuals might significantly help in further classifying the disease entities and provide information in the treatment of disease. Furthermore, this work inherits the advantage of the preceding work by Allard et al., that the resulting object is represented in 2-dimensional space both for visualization and for further analysis to disclose which internodal connections are deviated from the norms in these hyperbolic discs.

Composition of the network

To compose a framework of the functional brain network, we implemented inter-region time-series correlations of rs-fMRI, which grants a stable measure of the resting brain[21]. We applied the *absolute value* of Pearson's correlation between brain regions, which regards the

two brain regions with anticorrelated time series as connected, as same as the correlation of

the same strength. Anti-correlation between specific brain regions has a role in organizing

functional brain architectures[22-24]. Then, we thresholded the matrix to obtain a binary graph

for each network. In this study, we decided to apply the same threshold among patients in a

dataset for comparability.

Since only the one largest component can be used to be embedded in the model, we

needed to retain as many nodes as possible. If we apply the higher threshold value, we drop

out more nodes from the network, which makes it difficult to compare between individuals

and establish the difference clinically meaningful from the embedding of the whole-brain

networks. On the other hand, if we apply a too low threshold value, the binary networks

become denser with almost every edge connected, and the assumption of scale-freeness is

violated as we perform maximum likelihood estimation for embedding the functional brain

connectomes to the hyperbolic disc using the $\mathbb{S}^1/\mathbb{H}^2$ model embedding. Thus, we composed

the sparsest network while maintaining most of the brain regions in its largest component. We

assume that we could remove noise and/or artifacts in the observational data and also

emphasized the multi-dimensional tree-like internodal correlational structure of the functional

brain networks.

Scale-freeness of the network

The degree distributions of binarized brain networks showed patterns of straight downward lines in the log-log scale graph rather than concave or convex lines, which reveals that these networks have power-law degree sequences, which is a feature of a scale-free network[2].

That a network is a scale-free network means that the structure of the network has a similar structure independent of the scale of observation[25]. In detail, most nodes have a small number of connections, while some nodes have a large number of functional connections with other nodes. This indicates some of the topological features of the functional brain network, such as the hierarchical organization of nodes[26], as its structural counterpart[27]. Heterogeneity of degree distribution implies various models including hyperbolic one and we adopted hyperbolic model in this investigation.

The geometry of the brain network

Real-world networks can be embedded in a physical space corresponding to their structure and organization[28,29]. In this study, the architecture of the high-order high-dimensional internodal correlational structure of functional brain network, of which structural counterpart lies in 3-D Euclidean space, was investigated by comparing and computing the fidelity measures of embedding in manifolds of positive (spherical), negative (hyperbolic) and zero

(Euclidean) curvatures. Our result showed the better quality of embedding in 2-D hyperbolic spaces compared with the 2-D Euclidean or 1-D spherical spaces, which justifies further embedding of the network into the $\mathbb{S}^1/\mathbb{H}^2$ model, which is of 2-D hyperbolic space. Low distortion, global measure of fidelity from the original correlational structure, meant hyperbolic disc representation can be used as surrogate of the original functional brain network. Higher precision, local measure of fidelity, meant again the same.

Space of hyperbolic geometry is in fact, just the place we live in, as indicated by the special relativity with multi-layered, hierarchical and multiplex-correlated way. The most characteristic feature about the hyperbolic space against other types of space is that it best represents the data with hierarchical structure[30], as in deep neural network implemented in deep learning[31]. Prior research about embedding into non-Euclidean spaces also reports the hyperbolic space as the matching geometry to embed tree-like structures, employing the least distortion[32,33]. This reveals the tree-like nature of the network, follows from the nature of the hyperbolic space that the geodesic passes path near the origin, as the shortest path in the tree graph passes their common parent node. It should be reminded that functional brain networks form tree structure, not in a 3-dimensional space of real life, but in a higher-dimensional space derived from the correlations of nodes during 5 minutes (ABIDE) or 15 minutes (HCP) of rs-fMRI acquisition based on the stationarity assumption. The hyperbolic geometry

explains that the graphs, derived from this internodal functional brain connectomes, that represent the brain networks exhibit hierarchical and tree-like organization, which is suggested in prior research of humans or other animals[34,35].

Hyperbolic disc representation of the network

Since it has been known that many real-world networks have hyperbolic properties, many investigators have proposed algorithms for figuring out how to generate geometric objects that are most likely to generate the given network[36-39]. The present study makes use of *Mercator*[15], using Laplace eigenmaps (LE) for the reduction of dimension and maximum likelihood estimation (MLE) techniques for acquiring the most appropriate geometric object representing the original network[38]. By this means, we could visualize the functional brain network in the hyperbolic disc with the conformal structural properties with the real-world network[14,40]. Note that the two embeddings we used for testing fidelity of embedding on the spaces with various curvatures/dimensions and for final hyperbolic disc embedding represent two different procedures. In the former task for testing embedding spaces, we used the learning procedure by minimizing the loss function[32], while in the latter task of $\mathbb{S}^1/\mathbb{H}^2$ model embedding, we used *Mercator*[15] for reduction of dimension and maximizing likelihood for the geometric object to generate the original binary graph[14].

Embedding procedure of the binary binary graph onto the hyperbolic disc according to $\mathbb{S}^1/\mathbb{H}^2$ model provides the hyperbolic distance as a measure of how the two brain nodes are functionally similar, i.e., similar correlational structures derived from time-series of node pairs. As an effective distance[7], this combines factors that determine the connection probability between nodes (which are related as in Eq. (6) in the methods). As a result, this procedure effectively visualizes the network to give a quantitative comparison of the functional brain network among individuals.

The geometric meaning of the $\mathbb{S}^1/\mathbb{H}^2$ model is that the popularity and similarity of the nodes are represented by the radial and angular coordinate of the 2-D hyperbolic space, respectively[14]. The basic assumption is that the closer nodes are more likely to be connected. In other words, the short hyperbolic distance between the two nodes correlates with a high probability of connection in the generated network, and this process of embedding helps us to understand the topology of the network and growth dynamics for the system[41].

The radial representation of the embedded nodes of the network represents is hub characteristics or popularity. That is, nodes with higher degrees are located closer to the center of the disk. From this perspective, we point out that in all of our embedding results, centers of embedded disks were vacant. This implies that the functional brain network does not have any nodes with dominant high popularity implying that functional brain networks

have a decentralized information flow.

Previous similar studies performed with other kinds of real networks showed variable patterns. The network of world trade atlas in 2013[13] showed two global hubs remarkably close to the center of the disk, named "USA" and "China." These two nodes work as the global hub, which generally has a high connection probability with any other nodes from the whole network. On the other hand, the embedded map of internet connection[12] did not show heavily centered nodes, but several locally centered nodes were seen, which might function as a local hub of the system. Finally, the map of the structural brain network[7] showed a relatively uniform distribution of radial coordinate without noticeably centered node.

The mapping result of the functional brain network is most similar to the result from the structural network, which indicates that there is no definite global hub connected with the vast substructures of the network. This might result from the fact that both structural and functional brain network is based on the real neuronal network of the brain, of which the number of connection (i. e. degree of the node) is limited by physical constraints. Note that in the former two examples, the number of connections for each node is not physically limited. This does not mean that the hierarchy does not exist: the nodes have variation in their radial coordinates, which means it does exist in the functional brain network.

From the tendency that nodes from the same anatomic lobe tend to cluster in a

similar sections on the angular coordinates, we could address a certain degree of

neuroanatomical relevance, which is reported from previous literature on functional brain

networks[42]. The regions involved in sensory or motor function such as subcortical regions,

occipital lobes and cerebellum showed relatively strong concentration in narrow sections of

angular coordinates, while the association cortices such as frontal, temporal and parietal

regions were broadly distributed in angle.

Another notable feature is that nodes from the same lobes of both hemispheres,

which are also denoted as the homotopic area, tend to cluster in similar angular coordinates,

wherever they are located. This is markedly different from the map of the structural brain

network, in which the different hemispheres showed separation on angular coordinates. As

homotopic connection in the brain is reported by prior research[43-45], our results suggest a

stronger homotopic connection in functional connectivity, more than indicated by structural

connection.

Note that the set of positions of nodes has symmetry upon reflection and rotation[46]

and branch permutation invariance[47], which inevitably arise when we adopt hyperbolic

embedding of any kind, Poincare or other hyperbolic ones. These are key features to consider

when one compares a (group of) disc to another, and implementing the hyperbolic distance

between two nodes, which is a *relative* measure, resolves the reflection and rotational

symmetry issue. Since hyperbolic distance is an essential measure of this $\mathbb{S}^1/\mathbb{H}^2$ model

because it is the single argument that determines connection probability between two nodes

of the disc, we could also assure the reproducibility of the result in terms of hyperbolic

distance.

Abnormality of functional pathways in the diseased subjects

The autism spectrum disorder (ASD) is a diagnostic group of neurodevelopmental disorders

with deficits in communication and social interaction and repetitive, restrictive behaviors[48]. A

vast number of studies in neuroscience have accumulated sufficient data to make clear that

ASD is a disorder of abnormal connectivity of neural pathways[49-52], in spite of its complex

and heterogeneous nature[53].

We assessed the clinical applicability of our method by detecting abnormalities of the

network in the ASD subject compared with the control group. While the abnormality of

network on hyperbolic discs among subjects was variable, some subjects showed results

congruent with clinical context and literature reports. The striatum is pointed to as the key of

the pathophysiology of autism[54,55], and one of the subjects showed abnormal hyperbolic

distance in pathways connecting the frontoparietal cerebral cortex and striatum (**Fig. 7a**).

Asperger's syndrome, a high-functioning form of autism, is characterized by a higher

intelligence and better-than-average verbal skills, but impaired nonverbal communication and social interaction, with restrictive and repetitive behaviors as in classic autistic patients[56,57]. Though our study has presented the case of a single subject with Asperger's syndrome, the results showed an abnormal connection pattern of edges connecting the bilateral posterior superior temporal sulcus (pSTS) and subcortical regions compatible with the literature reports[58,59]. The bilateral pSTS is known to be associated with social interactions, and some prior literature reports its relevance with ASD. Our result suggests the abnormal connection of pSTS, which is consistent with impairment of social interaction in high-functioning autism patients, while the cortico-striatal pathway was relatively intact.

There are several limitations of this analysis. First, in the composition of the network, we used the absolute value of the correlation coefficient, which regards the anticorrelation between brain regions same as the same degree of correlation. Since the anticorrelation between brain regions is believed to have a distinct nature[60,61], we should consider multigraphs to take both types of correlation into account in the future study. Second, the embedding we performed in searching for the best fit manifold among spaces with various curvatures/dimensions is not the same as we have done finally to represent functional brain networks on hyperbolic discs according to $\mathbb{S}^1/\mathbb{H}^2$ model, and followingly, findings from the former investigation of comparison between various space embeddings might not guarantee

the highest quality of finally used hyperbolic disc embedding over any other choices. Third, we did not perform the multiple comparison adjustment in detecting the abnormality of the network, which reduces the statistical significance.

In conclusion, in this work, we aimed to find the most appropriate geometry for functional brain networks based on inter-regional time series correlation of rs-fMRI, and we embedded the networks onto 2-D hyperbolic discs of the $\mathbb{S}^1/\mathbb{H}^2$ model. The results demonstrated the absence of global hub, homotopic functional coherence, and a certain degree of functional-anatomical relevance and yielded a reliable parameter of hyperbolic distances on this hyperbolic disc. When this method was applied to the diseased subjects, we detected abnormal pathways by comparing internodal hyperbolic distances. This leads us to a new method of reproducible visualization of functional brain networks with high fidelity from correlational functional brain networks and anomaly detection of internodal pathways in the brain networks of diseased subjects.

Acknowledgments

This research was supported by the National Research Foundation of Korea (NRF) grant funded by the Korean Government (MSIT) (No. 2017R1A5A1015626, No. 2017M3C7A1048079 and No. 2020R1A2C2101069) and NRF grant funded by the Korean

Government (No. 2017R1D1A1B03032037). We deeply appreciate Dr. M. Ángeles Serrano

(Universitat de Barcelona) for helpful advice on the methodology, and Dr. Seonhee Lim

(Seoul National University) for her help and essential advice in constructing the theoretical

basis of the research and further comments that greatly improved the manuscript.

Author contributions

W. W., H. K., and D. S. L. designed this study. H. K. designed the methods of diseased

subejcts. W. W. and H. K. performed data collection and analysis. W. W., S. H. and D. S. L.

conducted the clinical interpretation. All authors interpreted data, drafted, and edited the

manuscript.

Competing interests

The authors declare that there are no competing interests.

ORCID for corresponding authors

Dong Soo Lee, 0000-0003-1627-6557

Methods

Subjects

Human Connectome Project (HCP) dataset

To investigate the general characteristics of the functional brain network, we used the

rs-fMRI datasets from healthy adults of the Human Connectome Project (HCP) S1200 release.

Participants were between 22 and 35 years of age at the time of recruitment and did not have

any documented history of psychiatric, neurological, or medical disorders known to influence

brain function. A more detailed description of the inclusion and exclusion criteria for HCP is

shown in the literature[62]. The sample of participants included one hundred and eighty subjects

(Mean age = 29.1, SD = 3.4), with 76 male and 104 female subjects.

Autism Brain Imaging Data Exchange II (ABIDE II) dataset

For the investigation of the characteristic of autistic spectrum disorder (ASD) diseased

subject, we made use of 247 resting-state fMRI datasets from Autism Brain Imaging Data

Exchange II (ABIDE II) datasets, 113 from diseased subjects, and 134 from the control group.

We selected data from the same age group as that of HCP datasets, whose age ranged

between 20 and 35 years of age in the control group (Mean age = 26.8, SD = 3.8), and 20 to

39 years of age in the diseased group (Mean age = 27.9, SD = 4.9). A more detailed

description of the subject information and image acquisition protocol is described in the

literature[63].

Functional connectivity analysis

We parcellated the whole brain in two scopes; a) 274 regions of interest (ROIs) using the

human Brainnetome Atlas[64]. All of the 274 sub-ROIs were included in the analysis. Detailed

information on ROIs, including full name and abbreviations, are available in

(https://atlas.brainnetome.org/). 2) cubic isotropic voxels of $6 \times 6 \times 6$ mm^3 size, the total

number of 5,937 voxels. The voxel-scope analysis was restricted to ten randomly selected

cases of the HCP dataset due to long computation time.

Spontaneous fluctuations were characterized by the variance of the population

$\sigma^2(X)$ of the BOLD signal of fMRI time-series X[59]. For the BOLD-fMRI time-series X =

$(X_1, ..., X_N)$ of a given ROI, the variance was computed by the sample variance $\hat{\sigma}^2(X)$

$$\hat{\sigma}^2(X) \;=\; \frac{1}{N-1}\sum_{i=1}^{N}(X_i - \bar{X})^2 \qquad\qquad (1)$$

in Eq. (1), $\bar{X}$ denotes the sample mean of X. Functional connectivity was assessed by the

Pearson correlation coefficient ρ:

$$\rho(X,Y) = \frac{Cov(X,Y)}{\sigma(X)\sigma(Y)} \qquad (2)$$

where (X,Y) stands for the BOLD-fMRI time-series. For a pair of BOLD-fMRI time-series

$X = (X_1, ..., X_N)$ and $Y = (Y_1, ..., Y_N)$, $\hat{\rho}$ was estimated by the sample Pearson correlation

coefficient $\hat{\rho}$:

$$\hat{\rho}(X,Y) = \frac{1}{N-1}\sum_{i=1}^{N} \frac{(X_i - \bar{X})(Y_i - \bar{Y})}{\hat{\sigma}(X)\hat{\sigma}(Y)} \qquad (3)$$

From the Pearson correlation coefficients, we obtained a square matrix of Pearson

correlation coefficient X for each of the subjects. The connectivity matrix that consists of

absolute values of both positive and negative correlation coefficients was used to establish a

binary graph from the network. We tried multiple threshold values for each group analysis

and compared the degree distribution and the number of nodes belonging to the largest

connected component. We determined fixed threshold values (0.36 for the HCP dataset and

0.40 for ABIDE II dataset) by considering both the scale-freeness and the maximal inclusion

of nodes in the chosen brain network. Consequently, we constructed an unweighted,

undirected graph for each subject by applying the threshold to the coefficient matrix.

Embedding the network into manifolds of various curvatures and dimensions

An embedding of the network is assigning nodes to representative low-dimensional space, which effectively preserves the network structure[65]. The analytical meaning of embedding is the mapping $f: U \rightarrow V$ for spaces *U, V* with distances d_U, d_V. We can measure the quality of embeddings with fidelity measures. The standard metric for graph embeddings is distortion *D* [33]. For an *n*-point embedding,

$$D = \frac{1}{\binom{n}{2}} \left(\sum_{u,v \in U: u \neq v} \frac{\left| d_V\big(f(u), f(v)\big) - d_U(u,v) \right|}{d_U(u,v)} \right) \quad (4)$$

The best distortion is *D(f)* = 0, preserving the edge lengths exactly. Also, note that *D(f)* can be larger than 1. This is a *global* metric, as it depends directly on the value of hyperbolic distances rather than the local relationships, or ranks, between distances.

Preceding work by Nickel & Kiela et al.[66] suggests mean average precision (mAP) for another measure. For a graph $G = (V, E)$, let $a \in V$ have neighborhood $\mathcal{N}_a = \{b_1, b_2, \cdots, b_{deg(a)}\}$, where $deg(a)$ denotes the degree of a. In the embedding *f*, consider the points closest to *f(a)*, and define R_{a,b_i} to be the smallest set of such points that contains b_i, i.e., R_{a,b_i} is the smallest set of nearest points required to retrieve the *i*th neighbor of *a* in f [67].

Then, the mAP is defined to be

$$mAP(f) = \frac{1}{|V|} \sum_{a \in V} \frac{1}{|\mathcal{N}_a|} \sum_{i=1}^{|\mathcal{N}_a|} \text{Precision}\left(R_{a,b_i}\right)$$

$$= \frac{1}{|V|} \sum_{a \in V} \frac{1}{deg(a)} \sum_{i=1}^{|\mathcal{N}_a|} \frac{\left|\mathcal{N}_a \cap R_{a,b_i}\right|}{\left|R_{a,b_i}\right|} \tag{5}$$

Note that mAP(f) ≤ 1. And the equal sign is the best case that preserves the rank of distances between the nodes. The mAP is not concerned with the exact value of underlying distances but only the relative ranks between the distances of immediate neighbors. This is a *local* metric.

To compute the quality of embeddings, we implemented the method proposed by Chami et al.[28] to optimize the placement of points using an auxiliary loss function[a].

Embedding onto hyperbolic discs of $\mathbb{S}^1/\mathbb{H}^2$ model

The binary graph from each patient was then embedded into latent hyperbolic geometry of $\mathbb{S}^1/\square^2$ geometric network model. In the model, the connection probability between two nodes i and j is determined by the hyperbolic distance between two nodes:

---

[a] Available at https://github.com/HazyResearch/hyperbolics

$$p_{ij} = \frac{1}{1 + e^{\frac{\beta}{2}(d_{ij} - \hat{R})}} \qquad (6)$$

, where d_{ij} is the hyperbolic distance, which has a good approximation:

$$d_{ij} \cong r_i + r_j + 2\,ln\frac{\Delta\theta_{ij}}{2} + O\left(\frac{1}{r}\right) \qquad (7)$$

, β is the clustering coefficient of network and $\hat{R}$ is the outermost radial coordinate among the embedded nodes. We described the detail of $\mathbb{S}^1/\square^2$ geometric model in the (**Supplementary Note 3**). To find out the most appropriate geometric object (i.e., a hyperbolic disc) that is most likely to generate the binary graph we made, we implemented a software named *Mercator*[b], introduced by García-Pérez et al.[15], which assumed that the structure of networks could be described by the $\mathbb{S}^1/\square^2$ geometric model. We embedded an undirected, unweighted adjacency matrix for each subject onto a hyperbolic disc. In other words, we searched a set of angular coordinates for N nodes $(r_1, \theta_1), (r_2, \theta_2), \cdots (r_N, \theta_N)$ and the clustering coefficient β on a hyperbolic disc.

Comparison with ICA-driven results

---

[b] Available at https://github.com/networkgeometry/mercator

To investigate the compatibility of the embedding with other established methods, resting-state networks determined from group independent component analysis (ICA)[68] were plotted on the individual hyperbolic discs for the voxel data. Each independent component (IC) was thresholded by a z-score larger than 6. As ROI-derived correlation matrix was embedded onto $\mathbb{S}^1/\mathbb{H}^2$ modeled hyperbolic discs, voxel-derived correlation matrix on rs-fMRI was embedded onto hyperbolic discs and colored for the lobes used in ROI-lobe coloring (Supplementary Fig. 1) and also each independent component such as default mode network (DMN), salience network (SN), visual network (VN) and others in voxel-independent component (IC) coloring (**Supplementary Fig. 2**).

Reproducibility of embedding in an individual

We computed the hyperbolic distance between ROIs over multiple performances of embedding for one representative case and computed the coefficient of variance (CV) for distance analog, which is correlated with connection probability,

$$D_{ij} = e^{\frac{(d_{ij} - \hat{R})}{2}} \qquad (8)$$

which appears denominator of the right term at Eq. (6) when we assume β equals 1 and is a

simple increasing function d_{ij}, for each pair of nodes. We averaged connection probability of edges of a certain node with every other nodes and the averages were assumed to be the average connection probability of this node and on the repeated embedding 100 times, the CV was calculated for this node. Each node has CV and this CV was plotted on the hyperbolic disc of any one embedded disc among 100 embedded discs of repetition. An example was shown in (**Fig. 6b**).

Detection of abnormality of hyperbolic distance in the diseased subjects compared with controls

To find the abnormal pathway of the functional brain network in ASD group subjects, we used the ABIDE II dataset and compared the distance matrices resulting from the $\mathbb{S}^1/\mathbb{H}^2$ model embedding, according to the following process.

After embedding the individual networks according to the $\mathbb{S}^1/\mathbb{H}^2$ hyperbolic embedding in the ROI scale, we computed the hyperbolic distance d_{ij} determined by Eq. (7) between each pair of ROIs for each individual subject in disease group and the control subjects, i.e., individual to group comparison. We set the distribution of hyperbolic distances for each edge in the control group dataset. For each ASD group subject, we considered significant edges with higher/lower hyperbolic distances seen on the $\mathbb{S}^1/\mathbb{H}^2$ models.

To compare the results with those from the traditional correlation study, we conducted a similar comparison by lower/higher correlation values between an individual and the controls group. We selected edges of which hyperbolic distance was located in upper or lower 2.5% of the distribution. In the control group, hyperbolic distance and correlation value for each edge were tested for normality ($P<0.05$). Multiple comparison correction was not performed.

References

Betzel, R. F. *et al.* Changes in structural and functional connectivity among resting-state networks across the human lifespan. *Neuroimage* **102**, 345-357 (2014).

Voitalov, I., van der Hoorn, P., van der Hofstad, R. & Krioukov, D. Scale-free networks well done. *Physical Review Research* **1**, 033034 (2019).

Meunier, D., Lambiotte, R. & Bullmore, E. T. Modular and hierarchically modular organization of brain networks. *NeuroImage* **4**, 200 (2010).

Bassett, D. S. & Bullmore, E. T. Small-world brain networks revisited. *The Neuroscientist* **23**, 499-516 (2017).

Gastner, M. T. & Ódor, G. The topology of large Open Connectome networks for the human brain. *Scientific Reports* **6**, 1-11 (2016).

Tadić, B., Andjelković, M. & Melnik, R. Functional geometry of human connectomes. *Scientific Reports* **9**, 1-12 (2019).

Allard, A. & Serrano, M. Á. Navigable maps of structural brain networks across species. *PLoS Computational Biology* **16**, e1007584 (2020).

Stam, C. *et al.* The relation between structural and functional connectivity patterns in complex brain networks. *International Journal of Psychophysiology* **103**, 149-160 (2016).

Markram, H. *et al.* Reconstruction and simulation of neocortical microcircuitry. *Cell* **163**, 456-492 (2015).

Sporns, O. Structure and function of complex brain networks. *Dialogues in Clinical Neuroscience* **15**, 247 (2013).

Clauset, A., Moore, C. & Newman, M. E. Hierarchical structure and the prediction of missing links in networks. *Nature* **453**, 98-101 (2008).

Boguná, M., Papadopoulos, F. & Krioukov, D. Sustaining the internet with hyperbolic mapping. *Nature Communications* **1**, 1-8 (2010).

García-Pérez, G., Boguñá, M., Allard, A. & Serrano, M. Á. The hidden hyperbolic geometry of international trade: World Trade Atlas 1870–2013. *Scientific Reports* **6**, 1-10 (2016).

Papadopoulos, F., Kitsak, M., Serrano, M. Á., Boguná, M. & Krioukov, D. Popularity versus similarity in growing networks. *Nature* **489**, 537-540 (2012).

García-Pérez, G., Allard, A., Serrano, M. Á. & Boguñá, M. Mercator: uncovering faithful hyperbolic embeddings of complex networks. *New Journal of Physics* **21**, 123033 (2019).

Serrano, M. A., Krioukov, D. & Boguná, M. Self-similarity of complex networks and hidden metric spaces. *Physical review letters* **100**, 078701 (2008).

Sporns, O. The human connectome: a complex network. *Annals of the New York Academy of Sciences* **1224**, 109-125 (2011).

Van Den Heuvel, M. P. & Pol, H. E. H. Exploring the brain network: a review on resting-state fMRI functional connectivity. *European Neuropsychopharmacology* **20**, 519-534 (2010).

Allard, A., Serrano, M. Á., García-Pérez, G. & Boguñá, M. The geometric nature of weights in real complex networks. *Nature communications* **8**, 1-8 (2017).

Thapar, A., Cooper, M. & Rutter, M. Neurodevelopmental disorders. *The Lancet Psychiatry* **4**, 339-346 (2017).

Greicius, M. D., Krasnow, B., Reiss, A. L. & Menon, V. Functional connectivity in the

resting brain: a network analysis of the default mode hypothesis. *Proceedings of the National Academy of Sciences* **100**, 253-258 (2003).

Kucyi, A. *et al.* Intracranial electrophysiology reveals reproducible intrinsic functional connectivity within human brain networks. *Journal of Neuroscience* **38**, 4230-4242 (2018).

Keller, J. B. *et al.* Resting-state anticorrelations between medial and lateral prefrontal cortex: association with working memory, aging, and individual differences. *Cortex* **64**, 271-280 (2015).

De Havas, J. A., Parimal, S., Soon, C. S. & Chee, M. W. Sleep deprivation reduces default mode network connectivity and anti-correlation during rest and task performance. *Neuroimage* **59**, 1745-1751 (2012).

Barabási, A.-L. & Bonabeau, E. Scale-free networks. *Scientific American* **288**, 60-69 (2003).

Sporns, O., Chialvo, D. R., Kaiser, M. & Hilgetag, C. C. Organization, development and function of complex brain networks. *Trends in Cognitive Sciences* **8**, 418-425 (2004).

Faskowitz, J., Yan, X., Zuo, X.-N. & Sporns, O. Weighted stochastic block models of the human connectome across the life span. *Scientific Reports* **8**, 1-16 (2018).

Chami, I., Wolf, A., Sala, F. & Ré, C. Low-dimensional knowledge graph embeddings via hyperbolic rotations. in *Graph Representation Learning NeurIPS 2019 Workshop.*

Smith, A. L., Asta, D. M. & Calder, C. A. The geometry of continuous latent space models for network data. *Statistical Science: a Review Journal of the Institute of Mathematical Statistics* **34**, 428 (2019).

Lazcano, D., Fredes, N. & Creixell, W. Hyperbolic Generative Adversarial Network. *arXiv preprint arXiv:.05567* (2021).

Peng, W., Varanka, T., Mostafa, A., Shi, H. & Zhao, G. Hyperbolic Deep Neural Networks: A Survey. *arXiv preprint arXiv:.04562* (2021).

Gu, A., Sala, F., Gunel, B. & Ré, C. Learning mixed-curvature representations in product spaces. in *International Conference on Learning Representations*.

Sala, F., De Sa, C., Gu, A. & Ré, C. Representation tradeoffs for hyperbolic embeddings. in *International Conference on Machine Learning.*   4460-4469 (PMLR).

Telesford, Q. K., Simpson, S. L., Burdette, J. H., Hayasaka, S. & Laurienti, P. J. The brain as a complex system: using network science as a tool for understanding the brain. *Brain Connectivity* **1**, 295-308 (2011).

Bardella, G., Bifone, A., Gabrielli, A., Gozzi, A. & Squartini, T. Hierarchical organization of functional connectivity in the mouse brain: a complex network approach. *Scientific Reports* **6**, 1-11 (2016).

Keller-Ressel, M. & Nargang, S. Hydra: a method for strain-minimizing hyperbolic embedding of network-and distance-based data. *Journal of Complex Networks* **8**, cnaa002 (2020).

Muscoloni, A. & Cannistraci, C. V. A nonuniform popularity-similarity optimization (nPSO) model to efficiently generate realistic complex networks with communities. *New Journal of Physics* **20**, 052002 (2018).

Papadopoulos, F., Psomas, C. & Krioukov, D. Network mapping by replaying hyperbolic growth. *IEEE/ACM Transactions on Networking* **23**, 198-211 (2014).

Suzuki, R., Takahama, R. & Onoda, S. Hyperbolic disk embeddings for directed acyclic graphs. in *International Conference on Machine Learning.*   6066-6075 (PMLR).

Papadopoulos, F., Aldecoa, R. & Krioukov, D. Network geometry inference using

common neighbors. *Physical Review E* **92**, 022807 (2015).

Alanis-Lobato, G., Mier, P. & Andrade-Navarro, M. A. Manifold learning and maximum likelihood estimation for hyperbolic network embedding. *Applied network science* **1**, 1-14 (2016).

Power, J. D. *et al.* Functional network organization of the human brain. *Neuron* **72**, 665-678 (2011).

Mancuso, L. *et al.* The homotopic connectivity of the functional brain: a meta-analytic approach. *Scientific Reports* **9**, 3346, doi:10.1038/s41598-019-40188-3 (2019).

Wei, P., Zhang, Z., Lv, Z. & Jing, B. Strong Functional Connectivity among Homotopic Brain Areas Is Vital for Motor Control in Unilateral Limb Movement. *Frontiers in Human Neuroscience* **11**, doi:10.3389/fnhum.2017.00366 (2017).

Lee, D. S. *et al.* Metabolic connectivity by interregional correlation analysis using statistical parametric mapping (SPM) and FDG brain PET; methodological development and patterns of metabolic connectivity in adults. *European Journal of Nuclear Medicine and Molecular Imaging* **35**, 1681-1691 (2008).

Ganea, O., Bécigneul, G. & Hofmann, T. Hyperbolic entailment cones for learning hierarchical embeddings. in *International Conference on Machine Learning.* 1646-1655 (PMLR).

Alvarez-Melis, D., Mroueh, Y. & Jaakkola, T. Unsupervised hierarchy matching with optimal transport over hyperbolic spaces. in *International Conference on Artificial Intelligence and Statistics.* 1606-1617 (PMLR).

Baio, J. *et al.* Prevalence of autism spectrum disorder among children aged 8 years—autism and developmental disabilities monitoring network, 11 sites, United States, 2014. *MMWR Surveillance Summaries* **67**, 1 (2018).

Belmonte, M. K. *et al.* Autism and abnormal development of brain connectivity. *Journal of Neuroscience* **24**, 9228-9231 (2004).

Bullmore, E. & Sporns, O. The economy of brain network organization. *Nature Reviews Neuroscience* **13**, 336-349 (2012).

Just, M. A., Cherkassky, V. L., Keller, T. A. & Minshew, N. J. Cortical activation and synchronization during sentence comprehension in high-functioning autism: evidence of underconnectivity. *Brain* **127**, 1811-1821 (2004).

Maximo, J. O., Cadena, E. J. & Kana, R. K. The implications of brain connectivity in the neuropsychology of autism. *Neuropsychology Review* **24**, 16-31 (2014).

Kleinhans, N. M. *et al.* Abnormal functional connectivity in autism spectrum disorders during face processing. *Brain* **131**, 1000-1012 (2008).

Green, S. A., Hernandez, L., Bookheimer, S. Y. & Dapretto, M. Salience network connectivity in autism is related to brain and behavioral markers of sensory overresponsivity. *Journal of the American Academy of Child Adolescent Psychiatry* **55**, 618-626. e611 (2016).

Uddin, L. Q. *et al.* Salience network–based classification and prediction of symptom severity in children with autism. *JAMA psychiatry* **70**, 869-879 (2013).

Wing, L. Asperger's syndrome: a clinical account. *Psychological Medicine* **11**, 115-129 (1981).

Frith, U. & Mira, M. Autism and Asperger syndrome. *Focus on Autistic Behavior* **7**, 13-15 (1992).

Isik, L., Koldewyn, K., Beeler, D. & Kanwisher, N. Perceiving social interactions in the posterior superior temporal sulcus. *Proceedings of the National Academy of Sciences* **114**, E9145-E9152 (2017).

Materna, S., Dicke, P. W. & Thier, P. Dissociable roles of the superior temporal sulcus and the intraparietal sulcus in joint attention: a functional magnetic resonance imaging study. *Journal of Cognitive Neuroscience* **20**, 108-119 (2008).

Fox, M. D., Zhang, D., Snyder, A. Z. & Raichle, M. E. The global signal and observed anticorrelated resting state brain networks. *Journal of Neurophysiology* **101**, 3270-3283 (2009).

Liang, Z., King, J. & Zhang, N. Anticorrelated resting-state functional connectivity in awake rat brain. *Neuroimage* **59**, 1190-1199 (2012).

Van Essen, D. C. *et al.* The Human Connectome Project: a data acquisition perspective. *Neuroimage* **62**, 2222-2231 (2012).

Di Martino, A. *et al.* Enhancing studies of the connectome in autism using the autism brain imaging data exchange II. *Scientific Data* **4**, 1-15 (2017).

Fan, L. *et al.* The human brainnetome atlas: a new brain atlas based on connectional architecture. *Cerebral Cortex* **26**, 3508-3526 (2016).

Cui, P., Wang, X., Pei, J. & Zhu, W. A survey on network embedding. *IEEE Transactions on Knowledge Data Engineering* **31**, 833-852 (2018).

Nickel, M. & Kiela, D. Poincaré embeddings for learning hierarchical representations. *arXiv preprint arXiv:.08039* (2017).

García-Pérez, G., Aliakbarisani, R., Ghasemi, A. & Serrano, M. Á. Precision as a measure of predictability of missing links in real networks. *Physical Review E* **101**, 052318 (2020).

van de Ven, V. G., Formisano, E., Prvulovic, D., Roeder, C. H. & Linden, D. E. Functional connectivity as revealed by spatial independent component analysis of fMRI measurements during rest. *Human Brain Mapping* **22**, 165-178 (2004).

Figures

Fig. 1 Distributions of time-series correlation of resting-state fMRI signal. a Histogram of Pearson's correlation from all edges of 180

human connectome project (HCP) subjects. The Horizontal axis is the value of Pearson's correlation, while the vertical axis denotes the

frequency of the value. The correlation is computed by ——— ————. A positive correlation between nodes was dominant

in healthy adults, while a small portion of edges showed a negative correlation. Overall, 6.70% of edges had a higher absolute value than the

threshold and considered as connected. **b** A matrix view of one representative subject. Symbols on each axis denote the anatomic lobe of the

nodes. F = Frontal, T = Temporal, P = Parietal, I = insula, L = Limbic, O = Occipital, S = Subcortical, C = Cerebellar, V = Vermis.

Control case A

Control case B

Control case C

99.5% of nodes included

98.3% of nodes included

95.2% of nodes included

Fig. 2 Determining the threshold of correlation for network composition. Probability distribution function (PDF) and complementary cumulative distribution function (CCDF) of degree distribution from three representative subjects from ABIDE II dataset. The threshold is set as **a** 0.35, **b** 0.40, **c** 0.45. **a** In a threshold value of 0.35, in which most of the nodes are preserved, the degree distribution forms a peaked curve, which violates the scale-freeness of the network. **c** While, in a higher threshold value of 0.45, 4.8% of nodes, an average of 13 nodes per network is excluded from the largest component, which is considered inappropriate for a whole-brain analysis. **b** Therefore, the threshold value was determined as 0.40.

Fig. 3 Fidelity measures in embedding onto spaces of various curvatures/dimensions. a, b Fidelity measures (average distortion, mean

average precision) of embedding for ten representative subjects from HCP and Autism Brain Imaging Data Exchange (ABIDE) II datasets. **c,**

d For both of the datasets, embedding to the 2-dimensional hyperbolic space of $\mathbb{H}^2$ showed lower distortion than embedding to $\mathbb{E}^2$ and $\mathbb{S}^1$.

Subject 1   Subject 2

Subject 3   Subject 4

R Frontal
R Temporal
R Parietal
R Insular
R Limbic
R Occipital
R Subcortical
Cerebellum
L Subcortical
L Occipital
L Limbic
L Insular
L Parietal
L Temporal
L Frontal

Fig. 4 Embedding results by $\mathbb{S}^1/\mathbb{H}^2$ **model.** The figure demonstrates the result from four representative cases from the HCP dataset. Color

denotes the anatomic lobe in which each ROI is located, while the lobes within the right, left cerebral hemisphere, and cerebellum are marked

with circle, square and triangular markers, respectively. The embedding result revealed vacant space in the center of the disk. ROIs from the

bilateral insula, subcortical, and cerebellum had narrow distributions of angular dimensions. ROIs from larger anatomic lobes (frontal,

temporal, parietal) were located with relatively broader distributions. And ROIs from the same lobes of both hemispheres (for example, right

and left frontal lobes) had similar distributions of angles.

Fig. 5 Connection probability versus absolute correlation coefficient. The lower triangle demonstrates the connection probability

calculated by $p_{ij} = \dfrac{1}{1+e^{\frac{\beta}{2}\left(d_{ij}-\widehat{R}\right)}}$ where d_{ij} is the hyperbolic distance between nodes, β is the clustering coefficient and $\widehat{R}$ is the outermost

radius of the node. The upper triangle denotes the absolute correlation value. The symbols in each axis denote the same anatomic lobe of the

nodes as in **Fig. 1**. The two measures tended to show similar patterns for each of the subjects. We discussed the comparison between the two

measures in (**Supplementary Note 1**).

Fig. 6 Reproducibility of results (Repetition of the embedding). We repeatedly performed the embedding procedure 100 times, in one

representative case. **a** Coefficient of variance (CV) of hyperbolic distances for each edge. The horizontal and vertical axis indicates the indices

of vertices embedded in the $\mathbb{S}^1/\mathbb{H}^2$ model, which is ordered by lobes. The symbols in each axis denote the same anatomic lobe of the nodes

as in **Fig. 1**. **b** Average CV value of connected edges for each node. Blue nodes (low CV) represent nodes with a lower variance of position

over embedding. Red nodes (high CV) represent a higher variance. The positions of vertices are positioned based on one sample result of

embedding. Most of the nodes have relatively low arbitrariness of position in repeated embedding procedure. In contrast, outermost positioned

nodes, which means nodes with low popularity, tended to have a position with higher variability.

Fig. 7 Detection of abnormal pathways in autism subjects. The 274 ROIs were reduced to 51 brain subregions for the sake of clarity of

visualization. The lines in the circular diagrams represent the abnormal connection probability or correlation compared to the control group

composed of 134 healthy adults. (*Uncorrected P* < 0.05) **a** One subject with autism showed longer hyperbolic distances of edges connecting

frontoparietal cortices and bilateral basal ganglia, which represents the cortico-striatal pathway, compared to the normal group. The pattern

was not clear in the means of the correlation coefficients. **b** Another subject with Asperger's syndrome showed shorter hyperbolic distances of

edges which connect bilateral posterior superior temporal sulcus (pSTS) and basal ganglia. The correlation study showed a similar pattern.

The list of abbreviations in the circular diagrams is noted in (**Supplementary Note 4**).

Tables

Embedded space	Fidelity measures (Mean ± SD)	
	D_{avg}	mAP
10-dimension spaces		
$\mathbb{E}^{10}$	0.2434 ± 0.0286	0.7743 ± 0.1016
$\mathbb{H}^{10}$	0.2181 ± 0.0351	0.8036 ± 0.1006
$\mathbb{S}^{10}$	0.2278 ± 0.0317	0.7675 ± 0.0874
2- and 1-dimension spaces		
$\mathbb{E}^{2}$	0.2669 ± 0.0752[a]	0.4854 ± 0.0740[b]
$\mathbb{H}^{2}$	0.1993 ± 0.0234[a]	0.6404 ± 0.0175[b]
$\mathbb{S}^{2}$	0.2798 ± 0.0607[a]	0.4834 ± 0.0803[b]
$\mathbb{S}^{1}$	0.3443 ± 0.0581[a]	0.3575 ± 0.0482[b]

Table 1 Fidelity measures of embedding into various manifolds for HCP dataset. Ten representative cases were used for embedding. For HCP dataset, embedding to the 2-dimensional hyperbolic space of $\mathbb{H}^{2}$ showed higher mean average precision and lower distortion compared to embedding to manifolds $\mathbb{E}^{2}$ or $\mathbb{S}^{1}$. D_{avg} = average distortion. mAP = mean average precision.

[a] Significantly lower D_{avg} in $\mathbb{H}^{2}$, compared with other results ($P < 0.05$).
[b] Significantly higher mAP in $\mathbb{H}^{2}$, compared with other results ($P < 0.05$).

Embedded space	Fidelity measures (Mean ± SD)

	D_{avg}	mAP
10-dimension spaces		
$\mathbb{E}^{10}$	0.2253 ± 0.0166^c	0.8674 ± 0.0372
$\mathbb{H}^{10}$	0.1295 ± 0.0468^c	0.9030 ± 0.0318^d
$\mathbb{S}^{10}$	0.1672 ± 0.0230	0.8316 ± 0.0237^d
2- and 1-dimension spaces		
$\mathbb{E}^2$	0.1487 ± 0.0511^e	0.7191 ± 0.1202^f
$\mathbb{H}^2$	0.0744 ± 0.0256^e	0.7081 ± 0.0674^f
$\mathbb{S}^2$	0.1726 ± 0.0316^e	0.6925 ± 0.1020
$\mathbb{S}^1$	0.2036 ± 0.0474^e	0.5793 ± 0.1477^f

Table 2. Fidelity measures of embedding into various manifolds for ABIDE II dataset.

For ABIDE II dataset, embedding to 10-dimensional hyperbolic space of $\mathbb{H}^{10}$ showed lower distortion than embedding to $\mathbb{E}^{10}$. For both of datasets, embedding to the 2-dimensional hyperbolic space of $\mathbb{H}^2$ showed lower distortion than embedding to $\mathbb{E}^2$ and $\mathbb{S}^1$.

[c] Significantly lower D_{avg} in $\mathbb{H}^{10}$, compared with the result in $\mathbb{E}^{10}$ ($P < 0.05$).

[d] Significantly higher mAP in $\mathbb{H}^{10}$, compared with the result in $\mathbb{S}^{10}$ ($P < 0.05$).

[e] Significantly lower D_{avg} in $\mathbb{H}^2$, compared with other results ($P < 0.05$).

[f] Significantly higher mAP in $\mathbb{H}^2$, compared with the result in $\mathbb{S}^1$ ($P < 0.05$).