1

# Integrating reward information for prospective behaviour

Abbreviated Title: Integrating reward for prospective behaviour

Sam Hall-McMaster[1,2,*], Mark G. Stokes[1,2], Nicholas E. Myers[1,2]

[1]Department of Experimental Psychology, University of Oxford, UK

[2]Wellcome Centre for Integrative Neuroimaging, University of Oxford, UK

Corresponding author: hall-mcmaster@mpib-berlin.mpg.de

Number of pages: 39

Number of figures: 4

Word count: 246 (abstract), 605 (introduction), 1327 (discussion)

Conflict of interest: The authors declare no competing financial interests.

Acknowledgements: This research was support by the Rutherford Foundation and William Georgetti Trusts of New Zealand (S.H.), the Wellcome Trust (award 201409Z/16/Z to N.E.M), University College Oxford (N.E.M.), the Biotechnology and Biological Sciences Research Council (award BB/M010732/1 to M.G.S.), the James S. McDonnell Foundation (award 220020405 to M.G.S.), and the NIHR Oxford Health Biomedical Research Centre. The Wellcome Centre for Integrative Neuroimaging is supported by core funding from the Wellcome Trust (203139/Z/16/Z). The authors would like to thank Keno Jüchems and Joshua Calder-Travis for comments on previous versions of the manuscript, Fabrice Luyckx for comments on the figures, as well as Nils Kolling and Laurence Hunt for helpful discussions.

**Abstract**

Value-based decision-making is often studied in a static context, where participants decide

which option to select from those currently available. However, everyday life often involves

an additional dimension: deciding *when* to select to maximise reward. Recent evidence

suggests that agents track the latent reward of an option, updating changes in their latent

reward estimate, to achieve appropriate selection timing (*latent reward tracking*). However,

this strategy can be difficult to distinguish from one in which the optimal selection time is

estimated in advance, allowing an agent to wait a pre-determined amount of time before

selecting, without needing to monitor an option's latent reward (*distance-to-goal tracking*).

Here we show that these strategies can in principle be dissociated. Brain activity was

recorded using electroencephalography (EEG) while human participants performed a novel

decision task. Participants were shown an option and decided when to select it, as its latent

reward changed from trial-to-trial. While the latent reward was uncued, it could be estimated

using cued information about the option's starting value and value growth rate. We then used

representational similarity analysis to assess whether EEG signals more closely resembled

latent reward tracking or distance-to-goal tracking. This approach successfully dissociated the

strategies in this task. Starting value and growth rate were translated into a distance-to-goal

signal, far in advance of selecting the option. Latent reward could not be independently

decoded. These results demonstrate the feasibility of using high temporal resolution neural

recordings to identify internally computed decision variables in the human brain.

**Significance Statement**

Reward-seeking behaviour involves acting at the right time. However, the external world

does not always tell us when an action is most rewarding, necessitating internal

representations that guide action timing. Specifying this internal neural representation is

challenging because it might stem from a variety of strategies, many of which make similar

predictions about brain activity. This study used a novel approach to test whether alternative

strategies could be dissociated in principle. Using representational similarity analysis, we

were able to distinguish between candidate internal representations for selection timing. This

shows how pattern analysis methods can be used to measure latent decision information in

non-invasive neural data.

## Introduction

Neural research on decision-making has provided detailed accounts of how rewards are compared between options (A vs. B), to determine which option should be selected (e.g. Fouragnan et al., 2019; Hunt & Hayden, 2017; Murray & Rudebeck, 2018; Padoa-Schioppa, 2011; Rich & Wallis, 2016). However, everyday life also requires us to decide when to act on our selection (Khalighinejad et al., 2020a, 2020b). For example, we might have purchased an avocado to use during the week, but want to time when we use it, to ensure it is not under or overripe. Such a decision can be challenging to optimise because the rewards associated with an option are rarely stationary and, as a result, the timing of selection is critical to achieve the desired outcome.

Prior research has shown that the basal forebrain integrates recent experience with ongoing sensory information about an option's reward prospect, to guide decisions about selection timing (Khalighinejad et al., 2020a, 2020b). But how such timing is calibrated without ongoing sensory reward cues remains largely unknown. Recent results indicate that the dorsal anterior cingulate cortex can encode latent information about an option's progress to a reward threshold, in the absence of sensory input (Stoll et al., 2016). This suggests that option selection could be timed using an internal representation that continuously updates an estimate of the option's latent reward (*latent reward tracking*). While this proposal holds theoretical appeal, optimal selection timing could also be achieved using prospection (e.g. Bulley et al., 2016) and delay estimation (e.g. Coull et al., 2011; Hassall et al., 2020), to anticipate when an option will be most rewarding in future and initiate selection when that time point is reached (*distance-to-goal tracking*).

Here we sought to develop an approach that could distinguish between these strategies. This is challenging because latent reward and distance-to-goal are often correlated; as reward increases towards a selection threshold, the distance to the selection event decreases. Therefore, even neural activity that appears to track one variable might be equally well explained by the other. Identifying which of these variables better fits neural activity is a critical step towards a mechanistic explanation of how the brain computes decision timing (O'Reilly & Mars, 2011). The present experiment recorded electroencephalograms (EEG) while human participants made selection timing decisions. Participants were shown an option that had a distinct starting value and growth rate. With each successive trial, the reward for deciding to select updated based on the growth rate, without corresponding sensory changes to indicate the current value. Pattern classification was then used to confirm that both an option's latent reward and distance-to-goal could be decoded from the EEG signal, consistent

with the fact that the two variables were correlated and, therefore, that the neural
representation of either variable could explain the decoding in both cases. Representational
similarity analysis (RSA) was then used to examine whether EEG signals corresponded more
closely to latent reward tracking or distance-to-goal tracking, while controlling for each
variable. We predicted that neural signals would be more consistent with latent reward
tracking, based on prior indications that reward monitoring is used to initiate select decisions
(Khalighinejad et al., 2020a, 2020b; Stoll et al., 2016),

The results from this experiment indicate that the two decision strategies could be
dissociated. Neural responses were better explained by distance-to-goal tracking. Independent
evidence for latent reward tracking was not detected. These results suggest that, in some
contexts, decisions about when to select an option might be made by transforming option
information into an estimate of optimal selection timing. At a broader level, we highlight the
utility of time-resolved EEG decoding to disambiguate latent decision variables in human
participants.
149
150
151
152

153
154

 **Materials and Methods**

 **Participants**

We set a target sample size of 32 participants based on previous M/EEG studies in our

group (e.g. Hall-McMaster et al., 2019; Tankelevitch et al., 2020; Wolff et al., 2020). Five

participants were excluded from the initial sample. One participant was excluded based on

low behavioural performance, which fell more than three standard deviations below the mean

percentage of points gained on the task (89.29%). Four participants were excluded based on

excessive EEG artefacts, which lead to the rejection of more than 400 trials during pre-

processing ($> 21.27$-$27.47\%$ of trials depending on the participant). To meet the 32

participant target, we therefore collected data from five additional participants. The final

sample were between 18 and 35 (mean age=25, 19 female). All participants reported normal

or corrected-to-normal vision (including normal colour vision) and no history of neurological

or psychiatric illness. Participants received £10 per hour or course credit for taking part and

could earn up to £20 extra for task performance. The study was approved by the Central

University Research Ethics Committee at the University of Oxford (R58489/RE001) and all

participants signed informed consent before taking part.

**Materials**

Stimuli were presented on a 24-inch screen with a spatial resolution of 1920 x 1080

and refresh rate of 100Hz. Stimulus presentation was controlled using Psychophysics

Toolbox-3 (RRID: SCR_002881) in MATLAB (RRID: SCR_001622, version R2015b). F

and J keys on a standard QWERTY keyboard were used to record left and right hand

responses. EEG data were recorded with 61 Ag/AgCl sintered electrodes (EasyCap,

Herrsching, Germany), a NeuroScan SynAmps RT amplifier, and Curry 7 acquisition

software (RRID: SCR_009546). Electrode impedance was reduced to <10 kΩ before

recording. EEG data were pre-processed in EEGLAB (RRID: SCR_007292, version 14.1.1b)

(Delorme & Makeig, 2004). Data were analysed in MATLAB (RRID: SCR_001622, version

R2020a). Bonferroni-Holm corrections were implemented using David Groppe's MATLAB

toolbox (shorturl.at/mpqvV). Bayesian paired t-tested were implemented using Bart

Krekelberg's MATLAB toolbox (https://klabhub.github.io/bayesFactor/). Bonus items used

to incentivise performance were created by icon developers Smashicons, Freepik, Flat Icons,

Goodware, Pixel Buddha, Kiranshastry, Dimitry Miroliubov, Surang and accessed at

www.freepik.com.

**Code Accessibility**

Task and analysis code, as well as raw data and pre-processed data will be released on

publication.

**Experimental Design**

Participants performed a sequential decision-making task that required deciding when

to select an option on screen, as its reward changed from trial to trial (Figure 1). There were

two critical aspects to the task. First, each option had a starting value and a growth rate (the

increase in reward per trial). These properties were varied independently, resulting in unique

options that reached a 500-point reward maximum after a different number of trials. After

reaching the 500-point maximum, the option reward began to decline, encouraging

participants to select the option on the single trial when it was at maximum reward. Second,

the visual appearance of the option remained the same from trial to trial, despite changes in

its reward value.

A single option was presented in each trial run. The option was a circle stimulus with

an approximate visual angle of 3.79° (150x150 pixels), calculated based on an approximate

viewing distance of 60cm. The option contained a coloured wedge, the size of which

indicated its starting value and the colour of which indicated its growth rate. On each trial in

the run, participants decided between waiting and selecting the option. The run continued

until participants decided to select, up to a maximum of 16 trials. Each trial had three phases:

a decision phase, where participants were instructed to decide whether to wait (allowing the

option's latent reward to update) or select the option (to gain the latent reward); a response

phase, where participants made a manual response to indicate their choice; and a feedback

phase. In the decision phase, the option was presented for 800ms on the left or right of the

screen, with the centre of the option being presented at an approximate visual angle 3.16°

(125 pixels) above and 3.16° to the left or right of the screen's centre. The decision phase was

followed by a 250ms blank delay. The response phase began with the presentation of a

central fixation cross, with the option appearing randomly on the left or right of the screen.

Participants were instructed to press the button on the side where the option was presented to

select it (e.g. left button if the option was presented on the left) and to press the button on the

opposite side to wait (e.g. left button if the option was presented on the right). Since the

option appeared randomly on the left or right of the screen, independent of where it had been

presented in the decision phase, participants were prevented from preparing a motor response

prior to the response phase, allowing us to decouple decision and response information in the

neural analyses. In the feedback phase, participants received 1 point for a wait response and

the option's latent reward for a select response (0-500 points). Feedback presentation lasted

500ms. Each trial was followed by an inter-trial interval (ITI). Durations for each ITI in a run

were taken from a shuffled ITI vector. The vector contained 8 durations from 500-1200ms,

which were spaced 100ms apart. The vector contained two repetitions of each duration.

The reward associated with each option could grow to a maximum of 500 points. The

reward was computed with the following linear function: $r = s + g\,(t-1)$, where $r$ is the

reward, $s$ is the starting value, $g$ is the growth rate and $t$ is the trial number within the run.

Eight different starting values were used in the study (0, 50, 100, 150, 200, 250, 300, 350).

On trial runs where the starting value was 0, a coloured wedge corresponding to 7.5 points

was used so that participants could see the coloured wedge and determine the growth rate.

Five different growth rates were used in the study (35, 40, 50, 60, 80). These were selected to

maximize behavioural variability, producing an even spacing in optimal trial on which to

selection the option (16, 14, 12, 10, 8 trial steps), when the option started from a value of 0

points. Two colours were used per growth rate so that abstract growth rate information,

independent of option colour, could be decoded from neural recordings. The mapping

between colours and growth rates was also balanced across participants; participants were

pseudo-randomly assigned to one of four colour-growth rate mappings, with approximately

equal numbers of participants for each mapping. On trials where the updated option value

exceeded 500 points, the option value was rounded down to the 500 maximum. The

maximum amount that the 500 points would have been exceeded by a condition without

rounding down was 70 points. If participants did not select the option on the trial where it

reached its maximum, the reward associated with the option would begin an exponential

decay given by the equation: $r = \mathrm{m}(e^{-\lambda t})$ , where $r$ is the reward, $m$ is the maximum value

of 500 points, $e$ is Euler's number, $\lambda$ is a decay constant set at 0.5 and $t$ is the number of trials

elapsed since the option reached the 500-point maximum. This equation meant that each

option had just one trial at maximum reward in a run. It was designed to be both distinct from

the linear growth function above and the uniform across all conditions, so that participants

could not gain information about an option through over-waiting and there would be a strong

incentive for participants to end the run once the maximum was reached. To motivate

participants to earn as many points as possible, every five percent of the maximum task

points earned resulted in a bonus item being unlocked (such as a rocket ship, balloons or an

electric guitar), each of which corresponded to additional £1 bonus payment.

Participants completed a training sequence of 40 trial runs prior to the main

experiment. If a participant scored below 70% or wished to do more practice, they completed

an additional 40-80 trial runs. Eight participants completed 40 practice runs, twenty-one

participants completed 80 practice runs and one participant completed 120 practice runs. The

main purpose of the practice was to learn the correspondence between the 10 colours and the

five growth rates. To facilitate this, participants were presented with an on-screen colour

legend during task practice, which indicated the colours for each growth rate. The colour

legend was not presented during the main task. Before beginning the main experiment,

participants performed a colour ranking task, in which they had to rank the colours on the

basis of their growth rates (from 1=lowest growth rate to 5=highest growth rate). If any

ranking was incorrect, the task practice was repeated; participants needed to score 100% on

the ranking task before starting the main experiment. During EEG recording, participants

performed 240 trial runs, with equal numbers of runs for each starting value/growth-rate

combination. Equal number of runs were also performed using the two colours for each

growth rate. As participants decided when to select the option during each trial run, different

numbers of individual trials were recorded per participant. On average, we recorded 1660

trials for each participant (min=1412, max=1898).

**EEG Pre-processing**

EEG data were down-sampled from 1000 to 250Hz and filtered using 40Hz low-pass

and 0.01Hz high-pass filters. For each participant, channels with excessive noise were

identified by visual inspection and replaced via interpolation, using a weighted average of the

surrounding electrodes. Data were then re-referenced by subtracting the mean activation

across all electrodes from each individual electrode at each time point. Data were divided into

epochs from -1 to +5 seconds from the first option onset of each trial. Epochs containing

artefacts (such as muscle activity) were rejected based on visual inspection. Data were then

subjected to an Independent Component Analysis. Structured noise components, such as eye

blinks, were removed, resulting in the data set used for subsequent analyses.

**Behavioural Analyses**

To test whether selection timing was sensitive to task variables, we used linear

regression. We first tested whether starting value and growth rate could be used to trial on

which the option was selected within the run. This used the following equation to estimate

one beta per predictor for each participant: $t = \beta_0 + \beta_1 s + \beta_2 \frac{1}{g} + \varepsilon$, in which $t$ is the trial

where the option is selected, $\beta_0$ is a constant, $s$ is the starting value, $g$ is the growth rate and $\varepsilon$

is the residual error. The $\frac{1}{g}$ in this expression arises from the fact that the reward, $r = s +$

$g(t - 1)$. This in turn means that the trial on which an option reaches maximum reward,

$r_{max}$, can be calculated as: $t = \frac{r_{max} - s}{g} + 1$. While appropriate due to the reward dynamics in

this task, $\frac{1}{g}$ has the effect of inverting growth rate values in the regression. This means that

higher growth rates are represented with lower numbers. We therefore multiplied the

subsequent $\beta_2$ estimates by -1, to correctly interpret the direction of the effect. Once one beta

had been estimated per predictor for each participant, the 32 participant betas for starting

value and the 32 participant betas for growth rate were tested against zero in separate two-

tailed t-tests. In further exploratory analyses, we found that participants tended to select

options earlier than would be optimal for the slowest trial runs (i.e. those that took the most

trials to reach maximum reward). We use the term action bias to refer to this tendency to

select earlier than would be optimal for reward maximisation. The action bias was computed

by subtracting the optimal trial to select the option within the run from the empirical trial on

which the option was selected. The vector was then multiplied by -1 to convert the action bias

to a positive scale. The following regression equation was used for the action bias analysis:

$b = \beta_0 + \beta_1 t + \varepsilon$, where $b$ is the action bias, $\beta_0$ is a constant, $t$ is the optimal to trial on

which to select the option to gain maximum points and $\varepsilon$ is the residual error. The resulting

32 participant $\beta_1$ estimates were tested against zero using a two-tailed t-test. Using a similar

approach, we explored whether the amount of reward lost on each trial run could be predicted

from the optimal number of trials to wait for each condition. The reward loss was computed

by subtracting the amount of reward earned on each run from the total reward possible on that

run. The total reward possible was the 500-point maximum plus one point for each wait

decision needed to reach the optimal selection time. The reward loss vector was then

multiplied by -1 to convert it to a positive scale. The following regression equation was used

for the reward loss analysis: $l = \beta_0 + \beta_1 t + \varepsilon$, where $l$ is the reward loss, $\beta_0$ is a constant, $t$ is

the optimal to trial on which to select the option to gain maximum points and $\varepsilon$ is the residual

error. The resulting 32 participant $\beta_1$ estimates were tested against zero using a two tailed t-

test. Trial runs in which a select response was not made within 16 trials were excluded from

all behavioural analyses. Dependent and independent variables were z-scored prior to running

all regressions. Exploratory analyses were corrected for multiple comparisons using the

Bonferroni-Holm correction (Holm, 1979). The correction was applied within each analysis.

For the one exploratory comparison between starting value and growth rate regressors, the

alpha threshold was unchanged. For the action bias and reward loss exploratory analyses

(which both used the optimal trials to wait as a predictor), the alpha threshold was corrected

for two exploratory tests.

**EEG Analyses**

We conducted a series of multivariate EEG analyses to understand the neural

processes underpinning task performance. The analyses aimed to identify EEG signals that

tracked three sets of task variables: (1) externally presented variables (starting value and

growth rate), (2) internally represented variables (distance-to-goal and latent reward) and (3)

action variables (distance-to-select, latent reward to select and select versus wait response).

We predicted that participants would track an option's latent reward and use this information

to decide when to select the option, a strategy that would be reflected as strong latent reward

encoding.

*Cross-validated neural decoding*

To test the encoding of each task variable, we used a cross-validated decoding

approach. We will describe the approach in general terms first and provide details about the

specific analyses in subsections below. To decode a specific task variable, we selected data

from the relevant trial (e.g. trial 1 within the run). Trials that involved a select response or no

response were excluded. Data were baselined from 250ms to 50ms before trial onset and

channel demeaned prior to all analyses. The analysis then ran through a series of train and

test folds. In each fold, a maximum of one trial per condition was held out as test data. As an

example, the test trials for one starting value fold could contain a total of 8 trials with one

trial for each starting value. The remaining trials were used as the training data for that fold.

The number of trials for each condition was balanced in the training fold by selecting a

random subsample of non-test trials for each condition. The number of trials in each random

subsample was one trial less than the lowest number of trials across the conditions, for trial

positions 1-3. Analyses primarily focused on trial positions 1-3 because these were trials in

which the majority of conditions (39/40) had not yet resulted in a decision to select, under the

optimal selection timing. Balancing the trial numbers across conditions and trial positions

meant the decoder would not be biased towards a particular condition and that decoding

results could be compared between trial positions.

Once the training data and test data were organised for a fold, the training trials were

averaged for each condition. This produced a channels × time matrix that reflected the mean

scalp topography for each condition. Each held out test trial was then compared to the

average topographies. To make this comparison, Mahalanobis distances (MDs) were

calculated at each time point between the test trial (a vector of 61 channel values) and each

condition mean (each a vector of 61 channel values). We selected the MD to measure

decoding because it explicitly accounts for covariance structure in the data. This makes it

well suited to EEG data, where channel values tend to be highly correlated. The MD between

the test vector (pattern A) and a condition vector (pattern B) was computed as: $MD_{AB} =$

$\sqrt{(Pattern\ A - Pattern\ B)^T \times Cov^{-1}(Pattern\ A - Pattern\ B)}$, where Pattern A-Pattern

B is the difference between topographies, T is the transpose and $Cov^{-1}$ is the inverse of the

channel covariance matrix. The channel covariance matrix was estimated using within-

condition error, meaning that trials were condition demeaned prior to estimating the

covariance (Walther et al., 2016). The channel covariance estimate also included a shrinkage

estimator (Ledoit & Wolf, 2004), which downweights noisy covariance estimates.

Once MDs had been computed between each test trial in a fold and the condition

averages, the MDs for each trial were then entered into a regression. The MDs were used as

the dependent variable and a vector of predicted condition distances were used as the

independent variable. The predicted distance vector assumed a linear increase in MD for

more dissimilar conditions. For example, a test trial with a starting value of 0 would have a

distance vector of [0,1,2,3,4,5,6,7], indicating there is no expected difference between the test

trial and the condition mean for a starting value of 0, but a maximal difference between the

test trial and the condition mean for a starting value of 350. Both dependent and independent

variables were z-scored prior to running the regression, which was performed at each time

point. Once this regression procedure had been completed for each test trial in the fold, the

next analysis fold began, using a new set of test trials. This process continued until all trials

had been used as a test trial once, resulting in a trials × time matrix of regression coefficients

(betas). To ensure the beta estimates were robust, the entire analysis procedure was repeated

50 times, with eligible data being randomly assigned to different folds on different

repetitions. The betas were then averaged over these repetitions and over trials, providing a

time course of beta that we interpret as neural coding of a given task variable. Once this

process was completed for trial position 1 data, it was applied to data from trial positions 2

and 3.

To assess significant decoding of a task variable, beta estimates for each trial position

were averaged over the decision phase, from trial onset (0s) to the offset of the option

stimulus (800ms) and tested against 0 using two-tailed t-tests, with Bonferroni-Holm (BH)

adjusted alpha thresholds to correct for the three trial positions (Holm, 1979). To test

differences in decoding between trial positions, the beta averages were compared for each

pair of trial positions (i.e. 1 vs 2, 1 vs 3, 2 vs 3) using two-tailed t-tests, with adjusted alpha

thresholds to correct for three between-position tests (Holm, 1979). When examining the

decoding time course for a task variable, trial numbers were matched across conditions

during the analysis but not across trial positions to increase power. Time courses were

smoothed with a 20ms Gaussian kernel prior to non-parametric cluster-based permutation

testing, which was used to correct for multiple comparisons (Maris & Oostenveld, 2007;

Hall-McMaster et al., 2019; Sassenhagen & Draschkow, 2019).

**Presented variables.**

*Starting value.* When decoding information related to the starting value of the choice

item (i.e. the arc length), there were 8 possible starting value conditions (0, 50, 100, 150, 200,

250, 300 and 350). For time-averaged analyses, where trial numbers were balanced across the

conditions and trial positions, the average number of trials per condition across participants

was 19.5 with a standard deviation of 2.94. When examining the time course at trial position

1, where starting value coding was strongest, matching trial numbers at trial position resulted

in a mean of 25.7 trials per condition and a standard deviation of 2.46.

*Growth rate.* When decoding abstract growth rate information, the analysis was

adjusted to leverage the fact that there were two colours per growth rate. This allowed us to

decode abstract growth rate information that could not be attributed to the colour of the

option. Trials using the first colour set were assigned to data split A and trials using the

second colour set were assigned to data split B. We then maintained a strict separation

between data splits A and B in our decoding analyses. Data split A was only used as training

data and data split B was only used as test data (and vice versa). There were 5 possible

growth rate conditions (35, 40, 50, 60, 80). The regression for each test trial therefore used a

vector of predicted condition differences that had 5 values as the independent variable. For

time-averaged analyses, where trial numbers were balanced across conditions, trial positions

and colour set, the average number of trials per condition across participants was 17.4 with a

standard deviation of 1.29. When examining the time course at trial position 1, where growth

rate coding was strongest, matching trial numbers for each growth rate resulted in a mean of

19.9 trials per condition and a standard deviation of 2.05.

**Latent variables.**

*Latent reward.* For latent reward decoding, data were separated into 50-point bins,

starting from 0 points (bin 1=0-49 points, bin 2=50-99 points, bin 3=100-149 points, bin

4=150-199 points, bin 5=200-249 points, bin 6=250-299 points, bin 7=300-349 points, bin

8=350-399 points, bin 9=400-449, bin 10=450-500 points). To make the analysis comparable

with our analysis of distance-to-goal (described next), we used a sliding range of 6 latent

reward bins (bins 4-9 at trial position 2 and 5-10 at trial position 3) that corresponded

approximately to the goal distances used in distance-to-goal decoding. Note that at trial

position 1, the reward value of the choice item is the starting value. The item's latent reward

value only differs from starting value after trial 1, which is why this analysis only considers

trials 2 and 3. Statistical tests were accordingly corrected for two comparisons (Holm, 1979).

For time-averaged analyses, where trial numbers were balanced across bins and trial

positions, the average trials per condition was 21.4, with a standard deviation of 1.77. The

vector of predicted conditions differences used in the regression was based on the difference

in reward bin number. When examining the time course at trial position two, the average

number of trials per condition was 21.9, with a standard deviation of 1.73.

***Distance-to-goal.*** This task variable refers to how many trials away the participant is

from the optimal trial to select the option. When decoding distance-to-goal information, trials

were therefore sorted by the difference between the current trial and the optimal trial to select

the option. The analysis used a sliding range of distance-to-goal conditions at each trial

position (trial position 1 = goal distances 3-8, trial position 2 = goal distances 2-7, trial

position 3 = goal distances 1-6). The sliding range aimed to maintain the same future

selection trials in the analysis at each trial position. At trial position 1, the optimal trials to

select spanned from trial 4 to trial 9 within the run. Sliding the goal distances meant this was

also true at trial positions 2 and 3. This ensured that differences in decoding between trial

positions were not due to differences in starting value, growth rate or the optimal trial to

select, because these factors were consistent across positions. The choice of which goal

distances to use aimed to balance a trade-off between data quality, in which behaviour was

increasingly suboptimal further into a trial run (Figure 1G), and power for the regressions

between each test trial's Mahalanobis distances and the vector of expected condition

distances. Using more goal distances would increase the number of points for these

regressions but it would also include more trial runs in which selection behaviour was

increasingly suboptimal. While we aimed to balance this trade-off, the choice of goal

distances was still somewhat arbitrary. This made it important to replicate the distance-to-

goal coding results in the more carefully controlled RSA analyses (described below). When

balancing all trial numbers across the conditions and trial positions, the average number of

trials per condition across participants was 11.3488 with a standard deviation of 3.1172.

When examining the time course at trial position 2, where distance-to-goal coding was

strongest, matching trial numbers across distance-to-goal conditions resulted in a mean of

16.7188 trials per condition and a standard deviation of 1.0234.

**Action variables.** The previous analyses were performed separately at each trial

position. When decoding action variables, trials were pooled across trial positions 3-6 and

entered into a single analysis to boost power. The increased trial numbers allowed us to do

10-fold cross-validation, as opposed to the more cumbersome process of holding out 1 trial

per condition for each test set in the analyses above. The trials in non-test folds were used as

training data. The number of trials from each condition and each trial position were balanced

in the training set by taking random subsamples from the non-test folds. To avoid potential

RT differences between conditions affecting the decoding results, RTs for each condition in

the training set were statistically compared using paired two-tail t-tests. The alpha threshold

was adjusted to correct for multiple comparisons using the Bonferroni-Holm correction

(Holm, 1979). If two conditions had significantly different RTs, a new random subsample

was selected from the available training trials until no significant differences between

condition RTs were detected. Only then was the analysis permitted to proceed with

calculating multivariate distances between training and test trials. As with previous analyses,

we repeated the analysis 50 times and averaged the outputs to ensure stability of the decoding

results.

*Distance-to-select.* The distance-to-select refers to the number of trials between the

current trial and the trial where a select response is made. For this analysis, select distances of

1-3 were used as conditions. To control for the possibility that the trial immediately before

the decision to select was distinct from all other trials prior to the decision to select, we ran a

control analysis that only included select distances of 2 and 3. To control for the possibility

that our decoding results were driven by different numbers of left and right handed responses,

we ran a second control analysis for select distances 1-3, in which we additionally balanced

the number of left/right button presses.

*Reward to select.* The reward to select refers to the difference in latent reward on the

current trial and the latent reward when the select response is made. We calculated this

difference for each trial in each run. The reward to select values were then separated into 50-

point bins (bin 1=0-49 points, bin 2=50-99 points, bin 3=100-149 points). Reward to select

bins of 1-3 were used as conditions in the analysis.

*Wait vs select.* This was same as the distance-to-select procedure, decoding select

trials vs the previous wait trial (i.e. distance-to-select 0 vs. distance-to-select 1).

***Representational Similarity Analysis***

We used RSA (Kriegeskorte et al., 2008) to control for the possible influence of
extraneous task variables when decoding distance-to-goal and latent reward. The logic of this
approach was to regress out neural coding of starting value, growth rate and latent reward
information, before testing for distance-to-goal coding. In a similar manner, we wished to
regress out neural coding starting value, growth rate and distance-to-goal, before testing for
latent reward coding. If decoding is still significant for the variable of interest after removing
the influence of other task variables, this confirms that our earlier cross-validated decoding
result is not being driven by correlations between task variables. If decoding for a variable of
interest is no longer significant, it indicates that our earlier cross-validated decoding result
could have been driven by another task variable.

We first focused on the analysis of data from trial position 1. We iterated through
each starting value-growth rate-colour set combination, yielding 80 conditions in total (8
starting values × 5 growth rates × 2 colour sets). The 80 conditions were repeated 3 times
each in the experiment. However, a condition could have less than 3 trials available for
analysis at a given trial position due to trials being rejected during pre-processing or due to
trials containing a select response. To ensure balanced trial numbers in the RSA, we included
conditions with all 3 available trials at a given trial position. This resulted in 15/80 conditions
being excluded on average at trial position 2, where latent reward and distance-to-goal were
detected in earlier decoding analyses. No significant differences were found between the
excluded and included conditions on trial 2, based on mean starting value ($t(31)$=-0.508,
$p$=0.615) or mean growth rate ($t(31)$=-1.015, $p$=0.318). For each eligible condition, we
averaged over trials to get the mean scalp topography at each time point. MDs between each
pair of conditions were computed at each time point, resulting in a participant-specific
representational dissimilarity matrix (RDM) for each time point. Next, we constructed a set
of model dissimilarity matrices to reflect the expected dissimilarity structure based on
different task variables. Model matrices were calculated by computing the difference between
each condition pair of a given task variable (starting value, growth rate, distance-to-goal,
latent reward, colour set used to indicate the growth rate). Note that unlike the decoding
analyses, here the latent reward model was not based on the difference in reward bins but the
exact difference in latent reward between conditions.

The first stage regression aimed to remove information that was extraneous to the
variable of interest from the data RDMs at each time point. When examining latent reward as
a variable of interest, model RDMs for the extraneous variables (starting value, growth rate
distance-to-goal, number of trials used to compute the condition average, growth rate colour

set), and the data RDM were transformed into vectors and z-scored. For each time point, the

data RDM was used as the dependent variable and model RDMs for the extraneous variables

above were used as independent variables in a multiple regression, which included a constant

regressor. In a second stage regression, the residual variance from the first stage was used as

the dependent variable latent reward RDM (transformed into a vector and z-scored) was used

as the independent variable. This resulted in a time course of regression coefficients (betas)

for latent reward coding that did not reflect a linear influence of the extraneous variables

above. The analysis procedure was repeated for trial positions 2 and 3. The procedure was the

same when distance-to-goal was the variable of interest, except that the distance-to-goal

model RDM was used as the independent variable during the second stage regression and the

latent reward model RDM was included as an extraneous variable in the first stage

regression. Like the cross-validated decoding analysis, latent reward coding was only tested

for trial positions 2 and 3 because latent reward and starting value were indistinguishable for

trial position 1. Statistical assessment of the decoding strength was tested in the same way as

cross-validated decoding analyses. Beta coefficients for the variable of interest were averaged

over the decision phase (0-800ms).

*Relationships between task performance and neural coding*

**Models of selection timing.** To provide broad insights about the cognitive strategy

used to guide selection behaviour, we performed an exploratory cross-validated model fitting

analysis. The aim of this analysis was to arbitrate between high-level explanations for

participants' bias to select early on long trial runs. We reasoned that early selection could

arise for two broad reasons. First, participants could assign subjective cost to the number of

steps waited, which would reduce the maximum reward that could be gained on a trial run.

This lower subjective maximum would be reached sooner than the true maximum and

thereby result in earlier selection. Second, participants could have a biased representation of

the starting value or growth rate, either of which would result in an inaccurate estimate of the

latent reward on each trial. Such a bias would have a compounding effect on the latent reward

estimate, resulting in more inaccurate reward estimates as more trials are waited. This in turn

would result in an increasing bias to select early as the optimal selection time increased.

To test these broad accounts, we created a series of different models. Each model was

based on the fact that the task's reward dynamics followed the equation: $r = s + g(t - 1)$,

where $r$ is the reward, $g$ is the growth rate and $t$ is the current trial within the run. This meant

that the optimal trial on which to select the option, $t^*$, could be expressed as: $t^* = \frac{r_{max} - s}{g} +$

1, where $r_{max}$ is 500 points. To create the cost of waiting model, we added a hyperbolic delay

discounting factor to the maximum reward (see van den Bos & McClure, 2013) resulting

in: $\frac{r_{max}}{[1+w(t^*-1)]} = s + g(t^* - 1)$, where $w$ is a free parameter for the cost of waiting. This

equation can in turn be rearranged into the form: $gwn^2 + (g + sw)n + (s - r_{max}) = 0$,

where $n = t^*- 1$. The equation can then be solved for n using the quadratic formula: $n =$

$\frac{-(g+sw) \pm \sqrt{(g+sw)^2 - 4gw(s-r_{max})}}{2gw}$, after which $t^*$ is calculated as $t^*= n + 1$. The biased starting

value model was formulated as: $t^* = \frac{r_{max} - s^b}{g} + 1$, where b is a free parameter for the starting

value bias. The biased growth rate bias model was formulated as: $t^* = \frac{r_{max} - s}{g^b} + 1$, where b is

a free parameter for the growth rate bias. An exponential bias was used in these models, as

opposed to a multiplicative or additive bias, to account for the non-linear bias observed in

empirical selection times (Figure 1G). We also created models with each pairwise

combination of the free parameters (wait cost, starting bias, growth bias) and one model with

all three free parameters.

      The performance of each model was evaluated in a cross-validation procedure. For

each participant, data were randomly divided into 10 folds. On each iteration of the analysis,

one fold was held out as test data and the remaining folds were used as training data. The best

fitting values of the free parameter/s in a model were selected by minimising the sum of the

squared error. The minimum and maximum possible parameter values for the waiting cost

parameter were constrained to 0 and +30. For the starting value and growth rate bias

parameters, these were 0 and +5. The best fitting parameter values were then used in each

model equation, to predict the trials waited until a selection response was made in each of the

held out test runs. The model predictions were rounded up to the nearest integer to account

for trials being discrete units. The model was then scored for that test fold by calculating the

mean squared error (MSE) between the predicted trials waited and the actual trials waited.

This process was repeated until each model had a MSE score for each test fold. The

procedure was repeated 50 times with random subsamples of trials in each fold to ensure

stable results. Within each subsample, the different models were trained and tested on the

same trials to provide a fair comparison of performance. Scores were then averaged across

the test folds and the subsamples. For each participant, we next calculated the difference in

MSE between each model and the cost of waiting model. Once we had an MSE difference

score for each model for each participant, we calculated bootstrapped 95% confidence

intervals for the mean difference in MSE. The differences in MSE were assessed using

597   Bayesian paired t-tests, to quantify the strength of evidence that the wait cost model had

598   lower error than the other models. When examining the predictions of the three best models

599   against the optimal selection model (Figure 4A-C), we added 1 to both the predicted number

600   of trials waited and the actual number of trials waited, thereby examining the model and

601   participant data in terms of the trial on which the option was selected.

602           **Relationship between neural coding and model parameters.** The model parameters

for the cost of waiting model were averaged over the test folds. These values were then

entered into a series of Spearman correlations with the decoding strength of different task

variables, taken from the cross-validated decoding analyses described above. These task

variables included the decoding strength, averaged over the decision phase (0-800ms), for the

starting value on trial 1, growth rate on trial 1, distance-to-goal on trial 2 and latent reward on

trial 2. The task variables also included the decoding strength, averaged over the response

phase (1050-2000ms), for the distance-to-select and wait versus select decoding. The alpha

threshold was adjusted for 6 exploratory tests using the Bonferroni-Holm correction (Holm,

1979). Correlations between these model parameters and the neural data could potentially

provide converging evidence for a cost of waiting account. Specifically, we reasoned that if

the cost of waiting parameters reflected a subjective waiting cost, they should correlate with a

decision variable needed to evaluate when a select response should be made, such as

distance-to-goal information. To validate the correlation results in a model-free manner, we

repeated the correlations but substituted the cost of waiting parameter for each participant

with their average action bias (the average number of trials earlier participants selected the

option than the optimal linear model).

**Results**

To investigate whether decisions about when to select an option arise from latent reward or distance-to-goal tracking, 32 participants completed a wait-select task (Figure 1). On each trial run, participants were presented with one of 40 specific options, defined by a combination of one of eight possible starting values and one of five growth rates. These properties were signalled using a triangular wedge shown on screen, the size of which indicated the starting value and the colour of which indicated the growth rate. On each individual trial within a run, participants decided between waiting and selecting the option. When deciding to wait, the option's reward increased based on its growth rate, towards a maximum of 500 points. Participants then moved to the next trial, making another wait-select decision. The unique starting value and growth rate combinations meant that different options reached the 500-point maximum after a different number of wait decisions. Once the reward maximum had been reached, continued wait decisions produced an exponential decline in the option's reward value, forcing participants to carefully time each select decision to gain the maximum number of points. The timing for optimal selection could range from 3 to 16 trials into the run (mean=8, SD=3) and the run could last for a maximum of 16 trials. Critically, the visual appearance of the option on the screen remained the same throughout the trial run, despite changes in its underlying reward value following each wait decision. This meant that participants could not use sensory information to guide decision-making after the first trial, and instead needed to use latent information that had been computed internally, such as the option's latent reward prospect. When deciding to select the option, participants earned its latent reward and the trial run ended.

Participants had experience with options prior to starting the experiment, to learn the correspondence between growth rates and wedge colours. Each participant completed 240 trial runs in the main task, averaging 1,660 individual wait-select decisions (SD=126). 61-channel electroencephalograms recorded during decisions were used to conduct a series of cross-validated decoding and multi-stage representational similarity analyses (RSA), to assess latent reward and distance-to-goal tracking, in the lead-up to option selection. The orthogonal manipulation of starting value and growth rate in the task made it possible to dissociate an option's latent reward from potentially confounding variables in the neural analyses, such as how many trials had passed since the beginning of a run and how many trials remained until an option reached its maximum.

**Decisions to select were influenced by starting value and growth rate**

To assess participant choices, we ran a regression that tested whether the number of trials waited before selecting the option was influenced by starting value and growth rate (Figure 1C). The analysis revealed that select decisions showed significant sensitivity to both starting value (mean beta=-0.640, SD=0.101, $p$=8.164-27) and growth rate information (mean beta=-0.467, SD=0.127, $p$=8.655e-20). The direction of these relationships indicated higher starting values and growth rates predicted earlier decisions to select. Participants' selection timing and optimal selection timing for each starting value-growth rate condition is visualised in Figures 1E-F. To summarise, our behavioural results indicate participant choices were influenced by the reward structure of the task.

**Decisions were biased towards early selection when options were slow to reach the maximum value**

Participants showed a bias to select options earlier than would be optimal for reward maximisation, especially in conditions which took longest to reach maximum value (Figures 1G and 1H). To explore this effect, we ran a regression that examined whether the bias to select early grew as optimal selection times increased. This confirmed that participants tended to show larger bias to select early when an option required more trials to reach the maximum value of 500 points (mean beta=0.440, SD=0.193, Bonferroni-Holm (BH) corrected $p$=1.101e-13, correction applied for the two exploratory tests in this section). The bias to select early on slow trial runs resulted in a loss in points compared to the optimal selection timing. The reward loss could be predicted from the optimal selection times (mean beta=0.271, SD=0.131, BH corrected $p$=5.711e-13), indicating larger reward losses for items that were slower to reach the maximum value.

## A  Wait response

Decision Phase
800ms
Run i, trial 1
Reward for selecting:
350 of max. 500

Delay
250ms

Response
Up to 2000ms

Wait Feedback
500ms
Always +1

ITI
600-2000ms

Decision Phase
800ms
Run i, trial 2
Reward for selecting:
410 of max. 500

Delay
250ms

## B  Select response

Decision Phase
800ms
Run i, trial 3
Reward for selecting:
470 of max. 500

Delay
250ms

Response
Up to 2000ms

Select Feedback
500ms

ITI
600-2000ms

Decision Phase
800ms
Run i + 1, trial 1
Reward for selecting:
200 of max. 500

Delay
250ms

## C  Option properties

Starting value     0   50   100   150   200   250   300   350
Wedge size

Growth rate     35   40   50   60   80
Colour (set A)
Colour (set B)

**D  Effect of task parameters on selection timing**

**E  Optimal selection time**

**F  Emprical selection time**

**G  Optimal vs. empirical selection timing**

**H  Empirical action bias**

**I  Empirical reward loss**

*Figure 1.* **A-B**: Task design. Participants were presented with an option that had a specific
starting value (wedge size) and growth rate (colour). **A:** Participants could choose to let the
option's reward increase, by selecting the blank side of the screen during the response phase.
The option reward was then updated by the growth rate and the participant performed another
trial with the same item. Importantly, the same starting value and growth rate information
were presented for each trial within a run, even though the underlying option reward was
changing. **B:** Participants could choose to end the trial run by selecting the side of the screen
with the option during the response phase. Participants then received the current option
reward and started a new trial run, with a new option. Option rewards increased linearly up to
their maximum value (500 points), after which value decayed exponentially if participants
continued to make wait responses. Trial runs lasted up to a maximum of 16 trials. **C:** Option
properties. Options could have one of eight starting values, ranging from 0-350 points.
Starting value was indicated by the size of a wedge shown on screen (with wedge size
oriented randomly on each trial run). The option could have one of five growth rates, which
determined the increase in an option's latent reward per wait response. Growth rates included
35, 40, 50, 60 and 80 points per wait trial, which were selected to maximise variability in the
optimal select trial from a starting value of 0. Two colours were used per growth rate for each
participant, with different colour mappings used for different participants. **D:** Regression
coefficients showing the influence of starting value and growth rate on the timing of option
selection (trial on which the option was selected within the trial run). The lower middle and
upper horizontal bars within each plot indicate the 25$^{th}$ percentile, the median and the 75$^{th}$
percentile respectively. Coloured circles within each box show the mean across participants
and vertical lines extending from these circles show the standard error of mean. Vertical
whiskers extending from each box indicate the most extreme upper and lower values within
1.5 times the interquartile range. Values outside this were deemed outliers and are indicated
with a + symbol. *** above each condition indicates regression coefficients are significantly
different from zero at p<0.001. **E-F:** Summary of selection timing for each starting value-
growth rate combination. **E:** The optimal trial on which to select each option to get the
maximum number of points. **F:** The median trial on which participants selected each option.
**G:** The trial on which participants selected the option (y-axis) as a function of the optimal
trial to select the option in order to gain maximum reward (x-axis). The black diagonal
provides a reference line for an optimal agent and the purple line shows mean participant
data. Shading around the purple line shows the standard error of mean. **E-F:** Summary of
performance biases for each starting value-growth rate combination. **H:** The difference
between the optimal and empirical selection timing (the action bias). **I:** The difference
between the median number of points earned and the maximum number that could be earned
(the reward loss).
724

**Starting value and growth rate were encoded in neural activity patterns**

Having established that participant choices were sensitive to the reward structure of

the task, we performed a series of decoding analyses to test whether task information was

encoded in patterns of neural activity. Unless otherwise specified, decoding was conducted

on the first three trials in a run, where almost all starting-value/growth-rate combinations

(39/40) had not yet resulted in a decision to select under the optimal timing. The analyses

balanced the number of trials from each condition when training the decoder and used

repeated subsampling to ensure stability of the results (see Methods). We first found that

information related to the starting value of the choice item (the wedge size) could be decoded during the decision phase (0-800ms following trial onset) during the first three trials within the trial run (Figure 2A). Starting value decoding was numerically highest on the first trial within a run (mean beta=0.018, SD=0.020, $t(31)$=5.107, BH corrected $p$=4.739e-5) and decreased on the second (mean beta=0.010, SD=0.013, $t(31)$=4.412, BH corrected $p$=2.998e-4) and third trials with the run (beta mean=0.008, SD=0.019, $t(31)$=2.304, BH corrected $p$=0.028). Despite this numerical reduction, we did not detect significant differences in the decoding strength for starting value related information between trial positions 1 and 2 ($t(31)$=1.685, BH corrected $p$=0.240), positions 1 and 3 ($t(31)$=1.809, BH corrected $p$=0.240 or positions 2 and 3 ($t(31)$=0.727, BH corrected $p$=0.472). When visualising the full time course from 0-2000ms during the first trial (Figure 2B), where starting value decoding was numerically strongest, we detected starting value information across most of the trial, from early in the decision phase into the response phase (window tested=0-2000ms, first significant cluster window=148-1108ms, cluster corrected $p$=3e-04; second cluster window=1140-1364ms, cluster corrected $p$=0.042; third cluster window=1680-2000ms, cluster corrected $p$=0.035). It is important to note that because starting value is coupled to the wedge size, these decoding results could reflect a combination of starting value and perceptual factors like shape and contrast, particularly in the early stimulus-evoked period of the trial (~100ms). It is equally important to note that separating these factors is not critical for the present study, in which the main aim was to decode latent reward information over time, while dissociating latent reward information from other task factors.

Unlike starting value, which was coupled to the wedge size, each growth rate corresponded to two wedge colours per participant. This meant we could use cross-decoding to dissociate growth rate encoding from perceptually-evoked responses by training the decoder on one colour set and testing it on the second colour set. Neural encoding of abstract growth rate information, independent of stimulus colour, was present during the decision phase on the first trial within a run (Figure 2C) (mean beta=0.011, SD=0.016, $t(31)$=3.701, BH corrected $p$=0.003). Significant growth rate encoding was not detected on the second (mean beta=0.001, SD=0.019, $t(31)$=0.375, BH corrected $p$>0.99) or third trial within a run second (mean beta=0.001, SD=0.022, $t(31)$=0.284, BH corrected $p$>0.99). We observed a numerical reduction in decoding strength following trial position 1, reflecting a strong trend towards reduced growth rate decoding between trial positions 1 and 2 ($t(31)$=2.484, BH corrected $p$=0.056) and positions 1 and 3 ($t(31)$=2.382, BH corrected $p$=0.056). No significant difference in growth rate decoding was observed between positions 2 and 3

(*t*(31)=0.027, BH corrected *p*=0.979). Visualising the full time course from 0-2000ms during

the first trial (Figure 2D), growth rate decoding was evident from midway through the

decision phase to the beginning of the response phase (window tested=0-2000ms, cluster

window=320-1096ms, cluster corrected *p*=9e-4).

To summarise, information related to an option's starting value (the wedge size) and

abstract information about its growth rate were encoded in patterns of neural activity as

participants performed the task. In addition, these task variables were most prominent

numerically on the first trial within each trial run.

*Figure 2.* Neural decoding of presented and latent variables. **A:** Average decoding strength
for starting value information (wedge size) during the decision phase (0-800ms), on the first
three trials within a run. **B:** Time course for starting value decoding for the first trial within a
run (0-2000ms from trial onset). **C-D:** Abstract growth rate decoding, independent of
stimulus colour due to cross-decoding across colour sets. **C:** Average decoding strength for
abstract growth rate information during the decision phase (0-800ms), on the first three trials
within a run. **D:** Time course for abstract growth rate decoding on the first trial within a run

(0-2000ms from trial onset). **E:** Average decoding strength for latent reward, which is the
starting value plus the product of growth rate × trials waited so far in the run. This is shown
during the decision phase (0-800ms) on the second and third trials in a run. Latent reward is
not shown on trial one because it would be equivalent to starting value. **F:** Time course for
latent reward decoding on the second trial within a run (0-2000ms). **G:** Average decoding
strength for distance-to-goal information (i.e. the number of trials from the current trial to the
optimal selection trial) during the decision phase (0-800ms), for the first three trials within a
run. **H:** Time course for distance-to-goal decoding on the second trial within a run (0-2000ms
from trial onset). **I-L:** Multi-stage representational similarity analysis (RSA) of latent task
variables. The cross-validated decoding in figures A-H does not control for the influence of
other task variables, which could drive the decoding results. The multi-stage RSA in I-L
regresses out neural activity related to other task variables, before decoding the variable of
interest. This provides a measure of latent variable decoding, independent from other task
variables. The pattern alignment measure refers to how much the neural dissimilarity matrix
can be predicted from a model dissimilarity matrix that contains expected condition
differences. **I-J:** Pattern alignment for latent reward encoding after starting value (wedge
size), growth rate (colour) and distance-to-goal have been regressed out of the neural
dissimilarity matrix obtained from the EEG signal. **I:** Average pattern alignment for latent
reward encoding during the decision phase (0-800ms) for the second and third trials within a
trial run. **J:** Pattern alignment time course for latent reward encoding on the second trial
within a run (0-2000ms). **K-L:** Pattern alignment for goal distance encoding when starting
value, growth rate and latent reward have been regressed out of the EEG signal. **K:** Average
pattern alignment for distance-to-goal during the decision phase (0-800ms), for the first three
trials within a run. **L:** Pattern alignment time course for distance-to-goal encoding on the
second trial within a run (0-2000ms). **A,C,E,G,I,K:** The lower middle and upper horizontal
bars within each box indicate the 25$^{th}$ percentile, the median and the 75$^{th}$ percentile
respectively. Coloured circles within each box show the mean across participants and vertical
lines extending from these circle show the standard error of mean. Vertical whiskers
extending from each box indicate the most extreme upper and lower values within 1.5 times
the interquartile range. Values outside this were deemed outliers and are indicated with a +
symbol. Asterisk symbols above each condition indicate decoding coefficients are
significantly different from zero at ***$p<0.001$, **$p<0.01$, *$p<0.05$. Asterisk symbols above
a bar that bridges two conditions indicate a significant difference between conditions at
***$p<0.001$, **$p<0.01$, *$p<0.05$. Asterisk symbols are based on Bonferroni-Holm (BH)
corrected p-values. **B,D,F,H,J,L:** Vertical lines show onset of the decision phase, delay and
response phase respectively. Shading in the decoding time courses show the standard error of
mean. Solid coloured lines under time courses indicate when significant decoding is observed
(cluster corrected p-values <0.05).
822

**Latent reward information was initially decodable from neural activity patterns**

So far we have verified that the main task variables were encoded on the first trial of

each run. However, either variable on its own is insufficient for participants to solve the task.

Starting value and growth rate need to be integrated in order to determine when an option has

reached its peak reward. We therefore investigated whether latent decision variables – which

were purely internal and could be used to guide selection timing - were encoded in neural

activity. One such variable is the option's latent reward value, which changed from trial to

trial, and could be internally tracked towards its maximum using starting value and growth

rate information (and elapsed time). On the first trial in the run, the latent reward was

equivalent to starting value. We therefore focused on trials two and three, separating trials

into 50-point latent reward bins for cross-validated decoding (see *Latent Variables* in

Methods). Latent reward information was detected on the second trial within the run (Figure

2E, mean beta=0.009, SD=0.015, $t(31)$=3.551, BH corrected $p$=0.003). Latent reward showed

a significant decrease in decoding strength between trials two and three ($t(31)$=2.111,

$p$=0.043), with no significant latent reward information detected on trial three (mean

beta=6.560e-6, SD=0.016, $t(31)$=0.002, BH corrected $p$=0.998). When examining the full

time course during trial two, where latent reward decoding was strongest, we observed a

significant cluster at the start of the decision phase (Figure 2F, window tested=0-2000ms,

first cluster window=296-548ms, cluster corrected $p$=0.0232; second cluster window=684-

932, cluster corrected $p$=0.031; third cluster window=1284-1648ms, cluster corrected

$p$=0.009). To summarise, we found initial evidence that latent reward information could be

decoded as early as the second trial.

**Distance-to-goal information was initially decodable from neural activity patterns**

847            Another latent variable that could be used to guide selection behaviour is the number

of trials until the maximum number of points is reached, a variable we call the distance-to-

goal. Distance-to-goal information could not be detected on the first trial in the run (Figure

2G. mean beta=7.586e-4, SD=0.020, $t(31)$=0.213, BH corrected $p$=0.833). Following trial

one, we observed a significant increase in distance-to-goal encoding ($t(31)$=-3.524, BH

corrected $p$=0.004), with significant distance-to-goal information overall on trial two (mean

beta=0.014, SD=0.020, $t(31)$=3.829, BH corrected $p$=0.002). This distance-to-goal

information was encoded transiently, as indicated by a significant decrease between trials two

and three within the run ($t(31)$=2.389, BH corrected $p$=0.046), with no detectable distance-to-

goal information on trial three (mean beta=0.003, SD=0.019, $t(31)$=0.967, BH corrected

p=0.682). No significant difference between trials one and three was detected ($t(31)$=-0.502,

BH corrected $p$=0.619). When examining the full time course during the second trial (Figure

2H), where distance-to-goal coding was present, distance-to-goal information was

represented during most of the trial, from the decision phase into the response phase (window

tested=0-2000ms, cluster window=292-1728ms, cluster corrected $p$=1e-4). To summarise, we

found that information about when to select the option for maximum reward could be initially

decoded on the second trial within a run, after information about the starting value and

growth rate had been encoded on trial one.

**Latent reward could not be decoded when controlling for other task variables**

While latent reward and distance-to-goal information could be decoded in the separate

analyses above, these variables were correlated because higher latent rewards meant

participants were closer to the optimal trial to select (mean Spearman's Rho=-0.851 for

behavioural data on trial position 2). This means that the decoding analyses above could be

sensitive to the same underlying information. To dissociate latent reward and distance-to-goal

information, we performed multi-stage RSA. The logic behind this analysis was to first

regress out multivariate activity related to extraneous task variables and then test whether

information about a variable of interest could still be decoded from the neural signal (see

Methods). This approach has the benefit of being able to use exact latent reward values rather

than bins, using pairwise differences between condition labels as regressors in a multivariate

regression. The correlation between latent reward and distance-to-goal information used in

the analysis was reduced in the RSA setup (mean Spearman's Rho=0.546 on trial 2). When

controlling for the possible influence of starting value, growth rate and distance-to-goal using

multi-stage RSA, latent reward information could not be detected on trial two (Figure 2I,

mean beta=-0.001, SD=0.006, $t(31)$=-1.239, BH corrected $p$=0.449) or trial three (mean

beta=4.170e-4, SD=0.014, $t(31)$=0.175, BH corrected $p$=0.862). There was no significant

difference in latent reward decoding between trials two and three ($t(31)$=-0.584, $p$=0.563).

When examining the full time course on trial two (Figure 2J), this control analysis did not

detect any significant decoding clusters (window tested=0-2000ms, strongest candidate

cluster=660-716ms, cluster corrected $p$=0.2381). To summarise, we found that when

accounting for other task variables, latent reward information could no longer be decoded on

trial 2 within the run.

**Distance-to-goal could be decoded when controlling for other task variables**

By contrast, when controlling for the possible influence of starting value, growth rate

and latent reward, the multi-stage RSA did replicate the cross-validated decoding of distance-

to-goal (Figure 2K). As with the decoding analysis, no distance-to-goal information was

detected during the decision phase on the first trial within the run (mean beta=-0.010,

SD=0.034, $t(31)$=-1.683, BH corrected $p$=0.205). On the second trial, however, distance-to-

goal information that was independent from starting value, growth rate and latent reward,

could be detected (mean beta=0.013, SD=0.025, $t(31)$=2.919, BH corrected $p$=0.019). This

information was transient, with no significant distance-to-goal information detected on trial

three (mean beta=-8.393e-4, SD=0.032, $t(31)$=-0.151, BH corrected $p$=0.881). The distance-

to-goal encoding seen on trial two was significantly higher than on trial one ($t(31)$=-3.290,

BH corrected $p$=0.008), but no significant differences were detected between trials one and

three ($t(31)$=-1.180, BH corrected $p$=0.247) or trials two and three ($t(31)$=1.752, BH

corrected $p$=0.179). When examining the full time course on trial two (Figure 2L), we

detected significant distance-to-goal coding that began in the decision phase and extended

into the delay phase (window tested=0-2000ms, candidate cluster window=388-900ms,

cluster corrected $p$=0.012). To summarise, distance-to-goal information, unlike latent reward,

was encoded in neural activity even when information about other task variables was

removed from the signal.

**Information about empirical selection timing was encoded in patterns of neural activity**

So far we have shown that, early within the trial run, participants encoded information

about when an option ought to be selected in the future. This distance-to-goal signal was

encoded transiently on trial 2 but could not be decoded on the following trial. We speculated

that this could arise if the neural response to a given condition starts out as a faithful

reflection of the optimal distance to reach the maximum number of points. But since

participants' actual choices were suboptimal (Fig 1G-I), their selection plan might

progressively reflect their actual selection timing rather than optimal selection timing,

especially on trial runs that involve longer optimal wait times. In this scenario, decoding the

actual selection behaviour might still be possible on later trials leading up to the choice. We

therefore tested whether participants monitored the number of trials until their actual

selection response, a variable we call the distance-to-select. This is distinct from the distance-

to-goal because it represents when people made their actual selection response, rather than

the optimal response for a given condition, and therefore accounts for suboptimal choice

behaviour. To maximise power, these cross-validated decoding analyses pooled data from

trial positions 3-6, using balanced trial numbers from each, and tested whether participants

were 1, 2 or 3 trials away from making a select response.

Distance-to-select information was encoded across trial positions 3-6 (Figure 3A),

with a time course that gradually ramped up from the decision phase to the response phase

(window tested=0-2000ms, cluster window=472-2000, cluster corrected $p$<1e-4). This effect

was not due to differences in average reaction times (RTs) between the selection distances.

No significant differences in RT were detected between conditions used to train the decoder.

This included RTs for selection distances of one (mean=487ms, SD=102) and two

(mean=486ms, SD=102; $t(31)=1.021$, BH corrected $p=0.532$), one and three

(mean=485,SD=104; $t(31)=1.763$, BH corrected $p=0.263$), as well as two and three

($t(31)=1.133$, BH corrected $p=0.532$). This effect was also not due to differences in the

number of left and right button presses between conditions. A control analysis that

additionally matched the number of left and right responses showed the same results (window

tested=0-2000ms, cluster window=476-2000ms, cluster corrected $p<1e-4$). To test whether

the effect could be driven by the trial before the select response being distinct from all other

trials, we repeated the analysis, but only included trials with a distance-to-select of two or

three. This confirmed that distance-to-select information was encoded prior to the trial before

option selection (window tested=0-2000ms, first cluster window=212-456, cluster corrected

$p=0.040$, second cluster window=1216-1452ms, cluster corrected $p=0.040$, third cluster

window=1616-2000ms, cluster corrected $p=0.012$).

These results suggest that participants performed a mental countdown to time their

selection response. However, an alternative explanation could be that participants were

counting down the number of points until the reward maximum was reached. This alternative

would be consistent with latent reward tracking. To test this possibility, we ran a decoding

analysis that examined whether participants were representing the difference in current

reward and reward they would get upon selecting the option (the reward to select). The

reward to select values were divided into 50-point bins starting from 0 and reward to select

bins of 1-3 were used for the analysis (0-150 points away from the select response). We did

not detect significant reward to select information during trial positions 3-6 (Figure 3B,

window tested=0-2000ms, strongest candidate cluster=44-64ms, cluster corrected $p=0.597$).

Having shown participants encoded the trials until their select response, we examined

whether decisions to select were neurally distinct from decisions to wait (distance-to-select 0

vs. 1). This revealed a strong select signal that began in the decision phase and became more

distinct during the response phase (window tested=0-2000ms, cluster window=192-2000ms,

cluster corrected $p<1e-4$).

To summarise, we found evidence indicating that participants tracked the number of

trials until their upcoming select response and that this result was not explained through latent

reward monitoring.

*Figure 3*. Neural decoding of empirical selection timing. **A:** Decoding time course for the number of wait trials until a select response is made (the distance-to-select). **B:** Decoding time course for the difference between the options current latent reward and its latent reward when selected (the reward to select. **C:** Decoding time course for the decision to select versus the decision to wait on the previous trial. **A,B,C:** Vertical lines show onset of the decision phase, delay and response phase respectively. Shading around the principal line in the decoding time courses show the standard error of mean. Solid coloured lines under time courses indicate when significant decoding is observed (cluster corrected p-values <0.05).

**Relationship between neural activity and the timing of option selection**

So far our neural decoding results point towards a time-oriented task strategy, in which participants evaluated when an option would become most valuable in the future and represented the number of time steps until their upcoming select decision. To understand the relationship between the neural coding results and the timing of option selection, we therefore sought to understand more about the strong bias to select options earlier than would be optimal, when options were slow to reach their maximum value (Figures 1G and 1H). We reasoned that this action bias could emerge for two distinct reasons. One reason would be that the participants discounted an option's maximum reward based on the number of trials that would need to be waited. This would result in earlier selection because the lower subjective maximum would be reached sooner than the true maximum. A second reason would be that an option's starting value or growth rate was misrepresented as being higher than its actual value. This would result in earlier selection because the latent reward estimate would become systematically higher than its true value with longer trial runs. When comparing the cross-validated performance between models that could potentially account for the action bias (see Methods), we found that the model discounting an option's maximum reward with a waiting cost made more accurate predictions about selection timing than models including a biased representation of the starting value (average difference in mean squared error (MSE)=-2.011; CIs=[-2.687 -1.483], $BF_{10}$=6.131e4), a biased representation of the growth rate (average

difference in MSE=-0.164, CIs=[-0.277 -0.079], $BF_{10}$=12.854) or both (average difference in

MSE=-0.1341, CIs=[-2.498e5 -2.430e5], $BF_{10}$=5.740). We also found the cost of waiting

model did not reliably make more accurate predictions when additional free parameters were

added to it, including a bias in the starting value (average difference in MSE=0.015, CIs=[-

0.039 0.068], $BF_{10}$=0.215), a bias in the growth rate (average difference in MSE=-0.007,

CIs=[-0.047 0.038], $BF_{10}$=0.197) or both (average difference in MSE=0.030, CIs=[-269.353 -

259.400], $BF_{10}$=0.242).

The cost of waiting model contained a single free parameter that reflected how much

participants discounted an option's reward prospect for the time that would need to be waited.

A larger cost of waiting parameter meant that participants showed a stronger bias to select

options early on slow trial runs. When comparing participants' best fitting wait cost

parameter with their neural data, we found a significant positive relationship between

distance-to-goal encoding over the decision phase (0-800ms) in the second trial in the run and

the cost of waiting parameter (Spearman's Rho=0.526, BH corrected $p$=0.014), indicating

that better distance-to-goal encoding was associated with a larger bias to switch early on slow

trials. No correlations were detected between the cost of waiting parameter and the neural

encoding of other task variables, including the starting value on trial 1 (Spearman's Rho=-

0.200, BH corrected $p$=0.624), growth rate on trial 1 (Spearman's Rho=-0.110, BH corrected

$p$=0.549), latent reward on trial 2 (Spearman's Rho=0.341, BH corrected $p$=0.227), distance-

to-select across trials 3-6 (Spearman's Rho=-0.228, BH corrected $p$=0.624) and select versus

wait responses across trials 3-6 (Spearman's Rho=-0.368, BH corrected $p$=0.194). To validate

these correlation results in a model-free manner, we examined the relationship between the

action bias (the behavioural bias to select earlier than the optimal selection trial) and neural

encoding of distance-to-goal. Consistent with the results above, we found a significant

relationship between the action bias and distance-to-goal encoding (Spearman's Rho=0.471,

BH corrected $p$=0.039) but not the remaining neural variables (max. Spearman's Rho=0.373,

min. BH corrected $p$=0.177).

1019

*Figure 4.* **A-C:** Top three performing models of selection timing. **A:** A cost of waiting model, which includes a reward cost proportional to number of steps waited. **B:** A model that includes a cost of waiting as well as biased representations of the starting value and growth rate. **C:** A model that includes a cost of waiting and a biased representation of the growth rate. **A-C:** Each plot shows the number of trials participants waited before selecting the option (purple line) as a function of the optimal number of trials to wait before selecting the option. The black diagonal provides a reference line for an optimal agent. The remaining coloured line shows the cross-validated performance of the model fit to participant data. Shading around each coloured line shows the standard error of the mean. **D:** The difference in mean squared error (MSE) between a given model and the cost of waiting model. More negative values indicate worse model performance, relative to the cost of waiting model. The y-axis shows each model being compared to the costs of waiting model. The x-axis shows the difference in MSE. Mean differences across the sample are shown with dots enclosed in a black circle and 95% confidence intervals are shown with black lines extending from the sample means. MSE differences for individual participants are shown for the top competitor models as coloured dots and the remaining competitor models as grey dots. **E:** Correlation between the average distance-to-goal coding during the decision phase (0-800ms) and the cost of waiting parameter estimates. Black lines indicate linear fits to the data and grey lines indicate 95% confidence intervals of the fits.

**Discussion**

The present study examined how people decide when to select a specific option as its reward changed reliably over time, in the absence of direct sensory cues to indicate its changing value. We hypothesized that an option's starting value and growth rate could be used to track the option's latent reward over time, allowing the option to be selected when its reward reached a certain threshold. We assessed whether this strategy could in principle be dissociated from an alternate strategy that might lead to similar neural responses, namely determining the optimal selection time at the beginning of a trial run and waiting for this time point to occur, without continuously updating a latent reward estimate. While starting value and growth rate were strong predictors of when an option would be selected, we did not find neural evidence consistent with latent reward tracking in the present experiment. Instead, we found neural evidence that people encoded option properties and used this information to evaluate when an option would reach its maximum value, far in advance of selecting it. This distance-to-goal information was present in the data even when controlling for the option's latent reward but not vice versa. Following the distance-to-goal signal encoded early in a trial run (on trial 2), we observed patterns of neural activity indicating how many steps into the future the option would actually be selected (on trials 3-6). These results provide evidence that even strategies that lead to very similar predictions about neural activity can be dissociated using representational similarity analysis. In the present study, people appeared to decide when to select the option in advance and monitored the time until their selection response, as opposed to actively tracking the option's changing reward prospect. Computational modelling further showed that selection behaviour could be captured with a model that discounted an option's maximum reward based on the time needed for its maximum to be reached. The core parameter in this model showed a positive correlation with the neural encoding of distance-to-goal information.

The present results add to recent studies examining when a specific option should be selected (Khalighinejad et al., 2020a, 2020b; Stoll et al., 2016). Research by Khalinghinejad and colleagues (2020a, 2020b) showed that recent task history is integrated with on-going sensory evidence about an option's reward, to determine when it will be selected. Our results suggest that when on-going sensory evidence is unavailable and reward increases at a predictable rate, temporal predictions about when an option will become most valuable can be used to determine selection timing, circumventing the need to integrate changing reward information. The present results also build on findings from Stoll and colleagues (2016), who found a transient signal in the cingulate cortex encoding latent information about an option's

progress to a reward threshold. While Stoll et al.'s (2016) results raise the possibility that an

option's latent reward could be tracked over time to guide select decisions, we did not find

evidence for latent reward tracking. There could be at least three explanations for this

difference. First, while Stoll et al. (2016) used options with different growth rates, allowing

latent reward progress and distance-to-goal to be dissociated in principle, the analysis did not

explicitly dissociate the two factors. The transient signal observed in Stoll et al. (2016) could

therefore reflect, in part, distance-to-goal information, signaling how soon an option would

reach the reward threshold. Second, while we used a multi-stage RSA procedure to dissociate

the two factors, the variables were still closely related. This could have meant that latent

reward was encoded in the neural signal but could not be detected after a large amount of

correlated variance, which could also be captured with distance-to-goal, was removed. Third,

different environmental constraints could promote different cognitive strategies. In Stoll et al.

(2016), macaques did not know how long it would take for the option to reach the reward

threshold when beginning a trial run and could check the option during the run to gain

information. In our study, participants had all the information needed to determine when an

option would become most valuable at the start of a run, which could have encouraged the

use of distance-to-goal as a proxy for changing reward values. Future studies could use the

analysis approach adopted here to investigate whether latent reward tracking might be

favoured when changes in reward are less reliable. For example, options that change growth

rate at unpredictable times during a trial run could make it more difficult to use distance-to-

goal information, which would need to be recomputed after each change in the growth rate.

One interesting aspect of the results was that distance-to-goal information was

detected transiently, appearing on trial 2 but not on trials 1 or 3. One speculative reason for

this could be that most participants computed distance-to-goal information on trial 1 but at

variable times across trial runs and across participants, making the decoding noisier. On trial

3, distance-to-goal could have become more difficult to decode due to increasing variability

in the encoding, as participants switched from thinking about the optimal selection timing to

when they would actually select the option. While the distance-to-select decoding seen on

trials 3-6 provides some evidence towards this, the reason distance-to-goal coding was so

transient remains elusive. For example, it could also be that decoding became more difficult

on trial 3 due to a general increase in recording noise further into a trial run, as participants

became more distracted. A second interesting aspect was the strong bias to select early, when

options were slow to reach their maximum reward. While unanticipated, this result is

consistent with findings showing humans and macaques do not wait for options to reach their

full expected value before selecting them (Khalighinejad et al., 2020a, 2020b), and that the

probability of making a select response in general increases over trials in sequential tasks

(Baumann et al., 2020). Our computational modelling results suggest that the bias could be

explained by a temporal discounting process, in which an option's subjective value was

reduced with increasing wait times (see van den Bos & McClure, 2013). One aspect the

modelling results do not clearly delineate is whether such discounting occurred at the start of

a trial run, when an option was first being evaluated, or whether it built up during the run, due

to a declining ratio between the maximum reward and the cognitive effort involved in waiting

longer (see Frömer et al., 2021; Kool & Botvinick, 2018; Shenhav et al. 2013; Westbrook et

al., 2020; Yee & Braver, 2018). A final interesting aspect was that participants with stronger

distance-to-goal encoding tended to show a stronger action bias, suggesting that those with

more accurate predictions about peak reward timing selected slow options earlier. One

speculative reason could be that while this has no benefit in a task with a fixed number of

trials, it does have a benefit in open-ended environments, where decisions to select a slow

option prematurely would give decision makers more time to encounter and exploit more

valuable options. This proposal is consistent with findings that human choices to abandon

options are sensitive to opportunity costs (Constantino & Daw, 2015) and that people show

reduced cognitive control performance when opportunity costs are high (Otto & Daw, 2019).

To conclude, we found that when option rewards followed reliable trajectories and

there were no direct sensory changes to indicate changes in reward, people encoded the time

when options would become most valuable in the future and monitored the number of actions

until the point of selection. In contrast, we did not find evidence for independent neural

coding of an option's latent reward over time. These results suggest that, in structured

environments where timing provides a useful proxy for changing reward, the human brain

might use time-oriented encoding to make decisions about when to select an option. At a

broader level, the approaches used in this experiment could be useful for dissociating how

closely related variables impact neural activity during decision-making.

1142

1143

1144

1145

1146

1147

1148

**Author Contributions**

S.H, M.G.S and N.E.M designed the study. S.H acquired the data. S.H and N.E.M. analysed the data with input from M.G.S. S.H wrote the original draft. S.H, N.E.M and M.G.S reviewed and edited the manuscript.

**Diversity Statement**

Here we report the predicted gender and ethnicity of authors in our reference list (Ambekar et al., 2009; Bertolero et al., 2020; Dworkin et al., 2020; Sood et al., 2018; Zhou et al., 2020). First, we obtained the predicted gender of the first and last author of each reference by using databases that store the probability of a first name being carried by a woman. By this measure (and excluding self-citations to the first and last authors of our current paper), our references contain 3.45% woman(first)/woman(last), 3.45% man/woman, 27.59% woman/man, and 65.52% man/man. This method is limited in that a) names, pronouns, and social media profiles used to construct the databases may not, in every case, be indicative of gender identity and b) it cannot account for intersex, non-binary, or transgender people. Second, we obtained the predicted ethnicity of the first and last author of each reference by databases that store the probability of a first and last name being carried by an author of colour. By this measure (and excluding self-citations), our references contain 2.93% author of colour(first)/author of colour(last), 13.6% white author/author of colour, 20.29% author of colour/white author, and 63.18% white author/white author. This method is limited in that a) names and Florida Voter Data to make the predictions may not be indicative of ethnicity, and b) it cannot account for Indigenous and mixed-race authors, or those who may face differential biases due to the ambiguous ethnicisation of their names.

**References**

Ambekar, A., Ward, C., Mohammed, J., Male, S., & Skiena, S. (2009). Name-ethnicity

classification from open sources. In *Proceedings of the 15th ACM SIGKDD*

*international conference on Knowledge Discovery and Data Mining* (pp. 49-58).

Baumann, C., Singmann, H., Gershman, S. J., & von Helversen, B. (2020). A linear threshold

model for optimal stopping behavior. *Proceedings of the National Academy of*

*Sciences*, 117(23), 12750-12755.

Bertolero, M. A., Dworkin, J. D., David, S. U., Lloreda, C. L., Srivastava, P., Stiso, J., ... &

Bassett, D. S. (2020). Racial and ethnic imbalance in neuroscience reference lists and

intersections with gender. *BioRxiv*.

Bulley, A., Henry, J., & Suddendorf, T. (2016). Prospection and the present moment: The

role of episodic foresight in intertemporal choices between immediate and delayed

rewards. *Review of General Psychology*, *20*(1), 29-47.

Constantino, S. M., & Daw, N. D. (2015). Learning the opportunity cost of time in a patch-

foraging task. *Cognitive, Affective, & Behavioral Neuroscience*, *15*(4), 837-853.

Coull, J. T., Cheng, R. K., & Meck, W. H. (2011). Neuroanatomical and neurochemical

substrates of timing. *Neuropsychopharmacology*, *36*(1), 3-25.

Delorme, A., & Makeig, S. (2004). EEGLAB: an open source toolbox for analysis of single-

trial EEG dynamics including independent component analysis. *Journal of*

*Neuroscience Methods*, *134*(1), 9-21.

Dworkin, J. D., Linn, K. A., Teich, E. G., Zurn, P., Shinohara, R. T., & Bassett, D. S. (2020).

The extent and drivers of gender imbalance in neuroscience reference lists. *Nature*

*Neuroscience*, *23*(8), 918-926.

Fouragnan, E. F., Chau, B. K., Folloni, D., Kolling, N., Verhagen, L., Klein-Flügge, M., ... &

Rushworth, M. F. (2019). The macaque anterior cingulate cortex translates

counterfactual choice value into actual behavioral change. *Nature*

*Neuroscience*, *22*(5), 797-808.

Frömer, R., Lin, H., Wolf, C. D., Inzlicht, M., & Shenhav, A. (2021). Expectations of reward

and efficacy guide cognitive control allocation. *Nature Communications*, *12*(1), 1-11.

Hall-McMaster, S., Muhle-Karbe, P. S., Myers, N. E., & Stokes, M. G. (2019). Reward

boosts neural coding of task rules to optimize cognitive flexibility. *Journal of*

*Neuroscience*, *39*(43), 8549-8561.

Hassall, C. D., Harley, J., Kolling, N., & Hunt, L. T. (2020). Temporal Scaling of Human

Scalp-Recorded Potentials During Interval Estimation. *BioRxiv*.

Hunt, L. T., & Hayden, B. Y. (2017). A distributed, hierarchical and recurrent framework for reward-based choice. *Nature Reviews Neuroscience*, *18*(3), 172-182.

Holm, S. (1979). A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 65-70.

Khalighinejad, N., Bongioanni, A., Verhagen, L., Folloni, D., Attali, D., Aubry, J. F., ... & Rushworth, M. F. (2020a). A basal forebrain-cingulate circuit in macaques decides it is time to act. *Neuron*, *105*(2), 370-384.

Khalighinejad, N., Priestley, L., Jbabdi, S., & Rushworth, M. F. (2020b). Human decisions about when to act originate within a basal forebrain–nigral circuit. *Proceedings of the National Academy of Sciences*, *117*(21), 11799-11810.

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis-connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, *2*, 4.

Kool, W., & Botvinick, M. (2018). Mental labour. *Nature Human Behaviour*, *2*(12), 899-908.

Ledoit, O., & Wolf, M. (2004). A well-conditioned estimator for large-dimensional covariance matrices. *Journal of Multivariate Analysis*, *88*(2), 365-411.

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG-and MEG-data. *Journal of Neuroscience Methods*, *164*(1), 177-190.

Murray, E. A., & Rudebeck, P. H. (2018). Specializations for reward-guided decision-making in the primate ventral prefrontal cortex. *Nature Reviews Neuroscience*, *19*(7), 404-417.

Otto, A. R., & Daw, N. D. (2019). The opportunity cost of time modulates cognitive effort. *Neuropsychologia*, *123*, 92-105.

O'Reilly, J. X., & Mars, R. B. (2011). Computational neuroimaging: Localising Greek letters? Comment on Forstmann et al. *Trends in cognitive sciences*, 15(10), 450.

Padoa-Schioppa, C. (2011). Neurobiology of economic choice: a good-based model. *Annual Review of Neuroscience*, *34*, 333-359.

Rich, E. L., & Wallis, J. D. (2016). Decoding subjective decisions from orbitofrontal cortex. *Nature Neuroscience*, *19*(7), 973-980.

Sassenhagen, J., & Draschkow, D. (2019). Cluster-based permutation tests of MEG/EEG data do not establish significance of effect latency or location. *Psychophysiology*, *56*(6), e13335.

Shenhav, A., Botvinick, M. M., & Cohen, J. D. (2013). The expected value of control: an integrative theory of anterior cingulate cortex function. *Neuron*, *79*(2), 217-240.

1255 Sood, G., & Laohaprapanon, S. (2018). Predicting race and ethnicity from the sequence of
1256    characters in a name. *arXiv preprint arXiv:1805.02109*.

1257 Stoll, F. M., Fontanier, V., & Procyk, E. (2016). Specific frontal neural dynamics contribute
1258    to decisions to check. *Nature Communications*, *7*(1), 1-14.

1259 Tankelevitch, L., Spaak, E., Rushworth, M. F., & Stokes, M. G. (2020). Previously reward-
1260    associated stimuli capture spatial attention in the absence of changes in the
1261    corresponding sensory representations as measured with MEG. *Journal of*
1262    *Neuroscience*, *40*(26), 5033-5050.

1263 van den Bos, W., & McClure, S. M. (2013). Towards a general model of temporal
1264    discounting. *Journal of the Experimental Analysis of Behavior*, *99*(1), 58-73.

1265 Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., & Diedrichsen, J. (2016).
1266    Reliability of dissimilarity measures for multi-voxel pattern
1267    analysis. *Neuroimage*, *137*, 188-200.

1268 Westbrook, A., van den Bosch, R., Määttä, J. I., Hofmans, L., Papadopetraki, D., *Cools, R.,
1269    & *Frank, M. J. (2020). Dopamine promotes cognitive effort by biasing the benefits
1270    versus costs of cognitive work. *Science*, *367*(6484), 1362-1366.

1271 Wolff, M. J., Kandemir, G., Stokes, M. G., & Akyürek, E. G. (2020). Unimodal and bimodal
1272    access to sensory working memories by auditory and visual impulses. *Journal of*
1273    *Neuroscience*, *40*(3), 671-681.

1274 Zhou, D., Cornblath, E. J., Stiso, J., Teich, E. G., Dworkin, J. D., Blevins, A. S., & Bassett,
1275    D. S. (2020). Gender diversity statement and code notebook v1.1.
1276    github.com/dalejn/cleanBib

1277

1278

1279