A general framework to learn tertiary structure for protein sequence characterization

Mu Gao[1]* and Jeffrey Skolnick[1]*

[1] Center for the Study of Systems Biology, School of Biological Sciences, Georgia Institute of
Technology, Atlanta GA 30332, USA

* Correspondence:
mu.gao@gatech.edu (MG) and skolnick@gatech.edu (JS)

**Keywords: protein structure prediction, protein folding, sequence alignment, deep-learning,
structural alignment. (Min.5-Max. 8)**

Abstract

During the past five years, deep-learning algorithms have enabled ground-breaking progress towards
the prediction of tertiary structure from a protein sequence. Very recently, we developed SAdLSA, a
new computational algorithm for protein sequence comparison via deep-learning of protein structural
alignments. SAdLSA shows significant improvement over established sequence alignment methods.
In this contribution, we show that SAdLSA provides a general machine-learning framework for
structurally characterizing protein sequences. By aligning a protein sequence against itself, SAdLSA
generates a fold distogram for the input sequence, including challenging cases whose structural folds
were not present in the training set. About 70% of the predicted distograms are statistically significant.
Although at present the accuracy of the intra-sequence distogram predicted by SAdLSA self-alignment
is not as good as deep-learning algorithms specifically trained for distogram prediction, it is remarkable
that the prediction of single protein structures is encoded by an algorithm that learns ensembles of
pairwise structural comparisons, without being explicitly trained to recognize individual structural
folds. As such, SAdLSA can not only predict protein folds for individual sequences, but also detects
subtle, yet significant, structural relationships between multiple protein sequences using the same deep-
learning neural network. The former reduces to a special case in this general framework for protein
sequence annotation.

1   Introduction

The amino acid sequence of a protein encodes the information for carrying out its function. One
essential aspect is the tertiary structure of the protein. Indeed, the prediction of protein tertiary structure
from its sequence is a fundamental question in biophysics (1). In order to predict protein structure at
high accuracy, one main challenge is to model the long-range, many-body effects that collectively
dictate a protein's tertiary structure (2). Over the past several years, exciting breakthroughs have been
made to better address these long-range interactions (2). Using a deep residual convolutional neural
network, significant success has been demonstrated in predicting contacts between individual residues
of a protein sequence (3). Such residue-residue contacts yield both the local secondary structure and
the global fold, and it is the accurate prediction of their synergy that improves model quality.
Subsequently, several groups demonstrated that better residue-residue contact or detailed distance
matrix (distogram) predictions led to significantly improved structure predictions, especially for
challenging targets (4-8). In CASP13, a blind biannual protein structure prediction competition, all
four top-ranked groups in the most challenging, free-modeling category used residue-residue contacts
or distance matrices predicted via deep-learning (9). Among them, DeepMind's AlphaFold achieved
the best performance using a high-quality distogram to derive statistical folding potentials (6). In
CASP14, many improved deep-learning approaches using the convolutional residual networks were
presented, e.g., (10), but AlphaFold2 dominated the competition using a new, end-to-end deep-learning
algorithm with an attention mechanism (11).

A topic closely related to protein structure prediction is protein sequence comparison or alignment
(12). In the low pairwise sequence identity regime of less than 30%, two protein sequences may exhibit
no apparent sequence similarity yet display significant fold similarity when their structures are revealed
and superimposed (13). This observation is attributed to the fact that the structural space of protein
folds is very small for both evolutionary (14) and physical reasons (15). Traditionally, a variety of
sequence alignment approaches have been developed and applied to assist protein structure prediction,
e.g., Hidden Markov Model (HMM) (16) and "threading" approaches (17-19). These efforts provide
the foundation for template-based modeling approaches (20). Conversely, if the structures encoded in
the two sequences are known, their structural alignment generally leads to a more accurate sequence
alignment than those from classical sequence alignment approaches. Such an accurate, meaningful
alignment is often the key to understanding what a novel protein sequence does, e.g., predicting
functional sites (21, 22).

Naturally, this leads to a question: can deep-learning be directly applied to generate a protein sequence
alignment with an accuracy close to the structural alignment counterpart? If so, this would not only
extend the ability to recognize evolutionarily distant sequence relationships but also enable a deeper
learning of the folding code. Moreover, it has practical applications for function and structure
prediction and possibly evolutionary inference. To answer this question, we recently developed
SAdLSA, a sequence alignment algorithm that uses a deep convolutional neural network to learn many
thousands of structural alignments (23). The advantage of SAdLSA was demonstrated in benchmark
tests against HMM-based HHsearch (24). For challenging cases, SAdLSA is ~150% more accurate at
generating pairwise alignments and ~50% more accurate at identifying the proteins with the best
alignments in a sequence library. This allowed the program to detect remote relationships that may be
useful for genome annotation or functional predictions.

Given the encouraging benchmarking results of SAdLSA, one would like to understand why it
performs better than classical sequence comparison approaches. Obviously, the deep-learning
algorithm plays a key role in this improvement, but how does it work? Previously, we have speculated
that SAdLSA implicitly learns the protein folding code without offering direct evidence. In this study,
we shall further substantiate this claim. We noticed that when the same sequence was input into
SAdLSA, SAdLSA aligns the sequence against itself, i.e., self-alignment, and outputs an intra-
sequence distogram for the input. This distogram could encode the fold much like a deep-learning
algorithm designed to predict the distogram for a single query sequence, e.g., DESTINI (4). We shall
perform analysis to understand the distogram generated by SAdLSA self-alignment and demonstrate
that SAdLSA provides a more general framework to learn protein structures for sequence annotation
purposes.

87 2   Methods

88 For this study, we mainly employ SAdLSA, a deep-learning (DL) based approach for protein sequence
89 alignment. The details of SAdLSA and the benchmark results have been described in detail elsewhere
90 (23). Here, we briefly recapitulate its key features.

91 2.1   SAdLSA

An overview of SAdLSA is presented in Figure 1. The inputs to this network are two position-specific
sequence profiles, each of dimension $N_k \times 20$, where N_k is the length of the k-th sequence ($k = 1, 2$),
and the 20 columns represent the 20 different amino acids at each residue position (hence position-
specific). Here, we use the profiles generated from HHblits (25). In machine-learning language, the
sequence profiles are also known as embeddings. The outer product of these two 1D sequence features
yields a 2D matrix of features, where at position (i,j) of the matrix the elements are a concatenation of
the 20 columns formed from the i-th residue of sequence 1 and the j-th residue of sequence 2.
Subsequently, these 2D features are fed into a fully convolutional neural network consisting of up to
34 residual blocks. The main objective of this neural network model is to predict residue-residue
distances between the two input sequences that recapitulates their optimal structural alignment, using
observed structural alignments as the training ground truth. The training distance labels are created
from structural alignments by APoc (21), which takes advantage of a global alignment provide by TM-
align (26).

Figure 1. Flowchart of SAdLSA, a deep-learning algorithm for protein sequence alignment. In this study, the
same sequence input is supplied to the SAdLSA pipeline, resulting in an intra-sequence C_α-C_α distogram
prediction of a single protein, instead of a typical application scenario, whereby the inter-sequence distogram
portraying the superimposition of two different proteins is predicted and utilized for deriving their sequence
alignment using dynamic programming.

The neural network is composed of multiple residual blocks, either conventional (27) or dilated (28)
in slightly different design variants. The residual block design is a key to train a deep neural network
model. Within a residual block, each convolutional layer is composed of about 64 filters with a kernel

size of 3×3 or 5×5. After the residual blocks, the last 2D convolutional layer outputs 22 channels,
representing 21 distance bins (1 to 20 at 1 Å each, and >20 Å) and channel 0 which is reserved for
ignored pairs (e.g., gap residues missing in a structure, or large distances >30 Å). Finally, a softmax
layer calculates the probability scores for each distance bin. Here, the same network was also applied
to the same two input. The mean probability scores of these two runs are the final output score for this
DL model. This ensures that the alignment is identical if one swapped the position of two input
sequences. For this study, we used the consensus scores from six DL models, including three models
with 14 residual blocks and 64 5×5 kernels in each convolutional layer, and three dilated model with
34 residual blocks (alternating 1,2,8,16,32 dilate rates) and 50 to 75 3×3 kernels. The two type of DL
models have 2.9 and 2.4 million parameters, respectively.

The outputs from a DL model are the probabilities of distance bins forming an inter-protein residue-
residue distance matrix. To build an alignment using dynamic programming (DP), we convert this
probability matrix into a mean distance matrix D, whose element

127
$$d_{ij} = \sum_{k=1}^{n} p_{ij}^{k} b_k - c \qquad \text{(Eq. 1)}$$

where i, j are target/template sequence positions, p_{ij}^{k} is the probability for bin k at position (i, j), b_k are
distance labels from the sequence (1, 2, ... 20, 22). D is subsequently adapted as the scoring matrix to
obtain the optimal alignment using a Smith-Waterman-like DP algorithm (29). The distance matrix D
is also used to calculate an estimated TM-score (30, 31) for ranking the significance of an alignment.
The constant c is set at 1 such that a perfect alignment gives an estimated TM-score of 1.

Since we study the self-alignment of a given sequence, we feed exactly the same sequence profiles into
SAdLSA, and the resulting sequence alignment itself is universally at 100% identity, with a predicted
TM-score ~1. We focus on the residue-residue distance matrix D, which is converted from a general
inter-sequence scenario into a special intra-sequence scenario, because the two input sequences are the
same.

2.2   Data sets

We employed the same test and training sets from the original SAdLSA study (23). Both sets are
curated from the SCOP database (32). The training set is composed of 79,000 pairs from a SCOP30
set of ~5000 domains. These training protein domain sequences share less than 30% identity. The test
set is an extrinsic test set of the sequences of 593 randomly selected protein domains from 391 SCOP
folds. Homologs of the testing sequences at 30% sequence identity or higher, or with a BLAST E-value
< 0.1, are excluded from the training set. In this study, we employed SAdLSA models trained on this
training set and conducted SAdLSA self-alignments on each of the 593 test sequences.

2.3   Analysis

2.3.1 Distogram assessment

It has been well-established that residue-residue contacts characterize a protein structural fold (2, 4).
The most common definition of a protein contact is based on the distance between C_α or C_β atoms.
That is, a contact between a pair of protein residues i and j is defined if the Euclidean distance between
their C_α (or C_β) atoms is less than a cutoff value, typically at 8 Å. A popular contact metric adopted by
the CASP assessors (33) is the precision of the top L/k C_β–C_β contact predictions within short, medium
or long ranges, where L is the length of the target and $k = 1, 2,$ and 5, and the sequential distance s_{ij} of
residues i and j, $s_{ij} \equiv |i - j|$, defines the range: *short* ($s_{ij} \in [6, 11]$), *medium* ($s_{ij} \in [12, 23]$), and *long*

($s_{ij} \in [24, \infty)$), i.e., nonlocal residue pairs. Since SAdLSA was trained on the distances between C_α
atoms, we use C_α–C_α contacts with an 8 Å cutoff as our definition of protein inter-residue contacts and
consider only those belonging in either the medium- or long-range regime, i.e., $s_{ij} \in [12, \infty)$. The
predictions are ranked by the probability of forming a C_α–C_α contact. To obtain the probability, one
simply sums the probabilities for distance bins from 0 to 8 Å, since the SAdLSA DL models output a
probability matrix D for 21 distance bins. This probability score is then employed for the precision
analysis as outlined above. The precision is defined as TP/(TP+FP), where TP is the number of true
positives, i.e., native contact observed in an experimental structure, and FP is the number of false
positives within the top L/k contact predictions evaluated.

In addition, we introduce the Mean Absolute Error (MAE) of the predicted distogram versus the ground
truth distogram. Specifically, we calculate the MAE using the coordinates of the C_α atoms of nonlocal
residue pairs, i.e., the sequential distance of residue pairs is no less than 6. The overall MAE for a
distogram is defined as

168
$$d_{MAE} = \sum_{i,j} |d_{ij}^{pre} - d_{ij}^{nat}| / M \qquad \text{(Eq. 2)}$$

where (i,j) are the indexes of a pair of nonlocal residues separated up to 20 Å in the native distogram,
M the total of such pairs, d_{ij}^{pre} the predicted distance by the SAdLSA self-alignment, and d_{ij}^{nat} the
distance observed in the native distogram. Additionally, for each target, we also obtain the MAE values
within each distance bin from 4 to 20 Å. If a target does not have any nonlocal residue pair within a
specific 1Å bin, the MAE calculation is skipped for this bin.

In order to estimate the statistical significance of d_{MAE}, we consider its expected value using a
background distribution based on the pairwise residue distances observed in the training distograms.
For each distance bin, we count the residue pairs within this bin as observed in the training ground
truth distograms, and then obtain the observed frequency f^k for this distance bin by dividing the count
against all counts of all bins from 1 to 21 (inter-residue distances between 20 to 30 Å are used for bin
21 as they are what collected for training). Substituting f^k for p_{ij}^k in Eq. 1, we obtain the expected
value of d_{ij}, d_{ij}^{exp}=15.5 Å for any (i,j) according to this reference distribution. Note that our training
ground truth distograms are of inter-sequence residues, in comparison to the distograms of intra-
sequence residues from the self-alignment. But, since the inter-sequence distograms are actually
employed for SAdLSA training, it is appropriate to use the distance distribution collected from these
distograms as the reference background. This leads to a naïve way to calculate the expect d_{MAE},
$d_{MAE}^{exp} = \sum_{i,j} |d_{ij}^{exp} - d_{ij}^{nat}| / M$, yielding a mean d_{MAE}^{exp} of 3.07 Å and a standard deviation of 0.20 Å by
applying the formula to 4,661 structures employed in the training set. Likewise, for comparison the
same formula is applied to the test set, including the overall error and errors for individual distance
bins. Using the one-tailed test for a normal distribution, one can calculate the p-value of an d_{MAE} value
using the background distribution derived from the training set.

2.3.2 t-SNE analysis

We performed t-distributed Stochastic Neighbor Embedding (t-SNE) (34) to analyze the factors that
contribute to the precision of contact predictions by SAdLSA self-alignment. This is a nonlinear
dimensionality reduction tool more suitable for this analysis than a classical principal component
analysis. Five features were used for this analysis including (i) the best training pair for each target
measured by their TM-score (33), (ii) the ratio of the total observed native contacts (combining both
medium- and long-range contacts, i.e., $s_{ij} \in [12, \infty)$) over the sequence length, whether the best training

pair belongs to (iii) the same fold or just the (iv) superfamily as the target according to the SCOP
classification, and (v) the sequence diversity of the multiple sequence alignment of the target. The TM-
score is a protein length-independent metric ranging from 0 to 1, and a TM-score > 0.4 indicates a
statistically significant alignment (26). We use (0,1) to represent the logical variables (e.g., is it a
member of the same SCOP fold or not). The sequence diversity is calculated with the Multiple
Sequence Alignment (MSA) of the target and defined as $ln(N_{eff}/\sqrt{L})$ taken from (23), where N_{eff} is
the number of effective sequences in the MSA without length normalization. In our t-SNE analysis,
we employed the default parameters including the perplexity parameter set at 30.

2.4   DESTINI2

For comparison purposes, we employed DESTINI2 to conduct inter-residue distance prediction on the
same test data set, i.e., 593 SCOP domain sequences, used to benchmark SAdLSA. DESTINI2
improves DESTINI by using a deeper, dilated convolutional residual network model. In this study, we
used 39 dilated residual blocks similar to the one implemented in SAdLSA. For training, about 10000
crystal structures with < 2.5 Å resolution were taken from a March 2020 release of PISCES (35), which
were curated from the PDB database (36). For a fair comparison, we retrained DESTINI2 models by
removing the test set entries and their close homologs from the original DESTINI2 training set using
the same criteria as that used for the SAdLSA test.

3   Results

We conducted self-alignments for 593 target sequences with SAdLSA, using deep-learning models
trained without obvious homologs to any of the 593 target sequences (see Methods). As one would
expect, SAdLSA returns a sequence alignment at 100% identity and a predicted TM-score close to 1.
This seems trivial. But, if one carefully inspects the residue-residue distogram prediction, it not only
contains information giving rise the identical alignment, but also contains inter-residue distance
information to structurally characterize the fold encoded by the sequence itself.

3.1   SAdLSA self-alignment generates a fold-depicting distogram.

Figure 2 illustrates an example of a SAdLSA self-alignment prediction. This 205 AA target sequence
encodes a classic Rossman fold, which is composed of an βαβ alternating secondary structural
segments found in many nucleotide-binding proteins (37). The characteristics of this fold are displayed
in the distance plot calculated between the C_α atoms determined in the crystal structure (Figure 2, top
left panel). The remaining residue-residue distance plots are generated by the SAdLSA self-alignment
of the same sequence. These are from the 21 scoring channels designed to predict the probability of
each pair of C_α atoms falling into each distance bin from 0 to beyond 20 Å. The first three channels are
straight diagonal lines, which give rise the 100% identity in the sequence alignment and are not the
focus of this study. Starting from plots ≥ 4 Å, one recognizes inter-residue distance relationships. First,
the immediate neighboring residues are shown between 3−4 Å. Then, the main secondary structure
elements including the fold's six α-helices and seven β-strands exhibit their patterns in the 4−5 and
5−6 Å plots. The packing between these secondary structural elements becomes clear in the subsequent
three plots from 6−9 Å. The detailed packing orientations among secondary structural elements are
further delineated in the remaining distance plots up to 20 Å. Finally, the highlights in the >20 Å plot
signal the regions that are distant from each other. The top L medium- or long-range contact predictions
for this case have a precision of 86%, which is sufficient to reconstruct a high-resolution structural
model whose TM-score > 0.7 (2). The mean absolute error d_{MAE}, calculated from the $C_\alpha−C_\alpha$ distances
of all nonlocal residue pairs separated up to 20 Å, is only 1.57 Å from the native distogram.

Fold-sensing sequence comparisons

Figure 2. An example of predicting residue-residue distance matrices by SAdLSA self-alignment. The
native (experimental) structure (PBD ID: 1hdo, chain A; SCOP ID: d1hdoa_) of the target sequence,
human Biliverdin IXβ reductase, encodes a classic Rossman fold shown in the cartoon representation
using the red-green-blue color scheme from the N- to C-terminus. For each pair of residues, its
experimentally observed (native) C_α-C_α distance is shown in the upper left corner. The remaining 21
probability density plots are generated by SAdLSA self-alignment for the target sequence. Each plot
predicts the probability of C_α-C_α distance within a distance bin from 0 to 20 Å at 1 Å spacing, and the
probability > 20 Å in the last plot.

How accurate is the SAdLSA self-alignment for predicting residue-residue distances in general? If one
examines the d_{MAE}, the overall number looks good with a mean of 2.43 Å, and 92.7% of targets are
below 3 Å (Figure 3 insert). By comparison, if one naively assigns distance distribution according to
the observed fractions from the training set (see Methods), one obtains a mean expected error, d_{MAE}^{exp},
at 3.08 Å. Overall, 96.6% of targets have a smaller distance prediction error by SAdLSA than the value
from the naïve reference approach. Moreover, about 408 (69%) targets have a significant d_{MAE} below
the p-value cutoff of 0.05. Figure 3 further details the distributions of MAE between the SAdLSA
predicted and the corresponding native distograms for individual distance bins from 4 to 20 Å. It is
clear that residues forming direct contacts within the first five bins are most challenging to predict and
exhibit large variations, with the mean MAE gradually decreasing from 6.6 Å in the 3−4 Å bin to 3.4

Figure 3. Mean absolute error of predicted distogram *vs* native distogram for 593 test cases. The main plot displays the distribution of MAE values within each C_α-C_α distance bin from 4 to 20 Å for nonlocal residue pairs. Each bin has a spacing of 1 Å and each blue point represents a target protein. Violin contours are proportional to the counts of targets at different MAE levels with a bin width of 0.025. Black boxes and bars represent the 2nd and 3rd quartiles (25% to 75% ranked by MAE values) and the median of the distributions. The red stars represent the mean values. For comparison, the expected MAE distributions are shown in orange error bars, which are centered at the mean and extended to ± sd. The insert shows the histograms of the d_{MAE} values in two separate assessments, calculated (purple) from the SAdLSA self-alignment and expected (teal) from the background distribution. For each target, its d_{MAE} value is calculated from all nonlocal residue pairs up to 20 Å as observed in the native distogram.

Å in the 8−9 Å bin. But these distance predictions by SAdLSA are actually highly significant in comparison to the expected values whose MAE errors are up to 8 Å higher on average than SAdLSA predictions. On the other hand, the large distance bins from 14 to 18 Å yield relatively small MAE values < 2.5 Å, but it is not surprising as the expected MAE is below 2 Å.

Fold-sensing sequence comparisons

Figure 4. Precision of inter-residue contact predictions via SAdLSA self-alignment. The precision of the top *L* (light green), *L*/2 (green), and *L*/5 (gold) are shown as circles for each target sequence. Violin contours are proportional to the counts of targets at different precision levels with a bin width of 0.01. Black boxes, median bars and means are represented following the same plotting scheme as in Figure 3.

264   **Table 1.** Mean precision of Medium/Long-range inter-residue contacts for 593 targets.

Method	Medium/Long-range Contacts[*]		
	L	*L/2*	*L/5*
SAdLSA ($C_\alpha - C_\alpha$)	0.403	0.526	0.637
DESTINI2 ($C_\alpha - C_\alpha$)	0.645	0.777	0.858
DESTINI2 ($C_\beta - C_\beta$)	0.678	0.803	0.879

* Medium/Long-range Contacts denote residue-residue contacts whose sequential distance are in
either the medium or long-range regime. Contact predictions are converted from the distogram
predicted by each method. All deep-learning models were re-trained to exclude the test set and their
close homologs from the original training sets (see Methods).

From a structural perspective, direct inter-residue contacts are the most important. Moreover, one only
needs to predict a fraction of the total number of contacts in order to obtain a correct fold prediction
(4). We therefore turn our focus to inter-residue contacts. According to the benchmark results on 593
protein sequences, the mean precisions are 40.3%, 52.6% and 63.7% for the top *L*, *L*/2, *L*/5 predictions
of medium- or long-range inter-residue C_α contacts, respectively (Table 1). The detailed distributions

of individual predictions are shown in violin plots (Figure 4). For instance, in the middle top $L/2$ plot,
about half of the sequences have a precision value > 50%, which is sufficient to derive the correct fold
for a single-domain using these predictions (4). At $L/5$, 107 (18%) entries have 100% precision, and
the median precision is at 69%. These numbers are not as good as the deep-learning approaches
specifically trained to predict residue distograms, e.g., they are about 25% worse than DESTINI2
(Table 1). Given the fact that SAdLSA was not trained to predict residue distances for a single structure
(see more reasoning in Discussions), but rather to recognize the similarity between pairs of structures,
these results are encouraging and clearly demonstrate the generality of the SAdLSA framework for
learning protein structures.

3.2   What contributes to successful distogram prediction by SAdLSA self-alignment?

Next, we seek to understand the factors that affect the accuracy of distogram predictions by SAdLSA
self-alignment. Like all machine-learning algorithms, the capability of distogram predictions must
come from the training data of SAdLSA. Although SAdLSA was not trained to learn individual protein
folds, we hypothesize that the fold-depicting distogram provided in the SAdLSA self-alignment comes
from learning the training pairs sharing fold similarity as the target sequence. During SAdLSA training,
it mainly focuses on aligned residues across two different sequences, but the network also observes the
relative positions among aligned residues. As a result, SAdLSA learns the folding code of individual
protein sequences, provided that they exhibit significant fold similarity. The more similar in their
structures, ideally the same fold as the training pair, the more likely the distogram pattern is learned
for this specific fold.

3.2.1 Presence of the same fold as a target in the training set is important.

To explore the validity of this hypothesis, for a target structure and a pair of training structures, we introduce T, defined as the minimal TM-score of the two training structures with respect to the target structure, using the target to normalize the TM-score. For each target, we find the highest T, denoted as $T*$, among all pairs in the training set. Figure 5 shows the correlations between $T*$ and the precision for the top $L/2$ residue-residue contact predictions. The violin plots demonstrate a clear upward trend in precision from the low $T*$ regime to high $T*$ regime. When there is a lack of obvious training structures that are similar to the target, e.g., when $T*$ < 0.4, the median precision is only at 39%. The same metric increases to 52% if $T* \in$ [0.5, 0.6), and dramatically to 82% if $T* >$ 0.7. The Pearson correlation coefficient between $T*$ and the precision of all targets is 0.34, which clearly shows the dependency of precision on $T*$, despite the indication that other factors are also in play.

Figure 5. Precision of inter-residue contact prediction *vs $T*$,* the highest TM-score to all structures in the pairs found in the training set. The violin and box plots follow the same scheme as in Figure 3.

For example, Figure 5 shows that there are still very good distogram predictions in the low T^* regime.
How could SAdLSA accurately predict a distogram when there is no similar training structure? There
are 11 target sequences with $L/2$ precision > 60% within $T^* < 0.4$. If one examines these structures,
some of them are composed of multiple domains or subdomain structures. For example, one target,
with SCOP ID d3u7qb, is a 522 AA sequence composed of three Rossman folds and two helical bundle
domains, despite the fact that SCOP defines it as a single domain. Although there is no other structure
in the training set that resembles the overall structure of this target, the folds of its individual domains
can be learned separately. As shown above, the Rossman fold is relatively easy to learn (Figure 2). As
a result, the overall precision prediction is 76% and the d_{MAE} is 2.44 Å (p-value = 8.0×10^{-4}) for this
query sequence. More interesting examples are analyzed below.

3.2.2 Evolutionary relationships facilitate fold-learning.

What are the other possible contributing factors? In addition to T^*, we further consider four other
features including the ratio of total observed native contacts (within either the medium- or long-range
regime) over the sequence length, whether the T^* training pair belong to the same fold or superfamily
according to the SCOP classification, and the sequence diversity of the multiple sequence alignment
of the target. The Pearson correlation coefficient between each of these four additional features and the
contact precision is 0.55, 0.30, 0.33, and 0.33, respectively. Figure 6 shows the results from t-SNE
analysis of these five features. Three big clusters emerge and represent targets whose T^* training pair
are from the same SCOP superfamily (240 entries), the same SCOP fold but not the same superfamily
(40 entries), and different SCOP fold (313 entries). They exhibit different levels of difficulty for contact

Figure 6. T-SNE analysis of factors affect the precision of inter-residue distance predictions. Each point in the plot represents one of 593 target sequence, color-coded according to its precision value of the top $L/2$ Cα-Cα contact prediction for those belonging in the medium- or long-range regime. The template pairs structurally most close to the target sequence found in the training set are classified according to their SCOP fold and Superfamily assignments. The brackets < · > denote the mean among all targets within the same cluster circled by dashed lines.

prediction, at mean precision values of 64%, 60%, and 43%, respectively. This result makes sense as
the sequence profiles from the same superfamily are similar and relatively easy to learn for a neural
network model, whereas sequence profiles from remote families or those without an apparent
evolutionary relationship are much harder to learn. In the same superfamily cluster, there are very few
"bad" predictions, e.g., 41 (17%) targets at $L/2$ have a precision $< 30\%$. One explanation is the
structural variation between the target and the training structures, despite the fact that they are from the
same superfamily. On the other hand, even for cases where the evolutionary relationship might not be
clear, it is still possible to predict a fold-depicting distogram reasonably well with SAdLSA, as is
evident in the clusters where the SCOP superfamilies are different. In particular, we note that SAdLSA
performs very well for a target structural fold if there are training structures originated from the same
SCOP fold but not necessarily the same SCOP superfamilies, as is evident in the mean precision of
60% among 40 such entries, close to the value of 64% in the cluster representing the same superfamily.

Moreover, the sequence diversity correlates positively with the contact precision at a correlation
coefficient of 0.33. There are 53 cases with $T^* < 0.4$, i.e., when there is a lack of similar fold in the
training set for these targets. Among them, those with high diversity, e.g., 28 targets with $N_{eff} > 1,000$,
have an average $L/2$ contact precision of 47% versus 30% for 25 cases with smaller sequence diversity.
Likewise, for cases when similar folds are present in the training set, e.g., $T^* > 0.6$, but the N_{eff} is low
< 100, the mean contact precision is at 42%, much lower than 64%, which the mean value for cases at
the same $T^* > 0.6$ criterion but with higher sequence diversity.

3.2.3 Delineation of protein folds via deep-learning across SCOP folds.

Notably, even when the best training structures are from a different SCOP fold, there are still many
highly accurate distogram predictions as exhibited in Figure 6. Indeed, there are 102 (33%) such cases
in the different fold cluster with precision $> 60\%$ among top $L/2$ predictions. Three representative
examples are displayed in Figure 7. One main reason for this observation is that they may still have
reasonably close or even a highly similar fold present in the training set, despite the different SCOP
classifications. For 102 targets, 91/62% of them have $T^* > 0.4/0.5$, respectively. Figure 7A illustrates
one such case, which is the C-terminal domain from pyruvate kinase of *Leishmania mexicana* (38).
Even though there is no structure belonging to the same SCOP fold as the target, there are 12239/498/10
training structures with TM-score $> 0.4/0.5/0.6$ to the target structure, and the precision for contact
prediction is at 98% with d_{MAE} of 1.68 Å (p-value $= 2.5 \times 10^{-12}$) from the native distogram. A second
example is delineated in Figure 7B for a domain from *Bacillus subtilis* Q45498 with unknown function.
It has a T^* value of 0.47, among 151 training structures in the TM-score regime 0.4 to 0.5 but none
higher. SAdLSA self-alignment makes a good prediction at 85% and d_{MAE} of 2.29 Å (p-value $= 5.1 \times 10^{-5}$).
For these examples, it is reasonable to conceive that SAdLSA learns to predict this fold at high
precision values through the training on the comparison of these structures.

In addition, there are 127 targets that do not share the same SCOP fold with any member in the training
set. Yet, for 32/41 cases, SAdLSA can predict residue-residue contacts at $> 50/60\%$ precision. One
such example is shown in Figure 7C. The target sequence is the hemophore HasA from *Yersinia pestis*
(39). The distogram prediction via SAdLSA alignment is at 67% with a d_{MAE} of 2.88 Å (p-value $=$
0.17). While the results are not as good as the above two cases, one can still find correct predictions
between the main secondary structure elements. Here, the long-range interactions by SAdLSA are
fuzzy and imprecise. Nevertheless, the result is remarkable giving that no training structure shares a

Figure 7. Examples of distogram predictions by SAdLSA self-alignment in comparison to native protein structures. Each panel is one example taken from targets whose fellow SCOP fold members (if any) were *not* present in the training set. The same scheme as Figure 2 was adopted to display the native structure and its distogram. Black lines in the native distograms belong to gap or non-standard amino acids in a crystal structure. The predicted distogram was calculated using the mean residue-residue distance matrix D formulated in the Methods. The precision values are for the medium/long-range residue contacts within top $L/2$ predictions. The value of d_{MAE} is obtained with Eq. 2.low overall structure similarity but high similarity to some individual domains, subdomains or fragments, like the example in 3.2.1, but here it is more general and subtle without a clear definition of the domain.

TM-score > 0.4, and its T^* is at 0.38. In these cases, SAdLSA likely learns the packing pattern for the

subdomains or fragments of a target sequence from its training structures, which may share relatively
low overall structure similarity but high similarity to some individual domains, subdomains or
fragments, like the example in 3.2.1, but here it is more general and subtle without a clear definition of
the domain.

Lastly, one technical reason why some targets have low precision is due to the definition of this metric,
which penalizes the case where very few medium or long-range contacts are present in the observed
native structure, e.g., coiled-coil structures. With relatively few or even no true positives in extreme
cases, the L/n normalization will bring down the precision value. In fact, the ratio of native contacts
over the length of the sequence has the strongest correlation (0.55) with the contact precision among
all five features considered. There are 22 cases whose ratio < 0.25 between the number of native
medium/long-range contacts and the length of protein. Their mean precision at $L/2$ is only 9%.
However, 15 of 22 have a significant $d_{MAE} < 2.68$ Å (p-value < 0.05). Moreover, due to the lack of
long-range contacts, such structures (e.g., #contacts/$L < 0.5$) are likely more flexible than compact
folds, and therefore, are challenging for structure accurate prediction. In the same superfamily/different
fold cluster, there are 12/49 cases forming the reddish subclusters at the edge in Figure 6. Of these 62
cases in total, 18 have a $d_{MAE} \geq 2.68$ Å. Thus, the reason for a few of these poor predictions might
reflect the intrinsic propensity towards disorder for some proteins.

4   Discussions

What structural information does one wish to obtain from a machine-learning algorithm, given an input
protein sequence? Very recently, numerous approaches have employed deep-learning techniques to
predict tertiary protein structure, notably through an inter-residue distogram (2). One may argue that a
more general machine-learning approach should go beyond the prediction of the tertiary structure for
a single sequence to predict structural relationships between multiple protein structures, which may
lead to a deeper understanding of their sequence or functional relationships. For this purpose, we
introduced SAdLSA, which predicts protein sequence alignments by learning their structural alignment
via deep-learning (23). In this contribution via a self-alignment analysis, we extended the previous
study and explicitly demonstrate that SAdLSA learns the protein folding code. The key to
understanding the deep-learning folding code lies in the analysis of the distogram prediction. Indeed,
we obtain distogram predictions at surprisingly high accuracy for many folds, at a mean precision of
52% for the top $L/2$ contact predictions and a mean absolute error of 2.43 Å in inter-residue distogram
predictions. In terms of d_{MAE}, about 97% of predicted inter-residue distograms are better than expected
from a background prediction, and 74% are statistically significant. This explains the advantage of
SAdLSA over the classic approaches as up to a 100% improvement was observed in benchmark tests
(23).

How does SAdLSA obtain its fold-depicting capability? The most important contribution comes from
similar fold structures subjected to training. The algorithm was designed to pay attention to the
distances between aligned residues. When these two training structures share a similar fold, the
distogram of such fold can be learned, as evident in the correlation between the target and training
structures (Figure 5). Additionally, if a training sequence is evolutionarily related to a target sequence,
even remotely, it facilitates fold learning. More interestingly, SAdLSA can learn from training
structures that go beyond the SCOP fold, e.g., cases that share no similar SCOP fold or even no similar

overall fold whose TM-score > 0.4 in the training set. This seems surprising at first but may be partially
explained as follows: First, a target may have many structural analogs with high structural similarity
that escapes human manual classification. Second, the protein's structure may consist of multiple-
domains, subdomains, or smaller fragments whose packing pattern may be learned individually and
separately from many training structures. As with all machine-learning based algorithms, since the
prediction capability of SAdLSA comes from the training set, the key question is how general is the
resulting model? The success in this SAdLSA self-alignment benchmark that includes many
challenging cases is a good indication of its generality. But ultimately, it needs the validation in real-
world, large-scale applications, ideally at the proteome-level.

Despite this success, we note that the fold-prediction ability of SAdLSA self-alignment is not as
accurate as deep-learning algorithms specially designed to predict protein structures, e.g., DESTINI2.
There are two main reasons for this reduced performance. First, the training of SAdLSA is on the inter-
sequence, inter-residue distances between a pair of superimposed structures, rather than the intra-
sequence, inter-residue distances observed in a single structure. As such, SAdLSA self-alignment
performs well when a pair of structures sharing a highly similar fold are present in the training set. But
this requirement is not always true, especially as our training set is derived from ~5000 SCOP domains,
which is half the size of the training set for protein structure prediction, e.g., ~10000 structures for
DESTINI2's training. Only 41% of the testing targets have a close training pair at $T^* > 0.6$. Second,
the current version of SAdLSA uses sequence profiles as its only input features, whereas many more
features, especially the direct co-evolutionary signals that are essential for the success of DESTINI2
and the like, are not employed for a technical reason. Nevertheless, more recent deep-learning
algorithms, such as AlphaFold2, directly learn from the multiple sequence alignment with an
"attention" mechanism. Since the same multiple sequence alignment was used to derive the sequence
profile used by SAdLSA as in DESTINI2, in principle, one may design a next generation, SAdLSA-
like algorithm with a similar attention mechanism. It will not only predict protein tertiary structure via
self-alignments, but also compare structures encoded by two different sequences at high precision.
Such work is now underway.

5   Conflict of Interest

The authors declare that the research was conducted in the absence of any commercial or financial
relationships that could be construed as a potential conflict of interest.

6   Author Contributions

MG and JS contributed to the conception and design of the study. MG performed the research and data
analysis and wrote the first draft of the manuscript. All authors contributed to manuscript revision,
read, and approved the submitted version.

7   Funding

This work was supported in part by the Division of General Medical Sciences of the National Institute
Health (NIH R35GM118039) and the DOE Office of Science, Office of Biological and Environmental
Research (DOE DE-SC0021303). The research used resources supported by the Director's Discretion
Project at the Oak Ridge Leadership Computing Facility and by the Partnership for an Advanced
Computing Environment (PACE) at Georgia Tech.

8   Acknowledgments

We thank Bartosz Ilkowski for internal computing support and Jessica Forness for proof-reading the
manuscript.

1   Data Availability Statement

The datasets in this study can be found at http://pwp.gatech.edu/cssb/sadlsa/.

References

1.   Anfinsen C, Scheraga H. Experimental and theoretical aspects of protein folding. *Advances*
in protein chemistry. 29. Elsevier (1975). p. 205-300.

2.   Skolnick J, Gao M. The role of local versus nonlocal physicochemical restraints in
determining protein native structure. *Curr Opin Struct Biol* (2021) 68:1-8. doi:
10.1016/j.sbi.2020.10.008.

3.   Wang S, Sun S, Li Z, Zhang R, Xu J. Accurate De Novo Prediction of Protein Contact Map
by Ultra-Deep Learning Model. *PLOS Comput Biol* (2017) 13(1):e1005324.

4.   Gao M, Zhou H, Skolnick J. DESTINI: A deep-learning approach to contact-driven protein
structure prediction. *Scientific reports* (2019) 9(1):3514. Epub 2019/03/07. doi: 10.1038/s41598-019-
40314-1. PubMed PMID: 30837676; PubMed Central PMCID: PMC6401133.

5.   Xu J. Distance-based protein folding powered by deep learning. *Proc Natl Acad Sci U S A*
(2019) 116(34):16856-65. Epub 2019/08/11. doi: 10.1073/pnas.1821309116. PubMed PMID:
31399549; PubMed Central PMCID: PMCPMC6708335.

6.   Senior AW, Evans R, Jumper J, Kirkpatrick J, Sifre L, Green T, et al. Improved protein
structure prediction using potentials from deep learning. *Nature* (2020) 577(7792):706-10. doi:
10.1038/s41586-019-1923-7.

7.   Hou J, Wu T, Cao R, Cheng J. Protein tertiary structure modeling driven by deep learning and
contact distance prediction in CASP13. *Proteins: Structure, Function, and Bioinformatics* (2019)
87(12):1165-78.

8.   Zheng W, Li Y, Zhang C, Pearce R, Mortuza SM, Zhang Y. Deep-learning contact-map
guided protein structure prediction in CASP13. *Proteins* (2019) 87(12):1149-64. Epub 2019/08/01.
doi: 10.1002/prot.25792. PubMed PMID: 31365149; PubMed Central PMCID: PMCPMC6851476.

9.   Abriata LA, Tamò GE, Dal Peraro M. A further leap of improvement in tertiary structure
prediction in CASP13 prompts new routes for future assessments. *Proteins: Structure, Function, and*
Bioinformatics (2019) 87(12):1100-12. doi: 10.1002/prot.25787.

10.   Yang J, Anishchenko I, Park H, Peng Z, Ovchinnikov S, Baker D. Improved protein structure
prediction using predicted interresidue orientations. *Proceedings of the National Academy of*
Sciences (2020) 117(3):1496-503. doi: 10.1073/pnas.1914677117.

11.   https://predictioncenter.org/casp14/index.cgi.

12.   Soding J, Remmert M. Protein sequence comparison and fold recognition: progress and good-
practice benchmarking. *Curr Opin Struct Biol* (2011) 21(3):404-11. Epub 2011/04/05. doi:
10.1016/j.sbi.2011.03.005. PubMed PMID: 21458982.

13.   Chothia C, Lesk AM. The relation between the divergence of sequence and structure in
proteins. *EMBO J* (1986) 5(4):823-6. PubMed PMID: ISI:A1986A906400028.

14.   Murzin AG. How far divergent evolution goes in proteins. *Curr Opin Struct Biol* (1998)
8(3):380-7. Epub 1998/07/17. doi: 10.1016/s0959-440x(98)80073-0. PubMed PMID: 9666335.

15.   Skolnick J, Gao M, Zhou H. On the role of physics and evolution in dictating protein
structure and function. *Israel journal of chemistry* (2014) 54(8-9):1176-88. Epub 2014/12/09. doi:
10.1002/ijch.201400013. PubMed PMID: 25484448; PubMed Central PMCID: PMCPMC4255337.

16.   A. Hildebrand, M. Remmert , A. Biegert, Söding J. Fast and accurate automatic structure
prediction with HHpred. *Proteins* (2009) 77(Suppl 9):128-32.

17.   Zhou H, Zhou Y. SPARKS2 and SP³ servers in CASP6. *Proteins(Supplement CASP issue)*
(2005) suppl 7:152--6.

18.   Skolnick J, Kihara D, Zhang Y. Development and large scale benchmark testing of the
PROSPECTOR_3 threading algorithm. *Proteins: Struct Funct Bioinform* (2004) 56(3):502-18. doi:
10.1002/prot.20106. PubMed PMID: WOS:000222675200009.

19.   Jones DT. GenTHREADER: an efficient and reliable protein fold recognition method for
genomic sequences. *J Mol Biol* (1999) 287:797--815.

20.   Zhang Y. Progress and challenges in protein structure prediction. *Curr Opin Struct Biol*
(2008) 18(3):342-8. doi: 10.1016/j.sbi.2008.02.004.

21.   Gao M, Skolnick J. APoc: large-scale identification of similar protein pockets. *Bioinformatics*
(2013) 29(5):597-604. doi: 10.1093/bioinformatics/btt024. PubMed PMID: 23335017; PubMed
Central PMCID: PMC3582269.

22.   Gao M, Skolnick J. A Threading-Based Method for the Prediction of DNA-Binding Proteins
with Application to the Human Genome. *PLoS Comp Biol* (2009) 5(11):e1000567. doi: e1000567

10.1371/journal.pcbi.1000567. PubMed PMID: ISI:000274228500015.

23.   Gao M, Skolnick J. A novel sequence alignment algorithm based on deep learning of the
protein folding code. *Bioinformatics* (2020). doi: 10.1093/bioinformatics/btaa810.

24.   Soding J. Protein homology detection by HMM-HMM comparison. *Bioinformatics* (2005)
21(7):951-60. Epub 2004/11/09. doi: 10.1093/bioinformatics/bti125. PubMed PMID: 15531603.

25.   Remmert M, Biegert A, Hauser A, Soding J. HHblits: lightning-fast iterative protein sequence
searching by HMM-HMM alignment. *Nat Methods* (2011) 9(2):173-5. Epub 2011/12/27. doi:
10.1038/nmeth.1818. PubMed PMID: 22198341.

26.   Zhang Y, Skolnick J. TM-align: a protein structure alignment algorithm based on the TM-
score. *Nucleic Acids Res* (2005) 33(7):2302-9. doi: 10.1093/nar/gki524. PubMed PMID:
WOS:000228778700028.

27.   He K, Zhang X, Ren S, Sun J, editors. Deep residual learning for image recognition.
Proceedings of the IEEE conference on computer vision and pattern recognition; 2016.

28.   Yu F, Koltun V, Funkhouser T, editors. Dilated residual networks. *Proceedings of the IEEE*
conference on computer vision and pattern recognition; 2017.

29.   Smith TF, Waterman MS. Identification of common molecular subsequences. *J Mol Biol*
(1981) 147(1):195-7. Epub 1981/03/25. doi: 10.1016/0022-2836(81)90087-5. PubMed PMID:
7265238.

30.   Zhang Y, Skolnick J. Scoring function for automated assessment of protein structure template
quality. *Proteins: Struct Funct Bioinform* (2004) 57(4):702-10. doi: 10.1002/prot.20264. PubMed
PMID: ISI:000225351100007.

31.   Xu J, Zhang Y. How significant is a protein structure similarity with TM-score = 0.5?
Bioinformatics (2010) 26(7):889-95. doi: 10.1093/bioinformatics/btq066.

32.   Fox NK, Brenner SE, Chandonia J-M. SCOPe: Structural Classification of Proteins—
extended, integrating SCOP and ASTRAL data and classification of new structures. *Nucleic Acids*
Res (2014) 42(D1):D304-D9. doi: 10.1093/nar/gkt1240.

33.   Schaarschmidt J, Monastyrskyy B, Kryshtafovych A, Bonvin A. Assessment of contact
predictions in CASP12: Co-evolution and deep learning coming of age. *Proteins* (2018) 86 Suppl
1:51-66. Epub 2017/10/27. doi: 10.1002/prot.25407. PubMed PMID: 29071738; PubMed Central
PMCID: PMCPMC5820169.

34.   Van der Maaten L, Hinton G. Visualizing data using t-SNE. *Journal of machine learning*
research (2008) 9(11).

35.   Wang G, Dunbrack RL, Jr. PISCES: a protein sequence culling server. *Bioinformatics* (2003)
19(12):1589-91. Epub 2003/08/13. PubMed PMID: 12912846.

36.   Berman HM, Westbrook J, Feng Z, Gilliland G, Bhat TN, Weissig H, et al. The Protein Data
Bank. *Nucleic Acids Res* (2000) 28(1):235-42. PubMed PMID: WOS:000084896300069.

37.   Hanukoglu I. Proteopedia: Rossmann fold: A beta-alpha-beta fold at dinucleotide binding
sites. *Biochem Mol Biol Educ* (2015) 43(3):206-9. Epub 2015/02/24. doi: 10.1002/bmb.20849.
PubMed PMID: 25704928.

38.   Morgan HP, McNae IW, Nowicki MW, Hannaert V, Michels PAM, Fothergill-Gilmore LA,
et al. Allosteric mechanism of pyruvate kinase from Leishmania mexicana uses a rock and lock
model *J Biol Chem* (2010) 285(17):12892-8. doi: 10.1074/jbc.M109.079905.

39.   Kumar R, Lovell S, Matsumura H, Battaile KP, Moënne-Loccoz P, Rivera M. The
Hemophore HasA from Yersinia pestis (HasAyp) Coordinates Hemin with a Single Residue, Tyr75,
and with Minimal Conformational Change. *Biochemistry* (2013) 52(16):2705-7. doi:
10.1021/bi400280z.