UnMICST: Deep learning with real augmentation for robust segmentation of highly multiplexed images of human tissues

Clarence Yapp*[1, 2], Edward Novikov*[1,3], Won-Dong Jang[1,3], Tuulia Vallius[1,4], Yu-An Chen[1], Marcelo Cicconet[2], Zoltan Maliga[1], Connor A. Jacobson[1], Donglai Wei[3], Sandro Santagata[1, 4, 5], Hanspeter Pfister[3], and Peter K. Sorger[1, 4, 6]

*authors contributed equally

[1]Laboratory of Systems Pharmacology, Harvard Medical School, Boston, MA 02115

[2]Image and Data Analysis Core, Harvard Medical School, Boston, MA 02115

Human Tumor Atlas Network

[3]School of Engineering and Applied Sciences, Harvard University, Cambridge, MA, 02138

[4]Ludwig Center for Cancer Research at Harvard, Harvard Medical School, Boston, MA, 02115

[5]Department of Pathology, Brigham and Women's Hospital, Harvard Medical School, Boston, MA, 02115

[6]Department of Systems Biology, Harvard Medical School, Boston, MA, 02115

ORCID IDS

Clarence Yapp clarence@hms.harvard.edu 0000-0003-1144-5710

Edward Novikov edward_novikov@seas.harvard.edu 0000-0003-1476-5111

Won-Dong Jang wdjang@seas.harvard.edu 0000-0002-5205-1024

Tuulia Vallius tuulia_vallius@hms.harvard.edu 0000-0002-3006-4887

Yu-An Chen yu-an_chen@hms.harvard.edu 0000-0001-7228-4696

Marcelo Cicconet marcelo_cicconet@hms.harvard.edu 0000-0003-2649-1509

Zoltan Maliga zoltan_maliga@hms.harvard.edu 0000-0003-4209-7253

Connor A. Jacobson connor_jacobson@hms.harvard.edu 0000-0002-0299-3451

Donglai Wei donglai@seas.harvard.edu 0000-0002-2329-5484

Sandro Santagata ssantagata@bics.bwh.harvard.edu 0000-0002-7528-9668

Hanspeter Pfister pfister@seas.harvard.edu 0000-0002-3620-2582

Peter K. Sorger peter_sorger@hms.harvard.edu, 0000-0002-3364-1838

ABSTRACT

Newly developed technologies have made it feasible to routinely collect highly multiplexed (20-60 channel) images at subcellular resolution from human tissues for research and diagnostic purposes. Extracting single cell data from such images requires efficient and accurate image segmentation, a challenging problem that has recently benefited from the use of deep learning. In this paper, we demonstrate two approaches to improving tissue segmentation that are applicable to multiple deep learning frameworks. The first uses "real augmentations" that comprise defocused and saturated image data collected on the same instruments as the actual data; using real augmentation improves model accuracy to a significantly greater degree than computational augmentation (Gaussian blurring). The second involves imaging the nuclear envelope to better identify nuclear outlines. The two approaches cumulatively and substantially improve segmentation on a wide range of tissue types and provide a set of improved segmentation models. We speculate that the use of real augmentations may have applications in image processing outside of microscopy.

INTRODUCTION

Optical microscopy is a method of long-standing importance in biology that is changing rapidly due to the introduction of new methods for highly-multiplexed imaging of normal and diseased tissues (**Supplementary Table 1**)[1–5]. High-plex imaging (sometimes called spatial proteomics) yields subcellular resolution data on the abundance of 20-60 antigens, which is sufficient to identify cell types, measure cell states (quiescent, proliferating, dying, etc.) and interrogate cell signaling pathways. High plex imaging also reveals the morphologies and positions of acellular structures essential for tissue integrity in a preserved 3D environment. The resulting data are substantially more challenging to analyze computationally than images of cultured cells, the primary emphasis of biology-focused machine vision systems to date, but analysis of tissues and similarly complex specimens is benefiting from recent advances in machine learning (deep learning). The different cell types, basement membranes, and connective structures that organize tissues and tumors are present on length scales ranging from subcellular organelles to whole organs (<0.1 to >10^4 μm). Microscopy using Hematoxylin and Eosin (H&E) complemented by immunohistochemistry[6] has long played a primary role in the study of tissue architecture[7,8] and clinical histopathology remains the primary means by which diseases such as cancer are staged and managed clinically[9]. However, classical histology provides insufficient molecular information to precisely identify cell subtypes, study mechanisms of development, and characterize disease genes. This has motivated development of highly multiplexed (20-60 plex) imaging methods and spatial transcriptomics. These methods differ in resolution, field of view, and multiplicity (plex), but all generate 2D images of tissue sections; in current practice these are usually 5 – 10 μm thick.

Developing effective image processing algorithms for the resulting image data is now the primary

challenge for molecular profiling of tissues in both research and clinical settings.

When multiplexed images are segmented and quantified, the resulting single cell data are a

natural complement to single cell RNA Sequencing (scRNASeq) data, which have had a dramatic

impact on our understanding of normal and diseased cells and tissues[10,11]. Unlike dissociative

RNASeq, however, multiplex tissue imaging preserves morphology and spatial information. Single

cell analysis of imaging data requires segmentation, a computer vision technique that assigns class

labels to an image in a pixel-wise manner to subdivide it; this is followed by quantification of the

levels of protein markers on a per-cell or per-organelle basis. Marker quantification typically involves

integrating fluorescent signal intensities across a segmentation mask or a shape (usually an

annulus) that outlines or is centered in the mask[12]. Extensive work has gone into the development of

methods for segmenting metazoan cells grown in culture, but segmentation of tissue images is a

more difficult challenge due to cell crowding and the diverse morphologies of different cell types.

Recently, segmentation routines that use machine learning have become standard, paralleling the

widespread use of convolutional neural networks (CNNs) in image recognition, object detection, and

synthetic image generation[13]. Architectures such as ResNet, VGG16, and more recently, UNet and

Mask R-CNN[14,15] have gained widespread acceptance for their ability to learn millions of parameters

and generalize across datasets, as evidenced by excellent performance in a wide range of

segmentation competitions, as well as in hackathon challenges[16] using publicly available image

datasets[17,18]. However, to our knowledge, the relative strengths and weaknesses of different CNN

segmentation frameworks has not yet been evaluated directly on tissue images.

In both cultured cells and tissues, localizing nuclei is an optimal starting point for segmenting

cells since most cell types have one nucleus (cells undergoing mitosis, muscle and liver cells and

osteoclasts are important exceptions), and nuclear stains with high signal-to-background ratios are

widely available. The nucleus is generally quite large (5-10 µm) relative to the resolution of wide-

field fluorescence microscopes (~0.5 µm for a 0.9 numerical aperture – NA – objective lens), making

it easy to detect at multiple magnifications. Nuclei are also often found at the approximate center of

a cell. There are possible advantages to using additional markers during image acquisition; for

example Schüffler et al.[19] used multiplexed IMC data and watershed methods for multi-channel

segmentation. Methods based on random forests such as Ilastik and Weka[20,21] also exploit multiple

channels for class-wise pixel classification via an ensemble of decision trees to assign pixel-wise

class probabilities in an image. However, random forest models have significantly less capacity for

learning than CNNs, which is a substantial disadvantage. The possibility of using CNNs with multi-

channel data to enhance nuclei segmentation has not been widely explored.

The accuracy of segmentation algorithms is crucially dependent on the quality of the original

images. In practice, many images of human and murine tissues have focus artefacts (blur) and

images of some cells are saturated (with intensities above the linear range of the camera). This is

particularly true of whole-slide imaging in which up to 1,000 sequentially acquired image tiles are
used to create mosaic images of specimens as large as several square centimeters. Whole slide
imaging is a diagnostic necessity[22] and essential to achieve sufficient power for rigorous spatial
analysis [23]. However, many recent papers addressing the segmentation of tissue images restrict
their analysis to the clearest in-focus fields. This is logical because, in the setting of supervised
learning, it is easier to obtain training data and establish a ground-truth when images are clear and
inter-observer agreement is high. In practice however, all microscopy images of tissue specimens
have issues with focus: the depth of field of objective lenses capable of high resolution imaging
(high NA lenses) is typically less than the thickness of the specimen so that objects above and
below the plane of optimal focus are blurred. Images of human biopsy specimens are particularly
subject to blur and saturation artefacts because the tissue sections are not always uniformly co-
planar with the cover slip. Since most research on human tissues is incidental to diagnosis or
treatment, it is rarely possible to reject problematic specimens outright. Moreover, reimaging of
previously analyzed tissue sections is rarely possible due to tissue disintegration. Thus, image
segmentation with real-world data must compensate for common image aberrations.

The most common way to expand training data to account for image artefacts is via
augmentation[24] which involves pre-processing images via random rotation, shearing, flipping, etc.
This is designed to prevent algorithms from learning irrelevant aspects of an image, such as
orientation. To date, focus artifacts have been tackled using computed Gaussian blur to augment
training data[25–27]. However, Gaussian blur is only an approximation of the blurring inherent to any
optical imaging system having limited bandpass (that is – any real microscope) plus the effects of
refractive index mismatches and light scattering.

In this paper, we investigate ways to maximize the accuracy of image segmentation in
multiplexed tissue images containing common imaging artefacts. We generate a set of training and
test data with ground-truth annotations via human curation of multiple normal tissues and tumors,
and use these data to score segmentation accuracy achieved on three deep learning networks,
each of which was independently trained and evaluated: UNet, Mask R-CNN, and Pyramid Scene
Parsing Network (PSPNet). The resulting models comprise a family of *Universal Models for*
Identifying Cells and Segmenting Tissue (UnMICST) in which each model is based on the same
training data but a different class of ML network. Based on our analysis we identify two ways to
improve segmentation accuracy for all three networks. The first involves adding images of nuclear
envelope staining (NES) to images of nuclear chromatin acquired using DNA-intercalating dyes. The
second involves adding "real augmentations", defined here as intentionally defocused and over-
saturated images (collected from the same specimens), to the training data to make models more
robust to the types of artefacts encountered in real tissue images. We find that augmentation with
real data significantly outperforms conventional Gaussian blur augmentation, offering a statistically

significant improvement in model robustness. Across a range of tissue types, improvements from
adding NES data and real augmentations are cumulative.
146
RESULTS
Data sets and ground truth annotation of nuclear boundaries
One challenge in supervised machine learning on tissue images is a lack of sufficient freely-
available data with ground truth labelling. Experience with natural scene images[14] has shown that
the acquisition of labels can be time consuming and rate limiting[28]. It is also well established that
cells in different types of tissue have nuclear morphologies that vary substantially from the spherical
and ellipsoidal shape observed in cultured cells[31]. Nuclear pleomorphism (variation in nuclear size
and shape) is even used in histopathology to grade cancers[32]. To account for variation in nuclear
morphology we generated training, validation, and test datasets from seven different tissue and
tumor types (lung adenocarcinoma, non-neoplastic small intestine, normal prostate, colon
adenocarcinoma, glioblastoma, non-neoplastic ovary, and tonsil) found in 12 cores from EMIT
(Exemplar Microscopy Images of Tissue[33], RRID : SCR_021052), a tissue microarray assembled
from clinical discards. The tissues had cells with nuclear morphologies ranging from mixtures of
cells that were large vs. small, round cells vs. narrow, and densely and irregularly packed vs.
organized in clusters. A total of ~10,400 nuclei were labelled by a human expert for nuclear
contours, centers, and background. In addition, two human experts labelled a second dataset from a
whole-slide image of human melanoma[34] to establish the level of inter-observer agreement and to
provide a test data set that was disjoint from the training data.
165
Evaluating the performance of ML segmentation algorithms and models
We implemented and then evaluated two semantic and one instance segmentation
algorithms that are based on deep learning/CNNs (UNet, PSPNet, and Mask R-CNN, respectively).
Semantic segmentation is a coarse-grained ML approach that assigns objects to distinct trained
classes, while instance segmentation is fine grained and identifies individual instances of objects.
We trained each of these models (UnMICST-U, UnMICST-P, and UnMICST-M, respectively) on
manually curated and labelled data from seven distinct tissue types. The models were not
combined, but were tested independently in an attempt to determine which network exhibited the
best performance.
A variety of metrics have been proposed for evaluating pixel-level and instance-level
segmentation. An example of a pixel-level metric is the sweeping intersection over union (IoU)
threshold described by Caicedo et al.[16] and implemented in the widely used COCO dataset, which is
based on images of cell lines[30]. The IoU (the Jaccard Index) is calculated by measuring the overlap
between the ground truth annotation and the prediction via a ratio of the intersection to the union of
pixels in two masks. The greater the IoU, the higher the accuracy, with an ideal value of 1 (although

this is very rarely achieved). The (IoU) threshold is evaluated over a range of values from the least

stringent, 0.55, to most stringent, 0.8[16]. Unlike a standard pixel accuracy metric (the fraction of

pixels in an image that were correctly classified), IoU is not sensitive to class-imbalance. IoU is a

particularly relevant measure of segmentation performance for analysis of high-plex images. When

masks are used to quantify marker intensities in other channels, we are concerned not only with

whether a nucleus is present or not at a particular location but whether the masks are the correct

size and shape.

Examples of instance-level metrics are true positives (TP) and true negatives (TN), which

classify predicted objects based on whether they overlap by 50% or greater, otherwise they are

deemed as false positives (FP) and false negatives (FN). The frequencies of these four states are

used to calculate the F1-score and average precision (AP). The F1-score is the weighted average of

precision (true positives normalized to predictions) and recall (true positives normalized to ground

truth), and AP considers the number of true positives, total number of ground truth and predictions.

A common approach judging the accuracy expected for a supervised learning method is to

use multiple human experts to label the same set of data and determine the level of inter-observer

agreement (of course, it may ultimately be possible to exceed this level of human performance [24,29]).

We assessed inter-observer agreement using both the F1-score and sweeping IoU scores with data

from whole-side images of human melanoma[34]. For a set of ~4,900 independently annotated

nuclear boundaries, two experienced microscopists achieved a mean F1-score of 0.78

(**Supplementary Figure 1**) and an IoU of 60% at a threshold of 0.6. In the discussion we compare

these data to values obtained in other recently published papers and address the discrepancy in F1-

scores and IoU values.

Real augmentations increase model robustness to focus artefacts

To study the impact of real and computed augmentations on the performance of

segmentation methods, we trained models with different sets of data involving both real and

computed augmentations and then tested the data on images that were acquired in focus, out of

focus or blurred using a Gaussian kernel. Where dataset sizes were unbalanced, we supplemented

such instances with rotation augmentations. We assessed segmentation accuracy quantitatively

based on IoU and qualitatively by visual inspection of predicted masks overlaid on image data. Real

augmentation involved adding additional empirical, rather than computed, training data having the

types of imperfections most commonly encountered in tissue. This was accomplished by positioning

the focal plane 3 µm above and below the specimen, resulting in de-focused images. A second set

of images was collected at long exposure times, thereby saturating 70-80% of pixels. Because

blurred and saturated images were collected sequentially without changing stage positions, it was

possible to use the same set of ground truth annotations. For computed augmentations, we

convolved a Gaussian kernel with the in-focus images using a range of standard deviations chosen

to cover a broad spectrum of experimental cases (**Figure 1a**). In both scenarios, the resulting

models were evaluated on a test set prepared in the same way as the training set.

In an initial set of studies, we found that models created using training data augmented with

Gaussian blur performed well on Gaussian blurred test data. However, when evaluated against test

data involving defocused and saturated images, we found that Gaussian blur augmentation

improved accuracy only slightly relative to baseline models lacking augmentations (**Figure 1b**). In

contrast, the use of training data supplemented with real augmentations increased the fraction of

cells retained at an IoU threshold of 0.6 by 40-60%. Statistically significant improvement was

observed up to an IoU cutoff of 0.8 with all three learning frameworks (UnMICST-U, UnMICST-M,

and UnMICST-P models). To perform a balanced comparison, we created two sets of training data

having equal numbers of images. The first set contained the original data plus computed 90- and

180-degree rotations, and the second set contained original data plus defocused data collected from

above and below the specimen. Again, we found that models trained with real augmentations

substantially outperformed rotationally augmented models when tested on defocused test data

(**Figure. 1c**). Thus, training any of the three different deep learning architectures with real

augmentation generated models that outperformed models with computed augmentation using test

data that contained commonly encountered artefacts.

Addition of NES improves segmentation accuracy

When we stained our TMA panel (the Exemplar Microscopy Images of Tissues and Tumors

(EMIT) TMA) we found that antibodies against lamin A and C (**Figure 2a)** (which are different splice

forms of *LMNA* gene) stained approximately only half as many nuclei as antibodies against lamin B1

(**Figure 2b**) or lamin B2 (**Figure 2c**) (products of the *LMNB1* and *LMNB2* genes). Staining for the

lamin B receptor (**Figure 2e**) exhibited poor image contrast. A pan-tissue survey showed that a

mixture of antibodies for nucleoporin NUP98 and lamin B2 conjugated to the same fluorophore

(Alexafluor-647) generated nuclear envelope staining (NES) for nearly all nuclei across multiple

tissues (**Figure 2f-h**). We judged this to be the optimal antibody cocktail. However, only some cell

types, epithelia in colorectal adenocarcinoma for example, exhibited the ring-like structure that is

characteristic of nuclear lamina in cultured epithelial cells. The nuclear envelope in immune and

other cells has folds and invaginations[35] and in our data, NES staining could be irregular and

diffuse, further emphasizing the difficulty of finding a broadly useful NES stain in tissue.

The value of NES images for model performance was assessed quantitatively and

qualitatively. In images of colon adenocarcinoma, non-neoplastic small intestine, and tonsil tissue,

we found that the addition of NES images resulted in significant improvements in segmentation

accuracy based on IoU with all three learning frameworks; improvements in other tissues, such as

lung adenocarcinoma, were more modest and sporadic (**Figure 3a,** Lung). For nuclear

segmentation of fibroblasts in prostate cancer tissue, UnMICST-U and UnMICST-M models with

NES data were no better than models trained on DNA staining alone. Most striking were cases in
which NES data slightly decreased performance (UnMICST-P segmentation on prostrate fibroblasts
and UnMICST-U segmentation of glioblastoma). Inspection of the UnMICST-P masks suggested
that the segmentation of well-separated fibroblast nuclei was already optimal with DNA images
alone (~60% of nuclei retained at IoU of 0.6), implying that the addition of NES images afforded little
improvement. With UnMICST-U masks in glioblastoma, the problem appeared to involve atypical
NES morphology, which is consistent with a high level of nuclear pleomorphism and the presence of
"giant cells," both of which are well-established features of high-grade glioblastoma[36,37]. We also
note that NES data alone was inferior to DNA staining as a sole source of training data and should
therefore be used in combination with images of DNA (**Supplementary Figure 2**). Thus, adding
NES to training data broadly but not universally improves segmentation accuracy.
266
Combining NES images and real augmentation has a cumulative effect
To determine whether real augmentation and NES would combine during model training to
achieve superior segmentation precision relative to the use of either type of data alone, we trained
and tested models under four different scenarios (using all three learning frameworks; **Figure 4**).
We used images from the small intestine, a tissue containing nuclei having a wide variety of
morphologies, and then extended the analysis to other tissue types (see below). Models were
evaluated on defocused DNA test data to increase the sensitivity of the experiment. In the first
scenario, we trained baseline models using in-focus DNA image data and tested models on unseen
in-focus DNA images. With tissues such as the small intestine, which are challenging to segment
because they contain densely-packed nuclei, scenario A resulted in slightly under-segmented
predictions. In Scenario B and for all subsequent scenarios, defocused DNA images were included
in the test set, giving rise to contours that were substantially misaligned with ground truth
annotations and resulted in higher undersegmentation. False-positive predictions and imprecise
localizations of the nuclei membrane were observed in areas devoid of nuclei and with very low
contrast (**Figure 4a**). When NES images were included in the training set (Scenario C), nuclear
boundaries were more consistent with ground truth annotations, although false-positive predicted
nuclei still remained. The most robust performance across ML frameworks and tissues was
observed when NES images and real augmentation were combined: accurate nuclear boundaries
were generally well aligned with ground truth annotations in both shape and in size. Observable
differences in the placement of segmentation masks were reflected in improvements in IoU: for all
three deep learning frameworks, including NES data and real augmentations increased the fraction
of nuclei retained by 50% at an IoU threshold of 0.6 (**Figure 4b**). The accuracy of UnMICST-P (blue
curve) trained on in-focus DNA data alone was higher than the other two baseline models at all IoU
thresholds, suggesting that UnMICST-P has a greater capacity to learn. UnMICST-P may have an
advantage in experiments in which staining the nuclear envelope proves difficult or impossible.

Combining NES and real augmentation is advantageous across multiple tissue types

To determine if improvements in segmentation would extend to multiple tissue types we
repeated the analysis described above using three scenarios for training and testing with both in-
focus (**Figure 5a**) and defocused images (**Figure 5b**). Scenario 1 used in-focus DNA images for
training (blue bars), scenario 2 used in-focus DNA and NES images (red bars), and scenario 3 used
in-focus DNA and NES images plus real augmentation (green bars). While the magnitude of the
improvement varied with tissue type and test set (panel a vs b), the results as a whole support the
conclusion that including both NES and real augmentations during model training confers
statistically significant improvement in segmentation accuracy with multiple tissue types and models.
The accuracy boost was greatest when models performed poorly (e.g., in scenario 1 where models
were tested on defocused colon image data; **Figure 5b,** blue bars), so that segmentation accuracy
became relatively uniform across tissue and cell types. As a final test, we re-examined the whole
slide melanoma image described above (which had not been included in any training data) and
evaluated IoU, AP and F1-scores. The data were consistent regardless of metric and showed that
all three models benefitted from the inclusion of training data that included NES images and real
augmentations (**Supplementary Figure 3**). The improvement in accuracy, however, was modest
and similar to lung adenocarcinoma. We attribute this to the fact that, like lung adenocarcinoma,
melanoma has less dense regions, which our baseline models already performed well on.

Applying UnMICST to highly multiplex whole-slide tissue images

To investigate the overall improvement achievable with a representative UnMICST model,
we tested UnMICST-U with and without real or computed augmentations and NES data on all six
tissues as a set, including in-focus, saturated and out-focus images (balancing the total amount of
training data in each case). A 1.7-fold improvement in accuracy was observed at an IoU of 0.6 for
the fully trained model (i.e. with NES data and real augmentations; **Figure 6a**). Inspection of
segmentation masks also demonstrated more accurate contours for nuclei across a wide range of
shapes. The overall improvement in accuracy was substantially greater than any difference
observed between semantic and instance segmentation frameworks. We, therefore, focused
subsequent work on the most widely used framework: U-Net.
We also tested a fully trained UnMICST-U model on a 64-plex CyCIF image of non-
neoplastic small intestine tissue from the EMIT TMA (**Figure 6b**). Staining intensities were
quantified on a per-cell basis, and the results visualized using Uniform Manifold Approximation and
Projection (UMAP; **Figure 6c**). Segmentation masks were found to be well-located with little
evidence of under or over-segmentation (**Figure 6d**). Moreover, whereas 21% of cells with
segmented nuclei stained positive (as determined by using a Gaussian-mixture model) for the
immune cell marker CD45, and 53% stained positive for the epithelial cell marker E-cadherin, less

than 3% were positive for both. No known cell type is actually positive for both CD45 and E-

cadherin, and the very low abundance of these double-positive "cells" is evidence of accurate

segmentation. When we examined some of the 830 double positive cells (blue dashed circle in

Figure 6c) we found multiple examples of a CD3[+] T cell (yellow arrowheads; light yellow dots in

Figure 6e) tightly associated with or between the epithelial cells of intestinal villi (green "kiwi"

structure visible in **Figure 6e**). This is consistent with the known role of the intestinal epithelium in

immune homeostasis[38]. In these cases, the ability of humans to distinguish immune and epithelial

cells relies on prior knowledge, multi-dimensional intensity features and subtle differences in shape

and texture – none of which were aspects of model training. Thus, future improvements in tissue

segmentation are likely to require the development of CNNs able to classify rare but biologically

significant spatial arrangements, rather than simple extensions of the general purpose segmentation

algorithms described here.

Some tissues still pose a challenge for nuclei segmentation

Of all the tissue types annotated and tested in this paper, non-neoplastic ovary was the most

difficult to segment (**Supplementary Figure 4a**) and addition of ovarian training data to models

trained on data from other tissues decreased overall accuracy (**Supplementary Figure 4b**). We

have previously imaged ovarian cancers at even higher resolution (60x/1.42NA sampled at 108 nm

pixel size); (Färkkilä et al., 2020) using optical sectioning and deconvolution microscopy; inspection

of these images reveals nuclei with highly irregular morphology, poor image contrast, and dense

packing (**Supplementary Figure 4c**) unlike colon adenocarcinoma (**Supplementary Figure 4d**).

Thus, additional research, possibly involving different NES antibodies, will be required to improve

performance with ovarian and other difficult to segment tissues. Until then, caution is warranted

when combining training data from tissues with very different nuclear morphologies.

DISCUSSION

This paper makes four primary contributions to the growing literature on the segmentation of

tissue images, which is an essential step in single-cell data analysis. First, we consciously included

in training and test data the types of focus and intensity artefacts that are commonly encountered in

whole-slide images, particularly images of human tissues acquired in the course of clinical care and

treatment. This contrasts with other recent papers that focus on optimal fields of view. Second, we

show that addition of real augmentations comprising defocused and saturated images to model

training data improves segmentation accuracy to a significant extent whereas augmentations based

on Gaussian blurring provide minimal benefit. These results extend to deep learning frameworks

based on instance segmentation (UnMICST-M) and on semantic segmentation (UnMICST-U and

UnMICST-P). Third, we show that it is often possible to increase segmentation accuracy by

including additional data (NES) on nuclear envelop morphology, although identifying suitable

antibody cocktails is not trivial. Finally, using newly generated labeled training data for multiple
tissue types, we show that real augmentation and NES combine to improve the robustness and
accuracy of segmentation across many tissues; these improvements are directly applicable to the
real-world task of segmenting high dimensional tissue and tumor images. Moreover, the magnitude
of improvement observed with NES data or real augmentation is substantially greater than the
differences observed between ML frameworks. UnMICST models, therefore, represent a good
starting point for performing image segmentation on rapidly growing tissue data repositories. Errors
remaining when multiplexed images are segmented using optimized UnMICST models appear to
have a subtle biological basis. Development of additional "physiology aware" machine-learning
models may be necessary to reduce these apparent errors.
One of the surprises in the current work was the seemingly low level of agreement achieved
by two human experts annotating the same image data; we estimated that only 60% of the
annotated nuclei between annotators had an overlap of 60% or greater (0.6 IoU threshold). Poor
agreement is almost certainly a consequence of our use of a stringent sweeping IoU scoring
criterion that measures the fraction of pixels that overlap between two segmentation masks. The
alternative, and widely-used F1 score, which determines whether two observers (or an observer and
a machine) agree on the of nuclear features, achieves inter-observer and automated segmentation
accuracy of 0.78, which is comparable to the highest F1-scoring tissue reported for Mesmer[39],
another deep learning model applied to tissue images. Moreover, our results with IoU values are
similar to those recently reported by Kromp et al.[17] (when IoU tresholds are adjusted to enable direct
comparison). The authors of Cellseg[40] also report comparable segmentation accuracies and note
the difficulty of achieving a high IoU value with cells that vary dramatically in shape and focus.
It would therefore appear that many studies have achieved similar levels of inter-observer
agreement and that our results are not an outlier, even though we include problematic data. This
points to a fundamental challenge for all supervised learning approaches whose solution is not
immediately clear. Collection of precise 3D data followed by imposition of different levels of blurring
and addition of intensity artefacts will be needed to understand the origins of inter-observer
disagreement in tissue images and achieve higher quality training and test data. Despite this
concern, it seems likely that practical improvements in segmentation are likely to come from
combining recently described advances. For example, Greenwald et al[41] use a clever community-
based approach to acquire much more training data than in the current work, Kromp et al.[17]
combine tissue images with ground truth annotation acquired from cultured cells (by a team of
undergraduate students), whereas the current work focuses on the use of NES and real
augmentations to improve the robustness of segmentation algorithms across the board.
From a machine learning perspective, the value of adding images to training data is self-
evident. Experimental feasibility is not always so clear. A key tradeoff is that the greater the number
of fluorescence channels used for segmentation, the fewer the channels available for the collection

of data on other markers. Fortunately, the development of highly multiplexed imaging has made this

less relevant because collection of 20-40 or more image channels (each corresponding to a different

fluorescent antibody) has become routine. This makes it straightforward to reserve two channels for

segmentation. The cost-benefit ratio of adding extra segmentation data will be different in high

content screening of cells in multi-well plates, for which inexpensive reagents are generally essential

than in tissue imaging. In tissues, the morphology of nuclear lamin changes with disease state[42], cell

type, activation state and numerous other biological processes. While this challenges segmentation

routines, imaging lamins is also likely to provide valuable biological information, further arguing for

routine collection of these data[43]. To allow others to build on the current work, we are releasing all

training and test images, their segmentation masks and annotations, and real augmentations for

multiple types of tissue (tonsil, ovary, small intestine and cancers of the colon, brain, lung, prostate)

via the EMIT resource; models are released as components of the UnMICST model resource (see

data and code availability information).

The most immediately generalizable finding from this work is that real augmentation

outperforms computed augmentation generated using Gaussian kernels. Blurring and image

saturation are an inevitable consequence of the limited bandwidth of optical systems, the thickness

of specimens relative to the depth of field, light scattering, diffraction, the use of non-immersion

objective lenses and consequent refractive index mismatches, and a variety of other physical

processes. Real out-of-focus blur also differs when the focal plane is above and below the

specimen. Areas for future application of real augmentations could include inhomogeneous light

sources and stage jitter. It will undoubtedly be useful to determine kernels for more effective

computed augmentation, but collecting real augmentation data imposes a minimal burden in a real-

world setting. Our observation that real augmentation outperforms computed augmentation may

also have general significance outside of the field of microscopy: with any high-performance camera

system, real out-of-focus data will inevitably be more complicated than Gaussian blur.

CODE AND DATA AVAILABILITY

To allow others to build on the current work, we are releasing all training, validation and test images,

their annotations, and real augmentations for multiple types of tissue (tonsil, ovary, small intestine

and cancers of the colon, brain, lung, prostate) via the EMIT resource; models and scripts for

training and inference are released as components of the UnMICST model resource (see data and

code availability information). https://labsyspharm.github.io/UnMICST-info/

METHODS

Sample preparation for imaging

To generate images for model training and testing, human tissue specimens from multiple

patients were used to construct a multi-tissue microarray (HTMA427) under an excess (discarded)

tissue protocol approved by the Institutional Review Board (IRB) at Brigham and Women's Hospital

(BWH IRB 2018P001627). One or two 1.5 mm diameter cores were taken from tissue regions with

the goal of acquiring one or two examples of different healthy or tumor types including non-

neoplastic medical diseases and secondary lymphoid tissues such as tonsil. Slides were stained

with the following reagents from Cell Signaling Technologies (Beverly MA, USA) and Abcam

(Cambridge UK).

Table 1: Antibodies used for immunofluorescence staining

Target	Fluorochrome	Species	Clone	Vendor	Cat. No.	RRID
DNA	Hoechst 33342	NA	NA	CST	4082	AB_10626776
Lamin B2	Alexafluor 647	Rabbit	EPR9701(B)	Abcam	ab200427	AB_2889288
NUP98	Alexafluor 647	Rabbit	C39A3	CST	13393	AB_2728831
Lamin B1	Alexafluor 488	Rabbit	EPR8985(B)	Abcam	ab194106	AB_2728786
Lamin A/C	Alexafluor 488	Mouse	4C11	CST	8617S	AB_10997529
Lamin B receptor	Alexafluor 488	Rabbit	E398L	Abcam	ab201532	AB_2889290

Before imaging, slides were mounted with 90% glycerol and a #1.5 coverslip. Prior to

algorithmic evaluation, the images were split into three mutually disjoint subsets and used for

training, validation, and testing.

Acquisition of image data and real augmentations

The stained TMA was imaged on a INCell 6000 (General Electric Life Sciences) microscope

equipped with a 20x/0.75 objective lens (370 nm nominal lateral resolution at 550 nm wavelength)

and a pixel size of 0.325 µm per pixel. Hoechst and lamin-A647 were excited with a 405 nm and

642 nm laser, respectively. Emission was collected with the "DAPI" (455/50 nm) and "Cy5" (682/60

nm) filter sets with exposure times of 60 ms and 100 ms, respectively. Whole-slide imaging involved

acquisition of 1,215 tiles with an 8% overlap, which is recommended for stitching in ASHLAR, a next

generation stitching and registration algorithm for large images

(https://github.com/labsyspharm/ashlar). To generate defocused data, we acquired images from

above and below the focal plane by varying the Z-axis by 3 µm in both directions. To generate

saturated images of DNA staining, a 150ms exposure time was used. These two types of

"suboptimal" data were then used for "real augmentation" during model training, as described below.

Representative cores for lung adenocarcinoma, non-neoplastic small intestine, normal

prostate, colon adenocarcinoma, glioblastoma, non-neoplastic ovary, and tonsil were extracted from

image mosaics and down-sampled by a factor of 2 to match the pixel size of images routinely

acquired and analyzed in MCMICRO[33]. Images were then cropped to 256 x 256-pixel tiles, and in-

focus DNA and NES were imported into Adobe Photoshop to facilitate human annotation of nuclear

boundaries. Annotations for contours and background classes were labelled on separate layers

while swapping between DNA and NES as necessary. To save time, we drew complete contours of

nuclei and filled these in using the Matlab *imfill* operation to generate nuclei centers. For nuclei at

the image borders where contours would be incomplete, we manually annotated nuclei centers. As

described by Ronneberger et al. (2015), a fourth layer was used to mark areas between clumped

cells. These additional annotations made it possible to specifically penalize models that incorrectly

classified these pixels. Annotations on a held-out test dataset were validated by a second

annotator and measured using the F1-score. The F1-score evaluation between both annotated

ground truths was high and demonstrated excellent agreement (**Supplementary Figure 1**).

Because original, defocused, and saturated images of DNA were all acquired in the same

image stack, it was possible to use a single registered set of DNA annotations across all augmented

image channels. To produce the training set, each image was cropped into 64 x 64 patches,

normalized to use the full dynamic range, and further augmented using 90-degree rotations,

reflections, and 20% upscaling. Consistent with the training set, the validation and test sets also

include defocused and saturated examples but were not augmented with standard transformations.

The ratio of data examples present in the training, validation, and test set split was 0.36:0.24:0.4.

For a fair comparison across models, the same dataset and split were used for the three deep

learning frameworks described in this manuscript (**Supplementary Table 2**).

Model implementation

To facilitate model training, three distinct state-of-the-art architectures were separately,

trained, implemented and evaluated. They are, in no particular order, UNet, Mask R-CNN, and

PSPNet and were adopted from their original references without modification to their architecture.

UNet was selected for its prior success in the biomedical domain, Mask R-CNN was selected for its

ability to perform both object detection and mask generation, and PSPNet was selected for its

capacity to integrate image features from multiple spatial scales. Training, validation, and test data

were derived from 12 cores in 7 tissues and a total of 10,359 nuclei in the composition of colon –

1,142; glioblastoma (GBM) – 675; lung – 1735; ovarian – 956; fibroblast – 922; small intestine –

1677; tonsil – 3252. To maintain consistency of evaluation across segmentation algorithms,

segmentation accuracy was calculated by counting the fraction of cells in a held out test set that

passed a sweeping Intersection over Union (IoU) threshold. The NES channel was concatenated to

the DNA channel as a three-dimensional array as input into each architecture.

Model Training

UnMICST-U models

A three-class UNet model[14] was trained based on annotation of nuclei centers, nuclei contours, and background. The neural network is comprised of 4 layers and 80 input features. Training was performed using a batch size of 32 with the Adam Optimizer and a learning rate of 0.00005 with a decay rate of 0.98 every 5,000 steps until there was no improvement in accuracy or ~100 epochs had been reached. Batch normalization was used to improve training speed. During training, the bottom layer had a dropout rate of 0.35, and L1 regularization was implemented to minimize overfitting[44,45] and early stopping. Training was performed on workstations equipped with NVidia GTX 1080 or NVidia TitanX GPUs.

UnMICST-M models

Many segmentation models are based on the Mask R-CNN architecture[15], Mask R-CNN has previously exhibited excellent performance on a variety of segmentation tasks. Mask R-CNN begins by detecting bounding boxes of nuclei and subsequently performs segmentation within each box. This approach eliminates the need for an intermediate watershed, or equivalent, segmentation step. Thus, Mask R-CNN directly calculates a segmentation mask, significantly reducing the overhead in traditional segmentation pipelines. We adopted a ResNet50[46] backbone model in the UnMICST-M implementation and initialized the weights using pretrained values from the COCO object instance segmentation challenge[30] to improve convergence properties. For efficient training, we upsampled the original input images to 800 x 800-pixels and trained a model for 24 epochs using a batch size of 8. The Adam optimizer, with a weight decay of 0.0001 to prevent overfitting, was exploited with a variable learning rate, initially set to 0.01 and decreased by a factor of 0.1 at epochs 16 and 22. Training was performed on a compute node cluster using 4 NVidia TitanX or NVidia Tesla V100 GPUs. For evaluation and comparison, we used the model with the highest performance on the validation set, following standard practice.

UnMICST-P models

We trained a three class PSPNet model[47] to extract cell nuclei centers, nuclei contours, and background from a wide variety of tissue types. PSPNet is one of the most widely used convolutional neural networks for the semantic segmentation of natural scene images in the computer vision field. The network employs a so-called pyramid pooling module whose purpose is to learn global as well as local features. The additional contextual information used by PSPNet allowed the segmentation algorithm to produce realistic probability maps with greater confidence. We used ResNet101 as a backbone. Training of the network was performed using a batch size of 8 with an image size of 256 x 256-pixels for 15,000 iterations or until the minimum loss model was

obtained. A standard cross entropy loss function was used during training. Gradient descent was
performed using the Adam optimizer with a learning rate of 0.0001 and a weight decay parameter of
0.005 via L2 regularization. Batch normalization was employed for faster convergence, and a
dropout probability of 0.5 was used in the final network layer to mitigate overfitting. The model
training was performed on a compute cluster node equipped with NVidia Tesla V100 GPUs.

Analysis of multi-dimensional data
For the analysis shown in Figure 6, a 64-plex CyCIF image of non-neoplastic small intestine
tissue from the EMIT TMA (https://www.synapse.org/#!Synapse:syn22345748/) was stained with a
total of 45 antibodies as described in protocols https://www.protocols.io/view/ffpe-tissue-pre-
treatment-before-t-cycif-on-leica-bji2kkge and dx.doi.org/10.17504/protocols.io.bjiukkew. Images
were segmented using the UnMICST-U model trained on DNA with NES data and real
augmentations. Mean fluorescence intensities across 45 markers for 27,847 segmented nuclei were
quantified as described in[33]. E-cadherin positive and CD45 positive cells were identified using
Gaussian-mixture models on log-transformed data. For multivariate clustering, log-transformed
mean intensities of all single cells of 14 selected protein markers (E-cadherin, pan-cytokeratin,
CD45 CD4, CD3D, CD8, RF3, PML, GLUT1, GAPDH TDP43, OGT, COLL4, an EPCAM) were pre-
processed using Uniform Manifold Approximation and Projection (UMAP)[48] and clustered using
Hierarchical Density-Based Spatial Clustering of Applications with Noise (HDBSCAN)[49]. Clusters
expressing a high level of both E-cadherin and CD45 were identified and overlaid on a false-colored
image showing the staining of DNA, E-cadherin, and CD45.

ACKNOWLEDGEMENTS
We thank Alyce Chen and Madison Tyler for their help with this manuscript. The work was funded
by NIH grants U54-CA225088 and U2C-CA233262 to P.K.S. and S.S and by the Ludwig Cancer
Center at Harvard. Z.M. is supported by NCI grant R50-CA252138. We thank Dana-Farber/Harvard
Cancer Center (P30- CA06516) for the use of its Specialized Histopathology Core.

AUTHOR CONTRIBUTIONS
The study design was conceived by CY, WDJ, EN, and PKS. Image acquisition and annotation was
done by CY. SS provided the EMIT TMA sample and validated the tissue types. TMA staining was
performed by ZM and CAJ. Data analysis was performed by CY, WDJ, EN, and YAC. YAC and CY
performed the single cell quantitative analysis and analysis found in figure 6. Additional coding was
done by MC. Additional experiments were conducted by DW. PKS, SS, HP supervised the study. All
authors contributed to the writing and editing of the manuscript.

OUTSIDE INTERESTS

PKS is a member of the SAB or BOD member of Applied Biomath, RareCyte Inc., and Glencoe

Software, which distributes a commercial version of the OMERO database; PKS is also a member

of the NanoString SAB. In the last five years the Sorger lab has received research funding from

Novartis and Merck. Sorger declares that none of these relationships have influenced the content of

this manuscript. SS is a consultant for RareCyte Inc. The other authors declare no outside interests.

REFERENCES

1. Gerdes, M. J. *et al.* Highly multiplexed single-cell analysis of formalin-fixed, paraffin-embedded cancer tissue. *Proc. Natl. Acad. Sci. U. S. A.* **110**, 11982–11987 (2013).

2. Giesen, C. *et al.* Highly multiplexed imaging of tumor tissues with subcellular resolution by mass cytometry. *Nat. Methods* **11**, 417–422 (2014).

3. Angelo, M. *et al.* Multiplexed ion beam imaging of human breast tumors. *Nat. Med.* **20**, 436–442 (2014).

4. Lin, J.-R. *et al.* Highly multiplexed immunofluorescence imaging of human tissues and tumors using t-CyCIF and conventional optical microscopes. *eLife* **7**, e31657 (2018).

5. Stack, E. C., Wang, C., Roman, K. A. & Hoyt, C. C. Multiplexed immunohistochemistry, imaging, and quantitation: A review, with an assessment of Tyramide signal amplification, multispectral imaging and multiplex analysis. *Methods* **70**, 46–58 (2014).

6. Immunologists, A. A. of. The Demonstration of Pneumococcal Antigen in Tissues by the Use of Fluorescent Antibody. *J. Immunol.* **45**, 159–170 (1942).

7. Albertson, D. G. Gene amplification in cancer. *Trends Genet.* **22**, 447–455 (2006).

8. Shlien, A. & Malkin, D. Copy number variations and cancer. *Genome Med.* **1**, 62 (2009).

9. Amin, M. B. *et al.* The Eighth Edition AJCC Cancer Staging Manual: Continuing to build a bridge from a population-based to a more 'personalized' approach to cancer staging. *CA. Cancer J. Clin.* **67**, 93–99 (2017).

10. Achim, K. *et al.* High-throughput spatial mapping of single-cell RNA-seq data to tissue of origin. *Nat. Biotechnol.* **33**, 503–509 (2015).

11. Slyper, M. *et al.* A single-cell and single-nucleus RNA-Seq toolbox for fresh and frozen human tumors. *Nat. Med.* **26**, 792–802 (2020).

12. McQuin, C. *et al.* CellProfiler 3.0: Next-generation image processing for biology. *PLOS Biol.* **16**, e2005970 (2018).

13. LeCun, Y., Bengio, Y. & Hinton, G. Deep learning. *Nature* **521**, 436–444 (2015).

14. Ronneberger, O., Fischer, P. & Brox, T. U-Net: Convolutional Networks for Biomedical Image Segmentation. *ArXiv150504597 Cs* (2015).

15. He, K., Gkioxari, G., Dollár, P. & Girshick, R. Mask R-CNN. *ArXiv170306870 Cs* (2018).

16. Caicedo, J. C. *et al.* Nucleus segmentation across imaging experiments: the 2018 Data Science

Bowl. *Nat. Methods* **16**, 1247–1253 (2019).

17. Kromp, F. *et al.* An annotated fluorescence image dataset for training nuclear segmentation

methods. *Sci. Data* **7**, 262 (2020).

18. Schwendy, M., Unger, R. E. & Parekh, S. H. EVICAN—a balanced dataset for algorithm

development in cell and nucleus segmentation. *Bioinformatics* **36**, 3863–3870 (2020).

19. Schüffler, P. J. *et al.* Automatic single cell segmentation on highly multiplexed tissue images.

Cytometry A **87**, 936–942 (2015).

20. Arganda-Carreras, I. *et al.* Trainable Weka Segmentation: a machine learning tool for

microscopy pixel classification. *Bioinformatics* **33**, 2424–2426 (2017).

21. Berg, S. *et al.* ilastik: interactive machine learning for (bio)image analysis. *Nat. Methods* **16**,

1226–1232 (2019).

22. Aeffner, F. *et al.* Introduction to Digital Image Analysis in Whole-slide Imaging: A White Paper

from the Digital Pathology Association. *J. Pathol. Inform.* **10**, 9 (2019).

23. Lin, J.-R. *et al.* Multiplexed 3D atlas of state transitions and immune interactions in colorectal

cancer. *bioRxiv* 2021.03.31.437984 (2021) doi:10.1101/2021.03.31.437984.

24. Krizhevsky, A., Sutskever, I. & Hinton, G. E. ImageNet Classification with Deep Convolutional

Neural Networks. in *Advances in Neural Information Processing Systems 25* (eds. Pereira, F.,

Burges, C. J. C., Bottou, L. & Weinberger, K. Q.) 1097–1105 (Curran Associates, Inc., 2012).

25. Ahmed Raza, S. E. *et al.* MIMO-Net: A multi-input multi-output convolutional neural network for

cell segmentation in fluorescence microscopy images. in *2017 IEEE 14th International*

Symposium on Biomedical Imaging (ISBI 2017) 337–340 (IEEE, 2017).

doi:10.1109/ISBI.2017.7950532.

26. Shorten, C. & Khoshgoftaar, T. M. A survey on Image Data Augmentation for Deep Learning. *J.*

Big Data **6**, 60 (2019).

27. Horwath, J. P., Zakharov, D. N., Mégret, R. & Stach, E. A. Understanding important features of

deep learning models for segmentation of high-resolution transmission electron microscopy

images. *Npj Comput. Mater.* **6**, 1–9 (2020).

28. Gurari, D. *et al.* How to Collect Segmentations for Biomedical Images? A Benchmark Evaluating

the Performance of Experts, Crowdsourced Non-experts, and Algorithms. *2015 IEEE Winter*

Conf. Appl. Comput. Vis. (2015) doi:10.1109/WACV.2015.160.

29. Deng, J. *et al.* ImageNet: A large-scale hierarchical image database. in *2009 IEEE Conference*

on Computer Vision and Pattern Recognition 248–255 (2009).

doi:10.1109/CVPR.2009.5206848.

30. Lin, T.-Y. *et al.* Microsoft COCO: Common Objects in Context. in *Computer Vision – ECCV*

2014 (eds. Fleet, D., Pajdla, T., Schiele, B. & Tuytelaars, T.) 740–755 (Springer International

Publishing, 2014). doi:10.1007/978-3-319-10602-1_48.

31. Skinner, B. M. & Johnson, E. E. P. Nuclear morphologies: their diversity and functional

relevance. *Chromosoma* **126**, 195–212 (2017).

32. Dalle, J.-R. *et al.* Nuclear pleomorphism scoring by selective cell nuclei detection. in *IEEE*

Workshop on Applications of Computer Vision (WACV 2009), 7-8 December, 2009, Snowbird,

UT, USA (IEEE Computer Society, 2009).

33. Schapiro, D. *et al.* MCMICRO: a scalable, modular image-processing pipeline for multiplexed

tissue imaging. *Nat. Methods* 1–5 (2021) doi:10.1038/s41592-021-01308-y.

34. Nirmal, A. J. *et al.* The spatial landscape of progression and immunoediting in primary

melanoma at single cell resolution. *bioRxiv* 2021.05.23.445310 (2021)

doi:10.1101/2021.05.23.445310.

35. Fischer, E. G. Nuclear Morphology and the Biology of Cancer Cells. *Acta Cytol.* **64**, 511–519

(2020).

36. Kros, J. M. Grading of Gliomas: The Road From Eminence to Evidence. *J. Neuropathol. Exp.*

Neurol. **70**, 101–109 (2011).

37. Louis, D., Ohgaki, H., Wiestler, O. & Cavenee, W. *WHO Classification of Tumours of the Central*

Nervous System. (2016).

38. Allaire, J. M. *et al.* The Intestinal Epithelium: Central Coordinator of Mucosal Immunity. *Trends*

Immunol. **39**, 677–696 (2018).

39. Greenwald, N. F. *et al. Whole-cell segmentation of tissue images with human-level performance*

using large-scale data annotation and deep learning.

http://biorxiv.org/lookup/doi/10.1101/2021.03.01.431313 (2021)

doi:10.1101/2021.03.01.431313.

40. Lee, M. Y. *et al.* CellSeg: a robust, pre-trained nucleus segmentation and pixel quantification

software for highly multiplexed fluorescence images. *BMC Bioinformatics* **23**, 46 (2022).

41. Greenwald, N. F. *et al.* Whole-cell segmentation of tissue images with human-level performance

using large-scale data annotation and deep learning. *bioRxiv* 2021.03.01.431313 (2021)

doi:10.1101/2021.03.01.431313.

42. Sakthivel, K. M. & Sehgal, P. A Novel Role of Lamins from Genetic Disease to Cancer

Biomarkers. *Oncol. Rev.* **10**, 309 (2016).

43. Bell, E. S. & Lammerding, J. Causes and consequences of nuclear envelope alterations in

tumour progression. *Eur. J. Cell Biol.* **95**, 449–464 (2016).

44. Ng, A. Y. Feature selection, L1 vs. L2 regularization, and rotational invariance. in *Proceedings*

of the twenty-first international conference on Machine learning 78 (Association for Computing

Machinery, 2004). doi:10.1145/1015330.1015435.

45. Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I. & Salakhutdinov, R. Dropout: a simple

way to prevent neural networks from overfitting. *J. Mach. Learn. Res.* **15**, 1929–1958 (2014).

46. He, K., Zhang, X., Ren, S. & Sun, J. Deep Residual Learning for Image Recognition. in *2016*

IEEE Conference on Computer Vision and Pattern Recognition (CVPR) 770–778 (2016).

doi:10.1109/CVPR.2016.90.

47. Zhao, H., Shi, J., Qi, X., Wang, X. & Jia, J. Pyramid Scene Parsing Network. *ArXiv161201105*

Cs (2017).

48. Becht, E. *et al.* Dimensionality reduction for visualizing single-cell data using UMAP. *Nat.*

Biotechnol. **37**, 38–44 (2019).

49. Campello, R. J. G. B., Moulavi, D. & Sander, J. Density-Based Clustering Based on Hierarchical

Density Estimates. in *Advances in Knowledge Discovery and Data Mining* (eds. Pei, J., Tseng,

V. S., Cao, L., Motoda, H. & Xu, G.) 160–172 (Springer, 2013). doi:10.1007/978-3-642-37456-

2_14.

Figure 1

Figure 1: Comparing the use of real augmentations (defocused and overexposed images)

and Gaussian blur. a) Schematic diagram showing the approach comparing test images on models

trained with Gaussian-blurred or defocused image data. Higher contrast probability maps signify

more confidence – areas of interest are highlighted with red arrows. Corresponding probability maps

indicate a model trained with defocused images performs better on defocused test images than a

Gaussian-blurred model. Scale bar denotes 20 micrometers. **b**) Plots show that incorporating real

augmentations (red curve) into the training set is statistically significantly superior to training sets

with Gaussian blur (yellow curve) and without real augmentations (blue curve) for UnMICST-U,

UnMICST-M, and UnMICST-P. Simulating defocused images with Gaussian blur is only marginally

better than not augmenting the training data at all. **c**) Comparing UnMICST-U model accuracy when

the training dataset size was held constant by replacing defocused augmentations (red curve) with

90 and 180 degree rotations (blue curve).

Figure 2

Figure 2: Comparing different nuclear envelope stains in colon adenocarcinoma. a-e)

Showcasing lamin A/C, lamin B1, lamin B2, NUP98, and the lamin B receptor in the same field of

view. Lamin B1 and B2 appear to stain similar proportions of nuclei while lamin A/C stains fewer

nuclei. The stain against the lamin B receptor was comparatively weaker. Lamin B2 (**f**) and NUP98

(**g**) are complementary and, when used in combination, maximize the number of cells stained. **h**)

Composite of lamin B2 (purple) and NUP98 (green). Scale bar denotes 100 micrometers.

Figure 3

Figure 3: NES with DNA improves nuclear segmentation. NES – nuclear envelope staining.

Assessing the addition of NES as a 2nd marker to DNA on segmentation accuracy on a per tissue

and per model basis. **a**) Variable IoU plots comparing the DNA-only model (blue curve) and the

DNA + NES model (red curve) across frameworks. Adding NES increased accuracy for densely

packed nuclei such as colon, small intestine, tonsil, and to some extent, lung tissue. Error bars are

standard errors of mean. **b**) Representative grayscale images of tissues stained with DNA and NES

comparing their variable morphologies, followed by UnMICST-U mask predictions (green) overlaid

onto ground truth annotations (purple). In tissue with sparse nuclei, such as fibroblasts from prostate

tissue, NES did not add an additional benefit to DNA alone. In tissues where NES does not exhibit

the characteristic nuclear ring, as in glioblastoma, the accuracy was similarly not improved. Scale

bar denotes 20 micrometers.

Figure 4

Scenario	DNA	NES	Real augmen-tation	Defocused test data
A	Yes	No	No	No
B	Yes	No	No	Yes
C	Yes	Yes	No	Yes
D	Yes	Yes	Yes	Yes

Figure 4: Combination of NES and real image augmentations on segmentation performance.

NES - nuclear envelope staining. **a**) Models trained with in-focus DNA data alone produced

probability maps that were undersegmented, especially in densely-packed tissue such as small

intestine (Scenario A). When tested on defocused data, nuclei borders were largely incorrect

(Scenario B). Adding NES restored nuclei border shapes (Scenario C). Combining NES and real

augmentations reduced false positive detections and produced nuclei masks better resembling the

ground truth labels (Scenario D). Scalebar denotes 20 micrometers. Table legend shows conditions

used for each scenario A-D. Yellow arrow indicates a blurry cell of interest where accuracy improves

with NES and real augmentation **b**) Graphs compare the accuracy represented as the number of
cells retained across varying IoU thresholds with all models from UnMICST-U (top), UnMICST-M
(center), and UnMICST-P (bottom). In all models, more nuclei were retained when NES and real
augmentations were used together during training (yellow curves) compared to using NES without
real augmentations (red curves) or DNA alone (blue curves).

Figure 5: Assessing different training strategies on a) in-focus and b) defocused test data for

different tissue types. **a**) In all tissue types apart from GBM, the addition of NES (red bars) and the

use of real augmentations combined with NES (green bars) in training data offered superior

accuracy compared to using DNA alone (blue bars). **b**) When the models were tested on defocused

data, all tissues (including GBM unexpectedly) showed benefits resulting from using NES (red bars)

combined with real augmentations (green bars). The line plot indicates highest accuracy achieved

for each tissue when tested on in-focus data from panel a.

Figure 6

Figure 6: Applying UnMICST models to highly multiplexed image data. a) Accuracy
improvement of UnMICST-U models trained with and without NES (nuclear envelope staining) as
compared to DNA alone, and real augmentations as compared to computed blur (GB; Gaussian
blur). To balance training dataset size, GB was substituted for NES data and computed 90/180
degree rotations were substituted for real augmentations. **b)** A 64-plex CyCIF image of a non-
neoplastic small intestine TMA core from the EMIT dataset. Dashed box indicates region of interest
for panels **d** and **e**. **c)** UMAP projection using single cell staining intensities for 14 marker proteins
(see methods). The color of the data points represents the intensity of E-cadherin (top left) or CD45
(bottom left) across all segmented nuclei. Density-based clustering using HDBSCAN identified
distinct clusters (each denoted by a different color) that were positive for either E-cadherin or CD45
as well as a small number of double-positive cells (blue dashed circle). **d)** Enlarged region of yellow
dashed box from **b** showing segmentation mask outlines (magenta) overlayed onto DNA channel
(green). **e)** Composite image of DNA, E-cadherin, and CD45 of the same region. Nuclei centroids
from segmentation denoted by brown dots. Cells positive for both E-cadherin and CD45 (from blue
dashed circle in panel **c** are marked with yellow arrows and yellow dots. Inset: enlarged view of
boxed region showing overlapping immune and epithelial cells.

842