Title: Dynamic task-belief is an integral part of decision-making

Authors: Cheng Xue, Lily E. Kramer, Marlene R. Cohen[1]

Affiliations: Department of Neuroscience and Center for Neural Basis of

Cognition, University of Pittsburgh, Pittsburgh, PA, 15260, USA

Summary

Natural decisions involve two seemingly separable processes: inferring the relevant task (task-belief) and performing the believed-relevant task. The assumed separability has led to the traditional practice of studying task-switching and perceptual decision-making individually. Here, we used a novel paradigm to manipulate and measure macaque monkeys' task-belief, and demonstrated inextricable neuronal links between flexible task-belief and perceptual decision-making. We showed that in animals, but not artificial networks that performed as well or better than the animals, stronger task-belief is associated with better perception. Correspondingly, recordings from neuronal populations in cortical areas 7a and V1 revealed that stronger task-belief is associated with better discriminability of the believed-relevant but not the believed-irrelevant feature. Perception also impacts belief updating: noise fluctuations in V1 help explain how task-belief is updated. Our results demonstrate that complex tasks and multi-area recordings can reveal fundamentally new principles of how biology affects behavior in health and disease.

[1] Lead contact. Correspondence should be addressed to Cheng Xue (chx31@pitt.edu) or Marlene R. Cohen (cohenm@pitt.edu)

Introduction

Humans and animals make countless decisions every day that affect their well-being or even survival. In the laboratory, decision-making has typically been studied by observing behaviors and neuronal activity while subjects perform simple, well-understood sensory-motor integration tasks (Gold and Shadlen, 2007; Kable and Glimcher, 2009; Uchida, Kepecs and Mainen, 2006). But real-life decisions usually need to contend with a more important problem even before making perceptual judgements: inferring the relevant task to solve in a certain situation (i.e., task-belief). Task-beliefs allow decision-makers to deploy attention to a relevant subset of feature dimensions out of the huge amount of information in natural environments, and task-beliefs are flexibly adapted as the environment evolves (task-switching(Monsell, 2003)). Flexibly adapting task-belief is critical but difficult: the inability to appropriately respond to changing conditions is a debilitating symptom of disorders including autism, dementia, and substance abuse (Brady, Gray and Tolliver, 2011; Thapar *et al.*, 2016; Dickstein *et al.*, 2007).

Typically, task-belief is assumed to be a separate functional step that occurs before, and independent of, perceptual decision-making. In this view, subjective beliefs about the task (possibly involving parietal, prefrontal, and cingulate cortical areas (Stoet and Snyder, 2009; Buschman *et al.*, 2012; Kamigaki, Fukushima and Miyashita, 2009; Sarafyazd and Jazayeri, 2019; Bartolo and Averbeck, 2020)) are used to identify task-relevant information. When that process is complete, the perceptual process (involving sensory areas such as visual cortex) makes a judgement about the believed relevant information (Purcell and Kiani, 2016a; Sarafyazd and Jazayeri, 2019; Mante *et al.*, 2013) (Figure S1A, upper panel).

The goal of our study was to use behavioral, physiological, and modeling methods to test the view that flexibly inferring the correct task and perception are independent processes. To that

end, we trained monkeys on a two-feature discrimination task that required them to report both

their task-belief and their perceptual judgment on each trial. By decoding task- and perception-

related signals from simultaneously recorded neuronal populations in parietal cortical area 7a and

visual cortical area V1, we demonstrated that: 1) trial-by-trial fluctuations in task-belief strength

correlate with perceptual performance and the fidelity of task-relevant information encoding in

visual cortex; and 2) neuronal variability in visual cortex, even when it is unrelated to the visual

input, plays an important role in updating task-belief (Figure S1A, lower panel). These results

suggest an integrated neuronal system that serves as a common substrate for flexible task-belief

and decision-making.

As neuroscience and cognitive science research start to shift focus from simplified

functions in isolation towards more complex and natural behavior, our work has implications for

methodology, basic science, and clinical translations at the time of this paradigm shift.

Methodologically, our work showcases how dynamic cognitive states (e.g. task-belief) can be

systematically manipulated and measured using large-scale neuronal recording from multiple

brain areas during complex cognitive tasks. Scientifically, we demonstrated inextricable links

between task-belief and perceptual decisions. These links would be impossible to see if each

process were studied alone, highlighting that complex cognitive processes cannot be understood

by investigating their components separately. Clinically, a wide variety of neuropsychiatric

disorders lead to malfunctions in task-switching and decision-making. The neuronal link between

the two processes suggests that potential treatments might do well to target neurotransmitters that

mediate communication between brain areas.

Results

Perceptual decision-making during task-switching

Task-belief is an internal state that continually changes. Even with experimenters' best

attempts to keep task-belief constant (with fixed stimuli, explicit instructions, and task statistics),

internal belief states still fluctuate substantially (Purcell and Kiani, 2016b; Ebitz, Tu and Hayden,

2020; Cohen and Maunsell, 2011a; Cohen and Maunsell, 2011b; Ashwood *et al.*, 2022). These

internal state fluctuations can impact visual cortical activity and perceptual decision-making

(which is typically the only process that is measured in those studies; (Cohen and Maunsell,

2011a; Cohen and Maunsell, 2011b; Monsell, 2003). These results suggest that beliefs and

perception interact in complex ways. The biggest barrier to understanding such interactions is

that it is difficult to estimate task-belief during each decision because it is by definition internal

and continually changing.

To address this challenge, we devised a novel two-feature discrimination task to assess

perception and belief simultaneously and on every trial. We present to the animals two Gabor

patches, one after the other. The second Gabor differs from the first in both of two features:

spatial location and spatial frequency. The changes in both features are independently

randomized. To obtain rewards, the animals were required to infer which of the two features as

behaviorally relevant and to discriminate the direction of change in the relevant feature.

Therefore, the task, requires two conceptually independent judgements to choose one choice

target out of four (Figure 1A, upper panel). The animals were rewarded only when they chose the

target corresponding to the correct direction of change in the relevant feature (Figure 1B, right

panel). The relevant feature was not cued and switched with a low probability from one trial to

the next (Figure 1A, lower panel).

This design provides rich and easy measurements and manipulations of task-belief and

perception through three key features: 1) on every trial, the animals make a perceptual

discrimination, so we measure perceptual accuracy on every trial, regardless of whether the

monkeys performed the correct task, 2) on every trial, the animals also explicitly indicate which

feature is believed to be relevant, providing a behavioral ground truth about task-belief, and 3)

by design, task-belief strength (the confidence that a chosen feature is behaviorally relevant) is

overall stronger following a rewarded trial than following an unrewarded trial, providing a

qualitative comparison with which to understand the implications of fluctuating belief state.

Another key aspect of our approach was to use neural population responses to decode

continuous measurements of each stimulus feature and the monkeys' task-belief on each trial.

We therefore recorded from groups of neurons from which we could decode information about

both visual features (in visual cortical area V1) and task-belief (in parietal area 7a (Kamigaki,

Fukushima and Miyashita, 2009; Stoet and Snyder, 2004)) (Figure 1C). Together, these

behavioral and physiological measurements provide a unique window into belief updating and

perceptual decision-making on every trial.

The animals learned this task and performed it well. After training, the animals successfully

discriminated the feature change they believed to be relevant and largely ignored the feature

believed to be irrelevant (Figure 2A). They also effectively updated their belief according to the

evolving task requirements, switching tasks only a couple of trials after the (uncued) task

changes occurred (Figure 2B). The number of trials the animals took to notice task changes was

close to optimal given their perceptual sensitivity (Figure 2C, see *Normative behavioral model* in

STAR Methods for the optimal behavioral model).

Figure 1. Behavioral paradigm and electrophysiological recording. (**A**) Schematic of the two-interval, two-feature discrimination task with stochastic task switching. On each trial, monkeys discriminate the difference in either spatial frequency or spatial location between two subsequent Gabor stimuli. The relevant feature is uncued and changes with 2.5% probability on each trial. The monkeys indicate their perceptual decision and the feature believed to be relevant by making a saccade to one of four choice targets. (**B**) and are rewarded for correctly reporting the sign of the change in the relevant feature. (**C**) Belief-based decisions could potentially be solved by independent hierarchical processes that compute belief and perception (black boxes). While the animals do the task, we simultaneously recorded population activity from one representative brain region related to each process (7a and V1 respectively, blue squares show approximate implant locations) to test the hypothesis that these processes are not separable (red arrow).

Perception covaries with task-belief strength

Behaviorally, we found that dynamically changing task-beliefs affect the accuracy of perceptual decision-making. By design, the animals' perceptual choices (as opposed to task choices) are informed by stimulus information within each trial and should ideally be independent from trial history. However, across experimental sessions (focusing on subsets of

trials with the same stimulus conditions), the animals had better perceptual performance (i.e.,

perceptual accuracy of whichever task the animal chose to perform) after rewarded trials (which

reinforced task-belief) than after unrewarded trials (which would weaken the monkeys' task-

belief; Figure 2G upper panel, Figure S2A).

Multiple lines of evidence suggest that the monkeys' worse perceptual accuracy following a

non-reward was due to a subsequent reduction in the animals' certainty about their task belief.

The perceptual worsening following non-reward is not explained by a potential tendency to make

consecutive perceptual errors. Perceptual performance was still higher following perceptually-

correct unrewarded trials (i.e. when subjects made correct perceptual decisions on the believed

relevant feature, but the task-belief was wrong) than following task errors (Figure S2E). Further,

the worsening of perceptual performance was even stronger following an easy perceptual

decision without reward. Among trials following non-rewards, perceptual performance was

worse when there was an obvious perceptual change in believed relevant feature, which

comprised stronger evidence against the current task-belief, than when the feature change was

ambiguous (i.e. weaker evidence against the task-belief; Figure S2F). Finally, the association

between strong task-belief and improved perception persisted even when taking task-switch cost

and task-set inertia (Alport, Styles and Hsieh, 1994) into account (Figure S2C-D).

Correspondingly, the monkeys' perceptual choices were more strongly related to V1 activity

following rewarded than unrewarded trials (Figure S2B).

Investigating the origin of the relationship between task-belief and perceptual accuracy

The observation that perceptual performance is related to task-belief can be explained by

three broad, non-mutually exclusive hypotheses. First, it could represent a good strategy. This

could occur if something about the structure of our task makes it more optimal to adopt a

strategy that results in a relationship between perceptual performance and belief strength.

Second, it could represent poor training or confusion, such as if the monkeys did not fully

understand some aspect of the task. In this scenario, what we called weak task-belief would

imply even more confusion, resulting in worse perceptual performance. Finally, this relationship

could come from biology. The monkeys' behavior could be constrained by a fundamental

biological (potentially indirect) interaction between the neurons that encode task-belief strength

and those that encode the visual features.

Figure 2. Trained behavior of animals and recurrent neural networks. (**A**) Psychometric curves showing the monkeys' perceptual choice proportion as a function of spatial frequency (left panel) and spatial location (right panel) differences. The flat curves for the irrelevant feature show that animals successfully ignored irrelevant visual information. (**B**) Distribution of number of trials it took the monkeys to adapt to task changes across experimental sessions (mean 3.1 trials). (**C**) Distribution of number of trials the monkey took to adapt to the task change relative to an ideal observer model (see STAR Methods) (mean 1.5 trials). Positive values refer to occasions where monkeys were slower than the model; negative values indicate that the monkeys were accidentally faster. (**D**) Schematic of the inputs and outputs of the network. The network receives sequential inputs containing information about stimulus changes, past model choices, and choice feedback (reward history) over the course of the last several trials. Like the monkey, the network model is trained to infer the implicit task rule from recent history and make corresponding decisions. (**E**) Similar to the monkeys' behavior in (A), the choices of a trained network are informed by the believed relevant feature information (solid line), while independent of

the believed irrelevant feature information (dashed line). (**F**) Distribution of differences
between reward rates between RNN and the monkeys across experiment session. Overall
the RNN obtained more reward than the monkeys in the same experiment sessions. (**G**)
Comparing perceptual performance following rewarded trials (abscissa) and unrewarded
trials (ordinate) for monkeys (upper panel) and the recurrent network model (lower panel).
Each point represents one stimulus condition of an experimental session, and we compute
perceptual performance based on the subjectively chosen task, regardless of whether that
task-belief was correct. Upper panel, the monkeys' perceptual performance is better
following rewarded trials than unrewarded trials. The distribution lies significantly below
the unity line ($p<10^{-6}$ for both monkeys and both features), showing lower perceptual
performances following a non-rewarded trial than following a rewarded trial, with the
same perceptual difficulty. Lower panel, the perceptual performance of the artificial
network does not significantly depend on feedback history ($p>0.05$ for both features). (**H**)
The difference between the monkey and network model is not explained by different extent
of training. The upper panel shows that the loss function decreased during time, indicating
the gradual learning process of the model on the task. In the lower panel, the black line
indicates the network model's difference between perceptual performance following
rewarded and unrewarded trials at each point of training. The red line indicates the
corresponding difference in the monkeys' perceptual performance, which always lies
outside the 90% confidence interval for the model (gray shading).

To investigate the plausibility of each of these hypotheses, we trained recurrent neural

networks (RNNs) to perform the same behavioral task. Although RNNs learn very differently

than real brains, they have the advantage that we could control the inputs, training history, and

motivation (the model is optimized only to gain rewards, not for any other motivation,

distraction, or effort that might influence human or monkey behavior). Like the monkeys, the

RNNs had information about both the visual stimuli on the current trial and the recent trial

history, and were required to infer the relationship between those inputs and the correct behavior

(Figure 2D). We chose the amount of noise associated with the sensory input to the model so that

the model and the monkeys have the same overall perceptual accuracy (Figure 2, A and E).

The behavior of the trained recurrent neural networks bears many similarities to the

monkeys' behavior. Like the monkeys, the network can distinguish relevant information from

irrelevant information (Figure 2E) and can efficiently detect task changes and adjust behavior

accordingly (Figure S3C). But unlike the monkeys, the network showed no relationship between

perceptual performance and the reward history (Figure 2G).

These results are broadly inconsistent with the first two hypotheses. If the relationship

between perception and belief were advantageous for receiving rewards, the enforced identical

overall perceptual accuracy between monkey and model would mean that overall, the monkeys

would receive more rewards than the model. We found the opposite: RNNs had higher reward

rates than the monkeys (Figure 2F). If, in contrast, the relationship between perception and belief

reflected the monkeys' incomplete understanding of the task or poor training, we would expect

the model to show this relationship early in training. We found the opposite: the network model

never displayed a significant relationship between perceptual performance and past feedback

during any stage of training (Figure 2H). These results demonstrate that better perceptual

performance after rewarded than after unrewarded trials is neither a necessary aspect of

performing this task, nor is it a necessary intermediate learning stage. Instead, they support the

third hypothesis, suggesting that the difference between monkeys and models reflects the

biological realities of how brains calculate task-belief and perception.

Figure 3. Neuronal measures of belief strength. (**A**) In a high dimensional neuronal space expanded by the activity of 7a units during the delay period, we find the best hyperplane to discriminate the task the animal performed on the trial. We define our single-trial neuronal measure of belief strength as the Euclidean distance from 7a population activity on each trial to the hyperplane. (**B**) Task-belief decoded from a neuronal population. Task-belief can be better classified by a linear hyper plane from area 7a population activity following rewarded than unrewarded trials. The abscissa and ordinate of each point show the performance of a linear classifier following rewarded and unrewarded trials respectively, with leave-one-out cross-validation. Each point represents one experimental session. (**C**) Belief strength is schematized as the distance from a rolling ball to a boundary. for trials leading up to the animals' decision to switch tasks, the average belief strength decreased monotonically, changed sign right at the point the monkey decided to switch tasks and recovered as the new task-belief was reinforced (histograms in bottom panel). Normalized activity of task-selective 7a units tracked the same dynamics as decoded belief around task switches (lines in bottom panel). Error bars indicate standard errors.

We therefore investigated potential neuronal interactions between task-belief strength and the

representation of relevant and irrelevant features in visual cortex in V1. To test this hypothesis

on a trial-by-trial basis, we looked for the neuronal correlate of task-belief in the activity of

populations of neurons in area 7a of parietal cortex, which encodes task-related information

(Stoet and Snyder, 2004; Kamigaki, Fukushima and Miyashita, 2009) and may mediate effects of

trial history on perceptual choices (Akrami *et al.*, 2018).

We reasoned that the worse perceptual performance following non-rewards might imply a

moment-by-moment relationship between the monkeys' internal belief state and the way the

relevant and/or irrelevant visual feature is encoded in the brain. We therefore investigated how

belief estimates in 7a relate to how visual information is encoded in V1 on a trial-by-trial basis.

We used area 7a to decode our estimate of the animals' belief state because, using a linear

decoder, we were able to predict the animals' choice of tasks significantly better from area 7a

than from area V1 (Figure S1B lower panel, S1C).

We decoded a continuous measure of the animals' task-belief from the population of neurons

in area 7a on each trial (Figure 3A), and these estimates were related to behavior in reassuring

ways. Consistent with the idea that rewards lead to stronger beliefs, the animals' choice of which

task to perform was better classifiable from area 7a after rewarded than an unrewarded trials

(Figure 3B). Decisions to switch tasks were associated with a dynamic change in decoded task-

belief away from the old task and toward the new task (Figure 3C).

We estimated the encoding of each visual feature on each trial using V1 population responses

(Figure 4A), and these measurements were also related to behavior in intuitive ways. As

expected, when comparing trials using the same stimuli (i.e. same difficulty), trials with larger

relevant feature discriminability yield better perceptual performance (Figure S1E-F).

Armed with a neuronal estimate of task-belief and the change in each visual feature on each

trial, we looked for interactions between them. Specifically, we tested the hypothesis that strong

task-beliefs are associated with stronger encoding of the believed-relevant, but not the believed-

irrelevant feature. For each task-belief and stimulus condition, we therefore measured the

correlation between belief strength measured from area 7a and perceptual discriminability

measured in V1 (Figure 4B). Despite the fact that the resulting correlation is based on few trials

and only a few dozen neurons across two very weakly connected areas (Markov *et al.*, 2014), we

found evidence supporting our hypothesis. There is a positive correlation between belief and the

encoding of each feature when it is believed to be relevant, but not when that same feature is

believed to be irrelevant (Figure 4C-D). Together, our results indicate that belief-based decision

making is an integrated system rather than a separable two-stage computation in which a task

decision is followed by a corresponding perceptual decision.

Figure 4. Belief and perception are linked on a trial-by-trial basis. (**A**) Using a
procedure similar to that described in Figure 3A, we define the perceptual discriminability
of each stimulus feature change on each trial as the Euclidean distance from V1 population
activity to the hyperplane that best classifies the stimulus change of that feature (e.g.,
higher vs. lower spatial frequency). (**B**) Trial-by-trial comparison between belief strength

(abscissae, decoded from 7a) and perceptual discriminability (ordinates, decoded from V1)
for an example stimulus/task condition. If belief decisions and perceptual decisions are
implemented by separate functional circuits of the brain, then internal fluctuations of the
two systems should have no correlation. (**C**) The belief- spatial location discriminability
correlation is positive when spatial location is believed to be relevant (histogram and
magenta cumulative distribution curve, $p=4\times10^{-6}$), but not when it is believed to be
irrelevant (cyan cumulative distribution curve, $p>0.05$). The two distributions are
significantly different (Wilcoxon rank sum test, $p=0.014$). (**D**) Similarly, belief- spatial
frequency discriminability is significantly positive when spatial frequency is believed to be
relevant ($p=0.0015$) but not when it is believed to be irrelevant ($p>0.05$). The two
distributions are significantly different (Wilcoxon rank sum test, $p=0.03$).

V1 fluctuations affect belief updating

In addition to the trial-by-trial interaction between belief and perception, two pieces of

evidence demonstrate that perception on the previous trial affects how task-belief is updated for

the upcoming trial. First, trial information beyond reward outcome affects how task-belief will

be updated. On average, the monkeys were more likely to switch tasks after they missed rewards

on trials with big changes in the stimulus feature believed to be relevant (Figure S4C). This

reliance of belief updating on vision is captured by our ideal observer model which optimally

updates task-belief based on historical reward, stimulus, and choices (see Methods and Figure

S4A). The ideal observer model consistently predicts the animals' behavior better than an

alternative strategy in which every unrewarded trial affects belief independent of visual and

choice experience (Figure S4B). Consistent with findings from studies with similar task structure

(Purcell and Kiani, 2016a; Sarafyazd and Jazayeri, 2019), our results demonstrate that belief

updating is related to the Bayesian posterior probability that the past perceptual decisions were

correct, given the evidence contributing to them.

Second, even for sets of ostensibly identical trials (with the same stimulus, choice, and

reward), there was a trial-to-trial relationship between fluctuations in the representations of the

visual stimuli and belief updating. We used a neuronal population version of the classic single-

neuron neurometric curve (Newsome, Britten and Movshon, 1989) to relate fluctuations in the

visual cortex to perceptual decision-making. For groups of trials with the same first stimulus,

given the perceptual discriminability decoded from V1 population responses to the second

stimulus (as in Figure 4A), we calculated the probability of each feature change direction using

logistic regression (Figure 5A, similar to the strategy in (Peixoto *et al.*, 2021). The population

neurometric curve provided a neuronally-derived confidence about the perceptual choice on each

trial. That confidence estimate was related to the animals' task switching behavior (Figure 5B).

These methods revealed that trial-by-trial fluctuations in visual cortex are related to task

switching behavior. A normative model based on the neuronally-derived perceptual confidence

on each trial (see STAR Methods) predicts the animals' behavior better than a comparable model

that assumes all trials within the same trial condition (stimuli, choice, outcome) have the same

perceptual confidence (Figure S4E). Furthermore, if we shuffle V1 responses among trials with

identical trial conditions (Figure 5C), the model's switch prediction performance suffers

significantly (Figure 5D-E). Consistently, unrewarded trials with V1 fluctuations indicating

stronger perceptual confidence are more often followed by task switches on the following trial

than unrewarded trials with the same trial condition but with V1 fluctuations indicating weaker

perceptual confidence (Figure S4D). Together, these results demonstrate that trial-to-trial

fluctuations in perception affect belief updating on the subsequent trial, even though these

fluctuations provide no benefit for estimating the relevant feature.

Figure 5. Trial to trial variability in visual cortex affects belief updating. (**A**) Example neurometric curve showing the ability of a decoder to discriminate spatial frequency changes from the population of recorded V1 neurons using logistic regression on the perceptual discriminability of spatial frequency (as in Figure 4A). (**B**) Based on perceptual confidence on each trial (estimated from V1 population activity), a normative model determines whether the subject should switch tasks given the trial history (see STAR Methods). (**C**) Based on the V1 projections to the relevant feature subspace on each trial, we estimate from the neurometric curve, which represents the probability the monkey's behavioral choice is correct (i.e. perceptual confidence (Hangya, Sanders and Kepecs, 2016)). In the trial-shuffle analysis, we randomly switch the confidence within trials with the same conditions (dots with same color). (**D**) Model predictions after trial-shuffle, conventions as in (b). (**E**) Trial-to-trial variability in V1 is related to belief. The models' sensitivity indices (*d'*) measures the performances predicting whether the monkey would switch tasks in a session. The histogram shows the differences in the *d'*s of models using the actual and trial-shuffled V1 activity. Across experimental sessions, shuffling V1

347   activity among trials with identical conditions limited the model's capability to predict the
348   monkeys task-switching behavior ($p=5\times10^{-4}$).

Discussion

Perceptual decision-making has long been studied as an independent cognitive process since

it typically occurs on a much faster time scale than the dynamics of higher-level cognitive

processes like belief, arousal, and learning. However, our findings demonstrate that there is no

such thing as a standalone perceptual decision-making process: every aspect of perceptual

decision-making is profoundly integrated with the dynamic task-belief states that dominate

natural behavior. We found the relationship between task-belief and perception to be

bidirectional.

First, we demonstrated that fluctuating task-beliefs affect perceptual performance. Using a

combination of multi-neuron, multi-area physiology, complex but controlled behavior, and

hypothesis-driven dimensionality reduction, we demonstrated that perception and task-belief are

intimately intertwined such that weak task-beliefs are associated with poor perception of task-

relevant information. This suggests that instead of a homogenous mechanism such as arousal,

task-belief strength is selectively associated with the processing of believed-relevant

information.

The specific cognitive origin of such flexible task-belief-specific modulation remains to be

investigated. Potential neuronal mechanisms may include a limit in working memory capacity

(Cowan, 2016; Bouchacourt and Buschman, 2019), a reinforcement learning mechanism in

perceptual decision-making (Lak *et al.*, 2020a; Mendonça *et al.*, 2020; Lak *et al.*, 2020b), a

tradeoff between stable encoding and cognitive flexibility (Driscoll et al., 2017), a neuronal

mechanism that limits reinforcement learning to the relevant feature (Niv et al., 2015), flexible

geometry of sensory representations (Bernardi et al., 2020; Okazawa et al., 2021), or a feedback-

induced change in the structure of correlated variability (Bondy, Haefner and Cumming, 2018).

In future work, it will be interesting to determine whether fluctuations in the dynamic weighting

of different sources of information (Gu, Angelaki and Deangelis, 2008; Raposo et al., 2012) or

other types of beliefs (e.g. those reviewed in Ma and Jazayeri, 2014) interact with perceptual

decision-making in similar ways as task beliefs.

Second, we demonstrated that fluctuations in perceptual decision-related neuronal activity

affect belief updating. This aspect brings new insights to the current knowledge about cognitive

flexibility from studies using unambiguous stimuli, and therefore has very little perceptual

involvement (Ravizza and Carter, 2008; Botvinick and Braver, 2015; Bartolo and Averbeck,

2020). Using perceptually challenging tasks is not only more realistic, but also offers powerful

tools to investigate, manipulate, and quantitatively understand the specific neuronal process

governing perception and belief updating. Our study demonstrates that incorporating these more

natural behavioral features into well-controlled laboratory studies leads to important new

insights.

In this regard, our findings are merely a starting point of a wide range of potential scientific

explorations that will shed light on cognitive flexibility, belief-based decision-making, and

learning. For instance, uncertain inference of the task environment would require nonlinear

adaptive evidence accumulation (Murphy *et al.*, 2021), which could constrain models of

individual learning policies (Ashwood *et al.*, 2020). These approaches could help uncover the

mechanisms underlying the loss of cognitive flexibility in patients with neurodegenerative

disorders (Owen *et al.*, 1993; Albert, 1996; Gorno-Tempini *et al.*, 2004).

The inextricable link between dynamic task-beliefs and perceptual decision-making
highlights the importance of studying complex behavior as a whole (Juavinett, Erlich and
Churchland, 2018), rather than as stacked building blocks of simpler functions. Complex
behaviors likely involve a wide variety of cognitive states other than task-belief, consistent with
extensive reports of dynamic cognitive influences on decision-making, including reward
expectation (Cicmil *et al.*, 2015; Starkweather *et al.*, 2017), biases (Akaishi *et al.*, 2014; Talluri
et al., 2018; Mochol, Kiani and Moreno-Bote, 2021), working memory (Panichello and
Buschman, 2021), and mood (Yuen and Lee, 2003). Our work therefore showcases a potentially
widely applicable approach to study these dynamic, internal cognitive states, using carefully
designed cognitive tasks, and by investigating the interaction between these internal states and
decision-making on single trials using neuronal population activity. This approach can
potentially bring important insights into the fundamental neuronal mechanisms underlying
flexible behavior.

Our results also open up exciting avenues for translational therapies that address deficits in
flexible decision-making associated with neuropsychiatric disorders. For instance, our results
imply that cognitive flexibility is mediated by interactions between neural populations
responsible for perception and task-belief. As such, therapies that affect communication between
brain areas (e.g. by affecting neurotransmitters like dopamine (Botvinick and Braver, 2015;
Mueller *et al.*, 2017) have the potential to improve cognitive flexibility in health and disease.
Indeed, stimulants that affect the dopamine system like methylphenidate or amphetamines can
change focus and flexibility (Bagot and Kaminer, 2014; Mueller *et al.*, 2017). Going forward,
studying the highly integrated belief-based decision-making system will open up doors to

potential treatments of conditions that affect cognitive flexibility and even solutions for healthy

individuals to become better decision-makers in volatile environments.

Acknowledgments

We are grateful to Karen McKracken for providing technical assistance and to Josh Gold, Lori

Holt, Douglas Ruff, Amy Ni, Ramanujan Srinath, and Morteza Sarafyazd for comments on an

earlier version of this manuscript. This work was supported by the Simons Foundation (Simons

Collaboration on the Global Brain award 542961SPI to MRC), the National Eye Institute of the

National Institutes of Health (awards R01EY022930 and R01NS121913

to MRC), and the McKnight Foundation (McKnight Scholar award to MRC).

Author contributions

426 C.X., and M.R.C. designed research; C.X., and L.E.K. performed research; C.X. performed data

427 analyses and computational modelling; M.R.C. supervised the findings of this work; C.X., and

428 M.R.C. wrote the paper.

Competing interests

430 The authors declare no competing interests.

Figure titles and legends

Figure 1. Behavioral paradigm and electrophysiological recording. (**A**) Schematic of
the two-interval, two-feature discrimination task with stochastic task switching. On each
trial, monkeys discriminate the difference in either spatial frequency or spatial location
between two subsequent Gabor stimuli. The relevant feature is uncued and changes with
2.5% probability on each trial. The monkeys indicate their perceptual decision and the
feature believed to be relevant by making a saccade to one of four choice targets. (**B**) and
are rewarded for correctly reporting the sign of the change in the relevant feature. (**C**)
Belief-based decisions could potentially be solved by independent hierarchical processes

that compute belief and perception (black boxes). While the animals do the task, we simultaneously recorded population activity from one representative brain region related to each process (7a and V1 respectively, blue squares show approximate implant locations) to test the hypothesis that these processes are not separable (red arrow).

Figure 2. Trained behavior of animals and recurrent neural networks. (**A**) Psychometric curves showing the monkeys' perceptual choice proportion as a function of spatial frequency (left panel) and spatial location (right panel) differences. The flat curves for the irrelevant feature show that animals successfully ignored irrelevant visual information. (**B**) Distribution of number of trials it took the monkeys to adapt to task changes across experimental sessions (mean 3.1 trials). (**C**) Distribution of number of trials the monkey took to adapt to the task change relative to an ideal observer model (see STAR Methods) (mean 1.5 trials). Positive values refer to occasions where monkeys were slower than the model; negative values indicate that the monkeys were accidentally faster. (**D**) Schematic of the inputs and outputs of the network. The network receives sequential inputs containing information about stimulus changes, past model choices, and choice feedback (reward history) over the course of the last several trials. Like the monkey, the network model is trained to infer the implicit task rule from recent history and make corresponding decisions. (**E**) Similar to the monkeys' behavior in (A), the choices of a trained network are informed by the believed relevant feature information (solid line), while independent of the believed irrelevant feature information (dashed line). (**F**) Distribution of differences between reward rates between RNN and the monkeys across experiment session. Overall the RNN obtained more reward than the monkeys in the same experiment sessions. (**G**) Comparing perceptual performance following rewarded trials (abscissa) and unrewarded trials (ordinate) for monkeys (upper panel) and the recurrent network model (lower panel). Each point represents one stimulus condition of an experimental session, and we compute perceptual performance based on the subjectively chosen task, regardless of whether that task-belief was correct. Upper panel, the monkeys' perceptual performance is better following rewarded trials than unrewarded trials. The distribution lies significantly below the unity line ($p<10^{-6}$ for both monkeys and both features), showing lower perceptual performances following a non-rewarded trial than following a rewarded trial, with the same perceptual difficulty. Lower panel, the perceptual performance of the artificial network does not significantly depend on feedback history ($p>0.05$ for both features). (**H**) The difference between the monkey and network model is not explained by different extent of training. The upper panel shows that the loss function decreased during time, indicating the gradual learning process of the model on the task. In the lower panel, the black line indicates the network model's difference between perceptual performance following rewarded and unrewarded trials at each point of training. The red line indicates the corresponding difference in the monkeys' perceptual performance, which always lies outside the 90% confidence interval for the model (gray shading).

Figure 3. Neuronal measures of belief strength. (**A**) In a high dimensional neuronal space expanded by the activity of 7a units during the delay period, we find the best hyperplane to discriminate the task the animal performed on the trial. We define our

single-trial neuronal measure of belief strength as the Euclidean distance from 7a population activity on each trial to the hyperplane. (**B**) Task-belief decoded from a neuronal population. Task-belief can be better classified by a linear hyper plane from area 7a population activity following rewarded than unrewarded trials. The abscissa and ordinate of each point show the performance of a linear classifier following rewarded and unrewarded trials respectively, with leave-one-out cross-validation. Each point represents one experimental session. (**C**) Belief strength is schematized as the distance from a rolling ball to a boundary. for trials leading up to the animals' decision to switch tasks, the average belief strength decreased monotonically, changed sign right at the point the monkey decided to switch tasks and recovered as the new task-belief was reinforced (histograms in bottom panel). Normalized activity of task-selective 7a units tracked the same dynamics as decoded belief around task switches (lines in bottom panel). Error bars indicate standard errors.

Figure 4. Belief and perception are linked on a trial-by-trial basis. (**A**) Using a procedure similar to that described in Figure 3A, we define the perceptual discriminability of each stimulus feature change on each trial as the Euclidean distance from V1 population activity to the hyperplane that best classifies the stimulus change of that feature (e.g., higher vs. lower spatial frequency). (**B**) Trial-by-trial comparison between belief strength (abscissae, decoded from 7a) and perceptual discriminability (ordinates, decoded from V1) for an example stimulus/task condition. If belief decisions and perceptual decisions are implemented by separate functional circuits of the brain, then internal fluctuations of the two systems should have no correlation. (**C**) The belief- spatial location discriminability correlation is positive when spatial location is believed to be relevant (histogram and magenta cumulative distribution curve, $p=4\times10^{-6}$), but not when it is believed to be irrelevant (cyan cumulative distribution curve, $p>0.05$). The two distributions are significantly different (Wilcoxon rank sum test, $p=0.014$). (**D**) Similarly, belief- spatial frequency discriminability is significantly positive when spatial frequency is believed to be relevant ($p=0.0015$) but not when it is believed to be irrelevant ($p>0.05$). The two distributions are significantly different (Wilcoxon rank sum test, $p=0.03$).

Figure 5. Trial to trial variability in visual cortex affects belief updating. (**A**) Example neurometric curve showing the ability of a decoder to discriminate spatial frequency changes from the population of recorded V1 neurons using logistic regression on the perceptual discriminability of spatial frequency (as in Figure 4A). (**B**) Based on perceptual confidence on each trial (estimated from V1 population activity), a normative model determines whether the subject should switch tasks given the trial history (see STAR Methods). (**C**) Based on the V1 projections to the relevant feature subspace on each trial, we estimate from the neurometric curve, which represents the probability the monkey's behavioral choice is correct (i.e. perceptual confidence (Hangya, Sanders and Kepecs, 2016)). In the trial-shuffle analysis, we randomly switch the confidence within trials with the same conditions (dots with same color). (**D**) Model predictions after trial-shuffle, conventions as in (b). (**E**) Trial-to-trial variability in V1 is related to belief. The models'

527 sensitivity indices (d') measures the performances predicting whether the monkey would
528 switch tasks in a session. The histogram shows the differences in the d's of models using
529 the actual and trial-shuffled V1 activity. Across experimental sessions, shuffling V1
530 activity among trials with identical conditions limited the model's capability to predict the
531 monkeys task-switching behavior ($p=5\times10^{-4}$).

STAR Methods

Resource Availability

Key resources table

REAGENT or RESOURCE	SOURCE	IDENTIFIER
Deposited data		
Original data	This paper	https://doi.org/10.6084/m9.figshare.19591012.v1
Experimental models: Organisms/strains		
Rhesus macaque (*Macaca mulatta*)	University of Pittsburgh	N/A
Software and algorithms		
Original analyses and modelling code	This paper	https://doi.org/10.6084/m9.figshare.19591012.v1
Psychophysics Toolbox	Brainard, 1997	http://psychtoolbox.org/
MATLAB	The MathWorks.	https://www.mathworks.com/products/matlab.html
PsychRNN	Ehrlich *et al.*, 2021	https://psychrnn.readthedocs.io/en/latest/
Tensorflow	Abadi *et al.*, 2016	https://www.tensorflow.org

Lead contact: Further information and requests for resources should be directed to and will be fulfilled
by Marlene Cohen (cohenm@pitt.edu), Department of Neuroscience and Center for Neural Basis of
Cognition, University of Pittsburgh, Pittsburgh, PA, 15260, USA.

Materials availability: This study did not generate new unique reagent.

Data and code availability:

Related data, along with original code, have been deposited at figshare and are publicly available as of
the date of publication. Accession numbers are listed in the key resources table.

Any additional information required to reanalyze the data is available from the lead contact upon
reasonable request.

Experimental subjects

The subjects in our study were two adult male rhesus monkeys (*Macaca mulatta*, monkey F weighed 12 kilograms, monkey G weighed 9 kilograms), who were both experimentally naïve prior to the current experiments. All animal procedures were approved by the Institutional Animal Care and Use Committees of the University of Pittsburgh and Carnegie Mellon University. After we implanted each animal with a titanium head post, they were trained to perform two-interval, two-feature discrimination with stochastic rule switching (Figure 1A-B) (monkey F was trained for 11 months, monkey G for 9 months). We made sure the animals understood the essential requirements of the task based on their behavior (Figure 1C-D), before implanting each animal with 6×8 microelectrode arrays (Blackrock Microsystems) in both parietal cortical area 7a and visual cortical area V1. Each array was connected to a percutaneous connector that allowed daily electrophysiological recordings. The distance between adjacent electrodes was 400 µm, and each electrode was 1 mm long. We implanted 7a arrays on the crown of gyrus between intraparietal sulcus and superior temporal sulcus at approximately 11mm lateral to the midline; and V1 arrays posterior to the lunate sulcus at approximately -13 mm to the intra-aural line and 7 mm lateral to the midline (Figure 1C).

Behavioral task

To study perceptual decision making under evolving task-beliefs in dynamic environment, we trained the animals to perform a two-interval, two-feature discrimination task with stochastic task switching. A trial began when the subjects fixated their gaze on a central dot on the screen and they were required to maintain fixation as long as the dot remained on the screen, or the trial would be aborted and unrewarded. A Gabor stimulus was then displayed for 200 ms. After a random delay (300ms to 500ms), a second Gabor stimulus was displayed for 200 ms with a slightly different spatial location (shifted left or right) and a slightly different spatial frequency (higher or lower), with independently randomized change amounts in the two features. The ranges of change amounts are titrated at the beginning of each session so that the overall perceptual performances of the spatial location task and spatial location task are both approximately 75%. Following a subsequent delay of 150ms, the fixation dot disappeared, and the animals were required to make a saccade to one out of four peripheral targets to indicate both the inferred relevant feature and the direction of change in that feature. The two cyan targets correspond to the increase and decrease of spatial frequency when it was believed to be the relevant feature, while the two magenta targets correspond to the left-shift and right-shift of spatial location. The location of the array of targets varied across experimental sessions but remained the same within each session. The monkeys were rewarded only if they correctly reported the direction of change in the relevant feature. The visual stimuli throughout a trial contain no information about the behavioral relevance of features. The relevant feature switches on a randomly chosen 2.5% of trials. The monkeys therefore needed to infer the relevant feature based on their choice and reward history.

Electrophysiological recording

All visual stimuli were displayed on a linearized CRT monitor (1,024 × 768 pixels, 120-Hz refresh rate) placed 57 cm from the animal. We monitored eye position using an infrared eye tracker (Eyelink 1000, SR Research) and used custom software (written in Matlab using the Psychophysics Toolbox(Brainard, 1997) to present stimuli and monitor behavior. We recorded eye position and pupil diameter (1,000 samples per s), neuronal responses (30,000 samples per s) and the signal from a photodiode to align neuronal responses to stimulus presentation times (30,000 samples per s) using hardware from Ripple.

We recorded neuronal activity from Utah arrays during daily experimental sessions for several months in
each animal (90 sessions from monkey F and 62 sessions from monkey G). We set the threshold for each
channel at three times the standard deviation and used threshold crossings as the activity on that unit.
We positioned the stimuli to maximize the overlap between potential stimulus locations and the joint
receptive fields of V1 units, as determined using separate data collected while the monkeys fixated and
Gabor stimuli were flashed across a range of retinal positions. Less than 5% of the recorded 7a units had
clear receptive fields that we could measure. Those that did had contralateral receptive fields ~30
degrees in the periphery, which is far away from the Gabor stimuli and the visual targets. We confirmed
that during the experiment, the recorded 7a units did not respond selectively to different stimuli (Figure
S1B, upper panel).

We included experimental sessions for analyses of neuronal data if they contained at least 480
completed trials (where monkeys successfully maintained fixation until they indicated their choice). We
analyzed the activity of area 7a units during the first 300ms after the offset of the first stimulus, when
there is no Gabor stimulus on the screen; and the activity of area V1 units during stimulus display
periods, shifted with 34 ms visual latency. Units from area 7a were included if their activity during the
average delay period was at least 5 sp/s. Units from V1 were included in the analyses if their average
stimulus response was 1) at least 25% larger than baseline activity, measured 100ms before stimulus
onset, and 2) larger than 5 sp/s. These procedures resulted in 77 sessions from Monkey F and 58
sessions from Monkey G. The median unit counts are 47 in area 7a, 30 in V1. The median trial number in
a session is 1086.

Recurrent Neural Network

We trained recurrent neural networks to perform the two-interval, two-feature discrimination task with
stochastic task switching. Similar to the monkeys, the network model was trained to infer the relevant
feature and make the correct perceptual discrimination based on the implicit task rule. The training and
testing of the neural network were implemented with custom code based on the open source package
PsychRNN (Ehrlich *et al.*, 2021) and Tensorflow (Abadi *et al.*, 2016). The model consists of 100 units with
all-to-all recurrent connections, without any a priori constraints on the connection weights. All results
are qualitatively consistent with network sizes of 50 or 200 units.

To produce a choice on each iteration, the recurrent neural network receives input from four channels
(Figure 2D): the spatial location change, the spatial frequency change, the recent choice history of the
model, and the reward feedback associated with those choices. The recurrent neural network is
connected to four output units, which correspond to the four saccade targets presented to the monkey.
We take the output unit with the highest activity during choice period as the behavioral choice of the
model. Gaussian noises were added to the stimulus changes so that the overall perceptual
performances of the model would match those of the monkey (Figure 2E). We trained the model using
custom code modified from PsychRNN that allowed the model's previous choice output to be part of the
trial history input for the following trials. The past trial history information was fed into the network in
chronological order: each trial starts with the stimulus changes followed by (in order) the choice the
model made on the previous iteration, the reward feedback, and finally an intertrial interval before
processing information from the next trial. For the model results shown in Figure 2 and Figure S3, the
neural network considered a trial history of 7 trials before the current trial, which is longer than most of

the monkeys' task-switch delays. The network behaviors shown in Figure 2 and Supplementary Figure S3
are qualitatively similar if the history input contained 4 trials or 10 trials before the current trial.

The loss function is defined as the squared error between the network output and the target output
during the choice period. The target output is 1 on the output unit of the correct choice, and 0 for the
other three output units. We initialized the weight matrix with random connections and used a learning
rate of 0.001 during training.

Population analyses

To obtain a continuous neuronal measure of the animals' belief state, we analyzed the activity of the
population of 7a neurons during the delay period in a high dimensional space in which the activity of
each unit was one dimension. We used linear discriminant analysis to identify the best hyperplane to
discriminate between 7a population activity on trials where monkeys chose spatial location targets from
trials when they chose spatial frequency targets. We defined the belief strength on each trial as the
Euclidean distance from the 7a population response to the discriminant hyperplane. Similarly, we
obtained a continuous neuronal measure of the discriminability of stimulus change using V1 activity.

Statistical tests

All p-values reported in this study are from Wilcoxon signed rank test unless otherwise specified.

Normative behavioral model

We use a normative model to characterize belief updating of an ideal observer, given the trial history
and the perceptual ability of the monkey (Sarafyazd and Jazayeri, 2019; Purcell and Kiani, 2016a; Glaze
et al., 2018). Based on the monkeys' psychometric curve in an experiment session and the change
amount of the chosen feature in each trial, we estimated the trial-by-trial probability that their
perceptual choice was incorrect. For a non-reward trialed, the odds of likelihoods that the actual task is
different from the monkeys' subjective belief is given by

$$\frac{p(diff|nr,\theta,c)}{p(same|nr,\theta,c)} = \frac{p(nr,\theta,c|diff) \cdot p(diff)}{p(nr,\theta,c)} \cdot \frac{p(nr,\theta,c)}{p(nr,\theta,c|same) \cdot p(same)} = \frac{p(nr,\theta,c|diff)}{p(nr,\theta,c|same)}$$

where θ and c refer to the stimulus change amount and perceptual choice in the feature the monkeys
believed to be relevant; and nr refers to a non-reward trial outcome. We assumed that overall, the
monkeys experienced an equal number of trials where the feature was the same or different from their
current belief (i.e., $p(diff) = p(same)$). The monkeys were never rewarded on trials when their
subjective task-belief was different from the actual task rule, so $p(nr,\theta,c|diff) = 1$. Meanwhile when
subjective task-belief is consistent with the actual rule, the probability of perceptual error can be simply
derived from the psychometric function associated with that choice:

$$\frac{p(diff|nr,\theta,c)}{p(same|nr,\theta,c)} = \frac{1}{1 - p(\theta|c)}$$

674 where $p(\theta|c)$ is the psychometric function associated with the perceptual choice c (Figure 1C). In Figure
675 4, the psychometric function is replaced with the neurometric function (Figure 4A, also see *Population*
676 *analyses* section).

678 For n consecutive non-reward trials, the likelihood ratio grows larger as perceptual evidence for a task
679 switch grows as

$$\frac{1 - \mathcal{L}_n^{same}}{\mathcal{L}_n^{same}} = \prod_{i=1}^{n} \frac{1}{1 - p(\theta_i | c_i)}$$

680 where $\mathcal{L}_n$ is the likelihood that the task has not changed after n consecutive non-rewarded trials
681 (examples in Figure S4A left panel). Aside from perceptual evidence, the observer presumably also has
682 prior knowledge about the volatility of the task environment. After n consecutive non-reward trials, the
683 prior probability that the task stays the same with the last rewarded trial is

$$Pr_n^{same} = Pr_{n-1}^{same} \cdot (1 - h) + (1 - Pr_{n-1}^{same}) \cdot h$$

684 where h represents the hazard rate of task change at each trial (for an ideal observer, $h = 0.025$, see
685 *behavioral task* section), with

$$Pr_0^{same} = 1 - h$$

686 Examples of Pr_n^{same} under different environment volatility are shown in Figure S4A middle panel. Taking
687 both perceptual evidence and prior knowledge of environment volatility into account, the model shows
688 that an ideal observer should switch tasks if the posterior probability is higher for actual task rule being
689 different from the subjective task-belief than when they are the same (Figure S4A right panel), i.e.:

$$switch\ odds = \log((1 - Pr_n^{same}) \cdot (1 - \mathcal{L}_n^{same})) - \log(Pr_n^{same} \cdot \mathcal{L}_n^{same}).$$

when positive, switch task

References:

Abadi, M., Agarwal, A., Barham, P., Brevdo, E., Chen, Z., Citro, C., Corrado, G. S., Davis, A.,
Dean, J. and Devin, M. (2016) 'Tensorflow: Large-scale machine learning on heterogeneous
distributed systems', *arXiv preprint arXiv:1603.04467*.
Akaishi, R., Umeda, K., Nagase, A. and Sakai, K. (2014) 'Autonomous mechanism of internal
choice estimate underlies decision inertia', *Neuron,* 81(1), pp. 195-206.
Akrami, A., Kopec, C. D., Diamond, M. E. and Brody, C. D. (2018) 'Posterior parietal cortex
represents sensory history and mediates its effects on behaviour', *Nature,* 554(7692), pp. 368-
372.
Albert, M. S. (1996) 'Cognitive and neurobiologic markers of early Alzheimer disease', *Proc*
Natl Acad Sci U S A, 93(24), pp. 13547-51.
Alport, A., Styles, E. A. and Hsieh, S. (1994) '17 Shifting Intentional Set: Exploring the
Dynamic Control of Tasks'.
Ashwood, Z., Roy, N. A., Bak, J. H. and Pillow, J. W. (2020) 'Inferring learning rules from
animal decision-making', *Advances in Neural Information Processing Systems,* 33.
Ashwood, Z. C., Roy, N. A., Stone, I. R., Urai, A. E., Churchland, A. K., Pouget, A., Pillow, J.
W. and The International Brain, L. (2022) 'Mice alternate between discrete strategies during
perceptual decision-making', *Nature Neuroscience,* 25(2), pp. 201-212.
Bagot, K. S. and Kaminer, Y. (2014) 'Efficacy of stimulants for cognitive enhancement in non-
attention deficit hyperactivity disorder youth: a systematic review', *Addiction,* 109(4), pp. 547-
57.

Bartolo, R. and Averbeck, B. B. (2020) 'Prefrontal Cortex Predicts State Switches during Reversal Learning', *Neuron,* 106(6), pp. 1044-1054.e4.

Botvinick, M. and Braver, T. (2015) 'Motivation and cognitive control: from behavior to neural mechanism', *Annu Rev Psychol,* 66, pp. 83-113.

Brady, K. T., Gray, K. M. and Tolliver, B. K. (2011) 'Cognitive enhancers in the treatment of substance use disorders: clinical evidence', *Pharmacol Biochem Behav,* 99(2), pp. 285-94.

Brainard, D. H. (1997) 'The Psychophysics Toolbox.', *Spatial vision,* 10(4), pp. 433-6.

Buschman, T. J., Denovellis, E. L., Diogo, C., Bullock, D. and Miller, E. K. (2012) 'Synchronous oscillatory neural ensembles for rules in the prefrontal cortex', *Neuron,* 76(4), pp. 838-846.

Cicmil, N., Cumming, B. G., Parker, A. J. and Krug, K. (2015) 'Reward modulates the effect of visual cortical microstimulation on perceptual decisions', *Elife,* 4, pp. e07832.

Cohen, M. R. and Maunsell, J. H. (2011a) 'Using neuronal populations to study the mechanisms underlying spatial and feature attention', *Neuron,* 70(6), pp. 1192-204.

Cohen, M. R. and Maunsell, J. H. (2011b) 'When attention wanders: how uncontrolled fluctuations in attention affect performance', *J Neurosci,* 31(44), pp. 15802-6.

Dickstein, D. P., Nelson, E. E., McCLURE, E. B., Grimley, M. E., Knopf, L., Brotman, M. A., Rich, B. A., Pine, D. S. and Leibenluft, E. (2007) 'Cognitive flexibility in phenotypes of pediatric bipolar disorder', *J Am Acad Child Adolesc Psychiatry,* 46(3), pp. 341-355.

Ebitz, R. B., Tu, J. C. and Hayden, B. Y. (2020) 'Rules warp feature encoding in decision-making circuits', *PLoS Biol,* 18(11), pp. e3000951.

Ehrlich, D. B., Stone, J. T., Brandfonbrener, D., Atanasov, A. and Murray, J. D. (2021) 'PsychRNN: An Accessible and Flexible Python Package for Training Recurrent Neural Network Models on Cognitive Tasks', *eNeuro,* 8(1).

Glaze, C. M., Filipowicz, A. L., Kable, J. W., Balasubramanian, V. and Gold, J. I. (2018) 'A bias–variance trade-off governs individual differences in on-line learning in an unpredictable environment', *Nature Human Behaviour,* 2(3), pp. 213-224.

Gold, J. I. and Shadlen, M. N. (2007) 'The neural basis of decision making', *Annu Rev Neurosci,* 30, pp. 535-74.

Gorno-Tempini, M. L., Rankin, K. P., Woolley, J. D., Rosen, H. J., Phengrasamy, L. and Miller, B. L. (2004) 'Cognitive and behavioral profile in a case of right anterior temporal lobe neurodegeneration', *Cortex,* 40(4-5), pp. 631-644.

Hangya, B., Sanders, J. I. and Kepecs, A. (2016) 'A Mathematical Framework for Statistical Decision Confidence', *Neural Comput,* 28(9), pp. 1840-58.

Juavinett, A. L., Erlich, J. C. and Churchland, A. K. (2018) 'Decision-making behaviors: weighing ethology, complexity, and sensorimotor compatibility', *Curr Opin Neurobiol,* 49, pp. 42-50.

Kable, J. W. and Glimcher, P. W. (2009) 'The neurobiology of decision: consensus and controversy', *Neuron,* 63(6), pp. 733-45.

Kamigaki, T., Fukushima, T. and Miyashita, Y. (2009) 'Cognitive set reconfiguration signaled by macaque posterior parietal neurons', *Neuron,* 61(6), pp. 941-51.

Lak, A., Hueske, E., Hirokawa, J., Masset, P., Ott, T., Urai, A. E., Donner, T. H., Carandini, M., Tonegawa, S., Uchida, N. and Kepecs, A. (2020a) 'Reinforcement biases subsequent perceptual decisions when confidence is low, a widespread behavioral phenomenon', *Elife,* 9.

Lak, A., Okun, M., Moss, M. M., Gurnani, H., Farrell, K., Wells, M. J., Reddy, C. B., Kepecs, A., Harris, K. D. and Carandini, M. (2020b) 'Dopaminergic and Prefrontal Basis of Learning from Sensory Confidence and Reward Value', *Neuron,* 105(4), pp. 700-711.e6.

Mante, V., Sussillo, D., Shenoy, K. V. and Newsome, W. T. (2013) 'Context-dependent
computation by recurrent dynamics in prefrontal cortex', *Nature,* 503(7474), pp. 78-84.
Markov, N. T., Ercsey-Ravasz, M. M., Ribeiro Gomes, A. R., Lamy, C., Magrou, L., Vezoli, J.,
Misery, P., Falchier, A., Quilodran, R., Gariel, M. A., Sallet, J., Gamanut, R., Huissoud, C.,
Clavagnier, S., Giroud, P., Sappey-Marinier, D., Barone, P., Dehay, C., Toroczkai, Z.,
Knoblauch, K., Van Essen, D. C. and Kennedy, H. (2014) 'A weighted and directed interareal
connectivity matrix for macaque cerebral cortex', *Cereb Cortex,* 24(1), pp. 17-36.
Mendonça, A. G., Drugowitsch, J., Vicente, M. I., DeWitt, E. E. J., Pouget, A. and Mainen, Z. F.
(2020) 'The impact of learning on perceptual decisions and its implication for speed-accuracy
tradeoffs', *Nat Commun,* 11(1), pp. 2757.
Mochol, G., Kiani, R. and Moreno-Bote, R. (2021) 'Prefrontal cortex represents heuristics that
shape choice bias and its integration into future behavior', *Curr Biol,* 31(6), pp. 1234-1244.e6.
Monsell, S. (2003) 'Task switching', *Trends Cogn Sci,* 7(3), pp. 134-140.
Mueller, A., Hong, D. S., Shepard, S. and Moore, T. (2017) 'Linking ADHD to the Neural
Circuitry of Attention', *Trends Cogn Sci,* 21(6), pp. 474-488.
Murphy, P. R., Wilming, N., Hernandez-Bocanegra, D. C., Prat-Ortega, G. and Donner, T. H.
(2021) 'Adaptive circuit dynamics across human cortex during evidence accumulation in
changing environments', *Nat Neurosci,* 24(7), pp. 987-997.
Newsome, W. T., Britten, K. H. and Movshon, J. A. (1989) 'Neuronal correlates of a perceptual
decision', *Nature,* 341(6237), pp. 52-4.
Owen, A. M., Roberts, A. C., Hodges, J. R., Summers, B. A., Polkey, C. E. and Robbins, T. W.
(1993) 'Contrasting mechanisms of impaired attentional set-shifting in patients with frontal lobe
damage or Parkinson's disease', *Brain,* 116 (Pt 5), pp. 1159-75.
Panichello, M. F. and Buschman, T. J. (2021) 'Shared mechanisms underlie the control of
working memory and attention', *Nature,* 592(7855), pp. 601-605.
Peixoto, D., Verhein, J. R., Kiani, R., Kao, J. C., Nuyujukian, P., Chandrasekaran, C., Brown, J.,
Fong, S., Ryu, S. I., Shenoy, K. V. and Newsome, W. T. (2021) 'Decoding and perturbing
decision states in real time', *Nature,* 591(7851), pp. 604-609.
Purcell, B. A. and Kiani, R. (2016a) 'Hierarchical decision processes that operate over distinct
timescales underlie choice and changes in strategy', *Proc Natl Acad Sci U S A,* 113(31), pp.
E4531-40.
Purcell, B. A. and Kiani, R. (2016b) 'Neural Mechanisms of Post-error Adjustments of Decision
Policy in Parietal Cortex', *Neuron,* 89(3), pp. 658-71.
Ravizza, S. M. and Carter, C. S. (2008) 'Shifting set about task switching: behavioral and neural
evidence for distinct forms of cognitive flexibility', *Neuropsychologia,* 46(12), pp. 2924-35.
Sarafyazd, M. and Jazayeri, M. (2019) 'Hierarchical reasoning by neural circuits in the frontal
cortex', *Science,* 364(6441).
Starkweather, C. K., Babayan, B. M., Uchida, N. and Gershman, S. J. (2017) 'Dopamine reward
prediction errors reflect hidden-state inference across time', *Nat Neurosci,* 20(4), pp. 581-589.
Stoet, G. and Snyder, L. H. (2004) 'Single neurons in posterior parietal cortex of monkeys
encode cognitive set', *Neuron,* 42(6), pp. 1003-12.
Stoet, G. and Snyder, L. H. (2009) 'Neural correlates of executive control functions in the
monkey', *Trends Cogn Sci,* 13(5), pp. 228-34.
Talluri, B. C., Urai, A. E., Tsetsos, K., Usher, M. and Donner, T. H. (2018) 'Confirmation Bias
through Selective Overweighting of Choice-Consistent Evidence', *Curr Biol,* 28(19), pp. 3128-
3135.e8.

Thapar, A., Martin, J., Mick, E., Arias Vásquez, A., Langley, K., Scherer, S. W., Schachar, R.,
Crosbie, J., Williams, N., Franke, B., Elia, J., Glessner, J., Hakonarson, H., Owen, M. J.,
Faraone, S. V., O'Donovan, M. C. and Holmans, P. (2016) 'Psychiatric gene discoveries shape
evidence on ADHD's biology', *Mol Psychiatry,* 21(9), pp. 1202-7.
Uchida, N., Kepecs, A. and Mainen, Z. F. (2006) 'Seeing at a glance, smelling in a whiff: rapid
forms of perceptual decision making', *Nat Rev Neurosci,* 7(6), pp. 485-91.
Yuen, K. S. and Lee, T. M. (2003) 'Could mood state affect risk-taking decisions?', *J Affect*
Disord, 75(1), pp. 11-8.

A

Proportion of perceptual choices

Large Small Small Large

SF decreases   SF increases

Choices

Large Small Small Large

SL left-shifts   SL right-shifts

B

Monkey's switches relative to task change

Number of switches

Trials in delay

C

Monkey's switches relative to ideal observer

p < 10⁻⁶

Trials in delay longer than optimal

D

Past experiences   Current Trial

Spatial frequency

Spatial location

Model past choice

Feedback

Trial -3   Trial -2   Trial -1   Trial 0

Inputs

Output

Recurrent Neural Network   Current trial choice

Time

E

Proportion of perceptual choices

Believed relevant
Believed irrelevant

Large Small Small Large
change change
against for
choice choice

F

Difference in reward rates

Proportion of sessions

p = 0.007

RNN - Monkey

H

Loss

ΔPerceptual performance (%)

Training time

G

Perceptual performance

monkey
G F
SF choices
SL choices

Monkeys

After an unrewarded trial (weak belief)

RNN

SF choices
SL choices

After a rewarded trial (strong belief)

A Neuronal space
in area 7a

Belief
strength

Neuron 2
firing rate

SL

SF

Task-belief
hyperplane

Neuron 1
firing rate

B Belief decoding
accuracy

0.8

After an
unrewarded
trial

Monkey
○ G
▼ F

p < 10⁻⁶

0.4   0.8
After a
rewarded trial

C Which feature is
behaviorally relevant?

Spatial
frequency
task

Spatial
location
task

Belief
strength

Belief strength

SL task preferring units
SF task preferring units

Normalized 7a activity

3   2   1   1   2   3
trials before   trials after

Monkeys switch
task here

A Neuronal space in area V1

Neuron 2 firing rate

Feature discriminant hyperplane

Neuron 1 firing rate

B Trial by trial belief~perception correlation

Perceptual discriminability for SF in V1

Task-belief strength in 7a

r = 0.24

C 7a task-belief ~ V1 SL change

Number of conditions

Under SF task

Under SL task

Cumulative proportion of conditions

Correlation coefficient

60
40

0.2   0   0.2

D 7a task-belief ~ V1 SF change

Number of conditions

Under SF task

Under SL task

Cumulative proportion of conditions

Correlation coefficient

0.2   0   0.2

A

SF perceptual confidence

Stimulus change
Perceptual confidence

V1 projection

B Model based on original V1 activity

— Switch odds
○ Actual switches
✕ Wrong predictions

Switch

Stay

C Trial shuffle within condition

Perceptual confidence

Trial sequence

D Model based on trial-shuffled V1 activity

Switch

Stay

Trial sequence

E Difference in switch detection d'

Proportion of sessions

0.2

0.1

p = 5×10⁻⁴

-0.1   0   0.1

Original sequence - shuffled sequence