Online single-cell data integration through projecting heterogeneous datasets into a common cell-embedding space

Lei Xiong[1,2,4,5], Kang Tian[1,2,5], Yuzhe Li[1,3], Qiangfeng Cliff Zhang[1,2,*]

[1] MOE Key Laboratory of Bioinformatics, Beijing Advanced Innovation Center for Structural Biology & Frontier Research Center for Biological Structure, Center for Synthetic and Systems Biology, School of Life Sciences, Tsinghua University, Beijing, China 100084

[2] Tsinghua-Peking Center for Life Sciences, Beijing, China 100084

[3] Academy for Advanced Interdisciplinary Studies, Peking University, Beijing, China 100871

[4] Shanghai Qi Zhi Institute, Shanghai 200030, China

[5] Co-first authorship

[*] Correspondence: qczhang@tsinghua.edu.cn (Q.C.Z.)

ABSTRACT

Computational tools for integrative analyses of diverse single-cell experiments are facing formidable new challenges including dramatic increases in data scale, sample heterogeneity, and the need to informatively cross-reference new data with foundational datasets. Here, we present SCALEX, a deep-learning method that integrates single-cell data by projecting cells into a batch-invariant, common cell-embedding space in a truly online manner (*i.e.*, without retraining the model). SCALEX substantially outperforms online iNMF and other state-of-the-art non-online integration methods on benchmark single-cell datasets of diverse modalities, (e.g., scRNA-seq, scATAC-seq), especially for datasets with partial overlaps, accurately aligning similar cell populations while retaining true biological differences. We showcase SCALEX's advantages by constructing continuously expandable single-cell atlases for human, mouse, and COVID-19 patients, each assembled from diverse data sources and

growing with every new data. The online data integration capacity and superior performance

makes SCALEX particularly appropriate for large-scale single-cell applications to build-upon

previously hard-won scientific insights.

INTRODUCTION

Single-cell experiments enable the decomposition of samples into their constituent,

diverse cell-types and cell states[1-4]. Many computational tools have been developed for

integrative analysis of single-cell datasets, all seeking to separate biological variations

from non-biological noise, such as batch effects of different donors, conditions, and/or

analytical platforms[5,6]. The scope of the integration task is expanding rapidly with

technical advances for single-cell studies, which continue to grow larger and larger in

scale, now exceeding 1 million cells in some cases[7,8]. Moreover, the range of

examined sample types is also increasing, and datasets now often include highly

heterogenous cell subsets[9,10]. Most importantly, as single-cell studies become more

routine, new studies should be informatively cross-referenced to foundational

research stuides[7,8,11-15]. Thus, there is a growing need for integration tools that can

manage single-cell data of large-scale and complex cell-type compositions while also

supporting accurate alignment to and exploration within existing datasets.

Most current single-cell data integration methods (e.g., Seurat[16-18], MNN[19],

Harmony[20], Conos[21], Scanorama[22], BBKNN[23], *etc.*) are based on the searching across

batches for cell-correspondence, for instance similar individual cells or cell

anchors/clusters. These methods suffer from three limitations. First, they are prone to

mixing cell populations that only exist in some batches, which becomes a severe

problem for the integration of complex datasets that contain non-overlapping cell

populations in each batch (*i.e.*, partially overlapping data)[16,17]. Second, they require

computational resources that increase dramatically as the number of cells and of

batches increase, making these methods increasingly unsuitable for today's large-scale

single-cell datasets[7,8,11-15]. Finally, these methods can only remove batch effects from

the current dataset being assessed. Each time a new dataset is added, it requires an

entirely new integration process that changes the existing integration results of

previous studies. This requirement severely limits a tool's ability to continuously

integrate arriving new single-cell data without recalculating existing integrations from

scratch, a capacity referred to as "online" data integration[24].

Online data integration ability is becoming increasingly crucial with today's

single-cell experiments. The recently developed tool, online iNMF[24], an online version

of LIGER[25], iteratively applies integrative non-negative matrix factorization (iNMF) to

decouple the shared and dataset-specific factors related to cell identities, and thus is

able to incorporate new data with existing datasets on-the-fly. Another recently

developed package, scvi-tools[26], combining scVI[27] with scArches[28], applies a

conditional variational autoencoder (VAE)[29] framework to model the inherent

distribution of the input single-cell data for data integration. However, the conditional

VAE design of scVI requires model augmentation and retraining when integrating new

data, meaning that scVI is not an online method.

Here, we developed SCALEX as a method for online integration of heterogeneous

single-cell data based on a VAE framework. The encoder of SCALEX is designed to be

a data projection function that only preserves batch-invariant biological data

components when projecting single-cells. Importantly, the projection function is a

generalized one that requires no retraining on new data, thus allowing SCALEX to

integrate single-cell data in an online manner. Working with an extensive collection of

benchmark datasets, we demonstrate that SCALEX substantially outperforms online

iNMF as well as non-online single-cell data integration tools, in terms of integration

accuracy, scalability, and computationally efficiency. The advantages make SCALEX

particularly appropriate for the integration and research utilization of today's

single-cell datasets, which continue to grow along with the ongoing explosion of
single-cell studies in biology and medicine.

RESULTS

SCALEX implements a generalized encoder that enables online integration of
single-cell data

To enable online integration, the fundamental design concept underlying SCALEX is
to implement a *generalized* projection function that disentangles the batch-related
components away from the batch-invariant components of single-cell data and projects
the batch-invariant components into a common cell-embedding space. We previously
applied VAE and designed SCALE (Single-Cell ATAC-seq Analysis via Latent feature
Extraction) to model and analyze single-cell ATAC-seq data[30]. We found that the
encoder of SCALE has the potential to disentangle cell-type-related and batch-related
features in a low-dimensional embedding space.

Here, to obtain a generalized encoder for data projection without retraining,
SCALEX includes three specific design elements (Fig. 1a, Fig. S1, Methods). First,
SCALEX implements a batch-free encoder that extracts only biological-related latent
features (z) from input single-cell data (x) and a batch-specific decoder[29] that
reconstructs the original data from z by incorporating batch information back during
data reconstruction. Supplying batch information only to the decoder focuses the
encoder exclusively on learning the batch-invariant biological components, which is
crucial for the encoder generalizability. In contrast, scVI includes a set of
batch-conditioned parameters into its encoder, which restrains the encoder from the
generalizability with new batches and thus precludes online data integration. Second,
SCALEX includes a Domain-Specific Batch Normalization (DSBN)[31] layer using
multi-branch Batch Normalization[32] in its decoder to support incorporation of
batch-specific variations during single-cell data reconstruction. Third, the SCALEX

encoder employs a mini-batch strategy that samples data from all batches (instead of

single batches), which more tightly follows the overall distribution of the input data.

Note that each mini-batch is subjected to a Batch Normalization layer in the encoder to

adjust the deviation of each mini-batch and to align it to the overall input distribution.

We conducted extensive analyses of SCALEX hyperparameters and also tested the

specific contributions of each design element by implementing a set of SCALEX

test-variants, each lacking an individual or a combination of the design elements, and

evaluating their performance for single-cell data integration (Supplementary Note). We

found that each design element is crucial for the integration performance of SCALEX.

More importantly, the combination of these design elements renders the encoder of

SCALEX a generalized function capable of accurate projection of single cell data from

different batches into a batch-invariant cell-embedding space, making SCALEX a truly

online data integration method.

SCALEX integration is substantially more accurate than state-of-the-art

single-cell data integration methods

We extensively assessed the basic data integration performance of SCALEX (Methods),

following the evaluative framework proposed in a recent comparative study[33]. We

examined multiple well-curated scRNA-seq datasets, including human *pancreas* (eight

batches of five studies)[34-38], *heart* (two batches of one study)[39] and *liver* (two

studies)[40,41]; as well as human non-small-cell lung cancer (*NSCLC*, four studies)[42-45]

and peripheral blood mononuclear cells (*PBMC*; two batches assayed by two different

protocols)[16]. Our comparison included online iNMF and other state-of-the-art

non-online single-cell data integration methods, including Seurat v3, Harmony, MNN,

Conos, BBKNN, Scanorama, LIGER (*i.e.*, batch iNMF), and scVI. We evaluated the

integration performance of these tools based on the benchmark datasets by Uniform

Manifold Approximation and Projection (UMAP)[46] embedding visualization as well as

a series of scoring metrics [19,20,47-49].

With UMAP embedding, we note that all of the raw datasets displayed strong batch

effects, with cell-types that were common in different batches separately distributed.

Overall, SCALEX, Seurat v3, and Harmony achieved the best integration performance

for most of the datasets by merging common cell-types across batches while keeping

disparate cell-types apart (Fig. S2). MNN, scVI, and Conos integrated many datasets

but left some common cell-types not well-aligned. Online iNMF, LIGER, BBKNN,

and Scanorama often had unmerged common cell-types, and sometimes incorrectly

mixed distinct cell-types together. For example, considering the T cell populations

between the two batches in the *PMBC* dataset (Fig. 1b), while SCALEX, Seurat v3,

Harmony, MNN, scVI integrations were effective, online iNMF misaligned some of

the CD4 naïve T cells with CD8 naïve T cells, and misaligned some NK cells with CD8

T cells.

SCALEX substantially outperformed all of the other methods for cell-type

clustering, as assessed by the adjusted Rand Index (ARI)[47] and the Normalized Mutual

Information (NMI)[48] (Fig. 1c, Fig. S3-S4). To quantify cell-type separation and batch

mixing we used two paired metrics (Methods): a pair comprising the Silhouette score[49]

and the batch entropy mixing score[19], as well as a pair comprising the cell-type and

integration local inverse Simpson's Indexes (cLISI and iLISI)[20]. Overall, SCALEX

achieved the highest scores for cell-type separation, and tied with Seurat v3 and

Harmony as the best-performing methods on the batch mixing metrics (Fig. S4).

Interestingly, we observed that both LIGER and online iNMF often scored the lowest

for cell-type separation yet the highest for batch mixing. However, after careful

investigation, we concluded that a higher batch mixing score does not necessarily

indicate better data integration, but instead often indicates an issue of over-correction,

which we consider in-depth in a dedicated subsection below.

SCALEX is scalable to Atlas-level datasets and accommodates diverse data modalities

Single-cell datasets that contain a large number of cells and consist of heterogenous and complex samples from multiple tissues have been termed "Atlas-level" datasets in a recent comparative study[33]. These Atlas-level datasets are posing new challenges to data integration tools. We tested the scalability and computation efficiency of SCALEX by applying it to a typical Atlas-level dataset, the Human Fetal Atlas dataset, which contains 4,317,246 cells from two data batches, GSE156793 and GSE134355 (Methods)[8,15] (Fig. S5a,b). SCALEX accurately integrated these two batches, showing good alignment of the same cell-types (Fig. 1d). In addition to SCALEX, only BBKNN, Scanorama, and scVI can be used to integrate this Atlas-level dataset, however, their integrations does not separate and align the cell-types well, as indicated by the UMAP embeddings (Fig. S5c) and the low cell-type separation and batch mixing scores (Fig. S5d).

We compared the computational efficiency of different methods using down-sampled datasets (of 10 K, 50 K, 250 K, 1 M, and 4M cells) from this Human Fetal Atlas dataset. Both SCALEX and online iNMF consumed very efficient runtime and memory that increased only linearly with data size. scVI also is scalable to 4M cells with acceptable memory usage, whereas Seurat v3, Harmony, Conos, and LIGER consumed runtime and/or memory that increased exponentially, thus did not scale beyond 1M cells on a workstation of 64 CPU cores and 256 GB memory (Fig. 1e). Notably, the deep learning framework of SCALEX enables it to run very efficiently on GPU devices, requiring much reduced runtime (using about 20 minutes and 90 GB of memory on the 4M dataset).

SCALEX can be used to integrate other modalities of single-cell data (*e.g.*, scATAC-seq[50,51], CITE-Seq[52], *etc.*) and cross-modality data (*e.g.*, simultaneous

analysis of scRNA-seq and scATAC-seq) (Methods). SCALEX substantially

outperformed all other methods for integration of mouse brain scATAC-seq datasets

(two batches assayed by snATAC and 10X)[53] (Fig. 1f, Fig. S6a-c), and performed well

for integration of additional single-cell data modalities including CITE-seq[52] and

spatial transcriptome MERFISH data[54] (Fig. S6d,e). We also used SCALEX to

integrate a cross-modality dataset (scRNA-seq and scATAC-seq)[55,56] and found that

SCALEX correctly integrated the two modalities of data and distinguished rare cells

that are specific to the scRNA-seq data, including pDC and platelet cells (Fig. 1g),

doing so better than other methods according to both UMAP embeddings and multiple

analytical metrics (Fig. S7).

SCALEX integrates partially overlapping datasets without over-correction

Many recent single-cell datasets, especially Atlas-level datasets, feature high sample

heterogeneity and complex cell-type compositions[9,10]. These datasets often contain

partially overlapping batches where each batch contains some non-overlapping cell

populations. For example, the *liver* dataset is a partially overlapping dataset where the

hepatocyte population contains multiple subtypes specific to different batches: three

subtypes are specific to LIVER_GSE124395, and two other subtypes only appear in

LIVER_GSE115469 (Fig. S8).

This partial overlap problem presents a major challenge for single-cell data

integration and often leads to an issue of over-correction (*i.e.*, mixing of distinct

cell-types), especially for those local cell similarity-based methods[16,17]. For example,

Seurat v3 mixed the hepatocyte-CXCL1, hepatocyte-CYP2A13, and

hepatocyte-TAT-AS1 cells and Harmony mixed the hepatocyte-CYP2A13 and

hepatocyte-TAT-AS1 cells (Fig. 2a). As a global integration method that projects cells

into a common cell-embedding space, SCALEX is expected to be less sensitive to this

problem. Indeed, we noticed that SCALEX correctly maintained the five hepatocyte

subtypes apart (as did scVI. Fig. 2a). Unexpectedly, despite being a global method,

online iNMF severely suffered from over-correction, mixing all five hepatocyte

subtypes, and even mixing B cells and NK cells (Fig. 2a), presumably because its

matrix factoring algorithm forced the alignment of distinct cell-types.

We defined an over-correction score, a metric to measure this over-correction

problem based on the percent of cells with inconsistent cell-types in the neighborhood

for each cell (Methods). Formally, the over-correction score is a negative index, *i.e.*, the

higher the over-correction score, the more severe the extent of inaccurate mixing of

cell-types. For the benchmark datasets, SCALEX had the lowest over-correction scores

(Fig. 2b), whereas online iNMF yielded extremely high over-correction scores.

To systematically characterize the performance of different methods on partially

overlapping datasets, we constructed test datasets with a range of common cell-types,

that we generated based on down-sampling of the six major cell-types in the *pancreas*

dataset (Methods). SCALEX integration was accurate for all cases, aligning the same

cell-types without over-correction, whereas Seurat v3, Harmony, and online iNMF

frequently mixed distinct cell-types (Fig. 2c-d). Although scVI showed one of the

lowest levels of over-correction when integrating partially overlapping datasets, it is

prone to mistakenly splitting one cell-type into many small groups. We noted that the

severity of over-correction and error-splitting is amplified as the overlapping number

decreases (Fig. S9). When there were no common cell-types, both Seurat v3 and

Harmony collapsed the six cell-types into three, mixing alpha with gamma cells, beta

with delta cells, and acinar with ductal cells to varying extents, whereas scVI split alpha

cells into 6 groups. We repeated this down-sampling analysis from the 12 cell-types in

the *PBMC* dataset and observed similar results of over-correction and error-splitting

(Fig. S10).

234   **SCALEX increases the scope and resolution of an existing cell space by adding**

235   **new data through online projection**

The generalizability of SCALEX's encoder to project cells from various sources into a

common cell-embedding space without model retraining allows SCALEX to integrate

new single-cell data with existing data in an online manner. We tested the online data

integration performance of SCALEX for newly arriving data based on the *pancreas*

dataset. Prior to projection, we first used SCALEX to integrate the *pancreas* dataset

and this accurately removed the strong batch effect that was evident in the raw data (Fig.

3a, Fig. S11a-b).

We subsequently projected three new batches of scRNA-seq data[57-59] for pancreas

tissues (Fig. 3b) into this "pancreas cell space" using the same SCALEX encoder

trained on the original *pancreas* dataset. After projection, most of the cells in the new

batches were accurately aligned to the correct cell-types in the pancreas cell space,

enabling their accurate annotation by cell-type label transfer (Fig. 3c, Method). We

benchmarked projection accuracy by calculating the ARI, the NMI, and the F1 score to

evaluate cell-type annotation by label transfer with cell-type information in the original

studies (Methods). We compared the results with online iNMF and scVI, the only two

tools that are able to project cells into an *existing* cell-space (note that data projection of

scVI needs model retaining through scArches). SCALEX achieved the highest

projection accuracy in comparisons with online iNMF and scVI (Fig. 3c). scVI also

achieved high accuracy, projecting most cells onto right locations, with only a few

exceptions of alpha and ductal cells (Fig. S11c). Online iNMF mixed distinct cell-types

when incorporating new batches, *e.g.* projecting some alpha cells onto the locations of

gamma and delta cells, and delta cells onto beta cells (Fig. S11c), which in turn led to

wrong annotations during label transfer (Fig. 3c).

The ability to project new single-cell data into an existing cell-embedding space

allows SCALEX to readily enrich (*i.e.*, to add biological resolution) this cell space with

additional informative details. To verify this, we projected two additional melanoma

data batches (SKCM_GSE72056, SKCM_GSE123139)[10,60] onto the previously

constructed PBMC space. Again, SCALEX correctly projected all common cell-types

were onto the same locations in the PBMC cell space (Fig. 3d), but online iNMF mixed

tumor cells with plasma, monocyte and CD8 T cells, and scVI split the CD8T cells into

several distinct groups (Fig. S12). Importantly, we noticed that for the tumor and

plasma cells only present in the melanoma data batches, SCALEX did not project these

cells onto any existing cell populations in the PBMC space; rather, it projected them

onto new locations close to similar cells, with the plasma cells projected to a location

near B cells, and the tumor cells projected to a location near HSC cells (Fig. 3e). This

indicates that SCALEX can enrich an existing cell space with new cell-types through

data projection.

SCALEX projection also enables *post hoc* annotation of unknown cell-types in an

existing cell space using new data. For instance, we noted a group of previously

uncharacterized cells in the *pancreas* dataset (Fig. 3a). We found that these cells

displayed high expression levels of known epithelial gene markers (Methods). We

therefore assembled a collection of epithelial cells from the *bronchial epithelium*

dataset[61], and then projected these epithelial cells onto the pancreas cell space. We

found that a group of antigen-presenting airway epithelial (SLC16A7+ epithelial) cells

were projected onto the same location of the uncharacterized cells (Fig. 3f). These data,

together with the observation that both cell populations showed similar marker gene

expression (Fig. 3g), suggest that these uncharacterized cells are also SLC16A7+

epithelial cells. Note that online iNMF and scVI were not able to identify this small

group of epithelial cells, because they were split into several smaller groups and/or

were often mixed with other cell-types (Fig. S2). SCALEX thus enables discovery

science in cell biology by supporting exploratory analysis with large numbers of
diverse datasets.

SCALEX integration constructs expandable single-cell atlases

The ability to combine heterogenous data into a common cell-embedding space makes
SCALEX a powerful tool to construct a single-cell atlas from a collection of diverse
datasets. We applied SCALEX integration to three large and complex datasets: the
Mouse Atlas dataset (comprising multiple organs from two studies assayed by 10X,
Smart-seq2, and Microwell-seq[12,14]), the Human Atlas dataset (comprising multiple
organs from two studies assayed by 10X and Microwell-seq[15,62]), and the Human Fetal
Atlas dataset[8,15] (Fig. S13).

Despite the strong batch effects in the raw data, SCALEX accurately integrated the
three batches of the Mouse Atlas data into a common cell-embedding space (Fig. 4a-c,
Fig. S14a). Common cell-types were well-aligned at the same position in the cell space,
including B, T, and endothelial cells presented in all tissues, and proximal tubule,
urothelial, and hepatocytic cells from particular tissues. Distinct cell-types were
located separately, such as sperm, Leydig, and small intestine cells from the
Microwell-seq data, keratinocyte stem cells and large intestine cells from the
Smart-seq2 data, indicating that biological variations were well preserved (Fig S14b,c).
We compared SCALEX with all other methods and found that SCALEX performed the
best for cell-type clustering, especially for avoiding over-correction (Fig. 4d,e, Fig.
S13b).

Importantly, atlases generated with SCALEX can be further expanded by
projecting new single-cell data to support comparative studies of cells both in the
original atlas and in the new data. To illustrate this utility, we projected two additional
data batches of aged mouse tissues from *Tabula Muris Senis* (Smart-seq2 and 10X)[13]
and two single tissue datasets (lung and kidney)[63] onto the SCALEX Mouse Atlas cell

space. We found that cells in the new data batches were correctly projected onto the locations of the same cell-types in the cell-embedding space of the initial atlas (Fig. 4f) as confirmed by the accurate cell-type annotations for the new data by label transfer (Fig. 4g. Methods).

Following the same strategy, we constructed a SCALEX Human Atlas by integration of multiple tissues from two studies (GSE134355, GSE159929) (Fig. S15a,b). SCALEX effectively eliminated the batch effects in the original data and integrated the two datasets (Fig. S15c,d). Again, we were able to correctly project two additional human skin datasets (GSE130973, GSE147424)[64,65] onto the Human Atlas cell space (Fig. S15e), and accurately annotated these projected skin cells (Fig. S15f. Methods). In sum, these results illustrate that SCALEX enables: i) researchers to evaluate their project-specific single cell datasets by leveraging existing information in large-scale (and ostensibly well annotated) cell atlases; and ii) atlas creators to informatively integrate new datasets and derive new biological insights from new research programs.

An integrative SCALEX COVID-19 PBMC Atlas revealed distinct immune responses among COVID-19 patients

Many single-cell studies have been conducted to analyze COVID-19 patient immune responses[66-73]. However, these studies often suffer from small sample size and/or limited sampling of various disease states[67,73]. For a comprehensive study, we used SCALEX to generate a COVID-19 PBMC Atlas, integrating data from nine COVID-19 studies, involving a total of 860,746 single cells in 10 batches[66-72] (Fig. 5a, Fig. S16a,b). We identified 22 cell-types, each of which has support from gene expression data for canonical markers (Fig. 5b,c, Fig. S16c,d. Methods). Cells across different studies were integrated accurately with the same cell-types aligned together, confirming the

integration performance of SCALEX (Fig. 5c, Fig. S16d), which was much better than

the other methods in terms of cell-type clustering (Fig. S16a,b).

Interestingly, we found that some cell subpopulations were differentially

associated with patient status (Fig 5d). A subpopulation of CD14 monocytes

(CD14-ISG15-Mono) was characterized by its high expression of Type I

interferon-stimulated genes (ISGs) and genes enriched with immune-response-related

GO terms (Fig 5e,f). The frequency of CD14-ISG15-Mono cells increased significantly

from mild/moderate to severe patients (Fig. 5g, Fig. S17a. Methods). Within the

COVID-19 patients, we observed a significant decrease in ISG gene expression in

CD14-ISG15-Mono cells between the mild/moderate and severe cases, suggesting an

immune exhaustion-like response in severe COVID-19 patients (Fig. 5e).

Additionally, a neutrophil subpopulation (NCF1-Immature_Neutrophil),

characterized by decreased expression of the genes responsible for neutrophil

activation but elevated expression of genes enriched with viral-process-related GO

terms, was specifically enriched in severe verse mild/moderate patients (Fig. S17b,c).

A plasma cell subpopulation (MZB1-Plasma), characterized by decreased expression

of genes related to antibody production and enriched for immune and inflammatory

response-related GO terms, were also enriched in severe patients (Fig. S17d,e). Thus,

the SCALEX COVID-19 PBMC atlas, generated by integrating a highly diverse

collection of single-cell data from individual studies, identified multiple immune

cell-types that become progressively dysfunctional during COVID-19 disease

progression. Importantly, these cell trends were not and could not have been detected in

the small-scale, individual studies that served as the basis for our SCALEX COVID-19

PBMC atlas.

Online integration of the SCALEX COVID-19 PBMC Atlas with the SC4

consortium study

Our analysis based on the SCALEX COVID-19 PBMC Atlas yielded findings

consistent with two conclusions from the Single Cell Consortium for COVID-19 in

China (SC4) study, a recent large-scale effort that generated a single-cell atlas of over 1

million cells from 171 COVID-19 patients and 25 healthy controls[7] (Fig. S18a). First,

both studies observed the same set of immune cell subpopulations which displayed

differential associations with COVID-19 severity. The proportions of CD14 monocytes,

megakaryocytes, plasma cells, and pro T cells were elevated with increasing disease

severity, while the proportion of pDC and mDC cells decreased (Fig. 5g). Second,

based on calculating the same cytokine score and inflammatory score (defined in the

SC4 study) for the cells in our SCALEX COVID-19 PBMC Atlas, we confirmed that

the megakaryocytes and monocyte subpopulations are associated with cytokine storms

triggered by SARS-Cov2 infection and are further elevated in severe patients[74] (Fig. 5j.

Methods).

SCALEX's online integration capacity enables us to project the SC4 consortium

dataset into the cell space of the SCALEX COVID-19 PBMC Atlas. We found that the

cell-types of two atlases were well-aligned (Fig. 5h,i, Fig. S18b,c). Integration of the

SC4 data further substantially improved both the scope and resolution of the SCALEX

COVID-19 PBMC Atlas. First, this data added macrophages and epithelial cells to the

cell space, enabling investigation of their potential involvement in COVID-19. The

integration also supported more precise characterization of specific cell subpopulations.

For example, the megakaryocyte population, not distinguished in either the SCALEX

COVID-19 PBMC Atlas or the SC4 Atlas (Fig. S18f), were divided into two

subpopulations in the combined atlas after projection of SC4 (Fig. 5h). An exploratory

functional analysis of the differentially expressed genes in these two newly delineated

megakaryocyte subpopulations (TUBA8-Mega and IGKC-Mega, Fig. S18d,e) revealed

enrichment for the GO terms "humoral immune response" for IGKC-Mega cells, yet

enrichment for "negative regulation of platelet activation" for TUBA8-Mega cells (Fig.

5k). These results illustrate how the continuously expandable single-cell atlases

generated using SCALEX capitalize on existing large-scale data resources and also

facilitate the discovery of new biological and biomedical insights.

DISCUSSION

Single cell studies are becoming more and more prevalent, growing larger and larger

in scale, and expanding in the scope of sample types, often with quite heterogenous

cell subsets. Thus, there is a great need for data integration tools to accurately and

efficiently handle these Atlas-level datasets[33]. Further, there is also a need for online

integration capacity to continuously incorporate incoming new data with existing

integrations without having to recalculate from scratch[24]. By design, SCALEX learns

a generalized projection function to project heterogeneous single-cell data into a

common cell-embedding space, enabling it to achieve *bona fide* online data integration.

SCALEX is also computationally efficient, and preserves biological variations and

avoids over-correction when integrating partially overlapping datasets.

These features make SCALEX particularly useful for Atlas-level datasets,

allowing the integration of many single-cell studies to support ongoing, very

large-scale research programs throughout the life sciences and biomedicine. We

speculate that use of SCALEX to project single-cell datasets from highly diverse

cancer types to construct a pan-cancer single-cell atlas may lead to the discovery of

previously unknown cell-types that are common to divergent carcinomas and that

function in pathogenesis, malignant progression, and/or metastasis.

REFERENCES

1   Kolodziejczyk, A. A., Kim, J. K., Svensson, V., Marioni, J. C. & Teichmann,
S. A. The technology and biology of single-cell RNA sequencing. *Mol Cell* **58**,
610-620, doi:10.1016/j.molcel.2015.04.005 (2015).

2   Papalexi, E. & Satija, R. Single-cell RNA sequencing to explore immune cell
heterogeneity. *Nat Rev Immunol* **18**, 35-45, doi:10.1038/nri.2017.76 (2018).

3   Tanay, A. & Regev, A. Scaling single-cell genomics from phenomenology to
mechanism. *Nature* **541**, 331-338, doi:10.1038/nature21350 (2017).

4   Satpathy, A. T. *et al.* Massively parallel single-cell chromatin landscapes of
human immune cell development and intratumoral T cell exhaustion. *Nature
Biotechnology* **37**, 925-936, doi:10.1038/s41587-019-0206-z (2019).

5   Leek, J. T. *et al.* Tackling the widespread and critical impact of batch effects
in high-throughput data. *Nat Rev Genet* **11**, 733-739, doi:10.1038/nrg2825
(2010).

6   Hicks, S. C., Townes, F. W., Teng, M. & Irizarry, R. A. Missing data and
technical variability in single-cell RNA-sequencing experiments. *Biostatistics*
19, 562-578, doi:10.1093/biostatistics/kxx053 (2018).

7   Ren, X. *et al.* COVID-19 immune features revealed by a large-scale
single-cell transcriptome atlas. *Cell*, doi:10.1016/j.cell.2021.01.053 (2021).

8   Cao, J. *et al.* A human cell atlas of fetal gene expression. *Science* **370**,
doi:10.1126/science.aba7721 (2020).

9   Azizi, E. *et al.* Single-Cell Map of Diverse Immune Phenotypes in the Breast
Tumor Microenvironment. *Cell* **174**, 1293-1308 e1236,
doi:10.1016/j.cell.2018.05.060 (2018).

10   Li, H. *et al.* Dysfunctional CD8 T Cells Form a Proliferative, Dynamically
Regulated Compartment within Human Melanoma. *Cell* **176**, 775-789.e718,
doi:https://doi.org/10.1016/j.cell.2018.11.043 (2019).

11   Regev, A. *et al.* The Human Cell Atlas. *Elife* **6**, doi:10.7554/eLife.27041
(2017).

12   Tabula Muris, C. *et al.* Single-cell transcriptomics of 20 mouse organs creates
a Tabula Muris. *Nature* **562**, 367-372, doi:10.1038/s41586-018-0590-4
(2018).

13   Tabula Muris, C. A single-cell transcriptomic atlas characterizes ageing
tissues in the mouse. *Nature* **583**, 590-595, doi:10.1038/s41586-020-2496-1
(2020).

14   Han, X. *et al.* Mapping the Mouse Cell Atlas by Microwell-Seq. *Cell* **172**,
1091-1107 e1017, doi:10.1016/j.cell.2018.02.001 (2018).

15   Han, X. *et al.* Construction of a human cell landscape at single-cell level.
Nature **581**, 303-309, doi:10.1038/s41586-020-2157-4 (2020).

16   Butler, A., Hoffman, P., Smibert, P., Papalexi, E. & Satija, R. Integrating
single-cell transcriptomic data across different conditions, technologies, and
species. *Nat Biotechnol* **36**, 411-420, doi:10.1038/nbt.4096 (2018).

17 Stuart, T. *et al.* Comprehensive Integration of Single-Cell Data. *Cell* **177**,
1888-1902 e1821, doi:10.1016/j.cell.2019.05.031 (2019).
18 Hao, Y. *et al.* Integrated analysis of multimodal single-cell data. *Cell*,
doi:https://doi.org/10.1016/j.cell.2021.04.048 (2021).
19 Haghverdi, L., Lun, A. T. L., Morgan, M. D. & Marioni, J. C. Batch effects in
single-cell RNA-sequencing data are corrected by matching mutual nearest
neighbors. *Nat Biotechnol* **36**, 421-427, doi:10.1038/nbt.4091 (2018).
20 Korsunsky, I. *et al.* Fast, sensitive and accurate integration of single-cell data
with Harmony. *Nat Methods*, doi:10.1038/s41592-019-0619-0 (2019).
21 Barkas, N. *et al.* Joint analysis of heterogeneous single-cell RNA-seq dataset
collections. *Nat Methods* **16**, 695-698, doi:10.1038/s41592-019-0466-z
(2019).
22 Hie, B., Bryson, B. & Berger, B. Efficient integration of heterogeneous
single-cell transcriptomes using Scanorama. *Nat Biotechnol*,
doi:10.1038/s41587-019-0113-3 (2019).
23 Polanski, K. *et al.* BBKNN: fast batch alignment of single cell transcriptomes.
Bioinformatics **36**, 964-965, doi:10.1093/bioinformatics/btz625 (2020).
24 Gao, C. *et al.* Iterative Refinement of Cellular Identity from Single-Cell Data
Using Online Learning. *bioRxiv*, 2020.2001.2016.909861,
doi:10.1101/2020.01.16.909861 (2020).
25 Welch, J. D. *et al.* Single-Cell Multi-omic Integration Compares and Contrasts
Features of Brain Cell Identity. *Cell* **177**, 1873-1887 e1817,
doi:10.1016/j.cell.2019.05.006 (2019).
26 Gayoso, A. *et al.* scvi-tools: a library for deep probabilistic analysis of
single-cell omics data. *bioRxiv*, 2021.2004.2028.441833,
doi:10.1101/2021.04.28.441833 (2021).
27 Lopez, R., Regier, J., Cole, M. B., Jordan, M. I. & Yosef, N. Deep generative
modeling for single-cell transcriptomics. *Nat Methods* **15**, 1053-1058,
doi:10.1038/s41592-018-0229-2 (2018).
28 Lotfollahi, M. *et al.* Query to reference single-cell integration with transfer
learning. *bioRxiv*, 2020.2007.2016.205997, doi:10.1101/2020.07.16.205997
(2020).
29 Kingma, D. P. & Welling, M. Auto-Encoding Variational Bayes.
arXiv:1312.6114 (2013).
30 Xiong, L. *et al.* SCALE method for single-cell ATAC-seq analysis via latent
feature extraction. *Nat Commun* **10**, 4576, doi:10.1038/s41467-019-12630-7
(2019).
31 Chang, W.-G., You, T., Seo, S., Kwak, S. & Han, B. Domain-Specific Batch
Normalization for Unsupervised Domain Adaptation. *arXiv:1906.03950*
(2019).
32 Ioffe, S. & Szegedy, C. Batch Normalization: Accelerating Deep Network
Training by Reducing Internal Covariate Shift. *arXiv:1502.03167* (2015).

33   Luecken, M. D. *et al.* Benchmarking atlas-level data integration in single-cell
genomics. *bioRxiv*, 2020.2005.2022.111161, doi:10.1101/2020.05.22.111161
(2020).
34   Lawlor, N. *et al.* Single-cell transcriptomes identify human islet cell signatures
and reveal cell-type-specific expression changes in type 2 diabetes. *Genome*
Res **27**, 208-222, doi:10.1101/gr.212720.116 (2017).
35   Segerstolpe, A. *et al.* Single-Cell Transcriptome Profiling of Human
Pancreatic Islets in Health and Type 2 Diabetes. *Cell Metab* **24**, 593-607,
doi:10.1016/j.cmet.2016.08.020 (2016).
36   Muraro, M. J. *et al.* A Single-Cell Transcriptome Atlas of the Human Pancreas.
Cell Syst **3**, 385-394 e383, doi:10.1016/j.cels.2016.09.002 (2016).
37   Grun, D. *et al.* De Novo Prediction of Stem Cell Identity using Single-Cell
Transcriptome Data. *Cell Stem Cell* **19**, 266-277,
doi:10.1016/j.stem.2016.05.010 (2016).
38   Baron, M. *et al.* A Single-Cell Transcriptomic Map of the Human and Mouse
Pancreas Reveals Inter- and Intra-cell Population Structure. *Cell Syst* **3**,
346-360 e344, doi:10.1016/j.cels.2016.08.011 (2016).
39   Litvinukova, M. *et al.* Cells of the adult human heart. *Nature* **588**, 466-472,
doi:10.1038/s41586-020-2797-4 (2020).
40   Aizarani, N. *et al.* A human liver cell atlas reveals heterogeneity and epithelial
progenitors. *Nature* **572**, 199-204, doi:10.1038/s41586-019-1373-2 (2019).
41   MacParland, S. A. *et al.* Single cell RNA sequencing of human liver reveals
distinct intrahepatic macrophage populations. *Nat Commun* **9**, 4383,
doi:10.1038/s41467-018-06318-7 (2018).
42   Lambrechts, D. *et al.* Phenotype molding of stromal cells in the lung tumor
microenvironment. *Nat Med* **24**, 1277-1289, doi:10.1038/s41591-018-0096-5
(2018).
43   Song, Q. *et al.* Dissecting intratumoral myeloid cell plasticity by single cell
RNA-seq. *Cancer Med* **8**, 3072-3085, doi:10.1002/cam4.2113 (2019).
44   Zilionis, R. *et al.* Single-Cell Transcriptomics of Human and Mouse Lung
Cancers Reveals Conserved Myeloid Populations across Individuals and
Species. *Immunity* **50**, 1317-1334 e1310, doi:10.1016/j.immuni.2019.03.009
(2019).
45   Kim, N. *et al.* Single-cell RNA sequencing demonstrates the molecular and
cellular reprogramming of metastatic lung adenocarcinoma. *Nat Commun* **11**,
2285, doi:10.1038/s41467-020-16164-1 (2020).
46   McInnes, L., Healy, J. & Melville, J. UMAP: Uniform Manifold
Approximation and Projection for Dimension Reduction. *arXiv:1802.03426*
(2018).
47   Hubert, L. & Arabie, P. Comparing partitions. *Journal of Classification* **2**,
193-218, doi:10.1007/BF01908075 (1985).

48   Amelio, A. & Pizzuti, C. in *Proceedings of the 2015 IEEE/ACM International*
Conference on Advances in Social Networks Analysis and Mining 2015
1584–1585 (Association for Computing Machinery, Paris, France, 2015).
49   Rousseeuw, P. J. Silhouettes: A graphical aid to the interpretation and
validation of cluster analysis. *Journal of Computational and Applied*
Mathematics **20**, 53-65, doi:https://doi.org/10.1016/0377-0427(87)90125-7
(1987).
50   Cusanovich, D. A. *et al.* Multiplex single cell profiling of chromatin
accessibility by combinatorial cellular indexing. *Science* **348**, 910-914,
doi:10.1126/science.aab1601 (2015).
51   Buenrostro, J. D. *et al.* Single-cell chromatin accessibility reveals principles of
regulatory variation. *Nature* **523**, 486-490, doi:10.1038/nature14590 (2015).
52   Stoeckius, M. *et al.* Simultaneous epitope and transcriptome measurement in
single cells. *Nat Methods* **14**, 865-868, doi:10.1038/nmeth.4380 (2017).
53   Fang, R. *et al.* Comprehensive analysis of single cell ATAC-seq data with
SnapATAC. *Nat Commun* **12**, 1337, doi:10.1038/s41467-021-21583-9 (2021).
54   Chen, K. H., Boettiger, A. N., Moffitt, J. R., Wang, S. & Zhuang, X. RNA
imaging. Spatially resolved, highly multiplexed RNA profiling in single cells.
Science **348**, aaa6090, doi:10.1126/science.aaa6090 (2015).
55   Genomics, X. 10k Peripheral blood mononuclear cells (PBMCs) from a
healthy donor, Single Cell ATAC Dataset by Cell Ranger 1.0.1.   (2018).
56   Genomics, X. 10k PBMCs from a Healthy Donor (v3 chemistry), Single Cell
Gene Expression Dataset by Cell Ranger 3.0.0.   (2018).
57   Wang, Y. J. *et al.* Single-Cell Transcriptomics of the Human Endocrine
Pancreas. *Diabetes* **65**, 3028-3038, doi:10.2337/db16-0405 (2016).
58   Enge, M. *et al.* Single-Cell Analysis of Human Pancreas Reveals
Transcriptional Signatures of Aging and Somatic Mutation Patterns. *Cell* **171**,
321-330 e314, doi:10.1016/j.cell.2017.09.004 (2017).
59   Xin, Y. *et al.* Pseudotime Ordering of Single Human beta-Cells Reveals States
of Insulin Production and Unfolded Protein Response. *Diabetes* **67**, 1783-1794,
doi:10.2337/db18-0365 (2018).
60   Tirosh, I. *et al.* Dissecting the multicellular ecosystem of metastatic melanoma
by single-cell RNA-seq. *Science* **352**, 189-196, doi:10.1126/science.aad0501
(2016).
61   Plasschaert, L. W. *et al.* A single-cell atlas of the airway epithelium reveals
the CFTR-rich pulmonary ionocyte. *Nature* **560**, 377-381,
doi:10.1038/s41586-018-0394-6 (2018).
62   He, S. *et al.* Single-cell transcriptome profiling of an adult human cell atlas of
15 major organs. *Genome Biol* **21**, 294, doi:10.1186/s13059-020-02210-0
(2020).

63   Kimmel, J. C. *et al.* Murine single-cell RNA-seq reveals cell-identity- and
580   tissue-specific trajectories of aging. *Genome Res* **29**, 2088-2103,
581   doi:10.1101/gr.253880.119 (2019).

582   64   Sole-Boldo, L. *et al.* Single-cell transcriptomes of the human skin reveal
583   age-related loss of fibroblast priming. *Commun Biol* **3**, 188,
584   doi:10.1038/s42003-020-0922-4 (2020).

585   65   He, H. *et al.* Single-cell transcriptome analysis of human skin identifies novel
586   fibroblast subpopulation and enrichment of immune subsets in atopic
587   dermatitis. *J Allergy Clin Immunol* **145**, 1615-1628,
588   doi:10.1016/j.jaci.2020.01.042 (2020).

589   66   Schulte-Schrepping, J. *et al.* Severe COVID-19 Is Marked by a Dysregulated
590   Myeloid Cell Compartment. *Cell* **182**, 1419-1440.e1423,
591   doi:10.1016/j.cell.2020.08.001 (2020).

592   67   Lee, J. S. *et al.* Immunophenotyping of COVID-19 and influenza highlights
593   the role of type I interferons in development of severe COVID-19. *Sci*
594   *Immunol* **5**, doi:10.1126/sciimmunol.abd1554 (2020).

595   68   Wilk, A. J. *et al.* A single-cell atlas of the peripheral immune response in
596   patients with severe COVID-19. *Nat Med* **26**, 1070-1076,
597   doi:10.1038/s41591-020-0944-y (2020).

598   69   Guo, C. *et al.* Single-cell analysis of two severe COVID-19 patients reveals a
599   monocyte-associated and tocilizumab-responding cytokine storm. *Nat*
600   *Commun* **11**, 3924, doi:10.1038/s41467-020-17834-w (2020).

601   70   Yao, C. *et al.* Cell-Type-Specific Immune Dysregulation in Severely Ill
602   COVID-19 Patients. *Cell Rep* **34**, 108590, doi:10.1016/j.celrep.2020.108590
603   (2021).

604   71   Zhang, J. Y. *et al.* Single-cell landscape of immunological responses in
605   patients with COVID-19. *Nat Immunol* **21**, 1107-1118,
606   doi:10.1038/s41590-020-0762-x (2020).

607   72   Ballestar, E. *et al.* Single cell profiling of COVID-19 patients: an international
608   data resource from multiple tissues. *medRxiv*, 2020.2011.2020.20227355,
609   doi:10.1101/2020.11.20.20227355 (2020).

610   73   Bernardes, J. P. *et al.* Longitudinal Multi-omics Analyses Identify Responses
611   of Megakaryocytes, Erythroid Cells, and Plasmablasts as Hallmarks of Severe
612   COVID-19. *Immunity* **53**, 1296-1314 e1299,
613   doi:10.1016/j.immuni.2020.11.017 (2020).

614   74   Chen, G. *et al.* Clinical and immunological features of severe and moderate
615   coronavirus disease 2019. *J Clin Invest* **130**, 2620-2629,
616   doi:10.1172/JCI137244 (2020).

617   75   Kingma, D. P. & Ba, J. Adam: A Method for Stochastic Optimization.
618   *arXiv:1412.6980* (2014).

619   76   Danese, A., Richter, M. L., Fischer, D. S., Theis, F. J. & Colomé-Tatché, M.
620   EpiScanpy: integrated single-cell epigenomic analysis. *bioRxiv*,
621   doi:10.1101/648097 (2019).
622   77   Wolf, F. A., Angerer, P. & Theis, F. J. SCANPY: large-scale single-cell gene
623   expression data analysis. *Genome Biol* **19**, 15,
624   doi:10.1186/s13059-017-1382-0 (2018).
625   78   Stuart, T., Srivastava, A., Lareau, C. & Satija, R. Multimodal single-cell
626   chromatin analysis with Signac. *bioRxiv*, doi:10.1101/2020.11.09.373613
627   (2020).
628   79   Abdi, H. & Williams, L. J. Principal component analysis. *WIREs Comput. Stat.*
629   **2**, 433-459, doi:10.1002/wics.101 (2010).
630   80   Traag, V. A., Waltman, L. & van Eck, N. J. From Louvain to Leiden:
631   guaranteeing well-connected communities. *Scientific Reports* **9**, 5233,
632   doi:10.1038/s41598-019-41695-z (2019).

Methods

Overview of the SCALEX model. SCALEX applies a variational autoencoder (VAE)

to project the different batches of datasets into the same batch-invariant

low-dimensional embeddings by learning a batch-free encoder and a batch-specific

decoder simultaneously. Since the encoder and decoder are coupled to learn a

batch-free encoder, a batch label (b) is only exposed to the decoder within the

domain-specific batch normalization (DSBN), thus the decoder captures the batch

information while the encoder learns the domain-invariant features. In the encoder,

SCALEX takes the input expression profile (x) across all the batches as a whole

mixture distribution without distinguishing their batch sources and extracts their mean

(μ) and variance (σ^2) of the latent representations (z) in a 10-dimension embedding

space to learn their global data structure. A standard multivariate Gaussian prior is

used for z, while the approximated distribution of z is re-parameterized by $z = \mu +$

$\sigma * \varepsilon$, where ε is sampled from $\mathbb{N}(0, I)$. In the decoder, SCALEX maps the latent

representations with batch label (b) back to their original profile. To enable the

decoder to capture the batch-specific variations, a DSBN layer is applied to learn a

batch-specific normalization for each batch label (b), before transforming them back

to their original profile with the new batch variations. To learn the global distribution

to avoid overcorrection on partially overlapping datasets, within each mini-batch in

the training process, SCALEX randomly samples data from all batches and trains on

them together with Batch Normalization to smooth the batch-specific shifts and align

to the global distribution. Once trained, the encoder of SCALEX is generalized to any

batches and serves as a universal function for globally mapping different batches of

datasets into the same batch-invariant space.

Training SCALEX is to maximize the log-likelihood of the observed single-cell

sequencing data x:

$$logp(x) = log \int_z p(x,z)dz$$
$$\geq E_{q(z|x)}\left[log\frac{p(x,z)}{q(z|x)}\right]$$
$$= \mathcal{L}_{ELBO}(x)$$

Then the loss function is transformed into the evidence lower bound (ELBO). While

the ELBO can be further decomposed into two terms:

$$\mathcal{L}_{ELBO}(x) = E_{q(z|x)}[logp(x|z)] - D_{KL}(q(z|x)||p(z))]$$

The first term is the reconstruction term, which minimizes the distance between the

generated output data x' and the original input data x, calculated as the binary cross

entropy between x' and x. The second term is the regularization term, which

minimizes the Kullback-Leibeler divergence between posterior distribution

$\mathbb{N}(\mu, \sigma)$ and prior distribution $\mathbb{N}(0, I)$ of latent representations z. To enable a more

flexible alignment under the latent space, we adjusted the coefficient of the second

term to 0.5 after hyper-parameter optimization via a grid search; thus, the final loss

function is:

$$\mathcal{L}_{ELBO}(x) = E_{q(z|x)}[logp(x|z)] - 0.5 * D_{KL}(q(z|x)||p(z))]$$

The overall network architecture of SCALEX consists of an encoder and a decoder.

The encoder is a two-layer neural network (fully connected [1024]-BN-ReLU-fully

connected[10]) for mean (μ) and variance (σ^2) of the 10-dimension latent

representations z using a reparameterization to obtain latent representations z, and the

decoder has only one layer (no hidden layer), directly connecting latent

representations z to the output x (fully connected-DSBN-Sigmoid) with

domain-specific batch normalization, where the latent representations z and batch ID

are provided as input, and a Sigmoid activation function. We used the Adam[75]

optimizer with a 5e-4 weight decay and betas (0.9, 0.999, the exponential decay rate

for the first and second moment parameters) to optimize the model under the learning

rate 2e-4. We adopted mini-batch strategy to iteratively optimize the model, in each

mini-batch, we randomly sampled data from all batches instead of from the same

batch, and the mini-batch size for training input is 64. The maximum number of

training iterations is 30,000 and an early stopping is triggered when there has been no

improvement for 10 epochs. The hyper-parameters are chosen after a grid search.

SCALEX is very robust with all of these hyper-parameters, all of the results in this

manuscript are produced under the same parameters.

Domain-specific batch normalization (DSBN). Batch normalization (BN)[32] is a

widely used training technique in deep neural networks to reduce internal covariate

shifting. A BN layer whitens activations within a mini-batch of samples followed by

scaling and shifting with learned affine parameters γ and β. For a mini-batch of

samples: $\mathcal{B} = \{x_{1 \dots m}\}$;

$$\mu_{\mathcal{B}} = \frac{1}{m} \sum_{i=1}^{m} x_i$$

$$\sigma_{\mathcal{B}}^2 = \frac{1}{m} \sum_{i=1}^{m} (x_i - \mu_{\mathcal{B}})^2$$

$$\hat{x}_i = \frac{x_i - \mu_\mathcal{B}}{\sqrt{\sigma_\mathcal{B}^2 + \epsilon}}$$

$$y_i = \gamma \hat{x}_i + \beta \equiv \text{BN}_{\gamma,\beta}(x_i)$$

Where $\mu_\mathcal{B}$ is the mini-batch mean, $\sigma_\mathcal{B}^2$ is the mini-batch variance, $\hat{x}_i$ is the

normalized output by $\mu_\mathcal{B}$ and $\sigma_\mathcal{B}^2$, y_i is the BN output by scaling and shifting $\hat{x}_i$

with parameters γ and β, and ϵ is a constant added to the mini-batch variance for

numerical stability.

Domain specific batch normalization (DSBN)[31] is a combination of multiple sets of

BN specific to each domain. DSBN learns domain-specific affine parameters γ_d and

β_d for each domain, d is the domain label; here, domain represents different batches.

In the neural network, DSBN serves like multi-channel BN and switches to the

corresponding BN given the domain label d. The DSBN layer can be written as:

$$y_d = \gamma_d \hat{x}_d + \beta_d \equiv \text{DSBN}_{\gamma_d,\beta_d}(x_d, d)$$

where d is the batch label, and γ_d and β_d are domain-specific affine parameters for

domain d.

DSBN could capture the domain-specific information by estimating mini-batch

statistics by learning affine parameters for each domain separately, thus enabling the

network to learn the domain-invariant features.

Preprocessing for scRNA-seq. We downloaded gene expression matrices and

preprocessed them using the following procedure: i). Cells with fewer than 600 genes

and genes present in fewer than 3 cells were filtered out. ii). Total counts of each cell

were normalized to 10,000. iii). Values of each gene were subjected to log

transformation with an offset of 1. iv). The top 2,000 highly variable genes were

identified. v). Values of each gene were normalized to the range of 0-1 within each

batch by the *MaxAbsScaler* function in the *scikit-learn* package in Python. The

processed matrix was used as input for the SCALEX model for downstream

differential gene expression analysis.

For the *human fetal atlas* dataset, we collected two batches (batch GSE156793,

which contains 4,062,980 cells by sciRNA-seq3, and batch GSE134355, which

contains 254,266 cells by Microwell-seq). We then selected the cells from the

common tissues (1,369,619 cells) for integration and computational efficiency

benchmarking (down-sampled from different data sizes including 10K, 50K, 250K,

1M, and 4M).

Preprocessing for scATAC-seq. We downloaded open chromatin profile matrices

(peaks or bins), merged them by peaks (or bins), and processed them using the

following procedure: i). The combined matrix was binarized and filter bins with fewer

than 3 cells. ii). The top 30,000 most variable peaks (or bins) were selected using the

select_var_feature function in the *EpiScanpy*[76] package. iii). Total counts of each cell

were normalized to the median of the total counts of all cells by using the

normalize_total function, with parameters *target_sum*="None" in the *Scanpy*[77]

package. iv). Values of each peak (or bin) were normalized to the range of 0-1 within

each batch by the *MaxAbsScaler* function in the *scikit-learn* package in Python. The

processed matrix was used as input for the SCALEX model.

Preprocessing for cross-modality data (scRNA-seq and scATAC-seq). We first

created a gene activity matrix by the *GeneActivity* function in the *Signac*[78] R package

to quantify the activity of each gene from scATAC-seq data. We then combined gene

activity score matrix with scRNA-seq data matrix as two individual "batches" for

integration. The subsequent preprocessing followed the same preprocessing used for

the scRNA-seq data (above).

Visualization. UMAP algorithm[46] was used for visualization. We applied the

neighbors function from the Python package *Scanpy* with the parameters

n_neighbors=30 and *metric*="Euclidean" for computing the neighbor graph, followed

by *umap* function with *min_dist*=0.1 to visualize cells in a two-dimensional space.

Adjusted Rand Index. The Rand Index (RI) computes a similarity score between two

clustering assignments by considering matched and unmatched assignment pairs,

independent of the number of clusters. The Adjusted Rand Index (ARI) score is

calculated by "adjust for chance" with RI as follows:

$$ARI = \frac{RI - Expected\_RI}{\max(RI) - Expected\_RI}$$

748   If given the contingency table, then ARI can also be represented by:

$$ARI = \frac{\sum_{ij}\binom{n_{ij}}{2} - [\sum_i\binom{a_i}{2}\sum_j\binom{b_j}{2}]/\binom{n}{2}}{\frac{1}{2}[\sum_i\binom{a_i}{2} + \sum_j\binom{b_j}{2}] - [\sum_i\binom{a_i}{2}\sum_j\binom{b_j}{2}]/\binom{n}{2}}$$

749   The ARI score is 0 for random prediction and 1 for perfectly matching.

750   **Normalized mutual information.**

$$NMI = \frac{I(P;T)}{\sqrt{H(P)H(T)}}$$

Where P and T are categorical distributions for the predicted and real clustering, I is

the mutual entropy, and H is the Shannon entropy.

Silhouette score. We used the silhouette score to assess the separation of biological

populations with the function *silhouette_score* in the *scikit-learn* package in Python.

The silhouette score was computed by combining the average intra-cluster distance (a)

and the average nearest-cluster (b) for each cell.

$$silhouette\ score = (b - a)/\max(a, b)$$

Here, we took UMAP embeddings as input to calculate silhouette score.

Batch entropy mixing score. Batch entropy mixing score (adapted from "entropy of

batch mixing"[19]) was used to access the regional mixing of cells from different

batches, with a high score suggesting that cells from different batches are well mixed

together.

The batch entropy mixing score was computed as follows:

(1) Calculated the proportion Pi of cell numbers in each batch to the total cell

numbers.

(2) Randomly chose 30 cells from all batches.

(3) Calculated the 30 nearest neighbors for each randomly chosen cell.

(4) The regional mixing entropies for each cell were defined as:

$$pi' = \frac{pi/Pi}{\sum_{i=1}^{n} pi/Pi}$$

$$E = \sum_{i=0}^{n} pi'log(pi')$$

where pi is the proportion of cells from batch i in a given region, such that $\sum_{i=0}^{n} pi = $

1, pi' is a correction item to eliminate the deviation caused by the different cell

numbers in different batches. The total mixing entropy was then calculated as the sum

of the regional mixing entropies.

(5) Repeated (2)-(4) for 10 iterations with different randomly chosen cells and

calculated the average, E, as the final batch entropy mixing score.

Note that to mitigate the effect of misalignment of batch-specific cell-types, we

calculated the batch entropy mixing score only based on cells from cell-types that are

common in different batches.

Local inverse Simpsons Index (LISI). The LISI metric was proposed by Korsunsky

et al. 2019 [20] to assess batch and cell-type mixing. We calculated integration LISI

(iLISI) and cell-type LISI (cLISI) values using the *compute_lisi* function in the *lisi* R

package. UMAP embeddings, batch labels, and cell-type labels were used as input in

calculation. Briefly,

$$LISI(x_i) = \frac{1}{\sum_{y \in Y} P(y|x_i)^2}$$

where $x_i \in \{x_1, x_2, \ldots, x_N\}$ is the *i*-th cell's UMAP embeddings in the dataset of size

N, and *Y* is the set of unique values with respect to the type of LISI we are computing

(*i.e.*, *Y* is the values of "batch label" for calculating iLISI and the value of "cell-type

label" for calculating cLISI). The probability $P(y|x_i)$ refers to the "relative

abundance" of the covariate *y* within KNN (k-nearest neighborhood) of x_i. A

Gaussian kernel-based distribution of neighborhoods was used and the perplexity was

fixed to 30.

Over-correction score. We defined an over-correction score to assess the level of

over-correction problem, based on calculating the percentage of cells with

inconsistent cell-types in each cell's neighborhood. We calculated the over-correction

score over all cells, and for each cell i we averaged the frequency of the k-nearest

neighboring cells with distinct cell-types to the cell i (see the following equation).

$$over\_correction\ score = 1 - \frac{1}{n * k} \sum_{i=1}^{n} \sum_{j=1}^{k} I(cell\_type_i, cell\_type_j)$$

794   where n is the total cell number, k represents the k-nearest neighbors of each cell,

795   the cell-type of the cell i is $cell\_type_i$, the cell-type of the neighboring cell j is

796    $cell\_type_j$, and I is an indicative function defined as:

$$I(cell\_type_i, cell\_type_j) = \begin{cases} 1 & if \ cell\_type_i = cell\_type_j \\ 0 & if \ cell\_type_i \neq cell\_type_j \end{cases}$$

Formally, the over-correction score is a negative index, i.e., the higher the
over-correction score, the more severe the extent of inaccurate mixing of cell-types.

Comparison with other integration methods. We compared SCALEX to nine other
batch effect removal methods (see below for specific details of each method). For
each dataset as input for all methods, we performed the same filtration, followed by
method-specific normalization, batch correction and visualization. Note that for visual
comparison, we also included the embeddings of the raw input data, wherein we
performed dimensionality reduction by Principal Component Analysis (PCA)[79]
followed by UMAP visualization to see the batch effects. No correction function was
used. All parameters were kept as default values.

Scanorama (v1.6). We performed the preprocessing pipelines as stated above (as the
same below), and used the *Scanpy* and *scanorama* Python packages for integration.
For the *highly_variable_genes* function, we set *flavor*="seurat", *batch_key*="batch",
and *n_top_genes*=2,000. After extracting highly variable genes, we divided the
datasets according to the batch labels and formed a new list of datasets as the input for
the *correct_scanpy* function. The integration matrix was kept for downstream analysis.
All other parameters were kept their default values.

BBKNN (v1.3.12). We used *Scanpy* and *bbknn* Python packages and followed the
suggested pipelines for integration. For the *highly_variable_genes* function, we set
flavor="seurat", *batch_key*="batch", and *n_top_genes*=2,000. After selecting cell
neighbors at the low-dimensional space from the PCA analysis, we performed the
bbknn function with *neighbors_within_batch*=5, *n_pcs*=20, and *trim*=0. All other
parameters were default.

scVI (scvi-tools, v0.11): We used the *scvi* Python package and followed the suggested

pipelines.   Batch information was added to the VAE model by setting n_batch.

Seurat v3 (v3.2.3): We used the *Seurat* R package and followed the standard

integration workflow. We normalized different batches of a dataset separately. For the

FindVariableFeatures function, we set *selection.method*="vst" and *nfeatures*=2,000

to select 2,000 highly variable genes for each batch of a dataset. For the

FindIntegrationAnchors function, we set *k.filter*=100. All other parameters were kept

at default values. If the number of input cells in a dataset exceeded 50,000, we

employed the reciprocal PCA and reference-based integration to improve

computational efficiency.

Harmony (v1.0): We used the *harmony* R package. We created a *Seurat* object with

all cells and performed the standard workflow. After PCA, we used the *RunHarmony*

function for integration. All parameters were default.

Conos (v1.3.1): We used the *Conos* R package. For each batch of dataset, we used the

basicSeuratProc and *RunTSNE* functions for preprocessing. After that, we built a

joint graph using the *buildGraph* function with k=30 and *k.self*=5. All other

parameters were default.

MNN (FastMNN, v0.3.0): We used the *SeuratWrappers* R package. We created a

Seurat object with all cells and performed the standard workflow. Then we used the

RunFastMNN function with default parameters for integration.

Online iNMF and LIGER (LIGER, v1.0.0): We used the *rliger* R package. For the

online iNMF method, we used the online_iNMF function with k=20,

miniBatch_size=5,000 and *max.epochs*=5. For the LIGER method, we used the

optimizeALS function with k=20. All other parameters were the default values.

Different from other methods, online iNMF only loads one mini-batch from the whole

data in the HDF5 file format (converted from the orginal data format by the *rhdf5* R

package) for a memory-efficient implementation; accordingly, a file conversion issue

with the down-sampled *human fetal atlas* dataset of 4M data size prevented online

iNMF from calculating computational efficiency with the 4M.

Cell-type annotation by clustering. This type of annotation was used for *de novo*

annotation of a single-cell dataset. We used a Leiden clustering[80] method for cell

clustering (specifically employing the *leiden* function from the Python package

Scanpy with default parameters). Then for each cluster, we annotate its cell-type

based on: i) cell-type annotations of each cell in the original study, if available, or ii)

expression levels of canonical marker genes in each cell. A majority vote strategy was

used when needed. Similar to Ren et al. 2021, we also employed a hierarchical

annotation strategy, *i.e.*, we first clustered all cells in a dataset into several major

clusters, then for some big clusters, we further clustered them into minor clusters

respectively.

Single cell projection. We defined single cell projection as the operation to convert

high-dimensional single-cell data (*e.g.*, gene expression profiles in scRNA-seq or open

chromatin profiles in scATAC-seq) to low-dimensional representations in the common

SCALEX cell-embedding space using the trained encoder.

Cell-type annotation by label transfer. This type of annotation was used for

annotation of a new single-cell data batch using the annotations in a large single-cell

dataset as a reference, or for *post hoc* annotations of unknown cell population(s) in a

large dataset using new batches of data of known cell-types. Both scenarios require

"single cell projection" (see details below).

The basic idea of cell-type annotation by label transfer is based-on that the same

cell-types will occupy the same locations in the low-dimensional SCALEX

cell-embedding space, thus cell-type annotation in one data batch can be transferred to

another data batch, for the cells positioned at the same locations. Technically, we used

the *KNeighborsClassifier* function from the *scikit-learn* package to train a prediction

model, using the representations (in the low-dimensional cell-embedding space) of the

single-cell data with known cell-type labels as input. We then used this model to make

cell-type predictions for cells without annotations using their representations (in the

low-dimensional cell-embedding space) as input. For comparison, label transfer for

online iNMF follows the same procedures as SCALEX by predicting the cell-type

based-on the projected locations.

Similarity matrix and confusion matrix. We used similarity matrix to evaluate the

congruence of two different batches for the same cell-types in the common

cell-embedding space. Technically, we merged all cells with the same cell-type label

and calculated an average representation (in the low-dimensional cell-embedding

space) for the cell-type. This was repeated for all cell-types. We then calculated the

similarity matrix $S=[S_{ij}]$ for the cell-type similarities of the two batches, where S_{ij} is

the Pearson correlation coefficient between the average representation of cell-type i in

data_batch_1 and the average representation of cell-type j in data_batch_2.

We used the confusion matrix to evaluate the accuracy of cell-type annotations

(prediction) when a gold-standard annotation is available, which is typical for

"cell-type annotation by label transfer" (see above). In cell-type annotation by label

transfer, we predict the cell-types for a single-cell data_batch_1, using the annotations

in another data_batch_2. When data_batch_1 was already annotated with cell-types,

we can calculate the confusion matrix $C=[C_{ij}]$ to compare the cell-type predictions

with the existing cell-type annotations, where C_{ij} equals the percentage of cells known

to be in cell-type i and predicted to be in cell-type j.

F1 score. F1 score is a weighted average of the precision and recall as a classification

metric, which is computed by:

$$F1\ score = 2 * (\text{precision} * \text{recall})/(\text{precision} + \text{recall})$$

Generation of partially overlapping datasets. To simulate partially overlapping

datasets from the *pancreas* dataset, we used the pancreas_celseq2 and

pancreas_smartseq2 data batches, and worked with only six cell-types (alpha, beta,

ductal, acinar, delta, gamma). For each simulated partially overlapping dataset, we

randomly selected three to six cell-types from each batch, and counted the number of

the common cell-types, which was used as the indicator for the overlapping level

(whole integers, 0 to 6). We required the union of cell-types in the newly simulated

partially overlapping dataset to cover all six cell-types.

For the *PBMC* dataset, we used both of the two data batches and worked with

twelve cell-types (B, CD4 T, CD4 naive T, CD8 T, CD8 naive T, DC, HSC,

Megakaryocyte, NK, monocyte-CD14, monocyte-FCGR3A, pDC). We used the same

down-sampling strategy as for the *pancreas* dataset (above).

Analysis of changes in cell-type frequency across multiple conditions. To identify

differences in cell-type frequency among the scRNA-seq data from the mild/moderate,

severe, convalescent COVID-19 patients, as well as the healthy and influenza patient

controls, we applied a Dirichlet-multinomial regression model. This model accounts

for the constraint that the cell frequencies in a scRNA-seq data are not independent of

each other. In detail, we normalized the regression coefficients to a standard normal

distribution and calculated a z score, and then conducted significance testing based on

the regression model generated by the *DirichReg* function in the R package

DirichletReg (v 0.7).

Differential gene expression analysis and Gene Ontology term enrichment

analysis. Differential gene expression analysis was performed on all expressed genes

using the *rank_genes_groups* function with *method*="t-test" in the *Scanpy* package,

for two certain cell-types in a COVID-19 single-cell atlas. A gene was considered

differentially expressed when a log2-fold change was >1 in the two conditions in

comparison, and the Benjamini-Hochberg adjusted P-value was < 0.01. The top 200 highly expressed genes sorted by scores (implemented in *Scanpy*) of each cell-type were used as the input for GO analysis, and enriched GO terms were acquired for each group of cells of the "GO_Biological_Process_2018" dataset using the Python package *GSEApy*.

Inflammatory and cytokine score analysis. We defined the inflammatory score and the cytokine score for each cell following Ren et al. 2021, based on the expression of a defined collection of cytokine genes and inflammatory-response-related genes, which were from Liberzon et al. 2015 (Supplementary Table 1). We then calculated the cytokine and inflammatory scores from the raw gene expression profile using the *score_genes* function implemented in the *Scanpy*.

Ablation studies using test-variants of SCLAEX

We evaluate the contributions of each design element by the performance of different ablation variant models on integration and projection tasks (Fig. S18, Fig. S19).

Baseline/full SCLAEX. The baseline or the full SCALEX model is described in the paper, including an encoder without batch label, mini-batch sampling from all batches with Batch Normalization, a decoder with DSBN, and beta=0.5. All other variant models are compared to this baseline model.

A variant of encoder with batch label. The baseline model with an encoder with batch label as input.

A variant of sampling by batch without Batch Normalization. The baseline model without the Batch Normalization layer in the encoder as well as each mini-batch is sampled by batch instead of from all batches.

A variant of decoder without DSBN. The baseline model without the DSBN layer in the decoder.

Software availability.

SCALEX is available at https://github.com/jsxlei/SCALEX.

Data availability.

All data analyzed in this study are publicly available; the data sources are detailed in

Supplementary Table 2.

Acknowledgements

We thank Jianbin Wang, Jin Gu and Fuchou Tang for helpful comments and advice.

This work is supported by the State Key Research Development Program of China

(Grant No. 2018YFA0107603 and 2019YFA0110002); the National Natural Science

Foundation of China (Grants No. 91740204, 91940306, and 31761163007); the Beijing

Advanced Innovation Center for Structural Biology; and the Tsinghua-Peking Joint

Center for Life Sciences.

Author contributions

Q.C.Z. conceived and supervised the project. L.X. designed and implemented the

SCALEX model. L.X. and K.T. validated the SCALEX model. L.X., K.T., and Y.L.

analyzed the results. L.X. and Q.C.Z. wrote the manuscript, with inputs from all the

authors.

Competing interests

The authors declare no competing interests.

Fig. 1 | The design and performance of SCALEX for single-cell data integration.

a, SCALEX models the global structure of single-cell data using a variational

autoencoder (VAE) framework. **b**, UMAP embeddings of the *PBMC* dataset before

and after integration by indicated methods. Cells are colored by batch (left) and

cell-type (right). Misalignments are highlighted with red circles. **c**, Scatter plot

comparing SCALEX and the other state-of-the-art single-cell data integration tools in

terms of the ARI score (y-axis) and the NMI score (x-axis), based on the Leiden

clustering results in the latent space across the indicated benchmark datasets. **d**,

UMAP embeddings of the SCALEX integration of the Human Fetal Atlas dataset

after integration by SCALEX, colored by batch and cell-type. **e**, Comparison of

computation efficiency based on datasets of different sizes sampled from the whole

Human Fetal Atlas dataset) including runtime (left) and memory usage (right). Online

iNMF was not successfully tested on 4M data due to a HDF5 file conversion issue for

large data (Methods). **f**, UMAP embeddings of the mouse brain scATAC-seq dataset

before (left) and after integration (middle, right); colored by data batch or cell-types. **g**,

UMAP embeddings of the PBMC scRNA-seq and scATAC-seq cross-modality

dataset before (left) and after SCALEX integration (middle, right); colored by batch

or cell-type.

Fig. 2 | Comparison of integration performance over partially overlapping

datasets by different methods. a, UMAP embeddings of the integration results by

the indicated methods based on the *liver* dataset. **b**, Over-correction score of different

methods based on the indicated benchmark datasets. **c**, Over-correction score of the

indicated methods based on the simulated datasets, with decreased numbers of

common cell-types (obtained by down-sampling the *pancreas* and *PBMC* dataset). **d**,

UMAP embeddings of the integration results by the indicated methods based on the

simulated *panceas* datasets with different numbers of specified common cell-types.

Over-corrections are highlighted with red circles and error-splittings with purple

circles, respectively.

Fig. 3 | Projecting heterogenous data into a common cell-embedding space. a,

UMAP embeddings of the *pancreas* dataset after integration by SCALEX, colored by

cell-type and by batch. **b**, UMAP embeddings of the common cell space obtained by

using SCALEX to project three additional indicated *pancreas* data batches onto the

pancreas dataset. Cells are colored by cell-type with light gray shadows representing

the original *pancreas* dataset. **c**, Confusion matrix between ground truth cell-types

and those annotated by different methods. ARI, NMI and F1 scores (top) measure the

annotation accuracy. **d**, UMAP embeddings of the common space obtained by using

SCALEX to project the two projected melanoma data batches onto the *PBMC* dataset,

colored by cell-types with light gray shadows represent the original *PBMC* dataset. **e**,

UMAP embeddings of the common cell space that includes the original *PBMC*

dataset and the two projected melanoma data batches. **f**, Annotating an

uncharacterized small cell population in the *pancreas* dataset by projection of the

bronchial epithelium data batches into the pancreas cell space. Only the

uncharacterized cells in the *pancreas* dataset (left) and the SLC16A7+ epithelial cells

in the bronchial epithelium data batches (right) are colored. **g**, Heatmap showing the

normalized expression of the top-10 ranking specific genes for the uncharacterized

cell population in different cell-types.

Fig. 4 | Construction of an expandable mouse single-cell atlas. a, Datasets acquired

using different technologies (Smart-seq2, 10X, and Microwell-seq) covering various

tissues used for construction of the mouse atlas. **b**, UMAP embeddings of the Mouse

Atlas dataset colored by batch and tissue. **c**, UMAP embeddings of the Mouse Atlas

after SCALEX integration, colored by cell-type. **d**, Scatter plot showing a quantitative

comparison of the ARI score (y-axis) and the NMI score (x-axis) based-on the Leiden

clustering results on the latent space based on the Human Atlas, Mouse Atlas, and

Human Fetal Atlas datasets. **e**, Comparison of over-correction score by the indicated

methods based on the Human Atlas, Mouse Atlas, and Human Fetal Atlas datasets. **f**,

UMAP embeddings of the common cell space obtained by using SCALEX to project

the two *Tabula Muris Senis* data batches and two mouse tissues (lung and kidney)

data batches onto the Mouse Atlas dataset. Cells are colored by cell-type with light

gray shadows representing the original Mouse Atlas dataset. **g**, Confusion matrix of

the cell-type annotations by SCALEX and those in the original studies. Color bar

represents the percentage of cells in confusion matrix C_{ij} known to be cell-type i and

predicted to be cell-type j.

Fig. 5 | Online integration of COVID-19 PBMC Atlas. a, The COVID-19 PBMC

Atlas dataset composition, including healthy controls and influenza patients, as well

as mild/moderate, severe, and convalescent COVID-19 patients. **b**,**c** UMAP

embeddings of the COVID-19 PBMC Atlas after SCLAEX integration colored by

cell-type (**b**), and by batch (**c**). **d**, UMAP embeddings of the COVID-19 PBMC Atlas

separated by disease state. Cells are colored by cell-type with light gray shadows

representing the other disease state cells. **e**, Stacked violin plot of

differentially-expressed ISGs among CD14 monocytes across disease states. **f**, GO

terms enriched in the differentially-expressed genes for CD14-IL1B-Mono and

CD14-ISG15-Mono cells. **g**, Cell-type frequency across healthy and influenza

controls, and among mild/moderate, severe, and convalescent COVID-19 patients.

Dirichlet-multinomial regression was used for pairwise comparisons, ***p<0.001,

p<0.01, *p<0.05. **h, UMAP embeddings of the common cell space obtained by

using SCALEX to project the SC4 Atlas (Single Cell Consortium for COVID-19 in

China). Cells are colored by cell-type from label transfer based-on the locations in the

COVID-19 PBMC Atla*s* dataset (left) and cell clusters in original SC4 study (middle),

and Unified UMAP embeddings combining the SCALEX COVID-19 PBMC Atlas

and the SC4 Atlas (right). **i**, Similarity matrix of meta-cell representations for

cell-types between the SCALEX COVID-19 PBMC Atlas and SC4 in the common

cell-embedding space after SCALEX projection. Color bar represents the Pearson

correlation coefficient between the average meta-cell representation of two cell-types

from a respective data batch. **j**, UMAP embeddings of the SCALEX COVID-19

PBMC Atlas colored by the cytokine score and the inflammatory score. **k**, GO terms

enriched in the differentially-expressed genes for TUBA8-Mega and IGKC-Mega

cells.

Supplementary figures

Fig. S1 | Three design elements to learn a generalized encoder. a, Assessing

encoders with or without batch labels. **b**, Assessing decoders with or without DSBN.

c, Assessing mini-batch sampling by batch without Batch Normalization or sampling

from all batches with Batch Normalization. **d**, Detailed architecture of SCALEX and

information flow.

Fig. S2 | Comparisons of integration performance of indicated methods across

the indicated benchmark datasets. UMAP embeddings of the indicated methods

across the indicated benchmark datasets colored by batches and cell-type.

Misalignments are highlighted with red circles.

Fig. S3 | Comparisons of clustering results of indicated methods across the

indicated benchmark datasets. UMAP embeddings of clustering results of the

indicated benchmark datasets after integration by indicated methods; colored by

Leiden (left) and Louvain (right).

Fig. S4 | Comparisons of integration performance by quantification metrics.

Scatter plots showing the ARI and NMI scores based-on the Leiden and Louvain

clustering results, the Silhouette and batch entropy mixing scores, and the cLISI/

iLISI scores.

1077 **Fig. S5 | Comparisons of integration performance of indicated methods based on**

1078 **Human Fetal Atlas dataset. a**, UMAP embeddings of the Human Fetal Atlas before

1079 integration. **b,** Dotplot of canonical marker genes for each cell-type. Dot color

1080 represents average expression level, and dot size represents the proportion of cells in

1081 the group expressing the marker. **c**, UMAP embeddings of the indicated methods

1082 (only SCALEX, BBKNN, Scanorama, and scVI are scalable to the Human Fetal Atlas

1083 dataset). Cells are colored by batch (left), cell-type (middle), and Leiden clustering

1084 (right). **d**, Scatter plot showing the ARI and NMI scores based-on the Leiden

1085 clustering results, the Silhouette and batch entropy mixing scores, and the iLISI and

1086 1/cLISI scores. Note that online iNMF was not successfully tested on the Human

1087 Fetal Atlas due to a HDF5 file conversion issue for large data.

1088 **Fig. S6 | Comparisons of integration performance of indicated methods based on**

1089 **scATAC-seq dataset and other modality datasets. a**, UMAP embeddings of the

1090 mouse brain scATAC-seq dataset before and after integration by indicated methods;

1091 colored by batch (left) and cell-type (right). **b**, Cell-type-specific peaks for the mouse

1092 brain scATAC-seq dataset. **c**, Scatter plot showing the ARI and NMI scores based-on

1093 the Leiden and Louvain clustering results, the Silhouette and batch entropy mixing

1094 scores, and the iLISI and 1/cLISI scores. **d,e**, UMAP embedding before and after

1095 SCALEX integration over CITE-seq (which measures abundance of both RNA and

1096 protein in single cells) spleen lymph dataset and cross-modality mouse brain dataset

1097 between spatial transcriptome (MERFISH) dataset and RNA-seq (10X) dataset.

1098 **Fig. S7 | Comparisons of integration performance of indicated methods based on**

1099 **cross-modality dataset. a**, UMAP embeddings of the PBMC cross-modality dataset

1100 by indicated methods. Cells are colored by batch or cell-type. **b**, Scatter plot showing

1101 a quantitative comparison of the silhouette score (y-axis) and the batch entropy

1102 mixing score (x-axis) (left), ARI (y-axis), and NMI (x-axis) based-on Leiden

clustering (middle) and Louvain clustering (right), the Silhouette and batch entropy

mixing scores, and the iLISI and 1/cLISI scores for the PBMC cross-modality dataset.

Fig. S8 | Canonical marker genes of different cell-types and UMAP embeddings

of the *liver* dataset. a, UMAP embeddings of the *liver* dataset, colored by batch (left)

and cell-type (right) after SCALEX integration. **b,** Dotplot of canonical marker genes

for each cell-type. Dot color represents average expression level, and dot size

represents the proportion of cells in the group expressing the marker. **c**, Normalized

marker gene expression on the UMAP embeddings of the five hepatocyte subtypes.

Color bar represents the expression level.

Fig. S9 | Comparisons of integration performance based on partially overlapping

simulated *pancreas* dataset. a, Partially overlapping datasets were generated by

down-sampling the *pancreas* dataset, consisted of common cell-types with a

decreased overlapping number (ranging from 0 to 6). Integration results for SCALEX,

Seurat, Harmony, and online iNMF are shown in the UMAP embeddings colored by

batches (left) and cell-types (right) respectively (overlapping number decreases from

6 to 0). Misalignments are highlighted with red circles. **b**, Scatter plot showing a

quantitative comparison of the indicated methods in terms of the ARI score (y-axis)

and the NMI score (x-axis), based on the Leiden (top) and Louvain (bottom)

clustering results in the latent space based on simulated *pancreas* datasets.

Fig. S10 | Comparisons of integration performance based on partially

overlapping simulated *PBMC* dataset. a, Partially overlapping datasets were

generated by down-sampling the *PBMC* dataset, consisted of common cell-types with

a decreased overlapping number (ranging from 0 to 6). Integration results for

SCALEX, Seurat, Harmony, and online iNMF are shown in the UMAP embeddings

colored by batches (left) and cell-types (right) respectively (overlapping number

decreases from 6 to 0). Misalignments are highlighted with red circles. **b**, Scatter plot

showing a quantitative comparison of the indicated methods in terms of the ARI score

(y-axis) and the NMI score (x-axis), based on the Leiden (top) and Louvain (bottom)

clustering results in the latent space based on simulated *PBMC* datasets.

Fig. S11 | Projection of three additional pancreas data batches onto the *pancreas*

dataset. a, UMAP embeddings of the *pancreas* dataset and the three additional

pancreas data batches and the bronchial epithelium data batches (data from three

donors) before integration. Cells are colored by batch. **b**, Dot plot of canonical

markers of cell-types of reference *pancreas* dataset; dot color represents average

expression level, and dot size represents the proportion of cells in the group

expressing the marker. **c,** UMAP embeddings of the common cell space obtained by

using online iNMF (top) and scVI (bottom) to project the three additional indicated

pancreas data batches onto the *pancreas* dataset. Cells are colored by cell-type with

light gray shadows representing the original *pancreas* dataset. Misalignments are

highlighted with red circles. Note that here for convenient comparison of the

projected data with the existing data, we showed the UMAP embeddings of the

pancreas dataset combined with the projected data, which are visualized differently

from the UMAP embeddings of the *pancreas* dataset alone in Fig. S2 as UMAP

visualizations change with embedding data.

Fig. S12 | Projection of two melanoma datasets onto the *PBMC* dataset. a, UMAP

embeddings of the *PBMC* dataset and the two additional melanoma data batches

before integration. Cells are colored by batch. **b**, Dot plot of canonical markers of

cell-types of each batch; dot color represents average expression level, while dot size

represents the proportion of cells in the group expressing the marker. **c**, UMAP

embeddings of the common cell space obtained by using online iNMF (top) and scVI

(bottom) to project the two additional indicated melanoma data batches onto the

PBMC dataset. Cells are colored by cell-type with light gray shadows representing the

original *PBMC* dataset. Misalignments are highlighted with red circles. Note that here

for convenient comparison of the projected data with the existing data, we showed the

UMAP embeddings of the *PBMC* dataset combined with the projected data, which are

visualized differently from the UMAP embeddings of the *PBMC* dataset alone in Fig.

S2 as UMAP visualizations change with embedding data.

Fig. S13 | Comparisons of integration across Atlas-level datasets. a, UMAP

embeddings of the indicated methods across the indicated datasets. Results are blank

for those methods not scalable to this data size. **b**, Scatter plots showing the

comparisons of indicated methods in terms of the ARI and NMI scores based-on the

Louvain clustering results, the Silhouette and batch entropy mixing scores, and the

cLISI/ iLISI scores based on the indicated Atlas-level datasets.

Fig. S14 | The SCALEX Mouse Atlas. a, UMAP embeddings of the Mouse Atlas

dataset before integration, colored by batch. **b**, UMAP embeddings of three mouse

atlas data batches (Smart-seq2, 10X, and Microwell-seq) after integration, colored by

cell-type; the light gray shadows represent the original Mouse Atlas dataset. **c**,

Dotplot of the top 5 cell-type-specific genes for each cell-type in the Mouse Atlas

dataset. Dot color represents average expression level, while dot size represents the

proportion of cells in the group expressing the marker. Note that here for convenient

comparison of the projected data with the existing data, we showed the UMAP

embeddings of the Mouse Atlas combined with the projected data, which are

visualized differently from the UMAP embeddings of the Mouse Atlas alone in Fig.

S13 as UMAP visualizations change with embedding data.

Fig. S15 | The SCALEX Human Atlas. a, The Human Atlas dataset acquired using

different technologies (Smart-seq2, 10X, and Microwell-seq) covering various tissues

used for construction of the human atlas. **b-c**, UMAP embeddings of the Human Atlas

dataset colored by batch and cell-type, before (**b**) and after integration (**c**). **d**,

Similarity matrix of meta-cell representations for cell-types in the two data batches in

the common cell-embedding space after SCALEX integration between two batches.

Color bar represents the Pearson correlation coefficient between the average meta-cell

representation of two cell-types from a respective data batch. **e**, UMAP embeddings

of the common cell space obtained by using SCALEX to project the two additional

indicated human skin data batches onto the Human Atlas dataset. Cells are colored by

cell-type with light gray shadows representing the original Human Atlas dataset. **f**,

Confusion matrix of the cell-type annotations by SCALEX and those in the original

study. Color bar represents the percentage of cells in confusion matrix C_{ij} known to be

in cell-type i and predicted to be in cell-type j. Note that here for convenient

comparison of the projected data with the existing data, we showed the UMAP

embeddings of the Human Atlas combined with the projected data, which are

visualized differently from the UMAP embeddings of Human Atlas alone in Fig. S13

as UMAP visualizations change with embedding data.

Fig. S16 | COVID-19 immune landscape. a, UMAP embeddings of the COVID-19

PBMC Atlas dataset before and after integration by indicated methods. Cells are

colored by batch (left), cell-type (middle) and Leiden clustering results (right). **b**,

Scatter plots showing the comparisons of indicated methods in terms of the ARI and

NMI scores based-on the Leiden and Louvain clustering results, the Silhouette and

batch entropy mixing scores, and the cLISI/ iLISI scores. Bar plot showing the

comparisons of indicated methods in terms of the over-correction scores based on the

COVID-19 PBMC Atlas dataset. **c**, Dotplot of canonical marker genes for each

cell-type. Dot color represents average expression level, while dot size represents the

proportion of cells in the group expressing the marker. **d**, UMAP embeddings of the

COVID-19 PBMC atlas in individual batches after SCALEX integration, colored by

cell-type; the light gray shadows represent the other batches of COVID-19 PBMC

atlas. Note that here for convenient comparison of the projected data with the existing

data, we showed the UMAP embeddings of the SCALEX COVID-19 PBMC Atlas

combined with the projected data, which are visualized differently from the UMAP

embeddings of SCALEX COVID-19 PBMC Atlas alone as UMAP visualizations
change with embedding data.

Fig. S17 | COVID-19 heterogeneous dysfunctional immune response. a,
Frequency of cell distributions across healthy people and influenza patient controls,
and among mild/moderate, severe, and convalescent COVID-19 patients.
Dirichlet-multinomial regression was used for pairwise comparisons, ***p<0.001,
p<0.01, *p<0.05. **b, Stacked violin plot of differentially-expressed genes between
PNPLA2-Immature_Neutrophil and NCF1-Immature_Neutrophil cells. **c**, GO terms
enriched in the differentially-expressed genes for PNPLA2-Immature_Neutrophil and
NCF1-Immature_Neutrophil cells. **d**, Stacked violin plot of differentially-expressed
genes between PRDM1-Plasma and MZB1-Plasma. **e**, GO terms enriched in the
differentially-expressed genes for PRDM1-Plasma and MZB1-Plasma cells.

Fig. S18 | Projection of the SC4 Atlas onto the SCLAEX COVID-19 PBMC Atlas.
a-b, UMAP embeddings of the SC4 Atlas before integration (**a**) and after projection
onto the SCALEX COVID-19 PBMC Atlas (**b**). **c**, Separate UMAP embeddings of
each SC4 data batch, after being projected onto the SCALEX COVID-19 PBMC
space, colored by cell-type. light gray shadows represent the COVID-19 PBMC Atlas.
d, UMAP embeddings of the TUBA8-Mega and IGKC-Mega cells. **e**, UMAP
embeddings of the differentially-expressed genes of TUBA8-Mega and IGKC-Mega
cells. **f**, UMAP embeddings of the common cell space obtained by using scVI to
project the *SC4 Atlas* onto the COVID-19 PBMC Atlas dataset. Cells are colored by
cell-type with light gray shadows representing the original COVID-19 PBMC Atlas
dataset. Misalignments are highlighted with red circles.

Fig. S19 | Ablation studies of different SCALE architectures for single-cell data
integration. a, UMAP embeddings after integration by SCALEX and other SCALEX
test-variants. **b**, Scatter plot showing a quantitative comparison of the performance of

the full and different test-variants of SCALEX using the ARI score (y-axis) and the

NMI score (x-axis), the Silhouette score (y-axis) and the batch entropy mixing score

(x-axis), and the 1/cLISI score (y-axis) and the iLISI score (x-axis), across the

indicated benchmark datasets.

Fig. S20 | Ablations studies of different SCALEX architectures for single-cell

data projection. Left: UMAP embeddings of three projected pancreas data batches

projected onto the pancreas space using different SCALEX architectures, colored by

cell-type; light gray shadows represent the original *pancreas* dataset. Right: UMAP

embeddings of the two projected melanoma data batches projected onto the PBMC

space using different SCALEX architectures, colored by cell-type; light gray shadows

represent the original *PBMC* dataset.

Fig. S21 | Comparison of SCALEX with beta=0.5 and beta=1 across the

indicated benchmark datasets. a, UMAP embeddings of SCALEX (beta=0.5) and

SCALEX (beta=1) across the indicated benchmark datasets; colored by batch (left)

and cell-type (right). **b**, Scatter plot showing a quantitative comparison of the

performance of SCALEX (beta=0.5) and SCALEX (beta=1) using the ARI score

(y-axis) and the NMI score (x-axis), the Silhouette score (y-axis) and the batch

entropy mixing score (x-axis), and the 1/cLISI score (y-axis) and the iLISI score

(x-axis), across the indicated benchmark datasets.

Fig 1

Fig 2

Fig 3

Fig 4

a

b batch | tissue

c SCALEX Mouse Atlas

d Mouse Atlas | Human Atlas | Human Fetal Atlas

e Over-correction Score

f Projected: tabula_muris_senis_Smart-seq2 | Projected: tabula_muris_senis_10X | Projected: mouse_lung | Projected: mouse_kidney

g Projected: tabulas_muris_senis_Smart-seq2 ARI:0.905 NMI:0.905 F1:0.871 | Projected: tabulas_muris_senis_10X ARI:0.886 NMI:0.900 F1:0.907 | Projected: mouse_lung ARI:0.885 NMI:0.843 F1:0.863 | Projected: mouse_kidney ARI:0.949 NMI:0.911 F1:0.939

Fig 5

Supplementary Fig 1

a

Encoder with batch label   Encoder without batch label

b

Batch Normalization   Domain-specific Batch Normalization (DSBN)

c

Mini-batch sampling by   Mini-batch sampling from all
batch without Batch Normalization   batches with Batch Normalization

d

x   dim=1024   dim=10   x'
                Encoder   Decoder

Supplementary Fig 2

Supplementary Fig 3

Supplementary Fig 4

Supplementary Fig 5

a

batch

UMAP2 / UMAP1

- GSE156793
- GSE134355

b

c

SCALEX
batch | cell-type | leiden
- GSE156793
- GSE134355

BBKNN
batch | cell-type | leiden

Scanorama
batch | cell-type | leiden

scVI
batch | cell-type | leiden

- Acinar cells
- Adrenocortical cells
- Alveolar cells
- Cardiomyocytes
- Chromaffin cells
- Endocrine cells
- Endothelial cells
- Erythroblasts
- Extravillous trophoblasts
- Eye cells
- Goblet cells
- Hepatoblasts
- Intestinal epithelial cells
- Mesangial cells
- Metanephric cells
- Myeloid cells
- Skeletal muscle cells
- Stromal cells
- T

d

Human Fetal Atlas
ARI / NMI

Human Fetal Atlas
Silhouette Score / Batch Entropy Mixing Score

Human Fetal Atlas
1/cLISI / iLISI

- raw
- SCALEX
- BBKNN
- Scanorama
- scVI

Supplementary Fig 6

Supplementary Fig 7

a

Supplementary Fig 8

Supplementary Fig 9

Supplementary Fig 10

Supplementary Fig 11

Supplementary Fig 12

Supplementary Fig 13

Supplementary Fig 14

a batch

UMAP2 / UMAP1

- Smart-seq2
- 10X
- Microwell-seq

b Mouse Atlas_Smart-seq2   Mouse Atlas_10X   Mouse Atlas_Microwell-seq

- AT2
- B
- Kupffer cell
- T
- acinar
- astrocyte
- basal
- basal of epidermis
- bladder
- cardiac muscle
- collecting duct
- dendritic
- endothelial
- erythroblast
- fibroblast
- granulocyte
- hepatic sinusoid
- hepatocyte
- immature T
- keratinocyte
- keratinocyte stem
- large intestine
- leydig
- luminal
- mesenchymal
- mesenchymal stem
- microglial
- monocyte progenitor
- multipotent progenitor
- myeloid
- myofibroblast
- neuron
- oligodendrocyte
- oligodendrocyte precursor
- ovary
- pancreatic ductal
- pancreatic endocrine
- pro-B
- proximal tubule
- secretory alveoli
- skeletal muscle satellite
- small intestine
- sperm
- stomach
- stromal
- urothelial
- uterus

c

Supplementary Fig 16

Supplementary Fig 17

a

b

c

PNPLA2-Immature_Neutrophil vs NCF1-Immature_Neutrophil2

- regulation of B cell activation
- phagocytosis, engulfment
- B cell receptor signaling pathway
- viral gene expression
- viral transcription
- positive regulation of B cell activation
- positive regulation of lymphocyte activation
- phagocytosis
- viral process
- complement activation, classical pathway
- humoral immune response mediated by circulating immunoglobulin

- cellular protein modification process
- transmembrane receptor protein tyrosine kinase signaling pathway
- regulation of platelet aggregation
- regulation of ERK1 and ERK2 cascade
- Fc receptor mediated stimulatory signaling pathway
- Fc-gamma receptor signaling pathway
- Fc-gamma receptor signaling pathway involved in phagocytosis
- neutrophil mediated immunity
- neutrophil degranulation
- neutrophil activation involved in immune response

$-\log_{10}$(Adjusted P-value)

d

e

PRDM1-Plasma vs MZB1-Plasma

- neutrophil activation involved in immune response
- neutrophil degranulation
- inflammatory response
- cytokine-mediated signaling pathway
- cellular response to cytokine stimulus
- platelet degranulation
- regulation of inflammatory response
- positive regulation of defense response
- positive regulation of interleukin-8 secretion
- positive regulation of inflammatory response
- cellular defense response

- ER to Golgi vesicle-mediated transport
- Golgi vesicle transport
- retrograde vesicle-mediated transport, Golgi to ER
- mitochondrial respiratory chain complex assembly
- mitochondrial respiratory chain complex I assembly
- mitochondrial respiratory chain complex I biogenesis
- NADH dehydrogenase complex assembly
- mitochondrial electron transport, NADH to ubiquinone
- respiratory electron transport chain
- mitochondrial ATP synthesis coupled electron transport

$-\log_{10}$(Adjusted P-value)

Supplementary Fig 18

Supplementary Fig 19

Supplementary Fig 20

a

Supplementary Fig 21

Supplementary Note: Ablation Study

To accomplish an accurate generalized encoder, the design of the full SCALEX included the following specific innovations:

1) an asymmetric autoencoder that inputs batch information only to the decoder (*i.e.*, never to the encoder) (See diagram in Fig. S1);

2) a DSBN layer in the decoder to release the encoder from the burden of capturing the batch-specific variations;

3) a mini-batching strategy that samples data from all batches simultaneously (rather than single batches iteratively) and thus more tightly follows the same overall distribution of the full input dataset; this strategy includes a Batch Normalization layer in the encoder that adjusts the deviation of each mini-batch and aligns them to the overall input distribution.

We conducted ablation studies to investigate the contributions of each design element of SCALEX. That is, we analyzed the performance (for integration and projection tasks) of the full SCALEX and four SCALEX "test-variants", each with a distinct network architecture (Fig. S19-21). These can be summarized as follows:

Full SCALEX (referred as "Baseline" in the following). This Baseline model includes an encoder without batch labeling, sampling from all batches with Batch Normalization, decoder with DSBN, and beta=0.5. All other ablations are compared relative to this.

Encoder with batch label. A test-variant with Baseline including an encoder with batch label as input. We found that the integration performance of this variant is similar with the full SCALEX, showing only a slight reduction in the evaluation scores (Fig. S19). However, the real issue is this: this addition of batch information at the beginning precludes online integration of newly arriving data. Put another way, this SCALEX test-variant is not capable of integrating single-cell data in a truly online manner.

Decoder without DSBN. A test-variant of Baseline removing the DSBN layer from decoder. The DSBN layer combines multiple batch-specific Batch Normalization layers to capture the batch-specific information; this approach has been demonstrated as effective for domain adaption, as it provides a weak alignment across different domains. We observed an obvious drop in the integration performance (in terms of all evaluation scores) and a slight drop in the

projection performance of this SCALEX test-variant, based-on the UMAP embeddings (Fig. S19,20).

Sampling by batch without the Batch Normalization (BN) layer in the encoder. Removing the Batch Normalization layer from the encoder, and each mini-batch is sampled by batch instead of from all the batches. The integration performance of this test-variant was obviously worse than full SCALEX (Fig. S19). The projection performance also dropped obviously, with clear deviations from the common cell-embedding space (Fig. S20).

Regular autoencoder. A test-variant that uses a regular autoencoder instead of a VAE framework. This variant performed the worst among all the variants we tested, for both the integration and projection tasks (Fig. S19,20).

Note that we also explored altering the Beta factor. Replacing the beta factor as 1 instead of 0.5. The integration performance of test variant of SCALEX for beta factor of 1 is worse than the SCALEX for beta factor of 1 (Fig. S21).