₁ morse: an R-package in support of Environmental Risk
₂ Assessment

₃ **Virgile Baudrot[1] and Sandrine Charles[1, 2]**

₄ **1** University of Lyon, University Lyon 1, CNRS UMR5558, Laboratory de Biometry and Evolutionary
₅ Biology, 69100 Villeurbanne, France. **2** Corresponding author (email)

Summary

₇ Package morse is devoted to the analysis of experimental data collected from standard toxicity
₈ tests. It provides ready-to-use functions to visualize a data set and to estimate several toxic-
₉ ity indices to be further used in support of environmental risk assessment in full compliance
₁₀ with regulatory requirements. Such toxicity indices are indeed classical requested by standard-
₁₁ ized regulatory guidelines on which national agencies base their evaluation of applications for
₁₂ marketing authorisation of chemical active substances.

₁₃ Package morse can be used to get estimates of LC_x (x% Lethal Concentration) or EC_x
₁₄ (x% Effective Concentration) by fitting standard exposure-response models on toxicity test
₁₅ data. Risk indicator estimates as well as model parameters are provided along with the
₁₆ quantification of their uncertainty. Package morse can also be used to get estimates of the
₁₇ NEC (No Effect Concentration) by fitting a Toxicokinetic-Toxicodynamic (TKTD) model
₁₈ (namely GUTS models, that is *General Unified Threshold models of Survival*). Using GUTS
₁₉ models also allow to get estimates of $LC_{(x,t)}$ (whatever x and t) and $LP_{(x,t)}$, this later being
₂₀ defined by EFSA as the x% multiplication factor leading to an additional reduction of x%
₂₁ in survival at the end of the exposure profile. Above all, GUTS models can be used on data
₂₂ collected under time-variable exposure profiles.

₂₃ This paper illustrates a typical use of morse with survival data collected over time and at dif-
₂₄ ferent increasing exposure concentrations, analysed with the reduced version of GUTS models
₂₅ based on the stochastic death hypothesis (namely, the GUTS-RED-SD model). This example
₂₆ can be followed step-by-step to analyse any new data set, as long as the data set format is
₂₇ respected.

Statement of Need

₂₉ Package morse (Baudrot et al., 2021) has been tested using R (version 3.5 and later)
₃₀ on macOS, Linux and Windows machines. Regarding the particular case of toxicokinetic-
₃₁ toxicodynamic (TKTD) models for survival, namely GUTS models (Jager & Ashauer, 2018),
₃₂ package morse was ring-tested together with nine other GUTS implementations under different
₃₃ software platforms. All participants to the ring-test received the same data sets and tasks,
₃₄ carried out their simulations independently from each other and sent the results back to the
₃₅ coordinator for analysis. Giving very similar results than the other implementations, package
₃₆ morse was thus confirmed as fit-for-purpose in fitting GUTS models on survival toxicity test
₃₇ data.

₃₈ All functions in package morse can be used without a deep knowledge of their underlying
₃₉ probabilistic model or inference methods. Rather, they were designed to behave as well as

possible, without requiring the user to provide values for some obscure parameters. Neverthe-
less, models implemented in `morse` can also be used as a first step to tailor new models for
more specific situations.

Note that package `morse` benefits from a web interface, MOSAIC, from which the same analyses can be reproduced directly on-line without needs to invest in `R` programming. MOSAIC
is freely available at https://mosaic.univ-lyon1.fr/ (Charles et al., 2018) (Figure 1).

Figure 1: Homepage of the MOSAIC web platform (https://mosaic.univ-lyon1.fr/)..

Availability

Package `morse` is available as an R package; it can be directly downloaded from CRAN https://
CRAN.R-project.org/package=morse, where package dependencies and system requirements
are also documented. The development version can be found on GitHub https://github.com/
pveber/morse, where code contributions, bug reports, fixes and feature requests are more than
welcome by opening issues and pull requests.

Main features

The main functions in package `morse` are `survData()`, `reproData()` and `plotDoseRespo
nse()` to visualize raw data. Functions `survFitTT()`, `reproFitTT()`, `survFit()` allow to
fit a model on data in order to estimate toxicity indicators, the choice depending on the type

of data. Fitting outputs can be either displayed with `plot()` or synthesized with `summary()`. Functions are available to check the goodness-of-fit, namely `ppc()` and `plot_prior_post()`. Predictions can be performed with `predict()`, `predict_ode()`, `predict_Nsurv()` and `predict_Nsurv_ode()`. At last, function `LCx()`and `MFx()` allow to get x% lethal concentrations or profiles, respectively.

The `morse` package currently handles binary and count data, as for example survival and reproduction data. Functions dedicated to binary (resp. count) data analysis start with a `surv` (resp. `repro`) prefix. `morse` provides a similar workflow in both cases:

1. create and validate a data set;
2. explore a data set;
3. plot a data set;
4. fit a model on data and get parameter estimates;
5. check goodness-of-fit with Posterior Predictive Check plot (PPC).

In addition, for binary data handled with `GUTS` models, package `morse` also allows to:

1. calculate and plot $LC_{(x,t)}$ and $LP_{(x,t)}$;
2. compute goodness-of-fit criteria: the PPC percentage, the Normalized Root Mean Square Error (NRMSE) and the Survival probability prediction error at the end of the exposure profile (SPPE).

See (EFSA PPR Panel, 2018) for details.

Those steps are presented in depth in the `Tutorial` available at https://cran.r-project.org/web/packages/morse/vignettes/tutorial.html, with all necessary details to plenty use all `morse` features. A more formal description of the models and the estimation procedures are provided in a document called "Models in morse package" available at https://cran.r-project.org/web/packages/morse/vignettes/modelling.pdf. Please refer to this documentation for further introduction to the use of the `morse` package.

Minimal Working Example

Loading `morse` and its dependencies

In order to use package `morse`, you need to install it with all its dependencies, including JAGS and C++ (see below), as well as other R-packages: mandatory ones (coda, deSolve, dplyr, epitools, graphics, grDevices, ggplot2 ($\geqslant$ 2.1.0), grid, gridExtra, magrittr, methods, reshape2, rjags ($\geqslant$ 4.0), stats, tibble, tidyr, zoo) and suggested ones (knitr, rmarkdown, testthat). For this purpose, you can use the two classical R commands:

```r
### install the `morse` package, if needed
if(is.element('morse', installed.packages()[,1]) == FALSE){
  install.packages('morse')
}
### load the `morse` package
library(morse)
```

The `morse` package is linked to JAGS http://mcmc-jags.sourceforge.net/ that is the Bayesian sampler used to perform inference with all implemented models. So, you need also to download and install JAGS at https://sourceforge.net/projects/mcmc-jags/. Then you must test that your R graphical user interface has access to JAGS, and, if not, to specify where JAGS can be found on your computer. Indeed, once installed, JAGS can be lost in the PATH. To help solving this issue, you can use package `runjags` which is not within `morse` so that you have to install and load it too.

```
### install the `runjags` package, if needed
if(is.element('runjags', installed.packages()[,1]) == FALSE){
  install.packages('runjags')
}
### load the `runjags` package
library("runjags")
### run test
testjags()
```

The output should look like this:

```
You are using R version 4.0.2 (2020-06-22) on a windows machine, with the RStudio
JAGS version 4.3.0 found successfully using the command
'C:/Program Files/JAGS/JAGS-4.3.0/x64/bin/jags-terminal.exe'
The rjags package is installed
```

Otherwise, you can specify to your R graphical user interface where JAGS executable is located in your computer (somewhere in `'C:/Program Files/JAGS/JAGS-4.3.0/x64/bin/jags-terminal.exe'` on Windows machines):

```
testjags(jags=runjags.getOption('jagspath'))
### replace `jagspath` by your own PATH to JAGS
### For instance
### 'C:/Program Files/JAGS/JAGS-4.3.0/x64/bin/jags-terminal.exe'
```

C++

The `morse` package is also linked to C++. C++ is used for running simulations leading to predictions. In R, you should not have issues with C++ requirements since it is very well integrated (many R functions are simple interfaces to C++ functions). Feel free to report any trouble at https://github.com/pveber/morse/issues by opening a new issue for the `morse` package.

Survival analysis

We assume hereafter that `morse` and all the above dependencies have been corrected installed. To illustrate the use of `morse`, we will use a standard survival data set coming from a chronic laboratory toxicity test with *Gammarus pulex*, a freshwater invertebrate, exposed to increasing concentrations of propiconazole (a fungicide) during four days. Eight concentrations were tested with two replicates of 10 organisms per concentration. Survival was monitored at five time points (at day 0, 1, 2, 3 and 4) (Nyman et al., 2012).

We will used the reduced version of the GUTS model based on the stochastic death hypothesis (namely, the GUTS-RED-SD model), as recommended by the *European Food Safety Authority* (EFSA) for the environmental risk assessment (ERA) of plant protection products potentially toxic for aquatic living organisms (EFSA PPR Panel, 2018). This model can also be fitted on-line with the MOSAIC web platform (Baudrot, Veber, et al., 2018). Below is the *modus operandi* with package morse to be followed step-by-step in order to be in full compliance with the EFSA workflow for ERA.

Calibration step

```
### load package `morse`
library(morse)
### load a data set
data("propiconazole")
### create a morse object for binary data analysis
survData_PRZ <- survData(propiconazole)
### fit a reduced GUTS model (GUTS-RED) with option "SD" (Stochastic Death)
fit_cstSD <- survFit(survData_PRZ, model_type = "SD")
### plot the fitting result
plot(fit_cstSD)
```

Figure 2: Fitting result with a GUTS-RED-SD model. The median fitted curves are in orange and the uncertainty bands in gray. Black dots are observed data surrounded by their binomial confidence intervals.

Get the x% lethal concentration

Using a GUTS model with `morse` allows to get a probability distribution on the x% lethal concentration whatever the exposure duration t, namely the $LC_{(x,t)}$. By default, t corresponds to the last time point in the data set and $x = 50$%.

```
### run function LCx()
LCX_cstSD <- LCx(fit_cstSD)
### plot the output as a concentration-response curve
plot(LCX_cstSD)
```

Figure 3: Simulated concentration-response curve corresponding to the previous fitting result on Figure 2.

Validation step

Validation consists in predicting the number of survivors over time under pulsed-exposure profiles for which observations have also been collected. Predictions are then compared to observations and their adequacy is checked according to several validation criteria defined by EFSA (EFSA PPR Panel, 2018). The aim of this step is to choose an appropriate model for the following step.

```
### load data collected under pulsed exposure profiles
data("propiconazole_pulse_exposure")
### predict the number of survivors for all profiles
predict_Nsurv <- predict_Nsurv_ode(
  object = fit_cstSD,
  data_predict = propiconazole_pulse_exposure
)
### plot results
plot(predict_Nsurv)
```

```
predict_Nsurv_check(predict_Nsurv)
```

Figure 4: Visual check of adequacy between predictions based on the GUTS-RED-SD model with parameter values estimated in the calibration step (median prediction in orange, uncertainty band in gray), and observations (black dots).

Once the predictions are visually checked (Figure 4), quantitative validation criteria need to be calculated.

```
### check for adequacy between predictions and observations
predict_Nsurv_check(predict_Nsurv)

check <- predict_Nsurv_check(predict_Nsurv)
check$Percent_PPC_global
check$Percent_NRMSE_global
```

This reveals that, in total, 84% of the observations lie within the uncertainty band of the predictions, while the global variability of data around the predictions is 16.2%. For both criteria, a maximum value of 50% is expected, what means here that we do not expect specific risk for the species and the chemical compound under consideration.

Prediction step

Risk assessors are interested in testing various exposure scenarios, having a certain environmental realism that is varying over time. Risk assessors expect to evaluate the potential impact of these profiles on survival of target species to protect. Typically, they want to compute the multiplication factor $MF_{(x,t)}$ that could be applied to the exposure profile without reducing more than by $x\%$ the survival probability at a specified test duration t (default being the last time point of the exposure profile). This is the so-called $x\%$ lethal profile, denoted LP_x, and newly proposed by (EFSA PPR Panel, 2018). This calculation is provided by function MFx() in morse.

The mathematical definition of the $x\%$ Multiplication Factor at time t (at the end of a time series $T = \{0, , t\}$) is given by:

$$S\left(MF_{(x,t)} \times C_w(\tau \in T), t\right) = S(C_w(\tau \in T), t) \times \left(1 - \frac{x}{100}\right)$$

where $C_w(\tau \in T)$ is the original exposure profile, and expression $S\left(MF_{(x,t)} \times C_w(\tau \in T), t\right)$ the survival probability after the exposure profile has been translated upward by a multiplication $MF_{(x,t)}$; the new exposure profile thus becomes equal to $MF_{(x,t)} \times C_w(\tau \in T)$.

```
### define an exposure profile (here a theoretical one)
data_4MFx <- data.frame(time = 1:10,
                        conc = c(0,0.5,8,3,0,0,0.5,8,3.5,0))
### run function MFx()
MFx_PRZ_cstSD <- MFx(object = fit_cstSD, data_predict = data_4MFx, ode = TRUE)
### plot the survival probability at the end of the exposure profile
### according to a range of multiplication factors (log-scale)
plot(MFx_PRZ_cstSD, log_scale = TRUE)
```

Figure 5: (left) Predicted survival probability according to a range of multiplication factors (log-scale) at the end of a theoretical exposure profile (right).

Predict survival probability under any exposure profile

Finally, it may be useful to predict the survival probability under any exposure profile (time-variable or not), for example when designing new experiments or to better understand what happens in field. Below are some examples from which you can inspire to perform your own simulations.

```r
### define an exposure profile (here a theoretical one)
### note that here you need to specify a third column `replicate`
data_example <- data.frame(
    time = c(1,1.9,2,15,15.1,20),
    conc = c(0,0,20,20,0,0),
    replicate = rep("Basic example", 6)
)
### perform basic prediction
predict_example_NULL <- predict_ode(
  object = fit_cstSD,
  data_predict = data_example,
  mcmc_size = 10,
  interpolate_length = NULL)
### plot the result for only few exposure time points
plot(predict_example_NULL)
### define the same basic exposure profile
### but by changing the `replicate` value
data_example <- data.frame(
    time = c(1,1.9,2,15,15.1,20),
    conc = c(0,0,20,20,0,0),
    replicate = rep("Basic example (interpolation)", 6)
)
##### perform prediction with interpolation of the exposure profile
predict_example_100 <- predict_ode(
  object = fit_cstSD,
  data_predict = data_example,
  mcmc_size = 10,
  interpolate_length = 100)
# plot the result
plot(predict_example_100)
### load an environmentally realistic profile
data("FOCUSprofile")
FOCUSprofile[,"replicate"] <- "FOCUS example"
### perform prediction
predict_FOCUS <- predict_ode(
  object = fit_cstSD,
  data_predict = FOCUSprofile,
  mcmc_size = 10,
  interpolate_length = NULL)
### plot the result
plot(predict_FOCUS)
```

Figure 6: (left) Basic exposure profile; (right) Environmentally realistic exposure profile.

Figure 7: (left) Predicted survival probability over time under the basic exposure profile without interpolation; (middle) Predicted survival probability over time under the basic exposure profile with interpolation; (right) Predicted survival probability over time under an environmentally realistic exposure profile.

Research using `morse`

Package `morse` was recently used to evaluate the added-value of using TKTD models in comparison with classical dose-response models, based on a case study with the snail *Limnaea stagnalis* when exposed to increasing concentrations of cadmium (Baudrot, Preux, et al., 2018). Also based on `morse`, we proposed some recommendations to address TKTD assessment using uncertainties in environmental risk models (Baudrot & Charles, 2019).

Data availability

A collection of eight data sets is made available directly in package `morse` (use function `data()`). These data sets can also be downloaded on-line from the MOSAIC web platform by visiting the different modules: https://mosaic.univ-lyon1.fr.

Author contributions

V.B. (main developer of `morse`): conceptualization, methodology, formal analysis, data curation, visualization, writing manuscript. S.C.: supervision, funding acquisition, project administration, formal analysis, data curation, writing manuscript.

Acknowledgments

Authors fully thank all contributors to the `morse` package: Marie Laure Delignette-Muller, Wandrille Duchemin, Benoît Goussen, Nils Kehrein, Guillaume Kon-Kam-King, Christelle Lopes, Philippe Ruiz, Alexander Singer and Philippe Veber. They also thank the French National Agency for Water and Aquatic Environments (ONEMA, now the French Agency for Biodiversity) for its financial support to the development of the `morse` package.

References

Baudrot, V., & Charles, S. (2019). Recommendations to address uncertainties in environmental risk assessment using toxicokinetics-toxicodynamics models. *Scientific Reports, Natureresearch, 9*, 11432. https://doi.org/http://dx.doi.org/10.1101/356469

Baudrot, V., Charles, S., Delignette-Muller, M. L., Duchemin, W., Goussen, B., Kehrein, N., Kon-Kam-King, G., Lopes, C., Ruiz, P., Singer, A., & Veber, P. (2021). *Morse: Modelling tools for reproduction and survival data in ecotoxicology*. https://CRAN.R-project.org/package=morse

Baudrot, V., Preux, S., Ducrot, V., Pavé, A., & Charles, S. (2018). New insights to compare and choose TKTD models for survival based on an inter-laboratory study for Lymnaea stagnalis exposed to Cd. *Environmental Science & Technology*, *52*(3), 1582–1590. https://doi.org/10.1021/acs.est.7b05464

Baudrot, V., Veber, P., Gence, G., & Charles, S. (2018). Fit Reduced GUTS Models Online: From Theory to Practice. *Integrated Environmental Assessment and Management*, *14*(5), 625–630. https://doi.org/10.1002/ieam.4061

Charles, S., Delignette-Muller, M. L., Veber, P., & Delignette-Muller, M. L. (2018). MOSAIC: a web-interface for statistical analyses in ecotoxicology. *Environmental Science and Pollution Research*, *25*, 11295–11302. https://doi.org/10.1007/s11356-017-9809-4

EFSA PPR Panel. (2018). Scientific Opinion on the state of the art of Toxicokinetic/Toxicodynamic (TKTD) effect models for regulatory risk assessment of pesticides for aquatic organisms. *EFSA Journal*, *16*(8), 5377. https://doi.org/10.2903/j.efsa.2018.5377

Jager, T., & Ashauer, R. (2018). *Modelling survival under chemical stress. A comprehensive guide to the GUTS framework* (Leanpub, pp. Version 1.0). ISBN: 9781999970505

203 Nyman, A.-M., Schirmer, K., & Ashauer, R. (2012). Toxicokinetic-toxicodynamic modelling of
204 survival of Gammarus pulex in multiple pulse exposures to propiconazole: model assump-
205 tions, calibration data requirements and predictive power. *Ecotoxicology*, *21*, 1828–1840.