Comprehensive benchmarking of tools to identify phages in metagenomic shotgun

sequencing data

Siu Fung Stanley Ho[1], Andrew D. Millard[2], Willem van Schaik[1, *]

[1] Institute of Microbiology and Infection, College of Medical and Dental Sciences, University

of Birmingham, Birmingham, United Kingdom

[2] Department of Genetics and Genome Biology, University of Leicester, Leicester, United

Kingdom

[*] Corresponding author: w.vanschaik@bham.ac.uk.

Abstract

Background

As the relevance of bacteriophages in shaping diversity in microbial ecosystems is becoming increasingly clear, the prediction of phage sequences in metagenomic datasets has become a topic of considerable interest, which has led to the development of many novel bioinformatic tools. A comprehensive comparative analysis of these tools has so far not been performed.

Methods

We benchmarked ten state-of-the-art phage identification tools. We used artificial contigs generated from complete RefSeq genomes representing phages, plasmids, and chromosomes, and a previously sequenced mock community containing four phage strains to evaluate the precision, recall and F1-scores of the tools. In addition, a set of previously simulated viromes was used to assess diversity bias in each tool's output.

Results

DeepVirFinder performed best across the datasets of artificial contigs and the mock community, with the highest F1-scores (0.98 and 0.61 respectively). Generally, machine learning-based tools performed better on the artificial contigs, while reference and machine learning based tool performed comparably on the mock community. Most tools produced a viral genome set that had similar alpha and beta diversity patterns to the original population with the notable exception of Seeker, whose metrics differed significantly from the diversity of the underlying data.

Conclusions

This study provides key metrics used to assess performance of phage detection tools, offers a framework for further comparison of additional viral discovery tools, and discusses optimal strategies for using these tools.

Introduction

Bacteriophages (phages) and archaeal viruses are globally ubiquitous, diverse and typically outnumber their prokaryotic hosts in most biomes [1]. Phages play a key role in microbial communities by shaping and maintaining microbial ecology by fostering coevolutionary relationships [2–4]; biogeochemical cycling of essential nutrients [5–7]; and facilitating microbial evolution through horizontal gene transfer [8–10]. Despite the abundance and perceived influence phages have on all microbial ecosystems, they continue to be one of the least studied and understood members of complex microbiomes [11]. Phages are obligate parasites which require their bacterial host's machinery to replicate, and subsequently spread via cell lysis. They can either be lytic or temperate, and while the former can only follow the lytic life cycle, temperate phages can either follow the lytic or lysogenic cycle [12]. During the lytic cycle, phages hijack host cell machinery to produce new viral particles. In the lysogenic cycle, phages can integrate their genomes into the genome of the bacterial host as linear DNA or as a self-replicating autonomous plasmid. In addition, an alternative life cycle, termed pseudolysogeny, has been documented, during which neither phage genome replication nor prophage formation occurs [13].

Traditionally, phage identification and characterisation relied on isolation and culturing techniques, which are time-consuming and often fail to capture the full repertoire of phages in an ecosystem as many hosts, and their phages, cannot be cultured under laboratory conditions [14]. The arrival of high-throughput next generation sequencing has allowed metagenomic data from various environments to be generated routinely. Metagenomic sequencing allows direct identification and analysis of all genetic material in a sample, regardless of cultivability [15]. In metagenomic studies, researchers can opt to either sequence the whole community metagenome and then computationally isolate viral sequences, or physically separate the viral fraction before library preparation to produce a metavirome. The latter approach risks eliminating a large proportion of phages owing to their association with the cellular fraction, due to their integration into their hosts' genome as prophages [16], attachment to their hosts' surface [17], or their presence in a pseudolysogenic state [18–20]. Purification methods may also remove certain types of phage, e.g. chloroform can inactivate lipid enveloped and/or filamentous phages [21, 22], increasing sampling bias. The isolation of viral particles frequently results in low DNA yields, leading to metavirome studies having to use multiple displacement amplification (MDA) to achieve sufficient quantities of DNA for library generation [11]. MDA has been shown to produce significant bias into virome composition [23, 24], by preferentially amplifying small circular ssDNA phage, such as those from the family *Microviridae* [25]. Ideally, the purification of viral particles will lead to a metavirome with very little host contamination.

However, it is very difficult to produce a viral fraction that is devoid of DNA originating from

microbes that are present in the ecosystem [26]. Alternatively, whole community

metagenomic sequencing can present insights into the host and viral fractions concurrently,

allowing host-phage dynamics to be analysed. Integrated phages or prophages which have

been found to be prevalent in some environments [27], can be identified since host genomes

are also sequenced in this process.

Many tools for identifying viral sequences from mixed metagenomic and virome assemblies

have been developed in the last five years (Table 1) and we will shortly discuss these here.

VirSorter [28] was one of the first of these, with previous tools focusing on prophage

prediction (PhiSpy [29], Phage_Finder [30], PHAST/PHASTER [31], ProPhinder [32]) or

virome analysis (MetaVir2 [33], VIROME [34]). VirSorter identifies phage sequences by

detecting viral hallmark genes that have homology to reference databases, and by building

probabilistic models based on different metrics (viral-like genes, PFAM genes,

uncharacterised genes, short genes, and strand switching) which measure the confidence of

each prediction. Since VirSorter's release, other homology based tools (MetaPhinder [35]

and VirusSeeker [36]) have been developed.

VirFinder was the first machine learning, reference-free viral identification tool, utilising k-mer

signatures [37]. VirFinder had considerably better performance in recovering viral sequences

than VirSorter, especially on shorter sequences (<5,000 bp). However, it displayed variable

performance in different environments, perhaps due to biases introduced by the reference

data used for training the machine learning model [38]. A number of machine/deep learning

tools have since been published, including DeepVirFinder [39], which boasts increased viral

identification at all contig lengths over its predecessor VirFinder, whilst mitigating the latter's

biases by including various metavirome datasets that contain uncultivated viral sequences.

Other recent tools have started utilising alternative approaches. MARVEL [40], integrates the

two approaches described above, using a random forest model to leverage sequence

features (gene density and strand shifts) and homologies (hits to pVOGs (Prokaryotic Virus

Orthologous Groups) database [41]). This allows the tool to identify metagenomic bins that

resemble phages, with comparable specificity but improved sensitivity to VirSorter and

VirFinder. This detection is however currently limited to phages of the *Caudovirales* order.

VIBRANT also employs a hybrid machine learning and protein similarity approach but is able

to recover a diverse array of phages infecting bacteria and archaea, including integrated

prophages. In addition, it characterises auxiliary metabolic genes and pathways after phage

identification.

MetaviralSPAdes [42] uses an entirely different approach by leveraging variations in depth

between viral and bacterial chromosomes in assembly graphs. The tool is split into three

separate modules: a specialised assembler based on metaSPAdes (viralAssembly); a viral

identification module that classifies contigs as viral/bacterial/uncertain using a Naive

Bayesian classifier (viralVerify); and a module which calculates the similarity of a constructed

viral contig to known viruses (viralComplete).

With the development of so many tools using a variety of approaches, a comprehensive

comparison and benchmarking is needed to evaluate which tools are most useful to

researchers. The performance of each method can vary based on sample content, assembly

method, sequence length, classification thresholds and other custom parameters. To

address these issues, we have benchmarked ten metagenomic viral identification tools using

both artificial contigs, mock communities and real samples.

Results

Benchmarking with RefSeq phage and non-viral artificial contigs

Ten commonly used tools for viral sequence identification in metagenomes were selected for

evaluation: DeepVirFinder; MARVEL; MetaPhinder; PPR Meta; Seeker; VIBRANT;

ViralVerify; VirFinder; VirSorter; and VirSorter2. All of these tools can be run locally without

the use of a web server; accept metagenomic contigs as input, except MARVEL which

requires bins to be created first; and have been published in the past decade.

We first evaluated all the programs on the same uniform datasets. All complete phage

genomes deposited in RefSeq between 1 January 2018 and 2 July 2020 later were

downloaded, quality controlled, and fragmented to create a true positive set of artificial

contigs. A negative set was constructed from all RefSeq bacterial and archaeal plasmids,

and a random 1:10 subsample of all RefSeq bacterial and archaeal chromosomes,

submitted in the same time frame. As chromosomes often have prophages integrated within

them, which would cause tools to falsely identify some contigs as viral, we removed these

with two state-of-the-art prophage detection tools, Phigaro [43] and PhageBoost [44]. The

negative dataset is considerably larger than the true positive dataset as we wanted to

consider the performance of these tools in metagenomic shotgun sequencing datasets which

are typically dominated by non-viral sequences. All evaluated programs, except MARVEL,

produce thresholds or confidence ranges for viral identification. For tools (DeepVirFinder,

MetaPhinder, PPR Meta, Seeker, VirFinder, and VirSorter2) that assign a continuous

threshold (score, identity, or probability), a F1 curve was plotted, and an optimal threshold

was determined (Additional File 1). For VIBRANT, VirSorter and ViralVerify, the categories

that returned the highest F1 score were used. In most tools there was a trade-off between

precision and recall. This is likely due to relaxed thresholds allowing for more viral and non-

viral sequences to be detected, increasing recall, and decreasing precision simultaneously.

Additionally, for VIBRANT and VirSorter, the true positive dataset was run in virome mode

and virome decontamination mode respectively, as this improves viral recovery in samples

composed mainly of viral sequences by adjusting the tools sensitivity [28, 45]. The optimal

settings for each of these two tools found determined using this dataset were then used for

subsequent analyses The tools we benchmarked on this dataset had highly variable

performance in terms of their F1-score (0.36 – 0.99), precision (0.23 – 0.98), and recall (0.46

– 1.00) (Figure 1). DeepVirFinder and its predecessor VirFinder achieved the highest F1-

scores of 0.99 and 0.98 respectively. These tools identified the majority of the true positive

dataset as viral, and classified markedly less of the bacterial chromosome and plasmids

fragments as viral, compared to other tools. PPR Meta, another machine learning based

classifier, also performed well with an F1-score of 0.89. The homology-based tool ViralVerify
similarly performed well (F1=0.81) with almost perfect recall (0.98) but a larger proportion of
false positives resulted in a lower precision score (0.69). MetaPhinder, VIBRANT, VirSorter
and VirSorter2 performed similarly (F1-scores of 0.60, 0.71, 0.63 and 0.68 respectively) with
Seeker and MARVEL achieving relatively low scores due to their poor precision (0.39 and
0.36 respectively). Generally, pure machine learning based tools (DeepVirFinder, Seeker,
PPR Meta, VirFinder) outperformed both mixed methods (MARVEL, VIBRANT, VirSorter2)
and reference-based methods (MetaPhinder, ViralVerify, VirSorter) with average F1-scores
of 0.81, 0.58, and 0.68 respectively, although these differences are not statistically
significant due to the small sample sizes. Across our benchmark, every true positive phage
contig was found by at least one tool, with 19.6% (1648/8411) found by all 10 tools
(Additional File 2).

Benchmarking tools with mock community shotgun metagenomes

We next sought to compare these tools on real community shotgun metagenomic contigs.
Thus, we obtained sequencing data of an uneven mock community created by Kleiner *et al.*
[46], containing 32 species from across the tree of life, including five bacteriophages, at a
large range of cell abundances (0.25%- 21.25%; Additional File 3). This allowed us to
assess the performance of our tools on real data whilst retaining knowledge of the ground
truth (sample composition) and determine each tool's detection limit on low abundance
species. In general, the tools' F1-scores were considerably lower on this dataset than on the
RefSeq artificial contigs, with F1-scores of machine learning-based tools dropping by 42%
and reference-based tools by 33%, compared to the RefSeq benchmark (Figure 2).
DeepVirFinder again outperformed all other tools despite a lower F1-score (0.61) and was
closely followed by MetaPhinder which obtained a similar score to the previous dataset
(0.56). However, DeepVirFinder achieved this score by having a lower recall (0.51) but the
best precision (0.76), with MetaPhinder generating the opposite result, with the highest recall
(0.94) and poorer precision (0.40). VirSorter, PPR Meta, and Seeker achieved comparable
scores of 0.47, 0.47, and 0.46 respectively, with the latter being the only tool that performed
better on this dataset than the first. VirSorter2 attained a lower F1-score (0.35) than its
predecessor in this experiment, as a result of predicting 26.1% more true positive contigs but
returning 166% more false positives, resulting in a low precision score (0.23). MARVEL,
despite now having real bins as input, had a 39% lower F1-score than its RefSeq benchmark
score, which is almost identical to the average decrease in F1-score across tools (40%).
VirFinder, one of the tools that performed very well on the previous dataset, only identified
nine out of 96 viral contigs across the three replicate samples, resulting in a very low recall

(0.09) and thus the lowest F1-score of all the tools (0.15). Similarly, ViralVerify performed
poorly with a F1-score of 0.25, as a result of relatively low recall (0.42) and very low
precision (0.17). Unlike in the previous analyses using the RefSeq benchmark dataset,
machine learning based tools and reference-based tools performed almost identically with
average F1-scores of 0.42 and 0.43 respectively, with mixed methods having a lower
average F1-score of 0.30.

Out of the four phage species found in the assemblies, no tool was able to identify M13.
PPR Meta, MetaPhinder, ViralVerify, and VirSorter2 were able to identify contigs belonging
to the other three species – F0, ES18, and P22. VirSorter and VIBRANT were able to
identify the three phage strains in two out of three samples and one out of three samples
respectively, missing out contigs belonging to phage ES18. MARVEL predicted two phages
across all samples, F0 and P22, with DeepVirFinder, VirFinder and Seeker only picking up
the most abundant phage strain, F0. No correlation was found between F1-score and the
number of phage strains detected (R_s = 0.146, p = 0.69) but a positive correlation was
observed between tools that identified more contigs of viral origin (true positives + false
positives), and the number of phage strains identified (R_s = 0.726, p = 0.02).

We also recorded the running times of each tool on this dataset on a high-performance
cluster (8 VCPU) (Figure 3). DeepVirFinder, MetaPhinder, PPR Meta, Seeker, and VirFinder
were the fastest tools finishing each sample in under twenty minutes. Vibrant and ViralVerify
performed their analyses in ~35 mins/sample and 1 hr/sample respectively. VirSorter
required just under two hours to run each sample, with both MARVEL and VirSorter2 taking
over four hours; MARVEL's runtime was over five hours/sample in total, if binning time is
included.

Impact of tool prediction on diversity metric estimation

To test the impact of these tools on diversity estimates, four simulated mock community
metaviromes containing an average of 719 viral genomes were retrieved from Roux *et al.*
[47]. Reads were mapped to contigs (>1 kb) that were identified as viral by each tool, and
these mapped reads were then mapped to a set of population contigs to estimate their
abundance in each sample. Original reads were also directly mapped to the population
contigs as a control. Read counts were then normalised by their length and sequencing
depth, which Roux *et al.* [47] found to be reliable normalisation method. Diversity estimation
metrics were then calculated using the normalised population counts. All tools returned less
genomes per sample compared to the initial population, although there was significant
variation between tools. DeepVirFinder, MetaPhinder, PPR Meta, and VirFinder retrieved the

greatest percentage of genomes with 90.8%, 88.5%, 80.9%, and 88.1% respectively (Figure

4A). All other tools were able to retrieve more than 50% of the genomes with the exception

of Seeker, which was only able to recover 28.7% of the population genomes. All Shannon's

alpha diversities calculated from the count matrices of each tool were within 3% of the initial

population with the exception of Seeker, whose H score was on average 27.2% lower

(Figure 4B). Similarly, all but two tools identified populations with a Simpson alpha diversity

index that was <1% different from the initial population, with MARVEL and Seeker's being

1.8% and 6.2% divergent, respectively (Figure 4C). MARVEL and ViralVerify, which only

predicted ~50% of the total genomes in the initial population, were the only tools to estimate

a comparatively higher alpha diversity than the initial population. For beta diversity, pairwise

Bray-Curtis dissimilarities within a sample were small between all tools except for Seeker

(Additional File 4), whose Analysis of Similarity (ANOSIM) showed significant dissimilarity

when compared to other tools (r = 0.495, p = 0.0002 with Benjamini–Hochberg correction for

multiple comparisons) (Figure 4D; Additional File 5).

Discussion

Bacteriophages are crucial members of microbial communities in nearly every ecosystem on Earth and are responsible for controlling host population size as well as having wider impacts on community functions. Tools designed to recover viral sequences from mixed community metagenomic and virome samples are fundamental to studying the role of bacteriophages in the wider context of their environment. Advancements in this field have produced an extensive suite of viral identification tools that each claim to improve on the performance of similar tools. Selecting which tool among these is ideal for a certain dataset is thus not straightforward, especially as each novel tool typically only benchmarks against two or three other existing tools. Most tools developed for this purpose, especially those released in recent years have utilised machine/deep learning to classify sequences, whereas others rely on direct sequence similarity to databases. Both these approaches have potential to improve over time with newly discovered viral genomes being added to training datasets and databases.

Here, we compare ten methods for identifying viral sequences from metagenomes across three datasets. We first benchmarked the tools on positive and negative datasets to evaluate their performance on an ideal set of contigs (size ≥ 1kb, without mis-assemblies), and determine approximate optimal thresholds. There was no significant difference in performance between machine learning and similarity-based classifiers, although the variance within these categories were high. DeepVirFinder and VirFinder, which were the only tools benchmarked that rely on k-mer frequencies, outperformed all other tools, exemplifying the power of this method. Machine learning tools performed better than reference and mixed-method tools, although the relatively low number of tools compared here may not mean that this is a generalisable observation. Prior to this study, we expected that mixed-method tools would gain an edge by providing the benefits of both machine learning and reference-based methods and minimising their weaknesses, but this does not seem to have been realised in the current generation of tools. Whilst the optimal thresholds that we determined may not necessarily be ideal for all other datasets, we believe they can be used as a basis for further usage of these tools as in each case they produced considerably better results than the default parameters. We therefore encourage researchers to apply these thresholds and parameters within the context of their prospective dataset.

When tested on real metagenomic data, most tools performed significantly worse compared to the RefSeq dataset, although DeepVirFinder had the best performance, along with MetaPhinder. Generally, reference similarity tools had a lower drop in F1-score compared to

the RefSeq dataset than deep learning tools, which is probably due to the presence of only
four phage strains in each sample, all of which are widely available in the public databases
used by these programs. This suggests that when studying metagenomic datasets where
viral species are expected to be present at low frequencies, or where only a few phage
strains of interest are being searched for, reference-based tools such as MetaPhinder or
VirSorter are reasonable choices, especially when recall is more important than precision.
When high precision is preferred, DeepVirFinder is the ideal choice, whilst also producing
the best F1-score overall. Runtime and computational load are also important factors to
examine, since these can become practical limitations if large samples take many hours or
days to be analysed. Most tools were reasonably fast, although a few took multiple hours to
complete their run. Generally, tools that only relied of machine learning prediction were
considerably faster. It is important to note that VIBRANT, VirSorter, and VirSorter2 annotate
the identified viral genomes and predict prophages and MARVEL's pipeline produces
metagenomic bins at the expense of runtime, although these can be useful for some
applications.

We also gauged any potential biases and impact these tools may have on the diversity of its
predicted viral population. Most tools performed well with alpha diversity indices within 10%
of the default population with the exception of Seeker which returned a considerably lower
value due to the very low number of viral population genomes Seeker originally predicted.
Some tools such as MARVEL and ViralVerify predicted higher alpha diversity than default
population. This is due to the tools missing some high abundance genomes from their
predictions, resulting in a more even diversity distribution. When evaluating beta diversity,
Seeker was the only tool that produced results that had significant dissimilarity from the
other tools and did not cluster with the other programs, again as a result of the low
proportion of genomes it recovered in this dataset. Hence beta diversity trends of the tools
examined here, with the exception of Seeker, are accurate to the original population, even
when only half the genomes are recovered.

Although these benchmarks comprehensively compared the performance of state-of-the-art
tools, there are a number of limitations with our study. First, whilst an effort was made to
benchmark the machine learning based tools on data that it was not trained on, not all tools
segregated their datasets by date or were not trained on NCBI RefSeq genome data (PPR
Meta, VIBRANT, VirSorter2, ViralVerify), so there may be instances of overlap between a
tool's training dataset and our RefSeq benchmark contig set. Second, whilst we use RefSeq
genomes, and a mock metagenomic community to benchmark these tools, we did not
address the tools' ability to identify viral sequences belonging to different phage families.
Some tools such as MARVEL are specifically designed to detect certain families (those

within the order *Caudovirales)*, and would therefore not perform as well on other phage

families such as the *Microviridae* [11]. Third, we used the default database or the original

trained model that was provided with each tool. Whilst providing each tool the same

database, or dataset to be trained on, may have been a fairer comparison of the underlying

algorithms, this was beyond the scope of our study. We note that most routine users are also

unlikely to retrain these tools prior to their use. Fifth, we did not assess the performance of

combining multiple tools, which could provide meaning insights that would be missed when

only one single tool is used, as in Marquet *et al.* [48] where the authors combined multiple

tools into a single workflow. Finally, a few recently developed tools we found during our

study were not included in our benchmarking either due to (1) requiring the use of its own

web server and therefore not being scalable (VIROME, VirMiner), (2) lack of clear

installation/running instructions (ViraMiner), or (3) errors when attempting to use the tool that

we were unable to resolve (PhaMers, VirNet, VirMine).

Conclusion

Our comprehensive, comparative analysis of 10 currently available metagenomic

virus/phage identification tools provides valuable metrics, and insights for other investigators

to use and build on. Using mock communities and artifical datasets, precision, recall and

biases of these tools could be calculated. By adjusting the filtering thresholds for viral

identification for each tool and comparing F1 scores, we were able to optimise performance

in every case. Among the tested tools, DeepVirFinder performed best, with the highest F1-

score in both the artifical RefSeq contig and mock uneven community datasets, whilst

displaying similar diversity indices to the original population. All tools, except Seeker, were

able to produce a diversity profile with similar indices to the original population, and are

therefore suitable for phage ecology studies. DeepVirFinder was also one of the fastest tools

in our study as were all other solely machine learning based tools such as PPR Meta, and

Seeker. Generally, we suggest that of currently available tools DeepVirFinder should be

considered the as an optimal solution in most cases, although this will depend on the type of

sample that is analysed, whether precision or recall is more valued, and whether the

additional functionality of other tools is required.

346 **Materials and Methods**

347

348 **Benchmarking with RefSeq dataset**

349 Complete bacterial and archaeal chromosomes and plasmids, and phage genomes

350 deposited in RefSeq [49] since January 2018 (inclusive) were downloaded (2 July 2020).

351 Chromosomes were then randomly down-sampled by a factor of 10, using reformat.sh from

352 BBTools suite [50], to reduce downstream computational load. Phigaro [43] (default settings)

353 and PhageBoost [44] (default settings), with genomes being split and run individually before

354 being concatenated back together, were run in succession on the chromosomal sequences

355 to remove prophage sequences. All sequences were then uniformly fragmented to between

356 1 kb and 15 kb, using a python script (available at [51]), to create artificial contigs. Each viral

357 prediction tool was then run on the three sets of contigs (chromosome, plasmid, and phage)

358 with default settings except for VIBRANT and VirSorter where the phage-derived contig set

359 was additionally run using the virome mode, due to their improved performance in datasets

360 consisting of mainly viral fragments [28, 45]. For tools where score/probability thresholds can

361 be manually adjusted (DeepVirFinder, MetaPhinder, PPR Meta, Seeker and VirFinder), F1

362 curves were plotted (100 data points) and optimal thresholds were determined by maximal

363 F1 score.

364 **Benchmarking with mock community metagenomes**

365 Three shotgun metagenomic sequencing replicates of an uneven mock community [46] was

366 retrieved from the European Nucleotide Archive (BioProject PRJEB19901). These

367 communities contain five phage strains: the DNA viruses ES18 (H1), F0, M13, and P22

368 (HT105), and the RNA virus F2. The quality of the data was checked using FASTQC (v11.8)

369 [52] and overrepresented sequences were removed with Cutadapt (--max-n 0) (v2.10) [53].

370 Cleaned paired-end reads were then assembled with MetaSPAdes (with default settings)

371 (v3.14.1) [54] and contigs <1 kb were removed. Each tool was then run on the three sets of

372 contigs using optimal parameters as determined previously. MetaQUAST (v5.0.2) [55] was

373 used to map contigs to reference phage genomes and calculate coverage. Run time of each

374 tool was recorded using a Linux virtual machine provided by Cloud Infrastructure for Big

375 Data Microbial Bioinformatics (CLIMB-BIG-DATA), with the following configuration: CPU:

376 Intel® Xeon® Processor E3-12xx v2 (8 VCPU); GPU: Cirrus Logic GD 5446; Memory: 64GB

377 Multi-Bit ECC.

378 **Benchmarking with simulated mock virome communities**

Four mock communities (samples 2, 7, 9, and 13) containing between 500 and 1000 viral

genomes created by Roux *et al.* were selected for analysis [47]. These samples belonged to

four different beta diversity groups and did not share any of their 50 most abundant viruses.

Each simulation of 10 million paired-end reads were quality controlled with Trimmomatic

(v.0.38) [56] and assembled with MetaSPAdes by Roux *et al.* [47]. The contigs were then

downloaded for benchmarking. As before, contigs with length <1 kbp were removed, and

then inputted into each viral identification program. Positive viral contig sets for each tool

were then extracted and reads were mapped to these with BBMap [57] with ambiguous

mapped reads assigned to contigs at random, as in Roux *et al.* [47]. Primary mapped reads

with pairs mapping to the same contig (options -F 0x2 0x904) were then extracted with

Samtools [58] and mapped to a pool of non-redundant population contigs. This pool was

created by clustering all four samples with nucmer (v3.1) [59], at ≥95% ANI (average

nucleotide identity) across ≥80% of their lengths. Abundance matrices for each tool were

calculated by normalising read counts by contig length and total library size (counts per

million) calculation commonly used in RNA-seq analyses. These abundance matrices were

then used to calculate Shannon, Simpson, and Bray-Curtis dissimilarity indices using the

vegan package [60]. Non-metric multidimensional scaling (NMDS) and analysis of similarity

(ANOSIM) were also computed with vegan. ANOSIM *p*-values were corrected with the

Benjamini–Hochberg method. Seed and permutations were set as 123 and 9999

respectively, where possible. All plots were generated with ggplot2 [61] and arranged with

ggarrange from ggpubr [62].

List of Abbreviations

ANI   Average Nucleotide Identity

ANOSIM   Analysis of Similarity

GPU   Graphics Processing Unit

kb   Kilobases

MDA   Multiple Displacement Amplification

NCBI   National Center for Biotechnology Information

NMDS   Non-metric Multidimensional Scaling

RefSeq   NCBI Reference Sequence Database

ssDNA   Single-stranded DNA

VCPU   Virtual Central Processing Unit

Declarations

Ethics approval and consent to participate

Not applicable

Consent for publication

Not applicable

Availability of data and material

All RefSeq genomes used in this study can be downloaded from NCBI - https://www.ncbi.nlm.nih.gov/genome/. Relevant accession numbers for virus and host genomes can be found in Additional file 6.

Sequencing data from other studies first described in other man are available as described in the relevant articles. Scripts and commands created for this study are available at our GitHub repository – https://github.com/sxh1136/Phage_tools.

Competing interests

The authors declare that they have no competing interests

Funding

SFSH was supported by the Wellcome Trust Antimicrobials and Antimicrobial Resistance Doctoral Training Programme (215154/Z/18/Z). ADM was supported by MRC (MR/T030062/1). WvS was supported by a Royal Society Wolfson Research Merit Award (WM160092) and BBSRC (BB/S017941/1).

Authors' contributions

The study was designed by all authors. SFSH analysed and interpreted the data generated in this study. All authors wrote and approved the manuscript.

Acknowledgements

We wish to thank the authors of Kleiner *et al.* [46] and Roux *et al.* [47] for making their sequencing data publicly available, allowing their use in this study.

448 **Tables**

Software	Description	Reference
DeepVirFinder	Predicts viral sequences via a k-mer based deep learning method using convolutional neural networks (CNN). Based on VirFinder.	[39]
MARVEL	Machine learning tool for predicting phage sequences in metagenomic bins.	[40]
MetaPhinder	Integrates BLAST hits to multiple phage genomes in a database to identify phage sequences in assembled contigs.	[35]
metaviralSPAdes (ViralVerify)	Identifies viral sequences by leveraging metagenomic assembly graphs and analyzing the variations in depth of coverage between viral and bacterial genomes. Made of three modules, it also calculates the completeness of predicted viral sequences.	[42]
PhaMers	*Identifies phage sequences by a machine learning model based on k-mer frequencies.*	[63]
PPR-Meta	Deep learning CNN approach to identify both phages and plasmids	[64]
Seeker	Deep learning framework that uses Long Short-Term Memory models which does not depend on sequence motifs.	[65]
VIBRANT	Deep learning neural network based on protein signatures which also highlights auxiliary metabolic genes and pathways.	[45]
ViraMiner	*Extension of DeepVirFinder that is trained to identify any virus that may colonise human samples.*	[66]
VirFinder	K-mer based machine learning method for identification of viral contigs.	[37]
virMine	*Iterative pipeline that relies on the abundance of non-viral sequences in databases to strictly filter out unwanted contigs. Pipeline accepts both reads or assembled contigs.*	[67]
VirMiner	*Web-based pipeline that handles genome assembly,*	[68]

	functional annotation using a variety of databases and identification of phage contigs via a random forest algorithm	
VirNet	*Deep learning neural network using an attentional neural model trained on nucleotide viral fragments.*	[69]
VIROME	*Web-based pipeline that classifies viral sequences based on homology to databases and functional annotates them. No local version.*	[34]
VirSorter	Uses referenced-based and reference-free approaches in unison relying on probabilistic similarity models and referenced based protein homology searches to increase novel virus detection.	[28]
VirSorter2	Builds on VirSorter by applying machine learning to evaluate "viralness" using genomic features. Works with a wider variety of viral groups than its predecessor.	[70]
VirusSeeker	*Consists of two BLAST-based pipelines – Virome and Discovery. Virome aligns reads to a curated database to identify viral sequences and compute their abundance in the sample. Discovery focuses on contig-based analysis to aid novel virus discovery.*	[36]

450 **Table 1. Overview of tools to identify and predict phage sequences in microbial**
451 **ecosystems.** Tools in italics were not included as they were either irrelevant to this study or
452 insurmountable technical difficulties were encountered during their use.

Sequence group	Number of sequences	Number of artificial contigs
Bacterial and archaeal chromosomes	719 (6,963)	326,595
Bacterial and archaeal plasmids	5,664	100,296
Bacteriophage and archaeal virus genomes	1,039	8,411

455 **Table 2. Sequences included in the RefSeq-based dataset.** Numbers in parenthesis

456 indicate the number of sequences before random down sampling. All sequences were

457 randomly fragmented into artificial contigs of lengths between 1 kb and 15 kb. Identities of

458 the included sequences are provided in Additional file 6.

Figure legends

Figure 1: Comparison of viral identification tools on artificial RefSeq contigs.
Contigs were generated by randomly fragmenting complete bacterial/archaeal/phage
genomes and plasmids deposited in the NCBI Reference Sequence Database (RefSeq)
between 1 January 2018 and 2 July 2020, to a uniform distribution. Each tool was then
separately run on the true positive (phage genome fragments) and negative
(bacterial/archaeal chromosome and plasmid fragments) datasets. For tools which
score/probability threshold or categories could be manually adjusted, values/categories were
selected based on optimal F1-scores. As MARVEL accepts bins as input, each contig was
treated as a separate bin.

**Figure 2: Comparison of viral identification tools on uneven mock community
samples**
Mock community reads were retrieved from a previous study [46]. and assembled with
metaSPAdes before running each identification tool using optimal thresholds based on
previous benchmarks. F1-score, Precision, and Recall metrics are displayed as separate
panels. Each sample is plotted as a single point for each tool, with a boxplot indicating the
interquartile ranges, extremes and mean of all three samples. Where no contigs were
identified as viral by the tool, precision was set as zero.

Figure 3: Comparison of tool runtimes on uneven mock community samples
Wall runtime of each tool on mock community samples was recorded on an 8 VCPU, 64GB
RAM, Linux high performance cluster without GPU acceleration. Each assembly contains
~50 million bp. For MARVEL, the lower bar indicates wall time of the prediction tool itself,
and the top bar indicates the wall time for binning each sample.

Figure 4: Estimation of diversity metrics of tool predicted virome populations.
To assess the impact of each tool on population diversity, four simulated virome assemblies
from Roux *et al.*[47] were downloaded. Each program was then run to determine the subset
of predicted viral contigs. Reads were mapped to these contig subsets and mapped reads
were then subsequently mapped to a pool of population contigs. All diversity metrics were
computed by the R package "vegan" [60]. 'Default' in each plot indicates each sample's

original assembly. A. Number of genomes observed from read mapping to predicted viral

contig populations for each tool. B. Comparison of estimated Shannon diversity indices from

each tool's virome subset. Estimations are based on read counts that were normalised by

contig size and sequencing depth of the virome. C. Comparison of Simpson diversity indices

from each tool's virome subset. D. Non-metric multidimensional scaling (NMDS) ordination

plot of Bray-Curtis dissimilarity of virome subsets predicted by each viral identification tool.

Ellipses indicate the 95% confidence interval for each sample cluster's centroid. Samples

are represented by the same symbol and ellipse line type; tools are denoted by colour.

References

1. Parikka KJ, Romancer ML, Wauters N, Jacquet S. Deciphering the virus-to-prokaryote
ratio (VPR): insights into virus–host relationships in a variety of ecosystems. Biol Rev.
2017;92:1081–100.

2. Cobián Güemes AG, Youle M, Cantú VA, Felts B, Nulton J, Rohwer F. Viruses as
Winners in the Game of Life. Annu Rev Virol. 2016;3:197–214.

3. Hoyles L, McCartney AL, Neve H, Gibson GR, Sanderson JD, Heller KJ, et al.
Characterization of virus-like particles associated with the human faecal and caecal
microbiota. Res Microbiol. 2014;165:803–12.

4. Silveira CB, Rohwer FL. Piggyback-the-Winner in host-associated microbial communities.
Npj Biofilms Microbiomes. 2016;2:1–5.

5. Emerson JB, Roux S, Brum JR, Bolduc B, Woodcroft BJ, Jang HB, et al. Host-linked soil
viral ecology along a permafrost thaw gradient. Nat Microbiol. 2018;3:870–80.

6. Jiao N, Herndl GJ, Hansell DA, Benner R, Kattner G, Wilhelm SW, et al. Microbial
production of recalcitrant dissolved organic matter: long-term carbon storage in the global
ocean. Nat Rev Microbiol. 2010;8:593–9.

7. Rohwer F, Thurber RV. Viruses manipulate the marine environment. Nature.
2009;459:207–12.

8. Brown-Jaque M, Calero-Cáceres W, Muniesa M. Transfer of antibiotic-resistance genes
via phage-related mobile elements. Plasmid. 2015;79:1–7.

9. Chiang YN, Penadés JR, Chen J. Genetic transduction by phages and chromosomal
islands: The new and noncanonical. PLoS Pathog. 2019;15.
doi:10.1371/journal.ppat.1007878.

10. McInnes RS, McCallum GE, Lamberte LE, van Schaik W. Horizontal transfer of antibiotic
resistance genes in the human gut microbiome. Curr Opin Microbiol. 2020;53:35–43.

11. Sutton TDS, Hill C. Gut Bacteriophage: Current Understanding and Challenges. Front
Endocrinol. 2019;10. doi:10.3389/fendo.2019.00784.

12. Campbell A. The future of bacteriophage biology. Nat Rev Genet. 2003;4:471–7.

13. Hobbs Z, Abedon ST. Diversity of phage infection types and associated terminology: the
problem with 'Lytic or lysogenic.' FEMS Microbiol Lett. 2016;363.
doi:10.1093/femsle/fnw047.

14. Walker AW, Duncan SH, Louis P, Flint HJ. Phylogeny, culturing, and metagenomics of
the human gut microbiota. Trends Microbiol. 2014;22:267–74.

15. Loman NJ, Constantinidou C, Christner M, Rohde H, Chan JZ-M, Quick J, et al. A
Culture-Independent Sequence-Based Metagenomics Approach to the Investigation of an
Outbreak of Shiga-Toxigenic Escherichia coli O104:H4. JAMA. 2013;309:1502–10.

16. Lwoff A. Lysogeny. Bacteriol Rev. 1953;17:269–337.

17. Labonté JM, Swan BK, Poulos B, Luo H, Koren S, Hallam SJ, et al. Single-cell
genomics-based analysis of virus–host interactions in marine surface bacterioplankton.
ISME J. 2015;9:2386–99.

18. Cenens W, Makumi A, Mebrhatu MT, Lavigne R, Aertsen A. Phage–host interactions
during pseudolysogeny. Bacteriophage. 2013;3. doi:10.4161/bact.25029.

19. Ripp S, Miller RV. The role of pseudolysogeny in bacteriophage-host interactions in a
natural freshwater environment. Microbiology,. 1997;143:2065–70.

20. Shkoporov AN, Khokhlova EV, Fitzgerald CB, Stockdale SR, Draper LA, Ross RP, et al.
ΦCrAss001 represents the most abundant bacteriophage family in the human gut and
infects Bacteroides intestinalis. Nat Commun. 2018;9:1–8.

21. Ackermann HW, Audurier A, Berthiaume L, Jones LA, Mayo JA, Vidaver AK. Guidelines
for bacteriophage characterization. Adv Virus Res. 1978;23:1–24.

22. Thurber RV, Haynes M, Breitbart M, Wegley L, Rohwer F. Laboratory procedures to
generate viral metagenomes. Nat Protoc. 2009;4:470–83.

23. Probst AJ, Weinmaier T, DeSantis TZ, Domingo JWS, Ashbolt N. New Perspectives on
Microbial Community Distortion after Whole-Genome Amplification. PLOS ONE.
2015;10:e0124158.

24. Yilmaz S, Allgaier M, Hugenholtz P. Multiple displacement amplification compromises
quantitative analysis of metagenomes. Nat Methods. 2010;7:943–4.

25. Kim M-S, Bae J-W. Lysogeny is prevalent and widely distributed in the murine gut
microbiota. ISME J. 2018;12:1127–41.

26. Roux S, Krupovic M, Debroas D, Forterre P, Enault F. Assessment of viral community
functional potential from viral metagenomes may be hampered by contamination with cellular
sequences. Open Biol. 2013;3:130160.

27. Kim M-S, Bae J-W. Lysogeny is prevalent and widely distributed in the murine gut
microbiota. ISME J. 2018;12:1127–41.

28. Roux S, Enault F, Hurwitz BL, Sullivan MB. VirSorter: mining viral signal from microbial
genomic data. PeerJ. 2015;3:e985.

29. Akhter S, Aziz RK, Edwards RA. PhiSpy: a novel algorithm for finding prophages in
bacterial genomes that combines similarity- and composition-based strategies. Nucleic Acids
Res. 2012;40:e126.

30. Fouts DE. Phage_Finder: Automated identification and classification of prophage regions
in complete bacterial genome sequences. Nucleic Acids Res. 2006;34:5839–51.

31. Arndt D, Marcu A, Liang Y, Wishart DS. PHAST, PHASTER and PHASTEST: Tools for
finding prophage in bacterial genomes. Brief Bioinform. 2017;20:1560–7.

32. Lima-Mendez G, Van Helden J, Toussaint A, Leplae R. Prophinder: a computational tool
for prophage prediction in prokaryotic genomes. Bioinforma Oxf Engl. 2008;24:863–5.

33. Roux S, Tournayre J, Mahul A, Debroas D, Enault F. Metavir 2: new tools for viral
metagenome comparison and assembled virome analysis. BMC Bioinformatics. 2014;15:76.

34. Wommack KE, Bhavsar J, Polson SW, Chen J, Dumas M, Srinivasiah S, et al. VIROME:
a standard operating procedure for analysis of viral metagenome sequences. Stand
Genomic Sci. 2012;6:427–39.

35. Jurtz VI, Villarroel J, Lund O, Voldby Larsen M, Nielsen M. MetaPhinder—Identifying
Bacteriophage Sequences in Metagenomic Data Sets. PLoS ONE. 2016;11.
doi:10.1371/journal.pone.0163111.

36. Zhao G, Wu G, Lim ES, Droit L, Krishnamurthy S, Barouch DH, et al. VirusSeeker, a
computational pipeline for virus discovery and virome composition analysis. Virology.
2017;503:21–30.

37. Ren J, Ahlgren NA, Lu YY, Fuhrman JA, Sun F. VirFinder: a novel k-mer based tool for
identifying viral sequences from assembled metagenomic data. Microbiome. 2017;5:69.

38. Ponsero AJ, Hurwitz BL. The Promises and Pitfalls of Machine Learning for Detecting
Viruses in Aquatic Metagenomes. Front Microbiol. 2019;10. doi:10.3389/fmicb.2019.00806.

39. Ren J, Song K, Deng C, Ahlgren NA, Fuhrman JA, Li Y, et al. Identifying viruses from
metagenomic data using deep learning. Quant Biol. 2020;8:64–77.

40. Amgarten D, Braga LPP, da Silva AM, Setubal JC. MARVEL, a Tool for Prediction of
Bacteriophage Sequences in Metagenomic Bins. Front Genet. 2018;9.
doi:10.3389/fgene.2018.00304.

41. Grazziotin AL, Koonin EV, Kristensen DM. Prokaryotic Virus Orthologous Groups
(pVOGs): a resource for comparative genomics and protein family annotation. Nucleic Acids
Res. 2017;45 Database issue:D491–8.

42. Antipov D, Raiko M, Lapidus A, Pevzner PA. MetaviralSPAdes: assembly of viruses from
metagenomic data. Bioinformatics. 2020;36:4126–9.

43. Starikova EV, Tikhonova PO, Prianichnikov NA, Rands CM, Zdobnov EM, Ilina EN, et al.
Phigaro: high throughput prophage sequence annotation. Bioinformatics. 2020.
doi:10.1093/bioinformatics/btaa250.

44. Sirén K, Millard A, Petersen B, Gilbert MTP, Clokie MRJ, Sicheritz-Pontén T. Rapid
discovery of novel prophages using biological feature engineering and machine learning.
NAR Genomics Bioinforma. 2021;3. doi:10.1093/nargab/lqaa109.

45. Kieft K, Zhou Z, Anantharaman K. VIBRANT: automated recovery, annotation and
curation of microbial viruses, and evaluation of viral community function from genomic
sequences. Microbiome. 2020;8:90.

46. Kleiner M, Thorson E, Sharp CE, Dong X, Liu D, Li C, et al. Assessing species biomass
contributions in microbial communities via metaproteomics. Nat Commun. 2017;8.
doi:10.1038/s41467-017-01544-x.

47. Roux S, Emerson JB, Eloe-Fadrosh EA, Sullivan MB. Benchmarking viromics: an in
silico evaluation of metagenome-enabled estimates of viral community composition and
diversity. PeerJ. 2017;5:e3817.

48. Marquet M, Hölzer M, Pletz MW, Viehweger A, Makarewicz O, Ehricht R, et al. What the
Phage: A scalable workflow for the identification and analysis of phage sequences. bioRxiv.
2020;:2020.07.24.219899.

49. Na O, Mw W, Jr B, S C, D H, R M, et al. Reference sequence (RefSeq) database at
NCBI: current status, taxonomic expansion, and functional annotation. Nucleic acids
research. 2016;44. doi:10.1093/nar/gkv1189.

50. Bushnell B. BBMap. 2020. https://sourceforge.net/projects/bbmap/.

51. Ho SFS. Benchmarking phage predection tool GitHub repository. 2021.
https://github.com/sxh1136/Phage_tools.

52. Andrews S, Krueger F, Segonds-Pichon A, Biggins L, Krueger C, Wingett S. FastQC.
2019.

53. Martin M. Cutadapt removes adapter sequences from high-throughput sequencing
reads. EMBnet.journal. 2011;17:10–2.

54. Nurk S, Meleshko D, Korobeynikov A, Pevzner PA. metaSPAdes: a new versatile
metagenomic assembler. Genome Res. 2017;27:824–34.

55. Mikheenko A, Saveliev V, Gurevich A. MetaQUAST: evaluation of metagenome
assemblies. Bioinforma Oxf Engl. 2016;32:1088–90.

56. Bolger AM, Lohse M, Usadel B. Trimmomatic: a flexible trimmer for Illumina sequence
data. Bioinformatics. 2014;30:2114–20.

57. Bushnell B. BBMap: A Fast, Accurate, Splice-Aware Aligner. 2014.
https://www.osti.gov/biblio/1241166.

58. Li H, Handsaker B, Wysoker A, Fennell T, Ruan J, Homer N, et al. The Sequence
Alignment/Map format and SAMtools. Bioinformatics. 2009;25:2078–9.

59. Marçais G, Delcher AL, Phillippy AM, Coston R, Salzberg SL, Zimin A. MUMmer4: A fast
and versatile genome alignment system. PLOS Comput Biol. 2018;14:e1005944.

60. Oksanen J, Blanchet FG, Friendly M, Kindt R, Legendre P, McGlinn D, et al. vegan:
Community Ecology Package. 2020. https://CRAN.R-project.org/package=vegan. Accessed
1 Feb 2021.

61. Wickham H. ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag New York;
2016. https://ggplot2.tidyverse.org.

62. Kassambara A. ggpubr: "ggplot2" Based Publication Ready Plots. 2020. https://CRAN.R-
project.org/package=ggpubr.

63. Deaton J, Yu FB, Quake SR. PhaMers identifies novel bacteriophage sequences from
thermophilic hot springs. bioRxiv. 2017;:169672.

64. Fang Z, Tan J, Wu S, Li M, Xu C, Xie Z, et al. PPR-Meta: a tool for identifying phages
and plasmids from metagenomic fragments using deep learning. GigaScience. 2019;8.
doi:10.1093/gigascience/giz066.

65. Auslander N, Gussow AB, Benler S, Wolf YI, Koonin EV. Seeker: alignment-free
identification of bacteriophage genomes by deep learning. Nucleic Acids Res.
2020;48:e121–e121.

66. Tampuu A, Bzhalava Z, Dillner J, Vicente R. ViraMiner: Deep learning on raw DNA
sequences for identifying viral genomes in human samples. PLoS ONE. 2019;14.
doi:10.1371/journal.pone.0222271.

67. Garretto A, Hatzopoulos T, Putonti C. virMine: automated detection of viral sequences
from complex metagenomic samples. PeerJ. 2019;7:e6695.

68. Zheng T, Li J, Ni Y, Kang K, Misiakou M-A, Imamovic L, et al. Mining, analyzing, and
integrating viral signals from metagenomic data. Microbiome. 2019;7. doi:10.1186/s40168-
019-0657-y.

69. Abdelkareem AO, Khalil MI, Elaraby M, Abbas H, Elbehery AHA. VirNet: Deep attention
model for viral reads identification. 2018 13th Int Conf Comput Eng Syst ICCES. 2018;:623–
6.

70. Guo J, Bolduc B, Zayed AA, Varsani A, Dominguez-Huerta G, Delmont TO, et al.
VirSorter2: a multi-classifier, expert-guided approach to detect diverse DNA and RNA
viruses. Microbiome. 2021;9:37.