Compositional perturbation autoencoder for single-cell response modeling

Mohammad Lotfollahi[1,3,⋆], Anna Klimovskaia Susmelj[2,5,⋆], Carlo De Donno [1,7,⋆⋆], Yuge Ji [1,⋆⋆], Ignacio L. Ibarra[1], F. Alexander Wolf [1,∘], Nafissa Yakubova [2], Fabian J. Theis[1,3,4,6‡], David Lopez-Paz[2]

1 Helmholtz Center Munich – German Research Center for Environmental Health, Institute of Computational Biology, Neuherberg, Munich, Germany.
2 Facebook AI, 6 Rue Ménars, Paris, 75002, France
3 School of Life Sciences Weihenstephan, Technical University of Munich, Munich, Germany.
4 Department of Mathematics, Technical University of Munich, Munich, Munich, Germany.
5 Swiss Data Science Center, Zurich, Switzerland.
6 Wellcome Trust Sanger Institute, Wellcome Genome Campus, Hinxton, Cambridgeshire, UK.
7 Department of Stress Neurobiology and Neurogenetics, Max Planck Institute of Psychiatry, Munich, Bavaria, Germany.

⋆ These authors contributed equally to the work
⋆⋆ These authors contributed equally to the work
∘ Present address: Cellarity, Inc., Cambridge, MA.
‡ Correspondence to fabian.theis@helmholtz-muenchen.de

Abstract

Recent advances in multiplexing single-cell transcriptomics across experiments are enabling the high-throughput study of drug and genetic perturbations. However, an exhaustive exploration of the combinatorial perturbation space is experimentally unfeasible, so computational methods are needed to predict, interpret and prioritize perturbations. Here, we present the Compositional Perturbation Autoencoder (CPA), which combines the interpretability of linear models with the flexibility of deep-learning approaches for single-cell response modeling. CPA encodes and learns transcriptional drug response across different cell types, doses, and drug combinations. The model produces easy-to-interpret embeddings for drugs and cell types, allowing drug similarity analysis and predictions for unseen dosages and drug combinations. We show CPA accurately models single-cell perturbations across compounds, dosages, species, and time. We further demonstrate that CPA predicts combinatorial genetic interactions of several types, implying it captures features that distinguish different interaction programs. Finally, we demonstrate CPA allows *in-silico* generation of 5,329 missing combinations (97.6% of all possibilities) with diverse genetic interactions. We envision our model will facilitate efficient experimental design by enabling *in-silico* response prediction at the single-cell level.

Introduction

Novel research in single-cell genomics allows profiling the gene expression of millions of cells across different tissues[1, 2] and species[3]. Recently, novel technologies have enabled the extension of these measurements to performing high-throughput screens (HTSs) to measure the response to thousands of independent perturbations[4, 5]. These advances enable applications in drug development[6] by performing HTSs at the single-cell level, offering both comprehensive molecular phenotyping and capturing heterogeneous responses not possible with traditional HTSs[4].

While the development of high-throughput approaches such as "cellular hashing" [4, 7, 8] facili-

tates single-cell RNA sequencing (scRNA-seq) in multi-sample experiments at a reduced cost, these strategies require expensive library preparation[4] and do not easily scale to large numbers of perturbations. These shortcomings become more prominent when exploring effects of combinations of therapies[9–11] or genetic perturbations[5, 12, 13], where the experimental screening of all combinations is impossible. While projects such as Human Cell Atlas[14] are extensively cartographing cellular states across tissues in reproducible fashion, building a similar atlas for perturbations is impossible due to the vast number of possibilities. This necessitates the development of computational tools to guide the exploration of the combinatorial space of perturbations, for instance to nominate promising candidate combinatorial therapies in HTSs. A successful method must be able to predict cellular behaviours when subject to novel perturbation combinations absent from the original experiment, referred to as Out-Of-Distribution (OOD) data. OOD prediction would then enable the study of perturbations biology in presence of dose-treatments[4, 15], combinatorial therapies[8] or genetic knock-outs[5] and changes across time[15].

Recently, computational approaches have been suggested for predicting cellular responses[16–20]. The first approach leverages mechanistic modeling approaches [18, 19] to predict low-dimensional cell viability[19] values or abundance of a few selected proteins[18]. While powerful in interpreting interactions, mechanistic models usually require temporally-resolved data often unavailable in practice, and most do not scale to genome-wide measurements and challenges such as predicting high-dimensional scRNA-seq data. Linear models[12, 21] do not suffer from these scalability issues but have limited predictive power and are unable to capture non-linear cell-type specific responses. In contrast, deep learning (DL) models do not face these limitations. Recently, DL has been suggested not only to model gene expression latent spaces from scRNA-seq data [22–25], but also to describe and predict single-cell responses [16, 17, 20, 26]. Yet, current DL-based approaches model only a handful of perturbations; are not interpretable; cannot handle combinatorial treatments; and are unable to incorporate continuous (e.g. dose, time) or discrete covariates (e.g. cell-types, species, patients). As such, state-of-the-art DL models are unsuited for to a majority of scenarios.

Inspired by recent advances in self-supervised learning[27, 28], the field of machine learning to train models without human-provided labels, we propose the *Compositional Perturbation Autoencoder(CPA)*, a novel interpretable method to analyze and predict scRNA-seq perturbation response across dose, time, drug and genetic combinations. CPA borrows ideas from interpretable linear models to the flexible DL realm, by learning a factorized latent representation of both perturbations and covariates. Specifically, given a scRNA-seq dataset along with perturbations and covariates describing the experimental setting, CPA decomposes the data into a collection of embeddings (representations) associated to the cell, the perturbation, and the external covariates. By virtue of an adversarial loss, these embeddings are independent from each other, so they can be later recombined to predict the effect of novel perturbation/covariate combinations. Therefore, by exploring novel combinations, CPA can guide experimental design. We demonstrate the usefulness of CPA on five public across multiple tasks, including the prediction and analysis of compound response, dose response, time-series information and genetic perturbations.

Figure 1 | Interpretable single-cell perturbation modeling using a compositional perturbation autoencoder (CPA). (a) Given a matrix of gene expressions per cell together with annotated potentially quantitative perturbations d and other covariates such as cell line, patient or species, CPA learns the combined perturbation response for a single-cell. It encodes the gene expression using a neural network into a lower dimensional latent space that is eventually decoded back to an approximate gene expression vector, aimed to be as close as possible to the original one. To make the latent space intepretable in terms of perturbation and covariates, the encoded gene expression vector is first mapped to a 'basal state', by feeding the signal to discriminators to remove any signal from perturbations and covariates. The basal state is then composed with perturbations and covariates - with potentially reweighted dosages - to reconstruct the gene expression. All encoder, decoder and discriminator weights as well as the perturbation and covariate dictionaries are learned during training. **(b)** Features of CPA are interpreted via plotting of the two learned dictionaries, interpolating covariate specific dose response curves and predicting novel unseen drug combinations.

Results

Multiple perturbations as compositional process in gene expression latent space

Prior work models the effects of perturbations on gene expression as separate processes: for example, differential expression compares each condition separately with control, and a conditional variational autoencoder[17, 26, 29]—while modeling a joint latent space—is highly unintepretable and not amenable to predict the effect of combinations of conditions. In contrast, our goal here is to factorize the latent space of neural networks to turn them into interpretable compositional models. If the latent space was linear, we could describe the observed gene expression as a factor model with each component being one perturbation.

However it has been shown that gene expression latent space, particularly in complex tissues, is highly nonlinear and best described by graph or nonlinear embedding approximations[30, 31]. Let us discuss scRNA-seq datasets where gene expression profiles of a cell population are observed under multiple perturbations—these could be drugs, genetic knock-outs, or multiple disease states— as well as (labeled) covariates such as cell lines, patients, or species. We allow perturbations to be quantitative (such as drugs under multiple dosages), and for each cell we know under which perturbation and condition it has been observed. Furthermore, we assume sufficiently dense cell samples to estimate the latent space in ground and perturbation space using a large neural network.

Instead of assuming a factor model in gene expression space, we instead model the nonlinear superposition of perturbation effects in the nonlinear latent space, in which we constrain the superposition to be additive (see **Methods**). Furthermore, we decouple effects of perturbations and covariates, and allow quantitative effects (e.g. drug doses) by encoding this information in a nonlinearly transformed scalar weight (i.e. a learned drug-response curve). The linear latent space factor model enables an interpretation of the this space by disentangling latent space variance driven by covariates from those stemming from each perturbation. At evaluation, we are able to not only interpolate and interpret observed perturbation combinations but also predict other other combinations, potentially in different covariate settings.

The compositional perturbation autoencoder

We introduce CPA (see **Methods**), a method combining ideas from natural language processing [28] and computer vision [27, 32] to predict the effects of combinations of perturbations on single-cell gene expressions. Given a single-cell dataset of multiple perturbations and covariates, CPA first uses an encoder neural network to decompose the cell's gene-expression into three learnable additive embeddings corresponding to the cell's basal state,the observed perturbation, and the observed covariates.Crucially, the embedding that the encoder from CPA learns about the cell's basal state is <u>disentangled from</u> (does not contain information about) the embeddings corresponding to the perturbation and the covariates. This is achieved by training a discriminator classifier[27]in a competition against the encoder network of CPA. More specifically, the goal of the encoder network in CPA is to learn an embedding about the cell's basal state from which the discriminator network cannot predict the perturbation or covariate values. Still, in order to perform well, the embedding of the cell's basal state should contain all the information about the cell's specifics. To account for continuous time or dose effects, the learnable embedding about each perturbation is scaled non-linearly via a collection of real-to-real neural networks of those continuous values for each cell. Next, and after recombining the learned embeddings about the cell's basal state, perturbation and covariate values into an unified embedding, CPA employs a neural network decoder to recover the cell's gene expression vector (**Figure 1**). As it is the case with any neural network model, CPA is trained using the backpropagation rule[33] on the reconstruction and discriminator errors (see **Methods**), tuning the parameters of the encoder network, the decoder network, the embeddings corresponding to each perturbation and covariate value, and the dose/time non-linear scalers. The learned embeddings allow to measure similarities between different perturbations and covariates, in terms of their effect on gene expression. The main feature of CPA is its flexibility of use at evaluation time. In particular, after obtaining the disentangled embeddings corresponding to some observed gene expression, perturbation, and covariate values, we can "intervene" and swap the perturbation embedding with any other of perturbation embedding of our choice. Effectively, this manipulation is a way of estimating the answer to the counterfactual question "What would have the gene expression of this cell looked like, had it been treated differently?." This is of special interest to predict the effect of unseen perturbation combinations on gene expression. CPA can also visualize the transcriptional similarity and uncertainty associated to perturbations and covariates, as later demonstrated.

CPA allows predictive and exploratory analyses of single-cell perturbation experiments

Figure 2 | CPA learns an interpretable latent space learning across drug dosages, drug combinations and experimental systems. **(a)** Sci-Plex 2 dataset from Srivatsan et al. [34]. Dose-response curves were generated using CPA model as a transfer from Vehicle cells to a given drug-dose combination. *MDM2* gene is the top diferentially expressed gene for *Nutlin* was selected as an example. Black dots on the dose-response curve denote points seen at training time, red dots denote examples held out for OOD predictions, the size is of the dots is proportional to the amount of cells observed in the experiment. Solid lines correspond to the model predictions, dashed lines correspond to the linear interpolation between measured points. Nutlin and BMS are selected as an example of uncertainty in predictions for drug combinations. **(b)** 96-plex-scRNAseq experiment from Gehring et al. [8], with UMAP showing variation of responses in gene expression space. Dashed circle on the UMAP represents the area on the UMAP where the majority of the cells from the left-out (OOD) condition lie. The experiment did not contain samples of individual drugs, therefore we represented latent space of the drug combinations measured in the experiment. Dose-response surface was obtained via model predictions for triplet of drugs: BMS at fixed dose 0.2, and EGF and RA changing on a grid. **(c)** Cross-species dataset from Hagai et al. [15], with samples of rat and mouse at time point 6 held out from training and used as OOD. Latent space representation of individual species and individual average response of a species across time demonstrates that the species are fairly different with a small similarity between rat and mouse. Time response curves of individual genes demonstrate that the model is able to capture non-linear behavior. OOD splits benchmark demonstrates how model performance on the distribution case changes when the model is trained of the different subsets of the data. Split2 corresponds to the most difficult case when all three-time points for rat were held out from training. Red dots denote examples held out for OOD predictions, the size is of the dots is proportional to the amount of cells observed in the experiment.

We first demonstrate the performance and functionality of CPA on three smaller single-cell datasets (**Figure** 2): A Sci-Plex2 dataset of human lung cancer cells perturbed by 4 drugs [35], a 96-plex-scRNAseq experiment of HEK293T under drug combinations [8] and a cross-species dataset of stimulated phagocytes [15]. All three datasets represent different scenarios of the model application: (a) diverse doses; (b) drug combinations; (c) several cell types and variation with respect to time instead of dose. We split each dataset into three groups: train (used for model training), test (used for the model parameters tuning), and out-of-distribution (never seen during training or parameters selection and intended to measure generalization properties of the model). **Supplementary Tables** 1–5 demonstrate R^2 metrics (see **Methods**) for the performance of CPA on these datasets and various splits.

Sci-plex from Srivatsan et al.[35] contains measurements of human lung adenocarcinoma cell line exposed to four drug perturbations at several distinct doses. In this scenario, the model learns to generalize to the unseen dosages of the drugs. To demonstrate OOD properties, we withhold cells exposed to the second to the largest dose among all drugs. This choice was made because the vast majority of cells are dead for most of the drugs at the highest dosage and we wouldn't have enough cells to statistically test CPA model generalization. Since the learned latent space representation learnt by CPA is still high-dimensional, we can use various dimensionality reduction methods to visualize it or simply depict it as a similarity matrix (**Figure** 2a). In **Supplementary Table** 2 we compared the performance of CPA on the OOD example on two simple baselines: taking the maximum dose as a proxy to the previous dose and a linear interpolation between two measured doses. These results demonstrate that the model consistently achieves high scores (maximum score of 1 yields perfect reconstruction) on all the OOD cases, and on two of them significantly outperform the baselines for Nutlin (0.92 vs 0.85) and BMS (0.94 vs 0.89). To demonstrate how well CPA captures dose-response dynamics of individual genes, we looked at the most deferentially expressed gene for Nutlin perturbation (**Figure** 2a). The dose-response curve agrees well with the observed data. We additionally propose a simple heuristic to measure the model's uncertainty (see **Methods**) with respect to unseen perturbation conditions. The model shows very low uncertainty on OOD split. This agrees well with CPA's high R^2 scores on OOD example. However, if we test the uncertainty of the model on a combination of two drugs (**Figure** 2a), we see that it gets much higher uncertainty compared to single drugs. That agrees well with the fact that the model never saw drug combinations during training and that such prediction could be unreliable.

As the second example, we took 96-plex-scRNAse from Gehring et al.[8]. This dataset contains 96 unique growth conditions constructed of combinations at various doses of four drugs applied to HEK293T cells. We hold out several combinations of these conditions for OOD cases: which ones exactly (**Supplementary Table** 3). We demonstrate that CPA is able to reliably predict expression patterns of unseen drug combinations (**Supplementary Table** 3) and produce a meaningful latent perturbation latent space (**Figure** 2b). For this dataset, even simple baselines are not applicable anymore, since the expression of cells exposed to the individual drugs is not measured. On the example of this dataset, we also see that our heuristic for uncertainty agrees with the model's performance on OOD examples.

The third example of the cross-species dataset from Hagai et al.[15] demonstrates that CPA can also be applied in the setting of multiple covariates (e.g. different species or cell types) and the dynamics of the covariate can be a non-monotonous function such as time response instead of the dose-response. In this example, bone marrow-derived mononuclear phagocytes from mouse, rat, rabbit, and pig challenged with lipopolysaccharide (LPS). **Figure** 2c CPA model demonstrates that the learned latent space agrees with the known similarities between species, finding that though all the species have a distinct response, there is still a certain level of similarity between rat and mouse. We compare generalization abilities of the model by withholding different parts of the data for OOD case: "split0" (rat at 6 hours), "split1" (rat at 2 and 6 hours), "split2" (rat at 2,4,6 hours), "split3" (rat at 4 and 6 hours), and "split" (rat and mouse at 6 hours, this split was used for main analysis) (see **Supplementary Table** 4). The model demonstrates very good performance compared to the performance on the test split (see **Supplementary Table** 5) on the majority of the OOD splits, and expected, showed a poor performance for the case when the model didn't see any examples of LPS response for the rat, except control expression. On this dataset, we see that the model with the lowest performance corresponds to the highest number of hold-out examples, yet the model uncertainty also spikes for these OOD cases, hinting that they might be not reliable (**Figure** 2c). In contrast, for the cases with high R^2 scores, the model is quite certain about its predictions (**Supplementary Table** 4).

Figure 3 | Learning drug and cell line latent spaces from massive single-cell screens of 188 drugs across cancer cell lines. (a) UMAP representation of sci-Plex samples of A549, K562 and MCF7 cell-lines colored by pathway of the compounds to which cells were perturbed. **(b)** Two dimensional representation of latent drug embeddings as learned by the compositional perturbation autoencoder. Compounds associated with the epigenetic regulation, tyrosine kinase signaling, and cell cycle regulation pathways are colored by their respective known pathways. The lower left panel show latent embedding for three cell lines in the data, indicating no specific similarity preference. **(c)** Latent drug embedding of CPA model trained on the bulk RNA-cell line profiles from the L1000 dataset, with focus on drugs shared with the sci-Plex experiment from (a). **(d)** Latent representation of 80 cell lines from L1000. **(e)** Distribution of top 5 differentially expressed genes after MCF7 were treated with Pracinostat at the highest dose for real, control and CPA predicted cells. **(f)** Box plots of R2 scores for predicted and real cells for 36 compounds and 108 unique held out perturbations across different cell lines. Baseline indicates comparison of real compounds with each other. **(g)** Mean gene expression of 5,000 genes and top 50 DEGs between CPA predicted and real cells cells together with the top five DEGs highlighted in red for four compounds for which the model did not see any examples of the highest dose. **(h)** Latent dose response obtained from dose encoder for all compounds colored by pathways. **(i)** Real and predicted dose response curves based on gene expression data, for a single compound with differential dose response across three cell lines. **(j)** R2 scores box plot for all and top 50 DEGs. Each column represent a scenario when cells exposed with specific dose for all compounds on a cell line or combinations of cell lines were held from training and later predicted.

CPA finds interpretable latent spaces in large-scale single-cell high-throughput screens

The recently proposed sci-Plex assay [35] allows to profile thousands of independent perturbations in a single experiment via nuclear hashing. We consider the main sci-Plex experiment, a high-throughput screen of 188 compounds in 3 cancer cell lines. The panel was chosen to target a diverse range of enzymes and molecular pathways: transcriptional and epigenetic regulators and diverse mechanisms of action. The screened cell lines A549 (lung adenocarcinoma), K562 (chronic myelogenous leukemia), and MCF7 (mammary adenocarcinoma) were exposed to each of these 188 compounds at four doses (10 nM, 100 nM, 1 μM, 10 μM), and scRNA-seq profiles have been measured for altogether 290 thousand cells (**Figure** 3a). As above, we split the dataset into 3 subsets: train, test and OOD. For the OOD case we selected 36 drugs with the strongest effect at the highest dosage (10 μM)) in all three cell lines. Drug, dose, and cell line combinations present in the OOD cases were removed from train and test sets.

We find that after training, CPA learns a compressed representation of the 188 compounds. To

test whether the learnt drug embedding is meaningful we asked if compounds with similar putative mechanisms of action are similar in latent space. Interestingly this holds for a large set of major mechanisms: In latent space each drug is represented by a single 256 dimensional vector, which we visualized in two dimensions (**Figure** 3b), where similarity is determined by cosine distance between the embedding vectors. We find that epigenetic drugs, tyrosine kinase signaling, and cell-cycle regulation compounds are clustered together by the model, which confirms that an interpretable embedding has been learnt.

We additionally demonstrate that the model learns universal relationships between compounds which remain true across datasets and even modalities. Using the same set of compounds tested in the sci-Plex dataset together with another 853 compounds, we train CPA on LINCS bulk perturbation measurement data across 82 cell lines [36]. We first observe that CPA works equally well on non-single cell data, and we find that again, the same epigenetic and tyrosine kinase signaling compounds are close to each other in the latent representation, indicating that the similarities in response as learned by the model apply across datasets (**Figure** 3c). This holds also for the other learnt embeddings: Applying the same similarity metric to the covariate embedding - here the 82 cell lines - we see that the cell line embedding learned by the model also represents cell line similarity in response to perturbation, as cell lines from lung tissue are clustered together (**Figure** 3d).

Interestingly, CPA is able to extrapolate to the unseen OOD conditions with unexpected accuracy, as it captures the difference between control and treated conditions also for a compound where it did not see an example of the highest dose. As one example, Pracinostat has a strong differential response to treatment as compared to control, as can be seen from the distributions of the top 5 differentially expressed genes (**Figure** 3e). Despite not seeing the effect of Pracinostat at the highest dose in any of the three cell lines, CPA correctly infers the mean and distribution of these genes (**Figure** 3e). Generally, CPA performs well in modeling unseen perturbations, as the correlation of real and predicted values across OOD conditions is overall better than the correlation between real values (**Figure** 3f). When looking at individual conditions in **Figure** 3g, CPA does well not only in recapitulating gene with low mean expression but also in predicting genes with high mean expression in the OOD condition.

As expected, CPA has a harder time predicting experiments where more covariates are unseen. To assess the ability of the model to generalize in unseen conditions, we trained CPA with 28 splits with different held out conditions, with one of the doses in anywhere from 1-3 cell lines held out (**Figure** 3j). We note that K562 is the hardest cell line to generalize, when considering training on two cell lines to generalize to another. Extrapolating to the highest dose is a harder task than interpolating intermediate doses, which is consistent with the difficulty of anticipating the experimental effect of a higher dose, versus fitting sigmoidal behavior to model intermediate doses. When examining the shape of the sigmoids learned by the model (**Figure** 3h), we see that epigenetic compounds, which caused the greatest differential expression in this dataset, have higher latent response curves, indicating that CPA learns a general, cell line agnostic response strength measure for compounds. This learned sigmoid behavior can then be used in conjunction with the latent vectors to reconstruct the gene-expression of treated cells over interpolated doses (**Figure** 3i).

Figure 4 | Learning and predicting combinatorial genetic perturbations. (a) UMAP representation of inferred genetic manifold latent space using CPA for 281 single- and double-gene perturbations obtained from Perturb-seq experiment by Norman et al.[5]. Each dot represents a genetic perturbation. Highlighted clusters denote perturbations inducing similar gene programs[5]. Comparison of CPA predicted and real genetic combinations for a synergistic (*CBL+CNN1*, **b-c**) and an epistatic (*DUSP9+ETS*, **d-e**) interaction, with marker genes were taken from original publication for **b-c**. Top 10 DEGs of *DUSP9+ETS* against control are shown for **d-e**. **(f)** R^2 values of mean gene-expression of real and predicted cells for all genes (blue) or top 100 DEGs for the prediction of all 131 combinations in the data by training 13 different models leaving out of $\approx$ 10 combinations each time. **(g)** Scatter plots of number sample in the real data for each combination (x-axis) versus R^2 values of predicted and real for that combination **(h)** Box-plots of R^2 values for predicted and real cells while increasing the number of combinations seen during training. **(i)** UMAP embedding of measured (n=284, red dots) and CPA-predicted (n=5,329, grey dots) perturbation combinations. **(j)** Same as (i), highlighting measurement uncertainty (cosine similarity). **(k)** Same as (i), showing prevalent genes within each cluster (with 25 or more observations). **(l)** Interaction mode metrics between double perturbations of *KLF1* with other genes. Clustering of metrics obtained from linear regression coefficients and calculated similarity between single and double perturbations, for measured (purple) and predicted (yellow) expression profiles. **(m)** Gene expression changes (Z-scores versus control cells values) of selected measured (purple) and predicted (yellow) single and double perturbations. Titles indicate regression linear regression coefficients for each gene, and interaction mode suggestion based on rules from[5].

CPA allows modeling combinatorial genetic perturbation patterns

Combinatorial drug therapies are hypothesized to address the limited effectiveness of mono-therapies[37] and preventing drug resistance in cancer therapies[37–39]. However, combinatorial expression of a small number of genes often drives the complexities at the cellular level leading to the emergence of new properties, behaviors, and diverse different cell types [5]. To study such genetic interactions (GIs) recent perturbation scRNA-seq assays[12, 13] allow to measure the gene expression response of a cell to perturbing a pair of genes alone or in combinations. While experimental approaches are necessary to assess the effect of combination therapies, the possible space of combinations grows exponentially with the number of single perturbations. Thus, in practice it becomes infeasible to

experimentally explore all possible combinations without computational prediction guiding the experimental design.

To pursue this aim, we applied our *CPA* model on scRNA-seq data collected from Perturb-seq (single-cell RNA-sequencing pooled CRISPR screens) to assess the overexpression of single or combinatorial interaction of 105 genes (i.e. single gene x, single gene y, and pair x+y) on the growth of K562 cells [5]. In total, this data contains 284 conditions measured across $\approx 108,000$ single-cells. This dataset contains 131 (out of 284) unique combination pairs (i.e. x+y) and the rest are single gene perturbations or control cells. We observed the latent genetic interaction manifold places GIs inducing known and similar gene programs close to each other (**Figure** 4a). For example, considering *CBL* (orange cluster in **Figure** 4a) and its surrounding points comprising of its regulators (e.g. *UBASH3A/B*) and multisubstrate tyrosine phosphatases (e.g. *PTPN9/12*) are all previously reported to induce erythroid markers [5]. Next, we sought to assess our ability to predict specific interactions. We examined a synergistic interaction between *CBL* and *CNN1* driving erythroid differentiation which has been previously validated [5]. We trained a CPA model while *CBL+CNN1* is held out from training data. Over-expression of either gene leads to the progression of cells from control to single perturbed and doubly perturbed cells (**Supplementary Fig**.2a) toward erythroid gene program. Specifically, overexpression of both *CBL* and *CNN1* actuate strong up-regulation known markers[5] such as haemoglobin genes(see *HBA1/2* and *HBG1/2* in **Figure 4b**). We observe our model successfully predicted this synergistic interaction recapitulate similar pattern as real data inline with original findings (**Figure** 4c). We further evaluated CPA to predict a previously reported[5] genetic epistatic interaction between *DUSP9* and *ETS* leading to domination of *DUSP9* phenotype in doubly perturbed cells (**Figure**4d-e).

To systemically evaluate CPA's generalization behavior, we trained 13 different models while leaving out all cells from ≈ 10 unique combinations covering all 131 doubly perturbed conditions in the dataset and further predicted them. The reported R^2 values show robust prediction for most of the perturbations while lower scores are seen for the perturbation where the evaluation is noisy due to sample scarcity (n<100) or the one of the perturbation is only available as singly perturbed cells in the data thus the model fails to predict the unseen combinations (**Figure** 4f-g, see **Supplementary Fig**.2). To further understand when CPA performance deteriorates, we first trained it on a subset with no combinations seen in the training and then increased the size of combinations seen during the training. As expected we find that overall prediction accuracy improves when the model is trained with more combinations, while it can fail to predict DEGs when trained with fewer combinations (see n<71 combinations in **Figure** 4h).

Hence, once trained with sufficiently large and diverse training data CPA can robustly predict unseen perturbations. We next asked whether our model can generalize beyond the measured combinations and *in-silico* generate all 5,329 combinations, which were not measured in the real dataset ($\approx 98\%$ of all possibilities). To study the quality of these predictions, we trained a model while all combinations are seen during training to achieve maximum training data and sample diversity. We then predicted 50 single-cells for all missing combinations. We find that, while the latent embeddings do not fully capture all the nuances in the similarity of perturbations compared to gene space, it provides an abstract and easier to perform high-level overview of potential perturbation combinations. Thus, we leveraged our latent space to co-embed (**Figure** 4i) all measured and generated data while proving an uncertainty metric based on the distance from the measure phenotypes (**Figure** 4j). We hypothesized that the closer the generated embedding to the measured data it is more likely to explore a similar space of the genetic manifold around the measure data. In contrast, the distant point can potentially provide novel behaviors while requiring more consideration and validation steps. Equipped with this, we annotated the embedding clusters based on gene prevalence, finding that single genes (i.e. gene x) paired with other genes (i.e. y) as combinations (i.e. x+y) are a main driver of cluster separation (**Figure** 4k). Genes without measured double perturbations were less likely to be separated as independent clusters using newly predicted transcriptomes (**Supplementary Fig**. 3a), suggesting that their interactoin-specific effects are less variable than the ones with at least one

₃₁₆ double perturbation available in the training data.

₃₁₇ To investigate genetic interaction types for the newly predicted conditions, we compared differences
₃₁₈ between double and single perturbations versus control cells and thus annotated interaction modes
₃₁₉ (adapted from [5] for in-silico predictions). In each gene-specific cluster we observed variability across
₃₂₀ these values, suggesting that our predictions contain further granularity that goes beyond single gene
₃₂₁ perturbation effects and cannot be fully dissected by two dimensional embeddings. Upon curation
₃₂₂ of gene perturbations by these metrics and levels of experimental data available (**Supplementary**
₃₂₃ **Fig**. 3b), we decided to predict and annotate interaction modes based on these values when double
₃₂₄ measurements were available for at least one gene. For example, we observed clustering of *KLF1*
₃₂₅ and partner gene perturbations pairs solely from these metrics, suggesting several interaction modes
₃₂₆ (**Figure** 4l). Further dissecting on differentially expressed genes in each co-perturbation, our metrics
₃₂₇ validated previously reported epistatic interactions (*CEBPA*), and proposed new ones with *KLF1*-
₃₂₈ dominant behavior (*NCL*), gene synergy (*FOXA3*), and epistatis (*PTPN13*), among others (**Figure**
₃₂₉ 4m). When repeating this analysis across all measured and predicted double perturbations, we found
₃₃₀ that genes have potential preferences for certain interaction modes (**Supplementary Fig**. 3c).
₃₃₁ Finally, among specific genes recurrently responding to several perturbations we found common gene
₃₃₂ expression patterns in terms of both direction and magnitude (**Supplementary Fig.** 3d), suggesting
₃₃₃ that their responses are modulated by conserved gene regulatory principles that potentially prevail
₃₃₄ across perturbations.

₃₃₅ Altogether, our analysis indicates that double perturbation measurements can be generated from
₃₃₆ CPA through leveraging of genetic perturbation data, which when combined with an uncertainty
₃₃₇ metric allows us to generate and interpret gene regulatory rules for a subset of the newly predicted
₃₃₈ gene-gene perturbations.

Discussion

₃₄₁ *In silico* prediction of cell behaviours in response to a perturbation is critical for optimal experiment
₃₄₂ design and the identification of effective drugs and treatments. With CPA, we have introduced
₃₄₃ a versatile and interpretable approach to model cell behaviours at single-cell resolution. CPA is
₃₄₄ implemented as a neural network trained with stochastic gradient descent, scaling to millions of
₃₄₅ cells and thousands of genes. We applied CPA on a variety of datasets and tasks, from predicting
₃₄₆ single-cell response to learning embeddings and expression response of small-compounds, with vari-
₃₄₇ able drug-dose combinations. Specifically, we illustrated how to model perturbations across dosage
₃₄₈ levels and time series, and have shown applications in drug perturbation studies, as well as genetic
₃₄₉ perturbation assays with multiple gene knockouts, revealing potential gene-gene interaction modes
₃₅₀ inferred by our model. CPA combines the interpretability of linear decomposition models with the
₃₅₁ flexibility of nonlinear embedding models.

₃₅₂ While CPA performed well on our experiments, in machine learning there is no free lunch and as
₃₅₃ any other machine learning model it will fail if the test data is wildly different from the training
₃₅₄ data. To signal CPA users about these cases, it is crucial to quantify model uncertainty. Here, we
₃₅₅ implemented a distance-based uncertainty score, scalable Bayesian uncertainty models are promising
₃₅₆ alternatives for future work[40]. Although here we opted to implement a deterministic, sample-
₃₅₇ transformation based autoencoder scheme, extensions towards variational models[17, 23], as well as
₃₅₈ other cost functions different to mean squared errors[22] are straightforward.

₃₅₉ Aside from CPA, existing methods[17, 26] such as scGen[16] have also been shown capable of pre-
₃₆₀ dicting single-cell perturbation responses when the dataset contains no combinatatorial treatment
₃₆₁ or dose-dependent perturbations. Therefore, it may be beneficial to benchmark CPA against such
₃₆₂ methods on less complicated scenarios with a few perturbations while it might not be practical
₃₆₃ considering current trend on the generation of massive perturbation studies[4, 5, 12].

Currently the model is based on gene expression alone, so it cannot directly capture other levels of interactions or effect for example due to post-transcriptional modifications, signaling or cell communication. However, due to the flexibility of neural network based approaches, CPA could be extended to include modalities, for example via multimodal single-cell CRISPR[41, 42] combined scRNA- and ATAC-seq[43, 44] and CUT&Tag[45, 46] . In particular, we expect spatial transcriptomics[47, 48] to be a great source of extensions of CPA due to its high sample numbers and the dominance of deep learning models in computer vision.

The CPA model is not limited to single-cell perturbations. While we chose the single-cell setting due to high sample numbers, CPA could be readily applied to large-scale bulk cohorts, where covariates could for example be patient ID or transcription factor perturbations, so these and any other available attributes could be controlled independently[27] to achieve compositional, interpretable predictions. Any bulk compositional model may be combined with a smaller-scale single-cell model to compose truly multi-scale models of observed variance. The flexibility of the deep learning setting will moreover allow to add constraints on perturbation or covariate latent spaces—these could for example be similarity of chemical compounds[49] or clinical-covariate induced differences of patient IDs. The key feature of CPA versus a normal autoencoder is latent space disentanglement and the induced interpretability of the perturbations in context of cell state and covariates. Eventually, any aim in biology is not only blind prediction but mechanistic understanding. This can be nicely seen with the direction that deep learning models are taking in sequence genomics, where the aim is not only the prediction of new interactions, but also the interpretation of the learnt gene regulation code. We therefore believe that CPA cannot only be used as a hypothesis generation tool for *in-silico* screens but also as an overall data approximation model. Deviations from our assumed data generating process (see **Methods**) would then tell us about missing information in the given data set and/or missing aspects in the factor model. By including multiple layers of regulation, the resulting model can grow in flexibility for prediction and also for mechanistic understanding on for example synergistic gene regulation or other interactions.

Finally, we expect CPA to facilitate new opportunities in expression-based perturbation screenings, not only to learn optimal drug combinations but also how to personalize experiments and treatments by tailoring them based on individual cell responses.

Code availability

Code to reproduce all of our results available at http://github.com/facebookresearch/CPA.

Data availability

All datasets analyzed in this manuscript are public and published in other papers. We have referenced them in the manuscript and made available at http://github.com/facebookresearch/CPA.

Author Contributions

M.L. conceived the project with contributions from D.L.P, F.J.T and A.K.S. D.L.P, M.L and A.K.S designed the algorithm and implemented the first version. Y.J and C.D performed the first refactor. The final code is implemented by D.L.P and A.K.S with contributions from C.D, Y.J and M.L. M.L and C.D curated the all datasets. F.A.W. helped interpret model and results. M.L. and F.J.T. designed analyses and use-cases. M.L, A.K.S., Y.J, I.L.I and C.D performed the analysis. F.J.T. and N.Y. supervised the research. All authors wrote the manuscript.

Acknowledgments

M.L. and F.J.T. are grateful for valuable feedback from Aviv Regev and Dana Pe'er. We appreciate support from all member of Theis lab specifically Malte D. Luecken and Fabiola Curion for their feedback and proof-reading. M.L is thankful for early graphical designs by Monir Jazaeri (Jaz) which did not make it to the final version of the paper. F.J.T. acknowledges support by the BMBF (grant L031L0214A, grant 01IS18036A and grant 01IS18053A), by the Helmholtz Association (Incubator grant sparse2big, grant ZT-I-0007) and by the Chan Zuckerberg Initiative DAF (advised fund of Silicon Valley Community Foundation, 2018-182835 and 2019-207271). This work was further supported by Helmholtz Association's Initiative and Networking Fund through Helmholtz AI [grant ZT-I-PF-5-01]. I.L.I. acknowledges funding support by discovAIR.

Competing interests

F.J.T. reports receiving consulting fees from Roche Diagnostics GmbH and Cellarity Inc., and ownership interest in Cellarity, Inc. and Dermagnostix. F.A.W. is a full-time employee of Cellarity Inc., and has ownership interest in Cellarity, Inc.

Methods

Data generating process

We consider a dataset $\mathcal{D} = \{(x_i, d_i, c_i)\}_{i=1}^N$, where each $x_i \in \mathbb{R}^G$ describes the gene expression of G genes from cell i. The perturbation vector $d_i = (d_{i,1}, \ldots, d_{i,M})$ contains elements $d_{i,j} \geq 0$ describing the dose of drug j applied to cell i. If $d_{i,j} = 0$, this means that perturbation j was not applied to cell i. Unless stated otherwise, the sequel assumes column vectors. Similarly, the vector of vectors $c_i = (c_{i,1}, \ldots c_{i,K})$ contains additional discrete covariates such as cell-types or species, where each covariate is itself a vector, more specifically $c_{i,j}$ is a K_j-dimensional one-hot vector.

We assume that an unknown generative model produced our dataset $\mathcal{D}$. The three initial ingredients of this generative process are a latent (unobserved) basal latent state z_i^{basal} for cell i, together with its perturbation vector d_i and covariate vector c_i. We assume that the basal latent state is independent from the perturbation vector d_i and covariate vector c_i. Next, we form the latent (also unobserved) perturbed latent state z_i as:

$$z_i = z_i^{\text{basal}} + V^{\text{perturbation}} \cdot (f_1(d_{i,1}), \ldots, f_M(d_{i,M})) + \sum_{j=1,\ldots,K} V^{\text{cov}_j} \cdot c_{i,j} \tag{1}$$

In the previous, each column of the matrix $V^{\text{perturbation}} \in \mathbb{R}^{d \times M}$ represents a d-dimensional embedding for one of the M possible perturbations represented in d_i. Similarly, each column of the matrix $V^{\text{cov}_j} \in \mathbb{R}^{d \times K_j}$ represents a d-dimensional embedding for the j-th discrete covariate, represented as a K_j-dimensional one-hot vector $c_{i,j}$. The functions $f_j : \mathbb{R} \to \mathbb{R}$ scale non-linearly each of the $d_{i,j}$ in the perturbation vector d_i, therefore implementing M independent dose-response (or time-response) curves. Finally, we assume that the generative process returns the observed gene expression x_i by means of an unknown decoding distribution $p(x_i|z_i)$. This process builds the observation (x_i, d_i, c_i), which is then included in our dataset $\mathcal{D}$.

Compositional Perturbation Autoencoder (CPA)

Assuming the generative process described above, our goal is to train a machine $x_i' = M((x_i, d_i, c_i), d')$ such that, given a dataset triplet (x_i, d_i, c_i) as well as a target perturbation d', estimates the gene expression x_i' representing *what would the counterfactual distribution of the gene expression x_i with covariates c_i look like, had it been perturbed with d' instead of d_i.*

Given a dataset and a learning goal, we are now ready to describe our proposed model, the Compositional Perturbation Autoencoder (CPA). In the following, we describe separately how to train and how to test CPA models.

Training

The training of a CPA model consists in auto-encoding dataset triplets (x_i, d_i, c_i). That is, during training, a CPA model does not attempt to answer counterfactual questions. Instead, the training process consists in (1) encoding the gene expression x_i into an estimated basal state $\hat{z}_i^{\text{basal}}$ that does not contain any information about (d_i, c_i), (2) combining $\hat{z}_i^{\text{basal}}$ with learnable embeddings about (d_i, c_i) to form an estimated perturbed state $\hat{z}_i$, and (3) decoding $\hat{z}_i$ back into the observed gene expression x_i.

More specifically, the CPA model first encodes the observed gene expression x_i into an estimated basal state:

$$\hat{z}_i^{\text{basal}} = \hat{f}^{\text{enc}}(x_i).$$

In turn, the estimated basal state is used to compute the estimated perturbed state $\hat{z}_i$:

$$\hat{z}_i := \hat{z}_i^{\text{basal}} + \hat{V}^{\text{perturbation}} \cdot (\hat{f}_1(d_{i,1}), \ldots \hat{f}_M(d_{i,M})) + \sum_{j=1,\ldots,K} \hat{V}^{\text{cov}_j} \cdot c_{i,j} \tag{2}$$

This expression, counterpart to (1), introduces three additional learnable components: the perturbation embeddings $\hat{V}^{\text{perturbation}}$, the covariate embeddings $\hat{V}^{\text{cov}}$ and the learnable dose-response curves $(\hat{f}_1, \ldots, \hat{f}_M)$, here implemented as small neural networks constrained to satisfy $\hat{f}_j(0) = 0$.

As a final step, a decoder $\hat{f}^{\text{dec}}$ accepts the estimated perturbed state $\hat{z}_i$ and returns $\hat{f}_\mu^{\text{dec}}(\hat{z}_i)$ and $\hat{f}_{\sigma^2}^{\text{dec}}(\hat{z}_i)$, that is, the estimated mean and variance of the counterfactual gene expression x_i'.

To train our CPA model, we need a few loss functions. First, the reconstruction loss function is the Gaussian negative log-likelihood:

$$\ell_i := \frac{\log s(\hat{f}_{\sigma^2}^{\text{dec}}(\hat{z}_i))}{2} + \frac{(\hat{f}_\mu^{\text{dec}}(\hat{z}_i) - x_i')^2}{2 \cdot s(\hat{f}_{\sigma^2}^{\text{dec}}(\hat{z}_i))}, \tag{3}$$

where $s(\sigma^2) = \log(\exp(\sigma^2 + 10^{-3}) + 1)$ enforces a positivity constraint on the variance and adds numerical stability. This loss function encourages that the end-to-end auto-encoding process produces the observed gene expression x_i.

Second, and according to our assumptions about the data generating process, we are interested in removing the information about (d_i, c_i) from $\hat{z}_i^{\text{basal}}$. To achieve this information removal, we follow an adversarial approach [27] to achieve this information removal. In particular, we set up the following auxiliary loss functions:

$$\ell_i^d := \text{CrossEntropy}(\hat{f}_d^{\text{adv}}(\hat{z}_i^{\text{basal}}), d_i),$$
$$\ell_{i,j}^c := \text{CrossEntropy}(\hat{f}_{c_{i,j}}^{\text{adv}}(\hat{z}_i^{\text{basal}}), c_{i,j}), \quad \forall j = 1, \ldots, K.$$

The functions $\hat{f}_d^{\text{adv}}$, $\hat{f}_{c_{i,j}}^{\text{adv}}$ are a collection of neural network classifiers trying to predict about (d_i, c_i) given the estimated basal state $\hat{z}_i^{\text{basal}}$.

Given this collection of losses, the training process is an optimization problem that alternates:

- sample $(x_i, d_i, c_i) \sim \mathcal{D}$, minimize $\ell_i^d + \sum_j \ell_{i,j}^c$ by updating the parameters of $\hat{f}_d^{\text{adv}}$ and $\hat{f}_{c_{i,j}}^{\text{adv}}$, for all $j = 1, \ldots, K$;

- sample $(x_i, d_i, c_i) \sim \mathcal{D}$, minimize $\ell_i - \lambda \cdot (\ell_i^d + \sum_j \ell_{i,j}^c)$ by updating the parameters of the encoder $\hat{f}^{\text{enc}}$, the decoder $\hat{f}^{\text{dec}}$, the perturbation embeddings $\hat{V}^{\text{perturbation}}$, the covariate embeddings $\hat{V}^{\text{cov}_j}$ for all $j = 1, \ldots, K$, and the dose-response curve estimators $(\hat{f}_1, \ldots, \hat{f}_M)$.

Testing

Given an observation (x_i, d_i, c_i) and a counterfactual treatment d', we can use a trained CPA model to answer *what would the counterfactual distribution of the gene expression x_i with covariates c_i look like, had it been perturbed with d' instead of d_i.* To this end, we follow the following process:

- Compute the estimated basal state $\hat{z}_i^{\text{basal}} = \hat{f}^{\text{enc}}(x_i)$;

- Compute the <u>counterfactual</u> perturbed state

$$\hat{z}_i' := \hat{z}_i^{\text{basal}} + \hat{V}^{\text{perturbation}} \cdot (\hat{f}_1(d_{i,1}'), \dots \hat{f}_M(d_{i,M}')) + \sum_{j=1,\dots,K} \hat{V}^{\text{cov}_j} \cdot c_{i,j}.$$

  Note that in the previous expression, we are using the counterfactual treatment d' instead of the observed treatment d_i.

- Compute and return the <u>counterfactual</u> gene expression mean:

$$x_{i,\mu}' = \hat{f}_\mu^{\text{dec}}(\hat{z}_i'),$$

  and variance:

$$x_{i,\sigma^2}' = \hat{f}_{\sigma^2}^{\text{dec}}(\hat{z}_i').$$

Hyper-parameters and training.

For each dataset, we perform a random hyper-parameter search of 100 trials. The table below outlines the distribution of values for each of the hyper-parameters involved in CPA training.

Group	Hyperparameter	Default value	Random search distribution
general	embedding dimension	256	RandomChoice([128, 256, 512])
	batch size	128	RandomChoice([64, 128, 256, 512])
	learning rate decay, in epochs	45	RandomChoice([15, 25, 45])
nonlinear scalers	hidden neurons, nonlinear scalers	64	RandomChoice([32, 64, 128])
	hidden layers	2	RandomChoice([1, 2, 3])
	learning rate	1e-3	$10^{\text{Uniform}}(-4, -2)$
	weight decay	1e-7	$10^{\text{Uniform}}(-8, -5)$
encoder and decoder	hidden neurons, encoder and decoder	512	RandomChoice([256, 512, 1024])
	hidden layers	4	RandomChoice([3, 4, 5])
	learning rate	1e-3	$10^{\text{Uniform}}(-4, -2)$
	weight decay	1e-6	$10^{\text{Uniform}}(-8, -4)$
discriminator	hidden neurons, discriminator	128	RandomChoice([64, 128, 256])
	hidden layers	3	RandomChoice([2, 3, 4])
	regularization strength	5	$10^{\text{Uniform}}(-2, 2)$
	gradient penalty	3	$10^{\text{Uniform}}(-2, 1)$
	learning rate	3e-4	$10^{\text{Uniform}}(-5, -3)$
	weight decay	1e-4	$10^{\text{Uniform}}(-6, -3)$
	number of learning steps	3	RandomChoice([1, 2, 3, 4, 5])

Model evaluation.

We use several metrics to evaluate the performance of our model: (1) quality of reconstruction for in and OOD cases and (2) quality of disentanglement of cell information from perturbation information. We split the dataset into 3 subsets: train, test and OOD. For OOD case we chose such combinations of perturbations, that they exhibit unseen behavior. This usually corresponds to extreme doses of the drugs. We select one perturbation combination as "control". Usually these are Vehicle or DMSO if real control samples were present in the dataset, otherwise we chose a drug perturbation at a lower dosage as "control". For the evaluation we use mean squared error of the reconstruction

of an individual cell and average it over the cells for the perturbation of interest. As an additional metric we use classification accuracy in order to check how well the information about the drugs was separated from the information about the cells.

Uncertainty estimation.

To estimate the uncertainty of the predictions we use as a proxy the minimum distance between the queried perturbation and the set of conditions (covariate + perturbation combinations) seen during training. The intuition being that predictions on queried conditions that are more distant from the set of seen conditions are less certain. In order to estimate this we first compute the set of embeddings of the training covariate and perturbation combinations:

$$\hat{z}^{comb} = \hat{V}^{\text{perturbation}} \cdot (\hat{f}_1(d'_1), \dots \hat{f}_M(d'_M)) + \sum_{j=1,\dots,K} \hat{V}^{\text{cov}_j} \cdot c_j. \tag{4}$$

The latent vector for the queried condition is computed in the same manner. The cosine and euclidean distances from the training embedding set are computed and the minimum distance is used as proxy for uncertainty.

$$u_{cosine} = \min(1 - \mathbf{S_C}(\hat{z}^{query}, \hat{z}^{comb})) \tag{5}$$

$$u_{eucl} = \min(\mathbf{d}(\hat{z}^{query}, \hat{z}^{comb})) \tag{6}$$

Where $\mathbf{S_C}(\mathbf{x}, \mathbf{y})$ stands for the cosine similarity and $\mathbf{d}(x, y)$ for the euclidean distance between the two vectors.

With this methodology, in the case of a drug screening experiment, if we query a combination of cell type, drug and dosage that was seen during training we get an uncertainty that quals 0, since this combination was present in the training set. It is important to note that with this method we get a condition-level uncertainty, in that all cells predicted under the same query will have the same uncertainty, thus not taking cell specific information into account.

R2 score

We used *r2_score* function from *scikit-learn* which reports R2 (coefficient of determination) regression score.

Datasets

Gehring *et al.*

This dataset[8] comprises of 21, 191 neural stem cells (NSCs) cells perturbed with EGF and bFGF, BMP4, decitabine and Scriptaid, and retinoic acid. We obtained normalized data from the original authors and after filtering 19, 637 cells remained. We further selected 5, 000 HVGs using scanpy's[50] *highly_variable_genes* function for training and evaluation of the model.

Genetic CRISPR screening experiment

We obtained the raw count matrcies from Norman *et al.*[5] from GEO accession ID GSE133344. According to authors guide we excluded "NegCtrl1_NegCtrl0__NegCtrl1_NegCtrl0" control cells and merged all unperturbed cells as one "ctrl" condition. We then normalized and log-transformed the data using scanpy and selected 5, 000 HVGs for training. The final datasets has 108, 497 single-cells.

Cross-species experiment

The data was generated by Hagai *et al.* (Nature, 2018) [15] and downloaded from ArrayExpress (accession: E-MTAB-6754). The data consists of 119.819 phagocytes obtained from four different species: mouse, rat, pig and rabbit. The phagocytes are treated with lypopolysaccharide (LPS) and the samples are collected at different time points: 0 (control), 2, 4, and 6 hours after the beginning of treatment. All gene IDs from non-mouse data were mapped to the respective orthologs in the mouse genome. We filtered out cells with a percentage of counts belonging to mitochondrial genes higher than 20%, then proceeded to normalize and log-transform the count data. For training and evaluation we select 5000 HVG using Scanpy. After filtering, the data consists of 113.400 cells.

sciPlex 2

The data was generated by Srivatsan *et al.* (Science, 2020) [35] and downloaded from GEO (GSM4150377). The dataset consists of A549 cells treated with one of the following four compounds: dexamethasone, Nutlin-3a, BMS-345541, or vorinostat (SAHA). The treatment lasted 24 hours across seven different doses. The count matrix obtained from GEO consists of 24.262 cells. During QC we filtered cells with fewer than 500 counts and 720 different genes detected, furthermore, we discarded cells whose mitochondrial gene fraction exceeded 0.1, thus reducing the dataset to 14.811 cells. Genes present in fewer than 100 cells were discarded. We normalized the data using the size factors provided by the authors and log-transformed it. We selected 5000 HVGs for training and further evaluations.

sciPlex 3

The data was generated by Srivatsan *et al.* (Science, 2020) [35] and downloaded from GEO (GSM4150378). The dataset consists of three cancer cell lines (A549, MCF7, K562), which are treated with 188 different compounds with different mechanisms of action. The cells are exposed to 4 dosages (10 nM, 100 nM, 1000 nM, 10000 nM) plus vehicle. The count matrix obtained from GEO consists of 581.777 cells. The data was subset to half its size, reducing it to 290.888 cells. We then proceeded with log-transformation and the the selection of 5000 HVGs using Scanpy.

Interpretation of combinatorial genetic interactions by perturbation pairs and responder genes

In the case of the genetic screenings, work done by [5] implemented a set of metrics to annotate and classify gene-gene interactions based on responder genes. Following on their idea, we used predicted measurement differences with respect to control cells (δ), for genes **a** (δa), **b** (δb) and the double perturbation **ab** (δab), to calculate interaction types based on those models and similarity between the three expression vectors.

To association coefficients, we use the linear regression coefficients obtained from the model

$$\delta ab = \delta a c_1 + \delta b c_2 \tag{7}$$

To describe interaction modes, we used the following metrics.

1. **similarity between predicted and observed values**: $dcor(\delta a c_1 + \delta b c_2, \delta ab)$.

2. **linear regression coefficients**: c_1 and c_2.

3. **magnitude**: $(c_1^2 + c_2^2)^{1/2}$.

4. **dominance**: $|log_{10}(c_1/c_2)|$.

5. **similarity of single transcriptomes**: $dcor(a, b)$

6. **similarity of single to double transcriptomes**: $dcor([a, b], ab)$.

7. **equal contributions**: $\frac{\min(dcor(a,b), dcor(b,ab))}{\max(dcor(a,b), dcor(a,ab))}$.

Following clustering and comparison of these metrics across measured and predicted cells, we decided
the following rules of thumb to define and annotate interaction modes:

1. **epistatic**: $min(abs(c_1), abs(c_2)) > 0.2$ and either **(i)** $(abs(c_1) > 2abs(c_2))$ or **(ii)** $(abs(c_2) > 2abs(c_1))$

2. **potentiation**: magnitude > 1 and abs($dcor(a,b)$) - 1 > 0.2.

3. **strong sinergy (similar phenotypes)**: magnitude > 1 and abs($dcor([a,b], ab)$) - 1 > 0.2

4. **strong sinergy (different phenotypes)**: magnitude > 1 and abs($dcor(a,b)$) - 1 > 0.5.

5. **additive**: abs(magnitude) - 1 < 0.1.

6. **redundant**: abs($dcor([a,b], ab)$) - 1 < 0.2 and abs($dcor(a,b)$) - 1 < 0.2

If more than one interaction mode is suggested from these rules, we included redundant labels to
predicted interactions. For visualization purposes we consider genes whose annotated interactions
with more than 50 interactions modes (**Supplementary Fig.3c**).

For visualization purposes of differentially expressed genes with similar response across perturba-
tions (**Supplementary Fig.3d**), we retrieved the top 200 genes selected based on a random forest
classifier for each perturbation pair, using as labels control, a, b and ab cells. Then, we annotated
the direction (positive or negative) and magnitude of those changes versus control cells, generating
a code for clustering and visualization. To label genes with potential interaction effects, we labeled
them if the double perturbation predicted magnitude is 1.5x times or higher than the best value
observed in single perturbations.

References

[1] Pisco, A. O. et al. A single cell transcriptomic atlas characterizes aging tissues in the mouse. BioRxiv 661728 (2019).

[2] Domcke, S. et al. A human cell atlas of fetal chromatin accessibility. Science **370** (2020).

[3] Han, X. et al. Construction of a human cell landscape at single-cell level. Nature 1–9 (2020).

[4] Srivatsan, S. R. et al. Massively multiplex chemical transcriptomics at single-cell resolution. Science **367**, 45–51 (2020).

[5] Norman, T. M. et al. Exploring genetic interaction manifolds constructed from rich single-cell phenotypes. Science **365**, 786–793 (2019). Publisher: American Association for the Advancement of Science Section: Research Article.

[6] Yofe, I., Dahan, R. & Amit, I. Single-cell genomic approaches for developing the next generation of immunotherapies. Nature medicine **26**, 171–177 (2020).

[7] McGinnis, C. S. et al. Multi-seq: sample multiplexing for single-cell rna sequencing using lipid-tagged indices. Nature methods **16**, 619–626 (2019).

[8] Gehring, J., Park, J. H., Chen, S., Thomson, M. & Pachter, L. Highly multiplexed single-cell rna-seq by dna oligonucleotide tagging of cellular proteins. Nature Biotechnology **38**, 35–38 (2020).

[9] Sachs, S. et al. Targeted pharmacological therapy restores β-cell function for diabetes remission. Nature Metabolism **2**, 192–209 (2020).

[10] Kim, K.-T. et al. Application of single-cell rna sequencing in optimizing a combinatorial therapeutic strategy in metastatic renal cell carcinoma. Genome biology **17**, 1–17 (2016).

[11] Al-Lazikani, B., Banerji, U. & Workman, P. Combinatorial drug therapy for cancer in the post-genomic era. Nature biotechnology **30**, 679–692 (2012).

[12] Dixit, A. et al. Perturb-seq: Dissecting molecular circuits with scalable single-cell rna profiling of pooled genetic screens. Cell **167**, 1853–1866.e17 (2016).

[13] Datlinger, P. et al. Pooled crispr screening with single-cell transcriptome readout. Nature methods **14**, 297–301 (2017).

[14] Rozenblatt-Rosen, O., Stubbington, M. J., Regev, A. & Teichmann, S. A. The human cell atlas: from vision to reality. Nature News **550**, 451 (2017).

[15] Hagai, T. et al. Gene expression variability across cells and species shapes innate immunity. Nature **563**, 197–202 (2018).

[16] Lotfollahi, M., Wolf, F. A. & Theis, F. J. scgen predicts single-cell perturbation responses. Nature methods **16**, 715–721 (2019).

[17] Lotfollahi, M., Naghipourfar, M., Theis, F. J. & Wolf, F. A. Conditional out-of-distribution generation for unpaired data using transfer vae. Bioinformatics **36**, i610–i617 (2020).

[18] Yuan, B. et al. Cellbox: Interpretable machine learning for perturbation biology with application to the design of cancer combination therapy. Cell Systems **12**, 128–140 (2021).

[19] Fröhlich, F. et al. Efficient parameter estimation enables the prediction of drug response using a mechanistic pan-cancer pathway model. Cell systems **7**, 567–579 (2018).

[20] Rampášek, L., Hidru, D., Smirnov, P., Haibe-Kains, B. & Goldenberg, A. Dr.VAE: improving drug response prediction via modeling of drug perturbation effects. Bioinformatics **35**, 3743–3751 (2019).

[21] Kamimoto, K., Hoffmann, C. M. & Morris, S. A. Celloracle: Dissecting cell identity via network inference and in silico gene perturbation. bioRxiv (2020).

[22] Eraslan, G., Simon, L. M., Mircea, M., Mueller, N. S. & Theis, F. J. Single-cell rna-seq denoising using a deep count autoencoder. Nature communications **10**, 1–14 (2019).

[23] Lopez, R., Regier, J., Cole, M. B., Jordan, M. I. & Yosef, N. Deep generative modeling for single-cell transcriptomics. Nature methods **15**, 1053–1058 (2018).

[24] Lotfollahi, M. et al. Query to reference single-cell integration with transfer learning. bioRxiv (2020).

[25] Lopez, R., Gayoso, A. & Yosef, N. Enhancing scientific discoveries in molecular biology with deep generative models. Molecular Systems Biology **16**, e9198 (2020).

[26] Russkikh, N. et al. Style transfer with variational autoencoders is a promising approach to rna-seq data harmonization and analysis. Bioinformatics **36**, 5076–5085 (2020).

[27] Lample, G. et al. Fader networks: Manipulating images by sliding attributes. In Advances in neural information processing systems, 5967–5976 (2017).

[28] Mikolov, T., Sutskever, I., Chen, K., Corrado, G. & Dean, J. Distributed representations of words and phrases and their compositionality. arXiv preprint arXiv:1310.4546 (2013).

[29] Sohn, K., Lee, H. & Yan, X. Learning structured output representation using deep conditional generative models. Advances in neural information processing systems **28**, 3483–3491 (2015).

[30] McInnes, L., Healy, J. & Melville, J. Umap: Uniform manifold approximation and projection for dimension reduction. arXiv preprint arXiv:1802.03426 (2018).

[31] Van der Maaten, L. & Hinton, G. Visualizing data using t-sne. Journal of machine learning research **9** (2008).

[32] Radford, A., Metz, L. & Chintala, S. Unsupervised representation learning with deep convolutional generative adversarial networks. arXiv preprint arXiv:1511.06434 (2015).

[33] Goodfellow, I., Bengio, Y., Courville, A. & Bengio, Y. Deep learning, vol. 1 (MIT press Cambridge, 2016).

[34] Srivatsan, S. R. et al. Massively multiplex chemical transcriptomics at single-cell resolution. Science **367**, 45–51 (2020). Tex.ids: srivatsanMassivelyMultiplexChemical2020a, srivatsanMassivelyMultiplexChemical2020b publisher: American Association for the Advancement of Science section: Research Article.

[35] Srivatsan, S. R. et al. Massively multiplex chemical transcriptomics at single-cell resolution. Science **367**, 45–51 (2020).

[36] Musa, A. et al. Systems pharmacogenomic landscape of drug similarities from lincs data: drug association networks. Scientific reports **9**, 1–16 (2019).

[37] Menden, M. P. et al. Community assessment to advance computational prediction of cancer drug combinations in a pharmacogenomic screen. Nature Communications **10**, 2674 (2019). Number: 1 Publisher: Nature Publishing Group.

[38] Adam, G. et al. Machine learning approaches to drug response prediction: challenges and recent progress. npj Precision Oncology **4**, 19 (2020).

[39] Jia, J. et al. Mechanisms of drug combinations: interaction and network perspectives. Nature Reviews Drug Discovery **8**, 111–128 (2009). Number: 2 Publisher: Nature Publishing Group.

[40] Gal, Y. & Ghahramani, Z. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In international conference on machine learning, 1050–1059 (PMLR, 2016).

[41] Frangieh, C. J. et al. Multimodal pooled perturb-cite-seq screens in patient models define mechanisms of cancer immune evasion. Nature genetics 1–10 (2021).

[42] Papalexi, E. et al. Characterizing the molecular regulation of inhibitory immune checkpoints with multimodal single-cell screens. Nature Genetics 1–10 (2021).

[43] Chen, S., Lake, B. B. & Zhang, K. High-throughput sequencing of the transcriptome and chromatin accessibility in the same cell. Nature biotechnology **37**, 1452–1457 (2019).

[44] Clark, S. J. et al. scnmt-seq enables joint profiling of chromatin accessibility dna methylation and transcription in single cells. Nature communications **9**, 1–9 (2018).

[45] Kaya-Okur, H. S. et al. Cut&tag for efficient epigenomic profiling of small samples and single cells. Nature communications **10**, 1–10 (2019).

[46] Wu, S. J. et al. Single-cell CUT&Tag analysis of chromatin modifications in differentiation and tumor progression. Nature Biotechnology 1–6 (2021). Publisher: Nature Publishing Group.

[47] van den Brink, S. C. et al. Single-cell and spatial transcriptomics reveal somitogenesis in gastruloids. Nature **582**, 405–409 (2020).

[48] Rodriques, S. G. et al. Slide-seq: A scalable technology for measuring genome-wide expression at high spatial resolution. Science **363**, 1463–1467 (2019).

[49] Mater, A. C. & Coote, M. L. Deep learning in chemistry. Journal of chemical information and modeling **59**, 2545–2559 (2019).

[50] Wolf, F. A., Angerer, P. & Theis, F. J. Scanpy: large-scale single-cell gene expression data analysis. Genome biology **19**, 1–5 (2018).

Supplementary Figure 1 | Uncertainty estimation. (a) Schematic representation of the steps involved in uncertainty estimation in the case of a dataset with 2 cell types and 2 drugs (single dosage per drug). The covariate and perturbation latent vectors are summed in order to generate the set of combinations in the training set. The distances from the query vector and all the vectors in the set are then computed. The closest distance is used as a proxy for uncertainty in the prediction of the model. **(b)** Example of uncertainty across dosage in the Sci-Plex 2 dataset. The ticks on the x-axis indicate dosages seen at training time for which the uncertainty is 0. **(c)** 2D plot of uncertainty across dosages of two different drugs and combinations thereof in the Sci-Plex 2 dataset. **(d)** Histogram of the cosine distances between the queried perturbation (SAHA (dose=0.5)) and the vectors in the set of training perturbations. The distribution shows that training vectors belonging to the same perturbation (but with different dosage) are the closest ones, with other drugs being progressively more distant.

Supplementary Figure 2 | Performance evaluation for CPA combinatorial perditions.(a) UMAP representation of control, singly and doubly perturbed cells with *CBL* and *CNN1* cells. **(b)** R2 values of variance for all genes (blue) or top 100 DEGs for the prediction of all 131 combinations in the data by training 13 different models leaving out of ≈ 10 combinations each time. **(c)** Scatter plots of number sample in the real data for each combination (x-axis) versus R2 values for the variance of predicted and real for that combination **(d)** Box-plots of R2 values for variance for predicted and real cells while increasing the number of combinations seen during training.

Supplementary Figure 3 | Gene-gene interaction insights revealed from genetic perturbation predictions using CPA. (a) Number of single gene observations in leiden clusters (from Figure 4i). Most leiden clusters contain mainly one gene. The majority of genes without any experimental double measurement (has double = no) tend to group in broader clusters. **(b)** Quality control and interaction metrics to compare gene expression differences between single (a, b) and double (ab) perturbations. Metrics have increasing/decreasing values based on number of genes in a predicted double perturbation with a measured double perturbation (See **Methods** for definitions). **(c)** Interaction type counts predicted for all datasets based on hierarchical clustering of metrics to annotate gene-gene interactions (c). Interaction annotations based on suggestions from [5]. **(d)** (*left*) Gene expression changes for double perturbations (ab) versus single perturbations (a, b), are compared by direction and magnitude. Positive (+), negative (-) labels indicate increase/decrease versus control cells, and double positive/negative (++/- -) indicate values higher than 1.5 times the highest comparable value in single perturbations. (*right*) 500 genes with highest prevalence in differentially expressed genes across datasets, cluster by prevalent response types from single and double perturbations.

condition	dose_val	R2_mean	R2_mean_DE	R2_var	split	num_cells
SAHA	0.01	0.99	0.99	0.95	test	160
SAHA	0.005	0.98	0.98	0.93	test	143
SAHA	0.05	0.98	0.95	0.93	test	118
SAHA	1.0	0.98	0.95	0.91	test	137
SAHA	0.001	0.97	0.97	0.92	test	169
SAHA	0.1	0.96	0.86	0.94	test	129
SAHA	0.5	0.96	0.86	0.89	**ood**	604
Nutlin	0.001	0.98	0.98	0.94	test	135
Nutlin	0.05	0.98	0.98	0.94	test	136
Nutlin	0.005	0.98	0.97	0.94	test	107
Nutlin	0.1	0.98	0.97	0.94	test	200
Nutlin	0.01	0.98	0.97	0.93	test	180
Nutlin	0.5	0.92	0.86	0.84	**ood**	265
Nutlin	1.0	0.26	0.61	0.00	test	1
Dex	0.5	0.99	0.99	0.98	**ood**	864
Dex	1.0	0.99	0.98	0.95	test	222
Dex	0.1	0.99	0.94	0.96	test	218
Dex	0.05	0.98	0.90	0.93	test	210
Dex	0.001	0.95	0.87	0.89	test	123
Dex	0.01	0.95	0.61	0.89	test	238
Dex	0.005	0.94	0.53	0.88	test	108
BMS	0.001	0.98	0.97	0.92	test	212
BMS	0.005	0.97	0.99	0.92	test	151
BMS	0.5	0.95	0.89	0.78	**ood**	34
BMS	0.01	0.95	0.80	0.86	test	82
BMS	0.05	0.93	0.87	0.75	test	59
BMS	0.1	0.92	0.89	0.74	test	50
BMS	1.0	0.55	-0.87	0.21	test	6

Supplementary Table 1 | Performance scores for sciplex 2 dataset. For the readability the columns are sorted by: condition (first priority) and scores (second priority).

condition	R2_mean	R2_mean_DE	method
SAHA	0.98	0.94	linear
SAHA	0.96	0.86	CPA
Nutlin	0.92	0.86	CPA
Nutlin	0.85	0.80	linear
Dex	1.00	1.00	linear
Dex	0.99	0.99	CPA
BMS	0.95	0.89	CPA
BMS	0.89	0.85	linear

Supplementary Table 2 | A simple benchmark on OOD split for sciplex 2 dataset.

condition	dose_val	R2_mean	R2_mean_DE	R2_var	split	num_cells
EGF+RA	0.2+1.0	0.98	0.95	0.84	test	553
EGF+RA	1.0+1.0	0.97	0.94	0.67	test	199
EGF+RA	0.2+0.2	0.96	0.98	0.89	test	87
EGF+RA	0.04+1.0	0.96	0.90	0.60	test	54
EGF+RA	1.0+0.2	0.95	0.91	0.75	test	30
EGF	0.2	0.98	0.96	0.86	test	90
EGF	1.0	0.94	0.71	0.60	test	73
BMP+RA	0.2+1.0	0.91	0.84	0.60	test	22
BMP+EGF+ScripDec	0.2+0.2+1.0	0.97	0.97	0.82	**ood**	166
BMP+EGF+ScripDec	0.04+0.04+1.0	0.97	0.96	0.61	test	28
BMP+EGF+ScripDec	0.04+0.2+1.0	0.97	0.94	0.50	test	39
BMP+EGF+ScripDec	0.2+0.2+0.2	0.97	0.92	0.65	**ood**	304
BMP+EGF+ScripDec	0.04+0.2+0.2	0.97	0.91	0.74	test	33
BMP+EGF+ScripDec	0.2+0.04+1.0	0.96	0.96	0.26	test	32
BMP+EGF+ScripDec	0.2+0.04+0.2	0.96	0.94	0.34	test	20
BMP+EGF+ScripDec	1.0+0.2+0.2	0.96	0.91	0.74	**ood**	113
BMP+EGF+ScripDec	0.2+1.0+1.0	0.95	0.89	0.51	**ood**	112
BMP+EGF+ScripDec	0.04+0.04+0.2	0.95	0.87	0.52	test	19
BMP+EGF+ScripDec	0.2+1.0+0.2	0.95	0.83	0.58	**ood**	105
BMP+EGF+ScripDec	0.04+1.0+1.0	0.94	0.96	0.57	test	17
BMP+EGF+ScripDec	1.0+0.04+0.2	0.91	0.86	0.51	test	15
BMP+EGF+RA	0.04+1.0+0.2	0.98	0.99	0.85	test	50
BMP+EGF+RA	0.2+0.04+0.2	0.98	0.98	0.74	test	63
BMP+EGF+RA	0.04+1.0+1.0	0.98	0.97	0.86	test	198
BMP+EGF+RA	0.04+0.2+1.0	0.97	0.96	0.88	test	552
BMP+EGF+RA	0.2+0.04+1.0	0.97	0.96	0.70	test	48
BMP+EGF+RA	0.04+0.2+0.2	0.97	0.92	0.80	test	73
BMP+EGF+RA	0.2+0.2+0.2	0.97	0.88	0.52	**ood**	206
BMP+EGF+RA	0.04+0.04+0.2	0.96	0.96	0.73	test	24
BMP+EGF+RA	0.2+1.0+0.2	0.96	0.89	0.66	**ood**	216
BMP+EGF+RA	0.2+1.0+1.0	0.96	0.87	0.66	**ood**	147
BMP+EGF+RA	0.2+0.2+1.0	0.95	0.77	0.59	**ood**	132
BMP+EGF	0.04+0.2	0.97	0.98	0.78	test	96
BMP+EGF	0.04+1.0	0.97	0.92	0.81	test	209
BMP+EGF	0.04+0.04	0.97	0.92	0.75	test	39
BMP+EGF	1.0+0.04	0.95	0.86	0.33	test	19
BMP+EGF	1.0+1.0	0.94	0.75	0.06	**ood**	113

Supplementary Table 3 | Performance scores for 96-plex-scRNAseq dataset. For the readability the columns are sorted by: condition (first priority) and scores (second priority).

split	species	time	R2_mean	R2_mean_DE	R2_var	num_cells
split4	rat	6.0	0.97	0.91	0.85	7827
split4	rat	6.0	0.96	0.86	0.89	7827
split4	mouse	6.0	0.97	0.90	0.81	5280
split4	mouse	6.0	0.96	0.85	0.93	5280
split3	rat	6.0	0.89	0.70	0.72	7827
split3	rat	6.0	0.86	0.55	0.40	7827
split3	rat	4.0	0.95	0.80	0.80	5755
split3	rat	4.0	0.94	0.77	0.63	5755
split2	rat	6.0	0.55	-0.65	-2.18	7827
split2	rat	6.0	0.54	0.02	0.02	7827
split2	rat	4.0	0.74	-0.47	0.26	5755
split2	rat	4.0	0.39	-0.85	-0.47	5755
split2	rat	2.0	0.81	-0.41	0.49	7025
split2	rat	2.0	0.41	-0.96	-0.64	7025
split1	rat	6.0	0.97	0.91	0.92	7827
split1	rat	6.0	0.97	0.91	0.92	7827
split1	rat	2.0	0.96	0.90	0.90	7025
split1	rat	2.0	0.96	0.90	0.90	7025
split0	rat	6.0	0.97	0.89	0.90	7827
split0	rat	6.0	0.96	0.90	0.81	7827

Supplementary Table 4 | Performance scores for cross species dataset among different splits.

species	time	R2_mean	R2_mean_DE	R2_var	split	num_cells
rat	2.0	1.00	1.00	0.99	test	2138
rat	4.0	1.00	1.00	0.99	test	1715
rat	6.0	0.96	0.86	0.89	**ood**	7827
rabbit	6.0	0.99	0.99	0.99	test	2088
rabbit	2.0	0.99	0.99	0.98	test	2662
rabbit	4.0	0.99	0.96	0.98	test	1732
pig	6.0	0.99	0.99	0.99	test	1535
pig	4.0	0.99	0.98	0.99	test	1954
pig	2.0	0.99	0.98	0.98	test	1662
mouse	2.0	1.00	0.99	0.99	test	2904
mouse	4.0	1.00	0.99	0.99	test	2793
mouse	6.0	0.96	0.85	0.93	**ood**	5280

Supplementary Table 5 | Performance scores for cross species dataset.