1 Evolving the Olfactory System with Machine Learning

Peter Y. Wang[1,3], Yi Sun[4], Richard Axel[1,2], L.F. Abbott[1] and Guangyu Robert Yang[1,5,6]*

[1] The Mortimer B. Zuckerman Mind Brain Behavior Institute, Department of Neuroscience,

Columbia University, New York, NY 10027, USA

[2] Howard Hughes Medical Institute, Columbia University

[3] Present address: Department of Bioengineering, Stanford University

[4] Present address: Department of Statistics, University of Chicago

[5] Present address: Department of Brain and Cognitive Sciences, MIT

[6] Lead Contact

*Correspondence: yanggr@mit.edu (G.R.Y.)

15
16
17

Summary

The convergent evolution of the fly and mouse olfactory system led us to ask whether the

anatomic connectivity and functional logic *in vivo* would evolve in artificial neural networks

constructed to perform olfactory tasks. Artificial networks trained to classify odor identity

recapitulate the connectivity inherent in the olfactory system. Input units are driven by a single

receptor type, and units driven by the same receptor converge to form a glomerulus. Glomeruli

exhibit sparse, unstructured connectivity to a larger, expansion layer. When trained to both

classify odor and impart innate valence on odors, the network develops independent pathways

for innate output and odor classification. Thus, artificial networks evolve even without the

biological mechanisms necessary to build these systems *in vivo*, providing a rationale for the

convergent evolution of olfactory circuits.

Introduction

The anatomic organization and functional logic of the olfactory systems of flies and mice are

remarkably similar despite the 500 million years of evolution separating the two organisms. Flies

and mice have evolved odorant receptors from different gene families and employ distinct

developmental pathways to construct a similar neural architecture for olfaction, suggesting that

the homology between the two olfactory systems emerged by convergent evolution. The

sensory neurons in each organism express only one of multiple odor receptors. This singularity

is maintained with the convergence of like neurons to form glomeruli so that mixing of olfactory

information occurs only later in the processing pathway. Convergent evolution of the olfactory

system may reflect the independent acquisition of an efficient solution to the problems of

olfactory perception. We asked whether networks constructed by machine learning to perform

olfactory tasks converge to the organizational principles of biological olfactory systems.

43 Artificial neural networks (ANNs) (Lecun, Bengio, & Hinton, 2015) capable of performing

44 complex tasks provide a novel approach to modeling neural circuits (Mante, Sussillo, Shenoy, &

45 Newsome, 2013; Yamins & DiCarlo, 2016). Neural activity patterns from higher visual areas of

46 monkeys viewing natural images resemble activity patterns from neural networks trained to

47 classify large numbers of visual images (Yamins & DiCarlo, 2016). These results reveal a

48 correspondence between the artificial and biological visually driven responses. However, it has

49 been difficult to determine to what extent the connectivity of ANNs recapitulates the connectivity

50 of the visual brain. Multiple circuit architectures can be constructed by machine-learning

51 methods to achieve similar task performance, and details of connectivity that might resolve this

52 ambiguity remain unknown for most mammalian neural circuits. In contrast, the precise

53 knowledge of the connectivity of the fly olfactory circuit affords a unique opportunity to

54 determine whether ANNs and biological circuits converge to the same neural architecture for

55 solving olfactory tasks. In essence, we have used machine learning to 'replay' evolution, to

56 explore the rationale for the evolutionary convergence of biological olfactory circuits.

58 In fruit flies, olfactory perception is initiated by the binding of odorants to olfactory receptors on

59 the surface of sensory neurons on the antennae (Figure 1a). Individual olfactory receptor

60 neurons (ORNs) express one of 50 different olfactory receptors (ORs), and all receptor neurons

61 that express the same receptor converge onto an anatomically invariant locus, a glomerulus

62 within the antennal lobe of the fly brain (Vosshall, Amrein, Morozov, Rzhetsky, & Axel, 1999;

63 Vosshall, Wong, & Axel, 2000a). Most projection neurons (PNs) innervate a single glomerulus

64 and send axons to neurons in the lateral horn of the protocerebrum (LHNs) and to Kenyon cells

65 (KCs) in the mushroom body (MB) (Jefferis et al., 2007; Marin, Jefferis, Komiyama, Zhu, & Luo,

66 2002; Wong, Wang, & Axel, 2002). The invariant circuitry of the lateral horn mediates innate

67 behaviors (Datta et al., 2008; Jefferis et al., 2007; Tanaka, Awasaki, Shimada, & Ito, 2004),

68 whereas the MB translates olfactory sensory information into associative memories and learned

behaviors (De Belle & Heisenberg, 1994; Dubnau, Grady, Kitamoto, & Tully, 2001; Heisenberg,

Borst, Wagner, & Byers, 1985; McGuire, Le, & Davis, 2001).

Individual Kenyon cells, the intrinsic neurons of the MB, receive unstructured input from ~4-10

PNs (Caron, Ruta, Abbott, & Axel, 2013; Li et al., 2020; Zheng et al., 2018) and densely

innervate MBONs, the extrinsic output neurons of the mushroom body (Aso et al., 2014b; Caron

et al., 2013; Chia & Scott, 2019; Hattori et al., 2017; Li et al., 2020; Tanaka et al., 2004; Zheng

et al., 2018). Synaptic plasticity at the KC-MBON synapse results in olfactory conditioning and

mediates learned behaviors (Cohn, Morantte, & Ruta, 2015; Felsenberg et al., 2018; Handler et

al., 2019; Hige, Aso, Rubin, & Turner, 2015). The mouse olfactory system is far larger than that

of the fly but exhibits a similar architecture.

The convergent evolution of the fly and mouse olfactory systems led us to ask whether the

anatomic connectivity and functional logic *in vivo* would evolve in artificial neural networks

constructed to perform olfactory tasks. We used stochastic gradient descent (Kingma & Ba,

2014; Lecun et al., 2015; Rumelhart, Hinton, & Williams, 1986) to construct artificial neural

networks that classify odors. We found singularity of receptor expression, convergence to form

glomeruli, and divergence to generate sparse unstructured connectivity that recapitulate the

circuit organization in flies and mice. We also trained neural networks to classify both odor class

and odor valence. After training, an initially homogeneous population of neurons segregated into

two populations with distinct input and output connections, resembling learned and innate

pathways. These studies provide logic for the functional connectivity of the olfactory systems in

evolutionarily distant organisms.

Fig. 1 | Artificial neural network evolves the connectivity of the fly olfactory system.

a. The fly olfactory system. **b.** Illustration of the task. Every odor (a million in total, 100 shown) is

a point in the space of ORN activity (50 dimensions, 2 dimensions shown) and is classified

based on the closest prototype odor (triangles, 100 in total, 4 shown). Each class is defined by

two prototype odors. **c.** Architecture of the artificial neural network. The expression profile of

ORs in every ORN as well as all other connection weights are trained. **d.** OR-ORN expression

profile after training. ORNs are sorted by the strongest projecting OR. **e.** ORN-PN mapping after

training. Each PN type is sorted by the strongest projecting ORN. **f.** Effective connectivity from

OR to PN type, produced by multiplying the matrices in (**d**) and (**e**). **g.** PN-KC connectivity after

training, only showing 20 KCs (2500 total). **h.** Distribution of PN-KC connection weights after

training showing the split into strong and weak groups. Connections weaker than a set threshold

(dotted gray line) are pruned to zero. **i.** Distribution of KC input degree after training. Text near

peak shows mean and standard deviation. **j**. Average cosine similarity between the weights of

all pairs of KCs during training. At every epoch, the cosine similarity was also computed after

shuffling the PN-KC connectivity matrix. This shuffling preserves the number of connections

each KC receives but eliminates any potential structured PN inputs onto individual KCs.

k,l. Investigating the impact of a recurrent inhibitory neuron in the KC layer. **k**, Schematics of a

network with a recurrent inhibitory neuron at the KC layer, modeling the Anterior Paired Lateral

(APL) neuron. The recurrent inhibitory neuron receives uniform excitation from all KC neurons,

and inhibits all KC neurons uniformly in return. **l**. (Top to bottom) Accuracy, GloScore, and KC

input degree for networks with different strengths of KC recurrent inhibition. Stronger KC

recurrent inhibition moderately increases KC input degree while having no clear impact on

accuracy and GloScore. K value is not shown for the network where KC input degree cannot be

reliably inferred (Methods).

Artificial neural networks converge to biological structures

We designed a family of odor classification tasks that mimic the ability of animals to distinguish

between odor classes and to generalize within classes. In the model, each odor elicits a unique

pattern of activation across the ORs. Odors are assigned to 100 classes that are defined by

odor prototypes. Specifically, each odor belongs to the class of its nearest prototype, measured

by the Euclidean distance between receptor activations (Figure 1b). Using only a single

prototype to define each class results in a relatively simple olfactory task that can be solved

without using the layers of olfactory processing that we wish to explore (Figure S2a-d). Thus, we

consider classes that are defined by multiple prototypes, predominantly using two prototypes

per class. This means that an odor class corresponds to an association involving multiple

different types of odors. We used a training set of a million randomly sampled odors to

construct the networks and assessed generalization performance with a test set of $8192 = 2^{13}$

additional odors.

We first modeled the olfactory pathway as a feedforward network with layers representing 50

ORs, 500 ORNs, 50 PN types, and 2,500 KCs (Figure 1c, Methods). The model also included a

set of 100 output units that allow us to read out the class assigned by the model to a given odor

(instead of directly modeling MBONs). The strengths of model connections between the OR and

ORN layers represent the levels of expression of the 50 different receptor types in each ORN.

ORN-to-PN and PN-to-KC connections represent excitatory synapses between these cell types

and are therefore constrained to be non-negative. We chose to represent the ~150 PNs in the

antennal lobe as 50 PN types because the ~3 homotypical 'sibling' PNs that converge onto the

same glomerulus show almost identical activity patterns (Kazama & Wilson, 2009; Masuda-

Nakagawa, Tanaka, & O'Kane, 2005). We hereafter refer to PN types as PNs. Initially, all

connections were all-to-all and random (Figure 1c), meaning that every ORN expressed every

OR at some level and connected to every PN. Similarly, each PN initially connected to all the

KCs. Neural responses were rectified linear functions of the total synaptic input. The network

was trained by altering its connection weights and bias currents with the goal of minimizing

classification loss. This occurs when there is high activity only in the readout unit representing

the correct class associated which each odor. This process can be thought of as evolving a

circuit architecture *in silico.*

Following training of the network, classification was ~75% accurate (chance is ~1%). The initial

random, all-to-all connectivity changed dramatically during the training process. After training, all

but one of the OR-to-ORN coupling strengths for each OR are close to zero (Figure 1d). This

corresponds to the expression of a single OR in each ORN. Similarly, all but ~10 of the ORN

connections to each PN approach zero (Figure 1e; Movie 1 in Methods) and, for each PN, all of

these connections arise from ORNs expressing the same OR type (Figure 1e). This

recapitulates the convergence of like ORNs onto a single glomerulus and the innervation of

single glomeruli by individual PNs (Mombaerts et al., 1996; Vosshall, Wong, & Axel, 2000b).

The extent that PNs receive input from a single OR type was quantified by a GloScore which,

for each PN, is the difference in magnitude between the strongest two connections it receives

from the OR types divided by their sum (Methods). A GloScore of 1 indicates that each PN

receives all its inputs from a single OR type, recapitulating fruit fly connectivity. During training

of the network, the GloScore of ORN-PN connectivity quickly approached values close to 1

(Figure S1b). Thus, the model recapitulates both the singularity of OR expression in the ORNs

and the existence of glomeruli in which ORNs expressing the same OR converge and connect a

glomerulus innervated by a single PN.

The model also recapitulated distinctive features of PN-to-KC connectivity. Each KC initially

received connections from all 50 PNs but, during training, connections from PNs to KCs became

sparser (Figure 1g). To quantify the number of PN inputs that each KC receives, weak PN-to-

KC connections were pruned to zero during training (Figure S1d-e). Results are insensitive to

the precise value of the pruning threshold, and pruning did not reduce classification

performance (Figure S1d). Furthermore, we found that the average number of PNs per KCs

plateaued during training, with a sparse ~3-7 PN inputs for each KC (Figure S1b). Importantly,

this sparse connectivity can also be obtained without pruning (Figure S1d, Methods). In some

cases, no distinct gap separated weak from strong synapses, making an estimate of connection

sparsity ambiguous; we identify these instances when they occur and exclude them from further

analysis (Figure 1l, Figure S1a).

The sparsity and lack of structure in the PN-to-KC connections of the model recapitulate the

properties of these connections in the fly (Caron et al., 2013; Li et al., 2020; Zheng et al., 2018).

The sparse KC input had no discernable structure (Figure 1g; Figure S3); the average

correlation between the input connections of all pairs of KCs is similar to the correlations

obtained by randomly shuffled connectivity at every training epoch (Figure 1j). Thus, from ORs

to KCs, the ANNs we have constructed to classify odors exhibit connectivity that mirrors the

layered circuitry of the fly olfactory system, with individual ORs expressing only 1 of 50

receptors, similar ORNs converging onto single glomeruli, and individual PNs that receive input

from only 1 glomerulus making sparse and unstructured connections to KCs. These results

were invariant to model hyper-parameters such as training rate and input noise (Figure S1).

Moreover, they were also independent of non-zero activity correlations between different ORs

(Figure S4). In all subsequent modelling experiments, we did not include the OR-to-ORN

connectivity; instead, every ORN was constructed to express a single OR.

KCs in the fly are inhibited largely through feedback from a non-spiking interneuron, APL (Aso

et al., 2014a; Lin, Bygrave, De Calignon, Lee, & Miesenböck, 2014; Tanaka, Tanimoto, & Ito,

2008). We modeled the APL assuming that it receives excitatory input from all KCs and

iteratively provides subtractive feedback inhibition onto every KC (Figure 1k). Feedback

inhibition did not strongly influence the number of PN inputs per KC, the formation of glomeruli,

or task performance (Figure 1l).

Fig. 2 | Dependence of results on biological features

(a) (From top to bottom) Accuracy, GloScore, and KC input degree as a function of training for

networks with and without the non-negativity constraint for ORN-PN connections. **(b,c)**

Summary of accuracy, GloScore and KC input degree for trained networks while varying the

number of KCs (**b**), and varying the number of PNs (**c**). When the number of PNs is high, the

KC input degree cannot be reliably inferred. (**d**) Schematics of two concentration-invariant tasks.

The odor prototypes (triangles) lie on the unit sphere, making classification boundaries radiate

outwards from the origin. The class that each odor belongs to therefore depends only on its

normalized activity and not on its concentration (i.e., magnitude), unlike in the standard task

(Figure 1b). (Left) A dataset where each OR's activity is uniformly distributed across odors.

(Right) A dataset where weak and strong odors are more common. The proportion of odors with

extreme concentration values is proportional to the "spread", a parameter between 0 and 1 (see

Methods). (**e**) Biological implementations of activity normalization (divisive normalization)

rescues classification performance in a concentration-invariant classification task when odor

concentration is highly variable. In contrast, a normalization method widely used in machine

learning, Batch Normalization (Ioffe & Szegedy, 2015), does not improve performance.

Dependence of results on model features

We next investigated how our results depend on key biological features in the models. The most

critical element for the results we have reported is the restriction to non-negative OR-ORN,

ORN-to-PN and PN-to-KC connections. Convergence of ORNs expressing the same OR onto

PNs does not occur if connections are not sign constrained. Gloscores drop if ORN-PN

connections are not sign constrained, although classification accuracy is maintained (Figure 2a).

In this case, PNs receive a dense array of inhibitory and excitatory connections from ORN

inputs, with the ORN connection patterns received by PNs largely uncorrelated (Figure S5a-d).

To explore the effect of varying cell numbers, we first trained networks with different numbers of

KCs, with ORNs and PNs fixed at 500 and 50, respectively. As the number of KCs was

decreased, PNs sampled from multiple ORs, decreasing the GloScore and classification

performance (Figure 2b, Figure S5f, S6g-h). Thus, a large expansion layer of KCs is necessary

for high classification performance but, with reduced numbers of KCs, some compensatory

mixing occurs at the PN level.

We also varied the number of PNs while keeping the numbers of ORNs and KCs fixed at 500

and 2,500, respectively. When the number of PNs is less than the number of unique OR types

(50), the PN layer acts as bottleneck and mixing occurs to ensure that all ORs are represented

(Figure 2c, Figure S5e, S6a), but performance suffers. When the number of PNs is greater than

50, we observed some PN mixing of ORN input, although this did not improve classification

accuracy, which saturates at 50 PNs (Figure 2c, Figure S5e, S6b). A closer examination

revealed that PNs segregate into two distinct populations, a population of uni-glomerular PNs

receiving a single type of OR and multi-glomerular PNs receiving multiple types of ORs (Figure

S6c-f). Moreover, the connection strengths from uni-glomerular PNs to KCs were strong and

crucial for classification performance. In contrast, connection strengths from multi-glomerular

PNs to KCs were weak, and silencing them minimally impaired classification performance

(Figure S6d-e).

Why does a PN layer exist if glomerular connectivity simply copies ORN activity forward to the

PNs? Experimental work has shown that the PN layer normalizes odor-evoked responses

(Olsen, Bhandawat, & Wilson, 2010), which is likely to be important for classification of odors

across a range of concentrations. We trained a feedforward network (Figure 1c) to perform

concentration-invariant classification with and without PN normalization while systematically

varying the range of odor concentrations in the task dataset (Figure 2d; Methods). We

normalized PN activity using a divisive normalization model inspired by the experimental studies

(Luo, Axel, & Abbott, 2010; Olsen et al., 2010). As the range of odor concentrations increased,

divisive normalization allowed the network to perform concentration-invariant classification

(Figure 2e).

Recurrent neural networks converge to biological structures

By varying the numbers of PNs and KCs, we found that performance plateaus when the number

of PNs (50) matches the number of ORs, and marginal performance gains were observed when

the number of KCs was increased past 2500. However, in the models we have considered thus

far, the number of neurons in each layer and the number of layers are fixed. We next asked

what structure emerges from a neural network that is not only capable of modifying connection

strengths, but also capable of allocating the number of neurons per layer.

To remove constraints on the numbers of neurons at each layer, we constructed a recurrent

neural network model (RNN) in which 'layers' are represented by network processing steps

(Figure 3a). This allowed us to explore how the network allocates its resources – neurons and

their connections – during each step and infer from this a particular layered network

architecture. The RNN model contained 2,500 neurons and was initialized with random, all-to-

all, non-negative connectivity between all neurons. At the first processing step, 500 of the 2,500

recurrently connected neurons were provided with OR inputs, and the remainder of the neurons

were silent. Thus, this first step of processing represents the ORN layer.

We first considered an RNN in which odor classes were read out after three processing steps

(Figure 3a). After training, this RNN reaches 67% accuracy, slightly lower than that of the

feedforward network. To test whether the RNN self-organized into a compression-expansion

structure like the feedforward network, we quantified how many neurons were active at each

processing step. Because we did not regularize for activity in the RNN units, a significant

number of neurons have non-zero but weak activations to odors (Figure S7a). These levels of

activity were bimodally separate from units possessing high levels of activity and were counted

as inactive (Figure S7a, Methods). Although the RNN could have used all 2,500 neurons at

each processing step, odor-evoked activity from the 500 neurons initialized with ORN

activations propagated strongly to only ~50 neurons after the second processing step (Figure

3d). This resulted from the convergence of ORNs onto single neurons (Figure 3b). In contrast,

nearly all neurons of the RNN at the third processing step had average activities (across odors)

above the threshold (Figure 3c). These neurons were driven by sparse, unstructured

connections from ~5-10 PN-like neurons to the remaining ~2,500 RNN neurons (Figure 3c,

Figure S7b-d).

We next examined the consequence of allowing the RNN to perform four processing steps,

which is equivalent to forcing an additional feedforward layer prior to classification of odors

(Figure 3e). Interestingly, this network did not use the extra layer to perform additional

computations. Rather, it simply copied the activity of the 50-55 PN-like neurons at the second

processing step to another similar set of ~100 neurons at the third processing step, only

activating the bulk of the 2,500 neurons at the fourth processing step (Figure 3f-i, Figure S7e-h).

Thus, the RNN recapitulated known features of the olfactory circuitry even when the numbers of

neurons available at each level was unconstrained.

Fig. 3 | a. Schematic of recurrent neural network using recurrent connections (W_{REC}) (left), and
the equivalent "unrolled" network diagram (right). **b, c**, Network connectivity between neurons
that are on-average active above a threshold at different steps. **b**, Connectivity from neurons
active at step 1 to neurons active at step 2. Connections are sorted. **c**, Connectivity from
neurons active at step 2 to neurons active at step 3, only showing the first 20 active neurons at
step 3. **d.** Number of active neurons at each step of computation. At step 1, only the first 500
units in the recurrent network are activated by odors. Classification performance is assessed
after step 3. **e-i,** Similar to (**a-d**), but for networks unrolled for 4 steps instead of 3. Classification

readout occurs at step 4. Effective step 2-4 connectivity is the matrix product of the step 2-3 (**g**)

and step 3-4 connectivity (not shown).

Network models with ongoing plasticity

We have shown thus far that biological connectivity emerges from both feedforward and

recurrent network models when trained on an odor classification task with fixed odor-class

mappings. However, the fly olfactory circuit must accommodate the learning of novel odor

associations for the fly to adapt successfully to new environments. Evidence strongly suggests

that plasticity in synaptic connections from KCs to MBONs underlies olfactory learning (Cohn et

al., 2015; Felsenberg et al., 2018; Handler et al., 2019; Hige et al., 2015), whereas PN-KC

connection strengths are thought to be fixed (Gruntman & Turner, 2013; Wilson, 2013). We

therefore introduced Hebbian plasticity between KCs and class neurons and sought to

understand how the KC representation can support ongoing learning. To focus on the PN-KC

representation, we eliminated the ORN layer in these studies (Figure 4a).

Up to this point, networks were trained to assign odors to a fixed set of classes. Now, we

construct networks that, after training, can continue to learn new odor classes. This is possible

because the networks are expanded to include ongoing plasticity at the synapses between the

KCs and output units (Methods). During the training process used to construct these networks,

the feedforward network (Figure 4a) learns a new odor-class mapping during each episode on

the basis of this synaptic plasticity (Figure 4b) (Finn, Abbeel, & Levine, 2017). On each episode,

we randomly select 16 odors from each of 5 odor classes drawn from the dataset described

previously (Figure 1b). Following training, the KC-output synapses undergo plastic updates

whereas the remaining network weights are fixed (Methods).

After the update of the plastic synapses, performance for each training episode is assessed by

a set of odors drawn from each one of the 5 odor classes used on that episode, and the non-

plastic network weights are adjusted by backpropagation to minimize errors. This encourages

the network to generalize to new odors on the basis of a limited set of sampled odors (16-shot

337 learning). At the start of each episode, non-plastic network weights are retained but plastic

338 weights are reset. We asked what connectivity evolved between PNs and KCs to support rapid,

339 flexible learning at the output synapses.

341 We found that, after training, networks with KC-output plasticity were capable of learning new

342 odor categories. These networks reached up to 80% accuracy in the 16-shot learning task

343 (Figure S8a). Sparse, unstructured connectivity emerged in plastic network models, with an

344 average of ~5 PNs per KC (Figure 4d-e). These results did not depend strongly on hyper-

345 parameters such as the addition of trainable ORN-PN weights, the number of classes per

346 episode, or the number of training odors per class (Figure S8a-c). We conclude that PN-KC

347 connectivity supporting rapid, flexible learning is similar to that observed in the original odor

348 classification task.

Figure 4

Fig. 4 | Network models with ongoing plasticity.

a. Schematic of a meta-trained network. The PN-KC architecture is evolved to support flexible odor learning at the KC-output synapse (W_{OUT}). **b.** Multiple datasets are sequentially presented to the network. Each dataset contains a small number of classes and 16 samples from each class. During the presentation of each dataset, KC-output connections undergo rapid plasticity to learn the classes. After fast KC-output learning, generalization performance to a new test set of odors is assessed and then used to update, i.e. meta-train, the weights of the network. **c.** PN-KC connectivity after training, showing 20 KCs. **d.** Distribution of PN-KC connection weights after training. **e.** Distribution of KC input degree after training.

Predicting connection sparsity for different species

The anatomic organization and functional logic of the fly olfactory system is shared with the mouse despite the large evolutionary distance separating the two species. In both mouse and fly, ORNs converge onto a glomerular compression layer, which then projects sparsely to an expansion layer (KCs in the fly, piriform cortex neurons in the mouse). Unlike in the fly, the input degree to the expansion layer in mouse (or any other species) can only been inferred from existing data as $K \sim 40 - 100$ (Davison & Ehlers, 2011; Miyamichi et al., 2011) (Figure 5, Methods).

We hypothesize that this input degree depends on a variety of parameters, but most heavily on the number of OR types (~1,000 in mouse compared to ~50 in fly). Therefore, in our neural network we asked how the expansion layer input degree (K) scales with the number of ORs (N), termed $K - N$ scaling. We have presented networks trained to perform two different tasks, one with a fixed set of odor classes, supervised training and non-plastic synapses, and the other with changing odor classes, meta-training and plastic synapses (Figure 4). Both of these led to similarly sparse PN-KC connectivity in fly-sized networks. We now quantify the $K - N$ scaling for each of them.

We constructed network models with different numbers of ORs to examine how their connectivity scales with OR number (Figure S9). Over the range we considered, connection number, K, always increases as a power law function, of N. However, the $K - N$ scaling is substantially different across the two tasks. We found that $K \approx 0.37N^{0.82}$ for networks trained with fixed classes, while $K \approx 2.84N^{0.12}$ for networks with plasticity (Figure 5, blue line). The shallower scaling found in plastic networks (Figure 5, red line) is broadly consistent with that predicted by previous theoretical work based on determining the wiring that maximizes

dimensionality (Figure 5, gray line, Litwin-Kumar et al. 2017). The connectivity that maximizes

dimensionality gives rise to $K \approx 1.16N^{0.31}$ (Methods).

Although both the fixed and plastic tasks we used to construct networks result in quantitatively

similar sparse PN-KC connectivity in fly-sized networks, they make different predictions for

mouse-sized networks and only fixed-category training appears to produce a result consistent

with the mouse data.

Fig. 5 | Sparsity for different species.

a. The connectivity K for networks with different numbers of ORs (N). K predicted by various methods (boxes and dots) and corresponding power-law fits (lines). Cyan: Training for the fixed odor categorization task; Red: Training for the plastic odor categorization task; Gray: Optimal K predicted by maximum dimensionality KC representation (Litwin-Kumar et al. 2017); Crosses: Experimental estimates. [2]: Miyamichi et al., 2011; [3]: (Davison & Ehlers, 2011). For each N, we include results from networks trained with different learning rates.

The emergence of an innate pathway

The repertoire of odorant receptors supports the detection of a vast number of odors in the environment, but a smaller number of receptors exhibit specificity for odors that elicit innate behaviors (Dweck et al., 2015; Ebrahim et al., 2015; Kurtovic, Widmer, & Dickson, 2007; Min, Ai, Shin, & Suh, 2013; Stensmyr et al., 2012; Suh et al., 2004). In flies, PNs activated by these odors project to topographically restricted regions of the LH to drive innate responses (Datta et al., 2008; Jefferis et al., 2007; Ruta et al., 2010; Varela, Gaspar, Dias, & Vasconcelos, 2019). We asked whether an artificial network could evolve segregated pathways for innate and learned responses.

We trained neural networks to classify both odor class and odor valence. Odor class was determined as in our original models. To add an innate component, each odor was assigned to one of 3 categories, 'appetitive', 'aversive', or 'neutral'. Of the 50 ORs, 5 were assigned innately appetitive responses, another 5 innately aversive responses. Neutral odors activate all ORs as in our previous networks, with activations drawn from a uniform distribution between 0 and 1 (Figure 6a, left). The 40 ORs with no innate selectivity are activated in this way by non-neutral valence odors as well. However, each odor bearing a non-neutral valence also activates a single innate OR especially strongly (on average 3 times stronger than other ORs) (Figure 6a, right). We used a feedforward architecture with 500 ORNs, 50 PNs, and 2,500 third-order neurons that project to both class and innate valence output units (Figure 6b). In this case, there are two sets of output units, one set to report odor class and another to report innate valence. The 2,500 third-order model neurons represent a mixture of LHN and KC neurons, allowing us to investigate whether the segregation into two distinct populations is recapitulated by the model.

The network successfully performed both odor classification and valence determination.

Glomeruli emerged for neutral, appetitive, and aversive ORs (Figure S10a). The network also

generated two segregated clusters of third-order neurons (Figure 6c-d, Figure S10b; Methods).

These clusters were segregated based on both input and output connectivity profiles. Cluster 1

typically contains ~2,000 neurons (Figure S10c-d). Cluster 1 neurons are analogous to KCs and

project strongly to class read-out neurons but weakly to valence read-out neurons (Figure 6c,

d). They receive ~5-7 strong inputs from random subsets of PNs (Figure 6e, f, Figure S10e-f). In

contrast, cluster 2 is smaller, containing ~50-200 neurons. Cluster 2 neurons, analogous to

LHNs, project strongly to valence read-out neurons (Figure 6c, d), and typically only receive a

single strong PN input (Figure 6e, f). Thus, the inputs to the KCs are unstructured whereas the

connections to LHN encoding innate valence are valence-specific (Figure 6f).

We lesioned each cluster of KC/LHN neurons separately to assess its contribution to odor and

valence classification. Lesioning the putative KC cluster (group 1) led to a dramatic impairment

in odor classification performance (Figure 6g) but left the determination of valence intact (Figure

6h). In contrast, lesioning the putative LH cluster (group 2) substantially impaired valence

determination (Figure 6h) but had little effect on classification performance (Figure 6g). These

results demonstrate that the model network can evolve two segregated pathways analogous to

those in the fly.

Fig. 6 | Emergence of separate innate and learned pathways.

a. Illustration of the class (left) and valence (right) tasks. Non-neutral odors (right, appetitive in

blue or aversive in red) each strongly activates one non-neutral OR. The network is trained to

identify odor class (left) as previously described (Figure 1b) and also to classify odors into 3

valences (right). **b**, Schematic of a neural network that is trained to identify both odor class and

odor valence using separate class and valence read-out weights. **c.** Distribution of third-layer

neurons based on output connection strengths to valence read-out neurons against connection

strengths to class read-outs. K-means clustering revealed that the third layer can be segregated

into two clusters. The density of each cluster is normalized to the same peak value. **d**, The

connectivity matrix from the first 10 third-layer neurons from each cluster to output units, the first

10 from identity output and all 3 from valence output. **e,** Distribution of third-layer neurons based

on output connection strengths to valence read-out neurons against input degrees. The

distribution of cluster 2 neurons is difficult to see because almost all of them have the same

input degree value of 1. **f**, The connectivity matrix from PNs to first 10 third-layer neurons from

each cluster. **g, h.** Lesioning the KC-like cluster (group 1) leads to a dramatic drop in odor class

performance. (**g**) Lesioning the LH-like cluster (group 2) substantially impaired odor valence

performance (**h**).

Discussion

Network models constructed from machine learning approaches have been used to study the

responses of neural circuits and their relationship to circuit function by comparing the activities

of network units and recorded neurons (Mante et al., 2013; Masse, Yang, Song, Wang, &

Freedman, 2019; Yamins & DiCarlo, 2016; Yamins et al., 2014; Yang, Joglekar, Song,

Newsome, & Wang, 2019). Machine-learning models generate unit responses and perform the

tasks they are trained to do by developing specific patterns of connectivity. It is difficult to

perform a detailed comparison of these connectivity patterns with biological connectomes

(Cueva, Wang, Chin, & Wei, 2019; Uria et al., 2020) given the limited connectomic data. The

current availability of connectome data from flies (Li et al., 2020; Zheng et al., 2018) and the

promise of more connectome results in the future make this an opportune time to explore links

between biological connectomes and machine learning architectures.

We found that important features of synaptic connectivity shared by the fly and mouse olfactory

systems also evolved in artificial neural networks trained to perform olfactory tasks. The

observation that machine learning evolves an olfactory system with striking parallels to

biological olfactory pathways implies a functional logic to the successful accomplishment of

olfactory tasks. Importantly, the artificial network evolves without the biological mechanisms

necessary to build these systems *in vivo*. This implies that convergent evolution reflects an

underlying logic rather than shared developmental principles. Stochastic gradient descent and

mutation and natural selection have evolved a similar solution to olfactory processing.

We constructed feedforward and recurrent networks using stochastic gradient descent. When

the feedforward networks were initialized with each ORN expressing all 50 receptors, each ORN

evolved to express a single receptor type, recapitulating the expression pattern of ORs in flies

and mice. Further, ORNs expressing a given receptor converge on a single PN and PNs

connect with like ORNs to create a glomerular structure. This convergence, observed in both

flies and mice, assures that mixing of information across ORs does not occur at early

processing layers.

In the network models we studied, each KC initially received input from all 50 PNs but these

connections become sparse during training, with each KC ultimately receiving information from

~4-10 PNs, in agreement with the fly circuitry. Although most of our machine modeling was

based on the olfactory system in flies, we extrapolated our networks to olfactory systems of far

greater size. The results of this extrapolation depended on the task and training procedure. For

fixed odor classes, the original task we considered, we obtained an estimate of the number of

inputs to piriform neurons from the olfactory bulb, in rough agreement with data from the mouse

(40-100).

The architecture of olfactory systems, *in vivo* and *in silica*, is based upon two essential features:

converge of a large number of ORNs onto a small number of glomeruli followed by an

expansion onto much larger number of third order neurons. Previous theoretical work suggests

that a goal of the olfactory system may be to construct a high-dimensional representation in the

expansion layer (KCs in the mushroom body or pyramidal cells in the piriform cortex) to support

inference about the behavioral relevance of odors (Babadi & Sompolinsky, 2014; Litwin-

Kumar,et al., 2017). This hypothesis has two important implications for our results.

One results of this previous work is that task performance is proportional to dimensionality when

odor classes are learned through synaptic plasticity of a Hebbian form (Litwin-Kumar et al.,

2017). In the learning task that we considered, new odor classes were learned through synaptic

plasticity that fits into the Hebbian category, so the resulting network should maximize the

dimension of the expansion layer odor representation to optimize performance. Indeed, we

found that the sparsity of the connections in the resulting networks has a power-law

dependence on the number of olfactory receptor types that roughly agrees with the scaling that

follows from maximizing dimensionality. However, we obtained a quite different scaling when

we trained non-plastic networks on the fixed-class task. Because these networks do not involve

Hebbian plasticity, it is not surprising that they exhibit a different degree of sparsity, but we do

not currently know of an underlying theoretical principle that can explain the sparsity and scaling

we found in the non-plastic case. Interestingly, it is this case that agrees with existing data on

the connectivity in the mouse (Davison & Ehlers, 2011; Miyamichi et al., 2011).

Another requirement for achieving maximimum dimensionality is that the representation of odors

by the PNs should be uncorrelated (Litwin-Kumar et al., 2017). This provides an explanation for

the formation of glomeruli in our network models. The OR activations we used were

uncorrelated and, to maximize dimensionality, the transformation from ORs to ORNs and then

to PNs must not introduce any correlation. When the weights along this pathway are

constrained to be non-negative, the only connectivity pattern that does not induce PN-PN

correlations is an identity mapping from OR types to PN output. This is precisely what singular

OR expression and OR-specific projection through olfactory glomeruli provides. Interestingly,

the results we found suggest that these ubiquitous features of biological olfactory pathways are

not simply a consequence of noise robustness, as has been conjectured, but rather arise as the

unique solution to eliminating correlations in the glomerular layer to maximize the dimension of

the expansion layer.

References

Aso, Y., Hattori, D., Yu, Y., Johnston, R. M., Iyer, N. A., Ngo, T.-T., … Rubin, G. M. (2014a).

The neuronal architecture of the mushroom body provides a logic for associative learning.

ELife, *3*. https://doi.org/10.7554/eLife.04577

Aso, Y., Hattori, D., Yu, Y., Johnston, R. M., Iyer, N. A., Ngo, T. T. B., … Rubin, G. M. (2014b).

The neuronal architecture of the mushroom body provides a logic for associative learning.

ELife. https://doi.org/10.7554/eLife.04577

Babadi, B., & Sompolinsky, H. (2014). Sparseness and Expansion in Sensory Representations.

Neuron, *83*(5), 1213–1226. https://doi.org/10.1016/j.neuron.2014.07.035

Cario, M. C., & Nelson, B. L. (1997). Modeling and generating random vectors with arbitrary

marginal distributions and correlation matrix. *Industrial Engineering*.

Caron, S. J. C., Ruta, V., Abbott, L. F., & Axel, R. (2013). Random convergence of olfactory

inputs in the Drosophila mushroom body. *Nature*. https://doi.org/10.1038/nature12063

Chia, J., & Scott, K. (2019). Activation of specific mushroom body output neurons inhibits

proboscis extension and feeding behavior. *BioRxiv*. https://doi.org/10.1101/768960

Cohn, R., Morantte, I., & Ruta, V. (2015). Coordinated and Compartmentalized

Neuromodulation Shapes Sensory Processing in Drosophila. *Cell*, *163*(7), 1742–1755.

https://doi.org/10.1016/j.cell.2015.11.019

Cueva, C. J., Wang, P. Y., Chin, M., & Wei, X. X. (2019). Emergence of functional and structural

properties of the head direction system by optimization of recurrent neural networks. *ArXiv*.

Datta, S. R., Vasconcelos, M. L., Ruta, V., Luo, S., Wong, A., Demir, E., … Axel, R. (2008). The

Drosophila pheromone cVA activates a sexually dimorphic neural circuit. *Nature*,

452(7186), 473–477. https://doi.org/10.1038/nature06808

Davison, I. G., & Ehlers, M. D. (2011). Neural circuit mechanisms for pattern detection and

feature combination in olfactory cortex. *Neuron*, *70*(1), 82–94.

De Belle, J. S., & Heisenberg, M. (1994). Associative odor learning in Drosophila abolished by

chemical ablation of mushroom bodies. *Science*. https://doi.org/10.1126/science.8303280

Dubnau, J., Grady, L., Kitamoto, T., & Tully, T. (2001). Disruption of neurotransmission in

Drosophila mushroom body blocks retrieval but not acquisition of memory. *Nature*.

https://doi.org/10.1038/35078077

Dweck, H. K. M., Ebrahim, S. A. M., Thoma, M., Mohamed, A. A. M., Keesey, I. W., Trona,

F., … Hansson, B. S. (2015). Pheromones mediating copulation and attraction in

Drosophila. *Proceedings of the National Academy of Sciences of the United States of*

America. https://doi.org/10.1073/pnas.1504527112

Ebrahim, S. A. M., Dweck, H. K. M., Stökl, J., Hofferberth, J. E., Trona, F., Weniger, K., …

Knaden, M. (2015). Drosophila Avoids Parasitoids by Sensing Their Semiochemicals via a

Dedicated Olfactory Circuit. *PLoS Biology*. https://doi.org/10.1371/journal.pbio.1002318

Felsenberg, J., Jacob, P. F., Walker, T., Barnstedt, O., Edmondson-Stait, A. J., Pleijzier, M.

W., … Waddell, S. (2018). Integration of Parallel Opposing Memories Underlies Memory

Extinction. *Cell*. https://doi.org/10.1016/j.cell.2018.08.021

Finn, C., Abbeel, P., & Levine, S. (2017). *Model-Agnostic Meta-Learning for Fast Adaptation of*

Deep Networks.

Gruntman, E., & Turner, G. C. (2013). Integration of the olfactory code across dendritic claws of

single mushroom body neurons. *Nature Neuroscience*, *16*(12), 1821–1829.

https://doi.org/10.1038/nn.3547

Handler, A., Graham, T. G. W., Cohn, R., Morantte, I., Siliciano, A. F., Zeng, J., … Ruta, V.

(2019). Distinct Dopamine Receptor Pathways Underlie the Temporal Sensitivity of

Associative Learning. *Cell*. https://doi.org/10.1016/j.cell.2019.05.040

Hattori, D., Aso, Y., Swartz, K. J., Rubin, G. M., Abbott, L. F., & Axel, R. (2017).

Representations of Novelty and Familiarity in a Mushroom Body Compartment. *Cell*.

https://doi.org/10.1016/j.cell.2017.04.028

Heisenberg, M., Borst, A., Wagner, S., & Byers, D. (1985). drosophila mushroom body mutants

are deficient in olfactory learning: Research papers. *Journal of Neurogenetics*.

https://doi.org/10.3109/01677068509100140

Hige, T., Aso, Y., Rubin, G. M., & Turner, G. C. (2015). Plasticity-driven individualization of

olfactory coding in mushroom body output neurons. *Nature*, *526*(7572), 258–262.

https://doi.org/10.1038/nature15396

Ioffe, S., & Szegedy, C. (2015). Batch normalization: Accelerating deep network training by

reducing internal covariate shift. *32nd International Conference on Machine Learning,*

ICML 2015.

Jefferis, G. S. X. E., Potter, C. J., Chan, A. M., Marin, E. C., Rohlfing, T., Maurer, C. R., & Luo,

L. (2007). Comprehensive Maps of Drosophila Higher Olfactory Centers: Spatially

Segregated Fruit and Pheromone Representation. *Cell*.

https://doi.org/10.1016/j.cell.2007.01.040

Kazama, H., & Wilson, R. I. (2009). Origins of correlated activity in an olfactory circuit. *Nature*

Neuroscience, *12*(9), 1136–1144. https://doi.org/10.1038/nn.2376

Kingma, D. P., & Ba, J. (2014). *Adam: A Method for Stochastic Optimization*. Retrieved from

http://arxiv.org/abs/1412.6980

Kurtovic, A., Widmer, A., & Dickson, B. J. (2007). A single class of olfactory neurons mediates

behavioural responses to a Drosophila sex pheromone. *Nature*.

https://doi.org/10.1038/nature05672

Lecun, Y., Bengio, Y., & Hinton, G. (2015). Deep learning. *Nature*.

https://doi.org/10.1038/nature14539

Li, F., Lindsey, J., Marin, E. C., Otto, N., Dreher, M., Dempsey, G., … Rubin, G. M. (2020). The

connectome of the adult drosophila mushroom body provides insights into function. *ELife*.

https://doi.org/10.7554/eLife.62576

Lin, A. C., Bygrave, A. M., De Calignon, A., Lee, T., & Miesenböck, G. (2014). Sparse,

decorrelated odor coding in the mushroom body enhances learned odor discrimination.

Nature Neuroscience, *17*(4), 559–568. https://doi.org/10.1038/nn.3660

Litwin-Kumar, A., Harris, K. D., Axel, R., Sompolinsky, H., & Abbott, L. F. (2017). Optimal
Degrees of Synaptic Connectivity. *Neuron*, *93*(5), 1153-1164.e7.
https://doi.org/10.1016/j.neuron.2017.01.030

Luo, S. X., Axel, R., & Abbott, L. F. (2010). Generating sparse and selective third-order
responses in the olfactory system of the fly. *Proceedings of the National Academy of
Sciences*, *107*(23), 10713–10718. https://doi.org/10.1073/pnas.1005635107

Mante, V., Sussillo, D., Shenoy, K. V., & Newsome, W. T. (2013). Context-dependent
computation by recurrent dynamics in prefrontal cortex. *Nature*.
https://doi.org/10.1038/nature12742

Marin, E. C., Jefferis, G. S. X. E., Komiyama, T., Zhu, H., & Luo, L. (2002). Representation of
the glomerular olfactory map in the Drosophila brain. *Cell*. https://doi.org/10.1016/S0092-
8674(02)00700-6

Marr, D. (1969). A theory of cerebellar cortex. *The Journal of Physiology*, *202*(2), 437–470.
Retrieved from http://www.ncbi.nlm.nih.gov/pubmed/5784296

Masse, N. Y., Yang, G. R., Song, H. F., Wang, X. J., & Freedman, D. J. (2019). Circuit
mechanisms for the maintenance and manipulation of information in working memory.
Nature Neuroscience. https://doi.org/10.1038/s41593-019-0414-3

Masuda-Nakagawa, L. M., Tanaka, N. K., & O'Kane, C. J. (2005). Stereotypic and random
patterns of connectivity in the larval mushroom body calyx of Drosophila. *Proceedings of
the National Academy of Sciences of the United States of America*.
https://doi.org/10.1073/pnas.0509643102

McGuire, S. E., Le, P. T., & Davis, R. L. (2001). The role of Drosophila mushroom body
signaling in olfactory memory. *Science*. https://doi.org/10.1126/science.1062622

Min, S., Ai, M., Shin, S. A., & Suh, G. S. B. (2013). Dedicated olfactory neurons mediating
attraction behavior to ammonia and amines in Drosophila. *Proceedings of the National*

Academy of Sciences of the United States of America.

https://doi.org/10.1073/pnas.1215680110

Miyamichi, K., Amat, F., Moussavi, F., Wang, C., Wickersham, I., Wall, N. R., … Luo, L. (2011).

Cortical representations of olfactory input by trans-synaptic tracing. *Nature*, *472*(7342),

191–196. https://doi.org/10.1038/nature09714

Mombaerts, P., Wang, F., Dulac, C., Chao, S. K., Nemes, A., Mendelsohn, M., … Axel, R.

(1996). Visualizing an Olfactory Sensory Map. *Cell*, *87*(4), 675–686.

https://doi.org/10.1016/S0092-8674(00)81387-2

Olsen, S. R., Bhandawat, V., & Wilson, R. I. (2010). Divisive normalization in olfactory

population codes. *Neuron*, *66*(2), 287–299. https://doi.org/10.1016/j.neuron.2010.04.009

Reardon, T. R., Murray, A. J., Turi, G. F., Wirblich, C., Croce, K. R., Schnell, M. J., … Losonczy,

A. (2016). Rabies Virus CVS-N2cδG Strain Enhances Retrograde Synaptic Transfer and

Neuronal Viability. *Neuron*. https://doi.org/10.1016/j.neuron.2016.01.004

Rumelhart, D. E., Hinton, G. E., & Williams, R. J. (1986). Learning representations by back-

propagating errors. *Nature*, *323*(6088), 533–536. https://doi.org/10.1038/323533a0

Ruta, V., Datta, S. R., Vasconcelos, M. L., Freeland, J., Looger, L. L., & Axel, R. (2010). A

dimorphic pheromone circuit in Drosophila from sensory input to descending output.

Nature. https://doi.org/10.1038/nature09554

Stensmyr, M. C., Dweck, H. K. M., Farhan, A., Ibba, I., Strutz, A., Mukunda, L., … Hansson, B.

S. (2012). A conserved dedicated olfactory circuit for detecting harmful microbes in

drosophila. *Cell*. https://doi.org/10.1016/j.cell.2012.09.046

Suh, G. S. B., Wong, A. M., Hergarden, A. C., Wang, J. W., Simon, A. F., Benzer, S., …

Anderson, D. J. (2004). A single population of olfactory sensory neurons mediates an

innate avoidance behaviour in Drosophila. *Nature*. https://doi.org/10.1038/nature02980

Tanaka, N. K., Awasaki, T., Shimada, T., & Ito, K. (2004). Integration of chemosensory

pathways in the Drosophila second-order olfactory centers. *Current Biology*.

https://doi.org/10.1016/j.cub.2004.03.006

Tanaka, N. K., Tanimoto, H., & Ito, K. (2008). Neuronal assemblies of the Drosophila mushroom

body. *Journal of Comparative Neurology*. https://doi.org/10.1002/cne.21692

Uria, B., Ibarz, B., Banino, A., Zambaldi, V., Kumaran, D., Hassabis, D., … Blundell, C. (2020).

The spatial memory pipeline: A model of egocentric to allocentric understanding in

mammalian brains. *BioRxiv*. https://doi.org/10.1101/2020.11.11.378141

Varela, N., Gaspar, M., Dias, S., & Vasconcelos, M. L. (2019). Avoidance response to CO 2 in

the lateral horn. *PLoS Biology*. https://doi.org/10.1371/journal.pbio.2006749

Vosshall, L. B., Amrein, H., Morozov, P. S., Rzhetsky, A., & Axel, R. (1999). A spatial map of

olfactory receptor expression in the Drosophila antenna. *Cell*.

https://doi.org/10.1016/S0092-8674(00)80582-6

Vosshall, L. B., Wong, A. M., & Axel, R. (2000a). An olfactory sensory map in the fly brain. *Cell*.

https://doi.org/10.1016/S0092-8674(00)00021-0

Vosshall, L. B., Wong, A. M., & Axel, R. (2000b). An Olfactory Sensory Map in the Fly Brain.

Cell, *102*(2), 147–159. https://doi.org/10.1016/S0092-8674(00)00021-0

Wilson, R. I. (2013). Early Olfactory Processing in Drosophila : Mechanisms and Principles .

Annual Review of Neuroscience. https://doi.org/10.1146/annurev-neuro-062111-150533

Wong, A. M., Wang, J. W., & Axel, R. (2002). Spatial representation of the glomerular map in

the Drosophila protocerebrum. *Cell*. https://doi.org/10.1016/S0092-8674(02)00707-9

Yamins, D. L. K., & DiCarlo, J. J. (2016). Using goal-driven deep learning models to understand

sensory cortex. *Nature Neuroscience*. https://doi.org/10.1038/nn.4244

Yamins, D. L. K., Hong, H., Cadieu, C. F., Solomon, E. A., Seibert, D., & DiCarlo, J. J. (2014).

Performance-optimized hierarchical models predict neural responses in higher visual

cortex. *Proceedings of the National Academy of Sciences of the United States of America*.

https://doi.org/10.1073/pnas.1403112111

Yang, G. R., Joglekar, M. R., Song, H. F., Newsome, W. T., & Wang, X. J. (2019). Task

representations in neural networks trained to perform many cognitive tasks. *Nature*

Neuroscience. https://doi.org/10.1038/s41593-018-0310-2

Zheng, Z., Lauritzen, J. S., Perlman, E., Robinson, C. G., Nichols, M., Milkie, D., … Bock, D. D.

(2018). A Complete Electron Microscopy Volume of the Brain of Adult Drosophila

melanogaster. *Cell*. https://doi.org/10.1016/j.cell.2018.06.019

Author contributions

Author contributions

This work is the result of a close collaboration between P.Y.W. and G.R.Y. P.Y.W. and G.R.Y.

performed the research. G.R.Y., P.Y.W., and Y.S. performed the analysis of the dependence of

K on N (Figure 5). P.Y.W, R.A., L.F.A. and G.R.Y. designed the study and wrote the manuscript.

Acknowledgements

We thank current and former members of the Axel and Abbott labs, and many colleagues at the

Center for Theoretical Neuroscience at Columbia for fruitful discussions. We particularly thank

Ashok Litwin-Kumar for discussions and for his guidance. We thank Li Ji-An and Sun Minni for

discussions that led to improved training of weight-constrained networks. We thank Jochen

Weber, Alexander Antoniades, and John Pellman for building and maintaining the Columbia

Axon GPU cluster. This work was supported by the Columbia Neurobiology and Behavior

Program (P.Y.W.), Simons Foundation (L.F.A, R.A.), a Simons Foundation junior fellowship

(G.R.Y.), NSF NeuroNex Award DBI-1707398 and the Gatsby Charitable Foundation (L.F.A,

G.R.Y.,P.Y.W.), and the Howard Hughes Medical Institute (R.A.). R.A. is an HHMI investigator.

Declaration of interest

The authors declare no competing interests.

Code availability

Upon acceptance, all code and pretrained networks to reproduce our results will be available on

Github at https://github.com/gyyang/olfaction_evolution. Besides code to reproduce every single

panel in the paper, we also make available a self-contained Jupyter notebook that reproduces

key results and allows easier exploration.

METHODS

Datasets

To generate the standard dataset, we first generated $N_{proto} = 200$ odor prototypes. Each

prototype $\tilde{x}^{(i)}$ activates $N_{OR} = 50$ ORN types or ORs, and the activation of each ORN type is

sampled independently from a uniform distribution between 0 and 1, $\tilde{x}_j^{(i)} \sim U(0, 1)$. The 200

prototypes are randomly assigned to N_{class} = 100 behavioral classes, each class containing two

prototypes. A given odor $\tilde{x}$ is a vector in the 50-dimensional ORN-type space, sampled the

same way as the prototypes. When the network's input layer corresponds to ORNs, each ORN

receives the activation of its OR plus an independent Gaussian noise $\epsilon \sim N(0, \sigma_{ORN}^2)$, where

$\sigma_{ORN} = 0$ by default (no noise). Its associated ground-truth class c is set to be the class of its

closest prototype, as measured by Euclidean distance in the ORN-type space. The training set

consists of 1 million odors. The validation set consists of 8192 odors.

Besides the standard dataset, we also considered several other datasets based on the standard

dataset, as detailed below.

Concentration dataset. In this dataset (Figure 2), the prototypes $\tilde{x}_{con}^{(i)}$ are the normalized

version of the prototypes in the standard dataset $\tilde{x}^{(i)}$, so $\tilde{x}_{con}^{(i)} = \frac{\tilde{x}^{(i)}}{|\tilde{x}^{(i)}|}$. The concentration of each

odor is explicitly varied while the average ORN activation across all odors is preserved. For

each odor, the activation of each ORN type is sampled from a uniform distribution as described

above, and is then multiplied by a concentration scale factor. This scale factor, s, is determined

by a single parameter, ϵ, in which:

753
$$s = (1 - \epsilon) + 2\,\epsilon\, \text{Beta}(1 - \epsilon, 1 - \epsilon)$$

A value of ϵ = 0 produces a dataset with no additional spread, whereas ϵ = 1 produces a

dataset exhibiting maximal spread with scale factors densely clustered around 0 and 2.

Relabel datasets. For the family of relabel datasets (Figure S2), we vary the number of

prototypes N_{proto}=100, 200, 500, 1000 while keeping the number of classes N_{class}= 100 fixed.

We refer to these datasets as relabel datasets, because N_{proto} prototypes are relabeled to N_{class}

classes. The standard dataset uses relabeling as well. The ratio between N_{proto} and N_{class} is the

odor prototypes per class.

Meta-learning dataset. This dataset is organized into episodes. Each episode includes a small

amount of training data and validation data. In each episode, we randomly select $N_{eps,class} = 2$

classes from the original $N_{class} = 100$ classes in the standard dataset. For each of the $N_{eps,class}$

classes chosen, we randomly select $N_{eps,sample} = 16$ odors for training and validation

respectively. Importantly, within each episode, we re-map each of the $N_{eps,class} = 2$ selected

classes to $N_{meta} = 2$ output classes. Intuitively, the network is always doing a ($N_{meta} =$) 2-way

classification task. However, the classification boundaries associated with each output class is

different in every episode. There is no fixed relationship between the original class label and the

new label in each episode, so the network has to learn the new class labels based on the

$N_{eps,sample}$ data points per class. In total, for each episode, there are $N_{eps,sample}N_{eps,class}$ data

points in the training set, and the same amount in the validation set.

Valence dataset. In the valence dataset, we replaced $N_{special} = 10$ prototypes from the original

N_{proto} prototypes with special prototypes that each lies along one axis in the ORN-type space.

In other words, each special prototype activates strongly a single ORN type (a special OR), at

activity level 1.0. Of the N_{special} special prototypes, $N_{\text{special}}/2 = 5$ are set to be appetitive or

"good" odors, and the other 5 to be aversive or "bad" odors. The rest of the $N_{\text{proto}} - N_{\text{special}}$

prototypes and associated odors are set to be neutral and are sampled the same way as the

standard dataset. The task is both to classify the odors, as in the standard dataset, and to

classify the valence (appetitive, aversive, neutral). In both the training and the validation

dataset, we have 10% of the overall odors be appetitive, another 10% be aversive, and the rest

80% be neutral. Therefore, if a network classifies all odors to neutral, the chance level

performance for valence classification is 80%. The neutral odors are sampled in the same way

as the standard dataset. Each appetitive or aversive odor is sampled by adding the activity level

of one special prototype (1.0 for the special OR and 0.0 otherwise) with an activity pattern

sampled from a uniform distribution between 0 and 1. In other words, the activity level of an

appetitive or aversive odor is sampled randomly from $U(1, 2)$ for the special OR, and from

$U(0,1)$ for other ORs.

Correlated dataset. In Figure S4, we introduce correlation between responses of different ORN

types. The correlation is independently controlled between 0 and 0.9, while maintaining the

marginal distribution of each ORN type to be uniform between 0 and 1. We used a previously

proposed method (Cario & Nelson, 1997) for generating such correlated random variables while

maintaining their marginal distributions.

Network architecture

We train networks of various architectures. The **ORN-PN-KC network architecture** consists of

an input layer of 500 model ORNs, 50 PNs, 2500 KCs, and 100 output units. The 500 ORNs are

made of 10 ORNs per type for all 50 types of ORNs. The activation of each ORN is the sum of

the activation of the corresponding ORN-type $\tilde{x}_j$ and an independent noise $\epsilon \sim N(0, \sigma_{\text{ORN}}^2)$, where

$\sigma_{\text{ORN}} = 0$ by default (no noise). The ORN-PN, PN-KC, and KC-output connections are all fully-

connected at initialization. The ORN-PN and PN-KC connectivity are initialized with a uniform

distribution of between $1/N$ and $4/N$, where N is the number of input neurons (500 for ORN-PN,

and 50 for PN-KC). The KC-output connectivity is initialized with the standard Glorot uniform

initialization. The ORN-PN and PN-KC connections are constrained to be non-negative using an

absolute function. All neurons use a rectified-linear activation function (ReLU).

In the **OR-ORN-PN-KC network**, we add an additional layer of OR-ORN connections. Here, the

inputs are 50 ORs, activated similarly to the ORNs from the ORN-PN-KC network. The OR-

ORN connections are non-negative as well and initialized similarly to ORN-PN and PN-KC

connectivity.

For the **identity/valence classification** task, we used a network with two output heads. One

containing 100 output neurons as usual. The other contains 3 output neurons for neutral,

appetitive, and aversive valence.

We briefly considered an **ORN-Output network** (Figure S2) that has the output directly read out

from the ORNs.

Optionally, we include **dropout** on the KC layer, which at training time, but not testing time, set

a certain proportion p_{dropout} of neurons to zero. The default dropout rate is $p_{\text{dropout}} = 0$ (no

dropout).

The **recurrent network** used in Figure 3 is a discrete-time vanilla recurrent network,

828
$$\boldsymbol{r}_{t+1} = f(W_r \boldsymbol{r}_t + W_u \boldsymbol{u}_t + \boldsymbol{b}), \quad t = 1, 2, \dots$$

The network consists of 2,500 units. The recurrent connection is initialized uniformly between 0

and $4./2500$, the input connection is initialized using Glorot uniform initialization. The recurrent

connection is constrained to be non-negative. Out of 2,500 units, 500 receive odor inputs at $t =$

1 in the same way as the ORNs in the feedforward network. The classification output is read-out

with at step T with connections that are not sign-constrained. By default, we have $T = 3$, which

means the network unrolled in time would have 3 layers ($t = 1, 2, 3$) and an output layer.

The **KC recurrent inhibition** mediated by a single APL neuron (Figure 1) is implemented by an

inhibitory neuron interacting with the KCs iteratively. The single inhibitory neuron has a neural

response equal to the mean KC activation level at each time step. This neuron then sends

subtractive inhibitory inputs to all KCs with a connection weight γ (KC recurrent inhibition

strength in Figure 1). Therefore, the KCs at each time step t are activated as

841
$$r_i(t) = f\left(u_i(t) - \gamma \cdot \frac{1}{N_{KC}} \sum_j r_j(t-1) \right).$$

842   Here $f(\cdot)$ is the ReLU activation function. $u_i(t) = u_i$ is the feedforward input to the i-th unit. $r_i(t)$

843   is the activation level of the i-th unit at time step t. We run this recurrent inhibition for 10 time

844   steps.

846   The **divisive normalization** used on the PN layer in Figure 2 is implemented in the following

847   way. Neuron i in this layer receives input u_i, and the final activation of this neuron, r_i follows,

848
$$r_i = r_{max} \cdot \frac{u_i}{u_i + \rho + m \sum_j r_j}$$

Here, r_{max}, ρ, m are parameters that are trained with gradient descent alongside other trainable

parameters. In initialization, we have $r_{max} = N/2, \rho = 0, m = 0.99$, where N is the number of

neurons in this layer. For stability during training, we clamped $N/10 \leq r_{max} \leq N$, $0 \leq \rho \leq 3$,

$0.05 \leq m \leq 2$.

Training

The output of the network is linearly read out with trainable weights from the final layer (KC layer

in feedforward networks, or the recurrent layer). The loss is softmax cross-entropy loss. The

default training method is the adaptive stochastic gradient descent method Adam with learning

rate 5e-4, and exponential decay rates for first and second moments 0.9 and 0.999 respectively

(the Pytorch default hyperparameter values). The training batch size is 256. By default, we used

batch-normalization on the PN layer to prevent individual neurons from being active or silent for

all odors. The network is typically trained for 100 epochs, each epoch would expose the network

to all of the one million odors from the training set.

Ongoing Plasticity

For the ongoing plasticity results in Figure 4, we use the delta rule to simulate ongoing plasticity

in the readout connections (KC-output weights for the model fly network) [Cite Dayan & Abbott

book]. The delta rule is more biologically plausible than the general gradient descent algorithm

because it relies on local information. However, it is not intended to model with high fidelity the

biological plasticity rules at the KC-MBON synapses. The delta rule is used here to encourage a

KC representation that supports rapid, flexible learning. The default delta rule learning rate is

5e-4.

During each learning episode (see Meta-learning dataset section), the network is presented with

a small amount of training and validation data from the meta-learning dataset. The network

takes a single delta rule step based on the training data, and the loss is evaluated based on the

validation data. The objective of meta-training is to minimize the expected validation loss of the

inner training. Meta-training updates all weights and biases in the network at the end of each

learning episode using the gradient descent variant, Adam. This meta-training method is a

special case of a more general method called MAML, or Model-Agnostic Meta-Learning (Finn,

Abbeel, & Levine, 2017a). This method aims at finding (meta-training) parameter values

(connection weights and biases) that allow rapid few-step gradient descent learning using a

small amount of new training data. We largely adhered to the method detailed in Finn et al., with

a few notable exceptions. First, the inner training only performs gradient descent on the KC-

output connection. Gradient descent applied only to the last layer reduces to the delta rule.

Second, the learning rate of the inner training is allowed to be adjusted by the meta-training

process. The latter assumption does not substantially impact our results.
887

GloScore

The glomeruli score (GloScore) of a PN-ORN connectivity matrix $W_{\text{PN}\rightarrow\text{ORN}}$ is computed by first

averaging all connections from ORNs of the same type. For each PN, we find the strongest

connection weight w_1 and the second strongest connection weight w_2 from the averaged ORNs.

For non-sign-constrained weights, we use the absolute values of weights. Then GloScore for

each unit is computed as,

$$\text{GloScore} = (w_1 - w_2)/(w_1 + w_2).$$

Final GloScore of the entire connection matrix is the average GloScore of all PNs.

Weight pruning and connection sparsity estimation

By default, we have synaptic weight pruning during training. Weights below a certain threshold θ

are permanently set to zero during and after training. The threshold is set to be $\theta = 1/N$, where

N is the number of input neurons for each connectivity matrix. Weight pruning provides a less

ambiguous quantitative estimate of connection sparsity.

We observe that in some networks, the distribution of weights has a clear, single peak away

from the pruning threshold, and the weight distribution approaches 0 towards the threshold (see

Figure S1c for examples). In these cases, the connection sparsity (or density) can be easily

inferred by simply quantifying the proportion of connection weights above threshold. However,

we found that in some networks (some hyperparameter settings), the distribution of weights has

a peak very close to the threshold, making it difficult to count the above-threshold weights.

Therefore, we employ a simple heuristic to check if there is a clear peak in the weight

distribution far from the pruning threshold. Our heuristic requires the peak of the above-

threshold weight distribution be at least $2./N$ larger than the threshold itself, which by default is

at $1./N$. Networks that do not satisfy this "clear peak" criteria are not used to compute the input

degree, and their K values not shown in plots (e.g. Figure S1a).

When the network does not undergo pruning of weak weights as in some control experiments

and for the RNN results, it is necessary to try inferring a threshold separating weak and strong

weights. We fit a mixture of two Gaussians model to the log-distribution of weights. The

weak/strong weight threshold is where the probability density of the two Gaussian modes cross.

In this case, the inferred threshold is used, instead of the pruning threshold, in the above

heuristics for determining whether the strong weights have a clear peak in its distribution.

We have done extensive comparisons between networks with and without pruning across

various hyperparameter values (many results not shown in figures). For the feedforward

network architectures, pruning almost always leads to clearer above-threshold peak in the

weight distribution. Importantly, the sparsity result is not a result of pruning per se. When there

is no pruning, and the weights clearly separate into weak and strong peaks (for example when

$N_{\text{proto}} = N_{\text{class}} = 100$), the inferred connection sparsity is quantitatively very close to that

obtained from networks with pruning. In addition, the network performance is generally identical

with or without pruning.

Inferring connection sparsity from experimental data in mouse

Two previous publications used different approaches to estimate the input degree, K, in mice.

The first experiment (Miyamichi et al., 2011) used retrograde anatomic tracing to derive a

convergence index of number of mitral/tufted cells (equivalent of PNs) over the number of

piriform neurons (equivalent of KCs), and found values ranging from 3-20. The transfection

efficiency of retrograde labeling was estimated to be roughly 10% (Reardon et al., 2016), so the

input degree may vary from 30-200 M/T inputs per piriform neuron. The second experiment

(Davison & Ehlers, 2011) used optical glutamate uncaging to activate defined points on the

olfactory bulb while recording piriform responses, and found that most cells responded to >15

uncaging sites. The authors estimate that 2-3 glomeruli are activated per uncaging site,

providing a lower bound of K=40 for input degree.

Randomness

To determine whether the frequency of PN input onto KCs is significantly above or below

chance expectations, PN-KC connections in the trained network were shuffled while maintaining

the number of connections each KC receives and the identity of PN inputs. We generated the

shuffled data by making a list of PNs that contributed to each PN-KC connection. We then

randomly permuted this list and drew from it sequentially to construct a new set of connections

for each of the 2500 KCs, drawing as many random connections for each KC as it receives in

the trained network. This shuffling eliminates any potential, non-random PN inputs onto

individual KCs, and is used to analyze whether KCs are connected to any preferential pair of

glomeruli (Figure S3).

To determine whether the distribution of PN inputs onto KCs is binomial, the probability of a

connection between each PN with each KC is sampled independently from a Bernoulli

distribution with the overall PN-KC connection probability, p, of a trained network.

Analysis of RNNs

In Figure 3, we analyzed a recurrent neural network, which unlike traditional recurrent networks,

is not running in time. Instead we use it as a way to force a limited budget on the total number of

neurons, without specifying the exact number of neurons to be used at each processing step.

The key analysis is to infer how many neurons are assigned by the network to each processing

step (the same neuron may be used at multiple steps). For each neuron, we computed its

average activity at each processing step in response to all odors shown the network. If its

average activity at a processing step exceeds a certain threshold, we deem this neuron active at

this step. Note that by this definition, an "active neuron" may not be active for each odor. All we

ask is that it is sufficiently active for some odors. We used the same threshold of 0.2 across all

processing steps, manually chosen after inspecting the distribution of activity (Figure S7). We

did not use a threshold of 0 because many neurons are activated very weakly but above zero on

average. With positive connection weights used in our networks, it is generally more difficult to

have a neuron be activated at 0 across all odors at a given processing step.

Analyzing networks of different numbers of OR types

For Figure 5, we trained networks with different numbers of OR types (N), ranging from 25 to

200. For simplicity, we focused on the connections from the compression to the expansion

layer, while ignoring the connections from ORNs to the compression layer. Therefore, all

networks consist of N input neurons representing ORN activity, which in turn project to M

expansion layer neurons. For each value of N, the number of expansion layer numbers M is set

as N^2. For each number of OR, we trained networks with different levels of learning rate 1e-3,

5e-4, 2e-4, 1e-4. We include in our summary plot (Figure 5) only networks that contain a clear

peak in the weight distribution, using the criteria established above.

To obtain the maximum dimensionality curve in Figure 5, for each number of OR, we first

computed the representation dimensionality (Litwin-Kumar et al. 2017) in response to the

training odors when the third-layer input degree is fixed at different values. Then we identified

the input degree corresponding to the maximum dimensionality. Finally, we repeat this process

for networks with different numbers of ORs. Importantly, we did not use feedforward inhibition

that sets the overall mean input to be zero. When mean-canceling feedforward inhibition is

used, the maximum dimensionality is achieved at $K = N/2$. When introducing an additional

constraint on the total number of connections, the optimal K becomes substantially lower,

around 7 for $N = 50$. However, since we do not constrain the total number of connections for

each network, we did not include feedforward inhibition in Figure 5, leading to a K that is around

3 for $N = 50$.

Analysis of identity/valence two-task networks

For the two-task networks, we used all combinations of the following hyperparameter values:

PN normalization (None or Batch Normalization), learning rate (1e-3, 5e-4, 2e-4, 1e-4), KC

dropout rate (0, 0.25, 0.5), resulting in 24 networks trained.

1000

To assess whether the expansion layer neurons break into multiple types when analyzing the

two-task networks, we represent each third-layer (expansion layer) neuron with three variables:

(1) its input degree (the number of above-threshold connections from the previous layer), (2) the

norm of its connection weights to the identity classification head, (2) the connection weight norm

to the valence classification head. Since these variables are of different scales, we z-scored

them (mean subtract then divide by standard deviation). We then obtained a 3-dimensional

depicture of each third layer neuron.

1008

Next we did k-means clustering on the normalized data with k (the pre-determined number of

clusters) ranging from 2 to 10. We quantified the quality of each clustering result with its

silhouette score (the higher the better), which intuitively compares the inter-cluster distance with

the intra-cluster distance. We found that the optimal number of clusters is generally 2 or 3. We

analyzed all networks with 2 optimal clusters. We named the cluster of neurons with stronger

connections to the identity readout head as cluster 1, the other as cluster 2.

1015

1016   In Figure 6c, e, we computed the density of neurons in these data spaces separately for each

1017   cluster, before adding the densities together. This visualization allows for a clearer depiction of

1018   the density peak of each cluster.

1019

1020   When lesioning either cluster 1 or 2 in Figure 6g, h, we set the outbound weights from the

1021   lesioned neurons to 0, equivalent to setting their activity to 0.

1022

1023   **Figure S1**

1024

Figure S1 | Robust formation of glomeruli and sparse connectivity, Related to Figure 1

a. Accuracy (top), GloScore (middle), and KC input degree (K, bottom) as a function of hyperparameters. From left to right, learning rate, noise level, PN normalization, KC dropout rate, and initial PN-KC weights. K values are not shown for networks where the PN-KC connectivity does not contain a single peak well separated from the pruning threshold (see Methods). When a single peak can be inferred (blue dots), GloScore remains high, and KC input degree remains around 5 to 10.

b. Accuracy (top), GloScore (middle), and KC input degree (K, bottom) during training. For each plot, one hyperparameter is varied, from left or right: learning rate, noise level, and KC dropout rate. Networks of different hyperparameter values converge to the same GloScore and KC input degree during training, as long as PN-KC connectivity is well separated (solid lines).

c. Distribution of PN-KC connection weights for networks of different hyperparameter values. Left to right: Learning rate, PN normalization, noise level, and KC dropout rate. Having no PN normalization leads to PN-KC weights poorly separated from the threshold, explaining why in (a) the K value is not shown for the network with no PN normalization.

d, e. The effect of pruning weak PN-KC weights. Pruning weak PN-KC weights does not affect performance (**d**), but it allows a cleanly separated distribution of PN-KC weights from the threshold (**e**). The lack of a clean separation without pruning (e) leads to unreliable estimation of the PN-KC input degree (d).

1044   **Figure S2**

1045

Figure S2 | Effect of having multiple odors associated with each class, Related to Figure

1

a, Schematics of two datasets. (Top) Illustrating a dataset where only one odor prototype

(triangle) is associated with each class. Each class then corresponds to a contiguous area in the

input activity space, and the dataset is linearly separable. (Bottom) Illustrating a dataset where

each class is associated with two odor prototypes residing in segregated locations in OR activity

space. **b**, From top to bottom, accuracy, GloScore, KC input degree, and KC activity sparsity

(percentage of KCs active on average) for networks trained on datasets with different numbers

of odor prototypes per class. Having more odor prototypes per class promotes KC activity

sparsity, while keeping GloScore high and KC input degree almost constant. Having KC dropout

has a similar impact. **c, d**, Comparing accuracy between the full ORN-PN-KC-Output network

(**c**) and a simple ORN-Output network (**d**). The ORN-Output network has classification readout

directly from the ORN input layer. This shallow network performs well on the dataset with 1 odor

prototype per class (linearly separable), but much worse than the full network on more complex

datasets.

Figure S3

1062

Figure S3 | Random sampling of PN inputs from KCs and the impact of KC recurrent

inhibition, Related to Figure 1

a, Average probability of connection from all KCs (n=2500) to each individual PN (n=50). KCs

sample uniformly from all PNs.

b, Plotting the distribution of number of KCs that receive each of the 1225 (=50x49/2) unique

pairs of glomeruli. Data derived from training is shown in blue, and shuffled connections are in

orange. Shuffling maintains the frequency of glomerular connections and the distribution of KC

input degrees, but eliminates non-random patterns of inputs onto individual KCs. KCs are not

preferentially connected to any specific pair of PNs.

c, Plotting the distribution of KC input degrees for all KCs (n=2500). Data derived from training

is in blue, and random connections are in orange (probability of connections is the same for all

PN-KC connections). Here, shuffling was Bernoulli, thus every PN-KC connection had an equal

probability of being non-zero. Training leads to a distribution that is more centered around 7

than a random model.

1077

1078

1079 **Figure S4**

1080

Figure S4 | The impact of input correlation, Related to Figure 1

a, Illustration of a dataset with 0.8 correlation coefficient between activity of different ORs. **b**,

(Top to bottom) Accuracy, GloScore, and KC input degree for networks trained on datasets with

different OR correlations. OR correlation level has no clear impact on GloScore and KC input

degree.

Figure S5

Figure S5 caption content:

Varying key network hyperparameters

a — ORN-PN connectivity
b — PN-KC connectivity
c — Non-negative ORN-PN
d — Unconstrained ORN-PN
e — Accuracy, GloScore, K vs Number of PNs
f — Accuracy, GloScore, K vs Number of KCs

1087

Figure S5 | Impact of key network hyperparameters, Related to Figure 2

a, b, ORN-PN connectivity (**a**) and PN-KC connectivity (**b**) in a network without non-negative

ORN-PN connections. **c, d**, Training decorrelates ORN-PN connections in networks with (**c**) and

without (**d**) non-negative ORN-PN connections. Each PN unit receives connections from 500

ORNs, their weights summarized by a 500-dimensional vector. For two PN units, we compute

the cosine similarity (cosine of angle) between each of their input weight vectors. The

distribution of cosine similarities between all pairs of PN units in trained networks (blue), and in

random networks (orange). If ORN-PN connections are non-negative, the random weights are

drawn from a uniform distribution between 0 and 1, otherwise drawn from a random Gaussian

distribution. These results show that training reduces the cosine similarity between input weights

to pairs of PNs, decorrelating PNs.

e, f, Accuracy, GloScore, KC input degree for networks with different numbers of PNs (**e**) and

KCs (**f**), and for different levels of KC dropout rate.

Figure S6

1102

Figure S6 | Impact of varying the number of neurons each layer, Related to Figure 2

a, ORN-PN connectivity (left) and PN-KC connectivity (right) for a network with 30 PNs. **b**,

Similar to (**a**), but for a network with 200 PNs. In neither case does ORN-PN connections form

clean glomeruli.

c-f, Analysis of a network with 200 PNs. **c**, The distribution of GloScore computed for each PN

unit. A proportion of PNs have close to 1 GloScore. The threshold separates UniGlo units and

MultiGlo units. **d**, UniGlo units tend to make stronger connections to KCs. **e**, Lesioning UniGlo

units has a far stronger impact on accuracy. **f**, Connections from ORNs to PN with highest

GloScore (left) and lowest GloScore (right).

g-h, Similar to (**a, b**), but for networks with 50 and 10,000 KCs.

     Figure S7

Figure S7 | Additional analyses of the recurrent neural network model, Related to Figure 3

a-d. Analysis of a RNN unrolled for 3 steps. (**a**) Distribution of neuron's mean activity level, computed at different processing steps. Left to right, step 1 to 3. For each neuron, we compute the average activity across all odors. Each dash line corresponds to the threshold used to define active neurons. The same value of 0.2 used for all distributions. (**b,c**) Distribution of step 1 to step 2 ('PN-KC') connection weights after training, in linear space (**b**) and log space (**c**). No weight pruning is used for RNNs. In log space, the distribution is fit by a bi-modal Gaussian distribution. Strong PN-KC weights refer to the connections above the threshold separating these two modes. **c,** The distribution of strong "PN inputs to KC". Here PN neurons refer to neurons active at step 1, while KC neurons refer to those active at step 2.

1126   **e-h,** Similar to (**a-d**), but for networks unrolled for 4 steps instead of 3. Classification readout

1127   occurs at step 4. Here "PN-KC weights" refers to the effective step 2-4 connectivity, which is the

1128   matrix product of the step 2-3 and step 3-4 connectivity.

1129 **Figure S8**

1130

Figure S8 | Formation of sparse connectivity during meta-learning, Related to Figure 4

a, Accuracy and KC input degree for networks meta-trained with different hyperparameter

values. From left to right, meta learning rate, whether weak PN-KC weights are pruned, whether

to include a trainable ORN-PN layer, KC dropout rate, number of classes within each meta

learning episode (see Methods), number of samples per class within each episode. By default,

the PN layer forms exact glomeruli (each PN unit receives connections only from the same type

of ORNs), and the ORN-PN connections are fixed. Although PN-KC connectivity remains

sparse, KC input degree is moderately affected by hyperparameter choices. Convention is the

same as Figure S1.

b, Accuracy and KC input degree during meta-training for networks with different

hyperparameter values.

c, Distribution of PN-KC weights after meta-training for different networks.

Figure S9

1144

Figure S9 | Impact of changing the number of olfactory receptors (ORs), Related to

Figure 5

a, Accuracy and KC input degree for networks trained with different learning rates. From top to

bottom, networks with different number of ORs (25, 100, 150). ORN-PN connectivity is fixed and

PNs form exact glomeruli. Here we use PN to refer to the second compression layer in the

network, and KC as the third expansion layer.

b, Accuracy and KC input degree across training. When the distribution PN-KC connectivity

shows a clear separated peak from the pruning threshold (solid lines), KC input degrees

converge to the same value across learning rate values.

c, The distributions of PN-KC weights for different learning rate values.

Figure S10

1156

Figure S10 | Additional analyses for the emergence of innate and learned pathways,
Related to Figure 6
a, b, Connectivity of an example network. ORN-PN connectivity (**a**) and PN-Third layer
connectivity (**b**). (**b**) is the same as Figure 3d.
c, Silhouette score as a function of the number of clusters used for K-means clustering
algorithm. Silhouette score rates how well the clusters segregate by comparing intra-cluster
distance with inter-cluster distance. Across networks with different hyperparameter
combinations (see Methods), Silhouette score peaks at number of cluster equals to 2 or, less
commonly, 3.
d, Across models, cluster 1 has around 2,000 neurons while cluster 2 has less than 200
neurons. Clusters are sorted according to their average connection strength to the valence
classification head. So cluster 1 neurons has on average weaker connections to the valence
output than cluster 2 neurons. Only analyzing networks where Silhouette score peaks at two
clusters (**c**).
e, f, Accuracy, GloScore, KC input degree during training for different values of learning rates
(**e**) and KC dropout rate (**f**).