Title

Subjective understanding of actions and emotions requires interaction of the semantic and action observation networks

Authors and Affiliations

Minye Zhan [1][2], Rainer Goebel [1][3], and Beatrice de Gelder [1][4]*

[1] Faculty of Psychology and Neuroscience, Department of Cognitive Neurosciences, Maastricht University, 6229EV Maastricht, The Netherlands

[2] U992 (Cognitive Neuroimaging Unit), INSERM, CEA, CNRS, Université Paris-Saclay, NeuroSpin center, 91191 Gif/Yvette, France

[3] Department of Neuroimaging and Neuromodeling, Netherlands Institute for Neuroscience, Institute of the Royal Netherlands Academy of Arts and Sciences, 1105 BA, Amsterdam, The Netherlands

[4] Department of Computer Science, University College London, WC1E 6BT, UK

* Corresponding author: b.degelder@maastrichtuniversity.nl

Abstract

Previous studies have investigated the neural basis of action and emotion perception conveyed by whole body postures and movements. However, subjective understanding of other people's bodily actions and emotions, raises different issues that are currently not well understood and have so far seldom been investigated. In this 7T fMRI study, we proceeded beyond conventional univariate/multivariate analyses with predefined categories, and examined the representational geometry of subjective action- and emotion-understanding by mapping individual subjective reports with word embeddings. Dimensionality reduction revealed that the representations for perceived action and emotion were high dimensional, each correlated to but were not reducible to the predefined action and emotion categories. Searchlight representational similarity analysis showed that the representations in the left middle superior temporal sulcus and left dorsal premotor cortex corresponded to the subjective action and emotion understanding of the participants. Furthermore, using task-residual functional connectivity and hierarchical clustering, we found that areas in the action observation network and the semantic/default-mode network were functionally connected to these two seed regions, and showed similar representations. Our study provides direct evidence that both networks were concurrently involved in subjective action and emotion understanding. Our approach shows how subjective understanding of action and emotion stimuli can be reliably studied and complement insights based on from predefined stimulus categories.

35   Keywords: body, action, emotion, subjective report, 7T fMRI, representational similarity analysis

Introduction

Imagine you are walking into a large conference hall and you see a person waving in your direction from far away. Within hundreds of milliseconds, this triggers a cascade of implicit and explicit brain processes: "Do I know this person? Is she waving towards me, perhaps to notify me something? Since I don't know her and she seems to be quite happy, is she perhaps waving towards someone close by who might be her acquaintance?" This is an example of the multifaceted information about the action, emotion, intention and identity that human bodies routinely convey, which we process effortlessly in daily life. Our brains extract and combine those various dimensions of information, enabling us to reach a personal/subjective understanding, and to act upon it.

These different dimensions of information have been the focus of specialized lines of inquiry. Univariate studies of action observation have found a fronto-parietal network (action observation network) including the intraparietal sulcus (IPS) and the dorsal and ventral premotor areas (PMd, PMv)(Caspers et al., 2010; Grafton and Hamilton, 2007; Rizzolatti et al., 2014). Studies focused on the body form found body/body parts-sensitive regions in the ventral-lateral pathway, the extrastriate body area (EBA) and the fusiform body area (FBA) (Peelen and Downing, 2007), while the posterior superior temporal sulcus (pSTS) is sensitive to the biological motion of both faces and bodies (Allison et al., 2000). Studies investigating how body posture and movements convey emotional information reported activation in areas associated with visual form, action and movement perception, which goes hand in hand with activation in more emotion-related areas including the IFG, insula and subcortical structures (de Gelder, 2006; de Gelder et al., 2004; Dricu and Frühholz, 2016; Kober et al., 2008; Lindquist et al., 2012; Molenberghs et al., 2012; Sinke et al., 2010).

So far, there has been limited evidence that bodily action and emotion processing also involves the default mode network (DMN) areas (Andrews-Hanna, 2012; Buckner et al., 2008), including the temporo-parietal junction (TPJ), precuneus, dorsal/ventral medial prefrontal cortex (dmPFC, vmPFC) (Amodio and Frith, 2006; Saxe et al., 2006). Univariate activation of DMN areas was rarely found in action perception, apart from a few studies (e.g. Brass et al., 2007; de Lange et al., 2008). Therefore the DMN was generally considered as a separate system that does not interact with the action observation network (Van Overwalle and Baetens, 2009). However, instead of univariate activation, studies using multivariate methods such as representational similarity analysis (RSA) (Kriegeskorte et al., 2008; Nili et al., 2014) found that the DMN areas were involved in more general and abstract emotion and valence processing, for some stimuli types other than bodies (Chikazoe et al., 2014; Peelen et al., 2010; Skerry and Saxe, 2015).

Most previous fMRI studies presented participants with exemplars from a few predefined categories, and often used an explicit action or emotion recognition/categorization task, serving as a proxy for participants' subjective action and emotion understanding. This approach reflects the traditional view of a few basic emotions (Ekman, 1999), assuming that (1) there exist a few

discrete categories of actions and emotions that participants are routinely able to recognize; (2)
there is high inter-individual consistency in recognizing and identifying these categories.

Under these assumptions, individual variability is typically treated as noise, partially due to the
difficulty to objectively quantify it across participants, especially for the case of verbal reports.
When individual variability is ignored, neural substrates that do not conform to the predefined
responses or the averaged behavior were missed. However, individual variability is prevalent in
multiple functions from perception to cognition, and some individual variability can show stable
brain-behavior mappings, including the size or function of specific brain areas (Charest et al.,
2014; Kanai and Rees, 2011; Seghier and Price, 2018). Specifically concerning action and
emotion perception, individual variability is seen in multiple validation studies for facial
expressions (e.g. Goeleven et al., 2008; Langner et al., 2010). Other studies also suggested that
different observers may reach a different understanding of the action/emotion, depending on
factors such as the personality of the viewer (Van den Stock et al., 2015) and various contexts
(Aviezer et al., 2008; Kret and de Gelder, 2010; Righart and de Gelder, 2006).

Recently, researchers argued that studying subjective experiences is important for
understanding high-level cognitions such as emotion, language, and music (Hartley and Poeppel,
2020; LeDoux and Hofmann, 2018). The presence of subjective variability in emotional
perception and production is also acknowledged in the recent literature (Barrett et al., 2019;
Cowen and Keltner, 2021). In response to these challenges, new studies utilized very large
stimulus sets, subjective reports, and the associated semantic space (Cowen et al., 2019; Cowen
and Keltner, 2021, 2020, 2017). The results found a large amount (13 to 28) of emotional
categories could be observed in subjective reports for facial, vocal, musical emotional
expressions. There were no discrete category boundaries, and the semantic space of these
categories was also high-dimensional. The brain-behavior mappings of such rich emotion
representations seen in subjective experience independent from the predefined basic categories
are still largely uncharted.

With the advancement of deep neural networks and natural language processing techniques,
word embeddings (see Boleda, 2020 for a review) are now increasingly used to describe
semantic concepts in an objective and quantitative way, and recent studies started linking them
to brain activity (Hebart et al., 2019; Zhang et al., 2020).

In this high-resolution 7T fMRI study (1.2 mm isotropic resolution, voxel volume = 1.728 mm³)
with RSA (Kriegeskorte et al., 2008; Nili et al., 2014), we aimed to go beyond conventional
analysis with predefined categories, and to examine the shared neural systems that enabled
each participant to independently reach his/her own version of action/emotion understanding,
be it a different version or not from other participants. To ensure subjective perception, the
participants were not given any action/emotion category labels or categorization task. During
functional runs, 10 participants passively viewed a large stimulus set of 10 predefined bodily
action categories (6 neutral, 4 emotional categories; each participant viewed 40 stimuli).

Immediately following the scanning session, participants provided free reports of the
subjectively perceived action and emotion for each stimulus.

We first examined the representational geometry of the subjective reports by principal
component analysis (PCA) and RSA, after mapping all subjective report entries into a common
300-dimensional vector space using Deconf word embeddings (Pilehvar and Collier, 2016). In the
conventional analyses of predefined categories, we examined their neural representations with
RSA searchlight and RSA regression. We also estimated the body joint positions using the
OpenPose library (Cao et al., 2019), to account for areas related to processing of low- and mid-
level visual features. In analyses examining representations of subjective understandings, we
again searched for corresponding neural representations by RSA searchlight, but with
individualized model matrices. For the resulting group-level areas, we then examined their
putative direct upstream/downstream areas by task-residual functional connectivity and
hierarchical clustering. We found neural representations for both perceived action and
perceived emotion, and the two analyses with predefined categories and with the subjective
reports converged as they both indicated joint involvement of the action observation network
and the DMN/semantic network, noting that the analyses of the subjective understanding
provided much more direct evidence.

Results

RDM construction

In the scanning session, participants passively viewed 40 gray-scale images from one of two
balanced stimuli sets (**Fig. 1A.** See **Fig. S1** for the complete sets of stimuli), to have enough
repetitions per stimulus while having enough stimulus image variability for each participant. We
used a slow event-related design, where each image (2.60 x 4.26 degrees) was presented for
500 ms, followed by an inter-stimulus interval of either 7.5, 9.5 or 11.5 s. Each image was
presented 12 times.

In the behavioral session directly after the fMRI scan, participants reported their subjective
understanding of the action and emotion of each stimulus by typing a short description, and
rated the implied motion and valence on a scale of 1 to 7 (See **Table S1** for the exact questions,
and examples of participants' free reports).

Individual reports were analyzed by mapping all response entries to the same high-dimensional
space using the pre-trained Deconf word embeddings (Pilehvar and Collier, 2016), which
combined the word2vec word embeddings and the WordNet database (see Methods for
details). Specifically, we lemmatized all the verbs, nouns, adjectives, adverbs typed in by the
participants (e.g. fighting/fights→fight), and selected the corresponding meaning for each word
in WordNet 3.1 (https://wordnet.princeton.edu/). We then retrieved the corresponding 300-

dimensional vectors from Deconf embeddings, averaged the word vectors in each response
entry, and computed RDMs for perceived action and perceived emotion (cosine distance) for
each individual participant, see **Fig. 1Bab** and **1Cab**.

Implied motion and valence ratings were one-dimensional attributes provided by individual
participants, which were related to but not fully represent the action and emotion aspects of
each stimulus. We used them to complement the analysis of action- and emotion-
understanding. These RDMs were computed directly from the individual behavioral ratings
(Euclidean distance, **Fig. 1Bcd, Ccd**).

For predefined categories (10 action categories, non-emotional/emotional actions), we followed
the RSA and perceptual categorization literature and constructed model RDMs (Euclidean
distance, **Fig. 1B**, first column), assuming that the stimuli representations were similar within
categories, but were different across categories between stimuli (Freedman et al., 2001).

We examined the correlations of the subjective report and the rating RDMs with the two
predefined RDMs. Throughout the whole study, correlations between RDMs were computed
with Spearman correlation, and submitted to a one-sample t test against 0 (two-tailed) at the
group level, after Fisher's Z transformation.

Perceived categories largely corresponded to the predefined ones, but with considerable individual variability

All four types of subjective report and rating RDMs were significantly correlated to the
predefined ones (one-sample t test against 0; coefficient of variation, CV, showing inter-
individual variability), perceived action to predefined action RDMs: mean rho=0.324, p=8.55×10^{-8},
CV=20.4%; perceived emotion to predefined emotion RDMs: mean rho=0.491, p=0.000164,
CV=51.2%; rated implied motion to the predefined action RDMs: mean rho=0.166, p=0.000541,
CV=60.4%; rated valence to the predefined emotion RDM: mean rho=0.496, p=5.91×10^{-7},
CV=25.5%. This indicates that the individual subjective understanding largely corresponded to
the predefined categories, especially for emotions, although there was considerable individual
variability (**Fig. 1C, D**). For all four types of subjective reports and ratings, the two stimuli sets
did not result in set-specific reports: the Spearman correlation similarity across individual RDMs
within a stimuli set was not different from the similarity between sets (Wilcoxon rank sum test,
all p>0.53).

We then examined the individual variability, to assess how appropriate it is to use group-
averaged RDMs to perform further analyses in individual participants. We first obtained a group-
averaged RDM from all 10 individual RDMs, then computed its Spearman correlation to each
individual RDM (one-sample t test against 0; CV). When inter-individual consistency is high, the
group-averaged RDM should have high correlation to each individual RDM, and a low CV. For
valence, the group-averaged RDM was very consistent with individual RDMs: mean rho=0.900,
p=6.91×10^{-8}, CV=19.9%. However, the other 3 group-averaged behavioral RDMs were less
consistent with individual RDMs, again showing considerable individual variability: perceived

action RDM: mean rho=0.517, p=4.74×10^{-6}, CV=32.7%; perceived emotion RDM: mean
rho=0.565, p=6.02×10^{-5}, CV=44.9%; rated implied motion RDM: mean rho=0.621, p=8.71×10^{-5},
CV=47.1%. This moderate consistency is unlikely to be caused by our small sample size, but
seems to be a persisting effect regardless of the sample size. In validation studies of facial
emotion stimuli with much larger sample sizes (Goeleven et al., 2008; Langner et al., 2010), the
consistency (measured by reporting accuracies) was in a similar range as the current study (see
Table S2 for comparison).

With these moderate correlation coefficients, indicating less tight brain-behavior links for
individual participants, using group-averaged RDMs or the predefined category RDMs in
subsequent analyses may be less suitable to capture the individualized neural substrates.

On the other hand, analyses based on the individual subjective responses may better capture
the individual neural processes, because the neural activity and patterns generating these
individualized subjective reports (behavioral outputs) may still map to brain locations in a
consistent and meaningful way. If the neural processes found this way are robust and consistent
enough, individual-level replication can be achieved (Smith and Little, 2018). Adopting this logic,
our subsequent analyses looked at the mapping of subjective reports to brain activity, and
accordingly focuses on individual-level data and results.

The perceived action and emotion representations were high-dimensional

To investigate perceived action and perceived emotion, we examined the high dimensional
space of all subjective responses across participants using principal component analysis (PCA),
since all 400 responses were in the same 300-dimensional space.

The first few principal components (PCs) for the perceived action and perceived emotion
representations captured a large amount of variance (First 10 PCs: 86.17% and 89.63% variance;
first 50 PCs: 97.76% and 99.18% variance, **Fig. 1F, G**, analysis performed on 1st to 50th PC for
both representations).

The perceived action representation showed considerable individual variability when compared
to the 10-action-category model (**Fig. 1Ea, Ga**). The first and biggest few components did not
show clear separation of action categories. Instead, individual variability was more prominent
(**Fig. 1H**, correlation to individual subject model in the range of 0.1 to 0.2), while it remains
elusive what accounts for the majority of the variance in PC 1. Only the later and much smaller
PCs were correlated more to the 10-action-category model (7th, 9th, 10th PCs), the non-
emotion/emotion model (7th, 22nd, 6th PCs), and the implied motion ratings (6th, 10th, 18th PCs),
and also showed relatively clear category separations (**Fig. 1H, I**). The presence of smaller PCs
correlated to the action categories, emotions and implied motion ratings indicates that the
perceived action representation is rich and high-dimensional. Since the categorization process
could be thought as drawing a hyperplane to separate a cloud of dots in a high-dimensional
space, such high-dimensional action representations potentially supports extracting the relevant

categorical and continuous information, but it is not equivalent and not reducible to one of the
predefined category structures.

The perceived emotion representation was lower-dimensional than the perceived action
representation (79 versus 174 independent PCs), and showed higher inter-individual consistency
(**Fig. 1Eb, Gb**, much lower correlation value to the individual subject model in **Fig. 1H**). The lower
dimension may either be due to the fewer emotion than action categories (4 vs 10), the higher
inter-individual consistency, or is an intrinsic property of the emotion representation. The first
few PCs showed a moderate correlation to the non-emotion/emotion model and valence
ratings, and even to the 10-action-category model (**Fig. 1H, J**). Interestingly, visual inspection of
the RDMs showed that the perceived emotion representation contained the separation of non-
emotion and emotion categories (**Fig. 1Eb**, PC1 and 2 in **Fig. 1Gb**), but also contained finer-
grained separation for individual emotions. These were captured by the 3rd, 4th and 6th PCs,
corresponding to happy, fearful and sad (**Fig. 1Gb**, see the locations of the prominent white/red
bars across all conditions, showing similarity within the category and dissimilarity to the other 9
categories). In the 3rd and 4th PC, the angry emotion could further be separated. This indicates
that the perceived emotion representation is also a high-dimensional one; brain areas
containing such representations could potentially support both the non-emotion/emotion
categorization, and categorization of each individual emotions.

Figure 1. The representational geometries of subjective reports were high-dimensional, and showed considerable individual variability.

A. Stimuli examples of 10 action categories, performed by one of 8 actors. Category abbreviations: CH: combing hair; DW: drinking water; OD: opening door; PH: phone; TR: putting on trousers; NE: neutral standing still; FE: fearful; AN: angry; HA: happy; SA: sad.

B. RDMs for predefined categories, perceived categories, ratings, averaged across 10

participants (40 by 40 matrices, sorted by the 10 action categories). **a.** perceived action; **b.**
perceived emotion; **c.** rated implied motion; **d.** rated valence. Colors in **B, C**, **E, G** were scaled
automatically by the minimal/maximal values within each RDM. Blue: similar; color: dissimilar.
C. RDMs for individual participants (each column) showed considerable individual variability.
RDM types **a** to **d** correspond to **a** to **d** in **B**. The left 5 participants viewed stimulus set A, the
other 5 viewed set B.
D. Correlation to the predefined models for individual participants were not high. **a** to **d**
correspond to the ones in **B** and **C**. Black bars: group average.
E to **J**. PCA results of all 400 behavioral report items for perceived action and perceived emotion.
The smaller PCs of the perceived action and the first PCs of the perceived emotion showed
correspondence to the predefined RDMs.
E. Same to **B**, but for all behavioral report items across participants (400 by 400 matrices).
F. The first 10 principal components (PCs) explained a large amount of variance. Curves:
cumulative explained variance (%).
G. RDMs for scores of the first 10 PCs (Euclidean distance), for perceived action (**a**) and
perceived emotion (**b**).
H. RDMs for the first 50 PCs, correlated to the predefined action, emotion models, behavioral
rating models, and to the individual subject model. The first PCs of the perceived action
correlated more to the individual subject model. Blue bars: FDR q<0.05.
I and **J.** Perceived action (**I**) and emotion (**J**) report items, plotted against the first two PCs, and
against the two PCs with highest correlation coefficients to each of the models.

Univariate results were consistent with the literature

For the fMRI data, as a sanity check, we first performed conventional group-level univariate
analysis with data smoothing, for the 10 action categories, and parametric modulations for
implied motion and valence (**Figure 2**). The 7T data were very robust: the activation location and
time course profiles at 7T were similar to 3T ones, but showed higher %-signal change (See
Figure S2). Participants remained attentive to the stimuli (mean response accuracy for catch
trials was 92.49%, SD=5.44%, the main mistakes being misses and false alarms, number of error
trials ≤ 3 per participant).

The 10-category one-way ANOVA showed differences across action categories in bilateral EBA,
right FBA, right lateral occipital cortex (LOC) and right mIPS (**Fig. 2A**). Similarly, the parametric
modulation of implied motion showed higher activity for actions rated with higher implied
motion, in bilateral EBA, right mIPS, left pIPS, right rostral cingulate zone (RCZ), where the
former 3 overlapped with the ANOVA clusters (**Fig. 2B**). The 10 categories > baseline contrast
showed activation in body-sensitive areas, and areas of the action observation network (**Fig. 2E**),
consistent with the literature (see de Gelder and Poyo Solanas, 2021 for a review).

When contrasting emotional and non-emotional categories (excluding the standing-still
condition), the left IFG and left middle temporal gyrus (MTG) showed higher activity for

emotional categories, while early visual areas (EVC) and right precentral gyrus showed higher
activity for non-emotional categories (**Fig. 2C**). The activation map was very similar when
including the standing-still condition. These univariate results were consistent with previous
findings (de Gelder et al., 2004; Dricu and Frühholz, 2016; Kober et al., 2008; Molenberghs et al.,
2012; Sinke et al., 2010). However, for the parametric modulation of valence, we only observed
clusters modulated by positive valence, but not for ratings of negative valence (negative
modulation). These clusters were found outside the frontal lobe, in bilateral early visual cortices
(including bilateral V3a and right calcarine sulcus/cuneus), right posterior collateral sulcus, right
supramarginal gyrus, left precentral gyrus/central sulcus (**Fig. 2D**).

We cannot exclude that some of these may be false negatives due to the exacerbated inter-
individual variability specifically at 7T, where activation clusters were small, and were
constrained to the gray matter even after spatial smoothing. This effect could be observed in
the functional localizer data: despite that we found robust EBA, FBA, FFA clusters in all individual
participants (data smoothed 3 mm FWHM, contrasts: bodies>faces, houses, tools, words;
faces>bodies, houses, tools, words), and the activation sites were reliable in one participant
between 3T and 7T scans on different days (**Figure S2**), the across-participant overlapping of
these clusters were low; the group-level GLM (data smoothed 6 mm FWHM) only showed an R
EBA/pSTS cluster for bodies, L EVC and bilateral precuneus clusters for faces (**Figure S3**). Thus
for whole-brain activation and searchlight analyses, we used the initial p threshold of 0.005 to
balance between the false positives and false negatives.

Figure 2. Univariate results. Data in volume space were plotted on the group-aligned surface
mesh after cortex-based alignment. Functional data were smoothed at 6 mm FWHM, all maps
were cluster-size thresholded with Monte-Carlo simulation, alpha=0.05, n simulations=5000. We
used the initial p<0.005 to alleviate the false negatives due to high anatomical inter-individual
variability, which was clearly observed in our functional localizer data.
A. ANOVA of 10 categories. Color bar p range: 0.005 to 0.0001.
B. Parametric modulation of rated implied motion.
C. Emotional categories > non-emotional categories (excluding neutral standing still).
D. Parametric modulation of rated valence.
E. 10 categories > baseline.
Color bar p range in **B to E**: 0.005 to 0.0005.
Cluster size thresholds in **A** to **E**: 115, 55, 46, 56, 128 functional voxels.
323
324

Predefined non-emotion/emotion and 10-action-category representations in the brain

Next we followed the conventional predefined-model-driven approach, and performed RSA
searchlight analysis for the RDMs of the 10 action categories, and the non-emotion/emotion
categories. We constructed neural RDMs from univariate t maps of the 40 individual stimuli (no
smoothing of functional data, Pearson's correlation distance), and performed RSA searchlight
(radius=5 voxels; Spearman correlation to the predefined category RDMs, one-sampled t test
against 0 for the Fisher's Z-transformed rho values at the group-level, cluster size thresholded at
alpha of 0.05, Monte-Carlo simulation n=5000). The same group-level test and cluster
thresholding scheme was used for all searchlight analysis throughout the study.

For the predefined non-emotion/emotion categories, we found two areas positively correlated
to the model RDM, in L central sulcus (adjacent to the cluster found in parametric modulation
for valence ratings in the univariate analysis, in **Fig. 2D**), and R PMd/FEF (**Figure 3B**). Another
four areas showed negative correlation to the RDM, in L precuneus, L caudal cingulate zone,
bilateral medial SFG, and L thalamus. These negative correlations may indicate fine-grained
processing of individual stimulus exemplars within each category (here the non-emotion or
emotion categories), or similar processing across categories. Since their interpretation would
require further systematic examination, we limit our interpretations on positive correlations.

For the predefined action categories, we found 29 brain areas positively correlated to the 10-
action-category RDM (**Figure 3A, S4**, **Table S3**, denoted "10-action-category areas" below), a lot
of which were medial areas, and no negatively-correlated areas. When thresholding at p<0.001,
eight of these areas were still present, including the R cuneus, R EBA/hMT+, L central sulcus, L
precuneus, R posterior cingulate gyrus and sulcus, bilateral medial superior frontal gyrus,
anterior RCZ. Some of these 10-action-category areas consistently showed group-level
univariate activation for multiple action categories, in body or action perception-related areas

including R EBA/hMT+, L pIPS and L RCZ; but several areas did not show above-baseline

univariate activation for any action category, including L central sulcus, R anterior SFS, R

cerebellum, L vmPFC and bilateral medial SFG (**Figure S5, Table S4**).

We next examined the task-residual functional connectivity, which presumably reflects

information transfer, and displays certain levels of consistency with structural connectivity

(Bullmore and Sporns, 2009), and thus could potentially capture the direct

upstream/downstream areas for a seed area. Using these 29 areas as seed regions, we observed

fine-grained connectivity patterns for each seed region, both showing hemispheric symmetry.

These areas were highly interconnected, and were also connected to the action-observation-

related areas (EBA, FBA, IPS, pSTS, SMA, PMd, PMv, M1, cerebellum), and DMN areas (dmPFC,

vmPFC, precuneus, TPJ, mSTS). Furthermore, most areas were heavily connected to bilateral

caudate, putamen and thalamus; and 14 out of 29 areas were connected to the hippocampus.

See supplementary **Figure S6** for a summary of these connectivity patterns.

Figure 3. Searchlight RSA showed multiple areas correlated to the predefined category models.

A. Results for the 10-action-category RDM, cluster size threshold=43 voxels. The labeled areas

were ones overlapped with the perceived action and emotion FC networks. **B**. Results for the non-emotion/emotion RDM, cluster size threshold=35 voxels. The areas labeled were ones with positive correlations to the RDM. Color bar p range in both **A** and **B**: 0.005 to 0.0005. Cluster size thresholds: 43, 35 functional voxels. Initial p<0.005.

The representations of low- or mid-level visual features and higher-level attributes

An important question to disentangle is, whether the brain areas showing category boundaries contained representations for the more abstract categories per se, or merely for the mid-level and/or lower-level visual feature differences between the stimuli, which could co-vary with the abstract category boundaries.

To investigate whether some of the 29 brain areas found by the 10-action-category RDM may be related to some low/mid-level visual features, we performed RSA regression, using the RDMs of higher-level stimuli attributes and low- or mid-level visual features as predictors. We only tested a limited number of features, motivated by the literature as in our previous studies (Poyo Solanas et al., 2020a, 2020b), because the model space is infinite and impossible to cover by our current study. High level stimulus attributes included non-emotion/emotion, implied motion, valence, and actor identity. The low level features included the raw pixel values of each stimulus picture, and the body joint coordinates, extracted from each stimulus picture by the OpenPose library (Cao et al., 2019). The presumed mid-level visual features were computed from the body joint coordinates,, including features related to body-part (head, shoulder, waist) orientation, as these may signal the directions of social interactions; the hands/feet-to-head distances, which may be related to the peripersonal space (Bufacchi et al., 2016); and the relaxation of the arms/legs. All RDMs were put in the same linear model, so that the unique contribution of each RDM could be examined.

Most of the low- mid-level RDMs indeed correlated to the 10-action-category RDM (rho ranging from 0.08 to 0.36), except the raw-pixel-value and head-orientation RDMs. See **Figure 4A, B**. These correlations are to be expected, because the actors of the stimuli set received specific instructions per action category (Stienen and de Gelder, 2011) (see all stimuli in **Figure S1**).

We found that some of these stimulus features and attributes could partially explain the activity in some of the 10-action-category brain areas (with a positive beta estimate significantly bigger than 0). For the low-level features, the raw pixel values representation could be found in R cuneus and R CCZ (negative beta in R SPOC); the raw-joint-coordinates representation could be found in R EBA (negative beta in R callosal sulcus). For mid-level features, the head orientation representation could be found in R SPOC (negative beta in R dmPFC); the shoulder orientation representation was found in L pIPS, and the shortest hand-head distance representation in R cerebellum. For higher-level attributes, only the actor identity representation showed a positive beta estimate again in the R SPOC (negative beta in R cuneus).

We then performed whole-brain searchlight analysis for all those attributes and features (**Figure**
4 C to **G**). For high-level features, we did not find areas positively correlated to the valence
rating RDMs. The implied motion rating RDMs showed positive clusters in L FEF (adjacent but
not overlapping with the L PMd cluster for perceived emotion) and R SPOC. And interestingly,
the actor identity RDM showed a positive cluster in L MTS, close to EBA and FBA.

We found positive clusters for two mid-level visual features: head orientation and shortest
hand-to-head distance, but not for any other low- or mid-level visual features, despite their
similarity to the two features with positive clusters (shoulder and waist orientation RDMs were
correlated to the head orientation RDMs: rho ranges from 0.317 to 0.412; the shortest hand-to-
head distance RDMs were correlated to the average hand-to-head distance RDMs, rho=0.593,
0.646 for stimuli set A and B). This indicated that these two features may be biologically
meaningful ones for the brain.

Figure 4. Low/mid-level features (**A** and **B**), and whole-brain searchlight results corresponding to these features (**C** to **G**).

A. Skeleton in the left panel: coordinates of the 18 joints extracted by the OpenPose library; white dots in the middle panel: joint coordinates after manual adjustment; right panel, magenta lines: distances used to compute head, shoulder, waist orientations, normalized by the corresponding distances in the neutral stand-still stimulus of the same actor (see middle panel); green lines: hand/foot-to-head distance.

B. The low/mid-level features, showing RDMs for stimuli set A. The raw coordinates RDMs were computed excluding joints on the ears and eyes, but was very similar to the ones computed including these joints (RDM similarity rho=0.976, 0.98 for stimuli set A and B). Most of these

RDMs correlated to the 10-action-category RDM.

C, D, E. Searchlight results for higher-level attributes. The valence RDM did not show positively

correlated clusters. Cluster size thresholds: 38, 44, 31 functional voxels.

F, G. Searchlight results for mid-level features that showed clusters positively correlated to the

corresponding RDMs. Cluster size thresholds: 48, 37 functional voxels.

Color bar p range in **C** to **G**: 0.005 to 0.0005. Initial p<0.005. Clusters showing positive

correlations to the corresponding RDMs were labeled. In **D**, clusters showing negative

correlations were also labeled.

RSA searchlight analysis revealed representations for perceived action in left mSTS and for perceived emotion in left PMd

We next returned to the individual subjective reports, searching for similar neural representations for the individualized perceived action and emotion RDMs. We found one positively correlated cluster for each of the subjective report RDMs, in left mSTS for perceived action, and in left PMd for perceived emotion, indicating that these two areas may be involved in the subjective understanding and reporting of action and emotion, respectively. The L PMd cluster is consistent with the analysis based on predefined non-emotion/emotion representation, where the R PMd/FEF cluster was at a very similar location on the other hemisphere to the PMd cluster found here. All other clusters were negatively correlated to the subjective category RDMs. See **Figure 5** and **TableS5** for the complete list of clusters.

Interestingly, the L mSTS and L PMd clusters did not show reliable univariate activation for the 10 action categories (one-sample t test of percent signal change against baseline, all p>0.052, except in L PMd for the Anger category, p=0.031), thus they could not be found by conventional univariate analysis. Neither was the 10-category univariate ANOVA significant in these two clusters, p=0.309 and p=0.945 respectively.

Figure 5. Searchlight RSA revealed corresponding clusters to the perceived action model in L mSTS **(A),** and to the perceived emotion model in L PMd **(B)**. Color bar p range: 0.005 to 0.0005. Cluster size thresholds in **A** and **B**: 39, 38 functional voxels. Initial p<0.005.

The putative direct upstream/downstream areas of L mSTS and L PMd identified by task residual functional connectivity and hierarchical clustering

The L mSTS and L PMd clusters were found by their representation similarity to individualized,
subjectively reported actions and emotions, which already showed considerable individual
variability and hard-to-interpret principle components. Thus, to further understand the
involvement of these two areas in the current task, we could no longer use the standard model-
comparison methodology, where a single predefined-model is compared to the neural RDMs
across all participants. Instead, we used a data-driven approach based on two assumptions: (1)
the information transfer stages of a given area can potentially be captured by functional
connectivity; (2) if the object representations are successively re-represented and "untangled"
in the ventral visual pathway (DiCarlo et al., 2012; DiCarlo and Cox, 2007), similarly the neural
representations of bodily action and emotion representations are gradually transformed across
a chain or a network of brain areas, from the representation of the visual input to the
representation of the subjective output, without sudden changes between two adjacent stages
in the information-transfer chain. In this way, we linked the functional connectivity and
representational analyses together (Ju and Bassett, 2020). To find the set of brain areas in the
same information-transformation chain, we performed task-residual functional connectivity to
the L mSTS seed and the L PMd seed, respectively. Using hierarchical clustering in the two
resulting networks, we could then find areas with neural representations most similar to the
two seeds, some of which may correspond to their direct upstream/downstream areas.

Task-residual functional connectivity
We regressed out the individual stimuli and head motion parameters from the functional data
(deconvolution, data smoothed at 3 mm FWHM), obtained task-residual time courses, and
performed functional connectivity (FC) analysis (Pearson's correlation), with L mSTS and L PMd
as seed regions. See **Figure 6A, B, left panels**. This analysis revealed two partially overlapping
networks for action/emotion understanding at the group level (**Figure 6D**), in action observation
related areas including (bilateral when unspecified) IPS, M1, PMd, PMv, L IFG; and in DMN areas
including TPJ, mSTS/MTG, precuneus, posterior cingulate cortex, dmPFC/vmPFC, mSFG, parietal
occipital cortex (POC), retrosplenial cortex.

Interestingly, some overlapping areas in these FC networks are part of the semantic network,
including mSTS, IFG, TPJ/angular gyrus, dmPFC, vmPFC, posterior cingulate cortex, retrosplenial
cortex (Binder et al., 2009); and the L mSTS FC network corresponded to the semantic network
especially well. See **Figure 6D** and **E**. The seed cluster L mSTS itself is an important area in the
semantic network, which could be activated by written word stimuli (Binder et al., 2009).
Although word-specific clusters around left mSTS were found in individual participants in the
functional localizer data (words>other categories), neither the seed region nor the more
extended FC cluster around the seed showed consistent group-level activation for words in the

functional localizer (one-sample t test against 0, L mSTS seed ROI: mean beta=0.589; t(9)=1.418;
p=0.190; L mSTS FC cluster: mean beta=0.369; t(9)=1.226, p=0.251). More interestingly,
although both FC networks overlapped around L mSTS, the cluster for perceived emotion was
much more posterior than the one for the perceived action, which corresponded to previous
findings that the STS is an heterogeneous structure with several different functions (e.g. Hein
and Knight, 2008).

In addition to the cortical clusters, the FC analysis revealed bilateral caudate and putamen
clusters in both FC networks (**Figure S7, S8**), which may be involved in categorization processing
(Seger, 2008; Seger and Miller, 2010). The left mSTS was also functionally connected to the R
hippocampus; the left PMd was also functionally connected to the bilateral thalamus, pulvinar,
cerebellum, the R septal nuclei, and the bilateral red nuclei (anatomical locations clearly
observable in the T2*-weighted functional images, **Figure S8**). The involvement of the
hippocampus, the septal nuclei and the red nuclei in bodily action and emotion understanding
were not routinely observed in previous bodily-action perception studies with univariate
methods (see de Gelder and Poyo Solanas, 2021 for a review).

Furthermore, the perceived action FC network overlapped with the 10-action-category clusters
in the L central sulcus, R POC/retrosplenial cortex and bilateral callosal sulci; while clusters in the
perceived emotion FC network overlapped with the 10-action-category clusters in L precuneus, L
pIPS, L cingulate sulcus, R SFS, R posterior cingulate/POC/retrosplenial cortex, R caudate, R
cerebellum and bilateral medial SFG (labels in **Figure 3**), again showing consistency to the
analysis based on predefined categories.

Hierarchical clustering
We then examined the possible direct upstream/downstream areas of the two seed regions,
which should show the most similar neural representations to the seeds. We performed
hierarchical clustering to all clusters within each FC network, on the group-averaged second-
level neural RDMs across areas (Spearman correlation distance, hierarchical cluster linkage
arbitrarily thresholded at 0.8). Since both seed regions were encompassed by more extensive
clusters with the shortest hierarchical clustering distance to the seed (cluster in the perceived
action FC network: spanning L mSTS, MTG and ITS; cluster in the perceived emotion network: an
extensive one spanning L PMd, PMv and LR medial SMG), we plotted the extensive clusters
(denoted as "seed clusters" below) instead of the seed regions themselves, in the dendrograms
and second-level RDMs. See **Figure 6A, B, Figure S9.**

In the perceived action FC network, the FC cluster with the most similar representation (shortest
distance in the dendrogram) to the seed cluster was one spanning L p/mIPS, TPJ, angular gyrus.
The other areas under the same branch of the dendrogram were: the R mSTS contralateral to
the seed; action-perception related areas including bilateral PMv, MFG, L PMd, L IFG;

DMN/semantic areas including L precuneus, R TPJ, L posterior cingulate gyrus, LR dmPFC, LR and
medial SFG.

In the perceived emotion FC network, the FC clusters with the most similar representation to
the seed cluster was one spanning R PMd and MFG, contralateral to the seed. The other FC
clusters in the same branch were: L pSTS, MTG, R pSTS, action-perception related areas
including bilateral IPS, IPL, angular gyrus, L IFS, IFG; DMN/semantic areas including L TPJ,
bilateral precuneus, POC; also the lateral and anterior prefrontal cortices including bilateral
MFG, anterior MFG, L MFS, R SFS.

These clusters may be directly involved in understanding the bodily actions and emotions. In
both FC networks, it is interesting to observe the strong involvement of both action-perception
related areas and DMN/semantic areas, showing symmetry across hemispheres. Especially for
the DMN/semantic areas, their direct involvement in bodily action/emotion understanding and
interactions with the action-perception related areas were not reported in previous studies. This
may be due to the fact that most of the areas in the two FC networks did not show an activation
level different from baseline (one-sample t-test of beta values per action condition against
baseline, FDR corrected across the 10 action categories per ROI). See **Figure 6A, B, C**. Thus, they
were unlikely to be reported when using only univariate methods.

The clustering in individual participants was relatively consistent, with moderately correlated
second-level matrices across participants (averaged Spearman Rho, perceived action: 0.418,
SD=0.0473; perceived emotion: 0.374, SD=0.0578). Also, the second-level pattern-similarity
clustering structure across areas does not seem to be linked to the low-level visual features
from the stimuli, but seem to be a real organization feature, because the clustering structure
could be seen in all 10 participants, despite the fact that each 5 participant saw a different
stimuli set (set A and B). See **Figure 6F**.

Apart from the clustering showing high similarity to the seed clusters in every participant
(upper-left side of each RDM), we saw another prominent clustering of areas in each of the two
FC networks of individual participants (27-32nd areas in the perceived action FC RDM, 36-51st
areas in the perceived emotion FC RDM, both in the middle of the RDMs, see an enlarged
version in **Figure S9**). However they showed lower similarity to the two seed regions (red shade
for FC clusters in **Figure 6A, B, left panels**), indicating that these areas are at different processing
stages than the final output stage of the seed regions. In these two groups of clusters, despite
their very different univariate activation levels, their multivariate RDM patterns were clustered
in the same branch of the dendrogram. The clustering in the perceived action FC network
consisted of areas around the bilateral central gyrus (lateral-central/central sulcus, post-central
gyrus, bilateral SMA), most showing above-baseline activation for 0 to 3 of the 10 action
categories, apart from the L lateral central sulcus showing activation for 8 categories. The
clustering in the perceived emotion FC network consisted of areas in the bilateral ventral-lateral
visual pathway (EVC, lingual gyrus, collateral sulcus, fusiform, EBA/hMT+, lingual gyrus, cuneus),
where 8 areas showed above-baseline activation for all 10 action categories, another area

showing activation for 8 categories, the other 7 areas showing no activation for any of the
categories.

Combining the results of functional connectivity and hierarchical clustering, our two
assumptions of the information-transfer-chains seems to be able to discover meaningful and
replicable functional organizations in the brain.

Figure 6. In the functional connectivity (FC) networks of the two seed regions overlapped with
the DMN/semantic networks.
A and **B**. Areas in the FC networks color-coded by pattern similarity to the seeds, L mSTS (**A**), and
L PMd (**B**). Initial p<0.001, cluster size threshold in functional voxels: L mSTS network: 32; L PMd
network: 40. The seed ROIs were in yellow. Color bars: representational similarities to the FC
cluster containing the seed region. For each network, the hierarchical clustering dendrograms
computed on group-averaged second-level RDMs across areas (Spearman distance) were
plotted in the right-most panels. The areas with the most similar representations to the FC
cluster containing the seed region were colored in yellow in the dendrograms (linkage distance
arbitrarily thresholded at 0.8, see a larger version in **Figure S9**), and labeled in the brain maps of
the left panels. The name of the areas containing the seed regions were marked in blue. The
areas with above-baseline univariate activation for more than 5 action categories were marked
with a "+" sign.
C. Histograms of number of conditions with above-baseline activity, for clusters in the two
networks. Most areas did not show univariate activation for any of the 10 action
categories/conditions.
D and **E**. The two FC networks overlapped with the DMN/semantic networks.
D. The overlap of two FC networks.
E. The overlap of the two FC networks, only showing clusters with most similar representations
to the seed (the clusters labeled in **A** and **B**).
F. The group-averaged and individual second-level RDMs. The yellow and black bars for the
group-average RDM denote the same clustering of the dendrogram in **A** and **B**. See a larger
version in **Figure S9**.

Discussion

Our goal in this 7T fMRI study was to go beyond the analysis based on predefined action and
emotion categories, and examine how participants perceived bodily actions by analyzing
participants' subjective understanding of the actions and emotions displayed. Dimension
reduction (PCA) revealed that subjectively perceived action and emotion representations were
high-dimensional and could not be reduced to the predefined category representations, despite
being correlated to them in smaller principle components. Some emotional categories were
reflected in the smaller principle components of the perceived emotion representation. Clusters
in L mSTS and L PMd had representations that were the most similar to the perceived action and
emotion representations. Areas located in the action-observation network and the semantic
network/DMN were functionally connected to these two clusters and also showed similar
multivariate patterns. This provided direct evidence for the involvement and interplay of both
networks in transforming the same visual inputs into individualized subjective understanding of
bodily actions and emotions.

For the predefined categories, the non-emotion/emotion representation corresponded well to
the perceived emotion representation both behaviorally and neurally, showing a cluster in R
PMd/FEF, contralateral to the cluster for perceived emotion. For the predefined 10-action-
category representation though, the resulting clusters were more numerous, and possibly
confounded by low/mid-level visual features that may co-vary with action/emotion categories.
Although less clear than the subjective report analysis, all of the clusters were strongly
connected to both the action-observation network and the semantic network/DMN, consistent
with the perceived action results. For mid-level visual features, we further found that the head
orientation and the shortest hand-to-head distance were represented in the brain, indicating
that these two features may be important for body perception.

Comparing the analysis of predefined categories with that of the subjective reports, our results
suggest that both analysis would yield similar results in the brain, when the subjective reports
are moderately correlated to the predefined categories (rho=0.491 to the non-emotion/emotion
RDM) and have moderate individual variability. However the results would converge less when
the subjective reports are less correlated to the predefined categories and have high individual
variability. In this case the individualized analysis of subjective reports would be more precise,
and capture additional information missed by predefined models, or group-averaged individual
models. The convergence of these two kinds of analyses needs further study.

The involvement of the DMN/semantic network in both action and emotion understanding

At first sight, it may seem that the involvement of the DMN/semantic network found in the
current study simply results from the use of word embeddings. We argue that this is not the
case, and that our study reveals the individual brain underpinnings of action and emotion
understanding as involving both the action observation network and the DMN/semantic
network. Although the word embeddings indeed represent the semantic distances between the
words, these semantic distances reflect the similarities between different concepts. Our
perceived action and emotion representations were different, despite being computed from
word vectors from the same 300-dimensional space. Also, the perceived emotion cluster in L
PMd is not a key node area in the semantic but rather in the action observation network, but
nevertheless was revealed being connected to the DMN/semantic network.

Actually, the involvement of IFG (Caspers et al., 2010; de Gelder et al., 2004; Dricu and Frühholz,
2016; Molenberghs et al., 2012) and areas in the DMN/semantic network (Chikazoe et al., 2014;
Peelen et al., 2010; Skerry and Saxe, 2015) has been consistently found in action perception and
emotional expression perception, although in separate studies and in different contexts. For the
DMN and especially for the vmPFC area, it was related to abstract representation of emotional
stimuli found with multivariate RSA (Chikazoe et al., 2014; Peelen et al., 2010; Skerry and Saxe,
2015), rather than with simple univariate contrasts. The simultaneous involvement of the IFG
and the DMN in action understanding was found in one univariate study contrasting
participant's attention on either the intention or means of the performed actions (de Lange et
al., 2008). In that study, the IFG activity was higher for actions with unusual intentions

compared to usual ones; the DMN was instead showing higher activity when participants were
paying attention to the intentions rather than the means of the action.

Two recent studies provided more evidence consistent with ours. One RSA fMRI study of
observed actions (Tucciarelli et al., 2019) used a large set of action categories, constructed a
semantic similarity model of the meanings of the actions as well as other similarity models
obtained from individual participants' behavioral sortings of similarities, and searched for
corresponding RDMs in the brain. They found bilateral clusters in IFG/PMv, pIPS, and lateral
occipitotemporal cortices (LOTC, close to EBA) corresponding to the semantic similarity model,
although only the left LOTC cluster remained after RSA regression controlling the effects of
other models. That study controlled the inter-individual consistency of the stimuli perception
during the stimuli selection process, which was not done in the current study, and may explain
the discrepancy. Another study (Lee Masson and Isik, 2021) examined the fMRI responses
during naturalistic movie watching using encoding models, and found that a social-affective
model (including features of an agent speaking, social interactions, theory of mind, perceived
valence and arousal) significantly explained the fMRI response in the left STS across two
different movies. This cluster fully overlapped with our L mSTS cluster.

In fact, the IFG and the areas in the DMN were all parts of the semantic network, thus their
involvements could also be studied in the future in the context of the semantic network, apart
from the context of "mentalizing" usually associated with the DMN. The importance of the
semantic network in emotion understanding is further supported by behavioral studies of
semantic dementia patients. In one such studies, three semantic dementia patients with left
temporal pole atrophy and impaired semantic knowledge were asked to sort faces into piles by
emotion. These patients were not able to distinguish between emotional faces with negative
valence, despite that their perception of positive/negative affect, the visual features for each
facial emotion and identity were intact (Lindquist et al., 2014).

Although we did not examine the temporal pole due to coverage limitation, our multivariate
RSA and functional connectivity results support the importance of the DMN/semantic network
in action and emotion understanding, and are consistent with the recent view that the DMN is
potentially the network that integrates extrinsic and intrinsic information (Yeshurun et al.,
2021). Our results are also consistent with the literature, which reported that the DMN did not
show above-baseline activation for passive action observation without deliberating the
goals/intentions (Van Overwalle and Baetens, 2009). We further revealed that both the
DMN/semantic network and the action observation network were involved in the process of
action and emotion understanding, that they were consistently found in all 10 participants
within the same functional connectivity networks and showed similar multivariate patterns
despite very different levels of univariate activation. The multivariate methods worked in our
study and in previous RSA studies, because they took the multiple dimensions in the high-
dimensional neural data into account, while the univariate method considers only one or a few
specific dimensions which associated with specific contrasts (Haxby et al., 2011). Our study

stresses the importance to further examine the function of the DMN/semantic network in action
and emotion understanding with multivariate methods in future studies.

Understanding versus categorization

Previous experiments have mostly used explicit emotion and action categorization tasks with
predefined categories, and implicitly used explicit categorization as a proxy for subjective
understanding. However, categorization and understanding may involve different neural
substrates, as categorization involves some level of abstraction. Our study could not
differentiate between these two processes, because first, the RSA method could not disentangle
categorical boundaries driven by lower-level visual features, or concrete perceptual categories
(Hoemann et al., 2020; Mansouri et al., 2020) that were bound to individual exemplars, or
abstract categories that generalize across exemplars. Second, what we obtained in the
subjective reports were descriptions or labels of action and emotion for each individual
stimulus, rather than more abstract categorization to the group of stimuli. Thus, the resulting L
mSTS and L PMd clusters for perceived action and emotion may not represent the most abstract
level, and the more abstract categorization may happen in other areas functionally connected to
these two areas, and could perhaps utilize these category boundaries in computation. The
different levels of abstractions may also have driven the discrepancy between the analyses with
subjective reports and predefined categories, although both analyses pointed to the strong
involvement of the caudate, which is in the executive loop of categorization learning tasks
(Seger, 2008; Seger and Miller, 2010). The areas found in our study could serve as target areas in
future studies, to examine the level of abstraction.

Brain areas for emotion understanding

Our analysis with the predefined non-emotion/emotion category model and with the perceived
emotion model pointed to the PMd areas in the right and left hemispheres. This area may
contain information exhibiting categorical boundaries between non-emotional/emotional
stimuli, but again the level of abstraction could not be disentangled. Future studies could use
emotional facial or voice stimuli, accompanied by subjective reports, to examine whether this
area is specific to bodies and actions, or is more general for emotions in different modalities
(Vaessen et al., 2019b).

We did not find evidence for coding of valence in frontal (higher-order) areas, either with
monotonic univariate activity modulation or with multivariate representations. However,
valence coding may be bivalent, such that the vmPFC/mOFC activity monotonically increased for
both positive and negative valence, as found in an RSA study (Chikazoe et al., 2014). This might
be the case, as we found evidence that the vmPFC was potentially showing a fine-grained
pattern between similarly perceived emotions (**Figure 5B**). With only one category of positive
emotion, we were not able to examine the possible bivalent activity.

In the analysis of the predefined action and emotion models, and in the univariate parametric
modulation of valence rating, we found adjacent/overlapping clusters in the L central sulcus
(**Fig. 2D, Fig. 3**). These clusters are also adjacent/overlapping to the two FC networks for

perceived action and emotion (**Fig. 6AB**), but with different neural representations to the two
seed regions for perceived action and emotion. This indicated that the primary sensorimotor
areas were involved in action and emotion processing, although the representation there may
be of lower-level features and may not be emotion-specific.

Importance of using individualized subjective reports to study higher-level cognition

With our subjective-report-based analysis, we found that the perceived action and emotion
representations were more high-dimensional and multi-faceted than the predefined category
representations, consistent with the recent series of studies examining subjective reports
(Cowen et al., 2019; Cowen and Keltner, 2021, 2020, 2017). We also found neural
representations corresponding to these subjective report representations in higher-level areas
outside the ventral and dorsal pathways.

Apart from a few RSA studies which linked individualized behavioral data to the brain data
(Chikazoe et al., 2014; Stolier and Freeman, 2016; Tucciarelli et al., 2019), many previous RSA
studies either utilized only the predefined categories (Peelen et al., 2010), or the behavioral
ratings from an independent group (Bracci and Op de Beeck, 2016; Mur et al., 2013; Peelen et
al., 2014; Skerry and Saxe, 2015; Vaessen et al., 2019a), or the averaged behavioral responses of
the same participants scanned (Connolly et al., 2012; King et al., 2019). For high-level cognition
that has a more remote relation with the sensory stimuli and has more variability between
individual participants, the use of individualized behavioral data may be of particular interest, as
shown for object recognition (Charest et al., 2014), traditionally thought to have considerable
behavioral judgment similarities between participants. In precision fMRI that densely samples
individual participants, it has also been found that a large part of the variance in the functional
network similarity was explained by factors related to the individual subjects (showing high
functional network similarity within individual), more in top-down control systems than
sensorimotor systems (Gratton et al., 2018). Such individual network variability may partially be
accounted for by subjective experience, which could be objectively quantified by multiple easy-
to-use pre-trained word embeddings.

Advantages and limitations of the current 7T experiment

The use of high-resolution 7T fMRI in the current study has advantages and limitations. With
higher gray-white-matter contrast and higher temporal signal-to-noise ratio, the resulting data
were very robust (see the functional localizer data in **Figure S2 and S3**), the activation clusters in
individual participants were highly localized in the gray matter, and we observed small
subcortical clusters in multiple analyses at the group level, including periaqueductal gray, medial
geniculate nucleus, substantia nigra, red nucleus, and the septal nuclei. However, the current 7T
data also induced the possibility of false negatives, where the inter-individual
anatomical/functional variability was exacerbated and would no longer be compensated by
extensive smoothing, as observed again in the functional localizer data (**Figure S3**). Better
whole-brain group-level analysis schemes apart from the ROI analysis are needed to benefit

from both the high functional resolution and the large brain coverage, which potentially include
more fine-grained functional parcellations (Glasser et al., 2016; Yeo et al., 2011) and
hyperalignment (Haxby et al., 2011).

Materials and Methods

Participants

The data of 10 healthy right-handed participants recruited from the campus of Maastricht
University were included in the analyses (mean age =23.4, SD=1.955, 5 females.) Two more
participants took part in the study, but due to excessive head motion observed during the scan,
their scanning sessions were either aborted, or data excluded from the analyses. We planned
this sample size according to previous high-resolution 7T studies, and because we perform
individualized analysis while aiming replicability of effects at individual participants (Smith and
Little, 2018). All participants had normal or corrected-to-normal sight and had no history of
psychiatric disorders. Participants provided written consent before the study and received
monetary reward afterwards. The experiment was approved by the ethical committee of
Maastricht University, and was carried out in accordance with the declaration of Helsinki. The
experiment was conducted in English.

Data acquisition

The MR data were acquired in a 7T Magnetom full-body scanner (Siemens, Erlangen, Germany)
in Scannexus, Maastricht University, with a Nova 1-transmitter/32-receiver head coil (Nova
Medical, Wilmington, USA). Dielectric pads were used for all participants except S10 (limited by
the head size), roughly covering bilateral occipito-temporal lobes. The stimuli were back-
projected onto a screen behind the participants' head (Projector: Panasonic PT-EZ57OEL,
projected screen size 30 x 18 cm, resolution 1920 x 1200 pixels, refresh rate = 60 Hz, viewing
distance ~99 cm, screen visual angle 17.23 x 10.38 degrees) and the participants viewed the
screen through a mirror fixed on the head coil. Participants came for two scanning sessions, a 2-
hour session for the main experiment, and a 1-hour session for functional localizers and
anatomical scans.

Whole-brain anatomical data were collected for each participant with a resolution of 0.6 mm
isotropic (MPRAGE sequences, FOV=229 x 229 mm^2, matrix size=384 x 384, flip angle=5. T1-
weighted: TR=3100 ms, TE=2.52 ms; proton-density-weighted: TR=1440 ms, TE=2.52 ms). For
the functional runs, a 2D gradient-echo multi-band EPI sequence was used, with a resolution of
1.2 mm isotropic (multi-band acceleration factor=2 (Moeller et al., 2010), iPAT=3, FOV=172.8 x
172.8 mm^2, matrix size=144 x 144, flip angle=75, number of slices=70, slice thickness=1.2 mm,
no gap, ascending interleaved 2, TR=2000 ms, TE=21 ms, encoding direction Anterior to
posterior, reference scan mode: GRE, MB LeakBlock kernel: off, fat suppression enabled). In
each scanning session, a head scout was acquired for localization, then the B0 field map was

acquired and loaded in the console. The interactive shimming was performed before acquiring
the B1 field map. The system voltage was then computed according to the B1 map values (set to
a maximum of 190 V across all sessions), to have a 90 degree flipping angle at the white matter
beside the lateral ventricles, and the specific absorption rate (SAR) level for the longest
functional run (432 volumes) was controlled at below 75%. The slices were tilted in an angle that
covered most of the occipital lobe, parietal lobe and frontal lobe, while leaving out the anterior
temporal lobe, part of the motor cortex, and the orbitofrontal cortex. This was to ensure that
most of the important areas involved in body perception were covered, including EBA, fusiform
gyrus, IPS, IPL, PMd, PMv. The amygdala was not consistently covered given the relatively
limited coverage (covered in 6 out of 10 participants). Immediately before each functional run, a
5-volume run of the same setup but with posterior to anterior encoding direction was acquired
(Invert RO/PE polarity: on), for post-hoc top-up EPI distortion correction (See the fMRI data
preprocessing sub-section). We informed the participants the purposes of these distortion
correction runs, and instructed them not to move between the distortion correction run and the
actual functional run.

Stimuli

The stimuli were gray-scale whole body images developed and validated in our lab (Stienen and
de Gelder, 2011). They consisted of 8 actors, each posing 10 actions with or without emotional
content. The first 5 categories were neutral actions: combing hair (CH), drinking water (DW),
opening door (OD), talking on the phone (PH), putting on trousers (TR); the 6th was neutral
standing still (NE), and the last 4 were emotional expressions: fear (FE), anger (AN), happy (HA),
sad (SA). The 80 postures were split into 2 balanced sets by randomly selecting images from 4
actors for each category, resulting in 2 sets of 40 stimuli (4 images per category, 5 images per
actor), which ensures that in each stimulus category the participants perceive as much
variability in the posture and the identity as possible. Each participant saw one of the sets.

The body stimuli were embedded in a gray background (RGB value = 128, 128, 128), with all
internal facial information removed. They were sized to 400 x 600 pixels, and presented
centrally on the screen (RGB value = 128, 128, 128). The whole-body shapes in the images
overall spanned 309 x 492 pixels on the screen (visual angles=2.60 x 4.26 degrees).

fMRI experiment design

The study used a slow event-related design. Stimuli were presented with Matlab (Version
R2012a, the MathWorks, Natick, USA) and Psychtoolbox 3.0.11 (Pelli, 1997). A white fixation
cross was present in the center of the screen throughout the experiment. The participants were
asked to always fixate on the fixation cross and take in the body posture as a whole. The
experiment consisted of 6 runs (14 min 18 s each, 429 volumes). Each run started with a fixation
period of 8 seconds, and then the whole set of 40 stimuli was presented to the participant twice
within each run. Each stimulus was presented for 500 ms, followed by an inter-stimulus interval
of either 7.5, 9.5 or 11.5 s. The stimuli and the ISI were presented in a pseudorandomized order.
In addition, 4 catch trials were included in each run. Within each catch trial, a body posture was

randomly drawn from the stimulus set, while the fixation cross changed to either red or blue
(RGB color red= 195, 32, 30; blue= 10, 109, 195) during the stimulus presentation period.
Participants were asked to indicate the color by pressing the corresponding button of the button
box as soon as they saw the fixation change color. Two seconds were added to the inter-
stimulus interval after each catch trial. Excluding the catch trials, each single stimulus image was
presented to the participant for 12 times throughout the main experiment. 9 participants
completed all 6 functional runs; 1 participant completed 5 runs.

Functional localizers

A separate scanning session was devoted to acquiring functional localizer data and the structural
images. Stimuli were presented under passive viewing condition using Presentation software
(Version 16.0, Neurobehavioral Systems, Inc., Berkeley, USA). In the static localizer run (14 min
24 s, 432 volumes), after a 12 s fixation period, gray-scale stimuli of faces, houses, bodies, tools
and words were presented in blocks of 12 s (12 stimuli per block, 800 ms stimuli presentation,
200 ms inter-stimulus interval), followed by resting periods of 12 s with the fixation cross on a
blank screen (RGB value=157,157,157). Each category block was presented 7 times, with a
pseudorandomized presentation order for both the stimuli and the blocks. Facial stimuli were
front-view neutral faces from the Karolinska Directed Emotional Faces (Lundqvist et al., 1998)
(24 identities, 12 males). The part below the neck (clothes, hair etc.) was removed from the face
images. Body stimuli were neutral still front-view bodies (de Gelder and Van den Stock, 2011)
(20 identities, 10 males) from a different set than the one used in the main experiment, with the
facial information removed. House and tool images were obtained from the internet. The house
images consisted of 19 facades of houses with 2-to-3-storey height; the tool images consisted of
18 hand-held tools; words images consisted of high-frequency English words of 4-6 letters in
Arial font. All the images were imbedded within a gray background (RGB value=157,157,157),
spanning a visual angle of 1.99 degrees (230 pixels).

The dynamic localizer run (5 min 36 s, 168 volumes) consisted of 1-s video clips of either facial or
bodily expressions, including neutral (coughing or clearing throat), angry, fear, happy (Kret et al.,
2011). The actors performed the actions against a green background, either wearing black
clothes for bodily expressions, or green clothes for facial expressions. Two exemplars were
selected for each expression category (in total 8 for faces and 8 for bodies). The actors in the
selected exemplars were all males. For the facial stimuli, two of the neutral expressions were
performed by the same identity. The facial and bodily expression clips were presented
separately in blocks of 8 s, with the stimuli order pseudorandomized. The face and body blocks
were presented 10 times each, separated by an inter-block interval of 8 s, where a black screen
and a white fixation cross was presented.

Behavioral ratings

Immediately following the scanning session, participants completed a behavioral task outside
the scanner. Each of the 40 stimuli participant saw in the scanner was presented once using
Psychopy (v1.83.04)(Peirce, 2007) on an LCD monitor (Acer VG248, resolution = 1920×1080,

refresh rate = 60 Hz, whole-body size in the stimuli spanning the visual angle of 13.42 x 8.43
degrees). For each stimulus image, 6 questions were answered either with a 7-point scale (for
implied motion and valence respectively), or with an open answer with free typing (for the
action the actor performed, and the emotion). See **Table S1** for details of the questions. We also
recorded whether the participants changed their perception during the scan (questions 2 and 3).
Four participants changed their perceptions (S4 and S9 for 2 stimuli, S6 for 7 stimuli, S10 for 12
stimuli). We used only the initial perception in the scanner (answer for question 1) for
subsequent analyses. The same stimulus image stayed on the screen for all 6 questions.
Participants answered the questions at their own paces (mean time spent=21.47 min, SD=6.98
min, range: 12.61 to 32.89 min).

Data analysis

Representational similarity analysis (RSA) for behavioral data

For ease of use, we mapped the subjective reports with Deconf word embeddings (Pilehvar and
Collier, 2016), which linked the Word2vec embeddings and the WordNet database. Word2vec
embeddings were trained on a very large corpus of text, able to capture various linguistic
relationships between words (Mikolov et al., 2013). After training, words with similar semantic
meanings were found to be situated closer to each other in the embedding vector space (cosine
distance); although for word2vec, different meanings of the same word were not
disambiguated. On the other hand, WordNet (Miller, 1995) is a curated lexicon database, where
different meanings of each single word were separated, and synonyms were grouped together;
but it does not provide a quantitative mapping for word similarities. Deconf embeddings
mapped the individual word meanings (senses) in WordNet into the 300-dimensional word2vec
vector space, offering us both a common high-dimensional semantic space trained by a large
corpus, and the precise separation of different meanings.

57.8% of the behavioral free reports collected were single words (action: 110/400; emotion:
353/400). For phrases and sentences, we omitted the pronouns (e.g. he is, she is, his, her), as
most of the times participants did not consistently type in the pronouns. The rest of the
words/phrases (nouns, verbs, adjectives, adverbs) that had a corresponding entry in WordNet
3.1 were lemmatized (e.g. stretching→stretch). For words/phrases not found in WordNet 3.1,
"how" was omitted; "something" was substituted by "thing"; "himself/herself/oneself" were
substituted by "self". The adverb "just" associated with verb phrases was omitted (e.g. just
watching→watch). When describing the perceived action, "not sure" was substituted by
"unsure"; when denoting that the participant had no idea about what the person was doing, "no
idea" and "not sure" were substituted by "not applicable". For words with multiple meanings
("senses" the term used in WordNet), the corresponding sense was selected. When a noun
denoting emotion (e.g. "happiness") has both senses of <noun.feeling> and <noun.state>, the
sense of <noun.feeling> was always selected, since this sense was the one mentioning
"emotion". There were very few cases that participants typed in "not". For one case the
participant denoting the emotion of the person in the stimuli "was not sure about something", it
was substituted with the word "unsure". All the other cases were in responses for perceived

actions, about participant's own uncertain understanding for the stimuli. For these and similar
cases we substituted the entry with "not applicable". For all response entries and word lists, see
https://osf.io/cuh9v/?view_only=efb12b7585ee4b6bbcfd7ca42c63b60d.

For each free report entry after lemmatization, the 300-dimension word vector with the
corresponding sense number and sense key were selected from the Deconf pre-trained
embeddings. When an entry has multiple words, the vectors were averaged for this entry. The
RDM for each participant were then computed in cosine distance (reflecting angles between
vectors), as this metric was routinely used for computing word-embedding distances in the
literature. Averaging resulted in the same matrix as addition (the angles didn't change).

The RDMs for behavioral ratings (implied motion, valence) were computed directly from the
ratings, in Euclidean distance.

For predefined RDMs, each category was binary-coded in vectors, with numbers of elements
corresponding to the total number of categories. E.g. for predefined actions, drinking water (2nd
category in 10) was coded as 0 1 0 0 0 0 0 0 0 0; for predefined non-emotion/emotion
categories, emotional ones were coded as 0 1. This coding assumes that each category was
orthogonal to the others. The resulting RDMs were computed in Euclidean distance.

For RDM comparisons throughout the study, the Spearman's correlation was computed
between 40×40 RDMs, with the 780 values below the diagonal of the RDMs as inputs. The
resulting rho values were Fisher's Z transformed, submitted to a one-sample t test against 0
(two-tailed) at the group level. The group-averaged Z values were back transformed to rho
values (or 1 - rho distance) and reported. To assess individual variability, we computed the
coefficient of variation (CV, sample standard deviation/sample mean, in %).

Since all 400 response entries across participants for the perceived action and emotion
representations were in the common 300-dimensional word-vector space, we performed PCA
on the 400 entries respectively for perceived action, and for perceived emotion (without
centering, since the word vectors were all normalized). To see whether predefined categories
were reflected in some dimensions of the subjective representations, the PCA scores for each
principal component (PC) was computed into RDMs (Euclidean distance), and correlated with
400×400 model RDMs. The model RDMs were created in the same way as the 40×40 RDMs, with
the only difference that the 400 entries were sorted by action categories across all participants.
Model RDMs included predefined action, predefined emotion, implied motion, valence,
individual subjects (entries of the same participant were coded as the same vector). The PCA
scores of all response entries were plotted in the two PCs that showed the highest positive
correlation to the model RDMs (**Fig. 1I, J**).

fMRI data Preprocessing

The data were processed with BrainVoyager (version 20.0, 20.2, 21.45, Brain Innovation, Maastricht, the Netherlands), MATLAB (version R2016a), and NeuroElf 1.0 toolbox implemented in MATLAB (http://neuroelf.net/). Before any preprocessing, the functional data underwent in-plane EPI distortion with the COPE plugin (v1.0) in BrainVoyager (https://support.brainvoyager.com/brainvoyager/available-tools/86-available-plugins/62-epi-distortion-correction-cope-plugin). The voxel-wise displacement was estimated between the first volume of each functional run and the first volume of the preceding 5-volume correction run (in reversed phase encoding direction). The in-plane voxel-wise displacement map was then applied to all the volumes of the functional run. The first volume of each run was saved as a separate file, and applied with distortion correction. This volume then served as the basis for subsequent motion correction and across-run alignments. After distortion correction, the functional runs underwent slice scan time correction with the slice timetable information from the scanner (interpolation: sinc), within-run 3D rigid motion correction with each run's first volume as references (interpolation: trilinear for motion estimation, sinc for applying transformations), and temporal high-pass filtering (GLM with Fourier basis set of 2 cycles, including linear trend). The order of distortion correction and motion correction was assessed on S06's sixth (last) main-task run, which has the biggest within-run rotation in all acquired runs in the current experiment (about 3 degrees in the x axis). Between the two processing orders, the resulting 429th volume showed negligible differences in the frontal lobe. Thus we believe the order of distortion correction and motion correction was not critical. For the anatomical data, the magnetic field inhomogeneity was corrected by dividing the T1 images with the PD images. The anatomical data was then spatially normalized into the Talairach space.

To ensure that all functional runs of each participant (6 runs of the main experiment, 2 functional localizer runs, from two scanning sessions, distortion-corrected) were aligned well with each other, we used a manual across-run alignment procedure, with careful visual inspections and multiple iterations/checks. The first volume of the main-task run was aligned to the anatomy, and then saved as an anatomical file in native space, keeping the T2* weighted contrast the same as the original functional run. This served as a "dummy" anatomical run for the subsequent alignment procedure. Then the first volumes of all the functional runs (including the first run itself) were aligned to this dummy anatomical run, and normalized into the Talairach space (with the position information and transformation matrices for the T1 weighted anatomical run). The first volumes of the 8 runs aligned in the Talairach space were then screen-captured and saved as different layers in Photoshop (version CS6, Adobe, United States), toggled on and off, and made into GIF animations to check alignment qualities across runs. Adjustments were made for imperfect aligned runs, followed by the same checking procedure, until there were not any big shifts/translations across runs at the whole-brain level. This procedure allowed us to visually spot tiny alignment imperfections across runs with the same T2* weighted modality. It is much easier than spotting misalignments across T2* weighted and T1 weighted image modalities in the conventional alignment procedure, where the two images look very different across modalities. The quality of the distortion correction was also checked when

aligning the functional run 1 to the anatomy, where a good distortion correction resulted in a
good shape correspondence between the T2* weighted and T1 weighted data. In some cases,
when the participants moved their head between the distortion correction run and the
functional task run, despite our repetitive instructions, the distortion correction quality was
affected. In those cases, we strived for aligning the occipital and temporal lobes.

After alignment across runs, the functional data of the main experiment were then spatially
smoothed with 6 mm FWHM for univariate analysis (comparable to the RSA searchlight radius),
3 mm FWHM for task residual functional connectivity analysis. Due to the individual
anatomical/functional variability, 3 mm was chosen for the functional connectivity analysis, as a
compromise between the 6 mm smoothing and no smoothing, with the former rendering too
extensive connectivity patterns almost covering the whole brain (data not shown), and the latter
rendering too much false negatives (shown in the functional localizer analysis). The unsmoothed
data were used for the (multivariate) representational similarity analysis, and univariate analysis
of 10 categories in RSA searchlight clusters. The static functional localizer data was smoothed at
6 mm FWHM for group random-effect GLM, 3 mm for individual participants, and not smoothed
for univariate analysis in RSA searchlight clusters.

All results in this study were computed in the volume space. For visualizing group-level results,
cortex-based alignments (CBA) were performed to alleviate the high inter-individual anatomical
variability. For each participant, the gray-white-matter boundary of the anatomical images in
Talairach space underwent automatic segmentation, and careful manual correction slice-by-
slice. Then a mesh with a high number of vertices was created for the white-gray-matter
boundary of each hemisphere (number of vertices ranging from 370k to 434k), inflated into a
sphere, corrected for distortions across vertices, and mapped to a high-resolution standard
sphere with down sampling (number of vertices=163842). The curvature patterns of the original
mesh were also smoothed and mapped to the standard sphere. The group-level cortex-based
alignment was separately performed for the left and right hemispheres. For each hemisphere,
the curvature patterns of all 10 participants' meshes were aligned into a dynamic group
average. After aligning, the average left and right hemispheres of the whole group were created.
This resulting group-average brain surface retained many anatomical landmarks, and was more
detailed than the ones usually created with 3T data. However, note that it was a bit smaller than
the actual brain, and was only meant to provide visual landmarks to localize the clusters.

Univariate analysis
To compare the univariate activation to the literature, three different general linear models
(GLMs, serial correlation correction: AR(2), data %-normalized before performing the GLM) were
applied to the datasets smoothed 6 mm FWHM, with the following predictors: 1) 10 action
categories; 2) the behavioral ratings of implied motion; 3) the behavioral ratings of valence. For
2) and 3), the presentation of all stimuli were defined as a single main predictor, the ratings for
40 stimuli were z-scored within each participant, and served as a parametric weight factor to
each corresponding stimulus. The parametric modulation effects were subsequently computed
for 2) and 3). For all the GLM models above, the time courses were %-transformed, the main

predictors were convolved with a two-gamma hemodynamic response function, and the 6
parameters of participant's head motion were z-scored and entered as confounding factors. The
catch trials were marked as a separate condition, and their parametric estimates (beta values)
were not used in subsequent analyses.

The group random-effect GLM analysis was performed for each predictor set. For the 10-
category predictor set, apart from the contrasts between action categories and versus baseline,
a whole-brain ANOVA was performed, with a 10-level factor "action categories". Cluster size
thresholds for all group-level maps in this study were estimated using Monte-Carlo simulation
(alpha level=0.05, numbers of iterations=5000, initial p<0.005 for univariate and RSA searchlight
analyses; initial p<0.001 for task-residual functional connectivity), with the BrainVoyager plugin
Cluster-Level Statistical Threshold Estimator
(https://support.brainvoyager.com/brainvoyager/functional-analysis-statistics/46-tresholding-
multiple-comparisons-problem/226-plugin-help-cluster-thresholding), masked with the common
functional data coverage across 10 participants. This mask was created from the averaged
functional images across participants, covering 830178 functional voxels.

The GLM of the static functional localizer (without smoothing, and smoothed 3 mm FWHM) was
performed for each individual participant. Since we do not assume that the bodies should only
be processed in category-specific areas, the static functional localizer data were used as an
indicator for inter-individual variability, and an indicator for the neural processes in some RSA
searchlight clusters.

Representational similarity analysis for fMRI data
For RSA analyses, the GLM model with 40 stimuli was fitted to each individual participants'
unsmoothed data, resulting in 40 t-maps, one per stimulus. The neural RDMs across the 40
stimuli were computed with Pearson's correlation distance. Searchlight spheres were
constructed for each voxel, with a radius of 5 voxels (515 voxels within the sphere, 889.92 mm^3),
comparable to the value for univariate smoothing (6 mm). Spheres containing more than 172
non-zero voxels were included in the analysis). The Spearman correlation values between the
neural RDM and the model RDM was Fisher-Z transformed, and wrote back to the sphere center
voxel. The group-level significance of the correlation was evaluated by a one-sample t-test
against zero (2-tailed).

For the clusters found by the searchlight RSA and subsequent whole-brain analyses, the
univariate percent signal changes for each of the 10 action categories were extracted (without
smoothing), and were compared to the baseline (one-sample t test against 0) in SPSS.

RSA regression with low/mid-level features
For each of the stimuli image, we extracted the body joint locations by the OpenPose library
(Cao et al., 2019) (https://github.com/CMU-Perceptual-Computing-Lab/openpose). The output
was the x, y values and a confidence score for the estimation, for 18 body joints (See **Figure 4A**).
The joint locations were imported in Adobe Illustrator CS6, overlaid on the stimulus image, and

manually adjusted with visual estimation. The correspondence of the joints and their location
are as follows: joint 1 (head)-nose tip; joint 2 (neck)-the jugular notch of the sternum; joint 3 & 6
(shoulders)-humerus; joint 4 & 7 (elbows)-the connecting point of the upper/lower arms; joint 5
& 8 (hands)-the wrist end of the radial bone; joint 9 & 12 (waist)-the widest points of the femur;
joint 10 & 13 (knees)-on the patella; joint 11 & 14 (feet)-the ankle end of the tibia; joint 15 & 16
(eyes); joint 17 & 18 (ears). Since the eyes were not present on the stimuli images (facial
features blurred), and the ears were often occluded by the hair or by the head, these joints were
visually estimated with linear perspective in mind.

We constructed low-level visual feature RDMs, for raw pixel values (as vectors), and raw
coordinates of the 14 joints (excluding joints for ears and eyes), although the resulting RDMs
were extremely similar to the ones including these 4 joints (RDM similarity rho=0.976, 0.98 for
stimuli set A and B).

The mid-level visual feature RDMs included head, shoulder, waist orientations, as well as
hands/feet-to-head distances. The head orientation was individually computed by the distance
between ears, normalized (divided) by the ear distance of the standing still condition, capped at
1 (1: facing the viewer; smaller than 1: facing left- or right-ward). The shortest hand-to-head
distance may reflect whether the hand enters the head's peripersonal space of the actor; the
average feet-to-head distance may reflect the relaxation of the torso and legs of that actor.

The low- and mid-level visual features were chosen for their theoretical and behavioral
relevance, and their ease for computing/handling. These were only a small subset in an infinite
model space.

For RSA regression in each of the 10-action-category areas (resulted from whole-brain
searchlight analysis of the 10-action-category model RDM), the low/mid-level visual feature
RDMs and the higher-level stimuli attribute RDMs (implied motion, valence, actor identity) were
squared for each element (to satisfy the linearity for squared Euclidean distance values), z-
scored across elements, then put together in the same linear regression model as predictors.
Each element of the neural RDM was also correspondingly squared. A set of beta values for
these predictors were obtained for each participant, and their group-level significance was
examined by one-sample t-test against zero (2-tailed), and FDR-corrected at $q<0.05$ (Storey,
2002) across all predictors for each searchlight cluster.

Task residual functional connectivity analysis
We smoothed the task data at 3 mm FWHM, regressed out the task-related activity by
deconvolution analysis (5 stick predictors per stimulus, covering the evolvement of the BOLD
shape per trial). For each seed region, the residual time course was extracted and averaged
across voxels, and correlated with the residual time courses of all voxels in each run, resulting in
one R map per run. The connectivity pattern across the runs were stable for all participants. The
R maps were Fisher's Z-transformed, averaged across runs per participant, and put in a one-

sample t-test against 0 (2 tailed). The resulting group-level maps were thresholded at p<0.001
for cluster size correction.

For the 10-action-category areas, the inter-area functional connectivity was also examined, by
correlating the seed ROI time courses per run, then again with the same group-analysis
procedure (Z-transform, averaging, t test), with FDR correction.

Hierarchical clustering of RDMs across functional connectivity clusters
We computed neural RDMs for all group-level clusters obtained from the task-residual
functional connectivity analysis (51 ROIs for the perceived action FC network, 76 ROIs for the
perceived emotion FC network), and computed second-level RDMs (Spearman correlation
distance, **Figure 6F**) from them within each participant. For the two FC networks, the second-
level RDM were averaged (with Z-transform) across participants (**Figure 6A, B**, right panels), and
served as inputs for hierarchical clustering (MATLAB function: linkage; method: average. Plot
function: dendrogram; clustering threshold for the most similar areas to the seed region: 0.8).
We also examined the univariate activation for 10 action categories, and plotted histograms.

1132

1133

1134

References

Allison T, Puce A, McCarthy G. 2000. Social perception from visual cues: role of the STS region.
Trends in Cognitive Sciences **4**:267–278. doi:10.1016/S1364-6613(00)01501-1
Amodio DM, Frith CD. 2006. Meeting of minds: the medial frontal cortex and social cognition.
Nature Reviews Neuroscience **7**:268–277. doi:10.1038/nrn1884
Andrews-Hanna JR. 2012. The Brain's Default Network and Its Adaptive Role in Internal
Mentation. *Neuroscientist* **18**:251–270. doi:10.1177/1073858411403316
Aviezer H, Hassin R, Bentin S, Trope Y. 2008. Putting facial expressions back in context. *First
impressions* 255–286.
Barrett LF, Adolphs R, Marsella S, Martinez AM, Pollak SD. 2019. Emotional Expressions
Reconsidered: Challenges to Inferring Emotion From Human Facial Movements.
Psychological Science in the Public Interest **20**:1–68. doi:10.1177/1529100619832930
Binder JR, Desai RH, Graves WW, Conant LL. 2009. Where is the semantic system? A critical
review and meta-analysis of 120 functional neuroimaging studies. *Cereb Cortex*
19:2767–2796. doi:10.1093/cercor/bhp055
Boleda G. 2020. Distributional Semantics and Linguistic Theory. *Annual Review of Linguistics*
6:213–234. doi:10.1146/annurev-linguistics-011619-030303
Bracci S, Op de Beeck H. 2016. Dissociations and Associations between Shape and Category
Representations in the Two Visual Pathways. *J Neurosci* **36**:432–444.
doi:10.1523/JNEUROSCI.2314-15.2016

Brass M, Schmitt RM, Spengler S, Gergely G. 2007. Investigating Action Understanding: Inferential Processes versus Action Simulation. *Current Biology* **17**:2117–2121. doi:10.1016/j.cub.2007.11.057

Buckner RL, Andrews-Hanna JR, Schacter DL. 2008. The Brain's Default Network. *Annals of the New York Academy of Sciences* **1124**:1–38. doi:10.1196/annals.1440.011

Bufacchi RJ, Liang M, Griffin LD, Iannetti GD. 2016. A geometric model of defensive peripersonal space. *Journal of Neurophysiology* **115**:218–225. doi:10.1152/jn.00691.2015

Bullmore E, Sporns O. 2009. Complex brain networks: graph theoretical analysis of structural and functional systems. *Nature Reviews Neuroscience* **10**:186–198. doi:10.1038/nrn2575

Cao Z, Hidalgo G, Simon T, Wei S-E, Sheikh Y. 2019. OpenPose: Realtime Multi-Person 2D Pose Estimation using Part Affinity Fields. *arXiv:181208008 [cs]*.

Caspers S, Zilles K, Laird AR, Eickhoff SB. 2010. ALE meta-analysis of action observation and imitation in the human brain. *Neuroimage* **50**:1148–1167. doi:10.1016/j.neuroimage.2009.12.112

Charest I, Kievit RA, Schmitz TW, Deca D, Kriegeskorte N. 2014. Unique semantic space in the brain of each beholder predicts perceived similarity. *PNAS* **111**:14565–14570. doi:10.1073/pnas.1402594111

Chikazoe J, Lee DH, Kriegeskorte N, Anderson AK. 2014. Population coding of affect across stimuli, modalities and individuals. *Nat Neurosci* **17**:1114–1122. doi:10.1038/nn.3749

Connolly AC, Guntupalli JS, Gors J, Hanke M, Halchenko YO, Wu Y-C, Abdi H, Haxby JV. 2012. The Representation of Biological Classes in the Human Brain. *Journal of Neuroscience* **32**:2608–2618. doi:10.1523/JNEUROSCI.5547-11.2012

Cowen AS, Elfenbein HA, Laukka P, Keltner D. 2019. Mapping 24 emotions conveyed by brief human vocalization. *American Psychologist* **74**:698–712. doi:10.1037/amp0000399

Cowen AS, Keltner D. 2021. Semantic Space Theory: A Computational Approach to Emotion. *Trends in Cognitive Sciences* **25**:124–136. doi:10.1016/j.tics.2020.11.004

Cowen AS, Keltner D. 2020. What the face displays: Mapping 28 emotions conveyed by naturalistic expression. *American Psychologist* **75**:349–364. doi:10.1037/amp0000488

Cowen AS, Keltner D. 2017. Self-report captures 27 distinct categories of emotion bridged by continuous gradients. *PNAS* **114**:E7900–E7909. doi:10.1073/pnas.1702247114

de Gelder B. 2006. Towards the neurobiology of emotional body language. *Nature Reviews Neuroscience* **7**:242–249. doi:10.1038/nrn1872

de Gelder B, Poyo Solanas M. 2021. A computational neuroethology perspective on body and expression perception. *Trends in Cognitive Sciences* **25**:744–756. doi:10.1016/j.tics.2021.05.010

de Gelder B, Snyder J, Greve D, Gerard G, Hadjikhani N. 2004. Fear fosters flight: a mechanism for fear contagion when perceiving emotion expressed by a whole body. *Proc Natl Acad Sci U S A* **101**:16701–16706. doi:10.1073/pnas.0407042101

de Gelder B, Van den Stock J. 2011. The Bodily Expressive Action Stimulus Test (BEAST). Construction and Validation of a Stimulus Basis for Measuring Perception of Whole Body Expression of Emotions. *Front Psychol* **2**:181–181. doi:10.3389/fpsyg.2011.00181

de Lange FP, Spronk M, Willems RM, Toni I, Bekkering H. 2008. Complementary Systems for Understanding Action Intentions. *Current Biology* **18**:454–457. doi:10.1016/j.cub.2008.02.057

DiCarlo JJ, Cox DD. 2007. Untangling invariant object recognition. *Trends in Cognitive Sciences* **11**:333–341. doi:10.1016/j.tics.2007.06.010

DiCarlo JJ, Zoccolan D, Rust NC. 2012. How Does the Brain Solve Visual Object Recognition? *Neuron* **73**:415–434. doi:10.1016/j.neuron.2012.01.010

Dricu M, Frühholz S. 2016. Perceiving emotional expressions in others: Activation likelihood
estimation meta-analyses of explicit evaluation, passive perception and incidental
perception of emotions. *Neuroscience & Biobehavioral Reviews* **71**:810–828.
doi:10.1016/j.neubiorev.2016.10.020
Ekman P. 1999. Basic emotions. *Handbook of cognition and emotion* **98**:16.
Freedman DJ, Riesenhuber M, Poggio T, Miller EK. 2001. Categorical Representation of Visual
Stimuli in the Primate Prefrontal Cortex. *Science* **291**:312–316.
doi:10.1126/science.291.5502.312
Glasser MF, Coalson TS, Robinson EC, Hacker CD, Harwell J, Yacoub E, Ugurbil K, Andersson J,
Beckmann CF, Jenkinson M, Smith SM, Van Essen DC. 2016. A multi-modal parcellation
of human cerebral cortex. *Nature* **536**:171–178. doi:10.1038/nature18933
Goeleven E, De Raedt R, Leyman L, Verschuere B. 2008. The Karolinska Directed Emotional
Faces: A validation study. *Cognition & Emotion* **22**:1094–1118.
doi:10.1080/02699930701626582
Grafton ST, Hamilton AF de C. 2007. Evidence for a distributed hierarchy of action
representation in the brain. *Hum Mov Sci* **26**:590–616.
doi:10.1016/j.humov.2007.05.009
Gratton C, Laumann TO, Nielsen AN, Greene DJ, Gordon EM, Gilmore AW, Nelson SM, Coalson
RS, Snyder AZ, Schlaggar BL, Dosenbach NUF, Petersen SE. 2018. Functional Brain
Networks Are Dominated by Stable Group and Individual Factors, Not Cognitive or Daily
Variation. *Neuron* **98**:439-452.e5. doi:10.1016/j.neuron.2018.03.035
Hartley CA, Poeppel D. 2020. Beyond the Stimulus: A Neurohumanities Approach to Language,
Music, and Emotion. *Neuron* **108**:597–599. doi:10.1016/j.neuron.2020.10.021
Haxby JV, Guntupalli JS, Connolly AC, Halchenko YO, Conroy BR, Gobbini MI, Hanke M, Ramadge
PJ. 2011. A Common, High-Dimensional Model of the Representational Space in Human
Ventral Temporal Cortex. *Neuron* **72**:404–416. doi:10.1016/j.neuron.2011.08.026
Hebart MN, Dickter AH, Kidder A, Kwok WY, Corriveau A, Wicklin CV, Baker CI. 2019. THINGS: A
database of 1,854 object concepts and more than 26,000 naturalistic object images.
PLOS ONE **14**:e0223792. doi:10.1371/journal.pone.0223792
Hein G, Knight RT. 2008. Superior Temporal Sulcus—It's My Area: Or Is It? *Journal of Cognitive*
Neuroscience **20**:2125–2136. doi:10.1162/jocn.2008.20148
Hoemann K, Wu R, LoBue V, Oakes LM, Xu F, Barrett LF. 2020. Developing an Understanding of
Emotion Categories: Lessons from Objects. *Trends in Cognitive Sciences* **24**:39–51.
doi:10.1016/j.tics.2019.10.010
Ju H, Bassett DS. 2020. Dynamic representations in networked neural systems. *Nature*
Neuroscience **23**:908–917. doi:10.1038/s41593-020-0653-3
Kanai R, Rees G. 2011. The structural basis of inter-individual differences in human behaviour
and cognition. *Nature Reviews Neuroscience* **12**:231–242. doi:10.1038/nrn3000
King ML, Groen IIA, Steel A, Kravitz DJ, Baker CI. 2019. Similarity judgments and cortical visual
responses reflect different properties of object and scene categories in naturalistic
images. *NeuroImage* **197**:368–382. doi:10.1016/j.neuroimage.2019.04.079
Kober H, Barrett LF, Joseph J, Bliss-Moreau E, Lindquist K, Wager TD. 2008. Functional grouping
and cortical–subcortical interactions in emotion: A meta-analysis of neuroimaging
studies. *NeuroImage* **42**:998–1031. doi:10.1016/j.neuroimage.2008.03.059
Kret ME, de Gelder B. 2010. Social context influences recognition of bodily expressions.
Experimental Brain Research **203**:169–180. doi:10.1007/s00221-010-2220-8

Kret ME, Pichon S, Grèzes J, de Gelder B. 2011. Similarities and differences in perceiving threat
from dynamic faces and bodies. An fMRI study. *NeuroImage* **54**:1755–1762.
doi:10.1016/j.neuroimage.2010.08.012
Kriegeskorte N, Mur M, Ruff DA, Kiani R, Bodurka J, Esteky H, Tanaka K, Bandettini PA. 2008.
Matching categorical object representations in inferior temporal cortex of man and
monkey. *Neuron* **60**:1126–1141. doi:10.1016/j.neuron.2008.10.043
Langner O, Dotsch R, Bijlstra G, Wigboldus DHJ, Hawk ST, van Knippenberg A. 2010. Presentation
and validation of the Radboud Faces Database. *Cognition & Emotion* **24**:1377–1388.
doi:10.1080/02699930903485076
LeDoux JE, Hofmann SG. 2018. The subjective experience of emotion: a fearful view. *Current*
Opinion in Behavioral Sciences, Emotion-cognition interactions **19**:67–72.
doi:10.1016/j.cobeha.2017.09.011
Lee Masson H, Isik L. 2021. Functional selectivity for social interaction perception in the human
superior temporal sulcus during natural viewing. *NeuroImage* 118741.
doi:10.1016/j.neuroimage.2021.118741
Lindquist KA, Gendron M, Feldman Barrett L, Dickerson BC. 2014. Emotion perception, but not
affect perception, is impaired with semantic memory loss. *Emotion* **14**:375–387.
doi:10.1037/a0035293
Lindquist KA, Wager TD, Kober H, Bliss-Moreau E, Barrett LF. 2012. The brain basis of emotion: a
meta-analytic review. *Behav Brain Sci* **35**:121–143. doi:10.1017/S0140525X11000446
Lundqvist D, Flykt A, Öhman A. 1998. Karolinska Directed Emotional Faces. doi:10.1037/t27732-
000
Mansouri FA, Freedman DJ, Buckley MJ. 2020. Emergence of abstract rules in the primate brain.
Nature Reviews Neuroscience **21**:595–610. doi:10.1038/s41583-020-0364-5
Mikolov T, Chen K, Corrado G, Dean J. 2013. Efficient Estimation of Word Representations in
Vector Space. *arXiv:13013781 [cs]*.
Moeller S, Yacoub E, Olman CA, Auerbach E, Strupp J, Harel N, Uğurbil K. 2010. Multiband
multislice GE-EPI at 7 tesla, with 16-fold acceleration using partial parallel imaging with
application to high spatial and temporal whole-brain fMRI. *Magn Reson Med* **63**:1144–
1153. doi:10.1002/mrm.22361
Molenberghs P, Cunnington R, Mattingley JB. 2012. Brain regions with mirror properties: A
meta-analysis of 125 human fMRI studies. *Neuroscience & Biobehavioral Reviews*
36:341–349. doi:10.1016/j.neubiorev.2011.07.004
Mur M, Meys M, Bodurka J, Goebel R, Bandettini PA, Kriegeskorte N. 2013. Human Object-
Similarity Judgments Reflect and Transcend the Primate-IT Object Representation. *Front*
Psychol **4**. doi:10.3389/fpsyg.2013.00128
Nili H, Wingfield C, Walther A, Su L, Marslen-Wilson W, Kriegeskorte N. 2014. A toolbox for
representational similarity analysis. *PLoS Comput Biol* **10**:e1003553–e1003553.
doi:10.1371/journal.pcbi.1003553
Peelen MV, Atkinson AP, Vuilleumier P. 2010. Supramodal representations of perceived
emotions in the human brain. *J Neurosci* **30**:10127–10134.
doi:10.1523/JNEUROSCI.2161-10.2010
Peelen MV, He C, Han Z, Caramazza A, Bi Y. 2014. Nonvisual and Visual Object Shape
Representations in Occipitotemporal Cortex: Evidence from Congenitally Blind and
Sighted Adults. *Journal of Neuroscience* **34**:163–170. doi:10.1523/JNEUROSCI.1114-
13.2014
Peirce JW. 2007. PsychoPy--Psychophysics software in Python. *J Neurosci Methods* **162**:8–13.
doi:10.1016/j.jneumeth.2006.11.017

Pelli DG. 1997. The VideoToolbox software for visual psychophysics: transforming numbers into
movies. *Spatial Vision* **10**:437–442. doi:10.1163/156856897x00366
Pilehvar MT, Collier N. 2016. De-Conflated Semantic Representations. Presented at the
Proceedings of the 2016 Conference on Empirical Methods in Natural Language
Processing. Association for Computational Linguistics. doi:10.18653/v1/d16-1174
Poyo Solanas M, Vaessen M, de Gelder B. 2020a. Computation-Based Feature Representation of
Body Expressions in the Human Brain. *Cerebral Cortex* **30**:6376–6390.
doi:10.1093/cercor/bhaa196
Poyo Solanas M, Vaessen MJ, de Gelder B. 2020b. The role of computational and subjective
features in emotional body expressions. *Sci Rep* **10**:6202. doi:10.1038/s41598-020-
63125-1
Righart R, de Gelder B. 2006. Context Influences Early Perceptual Analysis of Faces—An
Electrophysiological Study. *Cerebral Cortex* **16**:1249–1257. doi:10.1093/cercor/bhj066
Rizzolatti G, Cattaneo L, Fabbri-Destro M, Rozzi S. 2014. Cortical Mechanisms Underlying the
Organization of Goal-Directed Actions and Mirror Neuron-Based Action Understanding.
Physiological Reviews **94**:655–706. doi:10.1152/physrev.00009.2013
Saxe R, Moran JM, Scholz J, Gabrieli J. 2006. Overlapping and non-overlapping brain regions for
theory of mind and self reflection in individual subjects. *Soc Cogn Affect Neurosci* **1**:229–
234. doi:10.1093/scan/nsl034
Seger CA. 2008. How do the basal ganglia contribute to categorization? Their roles in
generalization, response selection, and learning via feedback. *Neurosci Biobehav Rev*
32:265–278. doi:10.1016/j.neubiorev.2007.07.010
Seger CA, Miller EK. 2010. Category learning in the brain. *Annu Rev Neurosci* **33**:203–219.
doi:10.1146/annurev.neuro.051508.135546
Seghier ML, Price CJ. 2018. Interpreting and Utilising Intersubject Variability in Brain Function.
Trends in Cognitive Sciences **22**:517–530. doi:10.1016/j.tics.2018.03.003
Sinke CBA, Sorger B, Goebel R, de Gelder B. 2010. Tease or threat? Judging social interactions
from bodily expressions. *NeuroImage* **49**:1717–1727.
doi:10.1016/j.neuroimage.2009.09.065
Skerry AE, Saxe R. 2015. Neural Representations of Emotion Are Organized around Abstract
Event Features. *Current Biology* **25**:1945–1954. doi:10.1016/j.cub.2015.06.009
Smith PL, Little DR. 2018. Small is beautiful: In defense of the small-N design. *Psychon Bull Rev*
25:2083–2101. doi:10.3758/s13423-018-1451-8
Stienen BMC, de Gelder B. 2011. Fear detection and visual awareness in perceiving bodily
expressions. *Emotion* **11**:1182–1189. doi:10.1037/a0024032
Stolier RM, Freeman JB. 2016. Neural pattern similarity reveals the inherent intersection of
social categories. *Nature Neuroscience* **19**:795–797. doi:10.1038/nn.4296
Storey JD. 2002. A direct approach to false discovery rates. *Journal of the Royal Statistical
Society: Series B (Statistical Methodology)* **64**:479–498. doi:10.1111/1467-9868.00346
Tucciarelli R, Wurm M, Baccolo E, Lingnau A. 2019. The representational space of observed
actions. *eLife* **8**:e47686. doi:10.7554/eLife.47686
Vaessen M, Abassi E, Mancini M, Camurri A, de Gelder B. 2019a. Computational Feature Analysis
of Body Movements Reveals Hierarchical Brain Organization. *Cerebral Cortex* **29**:3551–
3560. doi:10.1093/cercor/bhy228
Vaessen M, Heijden KV der, Gelder B de. 2019b. Decoding of emotion expression in the face,
body and voice reveals sensory modality specific representations. *bioRxiv* 869578.
doi:10.1101/869578

Van den Stock J, Hortensius R, Sinke C, Goebel R, de Gelder B. 2015. Personality traits predict brain activation and connectivity when witnessing a violent conflict. *Scientific Reports* **5**. doi:10.1038/srep13779

Van Overwalle F, Baetens K. 2009. Understanding others' actions and goals by mirror and mentalizing systems: A meta-analysis. *NeuroImage* **48**:564–584. doi:10.1016/j.neuroimage.2009.06.009

Yeo BT, Krienen FM, Sepulcre J, Sabuncu MR, Lashkari D, Hollinshead M, Roffman JL, Smoller JW, Zöllei L, Polimeni JR, Fischl B, Liu H, Buckner RL. 2011. The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *Journal of Neurophysiology* **106**:1125–1165. doi:10.1152/jn.00338.2011

Yeshurun Y, Nguyen M, Hasson U. 2021. The default mode network: where the idiosyncratic self meets the shared social world. *Nature Reviews Neuroscience* **22**:181–192. doi:10.1038/s41583-020-00420-w

Zhang Y, Han K, Worth R, Liu Z. 2020. Connecting concepts in the brain by mapping cortical representations of semantic relations. *Nature Communications* **11**:1877. doi:10.1038/s41467-020-15804-w

Acknowledgments

This study was supported by the European Research Council, under the European Union's Seventh Frame-Work Programme (FP7/2007–2013)/ERC (grant numbers 295673 to BdG and 269853 to RG), by the ERC-Synergy program grant RELEVANCE (Grant agreement 856495 to BdG), and by the FPN-MBIC funding of Maastricht University to MZ and BdG. MZ was supported by Fondation Bettencourt Schueller. We thank Federico de Martino for setting up the 7T scanning sequences and Giancarlo Valente for providing a part of the searchlight code. We thank Maarten Vaessen for commenting on a previous version of the manuscript.

Author Contributions

Conceptualization: M.Z. and B.dG.; **Methodology, Software, Validation, Formal Analysis, Investigation, Data Curation, Writing – Original Draft, Visualization**: M.Z.; **Resources**: R.G.; **Writing – Review & Editing**: M.Z., R.G. and B.dG.; **Project Administration, Funding Acquisition**: M.Z. and B.dG.; **Supervision**: B.dG.

Declaration of Interests

The authors declare no competing interests.

Data and code availability

The data and codes of this study are available at https://osf.io/cuh9v/?view_only=efb12b7585ee4b6bbcfd7ca42c63b60d, including: stimuli images with body joint estimations, subjective reports and corresponding word embeddings,

1380   whole-brain statistical result maps, ROI raw data for the RSA analysis, structural images and

1381   white-gray-matter-boundary segmentations.