Subjective understanding of actions and emotions involves the interplay of the semantic and action observation networks in the brain

Minye Zhan [1][2], Rainer Goebel [1][3], and Beatrice de Gelder [1][4]*

[1] Faculty of Psychology and Neuroscience, Department of Cognitive Neurosciences, Maastricht University, 6229EV Maastricht, The Netherlands

[2] U992 (Cognitive neuroimaging unit), NeuroSpin, INSERM-CEA, 91191 Gif sur Yvette, France

[3] Department of Neuroimaging and Neuromodeling, Netherlands Institute for Neuroscience, Institute of the Royal Netherlands Academy of Arts and Sciences, 1105 BA, Amsterdam, The Netherlands

[4] Department of Computer Science, University College London, WC1E 6BT, UK

* Corresponding author and lead contact: b.degelder@maastrichtuniversity.nl

Summary

How we subjectively generate an understanding of other people's bodily actions and emotions is not well understood. In this 7T fMRI study, we examined the representational geometry of bodily action- and emotion-understanding by mapping individual subjective reports with word embeddings, besides using conventional univariate/multivariate analyses with predefined categories. Dimensionality reduction revealed that the representations for perceived action and emotion were high dimensional, each correlated to but were not reducible to the predefined action and emotion categories. With searchlight representational similarity analysis, we found the left middle superior temporal sulcus and left dorsal premotor cortex corresponded to the subjective action and emotion representations. Furthermore using task-residual functional connectivity and hierarchical clustering, we found that areas in the action observation network and the semantic/default-mode network were functionally connected to these two seed regions and showed similar representations. Our study provides direct evidence that both networks were concurrently involved in subjective action and emotion understanding.

Keywords: body, action, emotion, subjective report, 7T fMRI, representational similarity analysis

Graphical abstract

Introduction

Imagine you are walking into a large conference hall and you see a person waving in your direction from far away. Within hundreds of milliseconds, this triggers a cascade of implicit and explicit brain processes: "Do I know this person? Is she waving towards me, perhaps to notify me something? Since I don't know her and she seems to be quite happy, is she perhaps waving towards someone close by who might be her acquaintance?" This is an example of the multifaceted information about the action, emotion, intention and identity that human bodies routinely convey, which we process effortlessly in daily life. Our brains extract and combine those various dimensions of information, enabling us to reach a personal/subjective understanding, and to act upon it.

These different dimensions of information have been the focus of specialized lines of inquiry. Univariate studies of action observation have found a fronto-parietal network (action observation network) including the intraparietal sulcus (IPS) and the dorsal and ventral premotor areas (PMd, PMv)(Caspers et al., 2010; Grafton and Hamilton, 2007; Rizzolatti et al., 2014). Studies focused on body forms found body/body parts-sensitive regions in the ventral-lateral pathway, the extrastriate body area (EBA) and the fusiform body area (FBA) (Peelen and Downing, 2007), while the posterior superior temporal sulcus (pSTS) is sensitive to the biological motion of both faces and bodies (Allison et al., 2000). A study addressing the intention aspect of action (de Lange et al., 2008) reported involvement of the inferior frontal gyrus (IFG) for understanding unusual intentions, and involvement of the default mode network (DMN) (Andrews-Hanna, 2012; Buckner et al., 2008) for attending to action intentions in general.

When the body posture and movements convey emotional information, the stimuli trigger activation in areas associated with visual form, action and movement perception, in concert with more emotion-specific areas including the IFG, insula and subcortical structures (Dricu and Frühholz, 2016; de Gelder, 2006; de Gelder et al., 2004; Kober et al., 2008; Lindquist et al., 2012; Molenberghs et al., 2012; Sinke et al., 2010). DMN areas including the temporo-parietal junction (TPJ), precuneus, dorsal/ventral medial prefrontal cortex (dmPFC, vmPFC) (Amodio and Frith, 2006; Saxe et al., 2006), are involved in emotion and valence processing (Chikazoe et al., 2014; Peelen et al., 2010; Skerry and Saxe, 2015), as revealed with multivariate methods such as representational similarity analysis (RSA) (Kriegeskorte et al., 2008; Nili et al., 2014). However univariate activation of DMN areas in action- and emotion-related studies had been scarce, the DMN was considered as a separate system that does not interact with the action observation network (Van Overwalle and Baetens, 2009).

Most previous fMRI studies presented participants with exemplars from a few predefined categories, and often used an explicit action or emotion recognition/categorization task, serving as a proxy for subjective action and emotion understanding. This approach also conforms to the traditional view of a few basic emotions (e.g. Ekman, 1999), assuming that (1) there exist a few discrete categories of actions and emotions that participants are routinely able to recognize; (2) there is high inter-individual similarity in recognizing and identifying these categories; (3) there

is a stable brain-behavior mapping between action and emotion categories and brain processes
across participants.

Under these assumptions, individual variability in perceiving the categories is typically treated as
noise. However, individual variability is prevalent in multiple functions from perception to
cognition, and some individual variability can be linked to the size or function of specific brain
areas (for reviews see Kanai and Rees, 2011; Seghier and Price, 2018). Specifically concerning
action and emotion perception, the first two assumptions of discrete categories and high inter-
individual similarity may not hold either. Different observers may well reach a different
understanding of the action/emotion, depending on factors such as the expressiveness of each
expression (as could often be observed in validation studies for expression databases, e.g.
Goeleven et al., 2008; Langner et al., 2010), the personality of the viewer (e.g. Van den Stock et
al., 2015), and various contexts (for a review see Aviezer et al., 2008; for examples see Kret and
de Gelder, 2010; Righart and de Gelder, 2006). However, the third assumption may still hold.
Different individual behavior may still map to the same neural underpinning, as one fMRI study
found individualized and unique dissimilarity ratings for objects were still represented in the
brain activity patterns in participants' inferior temporal cortices (Charest et al., 2014).

The tendency to treat individual variability as noise was also partially related to the difficulty to
objectively quantify individual variability across participants, especially for the case of verbal
reports. With the advancement of deep neural networks and natural language processing
techniques, word embeddings (see Boleda, 2020 for a review) are now used to describe
semantic concepts in an objective and quantitative way, and recent studies started linking them
to brain activity (Hebart et al., 2019; Zhang et al., 2020).

Recently, researchers argued that studying subjective experiences is important for
understanding the high-level cognitions such as emotion, language, and music (Hartley and
Poeppel, 2020; LeDoux and Hofmann, 2018). The presence of subjective variability in emotional
perception and production is also acknowledged in the recent literature (for a review for facial
expressions, see Barrett et al., 2019; for a review for more general emotional stimuli, see Cowen
and Keltner, 2021). In response to these challenges, new studies utilized very large stimulus sets,
subjective reports, and the associated semantic space (Cowen and Keltner, 2017, 2020, 2021;
Cowen et al., 2019). Results indicated that for the subjective experiences elicited by facial, vocal,
musical emotional expressions, over 20 emotional categories could be observed in the
subjective reports for some modalities. There were no discrete category boundaries, and the
semantic space of these categories was also high-dimensional. The brain-behavior mappings of
such rich emotion representations seen in subjective reports were largely uncharted,
independent from the pre-defined basic categories.

In this high-resolution 7T fMRI study (1.2 mm isotropic resolution, voxel volume = 1.728 mm^3)
with RSA (Kriegeskorte et al., 2008; Nili et al., 2014), our goal was to address both sides, the
subjective understandings of actions and emotions, and the researcher-defined action and
emotion categories. During functional runs, 10 participants passively viewed a large stimulus set

of 10 predefined bodily action categories (6 neutral, 4 emotional categories; each participant
viewed 40 stimuli). Immediately following the scanning session, participants provided free
reports of the subjectively perceived action and emotion for each stimulus.

We first examined the representational geometry of the subjective behavioral reports by
principal component analysis (PCA) and RSA, after mapping all subjective report entries into a
common vector space using Deconf word embeddings (Pilehvar and Collier, 2016). Then we
examined the neural representations for predefined categories with RSA searchlight and RSA
regression. There we estimated the body joint positions using the OpenPose library (Cao et al.,
2017), and computed low- and mid-level visual features. Lastly, we examined the relation
between subjective reports and brain activity. We searched for the subjective representations in
individual participant data by RSA searchlight, and examined their putative direct
upstream/downstream areas by task-residual functional connectivity and hierarchical clustering.
We found neural representations for perceived action and perceived emotion, and the two
analyses with predefined categories and with the subjective reports converged as they both
indicated joint involvement of the action observation network and the DMN/semantic network.

Results

RDM construction

In the scanning session, participants passively viewed 40 gray-scale images from one of two
balanced stimuli sets (**Fig. 1A.** See **Fig. S1** for the complete sets of stimuli). We used a slow
event-related design, where each image (2.60 x 4.26 degrees) was presented for 500 ms,
followed by an inter-stimulus interval of either 7.5, 9.5 or 11.5 s. Each image was presented 12
times.

In the behavioral session directly after the fMRI scan, for each stimulus image, participants
reported their subjective understanding of the action and emotion by typing a short description,
and rated the implied motion and valence on a scale of 1 to 7 (See **Table S1** for the exact
questions, and examples of participants' free reports).

Individual reports were analyzed by mapping all response entries to the same high-dimensional
space using the pre-trained Deconf word embeddings (Pilehvar and Collier, 2016), which
combined the word2vec word embeddings and the WordNet database (see Methods for
details). Specifically, we lemmatized all the verbs, nouns, adjectives, adverbs typed in by the
participants (e.g. fighting/fights→fight), and selected the corresponding meaning for each word
in WordNet 3.1 (https://wordnet.princeton.edu/). We then retrieved the corresponding 300-
dimensional vectors from Deconf embeddings, averaged the word vectors in each response
entry, and computed RDMs for perceived action and perceived emotion (cosine distance) for
each individual participant, see **Fig. 1Bab** and **1Cab**.

Implied motion and valence ratings were one-dimensional attributes provided by individual
participants, which were related respectively to the action and emotion aspects of each
stimulus. These RDMs were computed directly from the individual behavioral ratings (Euclidean
distance, **Fig. 1Bcd, Ccd**).

For predefined categories (10 action categories, non-emotional/emotional actions), we followed
the RSA and perceptual categorization literature and constructed model RDMs (Euclidean
distance, **Fig. 1B**, first column), assuming that the stimuli representations were similar within
categories, but were different across categories between stimuli (e.g. Freedman et al., 2001).

We examined the correlations of the subjective report and the rating RDMs with the two
predefined RDMs. Throughout the whole study, correlations between RDMs were computed
with Spearman correlation, and submitted to a one-sample t test against 0 (two-tailed) at the
group level, after Fisher's Z transformation.

Perceived categories largely corresponded to the predefined ones, but with considerable individual variability

All four subjective report and rating RDMs were significantly correlated to the predefined ones
(one-sample t test against 0; coefficient of variation, CV, showing inter-individual variability),
perceived action to predefined action RDMs: mean rho=0.324, $p=8.55\times10^{-8}$, CV=20.4%;
perceived emotion to predefined emotion RDMs: mean rho=0.491, p=0.000164, CV=51.2%;
rated implied motion to the predefined action RDMs: mean rho=0.166, p=0.000541, CV=60.4%;
rated valence to the predefined emotion RDM: mean rho=0.496, $p=5.91\times10^{-7}$, CV=25.5%. This
indicates that the individual subjective understanding largely corresponded to the predefined
categories, especially for emotions, although there was considerable individual variability (**Fig.
1C, D**).

We then examined the individual variability, to assess whether it is suitable to use group-
averaged RDMs to perform further analyses in individual participants. We first obtained a group-
averaged RDM from all 10 individual RDMs, then computed its Spearman correlation to each
individual RDM (one-sample t test against 0; CV). When inter-individual consistency is high, the
group-averaged RDM should have high correlation to each individual RDM, and a low CV. For
valence, the group-averaged RDM was very consistent with individual RDMs: mean rho=0.900,
$p=6.91\times10^{-8}$, CV=19.9%. However, the other 3 group-averaged behavioral RDMs were less
consistent with individual RDMs, again showing considerable individual variability: perceived
action RDM: mean rho=0.517, $p=4.74\times10^{-6}$, CV=32.7%; perceived emotion RDM: mean
rho=0.565, $p=6.02\times10^{-5}$, CV=44.9%; rated implied motion RDM: mean rho=0.621, $p=8.71\times10^{-5}$,
CV=47.1%. With these moderate correlation coefficients, indicating less tight brain-behavior
links for individual participants, using group-averaged RDMs in subsequent analyses may be less
suitable to capture the individualized neural substrates. It was also the case for the pre-defined
categories.

On the other hand, analyses based on the individual subjective responses may better capture
the individual neural processes, because the neural activity and patterns generating these
individualized subjective reports (behavioral outputs) may still map to brain locations in a
consistent and meaningful way. If the neural processes found this way are robust and consistent
enough, individual-level replication can be achieved (Smith and Little, 2018). Adopting this logic,
our subsequent analyses looked at the mapping of subjective reports to brain activity, and
accordingly focuses on individual-level data and results.

The perceived action and emotion representations are high-dimensional

For investigating perceived action and perceived emotion, we examined the high dimensional
space of all responses using principal component analysis (PCA), since all 400 subjective
responses were in the same high-dimensional space, each represented by a 300-dimensional
vector.

The first few principal components (PCs) for the perceived action and perceived emotion
representations captured a large amount of variance (First 10 PCs: 86.17% and 89.63% variance;
first 50 PCs: 97.76% and 99.18% variances, **Fig. 1F, G**, analysis performed on 1^{st} to 50^{th} PC for
both representations).

The perceived action representation RDM showed considerable individual variability when
compared to the 10-action-category model (**Fig. 1Ea, Ga**). The first and biggest few components
did not show clear separation of action categories. Instead, individual variability was more
prominent (**Fig. 1H**), while it remains elusive what accounts for the majority of the variance in
PC 1. Only the later and much smaller PCs were correlated more to the 10-action-category
model (7^{th}, 9^{th}, 10^{th} PCs), the non-emotion/emotion model (7^{th}, 22^{nd}, 6^{th} PCs), and the implied
motion ratings (6^{th}, 10^{th}, 18^{th} PCs), and also showed relatively clear category separations (**Fig.
1H, I**). The presence of smaller PCs correlated to the action categories, emotions and implied
motion ratings indicates that the perceived action representation is rich and high-dimensional. It
potentially supports extracting the relevant categorical and continuous information, but it is not
equivalent and not reducible to one of the predefined category structures.

The perceived emotion representation was lower-dimensional than the perceived action
representation (79 versus 174 independent PCs), and showed higher inter-individual consistency
(**Fig. 1Eb, Gb**, much lower correlation value to the individual subject model in **Fig. 1H**). The first
few PCs showed a moderate correlation to the non-emotion/emotion model and valence
ratings, and even to the 10-action-category model (**Fig. 1H, J**). Interestingly, visual inspection of
the RDMs showed that the perceived emotion representation contained the separation of non-
emotion and emotion categories (**Fig. 1Eb**, PC1 and 2 in **Fig. 1Gb**), but also contained finer-
grained separation for individual emotions. These were captured by the 3^{rd}, 4^{th} and 6^{th} PCs,
corresponding to happy, fearful and sad (**Fig. 1Gb**, see the locations of the prominent white/red
bars across all conditions, showing similarity within the category and dissimilarity to the other 9
categories). In the 3^{rd} and 4^{th} PC, the angry emotion could further be separated. This indicates

that the perceived emotion representation is also a high-dimensional one; brain areas
containing such representations could potentially support both the non-emotion/emotion
categorization, and categorization of each individual emotions.

Figure 1. The representational geometries of subjective reports were high-dimensional, and
showed considerable individual variability.

A. Stimuli examples of 10 action categories, performed by one of 8 actors. Category
abbreviations: CH: combing hair; DW: drinking water; OD: opening door; PH: phone; TR: putting
on trousers; NE: neutral standing still; FE: fearful; AN: angry; HA: happy; SA: sad.
B. RDMs for predefined categories, perceived categories, ratings, averaged across 10
participants (40 by 40 matrices, correlation distances 1-r, all diagonals were 0, sorted by the 10
action categories). The group-averaged RDMs showed correspondence to the predefined RDMs.
a. perceived action; **b.** perceived emotion; **c.** rated implied motion; **d.** rated valence. In **B**, **C**, **E**,
G: blue color: similar; red color: dissimilar. For all RDMs, the color ranges were scaled
automatically by the minimal/maximal values within each RDM.
C. RDMs for individual participants showed considerable individual variability. RDM types **a** to **d**
correspond to **a** to **d** in **B**. Each column corresponds to one participant. The left 5 participants
viewed stimulus set A, the other 5 viewed set B.
D. Correlation coefficients for individual participants were not high. **a.** perceived action
correlated to the 10- action-category model; **b.** perceived emotion correlated to the non-
emotion/emotion model; **c.** implied motion ratings correlated to the 10-action-category model;
d. valence ratings correlated to the non-emotion/emotion model. Black bars: group average.
E to **J**. PCA results of all 400 behavioral report items for perceived action and perceived emotion.
The smaller PCs of the perceived action and the first PCs of the perceived emotion showed
correspondence to the predefined RDMs.
E. Same to **B**, but for all 400 behavioral report items across participants (400 by 400 matrices).
F. The first 10 principal components (PCs) explained a large amount of variance. Curves:
cumulative explained variance (%).
G. RDMs for scores of the first 10 PCs (Euclidean distance), for perceived action (**a**) and
perceived emotion (**b**).
H. RDMs the first 50 PCs, correlated to the predefined action, emotion models, behavioral rating
models, and to the individual subject model. The first PCs of the perceived action correlated
more to the individual subject model. Gray bars: non-significant correlation values (FDR q>0.05).
I. Perceived action report items, plotted against the first two PCs, and against the two PCs with
highest correlation coefficients to each of the models.
J. Perceived emotion report items, plotted against the first two PCs, and against the two PCs
with highest correlation coefficients to each of the models. Fewer dots were shown on the plots,
because some items have overlapping values.

Univariate results were consistent with the literature

For the fMRI data, as a sanity check, we first performed conventional group-level univariate
analysis with data smoothing, for the 10 action categories (input for the participants), and
parametric modulations for implied motion and valence. The 7T data was very robust: the
activation location and time course profiles at 7T were similar to 3T ones, but showed higher %-
signal change (See **Figure S2**).

The 10-category one-way ANOVA showed differences across action categories in bilateral EBA,
right FBA, right lateral occipital cortex (LOC) and right mIPS (**Fig. 2A**). Similarly, the parametric
modulation of implied motion showed higher activity for actions rated with higher implied
motion, in bilateral EBA, right mIPS, left pIPS, right rostral cingulate zone (RCZ), where the
former 3 overlapped with the ANOVA clusters (**Fig. 2B**).

When contrasting emotional and non-emotional categories (excluding the standing-still
condition), the left IFG and left middle temporal gyrus (MTG) showed higher activity for
emotional categories, while early visual areas (EVC) and right precentral gyrus showed higher
activity for non-emotional categories (**Fig. 2C**). The activation map was very similar when
including the standing-still condition. These univariate results were consistent with previous
findings (Dricu and Frühholz, 2016; de Gelder et al., 2004; Kober et al., 2008; Molenberghs et al.,
2012; Sinke et al., 2010). However, for the parametric modulation of valence, we only observed
clusters modulated by positive valence, but not for ratings of negative valence (negative
modulation). These clusters were found outside the frontal lobe, in bilateral early visual cortices
(including bilateral V3a and right calcarine sulcus/cuneus), right posterior collateral sulcus, right
supramarginal gyrus, left precentral gyrus/central sulcus (**Fig. 2D**).

We cannot exclude that some of these may be false negatives due to the exacerbated inter-
individual variability at 7T, where activation clusters were small, and were constrained to the
gray matter even after spatial smoothing. This effect could be observed in the functional
localizer data: despite that we found robust EBA, FBA, FFA clusters in all individual participants
(data smoothed 3 mm FWHM, contrasts: bodies>faces, houses, tools, words; faces>bodies,
houses, tools, words), and the activation sites were reliable in one participant between 3T and
7T scans on different days (**Figure S2**), the across-participant overlapping of these clusters were
low; the group-level GLM (data smoothed 6 mm FWHM) only showed an R EBA/pSTS cluster for
bodies, L EVC and bilateral precuneus clusters for faces (**Figure S3**). Thus for whole-brain
activation and searchlight analyses, we used the initial p threshold of 0.005 to balance between
the false positives and false negatives.

Figure 2. Univariate results were consistent with the literature. Data in volume space were plotted on the group-aligned surface mesh after cortex-based alignment. Functional data were smoothed at 6 mm FWHM, all maps were cluster-size thresholded with Monte-Carlo simulation, alpha=0.05, n simulations=5000. We used the initial p<0.005 to alleviate the false negatives due to high anatomical inter-individual variability, which was clearly observed in our functional localizer data.

A. ANOVA of 10 categories. Color bar p range: 0.005 to 0.0001.

B. Parametric modulation of rated implied motion.

C. Emotional categories > non-emotional categories (excluding neutral standing still).

D. Parametric modulation of rated valence. Color bar p range in **B, C, D**: 0.005 to 0.0005.

Cluster size thresholds in **A** to **D**: 115, 55, 46, 56 functional voxels.

Predefined non-emotion/emotion and 10-action-category representations in the brain

Next we followed the conventional predefined-model-driven approach, basing the models on the predefined action and non-emotion/emotion categories, and performed RSA searchlight analysis for those RDMs. We constructed neural RDMs from univariate t maps of the 40 individual stimuli (no smoothing for functional data, Pearson's correlation distance), and performed RSA searchlight (radius=5 voxels; Spearman correlation to the predefined category RDMs, one-sampled t test against 0 for the Fisher's Z-transformed rho values at the group-level, cluster size thresholded at alpha of 0.05, Monte-Carlo simulation n=5000). The same group-level test and cluster thresholding scheme was used for all searchlight analysis throughout the study.

For the predefined non-emotion/emotion categories, we found two areas positively correlated to the model RDM, in L central sulcus (adjacent to the cluster found in parametric modulation

for valence ratings in the univariate analysis, in **Fig. 2D**), and R PMd/FEF (**Figure 3B**). Another
four areas showed negative correlation to the RDM, in L precuneus, L caudal cingulate zone,
bilateral medial SFG, and L thalamus, indicating fine-grained processing for stimuli within the
non-emotion or emotion categories.

We found 29 brain areas positively correlated to the 10-action-category RDM (**Figure 3A, S4**,
Table S2, denoted "10-action-category areas" below), and no negatively-correlated areas. When
thresholding at p<0.001, eight of these areas were still present, including the R cuneus, R
EBA/hMT+, L central sulcus, L precuneus, R posterior cingulate gyrus and sulcus, bilateral medial
superior frontal gyrus, anterior RCZ. Some of these 10-action-category areas consistently
showed univariate activation in body or action perception, including R EBA/hMT+, L pIPS and L
RCZ; but several areas did not show above-baseline univariate activation at the group level,
including L central sulcus, R anterior SFS, R cerebellum, L vmPFC and bilateral medial SFG (**Figure
S5, Table S3**).

We next examined the task-residual functional connectivity, which presumably reflects
information transfer, and displays certain levels of consistency with structural connectivity
(Bullmore and Sporns, 2009), and thus could potentially capture the direct
upstream/downstream areas for a seed area. Using these 29 areas as seed regions, we observed
fine-grained connectivity patterns for each seed region, showing hemispheric symmetry. These
areas were highly interconnected, and were also connected to the action-observation-related
areas (EBA, FBA, IPS, pSTS, SMA, PMd, PMv, M1, cerebellum), and DMN areas (dmPFC, vmPFC,
precuneus, TPJ, mSTS). Furthermore, most areas were heavily connected to bilateral caudate,
putamen and thalamus; and 14 out of 29 areas were connected to the hippocampus. See
supplementary **Figure S6** for a summary of their connectivity patterns.

Figure 3. Searchlight RSA showed multiple areas correlated to the predefined category models.
A. Results for the 10-action-category RDM, cluster size threshold=43 voxels. The labeled areas
were ones overlapped with the perceived action and emotion FC networks. **B**. Results for the
non-emotion/emotion RDM, cluster size threshold=35 voxels. The areas labeled were ones with
positive correlations to the RDM. Color bar p range in both **A** and **B**: 0.005 to 0.0005. Cluster size
thresholds: 43, 35 functional voxels. Initial p<0.005.

The representations of low- or mid-level visual features and higher-level attributes

We used the predefined 10 action categories to search for brain areas with corresponding
"category boundaries". However, these category boundaries in the brain may not only be
generated by higher-level abstractions between categories, but could also be generated by
lower-level visual feature differences between the stimuli. For our stimuli set, since the actors
received a fixed set of instructions for performing the actions (Stienen and de Gelder, 2011), the
postures may be somewhat stereotypical (see all stimuli in **Figure S1**), where low- or mid-level

visual features alone could contribute to clear category boundaries, but co-vary with the
abstract categories. Therefore, some of the brain areas found by the 10-action-category RDM
may correspond to the low/mid-level visual features.

To examine this possibility in the 10-action-category areas found by searchlight, we performed
RSA regression, using the RDMs of higher-level stimuli attributes and low- or mid-level visual
features as predictors. The higher-level stimuli attributes included non-emotion/emotion,
implied motion, valence, and actor identity. The low level features included the raw pixel values
of each stimulus picture, and the body joint coordinates, extracted from each stimulus picture
by the OpenPose library (Cao et al., 2019). The mid-level visual features were computed from
the body joint coordinates and based on suggestions from the literature: The body-part
orientations may signal the directions of social interactions; the hands/feet-to-head distances
may be related to the peripersonal space (Bufacchi et al., 2016) and the relaxation of the
arms/legs. Most of the low- mid-level RDMs indeed correlated to the 10-action-category RDM
(rho ranging from 0.08 to 0.36), apart from the raw pixel value and head orientation RDMs. See
Figure 4A, B. We acknowledge that these RDMs were only a very limited set from an infinitely
vast model space. All RDMs were put in the same linear model, so that the unique contribution
of each RDM could be examined.

We found that some of these stimulus features and attributes could partially explain the activity
in some of the 10-action-category brain areas. For the low-level features, the raw pixel values
representation could be found (with a positive beta estimate significantly bigger than 0) in R
cuneus and R CCZ, but showed a negative beta estimate in R SPOC; the raw joint coordinates
representation could be found in R EBA, but showed a negative beta estimate in R callosal
sulcus. For mid-level features, the head orientation representation could be found in R SPOC,
while showing a negative beta estimate in R dmPFC; the shoulder orientation representation
was found in L pIPS, and the shortest hand-head distance representation in R cerebellum. For
higher-level attributes, only the actor identity representation showed a positive beta estimate in
again the R SPOC, and a negative beta estimate in R cuneus.

We then performed whole-brain searchlight analysis for these attributes and features (**Figure 4**
C to **G**). For high-level features, we did not find areas positively correlated to the valence rating
RDMs, which may either correspond to a true negative, or a false negative due to again the
inter-individual anatomical variability. The implied motion rating RDMs showed positive clusters
in L FEF (adjacent but not overlapping with the L PMd cluster for perceived emotion) and R
SPOC. And interestingly, the actor identity RDM showed a positive cluster in L MTS, close to EBA
and FBA.

We found positive clusters for two mid-level visual features: head orientation and shortest
hand-to-head distance, but no positive clusters for any other low- or mid-level visual features,
despite their similarity to the two features with positive clusters (shoulder and waist orientation
RDMs were correlated to the head orientation RDMs: rho ranges from 0.317 to 0.412; the
shortest hand-to-head distance RDMs were correlated to the average hand-to-head distance

RDMs, rho=0.593, 0.646 for stimuli set A and B). This indicated that these two features may be
biologically meaningful ones for the brain.

Figure 4. Low/mid-level features (**A** and **B**), and whole-brain searchlight results corresponding to
these features (**C** to **G**).
A. Skeleton in the left panel: coordinates of the 18 joints extracted by the OpenPose library;
white dots in the middle panel: joint coordinates after manual adjustment; right panel, magenta
lines: distances used to compute head, shoulder, waist orientations, normalized by the
corresponding distances in the neutral stand-still stimulus of the same actor (see middle panel);
green lines: hand/foot-to-head distance.
B. The low/mid-level features, showing RDMs for stimuli set A. The raw coordinates RDMs were

computed excluding joints on the ears and eyes, but was very similar to the ones computed
including these joints (RDM similarity rho=0.976, 0.98 for stimuli set A and B). Most of these
RDMs correlated to the 10-action-category RDM.
C, D, E. Searchlight results for higher-level attributes. The valence RDM did not show positively
correlated clusters. Cluster size thresholds: 38, 44, 31 functional voxels.
F, G. Searchlight results for mid-level features that showed clusters positively correlated to the
corresponding RDMs. Cluster size thresholds: 48, 37 functional voxels.
Color bar p range in **C** to **G**: 0.005 to 0.0005. Initial p<0.005. Clusters showing positive
correlations to the corresponding RDMs were labeled. In **D**, clusters showing negative
correlations (fine-grained processing with similar valence rating) were also labeled.

RSA searchlight analysis revealed representations for perceived action in left mSTS and for perceived emotion in left PMd

We next turned to the individual subjective reports, and searched for neural representations similar to the individualized perceived action and emotion RDMs. We found one positively correlated cluster for each of the subjective report RDMs, in left mSTS for perceived action, and in left PMd for perceived emotion, indicating that these two areas may be involved in subjective understanding and reporting for action and emotion, respectively. The L PMd cluster is consistent with the analysis based on predefined non-emotion/emotion representation, where the R PMd/FEF cluster was at a very similar location on the other hemisphere to the PMd cluster found here.

All other clusters were negatively correlated to the subjective category RDMs, indicating fine-grained processing for similarly perceived actions or emotions within those clusters. For perceived action, the negative clusters include L RCZ and R supplementary motor area (SMA), which were implicated in action observation in the literature (Caspers et al., 2010). For perceived emotion, the negative clusters included R SMG/aIPS and R cerebellum for action observation, R insula for emotion processing, and mentalizing areas of R precuneus, R vmPFC, R dmPFC/medial superior frontal gyrus (mSFG). See **Figure 5** and **TableS4** for the complete list of clusters.

The L mSTS and L PMd clusters did not show reliable univariate activation for the 10 action categories (one-sample t test of percent signal change against baseline, all p>0.052, except in L PMd for the Anger category, p=0.031), thus they could not be found by conventional univariate analysis. Neither was the 10-category univariate ANOVA significant in these two clusters, p=0.309 and p=0.945 respectively.

Figure 5. Searchlight RSA revealed corresponding clusters to the perceived action model in L
mSTS **(A),** and to the perceived emotion model in L PMd **(B)**. Color bar p range: 0.005 to 0.0005.
Cluster size thresholds in **A** and **B**: 39, 38 functional voxels. Initial p<0.005.

The putative direct upstream/downstream areas of L mSTS and L PMd identified by task residual functional connectivity and hierarchical clustering

The L mSTS and L PMd clusters were found by their representation similarity to individualized,
subjectively reported actions and emotions, which already showed considerable individual
variability. Thus, to further understand the involvement of these two areas in the current task,
we could no longer use the standard predefined-model comparison methodology, which
compares neural RDMs to a same model RDM, assumed by the researcher. Instead, we used a
data-driven approach based on two assumptions: (1) We could potentially capture the
information transfer stages of a certain area by functional connectivity; (2) Based on the idea
that the object representations were successively re-represented and "untangled" in the ventral
visual pathway (DiCarlo and Cox, 2007; DiCarlo et al., 2012), we assumed that this would be the
case for bodily action and emotion representations throughout the brain, that the information
(in our case the neural representations) should be gradually transformed across a chain or
network of brain areas, from the representation of the visual input, to the representation of the
subjective output, without sudden changes between two adjacent stages in the information-

transfer chain. In this way, we linked the functional connectivity and representational analyses
together (also see Ju and Bassett, 2020). To find the set of brain areas in the same information-
transformation chain, we performed task-residual functional connectivity to the L mSTS seed
and the L PMd seed, respectively. Using hierarchical clustering in the two resulting networks, we
could then find areas with most similar neural representations to the two seeds, which may
include their direct upstream/downstream areas.

Task-residual functional connectivity
We regressed out the individual stimuli and head motion parameters from the functional data
(deconvolution, data smoothed at 3 mm FWHM), obtained task-residual time courses, and
performed functional connectivity (FC) analysis (Pearson's correlation), with L mSTS and L PMd
as seed regions. See **Figure 6A, B, left panels**. This analysis revealed two partially overlapping FC
networks for action/emotion understanding at the group level (**Figure 6D**), in action observation
related areas including (bilateral if unspecified) IPS, M1, PMd, PMv, L IFG; and in DMN areas
including TPJ, mSTS/MTG, precuneus, posterior cingulate cortex, dmPFC/vmPFC, mSFG, parietal
occipital cortex (POC), retrosplenial cortex.

Interestingly, some overlapping areas in these FC networks are part of the semantic network,
including mSTS, IFG, TPJ/angular gyrus, dmPFC, vmPFC, posterior cingulate cortex, retrosplenial
cortex (Binder et al., 2009); and the L mSTS FC network corresponded to the semantic network
especially well. See **Figure 6D** and **E**. The seed cluster L mSTS itself is an important area in the
semantic network, which could be activated by written word stimuli (Binder et al., 2009).
Although word-specific clusters around left mSTS were found in individual participants in the
functional localizer data (words>other categories), neither the seed region nor the more
extended FC cluster around the seed showed consistent group-level activation for words in the
functional localizer (one-sample t test against 0, L mSTS seed ROI: mean beta=0.589; t(9)=1.418;
p=0.190; L mSTS FC cluster: mean beta=0.369; t(9)=1.226, p=0.251), which could again be due to
the inter-individual anatomical/functional variability. More interestingly, although both FC
networks overlapped at the L mSTS, the cluster for perceived emotion was much more posterior
than the one for the perceived action, which corresponded to previous findings that the STS is
an heterogeneous structure with several different functions (Hein and Knight, 2008).

In addition to the cortical clusters, the FC analysis revealed bilateral caudate and putamen
clusters in both FC networks (**Figure S7, S8**), which may be involved in categorization processing
(Seger, 2008; Seger and Miller, 2010). The left mSTS was further functionally connected to the R
hippocampus; the left PMd was further functionally connected to the bilateral thalamus,
pulvinar, cerebellum, the R septal nuclei, and the bilateral red nuclei (anatomical locations
clearly observable in the T2*-weighted functional images, **Figure S8**). The involvement of the
hippocampus, the septal nuclei and the red nuclei in bodily action and emotion understanding
were not routinely observed in previous bodily-action perception studies with univariate
methods.

The perceived action and emotion FC networks also overlapped with some of the clusters that
negatively correlated to the perceived action/emotion RDMs in the searchlight analysis (**Figure**
3). They include R mSFG in the perceived action FC network; R posterior cingulate gyrus/callosal
sulcus, R EVC, R lingual gyrus/cerebellum in the perceived emotion FC network. This indicates
that subjective category-like processing and fine-grained within-category processing could be
mediated within the same networks.

Furthermore, the perceived action FC network overlapped with the 10-action-category clusters
in the L central sulcus, R POC/retrosplenial cortex and bilateral callosal sulci; while clusters in the
perceived emotion FC network overlapped with the 10-action-category clusters in L precuneus, L
pIPS, L cingulate sulcus, R SFS, R posterior cingulate/POC/retrosplenial cortex, R caudate, R
cerebellum and bilateral medial SFG (labels in **Figure 3**), again showing consistency to the
analysis based on predefined categories.

Hierarchical clustering
We then examined the possible direct upstream/downstream areas of the two seed regions,
which should show the most similar neural representations to the seeds. We performed
hierarchical clustering to all clusters within each FC network, on the group-averaged second-
level neural RDMs across areas (Spearman correlation distance, hierarchical cluster linkage
arbitrarily thresholded at 0.8). Since both seed regions were encompassed by more extensive
clusters with the shortest hierarchical clustering distance to the seed (cluster in the perceived
action FC network: spanning L mSTS, MTG and ITS; cluster in the perceived emotion network: an
extensive one spanning L PMd, PMv and LR medial SMG), we plotted the extensive clusters
(denoted as "seed clusters" below) instead of the seed regions themselves, in the dendrograms
and second-level RDMs. See **Figure 6A, B, Figure S9.**

In the perceived action FC network, the FC cluster with the most similar representation (shortest
distance in the dendrogram) to the seed cluster was one spanning L p/mIPS, TPJ, angular gyrus.
The other areas under the same branch of the dendrogram were: the R mSTS contralateral to
the seed; action-perception related areas including bilateral PMv, MFG, L PMd, L IFG;
DMN/semantic areas including L precuneus, R TPJ, L posterior cingulate gyrus, LR dmPFC, LR and
medial SFG.

In the perceived emotion FC network, the FC clusters with the most similar representation to
the seed cluster was one spanning R PMd and MFG, contralateral to the seed. The other FC
clusters in the same branch were: L pSTS, MTG, R pSTS, action-perception related areas
including bilateral IPS, IPL, angular gyrus, L IFS, IFG; DMN/semantic areas including L TPJ,
bilateral precuneus, POC; also the lateral and anterior prefrontal cortices including bilateral
MFG, anterior MFG, L MFS, R SFS.

These clusters may be directly involved in understanding the bodily actions and emotions. In
both FC networks, it is interesting to observe the strong involvement of both action-perception

related areas and DMN/semantic areas, showing symmetry across hemispheres. Especially for
the DMN/semantic areas, their direct involvement in bodily action/emotion understanding and
interactions with the action-perception related areas were not reported in previous studies. This
may be due to the observation that most of the areas in the two FC networks did not show an
activation level different from baseline (one-sample t-test of beta values per action condition
against baseline, FDR corrected across the 10 action categories per ROI). See **Figure 6A, B, C**.
Thus, they were not likely to be localized when using only univariate methods.

The clustering in individual participants was relatively consistent, with moderately correlated
second-level matrices across participants (averaged Spearman Rho, perceived action: 0.418,
SD=0.0473; perceived emotion: 0.374, SD=0.0578). See **Figure 6F**. Apart from the clustering
showing high similarity to the seed clusters in every participant (upper-left side of each RDM),
there appeared to be another prominent clustering of areas in each of the two FC networks of
individual participants (27-32nd areas in the perceived action FC RDM, 36-51st areas in the
perceived emotion FC RDM, both in the middle of the RDMs, see an enlarged version in **Figure
S9**), although less similar to the two seed clusters (red shade for FC clusters in **Figure 6A, B, left
panels**). The clustering in the perceived action FC network consisted of areas around the
bilateral central gyrus (lateral-central/central sulcus, post-central gyrus, bilateral SMA), most
showing above-baseline activation for 0 to 3 of the 10 action categories, apart from the L lateral
central sulcus showing activation for 8 categories. The clustering in the perceived emotion FC
network consisted of areas in the bilateral ventral-lateral visual pathway (EVC, lingual gyrus,
collateral sulcus, fusiform, EBA/hMT+, lingual gyrus, cuneus), where 8 areas showed above-
baseline activation for all 10 action categories, another area showing activation for 8 categories,
the other 7 areas showing no activation for any of the categories. Despite the very strong
differences in their univariate activation levels, their pattern similarity were clustered in the
same branch of the dendrogram. Also, the second-level pattern-similarity clustering structure
across areas does not seem to be linked to the low-level visual features from the stimuli, but
seem to be a real organization feature, because the clustering structure could be seen in all 10
participants, despite the fact that each 5 participant saw a different stimuli set (set A and B).

For these two groups of clustered areas, their further dissimilarity distance to the seed regions
indicate, that these areas are at different processing stages than the final output stage of the
seed regions, and our two assumptions of the information-transfer-chains seems to be able to
discover meaningful and replicable functional organizations in the brain.

Figure 6. In the functional connectivity (FC) networks of the two seed regions overlapped with
the DMN/semantic networks.
A and **B**. Areas in the FC networks colorcoded by pattern similarity to the seeds, L mSTS (**A**), and
L PMd (**B**). Initial p<0.001, cluster size threshold in functional voxels: L mSTS network: 32; L PMd
network: 40. The seed ROIs were in yellow. Color bars: representational similarities to the FC
cluster containing the seed region. For each network, the hierarchical clustering dendrograms
computed on group-averaged second-level RDMs across areas (Spearman distance) were
plotted in the right-most panels. The areas with the most similar representations to the FC
cluster containing the seed region were colored in yellow in the dendrograms (linkage distance
arbitrarily thresholded at 0.8, see a larger version in **Figure S9**), and labeled in the brain maps of
the left panels. The name of the areas containing the seed regions were marked in blue. The
areas with above-baseline univariate activation for more than 5 action categories were marked
with a "+" sign.
C. Histograms of number of conditions with above-baseline activity, for clusters in the two
networks. Most areas did not show univariate activation for any of the 10 action
categories/conditions.
D and **E**. The two FC networks overlapped with the DMN/semantic networks.
D. The overlap of two FC networks.
E. The overlap of the two FC networks, only showing clusters with most similar representations
to the seed (the clusters labeled in **A** and **B**).
F. The group-averaged and individual second-level RDMs. The yellow and black bars for the
group-average RDM denote the same clustering of the dendrogram in **A** and **B**. See a larger
version in **Figure S9**.

Discussion

In the current 7T fMRI study, we examined how participants perceived bodily actions, by
analyzing participants' subjective understanding of the actions and emotions displayed, besides
the conventional analysis by the predefined action and emotion categories. Dimension
reduction (PCA) revealed that subjectively perceived action and emotion representations were
high-dimensional and could not be reduced to the predefined category representations, despite
being correlated to them in smaller principle components. Some emotional categories were
reflected in the smaller principle components of the perceived emotion representation. Clusters
in L mSTS and L PMd had representations that were the most similar to the perceived action and
emotion representations. Areas located in the action-observation network and the semantic
network/DMN were functionally connected to these two clusters and also showed similar
multivariate patterns. This provided direct evidence for the involvement and interplay of both
networks in subjective understanding of bodily actions and emotions.

For the predefined categories, the non-emotion/emotion representation corresponded well
with the perceived emotion representation both behaviorally and neurally, showing a cluster in

R PMd/FEF, contralateral to the cluster for perceived emotion. For the predefined 10-action-
category representation though, the resulting clusters were more numerous, and likely
confounded by low/mid-level visual features that could co-vary with action/emotion categories.
However, all of the clusters were strongly connected to both the action-observation network
and the semantic network/DMN, consistent with the perceived action results. For mid-level
visual features, we further found that the head orientation and the shortest hand-to-head
distance were represented in the brain, indicating that these two features may be important for
the brain.

The involvement of the DMN/semantic network in both action and emotion understanding

At first sight, it may seem that the involvement of the DMN/semantic network found in the
current study simply results from the use of word embeddings. We argue that this is not the
case, and that our study reveals the individual brain underpinnings of action and emotion
understanding as involving both the action observation network and the DMN/semantic
network. Although the word embeddings indeed represent the semantic distances between the
words, these semantic distances reflect the similarities between different concepts. Our
perceived action and emotion representations were different, despite being computed from
word vectors from the same 300-dimensional space. Also, the perceived emotion cluster in L
PMd is not a key node area in the semantic but rather in the action observation network; the
two FC networks for perceived action and emotion did not completely overlap with each other
either.

Actually, the involvement of IFG (Caspers et al., 2010; Dricu and Frühholz, 2016; de Gelder et al.,
2004; Molenberghs et al., 2012) and areas in the DMN/semantic network (Chikazoe et al., 2014;
Peelen et al., 2010; Skerry and Saxe, 2015) has been consistently found in action perception and
emotional expression perception, although in separate studies and in different contexts. For the
DMN and especially for the vmPFC area, their involvement in emotion perception was for
abstract representation of emotional stimuli found with multivariate RSA (Chikazoe et al., 2014;
Peelen et al., 2010; Skerry and Saxe, 2015), rather than with simple univariate contrasts. The
simultaneous involvement of the IFG and the DMN in action understanding was found in one
univariate study contrasting participant's attention on either the intention or means of the
performed actions (de Lange et al., 2008). In that study, the IFG activity was higher for actions
with unusual intentions compared to usual ones; the DMN was instead showing higher activity
when participants were paying attention to the intentions rather than the means of the action.

Two recent studies provided more converging evidence to us. One RSA fMRI study about
observed actions (Tucciarelli et al., 2019) used a large set of action categories, constructed a
semantic similarity model of the meanings of the actions as well as other similarity models
obtained from individual participants' behavioral sortings of similarities, and searched for
corresponding RDMs in the brain. They found bilateral clusters in IFG/PMv, pIPS, and lateral
occipitotemporal cortices (LOTC, close to EBA) corresponding to the semantic similarity model,
although only the left LOTC cluster remained after RSA regression controlling the effects of

other models. That study controlled the inter-individual consistency of the stimuli perception
during the stimuli selection process, which was not done in the current study, and may explain
the discrepancy. Another study (Masson and Isik, 2021) examined the fMRI responses during
naturalistic movie watching using encoding models, and found that a social-affective model
(including features of an agent speaking, social interactions, theory of mind, perceived valence
and arousal) significantly explained the fMRI response in the left STS across two different
movies. This cluster fully overlapped with our L mSTS cluster.

In fact, the IFG and the areas in the DMN were all parts of the semantic network, thus their
involvements could also be studied in the future in the context of the semantic network, apart
from the context of "mentalizing" usually associated with the DMN. The importance of the
semantic network in emotion understanding is further supported by behavioral studies of
semantic dementia patients. In one such studies, three semantic dementia patients with left
temporal pole atrophy and impaired semantic knowledge were asked to sort faces into piles by
emotion. These patients were not able to distinguish between emotional faces with negative
valence, despite that their perception of positive/negative affect, the visual features for each
facial emotion and identity were intact (Lindquist et al., 2014).

Although we did not examine the temporal pole due to coverage limitation, our multivariate
RSA and functional connectivity results support the importance of the DMN/semantic network
in action and emotion understanding. These results are also consistent with the literature, that
the DMN did not show above-baseline activation, when passively observing actions (videos,
non-social, non-emotional) but without deliberating the goals/intentions (Van Overwalle and
Baetens, 2009). We further revealed that both the DMN/semantic network and the action
observation network were involved in the process of action and emotion understanding, that
they were consistently found in all 10 participants within the same functional connectivity
networks and showed similar multivariate patterns despite very different levels of univariate
activation. The multivariate methods worked in our study and in previous RSA studies, because
they took the multiple dimensions in the high-dimensional data into account, while the
univariate method considers only one or a few specific dimensions which associated with
specific contrasts (Haxby et al., 2011). Our study stresses the importance to further examine the
function of the DMN/semantic network in action and emotion understanding with multivariate
methods in future studies.

Understanding versus categorization
Previous experiments have mostly used explicit emotion and action categorization tasks with
predefined categories, and implicitly used explicit categorization as a proxy to study subjective
understanding. However, categorization and understanding may involve different neural
substrates, as categorization involves some level of abstraction. Our study could not
differentiate between these two processes, because first, the RSA method could not disentangle
categorical boundaries driven by lower-level visual features, or concrete perceptual categories
(Hoemann et al., 2020; Mansouri et al., 2020) that were bound to individual exemplars, or
abstract categories that generalize across exemplars. Second, what we obtained in the

subjective reports were descriptions or labels of action and emotion for each individual
stimulus, rather than more abstract categorization to the group of stimuli. Thus, the resulting L
mSTS and L PMd clusters for perceived action and emotion may not represent the most abstract
level, and the more abstract categorization may happen in other areas functionally connected to
these two areas, and could perhaps utilize these category boundaries in computation. The
different levels of abstractions may also have driven the discrepancy between the analyses with
subjective reports and predefined categories, although both analyses pointed to the strong
involvement of the caudate, which is in the executive loop of categorization learning tasks
(Seger, 2008; Seger and Miller, 2010). The areas found in our study could serve as target areas in
future studies, to examine the level of abstraction.

Brain areas for emotion understanding

Our analysis with the predefined non-emotion/emotion category model and with the perceived
emotion model pointed to the PMd areas in the right and left hemispheres. This area may
contain infromation exhibiting categorical boundaries between non-emotional/emotional
stimuli, but again the level of abstraction could not be disentangled. Future studies could use
emotional facial or voice stimuli, accompanied by subjective reports, to examine whether this
area is specific to bodies and actions, or is more general for emotions in different modalities
(Vaessen et al., 2019a).

We did not find evidence for coding of valence in frontal (higher-order) areas, either with
monotonic univariate activity modulation or with multivariate representations. However,
valence coding may be bivalent, such that the vmPFC/mOFC activity monotonically increased for
both positive and negative valence, as found in an RSA study (Chikazoe et al., 2014). This might
be the case, as we found evidence that the vmPFC was showing a fine-grained pattern between
similarly perceived emotions (**Figure 5B**). With only one category of positive emotion, we were
not able to examine the possible bivalent activity.

In the analysis of the predefined action and emotion models, and in the univariate parametric
modulation of valence rating, we found adjacent/overlapping clusters in the L central sulcus
(**Fig. 2D, Fig. 3**). These clusters are also adjacent/overlapping to the two FC networks for
perceived action and emotion (**Fig. 6AB**), but with different neural representations to the two
seed regions for perceived action and emotion. This indicated that the primary sensorimotor
areas were involved in action and emotion processing, although the representation there may
be of lower-level features and may not be emotion-specific.

Importance of using individualized subjective reports to study higher-level cognition

With subjective reports, we found that the perceived action and emotion representations were
more high-dimensional and multi-faceted than the predefined category representations,
consistent with the recent series of studies using subjective reports (Cowen and Keltner, 2017,
2020, 2021; Cowen et al., 2019). We also found neural representations corresponding to these
subjective report representations in higher-level areas outside the ventral and dorsal pathways.

Apart from a few RSA studies which linked individualized behavioral data to the brain data
(Chikazoe et al., 2014; Stolier and Freeman, 2016; Tucciarelli et al., 2019), multiple previous RSA
studies either utilized only the predefined categories (Peelen et al., 2010), or the behavioral
ratings from an independent group (Bracci and Op de Beeck, 2016; Mur et al., 2013; Peelen et
al., 2014; Skerry and Saxe, 2015; Vaessen et al., 2019b), or the averaged behavioral responses of
the same participants scanned (Connolly et al., 2012; King et al., 2019). For high-level cognition
that has a more remote relation with the sensory stimuli and has more variability between
individual participants, the use of individualized behavioral data may be beneficial, as was
evidenced for studying object recognition (Charest et al., 2014), which was traditionally thought
to have considerable behavioral judgment similarities shared between participants. The multiple
pre-trained word embeddings are also relatively easy to use and enable objective analyses of
subjective reports.

Advantages and limitations of the current 7T experiment
The use of high-resolution 7T fMRI in the current study has advantages and limitations. With
higher gray-white-matter contrast and higher temporal signal-to-noise ratio, the resulting data
were very robust (see the functional localizer data in **Figure S2 and S3**), the activation clusters in
individual participants were highly localized in the gray matter, and we observed small
subcortical clusters in multiple analyses at the group level, including periaqueductal gray, medial
geniculate nucleus, substantia nigra, red nucleus, and the septal nuclei. However, the current 7T
data also induced the possibility of false negatives, where the inter-individual
anatomical/functional variability was exacerbated and would no longer be compensated by
extensive smoothing, as observed again in the functional localizer data (**Figure S3**). Better
whole-brain group-level analysis schemes apart from the ROI analysis are needed to benefit
from both the high functional resolution and the large brain coverage, which potentially include
more fine-grained functional parcellations (Glasser et al., 2016; Yeo et al., 2011) and
hyperalignment (Haxby et al., 2011).

Acknowledgments
This study was supported by the European Research Council, under the European Union's
Seventh Frame-Work Programme (FP7/2007–2013)/ERC (grant numbers 295673 to BdG and
269853 to RG), by the ERC-Synergy program grant RELEVANCE (Grant agreement 856495 to
BdG), and by the FPN-MBIC funding of Maastricht University to MZ and BdG. MZ was supported
by Fondation Bettencourt Schueller. We thank Federico de Martino for setting up the 7T
scanning sequences and Giancarlo Valente for providing a part of the searchlight code. We
thank Maarten Vaessen for commenting on a previous version of the manuscript.

Author Contributions

Conceptualization: M.Z. and B.dG.; **Methodology, Software, Validation, Formal Analysis, Investigation, Data Curation, Writing – Original Draft, Visualization**: M.Z.; **Resources**: R.G.; **Writing – Review & Editing**: M.Z., R.G. and B.dG.; **Project Administration, Funding Acquisition**: M.Z. and B.dG.; **Supervision**: B.dG.

Declaration of Interests

The authors declare no competing interests.

Data and code availability

The data and codes of this study are available at https://osf.io/cuh9v/?view_only=efb12b7585ee4b6bbcfd7ca42c63b60d, including: stimuli images with body joint estimations, subjective reports and corresponding word embeddings, whole-brain statistical result maps, ROI raw data for the RSA analysis, structural images and white-gray-matter-boundary segmentations.

Materials and Methods

Participants

The data of 10 healthy right-handed participants recruited from the campus of Maastricht University were included in the analyses (mean age =23.4, SD=1.955, 5 females.) Two more participants took part in the study, but due to excessive head motion observed during the scan, their scanning sessions were either aborted, or data excluded from the analyses. All participants had normal or corrected-to-normal sight and had no history of psychiatric disorders. Participants provided written consent before the study and received monetary reward afterwards. The experiment was approved by the ethical committee of Maastricht University, and was carried out following the declaration of Helsinki. The experiment was conducted in English.

Data acquisition

The MR data were acquired in a 7T Magnetom full-body scanner (Siemens, Erlangen, Germany) in Scannexus, Maastricht University, with a Nova 1-transmitter/32-receiver head coil (Nova Medical, Wilmington, USA). Dielectric pads were used for all participants except S10 (when the head size didn't allow it), roughly covering bilateral occipito-temporal lobes. The stimuli were back-projected onto a screen behind the participants' head (Projector: Panasonic PT-EZ57OEL, projected screen size 30 x 18 cm, resolution 1920 x 1200 pixels, refresh rate = 60 Hz, viewing distance ~99 cm, screen visual angle 17.23 x 10.38 degrees) and the participants viewed the screen through a mirror fixed on the head coil. Participants came for two scanning sessions, a 2-hour session for the main experiment, and a 1-hour session for functional localizers and anatomical scans.

Whole-brain anatomical data were collected for each participant with a resolution of 0.6 mm
isotropic (MPRAGE sequences, FOV=229 x 229 mm^2, matrix size=384 x 384, flip angle=5. T1-
weighted: TR=3100 ms, TE=2.52 ms; proton-density-weighted: TR=1440 ms, TE=2.52 ms). For
the functional runs, a 2D gradient-echo multi-band EPI sequence was used, with a resolution of
1.2 mm isotropic (multi-band acceleration factor=2 (Moeller et al., 2010), iPAT=3, FOV=172.8 x
172.8 mm^2, matrix size=144 x 144, flip angle=75, number of slices=70, slice thickness=1.2 mm,
no gap, ascending interleaved 2, TR=2000 ms, TE=21 ms, encoding direction Anterior to
posterior, reference scan mode: GRE, MB LeakBlock kernel: off, fat suppression enabled). In
each scanning session, a head scout was acquired for localization, then the B0 field map was
acquired and loaded in the console. The interactive shimming was performed before acquiring
the B1 field map. The system voltage was then computed according to the B1 map values (set to
a maximum of 190 V across all sessions), to have a 90 degree flipping angle at the white matter
beside the lateral ventricles, and the specific absorption rate (SAR) level for the longest
functional run (432 volumes) was controlled at below 75%. The slices were tilted in an angle that
covered most of the occipital lobe, parietal lobe and frontal lobe, while leaving out the anterior
temporal lobe, part of the motor cortex, and the orbitofrontal cortex. This was to ensure that
most of the important areas involved in body perception were covered, including EBA, fusiform
gyrus, IPS, IPL, PMd, PMv. The amygdala was not consistently covered given the relatively
limited coverage (covered in 6 out of 10 participants). Immediately before each functional run, a
5-volume run of the same setup but with posterior to anterior encoding direction was acquired
(Invert RO/PE polarity: on), for post-hoc top-up EPI distortion correction (See the fMRI data
preprocessing sub-section). We informed the participants the purposes of these distortion
correction runs, and instructed them not to move between the distortion correction run and the
actual functional run.

Stimuli

The stimuli were gray-scale whole body images developed and validated in our lab (Stienen and
de Gelder, 2011). They consisted of 8 actors, each posing 10 actions with or without emotional
content. The first 5 categories were neutral actions: combing hair (CH), drinking water (DW),
opening door (OD), talking on the phone (PH), putting on trousers (TR); the 6[th] was neutral
standing still (NE), and the last 4 were emotional expressions: fear (FE), anger (AN), happy (HA),
sad (SA). The 80 postures were split into 2 balanced sets by randomly selecting images from 4
actors for each category, resulting in 2 sets of 40 stimuli (4 images per category, 5 images per
actor), which ensures that in each stimulus category the participants perceive as much
variability in the posture and the identity as possible. Each participant saw one of the sets.

The body stimuli were embedded a gray background (RGB value = 128, 128, 128), with all
internal facial information removed. They were sized to 400 x 600 pixels, and presented
centrally on the screen (RGB value = 128, 128, 128). The whole-body shapes in the images
overall spanned 309 x 492 pixels on the screen (visual angles=2.60 x 4.26 degrees).

fMRI experiment design

The study used a slow event-related design. Stimuli were presented with Matlab (Version R2012a, the MathWorks, Natick, USA) and Psychtoolbox 3.0.11 (Pelli, 1997). A white fixation cross was present in the center of the screen throughout the experiment. The participants were asked to always fixate on the fixation cross and take in the body posture as a whole. The experiment consisted of 6 runs (14 min 18 s each, 429 volumes). Each run started with a fixation period of 8 seconds, and then the whole set of 40 stimuli was presented to the participant twice within each run. Each stimulus was presented for 500 ms, followed by an inter-stimulus interval of either 7.5, 9.5 or 11.5 s. The stimuli and the ISI were presented in a pseudorandomized order. In addition, 4 catch trials were included in each run. Within each catch trial, a body posture was randomly drawn from the stimulus set, while the fixation cross changed to either red or blue (RGB color red= 195, 32, 30; blue= 10, 109, 195) during the stimulus presentation period. Participants were asked to indicate the color by pressing the corresponding button of the button box as soon as they saw the fixation change color. Two seconds were added to the inter-stimulus interval after each catch trial. Excluding the catch trials, each single stimulus image was presented to the participant for 12 times throughout the main experiment. 9 participants completed all 6 functional runs; 1 participant completed 5 runs.

Functional localizers

A separate scanning session was devoted to acquiring functional localizer data and the structural images. Stimuli were presented under passive viewing condition using Presentation software (Version 16.0, Neurobehavioral Systems, Inc., Berkeley, USA). In the static localizer run (14 min 24 s, 432 volumes), after a 12 s fixation period, gray-scale stimuli of faces, houses, bodies, tools and words were presented in blocks of 12 s (12 stimuli per block, 800 ms stimuli presentation, 200 ms inter-stimulus interval), followed by resting periods of 12 s with the fixation cross on a blank screen (RGB value=157,157,157). Each category block was presented 7 times, with a pseudorandomized presentation order for both the stimuli and the blocks. Facial stimuli were front-view neutral faces from the Karolinska Directed Emotional Faces (Lundqvist et al., 1998) (24 identities, 12 males). The part below the neck (clothes, hair etc.) was removed from the face images. Body stimuli were neutral still front-view bodies (de Gelder and Van den Stock, 2011) (20 identities, 10 males) from a different set than the one used in the main experiment, with the facial information removed. House and tool images were obtained from the internet. The house images consisted of 19 facades of houses with 2-to-3-storey height; the tool images consisted of 18 hand-held tools; words images consisted of high-frequency English words of 4-6 letters in Arial font. All the images were imbedded within a gray background (RGB value=157,157,157), spanning a visual angle of 1.99 degrees (230 pixels).

The dynamic localizer run (5 min 36 s, 168 volumes) consisted of 1-s video clips of either facial or bodily expressions, including neutral (coughing or clearing throat), angry, fear, happy (Kret et al., 2011). The actors performed the actions against a green background, either wearing black clothes for bodily expressions, or green clothes for facial expressions. Two exemplars were selected for each expression category (in total 8 for faces and 8 for bodies). The actors in the

878   selected exemplars were all males. For the facial stimuli, two of the neutral expressions were
879   performed by the same identity. The facial and bodily expression clips were presented
880   separately in blocks of 8 s, with the stimuli order pseudorandomized. The face and body blocks
881   were presented 10 times each, separated by an inter-block interval of 8 s, where a black screen
882   and a white fixation cross was presented.

Behavioral ratings

Right after the scanning session, participants completed a behavioral task outside the scanner.
Each of the 40 stimuli participant saw in the scanner was presented once using Psychopy
(v1.83.04)(Peirce, 2007) on an LCD monitor (Acer VG248, resolution = 1920×1080, refresh rate =
60 Hz, whole-body size in the stimuli spanning the visual angle of 13.42 x 8.43 degrees). For each
stimulus image, 6 questions were answered either with a 7-point scale (for implied motion and
valence respectively), or with an open answer with free typing (for the action the actor
performed, and the emotion). See **Table S1** for details of the questions. We also recorded
whether the participants changed their perception during the scan (questions 2 and 3). Four
participants changed their perceptions (S4 and S9 for 2 stimuli, S6 for 7 stimuli, S10 for 12
stimuli). We used only the initial perception in the scanner (answer for question 1) for
subsequent analyses. The same stimulus image stayed on the screen for all 6 questions.
Participants answered the questions at their own paces (mean time spent=21.47 min, SD=6.98
min, range: 12.61 to 32.89 min).

Data analysis

Representational similarity analysis (RSA) for behavioral data

We mapped the subjective reports with Deconf word embeddings (Pilehvar and Collier, 2016),
which linked the Word2vec embeddings and the WordNet database. Word2vec embeddings
were trained on a very large corpus of text, able to capture various linguistic relationships
between words (Mikolov et al., 2013). After training, words with similar semantic meanings
were found to be situated closer to each other in the embedding vector space (cosine distance);
although for word2vec, different meanings of the same word were not disambiguated. On the
other hand, WordNet (Miller, 1995) is a curated lexicon database, where different meanings of
each single word were separated, and synonyms were grouped together; but it does not provide
a quantitative mapping for word similarities. Deconf embeddings mapped the individual word
meanings (senses) in WordNet into the 300-dimensional word2vec vector space, offering us
both a common high-dimensional semantic space trained by a large corpus, and the precise
separation of different meanings.

For behavioral free reports, we omitted the pronouns (e.g. he is, she is, his, her), as most of the
times participants did not consistently type in the pronouns. The rest of the words/phrases
(nouns, verbs, adjectives, adverbs) that had a corresponding entry in WordNet 3.1 were
lemmatized (e.g. stretching→stretch). For words/phrases not found in WordNet 3.1, "how" was
omitted; "something" was substituted by "thing"; "himself/herself/oneself" were substituted by
"self". The adverb "just" associated with verb phrases was omitted (e.g. just watching→watch).

When describing the perceived action, "not sure" was substituted by "unsure"; when denoting
that the participant had no idea about what the person was doing, "no idea" and "not sure"
were substituted by "not applicable". For words with multiple meanings ("senses" the term used
in WordNet), the corresponding sense was selected. When a noun denoting emotion has both
senses of <noun.feeling> and <noun.state>, the sense of <noun.feeling> was always selected.
There were very few cases that participants typed in "not". For one case the participant
denoting the emotion of the person in the stimuli "was not sure about something", it was
substituted with the word "unsure". All the other cases were in responses for perceived acitons,
about participant's own uncertain understanding for the stimuli. For these and similar cases we
substituted the entry with "not applicable". For all response entries and word lists, see
https://osf.io/cuh9v/?view_only=efb12b7585ee4b6bbcfd7ca42c63b60d.

For each free report entry after lemmatization, the 300-dimension word vector with the
corresponding sense number and sense key were selected from the Deconf pre-trained
embeddings. When an entry has multiple words, the vectors were averaged for this entry. The
RDM for each participant were then computed in cosine distance, as this metric was routinely
used for computing word-embedding distances in the literature.

The RDMs for behavioral ratings (implied motion, valence) were computed directly from the
ratings, in Euclidean distance.

For predefined RDMs, each category was binary-coded in vectors, with numbers of elements
corresponding to the total number of categories. E.g. for predefined actions, drinking water (2nd
category in 10) was coded as 0 1 0 0 0 0 0 0 0 0; for predefined non-emotion/emotion
categories, emotional ones were coded as 0 1. This coding assumes that each category was
orthogonal to the others. The resulting RDMs were computed in Euclidean distance.

For RDM comparisons throughout the study, the Spearman's correlation was computed
between 40×40 RDMs, with the 780 values below the diagonal of the RDMs as inputs. The
resulting rho values were Fisher's Z transformed, submitted to a one-sample t test against 0
(two-tailed) at the group level. The group-averaged Z values were back transformed to rho
values (or 1 - rho distance) and reported. To assess individual variability, we computed the
coefficient of variation (CV, sample standard deviation/sample mean, in %).

Since all 400 response entries for the perceived action and emotion representations were in the
common 300-dimensional word-vector space, we performed PCA on the 400 entries for each
representation (without centering, since the word vectors were all normalized). The PCA scores
for each principal component (PC) was computed into RDMs (Euclidean distance), and
correlated with 400×400 model RDMs. The model RDMs were created in the same way as the
40×40 RDMs, with the only difference that the 400 entries were sorted by action categories
across all participants. Model RDMs included predefined action, predefined emotion, implied
motion, valence, individual subjects (entries of the same participant were coded as the same

vector). The PCA scores of all response entries were plotted in the two PCs that showed the
highest positive correlation to the model RDMs (**Fig. 1I, J**).

fMRI data Preprocessing
The data were processed with BrainVoyager (version 20.0 and 20.2, Brain Innovation,
Maastricht, the Netherlands), MATLAB (version R2016a), and NeuroElf 1.0 toolbox implemented
in MATLAB (http://neuroelf.net/). Before any preprocessing, the functional data underwent in-
plane EPI distortion with the COPE plugin (v1.0) in BrainVoyager
(https://support.brainvoyager.com/brainvoyager/available-tools/86-available-plugins/62-epi-
distortion-correction-cope-plugin). The voxel-wise displacement was estimated between the
first volume of each functional run and the first volume of the preceding 5-volume correction
run (in reversed phase encoding direction). The in-plane voxel-wise displacement map was then
applied to all the volumes of the functional run. The first volume of each run was saved as a
separate file, and applied with distortion correction. This volume then served as the basis for
subsequent motion correction and across-run alignments. After distortion correction, the
functional runs underwent slice scan time correction with the slice timetable information from
the scanner (interpolation: sinc), within-run 3D rigid motion correction with each run's first
volume as references (interpolation: trilinear for motion estimation, sinc for applying
transformations), and temporal high-pass filtering (GLM with Fourier basis set of 2 cycles,
including linear trend). The order of distortion correction and motion correction was assessed
on S06's sixth (last) main-task run, which has the biggest within-run rotation in all acquired runs
in the current experiment (about 3 degrees in the x axis). Between the two processing orders,
the resulting 429^{th} volume showed negligible differences in the frontal lobe. Thus we believe the
order of distortion correction and motion correction was not critical. For the anatomical data,
the magnetic field inhomogeneity was corrected by dividing the T1 images with the PD images.
The anatomical data was then spatially normalized into the Talairach space.

To ensure that all functional runs of each participant (6 runs of the main experiment, 2
functional localizer runs, from two scanning sessions, distortion-corrected) were aligned well
with each other, we used a manual across-run alignment procedure, with careful visual
inspections and multiple iterations/checks. The first volume of the main-task run was aligned to
the anatomy, and then saved as an anatomical file in native space, keeping the T2* weighted
contrast the same as the original functional run. This served as a "dummy" anatomical run for
the subsequent alignment procedure. Then the first volumes of all the functional runs (including
the first run itself) were aligned to this dummy anatomical run, and normalized into the
Talairach space (with the position information and transformation matrices for the T1 weighted
anatomical run). The first volumes of the 8 runs aligned in the Talairach space were then screen-
captured and saved as different layers in Photoshop (version CS6, Adobe, United States), toggled
on and off, and made into GIF animations to check alignment qualities across runs. Adjustments
were made for imperfect aligned runs, followed by the same checking procedure, until there
were not any big shifts/translations across runs at the whole-brain level. This procedure allowed

us to visually spot tiny alignment imperfections across runs with the same T2* weighted
modality. It is much easier than spotting misalignments across T2* weighted and T1 weighted
image modalities in the conventional alignment procedure, where the two images look very
different across modalities. The quality of the distortion correction was also checked when
aligning the functional run 1 to the anatomy, where a good distortion correction resulted in a
good shape correspondence between the T2* weighted and T1 weighted data. In some cases,
when the participants moved their head between the distortion correction run and the
functional task run, despite our repetitive instructions, the distortion correction quality was
affected. In those cases, we strived for aligning the occipital and temporal lobes.

After alignment across runs, the functional data of the main experiment were then spatially
smoothed with 6 mm FWHM for univariate analysis (comparable to the RSA searchlight radius),
3 mm FWHM for task residual functional analysis. The unsmoothed data were used for the
representational similarity analysis, and univariate analysis of 10 categories in RSA searchlight
clusters. The static functional localizer data was smoothed at 6 mm FWHM for group random-
effect GLM, 3 mm for individual participants, and not smoothed for univariate analysis in RSA
searchlight clusters.

All results in this study were computed in the volume space. For visualizing group-level results,
cortex-based alignments (CBA) were performed to alleviate the high inter-individual anatomical
variability. For each participant, the gray-white-matter boundary of the anatomical images in
Talairach space underwent automatic segmentation, and careful manual correction slice-by-
slice. Then a mesh with a high number of vertices was created for the white-gray-matter
boundary of each hemisphere (number of vertices ranging from 370k to 434k), inflated into a
sphere, corrected for distortions across vertices, and mapped to a high-resolution standard
sphere with down sampling (number of vertices=163842). The curvature patterns of the original
mesh were also smoothed and mapped to the standard sphere. The group-level cortex-based
alignment was separately performed for the left and right hemispheres. For each hemisphere,
the curvature patterns of all 10 participants' meshes were aligned into a dynamic group
average. After aligning, the average left and right hemispheres of the whole group were created.
This resulting group-average brain surface retained many anatomical landmarks, and was more
detailed than the ones usually created with 3T data. However, note that it was a bit smaller than
the actual brain, and was only meant to provide visual landmarks to localize the clusters.

Univariate analysis
To compare the univariate activation to the literature, three different general linear models
(GLMs, serial correlation correction: AR(2), data %-normalized before performing the GLM) were
applied to the datasets smoothed 6 mm FWHM, with the following predictors: 1) 10 action
categories; 2) the behavioral ratings of implied motion; 3) the behavioral ratings of valence. For
2) and 3), the presentation of all stimuli were defined as a single main predictor, the ratings for
40 stimuli were z-scored within each participant, and served as a parametric weight factor to
each corresponding stimulus. The parametric modulation effects were subsequently computed
for 2) and 3). For all the GLM models above, the time courses were %-transformed, the main

predictors were convolved with a two-gamma hemodynamic response function, and the 6
parameters of participant's head motion were z-scored and entered as confounding factors. The
catch trials were marked as a separate condition, and their parametric estimates (beta values)
were not used in subsequent analyses.

The group random-effect GLM analysis was performed for each predictor set. For the 10-
category predictor set, apart from the contrasts between action categories, a whole-brain
ANOVA was performed, with a 10-level factor 'action categories'. Cluster size thresholds for all
group-level maps in this study were estimated using Monte-Carlo simulation (alpha level=0.05,
numbers of iterations=5000, initial $p < 0.005$ for univariate and RSA searchlight analyses; initial
$p < 0.001$ for task-residual functional connectivity), with the BrainVoyager plugin Cluster-Level
Statistical Threshold Estimator (https://support.brainvoyager.com/brainvoyager/functional-
[analysis-statistics/46-tresholding-multiple-comparisons-problem/226-plugin-help-cluster-](https://support.brainvoyager.com/brainvoyager/functional-analysis-statistics/46-tresholding-multiple-comparisons-problem/226-plugin-help-cluster-thresholding)
[thresholding](https://support.brainvoyager.com/brainvoyager/functional-analysis-statistics/46-tresholding-multiple-comparisons-problem/226-plugin-help-cluster-thresholding)), masked with the common functional data coverage across 10 participants. This
mask was created from the averaged functional images across participants, covering 830178
functional voxels.

The GLM of the static functional localizer (without smoothing, and smoothed 3 mm FWHM) was
performed for each individual participant. Since we do not assume that the bodies should only
be processed in category-specific areas, the static functional localizer data were used as an
indicator for inter-individual variability, and an indicator for the neural processes in some RSA
searchlight clusters.

Representational similarity analysis for fMRI data
For RSA analyses, the GLM model with 40 stimuli was fitted to each individual participants'
unsmoothed data, resulting in 40 t-maps, one per stimulus. The neural RDMs across the 40
stimuli were computed with Pearson's correlation distance Searchlight spheres were
constructed for each voxel, with a radius of 5 voxels (515 voxels within the sphere, 889.92 mm^3),
comparable to the value for univariate smoothing. Spheres containing more than 172 non-zero
voxels were included in the analysis). The Spearman correlation values between the neural RDM
and the model RDM was Fisher-Z transformed, and wrote back to the sphere center voxel. The
group-level significance of the correlation was evaluated by a one-sample t-test against zero (2-
tailed).

For the clusters found by the searchlight RSA and subsequent whole-brain analyses, the
univariate percent signal changes for each of the 10 action categories were extracted (without
smoothing), and were compared to the baseline (one-sample t test against 0) in SPSS.

RSA regression with low/mid-level features
For each of the stimuli image, we extracted the body joint locations by the OpenPose library
(Cao et al., 2017) (https://github.com/CMU-Perceptual-Computing-Lab/openpose). The output
was the x, y values and a confidence score for the estimation, for 18 body joints (See **Figure 4A**).
The joint locations were imported in Adobe Illustrator CS6, overlaid on the stimulus image, and

manually adjusted with visual estimation. The correspondence of the joints and their location
are as follows: joint 1 (head)-nose tip; joint 2 (neck)-the jugular notch of the sternum; joint 3 & 6
(shoulders)-humerus; joint 4 & 7 (elbows)-the connecting point of the upper/lower arms; joint 5
& 8 (hands)-the wrist end of the radial bone; joint 9 & 12 (waist)-the widest points of the femur;
joint 10 & 13 (knees)-on the patella; joint 11 & 14 (feet)-the ankle end of the tibia; joint 15 & 16
(eyes); joint 17 & 18 (ears). Since the eyes were not present on the stimuli images (facial
features blurred), and the ears were often occluded by the hair or by the head, these joints were
visually estimated with linear perspective in mind.

We constructed low-level visual feature RDMs, for raw pixel values (as vectors), and raw
coordinates of the 14 joints (excluding joints for ears and eyes), although the resulting RDMs
were extremely similar to the ones including these 4 joints (RDM similarity rho=0.976, 0.98 for
stimuli set A and B).

The mid-level visual feature RDMs included head, shoulder, waist orientations, as well as
hands/feet-to-head distances. The head orientation was individually computed by the distance
between ears, normalized (divided) by the ear distance of the standing still condition, capped at
1 (1: facing the viewer; smaller than 1: facing left- or right-ward). The shortest hand-to-head
distance may reflect whether the hand enters the head's peripersonal space of the actor; the
average feet-to-head distance may reflect the relaxation of the torso and legs of that actor.

For RSA regression in each of the 10-action-category areas (resulted from whole-brain
searchlight analysis of the 10-action-category model RDM), the low/mid-level visual feature
RDMs and the higher-level stimuli attribute RDMs (implied motion, valence, actor identity) were
squared for each element (to satisfy the linearity for squared Euclidean distance values), z-
scored across elements, then put together in the same linear regression model as predictors.
Each element of the neural RDM was also correspondingly squared. A set of beta values for
these predictors were obtained for each participant, and their group-level significance was
examined by one-sample t-test against zero (2-tailed), and FDR-corrected at q<0.05 (Storey,
2002) across all predictors for each searchlight cluster.

Task residual functional connectivity analysis
We smoothed the task data at 3 mm FWHM, regressed out the task-related activity by
deconvolution analysis (5 stick predictors per stimulus, covering the evolvement of the BOLD
shape per trial). For each seed region, the residual time course was extracted and averaged
across voxels, and correlated with the residual time courses of all voxels in each run, resulting in
one R map per run. The connectivity pattern across the runs were stable for all participants. The
R maps were Fisher's Z-transformed, averaged across runs per participant, and put in a one-
sample t-test against 0 (2 tailed). The resulting group-level maps were thresholded at p<0.001
for cluster size correction.

For the 10-action-category areas, the inter-area functional connectivity was also examined, by
correlating the seed ROI time courses per run, then again with the same group-analysis
procedure (Z-transform, averaging, t test), with FDR correction.

Hierarchical clustering of RDMs across functional connectivity clusters
We computed neural RDMs for all group-level clusters obtained from the task-residual
functional connectivity analysis (51 ROIs for the perceived action FC network, 76 ROIs for the
perceived emotion FC network), and computed second-level RDMs (Spearman correlation
distance, **Figure 6F**) from them within each participant. For the two FC networks, the second-
level RDM were averaged (with Z-transform) across participants (**Figure 6A, B**, right panels), and
served as inputs for hierarchical clustering (MATLAB function: linkage; method: average. Plot
function: dendrogram; clustering threshold for the most similar areas to the seed region: 0.8).
We also examined the univariate activation for 10 action categories, and plotted histograms.

1120

1121

1122

References

Amodio, D.M., and Frith, C.D. (2006). Meeting of minds: the medial frontal cortex and social
cognition. Nature Reviews Neuroscience *7*, 268–277.

Andrews-Hanna, J.R. (2012). The brain's default network and its adaptive role in internal
mentation. Neuroscientist *18*, 251–270.

Aviezer, H., Hassin, R., Bentin, S., and Trope, Y. (2008). Putting facial expressions back in context.
First Impressions 255–286.

Barrett, L.F., Adolphs, R., Marsella, S., Martinez, A.M., and Pollak, S.D. (2019). Emotional
Expressions Reconsidered: Challenges to Inferring Emotion From Human Facial Movements.
Psychological Science in the Public Interest *20*, 1–68.

Binder, J.R., Desai, R.H., Graves, W.W., and Conant, L.L. (2009). Where is the semantic system? A
critical review and meta-analysis of 120 functional neuroimaging studies. Cereb Cortex *19*,
2767–2796.

Boleda, G. (2020). Distributional Semantics and Linguistic Theory. Annual Review of Linguistics *6*,
213–234.

Bracci, S., and Op de Beeck, H. (2016). Dissociations and Associations between Shape and
Category Representations in the Two Visual Pathways. J. Neurosci. *36*, 432–444.

Buckner, R.L., Andrews-Hanna, J.R., and Schacter, D.L. (2008). The Brain's Default Network.
Annals of the New York Academy of Sciences *1124*, 1–38.

Bufacchi, R.J., Liang, M., Griffin, L.D., and Iannetti, G.D. (2016). A geometric model of defensive
peripersonal space. Journal of Neurophysiology *115*, 218–225.

Bullmore, E., and Sporns, O. (2009). Complex brain networks: graph theoretical analysis of
structural and functional systems. Nature Reviews Neuroscience *10*, 186–198.

Cao, Z., Simon, T., Wei, S.-E., and Sheikh, Y. (2017). Realtime Multi-person 2D Pose Estimation
Using Part Affinity Fields. (IEEE), p.

Cao, Z., Hidalgo, G., Simon, T., Wei, S.-E., and Sheikh, Y. (2019). OpenPose: Realtime Multi-
Person 2D Pose Estimation using Part Affinity Fields. ArXiv:1812.08008 [Cs].

Caspers, S., Zilles, K., Laird, A.R., and Eickhoff, S.B. (2010). ALE meta-analysis of action
observation and imitation in the human brain. Neuroimage *50*, 1148–1167.

Charest, I., Kievit, R.A., Schmitz, T.W., Deca, D., and Kriegeskorte, N. (2014). Unique semantic
space in the brain of each beholder predicts perceived similarity. PNAS *111*, 14565–14570.

Chikazoe, J., Lee, D.H., Kriegeskorte, N., and Anderson, A.K. (2014). Population coding of affect
across stimuli, modalities and individuals. Nat Neurosci *17*, 1114–1122.

Connolly, A.C., Guntupalli, J.S., Gors, J., Hanke, M., Halchenko, Y.O., Wu, Y.-C., Abdi, H., and
Haxby, J.V. (2012). The Representation of Biological Classes in the Human Brain. Journal of
Neuroscience *32*, 2608–2618.

Cowen, A.S., and Keltner, D. (2017). Self-report captures 27 distinct categories of emotion
bridged by continuous gradients. PNAS *114*, E7900–E7909.

Cowen, A.S., and Keltner, D. (2020). What the face displays: Mapping 28 emotions conveyed by
naturalistic expression. American Psychologist *75*, 349–364.

Cowen, A.S., and Keltner, D. (2021). Semantic Space Theory: A Computational Approach to
Emotion. Trends in Cognitive Sciences *25*, 124–136.

Cowen, A.S., Elfenbein, H.A., Laukka, P., and Keltner, D. (2019). Mapping 24 emotions conveyed
by brief human vocalization. American Psychologist *74*, 698–712.

DiCarlo, J.J., and Cox, D.D. (2007). Untangling invariant object recognition. Trends in Cognitive
Sciences *11*, 333–341.

DiCarlo, J.J., Zoccolan, D., and Rust, N.C. (2012). How Does the Brain Solve Visual Object
Recognition? Neuron *73*, 415–434.

Dricu, M., and Frühholz, S. (2016). Perceiving emotional expressions in others: Activation
likelihood estimation meta-analyses of explicit evaluation, passive perception and incidental
perception of emotions. Neuroscience & Biobehavioral Reviews *71*, 810–828.

Ekman, P. (1999). Basic emotions. Handbook of Cognition and Emotion *98*, 16.

Freedman, D.J., Riesenhuber, M., Poggio, T., and Miller, E.K. (2001). Categorical Representation
of Visual Stimuli in the Primate Prefrontal Cortex. Science *291*, 312–316.

de Gelder, B. (2006). Towards the neurobiology of emotional body language. Nature Reviews
Neuroscience *7*, 242–249.

de Gelder, B., and Van den Stock, J. (2011). The Bodily Expressive Action Stimulus Test (BEAST).
Construction and Validation of a Stimulus Basis for Measuring Perception of Whole Body
Expression of Emotions. Front Psychol *2*, 181–181.

de Gelder, B., Snyder, J., Greve, D., Gerard, G., and Hadjikhani, N. (2004). Fear fosters flight: a
mechanism for fear contagion when perceiving emotion expressed by a whole body. Proc Natl
Acad Sci U S A *101*, 16701–16706.

Glasser, M.F., Coalson, T.S., Robinson, E.C., Hacker, C.D., Harwell, J., Yacoub, E., Ugurbil, K.,
Andersson, J., Beckmann, C.F., Jenkinson, M., et al. (2016). A multi-modal parcellation of human
cerebral cortex. Nature *536*, 171–178.

Goeleven, E., De Raedt, R., Leyman, L., and Verschuere, B. (2008). The Karolinska Directed
Emotional Faces: A validation study. Cognition & Emotion *22*, 1094–1118.

Grafton, S.T., and Hamilton, A.F. de C. (2007). Evidence for a distributed hierarchy of action
representation in the brain. Hum Mov Sci *26*, 590–616.

Hartley, C.A., and Poeppel, D. (2020). Beyond the Stimulus: A Neurohumanities Approach to
Language, Music, and Emotion. Neuron *108*, 597–599.

Haxby, J.V., Guntupalli, J.S., Connolly, A.C., Halchenko, Y.O., Conroy, B.R., Gobbini, M.I., Hanke,
M., and Ramadge, P.J. (2011). A Common, High-Dimensional Model of the Representational
Space in Human Ventral Temporal Cortex. Neuron *72*, 404–416.

Hebart, M.N., Dickter, A.H., Kidder, A., Kwok, W.Y., Corriveau, A., Wicklin, C.V., and Baker, C.I.
(2019). THINGS: A database of 1,854 object concepts and more than 26,000 naturalistic object
images. PLOS ONE *14*, e0223792.

Hein, G., and Knight, R.T. (2008). Superior Temporal Sulcus—It's My Area: Or Is It? Journal of
Cognitive Neuroscience *20*, 2125–2136.

Hoemann, K., Wu, R., LoBue, V., Oakes, L.M., Xu, F., and Barrett, L.F. (2020). Developing an
Understanding of Emotion Categories: Lessons from Objects. Trends in Cognitive Sciences *24*,
39–51.

Ju, H., and Bassett, D.S. (2020). Dynamic representations in networked neural systems. Nature
Neuroscience *23*, 908–917.

Kanai, R., and Rees, G. (2011). The structural basis of inter-individual differences in human
behaviour and cognition. Nature Reviews Neuroscience *12*, 231–242.

King, M.L., Groen, I.I.A., Steel, A., Kravitz, D.J., and Baker, C.I. (2019). Similarity judgments and
cortical visual responses reflect different properties of object and scene categories in naturalistic
images. NeuroImage *197*, 368–382.

Kober, H., Barrett, L.F., Joseph, J., Bliss-Moreau, E., Lindquist, K., and Wager, T.D. (2008).
Functional grouping and cortical–subcortical interactions in emotion: A meta-analysis of
neuroimaging studies. NeuroImage *42*, 998–1031.

Kret, M.E., and de Gelder, B. (2010). Social context influences recognition of bodily expressions.
Experimental Brain Research *203*, 169–180.

Kret, M.E., Pichon, S., Grèzes, J., and de Gelder, B. (2011). Similarities and differences in
perceiving threat from dynamic faces and bodies. An fMRI study. NeuroImage *54*, 1755–1762.

Kriegeskorte, N., Mur, M., Ruff, D.A., Kiani, R., Bodurka, J., Esteky, H., Tanaka, K., and Bandettini,
P.A. (2008). Matching categorical object representations in inferior temporal cortex of man and
monkey. Neuron *60*, 1126–1141.

de Lange, F.P., Spronk, M., Willems, R.M., Toni, I., and Bekkering, H. (2008). Complementary
Systems for Understanding Action Intentions. Current Biology *18*, 454–457.

Langner, O., Dotsch, R., Bijlstra, G., Wigboldus, D.H.J., Hawk, S.T., and van Knippenberg, A.
(2010). Presentation and validation of the Radboud Faces Database. Cognition & Emotion *24*,
1377–1388.

LeDoux, J.E., and Hofmann, S.G. (2018). The subjective experience of emotion: a fearful view.
Current Opinion in Behavioral Sciences *19*, 67–72.

Lindquist, K.A., Wager, T.D., Kober, H., Bliss-Moreau, E., and Barrett, L.F. (2012). The brain basis
of emotion: a meta-analytic review. Behav Brain Sci *35*, 121–143.

Lindquist, K.A., Gendron, M., Feldman Barrett, L., and Dickerson, B.C. (2014). Emotion
perception, but not affect perception, is impaired with semantic memory loss. Emotion *14*, 375–
387.

Lundqvist, D., Flykt, A., and Öhman, A. (1998). Karolinska Directed Emotional Faces.

Mansouri, F.A., Freedman, D.J., and Buckley, M.J. (2020). Emergence of abstract rules in the
primate brain. Nature Reviews Neuroscience *21*, 595–610.

Masson, H.L., and Isik, L. (2021). Functional selectivity for naturalistic social interaction
perception in the human superior temporal sulcus. BioRxiv 2021.03.26.437258.

Mikolov, T., Chen, K., Corrado, G., and Dean, J. (2013). Efficient Estimation of Word
Representations in Vector Space. ArXiv:1301.3781 [Cs].

Moeller, S., Yacoub, E., Olman, C.A., Auerbach, E., Strupp, J., Harel, N., and Uğurbil, K. (2010).
Multiband multislice GE-EPI at 7 tesla, with 16-fold acceleration using partial parallel imaging

with application to high spatial and temporal whole-brain fMRI. Magn Reson Med *63*, 1144–
1153.

Molenberghs, P., Cunnington, R., and Mattingley, J.B. (2012). Brain regions with mirror
properties: A meta-analysis of 125 human fMRI studies. Neuroscience & Biobehavioral Reviews
36, 341–349.

Mur, M., Meys, M., Bodurka, J., Goebel, R., Bandettini, P.A., and Kriegeskorte, N. (2013). Human
Object-Similarity Judgments Reflect and Transcend the Primate-IT Object Representation. Front.
Psychol. *4*.

Nili, H., Wingfield, C., Walther, A., Su, L., Marslen-Wilson, W., and Kriegeskorte, N. (2014). A
toolbox for representational similarity analysis. PLoS Comput Biol *10*, e1003553–e1003553.

Peelen, M.V., Atkinson, A.P., and Vuilleumier, P. (2010). Supramodal representations of
perceived emotions in the human brain. J Neurosci *30*, 10127–10134.

Peelen, M.V., He, C., Han, Z., Caramazza, A., and Bi, Y. (2014). Nonvisual and Visual Object Shape
Representations in Occipitotemporal Cortex: Evidence from Congenitally Blind and Sighted
Adults. Journal of Neuroscience *34*, 163–170.

Peirce, J.W. (2007). PsychoPy--Psychophysics software in Python. J Neurosci Methods *162*, 8–13.

Pelli, D.G. (1997). The VideoToolbox software for visual psychophysics: transforming numbers
into movies. Spatial Vision *10*, 437–442.

Pilehvar, M.T., and Collier, N. (2016). De-Conflated Semantic Representations. (Association for
Computational Linguistics), p.

Righart, R., and de Gelder, B. (2006). Context Influences Early Perceptual Analysis of Faces—An
Electrophysiological Study. Cerebral Cortex *16*, 1249–1257.

Rizzolatti, G., Cattaneo, L., Fabbri-Destro, M., and Rozzi, S. (2014). Cortical Mechanisms
Underlying the Organization of Goal-Directed Actions and Mirror Neuron-Based Action
Understanding. Physiological Reviews *94*, 655–706.

Saxe, R., Moran, J.M., Scholz, J., and Gabrieli, J. (2006). Overlapping and non-overlapping brain
regions for theory of mind and self reflection in individual subjects. Soc Cogn Affect Neurosci *1*,
229–234.

Seger, C.A. (2008). How do the basal ganglia contribute to categorization? Their roles in
generalization, response selection, and learning via feedback. Neurosci Biobehav Rev *32*, 265–
278.

Seger, C.A., and Miller, E.K. (2010). Category learning in the brain. Annu Rev Neurosci *33*, 203–
219.

Seghier, M.L., and Price, C.J. (2018). Interpreting and Utilising Intersubject Variability in Brain
Function. Trends in Cognitive Sciences *22*, 517–530.

Sinke, C.B.A., Sorger, B., Goebel, R., and de Gelder, B. (2010). Tease or threat? Judging social
interactions from bodily expressions. NeuroImage *49*, 1717–1727.

Skerry, A.E., and Saxe, R. (2015). Neural Representations of Emotion Are Organized around
Abstract Event Features. Current Biology *25*, 1945–1954.

Smith, P.L., and Little, D.R. (2018). Small is beautiful: In defense of the small-N design. Psychon
Bull Rev *25*, 2083–2101.

Stienen, B.M.C., and de Gelder, B. (2011). Fear detection and visual awareness in perceiving
bodily expressions. Emotion *11*, 1182–1189.

Stolier, R.M., and Freeman, J.B. (2016). Neural pattern similarity reveals the inherent
intersection of social categories. Nature Neuroscience *19*, 795–797.

Storey, J.D. (2002). A direct approach to false discovery rates. Journal of the Royal Statistical
Society: Series B (Statistical Methodology) *64*, 479–498.

Tucciarelli, R., Wurm, M., Baccolo, E., and Lingnau, A. (2019). The representational space of
observed actions. ELife *8*, e47686.

Vaessen, M., Heijden, K.V. der, and Gelder, B. de (2019a). Decoding of emotion expression in the
face, body and voice reveals sensory modality specific representations. BioRxiv 869578.

Vaessen, M.J., Abassi, E., Mancini, M., Camurri, A., and de Gelder, B. (2019b). Computational
Feature Analysis of Body Movements Reveals Hierarchical Brain Organization. Cerebral Cortex
29, 3551–3560.

Van den Stock, J., Hortensius, R., Sinke, C., Goebel, R., and de Gelder, B. (2015). Personality traits
predict brain activation and connectivity when witnessing a violent conflict. Scientific Reports *5*.

Van Overwalle, F., and Baetens, K. (2009). Understanding others' actions and goals by mirror
and mentalizing systems: A meta-analysis. NeuroImage *48*, 564–584.

Yeo, B.T., Krienen, F.M., Sepulcre, J., Sabuncu, M.R., Lashkari, D., Hollinshead, M., Roffman, J.L.,
Smoller, J.W., Zöllei, L., Polimeni, J.R., et al. (2011). The organization of the human cerebral
cortex estimated by intrinsic functional connectivity. Journal of Neurophysiology *106*, 1125–
1165.

Zhang, Y., Han, K., Worth, R., and Liu, Z. (2020). Connecting concepts in the brain by mapping
cortical representations of semantic relations. Nature Communications *11*, 1877.

1307