General object-based features account for letter perception

Daniel Janini[1], Chris Hamblin[1], Arturo Deza[1,2], Talia Konkle[1]

1: Department of Psychology, Harvard University, Cambridge, MA 02138

2: Department of Brain and Cognitive Sciences, Massachusetts Institute of Technology,

Cambridge, MA 02139

Corresponding author: Daniel Janini; daniel_janini@g.harvard.edu

ABSTRACT

After years of experience, humans become experts at perceiving letters. Is this visual capacity attained by learning specialized letter features, or by reusing general visual features previously learned in service of object categorization? To explore this question, we first measured the perceptual similarity of letters in two behavioral tasks, visual search and letter categorization. Then, we trained deep convolutional neural networks on either 26-way letter categorization or 1000-way object categorization, as a way to operationalize possible specialized letter features and general object-based features, respectively. We found that the general object-based features more robustly correlated with the perceptual similarity of letters. We then operationalized additional forms of experience-dependent letter specialization by altering object-trained networks with varied forms of letter training; however, none of these forms of letter specialization improved the match to human behavior. Thus, our findings reveal that it is not necessary to appeal to specialized letter representations to account for perceptual similarity of letters. Instead, we argue that it is more likely that the perception of letters depends on domain-general visual features.

AUTHOR SUMMARY

In literate societies, the ability to visually recognize letters is a highly important skill. For over a century, scientists have conducted behavioral experiments to investigate how the visual system recognizes letters, but it has proven difficult to propose a model of the

feature space underlying this capacity. Here we leveraged recent advances in machine learning to model a wide variety of features ranging from specialized letter features to general object-based features. Across two large-scale behavioral experiments we find that general object-based features account well for letter perception, and that adding letter specialization did not improve the correspondence to human behavior. It is plausible that the ability to recognize letters largely relies on general visual features unaltered by letter learning.

INTRODUCTION

A hallmark achievement of the human visual system is its ability to distinguish between thousands of objects. It has long been theorized that this capacity is achieved with a rich multidimensional feature space, where different features of the space detect the presence of different shape and texture properties (1–4). Another major achievement of the human visual system is its ability to distinguish between stimuli within specific domains (e.g., faces, letters). Longstanding debates concern which domains are represented with specialized mechanisms separate from the general mechanisms supporting object recognition (5–11). Letters are one domain of visual stimulus that literate humans expertly perceive. For example, if you are reading this paper visually, you have rapidly and effortlessly perceived over 600 letters since the start of this paragraph. What feature space allows for letters to be so easily perceived – the same feature space that supports object perception, or a feature space learned specifically for letters?

Functional neuroimaging studies indicate that learning to read alters the functional responses of visual cortex, but these findings have left open the nature of the visual feature space that underlies our perception of letters. It is clear that the intensive process of learning to read reshapes the macro-scale organization of visual cortex (5,12,13). Most prominently, in literate adults, a region of inferotemporal cortex termed the visual word form area exhibits preferential responses to letter strings, with perhaps the highest responses reserved for the letters of one's own alphabet (14–17). However, these brain-based changes are compatible with multiple learning stories, leaving open competing possibilities for the nature of features underlying letter perception. One possibility is that the visual system learns the specific visual features that are ideally tuned for categorizing the letters of one's alphabet, which we will refer to as "specialized letter features". Given the extensive reading instruction children receive and how often humans read in daily life, one might expect that the visual system learns specialized letter features. Alternatively, the visual system may learn how to categorize letters by reusing more general visual features which can support object representation. This latter possibility is articulated in the "neuronal recycling hypothesis" (12,18), where a recycling process could leave the object-based features unaltered, or it could alter the object-based features with some degree of experience-dependent specialization.

Over a century of behavioral experiments have established methods for measuring the representational similarity between visually presented letters, giving researchers a window into the underlying feature space (19–24); historically, however,

researchers have struggled to articulate a set of visual features that can account for these data (25). Similarity measurements are thought to reflect the feature space in which stimuli are represented, with perceptually similar stimuli sharing similar patterns of feature activation (26). Some early work attempted to use data-driven approaches to infer the feature space in which letters are represented, applying dimensionality reduction techniques to similarity measurements (1,20,27). Hypothesis-driven approaches have also been employed, positing that letters are represented by interpretable features such as line orientations, curves, terminations, and intersections (1,28–30). Throughout all this research, the features considered have been relatively simple visual properties accessible to experimenter intuition, and it has been nearly impossible for researchers to consider more complex object-based feature spaces. Indeed, as early as the 1960s, researchers studying letter perception lamented their dependence on intuition and wished for models capable of learning feature spaces on their own (1,3).

In the past decade, vision scientists have gained access to such models with the advent of deep convolutional neural networks, which are capable of learning features for a variety of tasks (31,32). In particular, neural networks trained to categorize objects have shown promise for capturing feature spaces that are similar to those of the human visual system (33), predicting neural responses to objects (34–39) and behavioral measurements of object similarity (40,41). Further, these networks are not trained to match the human visual system, so their correspondence to human perception is a natural consequence of the structure of the natural images, the constraints of the

trained task (e.g., categorization), and the prior of the deep convolutional network architecture. Most importantly for the sake of this paper, the nature of the feature spaces learned by a neural network are under experimental control. A convolutional neural network trained to categorize letter images into one of twenty-six categories will learn a hierarchy of feature spaces that are specialized for letter categorization, as the model only ever received letter images as input and only ever learns features to support letter classification. The same network architecture trained to categorize object images into one of a thousand categories will instead learn a hierarchy of more general object-based feature spaces. In this way, we used convolutional neural networks to operationalize different kinds of feature spaces, enabling us to explore whether these domain-specialized or domain-general features better account for the perception of letters.

In this project, we investigated the visual representations supporting letter perception by taking a behavioral-computational approach. We first measured the similarity of Roman alphabet letters in two behavioral tasks, visual search and letter categorization. Then, through the use of representational similarity analysis (42), we compared how well the features spaces learned from letter-trained vs object-trained deep convolutional neural networks could account for the behaviorally measured similarity of letters (**Figure 1A**). To preview the main results, we found that the object-trained features showed a more consistent correspondence to the behavioral tasks. Further, different attempts to alter these general-object-based features with experience-dependent letter specialization did not improve their ability to account for

the behavioral data. These findings lend computational plausibility to the theoretical position that letter perception is supported by general object-based features. By extension, we hypothesize that intensive letter learning may reflect the construction of read-out mechanisms which access (rather than alter) this general visual feature space.

RESULTS

Letter Search

We measured the perceptual similarity of letters in a large-scale online visual search task. Specifically, participants (n = 222) located the odd-letter-out as quickly as possible in displays with one letter among five other letters of a different identity (e.g., the letter a among five letter b's; **Figure 1B**). Visual search is faster when the target is more perceptually distinct from the distractors, and it is slower when the target is more similar to the distractors (43); in this way, visual search time serves as an implicit measure of the perceptual similarity between stimuli (44–49). Reaction times were measured for all pairs of 26 lowercase letters in 20 fonts, yielding a 26x26 representational dissimilarity matrix (RDM) reflecting the pairwise similarities of letters averaged across font variation. This experimental paradigm yielded a highly reliable RDM across participants and fonts (Spearman-Brown Corrected Reliability ρ=0.89, see Methods). The perceptual similarity of letters is visualized with a multi-dimensional scaling projection in **Figure 1B**.

Next, we leveraged convolutional neural networks to operationalize different features. To operationalize general object-based features, we considered the features of AlexNet trained to do 1000-way object classification on the ImageNet database

(31,50). Even though this object-trained network was never trained to distinguish between letter identities, its features can generalize to the task of letter recognition by supporting the linear decoding of letter identity across font and size variation (mean pairwise decoding accuracy of 95-97% in Layers 3-7, see Supplementary Fig 1). To operationalize specialized, domain-specific features, we trained another AlexNet model only on letter images, tasked to do letter classification across font variability and a variety of augmentations, over both typeset and handwritten characters (see Methods). The letter-trained model achieved 98.5% Top-1 accuracy on letter classification (Supplementary Table 1).

First, we examined the extent to which these two networks differed in how they represent letter information. To measure the representational structure of letters learned in these two different networks, we constructed model RDMs for each layer by measuring the feature activations to each letter stimulus and calculating the pairwise distances between letters in these feature spaces. This procedure yielded a hierarchical set of object-trained and letter-trained model RDMs. Next, we computed the correlation between the object-trained RDM and the letter-trained RDM for each layer. Correlations between the two models' RDMs were high in early layers (r = 0.98 and r = 0.86 for Layers 1 and 2) but decreased by the later layers (r = 0.41 and r = 0.37 for Layers 6 and 7; see full list of correlations in Supplementary Figure 2). Thus, both the object-trained and letter-trained networks have feature spaces that can support successful letter

classification, but they differ in terms of the feature spaces that support this performance.

How well do the feature spaces from the object-trained network and letter-trained network correspond to the representational space measured when human participants distinguish between letters? To answer this question, we calculated the Spearman correlation between each of the model RDMs and the perceptual RDM measured in the visual search task. The results are plotted in **Figure 1B**. Across the layers, the object-trained feature spaces yielded model-behavior correlations that were moderate in early layers and stronger in the mid-to-late layers. In contrast, model-behavior correlations in the letter-trained feature spaces were only high in Layer 4, with moderate correlations in early layers and poor correlations in later layers. Direct statistical comparisons between these models at each layer showed that the object-trained network exhibited higher model-behavior correlations in Layers 3-7 ($p < 10^{-4}$ for Layers 3 and 5-7, $p = 0.0219$ for Layer 4, bootstrap resampling of letter pairs), while the letter-trained network exhibited a higher model-behavior correlation only in Layer 1 ($p = 0.0166$, bootstrap resampling of letter pairs). In addition, we computed model-behavior correlations separately for each font tested, and we found that the maximum model-behavior correlations were higher for the object-trained network than the letter-trained network ($t(19)=5.62$, $p < 10^{-4}$).

These results show that at least one layer of both the letter-trained network and object-trained network exhibited a decent correspondence with the perceptual similarity

of letters. However, when comparing the two models, the object-trained model exhibited more consistent model-behavior correlations in the mid-to-late layers.

Letter Categorization

While our visual search experiment required participants to discriminate between letters, we note that visual search does not require participants to perform explicit letter categorization. For example, it is possible to complete visual search with letters from an alphabet one cannot read. Thus, we next conducted a second large-scale behavioral experiment in which we measured the perceptual similarity of letters using a categorization task. Both visual search and categorization are perceptual tasks, but the two tasks require different processes. Categorization involves holding a target letter template in mind and comparing it to the incoming stimulus, while visual search involves distinguishing between simultaneously presented stimuli. Thus, it is possible that the categorization task will measure a distinct representational structure of letters more suited to explicit categorization. This representational structure may better correspond with the letter-trained network given that this network was trained to categorize letters. On the other hand, prior empirical evidence shows that visual search speeds and categorization speeds are deeply related and may actually be constrained by the same underlying perceptual representational bottleneck (46,51).

In the categorization experiment, single letters were presented at fixation and the task was to categorize each letter as quickly as possible. Participants (n=517) were given a target letter (e.g., "a") and responded whether each presented letter was the

target or not ("a" or "not a"; **Figure 1C**). The critical trials were those in which the

presented letter was *not* the target. We measured the time it took to reject these letters

as an index of their similarity to the internally represented target letter (see also Cohen

et al., 2017 for this method). By assigning each letter as the target across sets of trials,

we measured the perceptual similarity of each possible letter pairing. Each participant

could only be tested on a subset of letter pairings in a reasonable experiment duration,

so we systematically distributed letter pairings across participants and used linear mixed

effect modeling to estimate the full 26x26 letter RDM (see Methods). This experiment

and modeling procedure yielded a reliable RDM across participants (Spearman-Brown

Corrected Reliability $\rho = 0.78$, see Methods). The mean accuracy among included

participants was 97.2±2.0%.

Next, we tested our main question: how well do general object-based features

and specialized letter features account for letter similarity measured during

categorization? The correlations between the behaviorally measured RDM and the

model RDMs from object-trained AlexNet and letter-trained AlexNet are shown in

Figure 1C. The object-trained network showed the highest correlation with the

categorization-based RDM ($p = 0.0008$, bootstrap resampling of letter pairs), with lower

model-behavior correlations in early layers and higher correlations in mid-to-late layers.

Model-behavior correlations from the letter-trained network did increase some from low-

to-mid-layers but not to the same extent as the object-trained network, and correlations

decreased in later layers. When comparing each layer between the two networks, the

object-trained network exhibited higher model-behavior correlations in Layers 3-7 ($p <=$

0.0002 in each layer), and the two networks did not differ in Layers 1 and 2 ($p = 0.8276$ and $p = 0.1264$, respectively).

Thus, the results from the categorization experiment were like those found in the visual search experiment, but with a relatively stronger dissociation between the two kinds of features. Specialized letter features were not necessary to account for human letter perception, as object-based feature spaces best accounted for the perceptual similarity of letters, with features of mid-to-late layers showing the highest correspondence.

A. Neural Network Model Feature Spaces

B. Experiment 1: Visual Search

C. Experiment 2: Letter Categorization

Figure 1. Results from the Visual Search and Categorization Experiments. A. Neural networks used to operationalize general object features and specialized letter features. AlexNet trained on 1000-way object classification was used as a model of general object-based features, and AlexNet trained on 26-way letter classification was used as a model of specialized letter features. B. Experiment 1: Visual Search. The structure of the behavioral task is displayed on the left. Reaction time was considered a measure of the perceptual similarity of the two letters, with slower reaction times indicating greater similarity. In the middle is a visualization of the pairwise letter similarities measured in the visual search task. More similar letters are closer together in this multidimensional scaling display. On the right, model-behavior correlations between the model RDMs and the RDM from the visual search experiment are plotted on the y-axis, as a function of the layer of the AlexNet model. The shaded error range indicates the 95% confidence interval across bootstrapped samples of letter pairs. C. Experiment 2: Letter

Categorization. Example trials are shown on the left. Participants were given a target letter (e.g., "a") and categorized each letter as "a" or "not a" as quickly as possible. The time to reject a letter was a measure of its similarity to the target letter. In the middle is a visualization of the pairwise letter similarities measured in the categorization experiment. On the right, model-behavior correlations are plotted as before.

Comparisons between visual search and categorization tasks

Direct comparisons of the two behavioral experiments reveal similar representational structure. That is, there was a high correlation between the RDMs measured in our visual search and categorization experiments ($\rho = 0.71$). In fact, the correlation between the two experiments was nearly as high as the noise ceiling of the categorization-based RDM ($\rho = 0.78$), implying that almost all the reliable variance in the categorization-based RDM was accounted for by the visual search RDM. In contrast, the correlation between the two experiments was a bit lower than the noise ceiling of the visual search RDM ($\rho = 0.89$). MDS plots depicting the representational space of letters from the two experiments, in addition to the representational spaces from object-trained and letter-trained AlexNet, can be viewed in Supplementary Figure 2. Thus, both experiments largely measured the same representational space for letters, but the RDM from the visual search experiment contained some reliable variance not measured in the categorization experiment. Our data thus indicate that there is a similar representational structure underlying both perceptual tasks that is accounted well by general object-based features.

Models of object-based features with experience-dependent specialization

So far, we have investigated two extremes in a spectrum of possibilities: from purely letter-specialized features on one end, to object-based features unaltered by experience with letters on the other end. However, a variety of feature spaces exist between these two extremes involving object-based features that are subsequently altered by letter learning. Further, while close, no models have yet reached the noise ceiling of the behavioral data, so there is some reliable, behaviorally relevant representational structure not accounted for by the object-trained model RDMs. Thus, we next altered object-based spaces with letter specialization, using three different approaches which each operationalize a different hypothesis about how experience-dependent specialization could be accomplished.

First, we considered fine-tuning operations. Perhaps extensive visual practice with letters alters the tuning of object-based features learned prior to letter training. To explore this possibility, we created a finetuned model in which AlexNet was first trained on object classification, then next trained to categorize both objects and letters, with the final 1000-way object classification layer replaced by a 1026-way classifier for 1000 objects and the 26 letters. By fine-tuning with a mixture of objects and letters, we created a network that could classify both objects and letters (see Supplementary Table 1), preventing the "catastrophic forgetting" of previously learned features that can occur when training a network on a sequence of tasks (52). Comparing the original and fine-tuned networks, we found that the learned feature spaces were similar through the early

and mid-layers (RDM correlations across layers 1-5: range: r = 0.795-0.995), while the

RDMs from the fully connected layers started to show more divergence (r = 0.68 and r =

0.57 in Layers 6 and 7, respectively), opening the possibility that the finetuned model

would better account for the perceptual similarity of letters. However, as shown in

Figure 2a, the highest model-behavior correlation in the finetuned network was either

worse than in the original object-trained network (p = 0.0037 for visual search) or they

did not differ (p = 0.9980 for letter categorization, bootstrap resampling of letter pairs).

Additionally, we created another fine-tuned model in which letter training alone

followed object training, with the final 1000-way object classification layer replaced by a

26-way letter classifier. Again, this method of fine-tuning either did not significantly

affect the maximum model-behavior correlation (p = 0.0848 for visual search) or actually

decreased the network's maximum model-behavior correlation (p = 0.00024 for letter

categorization). Thus, fine-tuning object-based features with letter training did not yield

representations more similar to the representational structure evident in behavior.

Next, we considered branching networks. Perhaps specialized letter features are

built from object-based features by branching at some stage of the object-based

hierarchy. To explore this account, we created a family of branching neural networks –

each a five-layer neural network with input from one of the first five layers of object-

trained AlexNet. The branches were trained to perform letter classification without

altering the object-based features they took as input (see Methods). Results are shown

in **Figure 2b**. None of these branches exhibited a higher maximum model-behavior

correlation than object-trained AlexNet. Because object-trained AlexNet exhibited high model-behavior correlations in Layers 3-5, one might have expected that branches from these layers would have transformed the feature space to better match the behaviorally measured similarity of letters. In fact, the opposite occurred, and for each of these network branches, model-behavior correlations decreased from the object-trained input space to the final layer of the specialized letter space (each $p < 10^{-4}$ for both visual search and letter categorization, bootstrap resampling of letter pairs). If anything, transitioning the representational space from object-based to letter-based made the resulting structure less like the structure evident in our behavioral experiments.

In a similar vein as the branching networks, we also tested a previously published model from Testolin et al. (53), which learned specialized letter features operating over a bank of general low-level features. We again found that the features of the object-trained AlexNet exhibit higher correlations with both behaviors than the specialized letter features ($p < 10^{-4}$ for both visual search and letter categorization, bootstrap resampling of letter pairs; see Supplementary Fig 3).

Finally, we explored the possibility that there is a letter-selective subspace embedded within the object-trained feature space, which might better capture the behaviorally-measured perceptual similarity among letters. In above analyses, the object-trained model RDMs were computed using all the features of each layer of AlexNet; however, one possibility is that letters are specifically represented by those

features which are preferentially activated by letters. Thus, we tested whether a subset

of the object-trained features exhibit letter-selectivity, even without letter training; and if

so, whether these letter-selective features constitute a feature subspace that better

accounts for the behavioral data.

To do so, we identified features in object-trained AlexNet which preferentially

responded to letters over objects, following procedures in Prince & Konkle (54).

Between 3-22% of features in each layer preferentially responded to letters. We

calculated the correlations between the RDMs from these letter-selective features and

the RDMs from our visual search and letter categorization experiments. Results are

shown in **Figure 2c**. The highest model-behavior correlation from the letter-preferring

features did not differ from the highest model-behavior correlation from the full object-

based feature spaces (p = 0.2104 for visual search, and p = 0.1323 for letter

categorization, bootstrap resampling of letter pairs), nor did it differ from a matched

number of randomly selected non-letter preferring features (p = 0.1824 for visual

search, and p = 0.0812 for letter categorization, bootstrap resampling of letter pairs).

We also conducted the same analysis for the letter-preferring features of AlexNet

finetuned on letters and objects, and the maximum model-behavior correlations were

either lower than AlexNet trained on object classification alone (p = 0.00028 for visual

search) or they did not differ (p = 0.3221 for letter categorization, bootstrap resampling

of letter pairs). Thus, it is not the case that there is a letter-preferring subspace of the

object-based feature space that better captures the perceptual similarity of letters.

Figure 2. Experience-dependent specializations for letters. A. Fine-tuning. An object-trained network was fine-tuned on letters alone (yellow) or with objects and letters (red). Layer-wise model-behavior correlations are shown for visual search (center), and letter categorization (right). The dashed-blue line indicates the performance of an object-trained network, for reference. B. Branching networks. Five branching networks were trained, with the input to each network from each of the first five ReLU layers of AlexNet trained on ImageNet and trained to do 26-way letter categorization (dark red to light orange). Adjacent plots show the model-behavior correlation of these networks, beginning with the final object-trained layer (dashed lines), followed by the specialized hierarchical feature spaces learned in the 5-layer branching networks. C. Subspace. In each layer of object-trained AlexNet, features were identified that showed higher activation to letter stimuli than objects, and the representational space for letters was measured in this letter-preferring subspace. The model-behavior correlations are shown in adjacent

subplots. The shaded error range indicate the 95% confidence interval across bootstrapped samples of letter pairs. Note that these shaded error ranges have been omitted for (A) and (B) for visualization clarity but were conducted for statistical tests.

Taken together, across these theoretically distinct approaches for how letter-based specialization could modify object-based feature spaces, we did not see any improvements in the correlations with the behaviorally measured similarity of letters. In fact, when experience-dependent specializations did change the model-behavior correlations, it was for the worse. Thus, the general feature spaces of AlexNet trained on ImageNet were the best of the models we explored, accounting very well for the similarity of letters, though a small amount of reliable variance in the behavioral similarity space of letters remains to be explained.

Additional Model Comparisons

We conducted several robustness tests and comparison models to further contextualize the results from object-trained AlexNet and letter-trained AlexNet. In comparison to a pixelwise model of similarity, we found that both the object-trained network and letter-trained network exhibited higher maximum model-behavior correlations (all $p < 10^{-4}$ for both visual search and categorization, bootstrap resampling of letter pairs). In addition, both the object-trained network and the letter-trained network exhibited a higher maximum model-behavior correlation than AlexNet with random weights (all $p < 10^{-4}$ for both visual search and categorization, bootstrap resampling of letter pairs; see Supplementary Figure 4). Finally, we considered another object-trained network which learned features from stylized ImageNet (55). For the

visual search experiment, the maximum model behavior-correlation from AlexNet trained on stylized ImageNet ($\rho = 0.72$) was a bit higher than the maximum model-behavior correlation from the typical object-trained network ($\rho = 0.69$; $p = 0.0338$, bootstrap resampling of letter pairs). For the categorization experiment, maximum model-behavior correlations did not significantly differ between stylized-ImageNet-trained AlexNet and the typical ImageNet-trained AlexNet ($p = 0.1575$, bootstrap resampling of letter pairs). Thus, both object-trained AlexNet and letter-trained AlexNet learned features accounted for the perceptual similarity of letters better than pixelwise and random feature models, and another model of object-based features also corresponded well with the behavioral data.

Previously, we kept the architecture constant between the object- and letter-trained networks to ensure that differences in learned features were due to the input image sets alone. However, while large architectures are needed to solve object categorization, much smaller networks can be trained to accurately classify written symbols (56). A smaller network may learn different features from a larger network, and it may be less likely to overfit to the training set. Therefore, we tested whether a smaller network would better approximate the behavioral data from our two experiments. We trained a smaller architecture on letter categorization (see Methods), then calculated the correlations between each of its layer-wise RDMs and the visual search RDM. While this model could also classify letters accurately, it only exhibited moderate correlations with the perceptual similarity of letters as measured in the visual search and categorization experiments (see Supplementary Figure 5). In both experiments, object-

trained AlexNet exhibited a higher maximum model-behavior correlation than the small letter-trained network ($p < 10$^-4 for visual search, $p = 0.00036$ for categorization, bootstrap resampling of letter pairs). Thus, a shallower letter-trained network still did not better account for perceptual similarity of letters in comparison to the object-trained model.

In earlier iterations of this project, our letter-trained networks were trained on only typeset images with a less variable augmentation scheme. In comparison to the main letter-trained networks reported in this study, the previous letter-trained networks showed an even weaker correspondence with the perceptual similarity of letters (see Supplementary Figure 6). These model explorations highlight that in addition to the domain of input images and the classification task, the scope of data augmentations has a clear impact on the formation of neural network feature spaces, and their resulting correspondence with perceptual similarity measures.

Finally, we considered a set of intuitive features previously proposed in the literature on letter perception, including line orientations, curves, intersections, and terminations (28–30). The model RDM computed from these intuitive features exhibited a moderate correlation with the visual search RDM ($\rho = 0.42$ for visual search and $\rho = 0.52$ for categorization); however, object-trained AlexNet again exhibited higher model-behavior correlations ($p < 0.001$ for both visual search and categorization, bootstrap resampling of letter pairs).

DISCUSSION

Here we probed the nature of the representations supporting letter perception, using a behavioral-computational approach. We trained a set of deep convolutional neural networks to operationalize different feature spaces, ranging from fully letter-specialized to more general and object-based, and estimated how well they could account for the behavioral similarity structure underlying two different letter perception tasks. We found that 1) the general object-based feature spaces best accounted for behavioral data on letter perception in comparison to the specialized letter features; 2) various attempts to add experience-dependent letter representations to the object-based features did not improve how well our models accounted for the behavioral data. Taken together, these results support the plausibility of the claim that letter perception is supported by a set of more general object-based features that can discriminate among many kinds of visual input.

Our findings develop the neuronal recycling hypothesis by comparing multiple ways in which object-based features could be adapted for letter perception. This framework proposes that learning to recognize letter strings involves the "minimal adaptation" of object representations in inferotemporal cortex (57,58). However, a range of possible mechanisms with varying degrees of letter specialization are compatible with this learning account, from learning linear classification boundaries over object-based features, to different forms of experience-dependent specialization. Previously, Testolin et al. (2017) investigated one mechanism of neuronal recycling – learning specialized

letter features which take general low-level features as input. This partially specialized

feature space showed several properties of human perception including correlating with

the perceptual similarity of letters, supporting letter decoding in noise-degraded images,

and exhibiting superior letter decoding for fonts with lower perimetric complexity. These

findings led Testolin et al. (2017) to conclude that letter perception primarily relies on

domain-general visual features with some degree of domain-specific tuning. Our

findings also support the claim that letter perception relies on domain-general features;

however, by studying a broader range of neuronal recycling mechanisms we argue for a

fully domain-general account of recycling. By investigating a hierarchy of general object-

based features we found that mid-to-high level features exceeded low-level features in

their ability to account for letter perception. These complex object-based features

accounted for letter perception so well that a variety of models with partial letter

specialization, including the model from Testolin et al. (2017), failed to show a superior

match to human perception. Thus, the range of models we tested provide evidence that

visual letter perception primarily relies on the recycling of features unaltered by letter

learning.

Recent findings using other methodologies also corroborate our computational-

behavioral evidence for this claim. For example, both readers and non-readers of an

alphabet have nearly identical representational geometries for letters, as measured

using a visual search paradigm over two different Brahmic scripts (44). Further, in the

macaque visual system, letters and words can be linearly decoded from neural

responses of inferotemporal cortex in monkeys who have never been trained to distinguish between letters (58). Together with our findings, these studies indicate that prior to learning to read an alphabet, the visual system already has complex general features which adequately distinguish between letters, and that learning to recognize letters may make at most negligible changes to this feature space.

An additional insight offered by this work is related to the complexity of the feature spaces. By leveraging the layer hierarchy of deep convolutional neural networks, we found that mid-to-late layers of the object-trained network, rather than the earliest layers, best accounted for the behaviorally measured similarity of letters. Thus, both qualitative characterizations of deep neural network feature tuning and intuitions about feature hierarchies suggest that the features underlying letter perception likely exhibit greater complexity than simple edge detectors (59). The intermediate-level complexity of these underlying features clarifies why simple feature models failed to fully capture letter similarity structure (1,28–30) and why early data-driven attempts to infer the feature space resisted easy interpretation (1,20,27). These layer-wise results also complement recent findings in macaques, in which letter identity could be more accurately decoded from inferotemporal cortex than from the earlier stage region of V4 (58). It has been theorized that object contour representations, specifically line junctions, are recycled to represent letters (60,61), which may lead some to assume that low-level edge detectors should account for letter perception. However, studies of the perception of line drawings (62) indicate that object contours are actually fairly high-

level representations abstracted from illusory edges created by illumination and shadows. Thus, while letters may appear to be relatively simple visual stimuli, our findings demonstrate that mid-to-high level features underlie our perception of letters, complementing previous research.

While our work here makes inferences about the nature of visual system representations through a behavioral-computational approach, our findings also lead to predictions about the representations of the visual word form area in the ventral stream. Neuropsychological studies have found that damage to the left occipitotemporal cortex (in the vicinity of the visual word form area) leads to slow and laborious letter-by-letter reading of words, though debates surround the extent to which such patients also show deficits in object perception (63,64). In addition, studies on the connectivity constraints between language regions and occipitotemporal cortex support the view that information on letter strings is preferentially read-out from the visual word form area (65–69). These neuropsychology and connectivity studies help arbitrate on whether causally relevant information on letter strings is represented in a local region of visual cortex. However, these findings do not directly speak to the nature of the feature tuning in this region - whether the features are specifically tuned to distinguish between letters, or if they are more generally tuned to distinguish among all visual inputs. Based on our behavioral findings, we make the following brain predictions about responses to letters in the visual word form area. First, we predict general object-based features will account for the representational space for letters both before and after letter learning. Second, we

predict letter learning will not create new patterns of response to letters in the visual

word form area. Instead, we predict that letter learning will increases the amplitude of

those patterns, facilitating read-out by increasing their signal-to-noise ratio.

In this study, we chose to focus on individually presented lowercase letters in the

Roman alphabet, raising the question of whether our claims would differ if our

behavioral tasks and models were aimed at letter-string and word-level representations.

This would be the case if the visual system learns specialized features for detecting

combinations of letters en route to whole word representations (70). However, focusing

on individual letter-representations is not wholly unjustified, as there is some empirical

support that letter string representations are simply linear combinations of letter

representations (44). For example, the perceptual similarity of bigrams as measured

through visual search is linearly predictable from the perceptual similarity of their

constituent letters (44). In addition, our work does not address the perception of non-

alphabetical writing systems. Future behavioral-modelling work could leverage the

approaches used here to investigate the extent to which other written symbol

representations rely on general versus specialized feature spaces.

While the object-based spaces considered in our study account well for the

perceptual similarity of letters, they did not reach the noise ceiling of our data, raising

the question of what model could fully account for the behavioral data. General object-

features and specialized letter features were operationalized in this paper through one

class of models (discriminative, deep neural networks). Perhaps a different class of computational model could fully explain the perception of letters, for example, generative Bayesian models trained on the motor routines used to produce letters (71). However, it is also possible that this small predictive gap for letter perception is simply due to the fact that object-trained neural networks only capture some aspects of human object perception (55,72–75). For example, object-trained neural networks tend to represent local contour and texture features more so than global shape features (55,72). Given how well the object-trained model in our study accounted for the perceptual similarity of letters, it is plausible that local shape features play a substantial role in the human perception of letters. However, if human letter perception also depends on global shape features, then this may explain why our object-trained network did not reach the noise ceiling of the behavioral data. As a first step in exploring this possibility we considered the representations learned from stylized-ImageNet (55), which relies less on local features in its classifications, though this network and the typical object-trained network did not consistently differ in how well they matched the perceptual similarity of letters. Perhaps the further discovery of object-trained models with more humanlike mixtures of local and global shape features would improve our ability to account for human letter perception. Another possibility is that the object-trained networks included in our study did not reach the noise ceiling of the data because they may not have been adequately trained to learn humanlike face representations, given the relationship between cortical territories selective for words and faces (66). Exploring all of these possible alternatives is beyond the scope of this

paper, thus this work leaves a small but theoretically important puzzle in accounting for the perceptual structure of letters.

While not the primary focus of this study, this work also corroborates prior findings on perceptual bottlenecks to cognitive tasks. Previous studies have found that measurements of perceptual similarity from a variety of visual tasks (e.g., tasks relying on working memory, visual search, categorization, and visual awareness) reflect the representational structure of occipitotemporal cortex (46,76,77). In this study, the visual search experiment and categorization experiment involved different task demands and cognitive operations, but the representational structures measured in the two tasks were highly similar. These findings indicate that the representational similarity of a visual feature space creates a bottleneck for a number of perceptual tasks – for example, limiting working memory capacity as well as reaction times in visual search and categorization tasks. However, there are minor differences in the representational structures measured in each of these tasks, and future work could account for these differences by more explicitly modelling the cognitive operations which read out information from visual feature spaces.

Broadly, we view our investigation into letter perception as one case study within wider debates concerning the extent to which perception includes domain-general versus domain-specific mechanisms. We join other researchers operationalizing feature spaces with neural networks to gain insight into this debate (78). These include

investigations into the perception of a wide variety of domains of sensory input including faces (54,79); objects, scenes, and near-scale "reachspaces" (80); approximate number (81); and language and music (82). We see the approach taken in this study as broadly useful for determining the degree to which different domains of stimuli are represented by specialized mechanisms versus domain-general mechanisms.

METHODS

Experiment 1: Odd-One-Out Visual Search

Participants. 222 participants completed the visual search experiment on Amazon Mechanical Turk. All participants gave informed consent according to procedures approved by the Institutional Review Board at Harvard University.

Stimuli. The stimulus set consisted of 520 images of the 26 letters across 20 fonts. Each image depicted an individual letter, presented in lower case. The following fonts were used: Al Bayan, American Typewriter, Arial Black, Arial, Ayuthaya, Baskerville, Chalkboard, Comic Sans MS, Courier, Didot, Futura, Georgia, Helvetica, Hiragino Sans, Impact, Kefa, Kokonor, Luminari, Noteworthy, and Papyrus. All stimuli can be viewed in Supplementary Figure 7A.

Procedure. Participants completed a visual search paradigm in which they viewed a set of stimuli and detected the odd one out as quickly as possible. On each trial, the target was one letter image, and the distractors were another letter image in

the same font. Each trial started with the presentation of a blank circular arena with a fixation cross at the center for 1s. Next, six stimuli were presented in a ring around the fixation cross. The target stimulus was presented in one randomly selected position, while the distractor stimuli were presented in the other five positions. Participants were instructed to press the space bar as soon as they detected the location of the odd-letter-out. Immediately following this keypress, the positions were masked with a white-noise image for 250ms. Next, the numbers 1-6 displayed over the positions, and participants reported the location of the target by pressing the corresponding number key. After the response, there was a 500ms pause, and the next trial automatically began.

Each Human Intelligence Task (HIT) completed by participants included 325 trials, one for each possible letter pairing. The target appeared at a random location on each trial and was equally likely to appear at any of the six locations. For each pair of letters, there were 6 possible target positions, 20 possible fonts, and 2 target-distractor assignments (e.g., a among b, or b among a), yielding 240 different combinations. Each of these combinations was tested in a separate HIT; therefore, target position, font, and target-distractor assignment were counterbalanced across 240 unique HITs. Because each HIT included all possible letter pairings, this design ensured that slower or faster participants equally influenced all letter pairings in the resulting representational dissimilarity matrix.

Five of the 222 participants completed multiple assignments (4-6 HITs). Due to an error in posting the experiment to Amazon Mechanical Turk, four participants completed the same assignment as others, so their data was excluded.

Constructing the representational dissimilarity matrix. The visual search reaction times were used to construct a representational dissimilarity matrix between pairs of letters. First, all incorrect trials were excluded (2.5% of trials). Then the reaction times from each HIT were log-transformed to account for the positive skew of the data (Palmer et al., 2011) and z-scored. Because each HIT tested all the letter pairs, these z-scores reflect the relative speed of each letter pairing in the distribution of all possible letter pairings. Trials that were more than three standard deviations from the mean were excluded. Next, we calculated the mean z-scored reaction time for each pair of letters across all the HITs. These values were multiplied by -1, so that higher numbers reflect more dissimilar letter pairs, and were used to fill the lower triangle of a 26x26 representational dissimilarity matrix (RDM).

Noise Ceiling Calculation. We determined the noise ceiling of the visual search data by measuring its reliability across HITs. We split the HITs in half by font, with each set containing all the HITs from ten of the twenty fonts. We calculated the RDM for each set of HITs, then we found the Spearman correlation between the two RDMs. This was conducted for all possible splits of the twenty fonts (184,756 splits). The mean of all these correlations was a measure of the reliability of a sample half the size of our full

sample. Finally, we used the Spearman-Brown prediction formula ($\frac{2*\rho_{12}}{1+\rho_{12}}$, where ρ_{12} is

the reliability of half the sample) to estimate of the reliability of our full sample. We

assume that this is the best we could expect any model to correlate with the data.

Error RDMs. While errors were not the planned target of the experiment, we also

constructed RDMs based on the mean accuracy of each letter pair. The accuracy-

based RDM was moderately reliable ($\rho = 0.44$) and was moderately correlated with the

RT-based RDM ($\rho = 0.47$).

Experiment 2: Letter Categorization

Participants. 518 participants completed the letter categorization experiment on

Amazon Mechanical Turk. All participants gave informed consent according to

procedures approved by the Institutional Review Board at Harvard University.

Stimuli. Stimuli were the same as the visual search experiment. Images were

sized and positioned to align the baseline of the letters.

Procedure. Participants were shown single letters one after another and

categorized them as quickly as possible. Each HIT consisted of two blocks of trials. At

the start of each block, participants were given a target letter (e.g., "a") via visual text in

font Arial. Each trial began with the presentation of an empty square arena for 750ms,

after which a single letter in a random font appeared in the middle of the arena.

Participants responded as quickly as possible whether it was an example of the target letter or not. Participants pressed "[" if the stimulus was an example of the target letter or "]" if the stimulus was not an example of the target letter. The next trial automatically began after the participant's response. If participants did not respond within 1250ms, then a screen appeared with the message: "Sorry, too slow! Answer quickly and correctly." If participants answered incorrectly, then a screen appeared with the message: "Try to answer each trial correctly."

The key measure we were interested in is the time it takes a participant to reject letters that did not match the target. We assume that letters that are more similar to the target will take longer to reject. For example, if the target for a given block of trials was "a" and the letter presented on a given trial was "b", then we would consider the reaction time of that trial to reflect the perceptual similarity between "a" and "b". Thus, we considered the reaction time of non-matching trials as a measure of the perceptual similarity of letters.

We measured the reaction times of all 650 possible pairs of targets and non-target letters across 664 HITs. To keep the length of each HIT under approximately 20 minutes while also obtaining reliable data, only a subset of all letter pairs could be measured in each HIT. Each HIT measured the perceptual similarity of 26 letter pairs, with 13 letter pairs included in each of the two blocks. Different target letters were assigned in the two blocks. Half the trials matched the target and half did not to prevent the creation of a bias toward either response. Each HIT included 416 trials, with each non-target letter repeated in 8 trials. Across all the HITs, each letter pairing was

measured in 50-56 HITs. These experimental design choices were made with the goal

of using linear-mixed effect modeling to estimate the reaction time of each pair of letters

while accounting for differences in overall reaction time between participants. Before

running the main large-scale experiment, we first ran a separate pilot study measuring

the similarity of 50 letter pairs to ensure that our design and counterbalancing

procedures would yield reliable data.

69 of the 517 participants completed multiple HITs, each completing up to 12

HITs. Data from 55 HITs were excluded because the trial accuracy was below 90%.

Data from one HIT was excluded because it did not save properly.

Constructing the representational dissimilarity matrix. First, incorrect trials were

excluded from each HIT. Next, the mean reaction time was calculated for each of the 26

target/non-target letter pairs tested in each HIT. If more than 4/8 trials for that pair of

letters were incorrect, then the mean reaction time for that pair of letters was excluded.

Across all the HITs, this data was compiled into a matrix with columns for three

variables: 1) a categorical variable (Condition) specifying the letter pair tested, 2) a

continuous variable (RT) specifying the mean reaction time for that letter pair, 3) a

categorical variable (HIT) specifying the HIT in which that mean reaction time was

collected.

We computed a linear mixed effects model to estimate the reaction time for each

letter pair across the HITs with the following equation: RT~Condition+(1|HIT). The

categorical variable of condition was dummy coded, so the model yielded an estimate of how each letter pair's reaction time differed from a reference letter pair. We added the estimated reaction time of this reference letter pair to every condition to get the estimate of their reaction times. For each pair of letters, there were two conditions corresponding to the two target/non-target assignments (e.g., the target is "a" when "b" is presented versus the target is "b" when "a" is presented). We took the mean of these two conditions to estimate the perceptual similarity of each pair of letters. The estimates of letter similarity were then multiplied by -1 to convert them into estimates of letter dissimilarity and inputted into the lower triangle of a 26x26 RDM.

Noise Ceiling. We determined the noise ceiling of the categorization data by measuring its reliability across measurements of each letter pair. Each letter pair was measured in at least 41 HITs after exclusion. We divided these measurements in half, so each split of the data included an equal number of measurements per letter pair. We calculated the RDM for each split of the data using the same procedure as above. Then we found the Spearman correlation between the two RDMs to measure the reliability of a sample half the size of our full sample. We completed this procedure across 10,000 random splits and calculated the mean split-half correlation. Finally, we used the Spearman-Brown prediction formula ($\frac{2*\rho_{12}}{1+\rho_{12}}$, where ρ_{12} is the reliability of half the sample) to estimate the reliability of our full sample. We assume that this is the best we could expect any model to correlate with the data.

Error RDMs. While errors were not the planned target of the experiment, we also

constructed RDMs based on the mean accuracy of each letter pair. The accuracy-

based RDM was moderately reliable ($\rho = 0.52$) and was moderately correlated with the

RT-based RDM ($\rho = 0.55$).

Neural Network Models

Primary Models

To obtain a model of general object-based features, we used an instantiation of

AlexNet trained to do 1000-way object classification on the ImageNet database (31,50),

available through the PyTorch ModelZoo. More specifically, AlexNet was trained on the

subset of ImageNet used in the 2012 ImageNet Large Scale Visual Recognition

Challenge (83).

To obtain a model of specialized letter features, we trained a randomly initialized

instantiation of AlexNet to do 26-way letter classification on a database including

typeset letter images we call GoogleFonts and handwritten letters from the NIST

database (84). By solely training this network with images of letters it could only learn

features present in letter images (rather than also training it with object images, which

would give the network the chance to learn both object and letter features). The

GoogleFonts database includes 60958 images, with each lowercase letter depicted in

2344 different fonts. When creating this database, we included fonts which had all

twenty-six lowercase letters, were not in cursive, and did not produce identical images

to another font. Example images from the GoogleFonts database can be viewed in

Supplementary Figure 7B. To introduce more variability to the images our letter-trained

models were exposed to, we included 1000 images per letter category from the

EMNIST database (84) in the data set, bringing the total number of images per class to

3344. 20% of these images were reserved for a test set, while the other 80% were used

for training.

Additionally, the following data augmentations were included during the training

of the letter model: 1. Varying the size of the letter within the image such that the

maximum size was 4x the minimum size in each dimension, 2. Varying the position of

the letter to be uniformly distributed in the image plane, 3. Uniformly distributed random

tilt between $\pm$15 degrees, 4. Uniformly distributed random horizontal and vertical shears

with a factor between .8 and 1.25. 5. Random letter and background color, under a

minimum contrast constraint. 6. Gaussian additive pixel noise with a standard deviation

uniformly selected from .01-.1 per image (given black/white pixel values have been

normalized to 0/1). We applied each of the above augments with a 60% probability

during training to ensure that the model was exposed to typical letter images in addition

to the augmented images. This allowed for the models to learn to classify both

augmented letters and the more typical letters used in the human experiments. Example

augmented images can be seen in Supplementary Figure 8.

The model was trained on minibatches of 64 images for 100 epochs using the

Adam optimizer (85), with betas .9 and .999, and an initial learning rate of .001. The

model epoch with highest test set accuracy was selected for comparison with human subjects.

Additionally, reasoning that Alexnet has far more parameters than necessary for letter classification, we created another model of specialized letter features by training a smaller five-layer CNN on the GoogleFonts and EMNIST database in the same manner. Architecturally, this network had 3 convolutional layers followed by 3 fully connected layers, with 4x4 adaptive average pooling in between. The first convolutional layer had 5x5 kernels, with a stride of 2, padding of 3, and 40 output channels. The next two convolutional layers had 3x3 kernels, with strides and padding of 1, with 20 and 60 output channels respectively. The fully connected layers had 500, 200, and 26 output channels, with 50% dropout between layers during training. All layers used ReLU activations.

All model test set accuracies can be viewed in Supplementary Table 1.

Models of object-based features with experience-dependent specialization

Two different fine-tuned networks were created, both starting with an AlexNet pre-trained on ImageNet. For the first fine-tuned network, we added 26 randomly initialized dimensions to the final classification layer to create a 1026-way classifier, then trained the network on both ImageNet and the letter database. The network was trained on minibatches of 128 images, each with a random collection of Imagenet and letter images. As there were many more Imagenet training images in the dataset, each letter training image was shown 3 times to the network per epoch. The model was

trained for 30 epochs with an initial learning rate of .0001. For the second fine-tuned

network, we replaced the final 1000-way classification layer with a randomly initialized

26-way classifier. This network was then fine-tuned only on letters for 100 epochs, and

the model epoch with highest test set accuracy was selected for comparison with

human subjects. Letter data was augmented during training as described above for both

these models.

To create specialized letter networks branching off ImageNet-trained AlexNet we

took inspiration from the methods introduced by Kell et al. (2018). Five different models

were created, each with a different branching point off the base AlexNet at one of the

first five ReLU layers. Each network branch was architecturally identical, varying only in

the number of input channels in the first layer, in order to match the number output

channels from the different AlexNet layers. Besides this difference, each branch is

architecturally identical to the custom small CNN architecture described above. Note

that the weights of pre-trained base AlexNet were frozen, so feature learning only

occurred in the network branches. The branching networks were trained on the letter

database in the same manner as letter-trained AlexNet.

Finally, we used the following procedure to identify any letter-preferring features

found across the layers of both the primary AlexNet trained on ImageNet model, and of

the first fine-tuned AlexNet model (fine-tuned on a mixture of ImageNet and letters).

First, we measured activations to the 50,000 image ImageNet test set and the 2860

image GoogleFonts test set, evenly sampled by category. Next, for each feature in each network, we conducted a two-sample t-test comparing the activations to the 26 letter categories of GoogleFonts and the 1000 object categories of ImageNet. Finally, features were selected which exhibited greater activation to letters and a p-value of < 0.05.

To select features which did not prefer letters, we identified features which responded to any letters, and which were not previously identified as letter-preferring. For each layer of each network, we selected 100 random samples of these features, matching in size to the letter-preferring features of that layer. When comparing the letter-preferring and non-letter-preferring subspaces, the mean model-behavior correlation was computed across the 100 samples of non-letter-preferring subspaces.

Measuring Activations and Creating RDMs.

Feature activations to the 520 experimental stimuli were measured in each convolutional neural network, from the ReLU stages of each layer. For convolutional layers, we computed the total amount each image activated each feature by summing the activation maps of each feature. For example, Layer 5 of AlexNet has 256 features each with an activation map of dimensionality 13x13; by summing across the activation maps we obtained a 256-dimensional vector for each image. This step was taken to make the RDMs measured from our models comparable to the RDMs measured in our behavioral tasks. In visual search, participants compare the features of multiple stimuli at different visual locations, requiring abstracting from each stimulus's retinotopic

location. One way this comparison could be accomplished is by computing the total amount each feature is activated by each stimulus, then comparing the feature activations between stimuli. We chose to model such a comparison mechanism here.

After computing feature activations to each stimulus, representational dissimilarity matrices were then computed for each layer of each network. The procedure for making these RDMs differed between the two experiments to best parallel the tasks completed by participants. For Experiment 1, participants only ever directly discriminated between letters of the same font, so the model RDMs for this experiment only included dissimilarities between letters of the same font. Specifically, activations were measured for each letter stimulus, and the Euclidean distance was computed between all pairs of letters within each font, yielding a 26x26x20 matrix (26 letters x 26 letters x 20 fonts). The mean of this matrix was calculated across fonts to create a 26x26 RDM for each layer of each neural network. For Experiment 2, participants categorized letters across random font assignments, comparing letters in a specific font to a target letter, so the model RDMs for this experiment included dissimilarities between letters of all fonts. Specifically, the mean activations were calculated for each letter across font, providing an estimate of the target letter in each feature space. The Euclidean distance was computed between the activations of each font-specific letter and the mean activations of each letter. Then the mean of these distances was computed for each letter to create a 26x26 RDM for each layer of each neural network. To ensure that our results were not dependent on our choice of distance measure, we also conducted all analyses after computing RDMs with correlation distance and cosine

distance, and we found that all the patterns of results were consistent across distance metrics.

Intuitive feature model

We also computed a model RDM using a set of intuitive features previously described in the literature on letter perception (Fiset, 2008; Wiley, 2016; Wiley, 2020). The features were the following: straight lines at different orientations (vertical, horizontal, slanted right, and slanted left), curved lines (open on the right, left, bottom, and top), intersections (two-, three-, and four-way), line terminations (on the right, left, bottom, and top), diacritics, symmetry, and closed space. We judged the number of times each feature was present in each letter image used in our experiments (author DJ completed the ratings). As above, Euclidean distance in the feature space was used to construct the model RDM.

Computing Model-Behavior Correlations

For each experiment, we compared the behaviorally measured RDM with each of the RDMs from our convolutional neural networks to determine which model features best matched human behavior. We took the values below the diagonal of each RDM, then computed the Spearman correlation between the behaviorally measured RDM and each of the model RDMs. See the Supplementary Information section for further explanation of the theoretical assumptions underlying the way we relate the behaviorally measured RDMs and model RDMs. Note that we did not conduct RSA-reweighting when computing model-behavior correlations. This sets a higher bar for models to

exhibit high model-behavior correlations. Network feature spaces could fail to capture the perceptual similarity of letters because they have the wrong features or features in the wrong proportions.

Comparing Model-Behavior Correlations Between Networks

We conducted bootstrapping statistical tests to compare pairs of networks to see which yielded the highest correlation to the behaviorally measured similarity of letters. Our experiments measured the similarity of 325 letter pairs, so we bootstrapped 50,000 samples of 325 letter pairs. We compared pairs of networks two ways: i) by their maximum model-behavior correlations, and ii) layer by layer. To compare networks by their maximum model-behavior correlation, we selected the layer from each network which exhibited the highest model-behavior correlation in the original sample, then we determined which of the two feature spaces had the higher model-behavior correlation for each bootstrapped sample. To compare pairs of networks layer by layer, we compared the model-behavior correlations for each layer for each bootstrapped sample.

Data Availability

The behavioral data from both experiments are available at: https://osf.io/8s3vy/. This repository includes data at the trial level for each participant and the stimuli used in the experiments.

Code Availability

To reproduce the analyses of this study, code is available here: https://osf.io/8s3vy/.

Code is included to construct RDMs from the behavioral data, construct RDMs from the

neural network models, conduct model-behavior correlations and statistical tests, and

plot the results in figures.

<u>**REFERENCES**</u>

1. Gibson EJ. Principles of perceptual learning and development. East Norwalk, CT, US: Appleton-Century-Crofts; 1969. (Principles of perceptual learning and development).

2. Gross CG, De Schonen S, Bruce V, Cowey A, Ellis AW, Perrett DI. Representation of visual stimuli in inferior temporal cortex. Philos Trans R Soc Lond B Biol Sci. 1992 Jan 29;335(1273):3–10.

3. Selfridge OG, Neisser U. Pattern Recognition by Machine. Sci Am. 1960;203(2):60–9.

4. Tanaka K. Mechanisms of visual object recognition: monkey and human studies. Curr Opin Neurobiol. 1997 Aug;7(4):523–9.

5. Cohen L, Dehaene S. Specialization within the ventral stream: the case for the visual word form area. NeuroImage. 2004 May 1;22(1):466–76.

6. Downing PE, Jiang Y, Shuman M, Kanwisher N. A Cortical Area Selective for Visual Processing of the Human Body. Science. 2001 Sep 28;293(5539):2470–3.

7. Epstein R, Kanwisher N. A cortical representation of the local visual environment. Nature. 1998 Apr;392(6676):598–601.

8. Haxby JV. Distributed and Overlapping Representations of Faces and Objects in Ventral Temporal Cortex. Science. 2001 Sep 28;293(5539):2425–30.

9. Ishai A, Ungerleider LG, Martin A, Schouten JL, Haxby JV. Distributed representation of objects in the human ventral visual pathway. Proc Natl Acad Sci. 1999 Aug 3;96(16):9379–84.

10. Kanwisher N. Domain specificity in face perception. Nat Neurosci. 2000 Aug;3(8):759–63.

11. Kanwisher N. Functional specificity in the human brain: A window into the functional architecture of the mind. Proc Natl Acad Sci. 2010 Jun 22;107(25):11163–70.

12. Dehaene S, Cohen L. Cultural Recycling of Cortical Maps. Neuron. 2007 Oct;56(2):384–98.

13. Wandell BA, Rauschecker AM, Yeatman JD. Learning to See Words. Annu Rev Psychol. 2011 Nov 30;63(1):31–53.

14. Baker CI, Liu J, Wald LL, Kwong KK, Benner T, Kanwisher N. Visual word processing and experiential origins of functional selectivity in human extrastriate cortex. Proc Natl Acad Sci. 2007 May 22;104(21):9087–92.

15. Cohen L, Lehéricy S, Chochon F, Lemer C, Rivaud S, Dehaene S. Language-specific tuning of visual cortex? Functional properties of the Visual Word Form Area. Brain. 2002 May 1;125(5):1054–69.

16. Hasson U, Levy I, Behrmann M, Hendler T, Malach R. Eccentricity Bias as an Organizing Principle for Human High-Order Object Areas. Neuron. 2002 Apr;34(3):479–90.

17. Puce A, Allison T, Asgari M, Gore JC, McCarthy G. Differential sensitivity of human visual cortex to faces, letterstrings, and textures: a functional magnetic resonance imaging study. J Neurosci Off J Soc Neurosci. 1996 Aug 15;16(16):5205–15.

18. Dehaene S, Cohen L. The unique role of the visual word form area in reading. Trends Cogn Sci. 2011 Jun;15(6):254–62.

19. Courrieu P, Farioli F, Grainger J. Inverse discrimination time as a perceptual distance for alphabetic characters. Vis Cogn. 2004 Oct 1;11(7):901–19.

20. Dunn-Rankin P. The similarity of lower-case letters of the English alphabet. J Verbal Learn Verbal Behav. 1968;7(6):990–5.

21. Podgorny P, Garner WR. Reaction time as a measure of inter- and intraobject visual similarity: Letters of the alphabet. Percept Psychophys. 1979 Jan 1;26(1):37–52.

22. Sanford EC. The Relative Legibility of the Small Letters. Am J Psychol. 1888;1(3):402–35.

23. Tinker MA. The Relative Legibility of the Letters, the Digits, and of Certain Mathematical Signs. J Gen Psychol. 1928 Jul 1;1(3–4):472–96.

24. Mueller ST, Weidemann CT. Alphabetic letter identification: Effects of perceivability, similarity, and bias. Acta Psychol (Amst). 2012 Jan 1;139(1):19–37.

25. Grainger J, Rey A, Dufau S. Letter perception: from pixels to pandemonium. Trends Cogn Sci. 2008 Oct;12(10):381–7.

26. Kriegeskorte N, Kievit RA. Representational geometry: integrating cognition, computation, and the brain. Trends Cogn Sci. 2013 Aug;17(8):401–12.

27. Gilmore GC, Hersh H, Caramazza A, Griffin J. Multidimensional letter similarity derived from recognition errors. Percept Psychophys. 1979 Sep 1;25(5):425–31.

28. Fiset D, Blais C, Éthier-Majcher C, Arguin M, Bub D, Gosselin F. Features for Identification of Uppercase and Lowercase Letters. Psychol Sci. 2008 Nov 1;19(11):1161–8.

29. Wiley RW, Wilson C, Rapp B. The effects of alphabet and expertise on letter perception. J Exp Psychol Hum Percept Perform. 2016;42(8):1186–203.

30. Wiley RW, Rapp B. From complexity to distinctiveness: The effect of expertise on letter perception. Psychon Bull Rev. 2019 Jun 1;26(3):974–84.

31. Krizhevsky A, Sutskever I, Hinton GE. ImageNet classification with deep convolutional neural networks. Adv Neural Inf Process Syst. 2012;25:1097–105.

32. Zamir AR, Sax A, Shen W, Guibas LJ, Malik J, Savarese S. Taskonomy: Disentangling Task Transfer Learning. In 2018 [cited 2021 Mar 22]. p. 3712–22. Available from: https://openaccess.thecvf.com/content_cvpr_2018/html/Zamir_Taskonomy_Disentangling_Task_CVPR_2018_paper.html

33. Yamins DLK, DiCarlo JJ. Using goal-driven deep learning models to understand sensory cortex. Nat Neurosci. 2016 Mar;19(3):356–65.

34. Bankson BB, Hebart MN, Groen IIA, Baker CI. The temporal evolution of conceptual object representations revealed through models of behavior, semantics and deep neural networks. NeuroImage. 2018 Sep 1;178:172–82.

35. Cichy RM, Khosla A, Pantazis D, Torralba A, Oliva A. Comparison of deep neural networks to spatio-temporal cortical dynamics of human visual object recognition reveals hierarchical correspondence. Sci Rep. 2016 Jun 10;6(1):27755.

36. Khaligh-Razavi SM, Kriegeskorte N. Deep Supervised, but Not Unsupervised, Models May Explain IT Cortical Representation. Diedrichsen J, editor. PLoS Comput Biol. 2014 Nov 6;10(11):e1003915.

37. King ML, Groen IIA, Steel A, Kravitz DJ, Baker CI. Similarity judgments and cortical visual responses reflect different properties of object and scene categories in naturalistic images. NeuroImage. 2019 Aug 15;197:368–82.

38. Long B, Yu CP, Konkle T. Mid-level visual features underlie the high-level categorical organization of the ventral stream. Proc Natl Acad Sci. 2018 Sep 18;115(38):E9015–24.

39. Yamins DLK, Hong H, Cadieu CF, Solomon EA, Seibert D, DiCarlo JJ. Performance-optimized hierarchical models predict neural responses in higher visual cortex. Proc Natl Acad Sci. 2014 Jun 10;111(23):8619–24.

40. Jozwik KM, Kriegeskorte N, Storrs KR, Mur M. Deep Convolutional Neural Networks Outperform Feature-Based But Not Categorical Models in Explaining Object Similarity Judgments. Front Psychol. 2017 Oct 9;8:1726.

41. Peterson JC, Abbott JT, Griffiths TL. Evaluating (and Improving) the Correspondence Between Deep Neural Networks and Human Representations. Cogn Sci. 2018;42(8):2648–69.

42. Kriegeskorte N, Mur M, Bandettini PA. Representational similarity analysis - connecting the branches of systems neuroscience. Front Syst Neurosci [Internet]. 2008 [cited 2021 Mar 22];2. Available from: https://www.frontiersin.org/articles/10.3389/neuro.06.004.2008/full?utm_source=F WEB&utm_medium=NBLOG&utm_campaign=ECO_10YA_top-research

43. Duncan J, Humphreys GW. Visual search and stimulus similarity. Psychol Rev. 1989;96(3):433–58.

44. Agrawal A, Hari KVS, Arun SP. Reading Increases the Compositionality of Visual Word Representations. Psychol Sci. 2019 Dec 1;30(12):1707–23.

45. Arun SP. Turning visual search time on its head. Vision Res. 2012 Dec 1;74:86–92.

46. Cohen MA, Alvarez GA, Nakayama K, Konkle T. Visual search for object categories is predicted by the representational architecture of high-level visual cortex. J Neurophysiol. 2017 Jan 1;117(1):388–402.

47. Long B, Konkle T, Cohen MA, Alvarez GA. Mid-level perceptual features distinguish objects of different real-world sizes. J Exp Psychol Gen. 2016 Jan;145(1):95–109.

48. Long B, Störmer VS, Alvarez GA. Mid-level perceptual features contain early cues to animacy. J Vis. 2017 Jun 1;17(6):20–20.

49. Magri C, Konkle T. Comparing facets of behavioral object representation: implicit perceptual similarity matches brains and models. In: 2019 Conference on Cognitive Computational Neuroscience [Internet]. Berlin, Germany: Cognitive Computational Neuroscience; 2019 [cited 2021 Mar 22]. Available from: https://ccneuro.org/2019/Papers/ViewPapers.asp?PaperNum=1395

50. Deng J, Dong W, Socher R, Li L, Kai Li, Li Fei-Fei. ImageNet: A large-scale hierarchical image database. In: 2009 IEEE Conference on Computer Vision and Pattern Recognition. 2009. p. 248–55.

51. Nakayama K, Martini P. Situating visual search. Vision Res. 2011 Jul 1;51(13):1526–37.

52. French RM. Catastrophic forgetting in connectionist networks. Trends Cogn Sci. 1999 Apr 1;3(4):128–35.

53. Testolin A, Stoianov I, Zorzi M. Letter perception emerges from unsupervised deep learning and recycling of natural image features. Nat Hum Behav. 2017 Sep;1(9):657–64.

54. Prince JS, Konkle T. Computational evidence for integrated rather than specialized feature tuning in category-selective regions. J Vis. 2020 Oct 20;20(11):1577–1577.

55. Geirhos R, Rubisch P, Michaelis C, Bethge M, Wichmann FA, Brendel W. ImageNet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. ArXiv181112231 Cs Q-Bio Stat [Internet]. 2019 Jan 14 [cited 2021 Apr 1]; Available from: http://arxiv.org/abs/1811.12231

56. LeCun Y, Boser B, Denker JS, Henderson D, Howard RE, Hubbard W, et al. Backpropagation Applied to Handwritten Zip Code Recognition. Neural Comput. 1989 Dec 1;1(4):541–51.

57. Dehaene S, Cohen L, Sigman M, Vinckier F. The neural code for written words: a proposal. Trends Cogn Sci. 2005 Jul 1;9(7):335–41.

58. Rajalingham R, Kar K, Sanghavi S, Dehaene S, DiCarlo JJ. The inferior temporal cortex is a potential cortical precursor of orthographic processing in untrained monkeys. Nat Commun. 2020 Aug 4;11(1):1–13.

59. Güçlü U, Gerven MAJ van. Deep Neural Networks Reveal a Gradient in the Complexity of Neural Representations across the Ventral Stream. J Neurosci. 2015 Jul 8;35(27):10005–14.

60. Szwed M, Cohen L, Qiao E, Dehaene S. The role of invariant line junctions in object and visual word recognition. Vision Res. 2009 Apr 29;49(7):718–25.

61. Szwed M, Dehaene S, Kleinschmidt A, Eger E, Valabrègue R, Amadon A, et al. Specialization for written words over objects in the visual cortex. NeuroImage. 2011 May 1;56(1):330–44.

62. Sayim B, Cavanagh P. What Line Drawings Reveal About the Visual Brain. Front Hum Neurosci [Internet]. 2011 [cited 2021 Mar 25];5. Available from: https://www.frontiersin.org/articles/10.3389/fnhum.2011.00118/full

63. Turkeltaub PE, Goldberg EM, Postman-Caucheteux WA, Palovcak M, Quinn C, Cantor C, et al. Alexia due to ischemic stroke of the visual word form area. Neurocase. 2014 Mar 4;20(2):230–5.

64. Behrmann M, Nelson J, Sekuler EB. Visual complexity in letter-by-letter reading: Pure alexia is not pure. Neuropsychologia. 1998 Nov 1;36(11):1115–32.

65. Hannagan T, Amedi A, Cohen L, Dehaene-Lambertz G, Dehaene S. Origins of the specialization for letters and numbers in ventral occipitotemporal cortex. Trends Cogn Sci. 2015 Jul 1;19(7):374–82.

66. Behrmann M, Plaut DC. Distributed circuits, not circumscribed centers, mediate visual recognition. Trends Cogn Sci. 2013 May;17(5):210–9.

67. Yeatman JD, Rauschecker AM, Wandell BA. Anatomy of the visual word form area: Adjacent cortical circuits and long-range white matter connections. Brain Lang. 2013 May 1;125(2):146–55.

68. Grotheer M, Yeatman J, Grill-Spector K. White matter fascicles and cortical microstructure predict reading-related responses in human ventral temporal cortex. NeuroImage. 2021 Feb 15;227:117669.

69. Saygin ZM, Osher DE, Norton ES, Youssoufian DA, Beach SD, Feather J, et al. Connectivity precedes function in the development of the visual word form area. Nat Neurosci. 2016 Sep;19(9):1250–5.

70. Vinckier F, Dehaene S, Jobert A, Dubus JP, Sigman M, Cohen L. Hierarchical Coding of Letter Strings in the Ventral Stream: Dissecting the Inner Organization of the Visual Word-Form System. Neuron. 2007 Jul 5;55(1):143–56.

71. Lake BM, Salakhutdinov R, Tenenbaum JB. Human-level concept learning through probabilistic program induction. Science. 2015 Dec 11;350(6266):1332–8.

72. Baker N, Lu H, Erlikhman G, Kellman PJ. Local features and global shape information in object classification by deep convolutional neural networks. Vision Res. 2020 Jul 1;172:46–61.

73. Jacob G, Pramod RT, Katti H, Arun SP. Qualitative similarities and differences in visual object representations between brains and deep networks. Nat Commun. 2021 Mar 25;12(1):1872.

74. Serre T. Deep Learning: The Good, the Bad, and the Ugly. Annu Rev Vis Sci. 2019;5(1):399–426.

75. Xu Y, Vaziri-Pashkam M. Limited correspondence in visual representation between the human brain and convolutional neural networks. bioRxiv. 2020 Mar 14;2020.03.12.989376.

76. Cohen MA, Konkle T, Rhee JY, Nakayama K, Alvarez GA. Processing multiple visual objects is limited by overlap in neural channels. Proc Natl Acad Sci. 2014 Jun 17;111(24):8955–60.

77. Cohen MA, Nakayama K, Konkle T, Stantić M, Alvarez GA. Visual Awareness Is Limited by the Representational Architecture of the Visual System. J Cogn Neurosci. 2015 Nov 1;27(11):2240–52.

78. Kell AJ, McDermott JH. Deep neural network models of sensory systems: windows onto the role of task constraints. Curr Opin Neurobiol. 2019 Apr;55:121–32.

79. Dobs K, Martinez J, Kell AJE, Kanwisher N. Brain-like functional specialization emerges spontaneously in deep neural networks. Sci Adv. 8(11):eabl8913.

80. Josephs EL, Konkle T. Perceptual dissociations among views of objects, scenes, and reachable spaces. J Exp Psychol Hum Percept Perform. 2019;45(6):715–28.

81. Nasr K, Viswanathan P, Nieder A. Number detectors spontaneously emerge in a deep neural network designed for visual object recognition. Sci Adv. 2019 May;5(5):eaav7903.

82. Kell AJE, Yamins DLK, Shook EN, Norman-Haignere SV, McDermott JH. A Task-Optimized Neural Network Replicates Human Auditory Behavior, Predicts Brain Responses, and Reveals a Cortical Processing Hierarchy. Neuron. 2018 May;98(3):630-644.e16.

83. Russakovsky O, Deng J, Su H, Krause J, Satheesh S, Ma S, et al. ImageNet Large Scale Visual Recognition Challenge. Int J Comput Vis. 2015 Dec 1;115(3):211–52.

84. Cohen G, Afshar S, Tapson J, van Schaik A. EMNIST: Extending MNIST to handwritten letters. In: 2017 International Joint Conference on Neural Networks (IJCNN). 2017. p. 2921–6.

85. Kingma DP, Ba J. Adam: A Method for Stochastic Optimization. ArXiv14126980 Cs [Internet]. 2017 Jan 29 [cited 2021 Apr 5]; Available from: http://arxiv.org/abs/1412.6980

Acknowledgements

This work was supported by NSF CAREER BCS-1942438 (T.K.), and the National

Defense Science and Engineering Graduate Fellowship Program (D.J.).

Author Contributions

Daniel Janini and Talia Konkle developed the study idea. D. Janini coded the

experiments and collected the data. Chris Hamblin and Arturo Deza trained the

convolutional neural network models. D. Janini analyzed the experimental data. D.

Janini and T. Konkle wrote the paper.

Supplementary Information for

General object-based features account for letter perception better than specialized letter features

Daniel Janini, Chris Hamblin, Arturo Deza, Talia Konkle

Corresponding author: Daniel Janini
Email: daniel_janini@g.harvard.edu

Decoding analyses from object-based features. To test the plausibility of recycling object-based features for letter perception, we conducted decoding analyses. First, we tested whether object-based features support the linear classification of letter identity across font and size variation. For each layer of AlexNet trained on ImageNet, we measured responses to images of the 26 lowercase letters across 550 fonts and 5 sizes ranging from 45 pixels to 224 pixels. We trained linear classifiers on 80% of the fonts and sizes, then we tested the classifier on letter images from the left-out size and fonts. While classification accuracy was above chance for all layers (all $p<10^{-4}$), it reached a plateau beginning with Layer 3, with decoding accuracies ranging from 95-97% between Layers 3-7 (chance-level: 50%). Thus, we found that features of object-trained networks with mid-to-high level layer depth best distinguished between letter categories, complementing our findings that these feature spaces best correlated with the visual similarity of letters.

Next, we tested whether the letter-preferring subspace of the object-based feature space especially carried information on letter identity. For each layer, we trained and tested classifiers on the features which preferentially responded to letters over objects. As a point of comparison, we also trained classifiers on randomly selected sets of features matching the size of the letter-preferring subspace. Decoding accuracy was higher in the letter-preferring subspace than the randomly selected subspace in Layers 2-5 and 7 (all $p<10^{-4}$), though decoding accuracy was a bit higher in the randomly selected subspace for Layer 6 ($p<10^{-4}$). Thus, in most layers of the object-trained network, the letter-preferring feature subspace better distinguished between letter categories. These results are suggestive that read-out mechanisms which preferentially operate over a letter-preferring subspace of an object-based feature space will more accurately represent the identity of letters across font and size variation. However, to fully investigate how letter identities are read out from visual features, one would need to more fully compare multiple models of read out mechanisms, linking the algorithms of classification to neural mechanisms of read out operating over the visual system.

Supplementary Figure 1. Linear decoding of letter identity from object-trained features. A. Linear support vector machines were trained to categorize letters across font and size variation from the features of AlexNet trained on ImageNet. Three subsets of features are compared: 1) all the features from each layer, 2) only the features from each layer which preferentially responded to letters over object images, 3) a random subset of features matching the number of letter-preferring features. Classifiers were trained on random sets of letter fonts and sizes, then tested on left out fonts and sizes. The shaded areas indicate the 95% confidence interval across random testing/training splits. For the random subset of features, the confidence interval also includes variance introduced by the random selection of features during each instance of classifier training and testing.

Supplementary Figure 2. MDS plot visualizations of letter similarity as measured in behavior and the two primary feature models. Multidimensional scaling was used to project 26x26 RDMs onto two dimensions. Distance between letters illustrates their similarity as measured during visual search and letter categorization (above). Layer-wise MDS plots for object-trained AlexNet (middle) and letter-trained AlexNet (bottom) are also illustrated. Please note that reducing the dimensionality of neural network feature spaces to two dimensions obscures a lot of meaningful variance, and these visualizations are only for exploratory inspection.

Comparison of letter perception to model from Testolin et al. (2017). In addition to our specialized letter models, we considered a previously published model from Testolin et al. (2017), which learns specialized letter features which operate over domain-general low-level features. This model includes four layers: 1) a layer which performs a whitening algorithm over the image input, 2) a layer of primitive domain-general features acquired from unsupervised learning over natural scene images, 3) a layer of specialized letter features acquired from unsupervised learning over letter images, 4) a linear read out layer which classifies letter identity. The original model from Testolin et al. (2017) was trained on an image set of uppercase letters, so to compare their model to our behavior data, we trained it on our lowercase GoogleFonts database. The model was trained according to specifications from the original paper and code available on their OSF repo (https://osf.io/s6ytk/). We calculated the RDMs from the primitive domain-general features and the specialized letter features of their model and compared them to our two behavioral experiments. The RDM from these specialized letter features exhibited moderate correlations with both of our behaviorally measured RDMs ($\rho = 0.45$, $\rho = 0.39$ for visual search and categorization, respectively). However, Layers 3-7 of object-trained AlexNet exhibited higher correlations with both behaviors (all $p <= 0.003$, bootstrap resampling of letter pairs). Thus, the mid-to-late level features of object-trained AlexNet better accounted for human perception of letters than an unsupervised architecture recycling low-level general features.

Model-Behavior Correlations

Supplementary Figure 3. Model-Behavior Correlations for Letter Features from Testolin et al. (2017). Model-behavior correlations are plotted on the y-axis, as a function of the layer of AlexNet trained on ImageNet. Model-behavior correlations for the letter-trained features from Testolin et al. (2017) are plotted in orange. The shaded error range indicate the 95% confidence interval across bootstrapped samples of letter pairs.

A. Model-Behavior Correlations from AlexNet without training

Supplementary Figure 4. Comparisons of object-trained and letter-trained networks with AlexNet with random weights. The shaded error range indicate the 95% confidence interval across bootstrapped samples of letter pairs.

A. Smaller network trained on letters

Model-Behavior Correlations

Supplementary Figure 5. Model-Behavior Correlations for a Smaller Network Trained on Letters Categorization. A smaller architecture (see Methods) was trained on 26-way letter classification to create another model of specialized letter features. Model-behavior correlations are plotted on the y-axis, as a function of the model layer. The shaded error range indicate the 95% confidence interval across bootstrapped samples of letter pairs.

A. Letter training with a smaller stimulus set and fewer augmentations

Supplementary Figure 6. Model-Behavior Correlations When Letter-trained Models Have Less Varied Input. The letter-trained model shown here was trained on an image set with 550 typeset fonts per letter with size augmentation. In comparison, the letter-trained models in the main text were trained with 2344 typeset and handwritten letters across augmentations of size, position, skew, tilt, color, and noise.

A. Letter images used in behavioral experiments

B. Example images from GoogleFonts

Supplementary Figure 7. Example letter images. A. Images used in the two behavioral experiments: all twenty-six lower case letters across twenty fonts. B. Example images from the GoogleFonts database used to train specialized letter networks. The full database includes all twenty-six lowercase letters across 550 fonts.

Supplementary Figure 8. Example augmented letter images used when training letter-classifying neural networks. Augmentations included size, position, tilt, shearing, Gaussian noise, and color. For a full description of augmentations see the Methods section.

| | Models | | Model-Behavior Correlations | | | | | | | | | | | | | | | Model Accuracy (Top 1) | |
| | | | Visual Search Task | | | | | | | Letter Categorization Task | | | | | | | | |
Architecture		Training Set / Description	L1	L2	L3	L4	L5	L6	L7	L1	L2	L3	L4	L5	L6	L7	Letters	ImageNet
Primary Networks																		
1	AlexNet	ImageNet	.39	.42	.67	.69	.60	.61	.62	.32	.39	.62	.64	.61	.63	.64	-	56.5
2	AlexNet	Letters	.42	.43	.44	.63	.34	.02	-.02	.32	.34	.46	.52	.34	.19	.17	98.5	-
3	Small Network	Letters	.40	.38	.35	.43	.27	-	-	.30	.32	.42	.51	.39	-	-	96.2	-
Fine-tuned Networks																		
4	AlexNet	ImageNet & Letters	.40	.45	.65	.65	.40	.28	.32	.31	.42	.61	.64	.50	.40	.46	98.4	55.3
5	AlexNet	Letters	.40	.46	.55	.65	.03	-.04	-.08	.32	.42	.51	.49	.21	.16	.11	98.9	-
Branching Networks																		
6	Branch-ReLU1	Letters	.34	.39	.25	.14	.03	-	-	.31	.35	.36	.31	.26	-	-	98.4	-
7	Branch-ReLU2	Letters	.42	.44	.14	.15	-.08	-	-	.44	.50	.34	.33	.09	-	-	98.3	-
8	Branch-ReLU3	Letters	.42	.39	.30	.09	-.11	-	-	.50	.42	.40	.31	.12	-	-	98.1	-
9	Branch-ReLU4	Letters	.59	.52	.46	.05	-.08	-	-	.58	.53	.47	.16	.04	-	-	98.0	-
10	Branch-ReLU5	Letters	.59	.62	.42	.15	-.05	-	-	.58	.59	.43	.25	.06	-	-	97.0	-
Letter-Preferring Feature Subsets																		
-	Alexnet	From Network #1	.37	.36	.66	.58	.50	.60	.63	.24	.34	.58	.60	.52	.65	.67	-	-
-	Alexnet	From Network #4	.39	.41	.60	.60	.42	.24	.28	.25	.34	.52	.61	.44	.41	.42	-	-

Supplementary Table 1. Summary of neural network models. Here we list the model-behavior correlations (Spearman rho) of each neural network model. In addition, we list their accuracies on ImageNet or letters depending on which database they were trained on.

Further explanation of relating behavioral measurements to neural network feature spaces.

Comparing measurements from human behavior with measurements of representational similarity in a neural network requires making certain assumptions about the mechanisms of behavior during the experimental task. When a participant distinguishes between stimuli in a visual search or categorization task, we assume that a read-out mechanism operating over a visual feature space is supporting the behavior. We begin with the simple assumption that no matter the read-out mechanism, representations that are closer together in the feature space will be harder to distinguish than representations that are farther apart. For the visual search experiment, participants needed to find the odd-one-out without knowing the letter identities of the target and distractor before each trial. We propose they accomplished this by computing the visual similarity between each pair of items that appeared next to each other on the screen – more specifically by taking the Euclidean distance between their features. The distractors were always the same item, so they did not differ in their features. In this context, the task of identifying the target is synonymous with identifying the location at which the similarity between an item and its neighbor is not zero. When the target shared features with the distractors, the measure of its dissimilarity to its neighboring distractors would be small, so it would take more time to locate. For the categorization experiment, we propose a similar behavioral mechanism: the participant computed the Euclidean distance between the features present in the item on the screen and the average features present in the letter identity they were comparing it to. The more the letter on the screen shared features with the letter identity they were comparing it to, the longer it would take for the participant to know that the feature distance between the two stimuli was greater than 0, and to respond that they were different. Under these assumptions computing the Spearman correlation between each of our model RDMs and our behaviorally measured RDMs is appropriate.

SI References:

1. LeCun, Y., Boser, B., Denker, J. S., Henderson, D., Howard, R. E., Hubbard, W., & Jackel, L. D. (1989). Backpropagation Applied to Handwritten Zip Code Recognition. *Neural Computation*, *1*(4), 541–551. https://doi.org/10.1162/neco.1989.1.4.541

2. Testolin, A., Stoianov, I., & Zorzi, M. (2017). Letter perception emerges from unsupervised deep learning and recycling of natural image features. *Nature Human Behaviour, 1*(9), 657–664. https://doi.org/10.1038/s41562-017-0186-2