ElectroEncephaloGraphy robust linear modelling using weights reflecting single trials' dynamics

Cyril Pernet[1,2], Guillaume Rousselet[3], Ignacio Suay Mas[1], Ramon Martinez[4], Rand Wilcox[5] & Arnaud Delorme[4,6,7]

[1] Centre for Clinical Brain Sciences, University of Edinburgh, United Kingdom, [2] Neurobiology Research Unit, Copenhagen University Hospital, Rigshospitalet, Denmark, [3] Centre for Cognitive Neuroimaging, Institute of Neuroscience and Psychology , University of Glasgow, United Kingdom, [4] Swartz Center for Computational Neurosciences, University of California, United States of America, [5] Department of Psychology, University of Southern California, United States of America, [6] Centre de Recherche Cerveau et Cognition, Université Toulouse III – Paul Sabatier, Toulouse, France, [7] Centre National de la Recherche Scientifique, Centre de Recherche Cerveau et Cognition, Toulouse, France

Abstract

Being able to remove or weigh down the influence of outlier data is desirable for any statistical models. While Magnetic and ElectroEncephaloGraphic (MEEG) data are often averaged across trials per condition, it is becoming common practice to use information from all trials to build linear models. Individual trials can, however, have considerable weight and thus bias inferential results. Here, rather than looking for univariate outliers, defined independently at each measurement point, we apply the principal component projection (PCP) method at each channel, deriving a single weight per trial at each channel independently. Using both synthetic data and open EEG data, we show (1) that PCP is efficient at detecting a large variety of outlying trials; (2) how PCP-based weights can be implemented in the context of the general linear model with accurate control of type 1 family-wise error rate; and (3) that our PCP-based Weighted Least Square (WLS) approach increases the statistical power of group analyses as well as a much slower Iterative Reweighted Least Squares (IRLS), although the weighting scheme is markedly different. Together, our results show that WLS based on PCP weights derived from whole trial profiles is an efficient method to weigh down the influence of outlier EEG data in linear models.

Keywords: ElectroEncephaloGraphy, single trials, Weighted Least Squares, General Linear Model 38 39

Data availability: all data used are publicly available (CC0), all code (simulations and data 40 analyzes) is also available online in the LIMO MEEG GitHub repository (MIT license).

Introduction

MEEG data are often epoched to form 3 or 4-dimensional matrices of, e.g., channel x time x trials and channel x frequency x time x trials. Several neuroimaging packages are dedicated to the analyses of such large multidimensional data, often using linear methods. For instance, in the LIMO MEEG toolbox (Pernet et al., 2011), each channel, frequency, and time frame is analyzed independently using the general linear model, an approach referred to as mass-univariate analysis. Ordinary Least Squares (OLS) are used to find model parameters that minimize the error between the model and the data. For least squares estimates to have good statistical properties, it is however expected that the error covariance off-diagonals are zeros, such that $Cov(e) = \sigma^2 I$, I being the identity matrix (Christensen, 2002), assuming observations are independent and identically distributed. It is well established that deviations from that assumption lead to substantial power reduction and to an increase in the false-positive rate. When OLS assumptions are violated, robust techniques offer reliable solutions to restore power and control the false positive rate. Weighted Least Squares (WLS) is one such robust method that uses different weights across trials, such that $Cov(e) = \sigma^2 V$, with V a diagonal matrix:

$$y = X\beta + e, \quad E(e) = 0, \quad Cov(e) = \sigma^2 V \qquad \text{equation 1}$$

with y a n-dimensional vector (number of trials), X the n*p design matrix, β a p dimensional vector (number of predictors in X) and e the error vector of dimension n. The WLS estimators can then be obtained using an OLS on transformed data (eq. 2 and 3):

$$Wy = WX\beta + We, \quad E(e) = 0, \quad Cov(e) = \sigma^2 I \qquad \text{equation 2}$$

$$\hat{\beta} = (X^T W X)^{-1} X^T W y \qquad \text{equation 3}$$

with W a 1*n vector of weights.

When applied to MEEG data, a standard mass-univariate WLS entails obtaining a weight for each trial but also each dimension analyzed, i.e. channels, frequencies and time frames. Following such procedure, a trial could be considered as an outlier or be assigned a low weight, for a single frequency or time frame, which is implausible given the well-known correlations of MEEG data over space, frequencies and time. We propose here that a single or a few consecutive data points should never be flagged as outliers or weighted down, and that a single weight per trial (and channel) should be derived instead, with weights taking into account the whole temporal or spectral profile. In the following, we demonstrate how the Principal Component Projection method (PCP - Filzmoser et al., 2008) can be used in this context, and how those weights can then be used in the context of the general linear model, applied here to event-related potentials.

Method

Trial-based Weighted Least Squares

An illustration of the method is shown in figure 1. Trial weights are computed as a distance among trials projected onto the main (>=99%) principal components space. Here, the principal components computed over the f time frames are those directions which maximize the variance across trials for uncorrelated (orthogonal) time periods (figure 1B). Outlier trials are points in the f-dimensional space which are far away from the bulk. By virtue of the PCA, these outlier trials become more visible along the principal component axes than in the original data space. Weights (figure 1E) for each trial are obtained using both the Euclidean norm (figure 1C, distance location) and the kurtosis weighted Euclidean norm (figure 1D, distance scatter) in this reduced PCA space (see Filzmoser et al., 2008 for details). We exploit this simple technique because it is computationally fast given the rich dimensional space of EEG data and because it does not assume the data to originate from a particular distribution. The only constraint is that there are more trials present than time frames. For instance, with trials ranging from -50 ms to +650 ms, sampled at 250 Hz (thus 176 time points), the method requires at least 177 trials. The PCP algorithm is implemented in the *limo_pcout.m* function, distributed with the LIMO MEEG toolbox (https://limo-eeg-toolbox.github.io/limo_meeg/). The WLS solution, implemented in *limo_WLS.m*, consists of computing model beta estimates using weights from the PCP method on OLS standardized robust residuals, following three steps:

(1) After the OLS solution is computed, an adjustment is performed on residuals by multiplying them by $1/\sqrt{1-h}$ where h is a vector of Leverage points (i.e. the diagonal of the hat matrix $H = X(X'X)^{-1}X'$ where X is the design matrix). This adjustment is necessary because leverage points are the most influential on the regression space, i.e. they tend to have low residual values (Hoaglin & Welsch, 1978).

(2) Residuals are then standardized using a robust estimator of dispersion, the median absolute deviation to the median (MAD), and re-adjusted by the tuning function. Here we used the bisquare function. The result is a series of weights with high weights for data points having high residuals (with a correction for Leverage).

(3) The WLS solution is then computed following equation 3.

Figure 1. Illustration of the PCP weighting scheme using trials for 'famous faces' of the OpenNeuro.org publically available ds002718 dataset. Data are from subject 3, channel 34 (see Section on empirical data analysis). Panel A shows the single-trial responses to all stimuli. The principal component analysis is computed over time, keeping the components explaining the most variance and summing to at least 99% of explained variance (giving here 69 eigenvectors i.e. independent time components from the initial 176 time points). The data are then projected onto those axes (panel B). From the data projected onto the components, Euclidean distances for location and scatter are computed (panels C, D - showing smooth histograms of weights) and combined to obtain a distance for each trial. That distance is either used as weights in a linear model or used to determine outliers (panel E, with outliers identified for weights below ~0.27, shown in dark grey). At the bottom right, the mean ERP for trials classified as good (red) vs. outliers (black) and the weighted mean (green) are shown (panels F and G). Shaded areas indicate the 95% highest-density percentile bootstrap intervals.

Simulation-based analyses

A. *Outliers detection and parameters estimation.*

Simulated ERPs were generated to evaluate the classification accuracy of the PCP method and to estimate the robustness to outliers and low signal-to-noise ratio of the WLS solution in comparison to an OLS solution and a standard Iterative Reweighted Least Squares (IRLS) solution, which minimizes residuals at each time frame separately (implemented in *limo_IRLS.m*). To do so, we manipulated (i) the percentage of outliers, using 10%, 20%, 30%, 40% or 50% of outliers; (ii) the signal to noise ratio (defined relative to the mean over time of the background activity); and (iii) the type of outliers. The first set of outliers were defined based on the added noise: white noise, pink noise, alpha oscillations and gamma oscillations. In these cases, the noise started with

137　the P1 component and lasted ~ 200ms (see below). The second set of outliers were defined based
138　on their amplitude, or outlier to signal ratio (0.5, 0.8, 1.2, and 1.5 times the true N1 amplitude).
139
Synthetic data were generated for one channel, using the model developed by Yeung et al.
(2018). The simulated signal corresponded to an event-related potential with P1 and N1
components (100 ms long) added to background activity with the same power spectrum as
human EEG, generating 200 trials of 500 ms duration with a 250 Hz sampling rate. Examples for
each type of simulation are shown in figure 2 and results are based, for each case, on a thousand
random repetitions. Performance of the PCP algorithm at detecting outlying synthetic EEG trials
was investigated by computing the confusion matrix and mapping the true and false positives
rates in the Receiver Operating space, and by computing the Matthew Correlation Coefficients
(MCC). Robustness was examined by computing the Pearson correlations and the Kolmorov-
Smirnov (KS) distances between the ground truth mean and the OLS, WLS, and IRLS means.
Pearson values allowed to estimate the linear relationships between estimated means and the
truth while KS distances provide a fuller picture of the overall differences in distributions.
152
153　The code used to generate the ERP and the results are available at https://github.com/LIMO-
154　EEG-Toolbox/limo_test_stats/tree/master/PCP_simulations.

Figure 2. Illustration of simulated ERP ground truth with the different types of outlier trials. At the top is shown the mean background, mean signal and resulting generated ERP with it's 95% confidence intervals. In each subsequent subplot is shown the mean ERP ground truth from 160 trials with their 95% confidence intervals (blue) with a SNR of 1. The first row shows in red the mean ERP from outlier trials generated by adding white noise, pink noise, alpha or gamma oscillations; the second row shows the mean ERP from outlier trials generated with variable Outlier to Signal Ratio (OSR) on the N1 component.

B. Statistical inference.

Accurate estimation of model parameters (i.e. beta estimates in the GLM - equation 3) is particularly important because it impacts group-level results. Inference at the single-subject level may, however, also be performed and accurate p-values need, therefore, to be derived. Here, error degrees of freedom are obtained using the Satterwaithe approximation (equation 4).

$$dfe = tr([I - H]^T[I - H]) \quad equation\ 4$$

with dfe, the degree of freedom of the error, I the identity matrix, and H the hat matrix.

To validate p-values, simulations under the null were performed. Two types of data were
generated: Gaussian data of size 120 trials x 100 time frames and EEG data of size 120 trials x 100
time frames with a P1 and N1 component as above, added to coloured background activity with
the same power spectrum as human EEG. In each case, a regression (1 Gaussian random
variable), an ANOVA (3 conditions of 40 trials - dummy coding) and an ANCOVA (3 conditions of
40 trials and 1 Gaussian random covariate) model were fitted to the data using the OLS, WLS and
IRLS methods. The procedure was performed 10,000 times, leading to 1 million p-values per
data/model/method combination and Type 1 errors with binomial confidence intervals were
computed.
182
183 *Empirical data analysis*
184
A second set of analyses used the publicly available multimodal face dataset (Wakeman &
Henson, 2016) to (i) investigate the PCP classification; (ii) validate the GLM implementation for
type 1 error family-wise control at the subject level; (iii) evaluate group results, contrasting WLS
against the OLS and IRLS methods. This analysis can be reproduced using the script available at
https://github.com/LIMO-EEG-
Toolbox/limo_meeg/blob/master/resources/code/Method_validation.m.
191
192 *A. EEG Data and Preprocessing*
193
The experiment consisted in the presentation of familiar, unfamiliar, and scrambled faces,
repeated twice at various intervals, leading to a factorial 3 (type of faces) by 3 (repetition) design.
The preprocessing replicated Pernet et al (2021). EEG data were extracted from the MEG fif files,
time corrected and electrode position re-oriented and saved according to EEG-BIDS (Pernet et
al., 2019 - available at OpenNeuro 10.18112/openneuro.ds002718.v1.0.2.). Data were imported
into EEGLAB (Delorme & Makeig, 2004) using *the bids-matlab-tools v5.2 plug-in* and non-EEG
channel types were removed. Bad channels were next automatically removed and data filtered
at 0.5 Hz using *pop_clean_rawdata.m* of the *clean_radata* plugin v2.2 (transition band [0.25
0.75], bad channel defined as a flat line of at least 5 sec and with a correlation to their robust
estimate based on other channels below 0.8). Data were then re-referenced to the average
(*pop_reref.m*) and submitted to an independent component analysis (Onton et al., 2006)
(*pop_runica.m* using the runnica algorithm sphering data by the number of channels -1). Each
component was automatically labelled using the *ICLabel* v1.2.6 plug-in (Pion-Tonachini et al.,
2019), rejecting components labeled as eye movements and muscle activity above 80%
probability. Epochs were further cleaned if their power deviated too much from the rest of the
data using the Artifact Subspace Reconstruction algorithm (Kothe & Makeig, 2013)
(*pop_clean_rawdata.m*, burst criterion set to 20).
211
212 *B. High vs. low weight trials and parameters estimation.*
213
At the subject level (1st level), ERP were modelled at each channel and time frame with the 9
conditions (type of faces x repetition) and beta parameter estimates obtained using OLS, WLS,
and IRLS. For each subject, high vs. low weight trials were compared with each other at the

channel showing the highest between trials variance to investigate what ERP features drove the
weighting schemes. High and low trials were defined a priori as trials with weights (or mean
weights for IRLS) below the first decile or above the 9th decile. We used a two-sample bootstrap-
t method to compare the 20% trimmed means of high and low trials in every participant, for each
of these three quantities: temporal SNR (the standard deviation over time); global power (mean
of squared absolute values, Parseval's theorem); autocorrelation (distance between the 2 first
peaks of the power spectrum density, Wiener-Khinchin theorem). A similar analysis was
conducted at the group level averaging the metrics across trials. Computations of the three
quantities have been automatized for LIMO MEEG v3.0 in the *limo_trialmetric.m* function.
226
227 *C. Statistical inference.*
228
In mass-univariate analyses, once p-values are obtained, the family-wise type 1 error rate can be
controlled using the distribution of maxima statistics from data generated under the null
hypothesis (Pernet et al., 2015). Here, null distributions were obtained by first centering data per
conditions, i.e. the mean is subtracted from the trials in each condition, such that these
distributions had a mean of zero, but the shape of the distributions is unaffected. We then
bootstrap these centred distributions (by sampling with the replacement), keeping constant the
weights (since they are variance stabilizers) and the design. We computed 2500 bootstrap
estimates per subject. A thousand of these bootstrap estimates were used to compute the family-
wise type 1 error rate (FWER), while maxima and cluster maxima distributions were estimated
using from 300 to 1,500 bootstraps estimates in steps of 300, to determine the convergence
rate, i.e. the number of resamples needed to control the FWER. Since OLS was already validated
in Pernet et al. (2015), here we only present WLS results. Statistical validations presented here
and other statistical tests implemented in the LIMO MEG toolbox v3.0 (GLM validation, robust
tests, etc.) are all available at https://github.com/LIMO-EEG-Toolbox/limo_test_stats/wiki.
243
244 *D. Performance evaluation at the group level*.
245
246 At the group level (2nd level), we computed 3 by 3 repeated measures ANOVAs (Hotelling T^2
247 tests) separately on OLS, WLS, and IRLS estimates, with the type of faces and repetition as factors.
248 Results are reported using both a correction for multiple comparisons with cluster-mass and with
249 TFCE (threshold-free cluster enhancement) at $p < .05$ (Maris & Oostenveld, 2007; Pernet et al.,
250 2015).
251
In addition to these thresholded maps, distributions were compared to further understand where
differences originated from. First, we compared raw effect sizes (Hotelling T^2) median
differences between WLS vs. OLS and WLS vs. IRLS for each effect (face, repetition and
interaction), using a percentile t-test with alpha adjusted across all 6 tests using Hochberg's step-
up procedure (Hochberg, 1988). This allowed checking if differences in results were due to effect
size differences. Then, since multiple comparison correction methods are driven by the data
structure, we compared the shapes of the F value and of the TFCE value distributions (TFCE
reflecting clustering). Each distribution was standardized (equation 5) and WLS vs. OLS and WLS
vs. IRLS distributions compared at multiple quantiles (Rousselet et al., 2017).

$$Yzi = \frac{(Yi - median(Y))}{\sqrt{(pi/2)*MAD(Y)}} \quad equation\ 5$$

with Yzi the standardized data, Y the data, and MAD the median absolute deviation.

Results

Outliers detection

While the PCP method is used in the GLM to obtain weights and not to remove outliers directly,
simulations allowed us to better understand what kind of trials are weighted down and how good
the method is at detecting such trials. Figure 3 shows all the results for ERP simulated with a SNR
of 1. Similar results were observed when using a SNR of 2 (supplementary figure 1). First and
foremost, in all cases and for up to 40% of outlying trials, the PCP data are located in the upper
left corner of the ROC space, indicating good performances. When reaching 50% of outliers, the
true positive rate falls down to ~40% and the false positive rate remains below 40%. This is best
appreciated by looking at the plots showing perfect control over false positives when data are
contaminated with up to 40% of white, alpha, and gamma outliers. In those cases, the Matthew
Correlation Coefficients also remain high (>0.6) although not perfect (not =1), indicating some
false negatives. Compared with other types of noise, pink noise elicited very different results,
with Matthew Correlation Coefficients around 0 indicating chance classification level. Results
from amplitude outliers also show Matthew Correlation Coefficients close to 0 with a linear
decrease in true positives and a linear increase in false positives as the percentage of outliers
increases. This implies that the PCP method did not detect amplitude changes around peaks.
These results are simply explained by the principal components being computed over time
frames, and outliers with pink noise and weaker or stronger N1 do not affect the temporal profile
of the ground truth sufficiently to lead to different eigenvectors ('directions') in this dimension
when decomposing the covariance matrix, i.e. their temporal profiles do not differ from the
ground truth.

Figure 3. PCP performance at detecting outlying trials with a SNR of 1. (A) Results for outliers affected by white noise, pink noise, alpha, and gamma oscillations. (B) Results for trials affected by amplitude changes over the N1 component (0.5, 0.8, 1.2, 1.5 times the N1). The scatter plots map the Receiver Operating Characteristic Space (False Positive rate vs. True Positive rate); the curves display, from left to right, the median True Positive rate, False Positive rate, and Matthew Correlation Coefficients.

297
Supplementary Figure 1. PCP performance at detecting outlying trials with a SNR of 2. (A) Results for outliers affected
by white noise, pink noise, alpha, and gamma oscillations. (B) Results for trials affected by amplitude changes over
the N1 component (0.5, 0.8, 1.2, 1.5 times the N1). The scatter plots map the Receiver Operating Characteristic Space
(False Positive rate vs. True Positive rate); the curves display, from left to right, the median True Positive rate, False
Positive rate, and Matthew Correlation Coefficients.

High vs. low trial weights
304
The classification for real ERP data confirmed the simulation results: the PCP algorithm weighted
down trials with dynamics different from the bulk. Single subject analyses (supplementary table
1) and group analyses (figure 4) for WLS showed that trials with a low weight are less smooth
than trials with a high weight (higher temporal variance ~10 vs. 7.26 uV and power ~131 vs. 69
dB, lower autocorrelation 11 vs. 12.25 ms), despite having similar spectra (as expected from data
filtering and artefact reduction). In comparison, trials with low and high mean weights based on
IRLS, were similar on those metrics (temporal variance ~9 vs. 7 uV, and power ~126 vs. 65 dB,
autocorrelation 12.25 vs. 12 ms). While 11 out of 18 subjects show maximum between-trial
variance on the same channels for WLS and IRLS, only 28% of low weight trials were the same
between the two methods, and 56% of high weight trials. Since different trials have low or even
high weights between methods, this further indicates that the weighting scheme from WLS
differs from IRLS which relies on amplitude variations only.
317
318   *Estimation and Robustness*
319
The effect of adding outliers on the mean can be seen in figure 5 and supplementary figure 2.
The standard mean, i.e. the ordinary least squares ERPs, shows an almost linear decrease in
Pearson correlations and linear increase in KS distances to the ground truth as the percentage of
outlier increases, an expected behaviour since OLS are not robust. Our reference robust
approach, IRLS, shows robustness to white noise, alpha, and gamma oscillations with higher
Pearson correlations than the OLS. Yet it performed worse than the OLS with pink noise and
amplitude outliers, showing lower correlations with the ground truth, despite having similar KS
distances in all cases. As the IRLS solution for pink noise and amplitude outliers weights data to
minimize residuals at each time point separately, these are also expected results, resulting in an
average distance (over time) larger than OLS. The new WLS approach showed stronger resistance
to outliers for white noise, alpha and gamma oscillations than the IRLS approach, with higher
Pearson correlations. For pink noise and N1 amplitude outliers, it performs as well as the IRLS,
despite different KS distances. The IRLS algorithm attenuates the influence of those data points
that differ from the ground truth, but this may be from different trials at different time points.
By doing so, KS distances to the ground truth were similar or lower (for alpha and gamma
oscillations) than the OLS. The WLS approach attenuates the influence of trials with different time
courses and thus, the WLS ERP mean is affected at every time point, even if the detection
concerns a small part of the time course, leading to higher KS distances even with a small number
of outliers.

339
Figure 4. Face ERPs computed using low and high weight trials. The top of the figure displays the mean of
low weight (red) and high weight (black) trials over right posterior temporal (subject 2, channel 50), left
frontal (subject 14 channel 4), and left posterior central (subject 19, channel 66) areas. The weights were
obtained either with the PCP-WLS or the IRLS methods. The lower part of the figure displays single subject
mean tSNR, power and autocorrelation (scatter plots) along with the percentile bootstrap difference
between low and high weight trials (black circles are the bootstrap 20% trimmed mean differences and
the pink rectangles show the 20% trimmed mean and 95% confidence intervals).
347

	tSNR difference (uV)		Power difference (dB)		autocorrelation difference (ms)	
	WLS	IRLS	WLS	IRLS	WLS	IRLS
s2	[-0.03 0.54]	[0.26 1.14]	[-2 6]	[3 18]	[-8.5 1.8]	[5.09 16.4]
s3	[2.35 2.92]	[-4.48 -2.34]	[35 50]	[-55 -22]	[-3.9 3.5]	[16.6 45.9]
s4	[0.14 069]	[1.9 3.43]	[1 13]	[39 64]	[-13 -6.7]	[-12.8 3.2]
s5	[4.03 8.25]	[10.7 13.57]	[77 200]	[297 382]	[-13 -4.7]	[-14.6 -4.9]
s6	[1.51 2.87]	[-0.74 1.98]	[24 48]	[-6 33]	[-4.8 -0.39]	[-0.6 17.8]
s7	[1.16 5.1]	[2.44 5.26]	[38 141]	[54 129]	[-4 11.1]	[-7.3 11.2]
s8	[7.49 8.21]	[7.57 8.55]	[154 173]	[159 183]	[-24 -19.8]	[-20.2 -14.1]
s9	[2.97 7.96]	[-4.55 0.44]	[52 169]	[-74 28]	[-16 -7.1]	[-1.5 7.1]
s10	[-0.61 0.9]	[-3.47 2.27]	[-11 11]	[-107 102]	[0.9 9.1]	[-0.2 1.5]
s11	[-0.73 4.46]	[4.57 7.27]	[-11 168]	[123 200]	[-2.9 1.4]	[0 7.8]
s12	[6.69 11.17]	[-2.06 4.85]	[149 250]	[-98 93]	[-31 -22]	[-13.1 -2.7]
s13	[-5.06 0.1]	[-6.8 2.91]	[-222 2]	[-285 142]	[4.4 12]	[-6.2 0.19]
s14	[4.81 7.63]	[3.54 7.77]	[174 270]	[123 270]	[-0.4 24]	[-6.9 13.3]
s15	[1.69 3.91]	[-0.97 2.06]	[36 93]	[-20 51]	[-6.5 1.1]	[1.8 10.5]
s16	[-6.85 8.4]	[-2.13 13.82]	[-164 300]	[-65 444]	[-8.3 8.7]	[-16 14.1]
s17	[2.34 3.72]	[2.31 4.09]	[34 68]	[45 83]	[-29.4 -15.9]	[-13.8 2.4]
s18	[0.54 1.28]	[-0.64 1.86]	[6 20]	[-3 27]	[-15.7 -2.43]	[-28.8 11.4]
s19	[-0.39 0.71]	[-0.40 0.57]	[-8 16]	[-9 17]	[-6.9 -1.3]	[-7.1 -1.5]

Supplementary Table 1. Subjects 95% percentile bootstrap confidence intervals of 20% trimmed mean differences between high and low trials obtained using PCP-WLS or IRLS at channels with the highest between-trial variance. Intervals which do not include 0 (i.e., the difference between high vs. low trials is statistically significant) are shown on a gray background.

352
Figure 5. Robustness of the PCP method to outlying trials with a SNR of 1. The upper part of the figure
shows median and 95% CI results for outliers affected by white noise, pink noise, alpha and gamma
oscillations. The lower part of the figure shows results for trials affected by amplitude changes over the N1
component (0.5, 0.8, 1.2, 1.5 times the N1). Mean Pearson correlations indicate how similar the
reconstructed means are to the ground truth, while mean Kolmogorov-Smitnov distances indicate how
much the overall distribution of values differ from the ground truth. OLS is in blue, IRLS in green, WLS in
red.

360
Supplementary figure 2. Robustness of the PCP method to outlying trials with a SNR of 2. The upper part
of the figure shows median and 95% CI results for outliers affected by white noise, pink noise, alpha and
gamma oscillations. The lower part of the figure shows results for trials affected by amplitude changes
over the N1 component (0.5, 0.8, 1.2, 1.5 times the N1). Mean Pearson correlations indicate how similar
the reconstructed means are to the ground truth, while mean Kolmogorov-Smirnov distances indicate how
much the overall distribution of values differ from the ground truth. OLS is in blue, IRLS in green, WLS in
red.
368

Statistical inference for single subjects

The average type 1 error rate for every channel and time frame tested with simulated data is at the nominal level (5%) for OLS. Results also show that IRLS are a little lenient, with small but significantly smaller p-values than expected, leading to an error rate of ~0.055. Conversely, WLS are conservative for simulated ERP, with p-values slightly too high, giving a type 1 error rate of ~0.04) and lenient with purely Gaussian data (type 1 error ~0.065 – table 1). This behaviour of WLS is caused by the PCP method which optimizes weights based on distances across time, except that with simulated Gaussian data there is no autocorrelation and the PCA returns a much higher number of dimensions, leading to a meaningless feature reduction and thus meaningless trial distances and weights.

		Null Gaussian	Null ERP
Regression	OLS	[0.0495 0.0503]	[0.0498 0.0507]
	WLS	[0.0636 0.0645]	[0.0400 0.0408]
	IRLS	[0.0555 0.0564]	[0.0527 0.0536]
ANOVA	OLS	[0.0493 0.0502]	[0.0493 0.0501]
	WLS	[0.0695 0.0706]	[0.0374 0.0382]
	IRLS	[0.0575 0.0584]	[0.0540 0.0549]
ANCOVA condition	OLS	[0.0494 0.0502]	[0.0493 0.0502]
	WLS	[0.0699 0.0709]	[0.0379 0.0386]
	IRLS	[0.0578 0.0587]	[0.0546 0.0555]
ANCOVA covariate	OLS	[0.0496 0.0505]	[0.0496 0.0504]
	WLS	[0.0638 0.0648]	[0.0410 0.0418]
	IRLS	[0.0563 0.0572]	[0.0538 0.0547]

Table 1. Type I error rate binomial 95% confidence intervals at every time frames and channels for simulated data under the null hypothesis.

The WLS family-wise type 1 error rate (i.e. controlling the error for statistical testing across the whole data space) examined using nullified ERP data from Wakeman and Henson (2015) shows a good probability coverage for both maximum and cluster statistics with 95% confidence intervals overlapping with the expected nominal value (figure 6). Individual mean values ranged from 0.039 to 0.070 for maximum statistics (across subject average 0.052) and 0.044 to 0.07 for spatial-temporal clustering (across subject average 0.051). Those results do not differ significantly from OLS results (paired bootstrap t-test). Additional analyses based on the number

of bootstraps used to build the null distribution indicate that 800 to a 1000 bootstrap samples
are enough to obtain stable results, and that the errors are relatively well distributed in space
and time even if some channels tend to be more affected than others, i.e. there is no strong
sampling bias: maximum number of error occurring at the same location was 0.05% using
maximum statistics and 0.9% using spatial-temporal clustering, see bottom for figure 6, error
density maps.
397

398
Figure 6. Type 1 error rates under the null using the PCP-WLS method. The top row shows the subjects'
error rates: cell-wise, i.e. averaged across all time frames and channels, and corrected for the whole data
space, i.e. type 1 family wise error rate using either the distribution of maxima or the distribution of the
biggest cluster-masses. Results are within the expected range (marked by dotted black lines) with
overlapping 95% confidence intervals for maximum statistics and spatial-temporal clustering. The middle
row shows the effect of the number of resamples, with the dashed lines representing the boundaries of the
individual 95% average confidence intervals, and the black lines the average. The cell-wise error is not
affected by the number of bootstrap samples since it does not depend directly on this parameter to
estimate the null (left). Using maximum statistics and cluster-mass distribution estimates shows a stronger
dependency on the number of bootstrap estimates, with results stable after 800 to 1000 bootstraps. The
bottom row shows error density maps (sum of errors out of 27000 null maps). The cell-wise error (i.e. no
correction for multiple comparisons) shows that errors accumulate, with some channels showing many
consecutive time frames with 5% error. By contrast, maximum statistics (middle) and the maximum
cluster-masses (right) do not show this effect (maxima at 0.05% and 0.9%), suggesting little to no spatial
bias in sampling (note the very different density scales for the three measures).

Performance evaluation at the group level
415
Repeated measures ANOVAs using parameter estimates from each method revealed 2 spatial-
temporal clusters for the face effect for both WLS and IRLS, but only the 1st cluster was declared
statistically significant using OLS (table 2). The expected results (Wakeman & Henson, 2015) with
full faces having stronger N170 responses than scrambled faces are replicated for all approaches
(start of cluster 1). Maximum differences were observed over the N170 only when using OLS
parameters. Using WLS and IRLS gave maxima much later (P280), a result also observed when
using TFCE rather than spatial-temporal clustering. In each case, a repetition effect was also
observed in a much more consistent way among methods with the second presentation of stimuli
differing from the 1st and 3rd presentations (figure 7).
425

	OLS	WLS	IRLS
Face effect			
cluster 1	140ms to 504ms, max=74, p=0.002 at 184ms channel EEG049	140ms to 424ms, max=64, p= 0.002 at 280ms channel EEG017	136ms to 432ms, max=74, p= 0.002 at 292ms channel EEG006
cluster 2		440ms to 648ms, max=17.6, p= 0.032 at 616ms channel EEG057	520ms to 648ms, max=22, p= 0.032 at 636ms channel EEG055
TFCE	max=74, p=0.026 at 184ms channel EEG049	max=64, p=0.012 at 280ms channel EEG017	max=74, p=0.012 at 292ms channel EEG006
Repetition effect			
cluster 1	232ms to 648ms, max=50, p= 0.001 at 588ms channel EEG057	232ms to 648ms, max=51, p= 0.001 at 612ms channel EEG045	236ms to 648ms, max=52, p= 0.001 at 588ms channel EEG057
TFCE	max=50, p=0.002 at 588ms channel EEG057	max=51, p= 0.001 at 612ms channel EEG045	max=52, p= 0.001 at 588ms channel EEG057

426   *Table 2: Face and repetition effects results using cluster-mass correction and TFCE for each of the three*
427   *methods.*

428
Figure 7. Main Face effects observed using OLS, WLS or IRLS 1st level derived parameters. The left column shows the full channels * times thresholded maps using cluster-mass correction for multiple comparisons (p<.05). Topographies are plotted at three local maxima. The middle and right columns show time courses of the mean parameter estimates per condition (blue, red, orange) and condition differences (green, purple, black) over channel 50 (right inferior-temporal) and channel 6 (middle anterior frontal).

The statistical maps show that group results using based on WLS parameter estimates lead to
smaller F values than those obtained from OLS or IRLS estimates (note the difference in maxima
table 1 and scale in Figure 7), which is confirmed by the median differences in Hotelling T^2 values
(supplementary tables 2, 3 & table 3). Considering uncorrected p-values, this translates into
weaker statistical power for WLS: Face effect OLS = 34% of significant data frames, WLS = 31%,
IRLS = 34%, Repetition effect OLS = 39%, WLS = 35%, IRLS = 39%. Results based on cluster-
corrected p-values showed however more statistical power for WLS relative to OLS for the Face
effect (OLS 20% WLS 22% IRLS 25% of significant data frames with cluster mass and 3%, 5% 3%
of significant data frames with TFCE), and mixed results for the Repetition effect (OLS 31% WLS
28% IRLS 31% of significant data frames with cluster mass and 7%, 8% 7% of significant data
frames with TFCE).
446
To further understand how cluster-based results lead to more statistical power for WLS while F
values are smaller, we compared distributions' shapes by comparing the deciles of normalized
values (figure 8). For the face effect, WLS did not differ significantly from OLS or from IRLS for F-
values, while TFCE values were significantly larger, from the 2nd decile onward when compared
to OLS, and for deciles 2, 3, 4, 7, 8 and 9 compared to IRLS. For the repetition effect, WLS differed
from OLS on deciles 2, 7, 8 and 9 for both F-values and TFCE values while it differed from IRLS on
decile 9 only when looking at F-values, and deciles 2, 5, 8 and 9 when looking at TFCE values.
Finally, for the interaction effect, WLS did not differ from OLS or IRLS in terms of F-values but had
significantly weaker TFCE values than OLS (deciles 1, 3, 6, 7, 8 and 9) and IRLS (all deciles but the
4th). In summary, for the significant main face effect and repetition effect, a general pattern of
more right skewed distributions of F-values and TFCE-values for WLS than for OLS and IRLS was
observed while a shorter tail was observed for the non significant interaction effect.
459

	face effect	repetition effect	interaction effect
WLS vs OLS	-0.32 [-0.36 -0.28]	-0.54 [-0.59 -0.48]	-0.21 [-0.29 -0.13]
WLS vs IRLS	-0.34 [-0.39 -0.30]	-0.53 [-0.58 -0.48]	-0.14 -0.21 -0.08]

460 *Table 3. Median differences in Hotteling T^2 values for each effect tested with percentile*
461 *bootstrap 95% confidence intervals (p=0.001).*
462

		OLS	WLS	IRLS
Cluster 1 Channel 50	Famous Faces vs. Scrambled	-4.93 [-12.2 2.32]	-4.52 [-11.39 2.34]	-5.82 [-12.76 1.11]
	Unfamiliar Faces vs. Scrambled	-4.77 [-12.42 2.86]	-4.64 [-13.02 3.72]	-5.19 [-11.93 1.54]
	Famous vs Unfamiliar Faces	-0.15 [-3.13 2.81]	0.12 [-3.28 3.53]	-0.62 [-4.86 3.60]
Cluster 1 Channel 6	Famous Faces vs. Scrambled	2 [-5.25 9.25]	1.71 [-5.16 8.59]	1.68 [-6.05 9.41]
	Unfamiliar Famous Faces vs. Scrambled	3.21 [-5.80 12.22]	2.20 [-5.97 10.38]	2.95 [-6.08 11.99]
	Famous vs Unfamiliar Faces	-1.20 [-5.72 3.30]	-0.49 [-5.03 4.04]	-1.27 [-5.47 2.93]
Cluster 2 Channel 50	Famous Faces vs. Scrambled	-4 [-13.82 5.82]	-4.11 [-15.62 7.40]	-4.04 [-13.31 5.23]
	Unfamiliar Faces vs. Scrambled	-2.16 [-9.20 4.87]	-2.17 [-9.83 5.48]	-2.32 [-8.96 4.31]
	Famous vs Unfamiliar Faces	-1.83 [-6.47 2.81]	-1.93 [-9.76 5.88]	-1.71 [-7.47 4.03]

463 *Supplementary table 2. Pairwise differences in mean parameter estimates (arbitrary unit) measured at*
464 *channel 50 and 6 at the maximum of the famous faces responses.*
465

		medianT	maxT	medianF	maxF	medianCluster	maxCluster	medianTFCE	maxTFCE
Face effect	OLS	4.44	157.64	2.09	74.19	72.57	22591.41	130.41	40992.1
	WLS	3.98	136.27	1.87	64.13	64.29	19453.52	85.72	35828.8
	IRLS	4.49	157.77	2.11	74.25	34.41	23300.19	130.88	54888.48
Repetition Effect	OLS	5.38	107.03	2.53	50.37	35.25	39116.91	244.38	82143.67
	WLS	4.46	109.14	2.1	51.36	33.76	33979.02	129.89	76244.1
	IRLS	5.32	110.86	2.5	52.17	37.31	39870.66	212.27	98429.06
Interaction Effect	OLS	5.45	126.31	1.12	26.01	23.79	387.94	27.64	483.46
	WLS	5.17	78.15	1.06	16.09	21.14	317.38	25.69	470.1
	IRLS	5.32	135.67	1.09	27.93	30.57	283.44	22.9	366.41

466   *Supplementary table 3. Medians and maxima of the Hotelling T^2, F-values, Cluster-mass and TFCE scores*
467   *for each effect of the ANOVA and methods used at the 1st level.*
468

469
470   *Figure 8. Comparisons of the deciles of standardized F-value (1st and 2nd column) and TFCE value (3rd and*
471   *4th column) distributions. Comparisons were done independently for the face effect, the repetition effect*
472   *and their interaction.*

Discussion

Simulation and data-driven results indicate that the proposed WLS-PCP method is efficient at down weighting trials with dynamics differing from the bulk, leading to more accurate estimates. Results show that, for ERP, deriving weights based on the temporal profile provides a robust solution against white noise or uncontrolled oscillations. For biological (pink) noise and amplitude variations which do not alter the temporal profile, the PCP algorithm does not classify well outlier trials, leading to a decrease in detection performance compared with white, alpha or gamma noise. Rather than a defect, we see this as biologically relevant (see below). Importantly, even in those cases of failed detection, the overall correlations with the ground truth remained high (>=0.99). When analyzing real data, differences in amplitude variations were nevertheless captured by the PCP/WLS approach, with amplitude variations related to trials which were out of phase with the bulk of the data.

Group-level analyses of the face dataset replicated the main effect of face type (faces>scrambled) in a cluster from ~150ms to ~350ms but also revealed a late effect (>500ms), observed when using WLS and IRLS parameter estimates but absent when using OLS parameter estimates. Despite more data frames declared significant with WLS than OLS, effects sizes were smaller for WLS than for OLS and IRLS. The shape of the F distributions when using WLS parameter estimates were however more right skewed than when using OLS or IRLS, leading cluster corrections to declare more data points as significant. Indeed, under the null, very similar distributions of maxima are observed for the three methods leading to more power for the more skewed observed distributions. The interplay between 1st level regularization, 2nd level effect size, and multiple comparison procedures depends on many parameters and it is not entirely clear how statistical power is affected by their combination and requires deeper investigation via simulations. Empirically, we can nevertheless conclude that group results were statistically more powerful using robust approaches at the subject level than when using OLS.

Using the trial dynamics (temporal or spectral profile) to derive a single weight per trial makes sense, not just because the observed signal is autocorrelated, but also because it is biologically relevant. Let's consider first the signal plus noise model of ERP generation (Hillyard, 1985; Jervis et al., 1983; Shah, 2004). In this conceptualization, ERPs are time-locked additive events running on top of background activity. An outlier time frame for a given trial may occur if 1) the evoked amplitude deviates from the bulk of evoked trials, or 2) the background activity deviates from the rest of the background activity. In the former case, the additional signal may be conceived either as a single process (a chain of neural events at a particular location) or a mixture of processes (multiple, coordinated neural events). In both cases, the data generating process is thought to be evolving over time (auto-regressive) which speaks against flagging or weighting a strong deviation at a particular time frame only. It is likely that several consecutive time frames deviate from most other trials, even though only one time frame is deemed an outlier. In the case of a deviation in background activity, it would mean that for an extremely brief period, a large number of neurons synchronized for non-experimentally related reasons, and for this trial only. Although we do not contend that such events cannot happen in general, this would mean that, in the context of ERP outlier detection, the background activity varies by an amount several folds

bigger than the signal, which goes against theory and observations. Let now us consider the phase
resetting model (Makeig et al., 2002; Sayers et al., 1974). In this model, ERPs are emerging from
phase synchronization among trials, due to stimulus induced phase-resetting of background
activity. If a trial deviates from the rest of the trials, this implies that it is out-of-phase. In this
scenario, deriving different weights for different time frames (i.e. IRLS solution) means that the
time course is seen as an alternation of normal and outlying time frames, which has no
meaningful physiological interpretation. Thus, irrespective of the data generating model, the WLS
approach seems biologically more appropriate than the IRLS method.
525
526 In conclusion, we propose a fast and straightforward weighting scheme for trials based on their
527 temporal or spectral profiles. Results indicate that it captures and attenuates well ERP noise,
528 leading to increased estimation precision and possibly increased statistical power at the group
529 level.
530
531 **Acknowledgements**
532

533 Thank you to EEGLAB/LIMO MEEG users who engaged with the beta version, got stuck but
534 persevered until we solved their issues.

535
536 **References**
537

Christensen, R. (2002). *Plane Answers to Complex Questions. The theory of Linear Models.* (3rd
ed.). Springer.
Delorme, A., & Makeig, S. (2004). EEGLAB: An open source toolbox for analysis of single-trial EEG
dynamics including independent component analysis. *Journal of Neuroscience Methods*,
134(1), 9–21. https://doi.org/10.1016/j.jneumeth.2003.10.009
Filzmoser, P., Maronna, R., & Werner, M. (2008). Outlier identification in high dimensions.
Computational Statistics & Data Analysis, *52*(3), 1694–1711.
Hillyard, S. A. (1985). Electrophysiology of human selective attention. *Trends in Neurosciences*, *8*,
400–405. https://doi.org/10.1016/0166-2236(85)90142-0
Hochberg, Y. (1988). A Sharper Bonferroni Procedure for Multiple Tests of Significance.
Biometrika. 75 (4): 800–802
Hoaglin, D. C., & Welsch, R. E. (1978). The Hat Matrix in Regression and ANOVA. *The American
Statistician*, *32*(1), 17–22. https://doi.org/10.2307/2683469
Jervis, B. W., Nichols, M. J., Johnson, T. E., Allen, E., & Hudson, N. R. (1983). A Fundamental
Investigation of the Composition of Auditory Evoked Potentials. *Biomedical Engineering,
IEEE Transactions On*, *BME-30*(1), 43–50. https://doi.org/10.1109/TBME.1983.325165
Kothe, C. A., & Makeig, S. (2013). BCILAB: A platform for brain-computer interface development.
Journal of Neural Engineering, *10*(5), 056014. https://doi.org/10.1088/1741-
2560/10/5/056014
Makeig, S., Westerfield, M., Jung, T-P., Enghoff, S., Townsend, J., Courchesne, E., & Sejnowski,
T.J. (2002). Dynamic Brain Sources of Visual Evoked Responses. *Science*, *295*(5555), 690–
694.
Maris, E. & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-data.

Journal of Neuroscience Methods, *164*(1), 177–190.

Onton, J., Westerfield, M., Townsend, J., & Makeig, S. (2006). Imaging human EEG dynamics using independent component analysis. *Neuroscience & Biobehavioral Reviews*, *30*(6), 808–822. https://doi.org/10.1016/j.neubiorev.2006.06.007

Pernet, C.R., Latinus, M., Nichols, T. E., & Rousselet, G. A. (2015). Cluster-based computational methods for mass univariate analyses of event-related brain potentials/fields: A simulation study. *Journal of Neuroscience Methods*, *250*, 85–93. https://doi.org/10.1016/j.jneumeth.2014.08.003

Pernet, C.R., Appelhoff, S., Gorgolewski, K. J., Flandin, G., Phillips, C., Delorme, A., & Oostenveld, R. (2019). EEG-BIDS, an extension to the brain imaging data structure for electroencephalography. *Scientific Data*, *6*(1), 103. https://doi.org/10.1038/s41597-019-0104-8

Pernet, C.R., Chauveau, N., Gaspar, C., & Rousselet, G. A. (2011). LIMO EEG: A Toolbox for Hierarchical LInear MOdeling of ElectroEncephaloGraphic Data. *Computational Intelligence and Neuroscience*, *2011*, 1–11. https://doi.org/10.1155/2011/831409

Pernet, C.R., Martinez-Cancino, R., Truong, D., Makeig, S., & Delorme, A. (2021). From BIDS-Formatted EEG Data to Sensor-Space Group Results: A Fully Reproducible Workflow With EEGLAB and LIMO EEG. *Frontiers in Neuroscience*, *14*, 610388. https://doi.org/10.3389/fnins.2020.610388

Pion-Tonachini, L., Kreutz-Delgado, K., & Makeig, S. (2019). The ICLabel dataset of electroencephalographic (EEG) independent component (IC) features. *Data in Brief*, *25*, 104101. https://doi.org/10.1016/j.dib.2019.104101

Sayers, B. MCA., Beagley, H. A., & Henshall, W. R. (1974). The Mechanism of Auditory Evoked EEG Responses. *Nature*, *247*(5441), 481–483. https://doi.org/10.1038/247481a0

Shah, A. S. (2004). Neural Dynamics and the Fundamental Mechanisms of Event-related Brain Potentials. *Cerebral Cortex*, *14*(5), 476–483. https://doi.org/10.1093/cercor/bhh009

Yeung, N., Bogacz, R., Holroyd, C., Nieuwenhuis, S., & Cohen, J. (2018). *Simulated EEG data generator* [Matlab]. https://data.mrc.ox.ac.uk/data-set/simulated-eeg-data-generator