Linked machine learning classifiers improve species classification of fungi when using

error-prone long-reads on extended metabarcodes

Tavish Eenjes[1†], Yiheng Hu[1,8†], Laszlo Irinyi[2,3,4], Minh Thuy Vi

Hoang[2,3,4], Leon M. Smith[1,9], Celeste C. Linde[1], Wieland Meyer[2,3,4,5,6],

Eric A. Stone[1,7], John P. Rathjen[1], Benjamin Mashford[7*], Benjamin

Schwessinger[1*]

[1] Research School of Biology, Australian National University, Acton, ACT, 2601, Australia

[2] Molecular Mycology Research Laboratory, Centre for Infectious Diseases and

Microbiology, Faculty of Medicine and Health, Sydney Medical

School, Westmead Clinical School, The University of Sydney, Camperdown, NSW, 2006,

Australia

[3] Sydney Institute for Infectious Diseases, The University of Sydney, Camperdown, NSW,

2006, Australia

[4] Westmead Institute for Medical Research, Westmead, NSW, 2145, Australia

[5] Westmead Hospital (Research and Education Network), Westmead, NSW, 2145,

Australia

[6] Curtin Medical School, Curtin University, Perth Bentley, WA 6102, Australia

[7] Biological Data Science Institute, Australian National University, Acton, ACT, 2601,

Australia

[8] Current address: Department of Microbial Interactions, IMIT/ZMBP, University of

Tübingen, Tübingen, 72074, Germany

[9] Diversity Arrays Technology, Bruce, ACT, 2617, Australia

† These authors contributed equally to this work.

* Correspondence should be addressed to

Benjamin Mashford (benjamin.mashford@anu.edu.au)

and Benjamin Schwessinger (benjamin.schwessinger@anu.edu.au)

ABSTRACT

Background: The increased usage of error-prone long-read sequencing for metabarcoding of fungi has not been matched with adequate public databases and concomitant analysis approaches. We address this gap and present a proof-of-concept study for classifying fungal taxa using linked machine learning classifiers. We demonstrate the capability of linked machine learning classifiers to accurately classify species and strains using real-world and simulated fungal ribosomal DNA datasets, including plant and human pathogens. We benchmark our new approach in comparison to current alignment and k-mer based methods based on synthetic mock communities. We also assess real world applications of species identification in complex unlabelled datasets.

Results: Our machine learning approach assigned individual nanopore long-read amplicon sequences to fungal species with high recall rates and low false positive rates. Importantly, our approach successfully distinguished between closely-related species and strains when individual read errors were higher than the genetic distance between individual taxa, which the alignment and k-mer methods could not do. The machine learning approach showed an ability to identify key species with high recall rates, even in complex samples of unknown species composition.

Conclusions: A proof of concept machine learning approach using a tree-descent approach on a decision tree of classifiers can identify known taxa with high accuracy, and precisely detect known target species from complex samples with high recall rates. We propose this approach is suitable for detecting the known knowns of pathogens or invasive species in any environment of mostly unknown composition, including agriculture and wild ecosystems.

KEYWORDS

Machine learning, fungi, long-read sequencing, MinION, convolutional neural network

BACKGROUND

DNA sequencing is increasingly becoming an important part of detecting, identifying and classifying fungal species, particularly through DNA barcoding [1]. To date, this process mostly involves the use of short, variable regions of DNA that differ between species and are surrounded by conserved regions suitable for 'universal' primers, enabling PCR amplification over a large variety of fungal taxa [2, 3]. The internal transcribed spacer (ITS) region is used as the primary DNA barcode region for fungal diversity studies [4]. This region contains the two variable components, ITS1 and ITS2, which are a combined 550-600 bp long on average [5]. ITS1 and ITS2 are separated by the conserved 5.8S rRNA gene and flanked by the conserved 18S and 28S rRNA genes (Figure 1a). Although these regions offer a targetable region for identifying fungal species, they have limitations that affect the ability to accurately classify fungi especially at lower taxonomic ranks [5, 6]. The length of the complete ITS1/2 region prevents short-read sequencing platforms to use both in combination for taxonomic classification. Furthermore, the limited selection of 'universal' primers in the region can subject taxonomic studies to primer biases [7].

With the advent and increasing use of long-read sequencing, some of the limitations of short-reads can be bypassed [8]. With long-reads, an extended ITS region can be sequenced encompassing ITS1 and ITS2 in addition to the minor variable regions of the 18S and 28S rRNA subunits using a single 'universal' primer set (Figure 1a) [9-12]. Long-read sequencing technologies from Pacific Biosciences (PacBio) have been extensively benchmarked for fungal metabarcode sequencing [13]. Previous work by Tedersoo et al. [14] using the PacBio

RSII and Sequel instruments suggest long-read sequencing offers higher resolution for

species identification than short-reads. Specifically, they found that using full-length ITS

sequences increased identification precision for fungi by 33% compared to using ITS1 or

ITS2 alone. Further, PacBio long-reads better reflected the community composition of a

template mock community than traditional Illumina MiSeq short-reads [13, 14]. In contrast,

Oxford Nanopore Technologies (ONT) products have not been as extensively benchmarked

for fungal species identification using metabarcodes [15]. This is despite the fact that the

ONT MinION has the unique advantage of being highly portable for field studies.

Here, we apply ONT long-read sequencing to fungal ribosomal DNA amplicons generated

with the NS3 and LR6 primers [16], spanning close to 2900 bp in size (Figure 1a). We refer

to this amplicon hereafter as the fungal ribosomal DNA region. Nanopore sequencing

introduces a relatively high read error of around 10% at the time of conducting our study

[15], but this read error has recently been improved to ~5% with the ONT super high

accuracy basecalling models. These high error rates make individual reads less suited for

species identification using DNA metabarcodes with currently existing sequence clustering,

alignment and k-mer based methods because the genetic distance of the variable regions

between closely related species are often lower than the per read error rate [17]. In addition,

the entries in most fungal DNA barcode databases, such as the NCBI ITS database and

UNITE [18] are relatively short, with a median sequence length of 580 bp and 540 bp,

respectively. This limits the analysis capacity of long-reads which encompass both ITS

sequences and include minor variable regions in both 18S and 28S rRNA (Figure 1a).

The fungal kingdom is diverse, with an estimated 1.5-5 million species globally, performing

important ecosystem functions [19]. For example, mycorrhizal fungi play a key role in

regulating the nutrient uptake of almost all land plant species [20] and can improve plant

growth under adverse conditions [21], while detritus-degrading saprotrophic fungi play an

important role in improving soil fertility [22]. However, fungal pathogens can have severe

adverse effects on human and animal health and agriculture. Fungi can cause large-scale

biodiversity losses [23, 24], as demonstrated by the near extinction of amphibian taxa by the

globally devastating fungal pathogen *Batrachochytrium dendrobatidis* [25], and the local

extinction of several myrtaceae tree species by the rust fungus *Austropuccinia psidii* [26].

Fungal plant pathogens cost billions of dollars in global food production annually [27].

The importance of fungi warrants the development of improved sequence-based detection

methods for fungi. In our current study we address the shortcomings of current techniques

and assess the applicability of novel machine learning-based sequence analysis methods for

long-read metabarcodes from the fungal kingdom. We focus on the detection of known

knowns – taxa known to be present in a system – in the context of pathogen infections or

host-associated samples. We explored the potential of machine learning classifiers as an

alternative method for assigning individual error-prone long-reads to taxa, especially for

detecting known or likely pathogen candidates. We demonstrate that our approach works on

real data, and demonstrate that machine learning has a place in the pathogen detection space

as a supplementary tool with specific functions, rather than as a replacement for existing

methods.

Within the existing machine learning methods for identifying patterns across various data

types [28-30], convolutional neural networks (CNNs) are one method especially suited for

identifying the deterministic spatial relationships in a DNA sequence [31-34]. We applied a

CNN approach to metabarcoding-based fungal species identification using a uniquely

labelled sequencing dataset of a 2900 bp fungal ribosomal DNA region from 44 individually

sequenced fungal taxa. This included species and strains associated with plants, from

environmental and soil samples, and human pathogens. We used real-world datasets to

closely mimic real-world sequencing conditions and demonstrate the potential of machine-

learning in the pathogen detection space, and further demonstrate that this method can be

used alongside simulated read datasets. We compared our machine learning approach to three

commonly used analysis approaches, including alignment and k-mer based methods, on

different in house and publicly available databases. We demonstrated its potential advantage

on classifying closely related fungal species with few basepairs difference within the fungal

ribosomal DNA region. Furthermore, by including a broad list of fungal taxa across the

fungal kingdom and a comprehensive and focused group of fungal taxa related to the target

species when training the machine learning models, the approach can identify and detect a

known or suspected target species from a complex sample even if not all species present in

the sample were included in the training dataset.

RESULTS

Design of a decision tree for machine learning classifiers for taxonomic assignment of

fungal species

Here we explored the application of machine learning on individual nanopore reads for

fungal taxonomic classification. We sequenced the fungal ribosomal DNA region of 44

fungal taxa individually to generate a labelled real-world dataset for which the ground truth is

known for each individual read. This makes our dataset uniquely suited for our supervised

machine learning approach and for benchmarking studies when comparing this to commonly

used classification approaches. Our fungal species dataset included 39 ascomycetous taxa,

spanning 19 families and 27 genera, in addition to five basidiomycetes. Given the high

sequencing depth of the amplicon sequencing, we performed stringent quality-control steps

on all reads to eliminate sequencing biases. We first filtered reads based on homology against

a custom-curated database of the fungal ribosomal DNA region, to remove partial reads or

reads from other areas of the fungal genome with partial primer binding. We then filtered

reads by length to remove reads that were not within a 90% confidence interval around the

mean read length of the fungal ribosomal DNA region for each taxon (see Supporting

Information Table T1). The *Geotrichum candidum* (former *Galactomyces geotrichum*)

sample had too few reads for further processing, hence we complimented those with

simulated reads using NanoSim [35]. This resulted in an average of $54,832 \pm 35,537$ reads

available across all taxa. We took a subsample of these quality-controlled reads and split

them into a training set and a test set, containing 85% and 15% of the subsampled reads

respectively, to be used for training the machine learning classifiers and assessing the

performance of the newly generated machine learning classifiers, respectively. We

implemented a decision tree to be able to classify individual reads at each taxonomic rank

from phylum to species (Figure 1). The taxonomic information for the 44 available

individually sequenced taxa was used to create the cladogram for this decision tree. For

simplification, we counted individual strains as separate species for this purpose to test the

ability to discern between very closely related taxa. We generated one machine learning

classifier for each node in our decision tree, where two or more sub-taxa diverged along the

cladogram (Figure 1).

Figure 1: Visualisation of the fungal ribosomal DNA region and machine learning decision tree.

(a) The fungal ribosomal DNA region between the NS3 and LR6 primers covers around ~2900 bp. Shown is the alignment of consensus sequences (created with Geneious Prime), with highly conserved regions in green and variable regions in red. **(b)** Taxonomic information for 44 species was used to create a decision tree showing the relationship between samples at each taxonomic rank. Where two or more species shared a common taxon, a machine learning classifier (node) was created to distinguish between those taxa. These classifiers were chained together to create a decision tree, whereby the classification of a read was undertaken by a cascade of classifiers. An example path down the decision tree is shown for *Candida albicans*.

For training each of these classifiers, a balanced dataset was used, such that each possible outcome of the machine learning classifier had an equal number of reads. By giving equal weight to each group within the classifiers, we ensure that the machine learning model can identify the best distinguishing features between groups. These individual classifiers at different taxonomic ranks had a mean recall rate of 97.9 ± 1.1% for correctly classifying reads using the test read dataset. The lowest recall rate belonged to the species-level classifier that distinguished between *Candida* species, with a recall rate of 94.4%. The receiver operator characteristic (ROC) curves demonstrated a good classifier (see the GitHub repository at https://github.com/teenjes/fungal_ML).

To fully classify a read, we used the cladogram as a decision tree to link individual machine

learning classifiers at each taxonomic rank. This allowed us to chain classifiers together to

classify a read at each taxonomic rank, moving through the tree from phylum to species

assignments. The outcome of a classifier at one taxonomic rank was used to decide the path

along the tree, and thus this decision defined which classifier was appropriate for use at the

next lower taxonomic rank (Figure 1). We refer to a classifier by the taxonomic rank that it

outputs. For example, a species-level classifier takes reads from a specific genus and outputs

a species, while a class-level classifier takes reads from a specific phylum and outputs a

decision on the taxonomic class of the read. The recall rate of the individual classifiers at

different taxonomic ranks can affect the final species-level recall rate for each individual read

as it moves through the decision tree. This means that the final species-level recall rate is

equal to or worse than the individual species-level classifier's recall rate. Since not every path

through the decision tree had a node at each taxonomic rank, the total number of nodes with

classifiers is less than the total number of taxa. For example, the basidiomycete species

Puccinia striiformis f. sp. *tritici* has only two classifiers, at the phylum level and the class

level. The latter decides the class classification, but as *P. tritici* is the only species in the class

Pucciniomycetes in our sequencing dataset, no further nodes were required to distinguish

between this species and other taxa present in our dataset. Further, both the *Discula quercina*

and *Tapesia yallundae* species were represented in two samples with different strains,

although each was classified as a species for the purposes of this model. In total we trained 22

classifiers to distinguish our 44 fungal taxa.

Machine learning methods provide robust classification, especially at the genus and

species level

We compared the machine learning decision tree to other, more standard methods for read

classification to determine the effectiveness of this technique. We assessed the ability of the

other methods at classifying reads across multiple taxonomic ranks because the tiered nature

of the decision tree offers the potential to gleam taxonomic information from a read, even

when it cannot be confidently classified at the species level. We first looked at the use of a

naïve Bayes classifier, however this performed very poorly and was inconsistent in the results

produced (data not shown), which is consistent with previous studies [34]. We used two

additional classification techniques. We applied *minimap2*, a pairwise alignment-based

method designed to be used with long-reads, against a gold-standard custom-curated database

generated from the consensus sequences of all 44 species present in the decision tree (gold

standard alignment). This is the most appropriate comparison for our machine learning

approach because the gold standard and machine learning approaches are directly derived

from our sequencing dataset. To compare the machine learning approach with methods where

the sequencing data was not used to create the classification database in some way, we

applied *minimap2* to a large publicly-available database of fungal ITS sequences from NCBI

[36, 37] (NCBI alignment), and applied *Kraken2*, a k-mer-based classifier, to the same NCBI

database (*Kraken2*).

To compare these methods, an *in silico* mock community was generated from our labelled

sequencing data via subsampling for which we know the ground truth classification for each

sequencing read. We selected 13 species from the original 44 taxa, including some that

required four or more classifiers to generate the machine learning decision tree, particularly

those from populous genera with closely related species. Although all species from this mock

community were present in the gold standard database, the NCBI database was missing some

genera and species. All of these missing or unclassified taxonomies were recorded as having

a recall rate of zero percent, artificially decreasing the quality at lower taxonomic ranks.

Our machine learning decision tree approach maintained a consistently high recall rate across

all taxonomic ranks, with a mean species level recall rate of $93.0 \pm 2.8\%$ (1σ). Notably, it

performed very well for closely related taxa, including the cryptic species *Candida*

metapsilosis and *Candida orthopsilosis* and another closely related species *Candida albicans*.

The two cryptic *Candida* species (*C. metapsilosis* and *C. orthopsilosis*) had a very high

consensus sequence similarity, with a genetic distance of 2.74% (97.26% identity) in our

fungal ribosomal DNA target region representing the genetically least distinct species pair.

Our machine learning approach achieved species level recall rates of 90.1% and 89.1% for *C.*

metapsilosis and *C. parapsilosis*, respectively, even with per read error rates of about 10%.

This highlights the strength of our approach.

The gold standard alignment approach also performed very well when compared to the

machine learning approach across all taxonomic ranks (Figure 2). The majority of the species

were classified with recall rates in excess of 95%. Yet this approach significantly

underperformed when trying to differentiate taxa with low genetic distance such as those

from the *Candida* genus. As with the machine learning approach, the three *Candida* species

were classified with the lowest recall rate at the species level, with *C. albicans, C.*

metapsilosis and *C. parapsilosis* being classified with recall rates of 35.8%, 34.0% and 57.5%

respectively. These difficulties are also reflected in the overall mean species level recall rate

of $76.6 \pm 25.5\%$, which is much lower than our machine learning approach.

Figure 2: Machine learning based species identification performs especially well for closely related species

Recall rates of the alignment-based *minimap2* technique, k-mer-based *Kraken2* method and the machine learning decision tree across different taxonomic ranks **(a-f)**. The *minimap2* technique, as applied to the gold standard database, was successful across most taxonomic ranks, but lower recall rates were recorded for closely related species at the species level **(f)**. Both the *minimap2* and *Kraken2* methods were applied to the NCBI database, and while the *minimap2* NCBI alignment was more accurate across most taxonomic ranks, both showed comparable recall at the species level. The machine learning decision tree approach provided the greatest classification power for closely related species, despite lower recall rates for some distantly-related species than the gold standard alignment method.

Next, we assessed our dataset with alignment and k-mer based analysis approaches when

using the publicly available NCBI database. Overall, NCBI alignment with *minimap2*

performed similarly well at higher taxonomic ranks. However, inconsistent or missing

naming conventions at the family level and missing or alternate species labels, meant that the

overall recall rate was low at the species level, although most of the samples were classified

with a high recall rate at the genus level. This low species level recall rate is an artefact

created from the choice of database, which is reflected in the similarly poor species level

recall rates of the *Kraken2* method. Overall, the k-mer based *Kraken2* was less accurate than

all other methods tested across all taxonomic ranks.

Identifying target species from a complex sample of unknown composition using the

machine learning decision tree

A key feature of a species classification tool is its ability to identify a known target species

from a complex sample of unknown composition. This is especially important when

attempting to identify the presence of a target species, such as a specific pathogen, from a

patient or environmental sample.

We generated two additional sequencing datasets of unknown composition from two distinct

environments to test the capability of our machine learning decision tree to identify a given

target species. These datasets were generated with the same PCR and sequencing protocols as

for the individual 44 training species focusing on the fungal ribosomal DNA region. The first

dataset was derived from amplicon sequencing of fungi-infected wheat leaves (wheat dataset)

and the second was derived from bronchoalveolar wash in a clinical setting (clinical dataset).

To each of these sequencing datasets of unknown composition, we spiked *in silico* a known

number of reads with known labels as test case. We choose *Aspergillus flavus*, a crop

pathogen, and *Candida albicans*, a human pathogen, to compare two species without and

with very close sister species in our linked machine learning classifiers. We then tested recall

and false positive rate of our machine learning classifiers using our *in silico* spiked reads,

assuming that the original datasets of unknown composition did not contain any reads of

either species.

We first plotted the propagated confidence score of the species level classification for all

reads in each *in silico* spiked dataset to better understand the behaviour of our machine

learning decision tree on samples containing reads of unknown origin (Supporting

Information Figure S1). This clearly shows that the propagated confidence scores for reads of

unknown origin are far lower than reads of species the classifiers were trained on. We then

assessed the recall and false positive rate of the *in silico* spiked datasets at different

confidence scores thresholds assuming that the original sample did not include any reads of

the *in silico* spiked in species (Figure 3). Increasing the thresholds reduced the recall and

false positive rate in both cases. For *A. flavus*, the recall rate remained above 90% until the

confidence threshold reached 0.9, and the false positive rate was consistently low across both

the clinical and wheat datasets with reads of unknown origin. A confidence threshold of 0.85

resulted in a high recall rate of 0.917, while maintaining a low false positive rate of just one

percent. For *C. albicans*, not using a confidence threshold at all resulted in a recall rate of

87.7% and false positive rate of 11.7%. However, by using a confidence threshold of 0.85,

the recall rate was only decreased to 72.4% while reducing the false positive rate to only

1.7% in the clinical dataset. We recommend this confidence score threshold of 0.85 as

suitable for retaining a high recall rate while achieving a low false positive rate, even for a

member of a difficult-to-distinguish genus like *Candida*.

Training a machine learning classifier with simulated reads resulted in similar accuracy

to those trained on real data

Previously, models were trained using sequence data from pure fungal culture. However, this

is not always accessible, and limits the ability for the approach to be extended. This allows

for samples with low read counts, such as the *G. candidum* sample, to be augmented to have

sufficient read counts for training and enables rapid extension of the suggested approach to

more species. We simulated 35,000 reads for *A. flavus* based on our reference ribosomal

DNA sequence using NanoSim v3.0.0 to test whether training machine learning models using

simulated reads would produce the same level of accuracy as training with reads generated by

sequencing amplicons generated from fungal reference cultures.

We retrained all models in the decision tree path of *A. flavus* using these simulated reads.

None of the resultant models were statistically different to those models trained using real

sequenced data in terms of precision or recall. Further, they showed similar ROC curves (see

the GitHub repository at https://github.com/teenjes/fungal_ML). This suggests machine

learning classifiers can be trained using simulated reads and still accurately distinguish

between taxa across all taxonomic ranks.

We also used these modes trained using simulated data to test whether the use of simulated

training data affected the ability of the system to detect target species from a complex sample.

We found no difference in the recall or false positive rates for detecting the target species

using these simulated-trained models, with a near identical distribution to that shown in

Supporting Information Figure S1, and a recall rate of 0.910 when using a confidence

threshold of 0.85 compared to the recall rate of 0.917 when trained on real data.

Figure 3: Varying the confidence score threshold affects the recall rate and false positive rate when identifying target species from complex samples of unknown composition.

The plots show the recall rate (left axis, blue dots) and false positive rate (right axis, orange or green dots) at varying propagated confidence score thresholds for *Aspergillus flavus* (a) and *Candida albicans* (b) when spiked into clinical (orange) or wheat (green) datasets. Both plots are based on 2000-read *in silico* spiked samples containing 1000 reads with known labels (*A. flavus* or *C. albicans*) and 1000 reads of unknown origin. For *A. flavus*, a confidence threshold of 0.85 maintains a recall rate of 91.7%, while reducing the false positive rate to 1% for both datasets. For *C. albicans*, the same confidence threshold of 0.85 has a recall rate of 72.4% and reduces the false positive rate below 2% for both datasets.

DISCUSSION

Nanopore sequencing offers portable sequencing platforms and generates long-reads that can

cover extended metabarcodes that include more sequence information than the classic

metabarcodes from Illumina short-read sequencing [38]. The use of long-read nanopore

sequencing is increasing, and analysis pipelines have been developed for real-time species

identification on the MinION, such as the 'What's in my pot' pipeline for complex sample

analysis [39]. Yet currently, metabarcode datasets in publicly available databases are limited

in barcode length and often do not cover these extended regions, limited only to ITS1 and

ITS2 regions of ~580 bps. This poses challenges when classifying error-prone long-reads into

different species when the genetic differences within those metabarcode regions are less than

the differences from sequencing errors [40].

Here, we implement a novel machine learning approach for species level classification. We

used a tree descent approach, with a similar strategy to the IDTAXA taxonomic classifier

[41], although the objectives differ. IDTAXA also uses a tree-like approach to classify a

subsample of the k-mers into a given taxonomic rank using machine learning, and the user

can specify certain confidence thresholds to avoid over-classification when confidence is low

[41]. While IDTAXA's goal is to classify unknown reads to a confident taxonomic rank, our

approach is more focused on the detection of one or a few target species from mixed samples.

As such, we used full-length reads rather than k-mers from the short ITS regions, as used by

Vu et al. [34], for training the machine learning models. Training these models with long

reads is computationally less efficient than with k-mers, but is more suitable for detection-

focused objectives. The use of only the ITS regions themselves, rather than the extended read

used here, may be feasible for detection-focused tasks, but may lose resolution gained from

small variations in the otherwise conserved RNA-coding regions that surround the ITS. As

such, very closely related taxa may be more difficult to distinguish if only the non-coding ITS

is used [34].

Our approach showed great potential on improving the accuracy of sequencing-based fungal

classification at a species level. For example, some closely related species, such as those from

the *Candida* genus, were readily misclassified with a recall rate lower than 50% using the

gold standard alignment strategy. This is indicative of the problems of alignment-based

classification methods for fungi, especially given the relatively high error rate of the

nanopore long-reads [42]. Using our machine learning method, the same group of species

was classified with recall rates of at least 90% (Figure 2f). This is remarkable given the per-

read error rate of 10% for the nanopore reads used, which is much larger than the genetic

distance of 2.74% observed between some closely related taxa. With recent improvements in

the sequencing and basecalling of nanopore reads reducing the per-read error rate [43], the

resolution of our method is likely to increase.

To ensure accurate classification of reads from closely related taxa using our machine

learning classifiers, the training of species-level classifiers must include metabarcodes from

other taxa closely related to the target for detection. If closely related taxa are not included in

training, the likelihood of false positive hits increases as closely related taxa may be

identified as the target taxon even when the target taxon is not present. For example, *Candida*

metapsilosis may be falsely identified as *Candida albicans* if the model was not trained on

both species. As such, accurate species-level identification requires that machine learning

classifiers are trained on long metabarcodes from as many fungal species in the same genus

as possible. This is especially important when a genus contains both pathogenic and non-

pathogenic species. In this way, our approach might be particularly applicable to targeted

diagnostic tasks in specific settings, such as detecting fungal pathogens in agriculture [44],

forest management [45] and medicine [46], or screening imports for invasive pathogens in aid

of border biosecurity [47, 48].

The initial comparisons were based on idealised databases derived from our sequencing

dataset, for which metabarcode length and online database entry length were equivalent.

Hence, is it expected that analyses based on these idealised databases will outperform other

approaches relying on public databases with short reference sequences of uneven length, as

shown by our results (Figure 2). Interestingly, the *Kraken2* approach underperformed

compared to the alignment-based approach in our current study. This is consistent with

previous studies with nanopore data, where the classification accuracy of *Kraken2* never

exceeded that for BLAST, another alignment-based classification program, when using the

default 35 bp k-mers [49, 50]. One approach to improve the k-mer based classification

accuracy for error-prone reads would be to use a smaller k-mer length. Another common

issue of public fungal databases was that many species were not included in the database or

were presented with different taxonomic labels, which resulted 0% recall rates of some

families and species. Changing fungal nomenclature over time can be an issue when using

these online databases for classifying fungal metabarcode reads, as the nomenclature is not

always updated, leading to outdated or uncorrected taxonomic information persisting in

databases [51, 52].

We also tested if our machine learning approach could accurately identify target species in

complex samples of unknown composition without having classifiers for all fungal species

present in the sample. These complex samples had previously been explored through shogun

sequencing [53, 54]. We were able to show that by only training a limited set of classifiers we

can detect target species with relatively low false positive and high recall rates in *in silico*

spiked datasets with known ground truth of the spiked reads only. By adjusting the

confidence score one can decide how much false positive and false negatives one is willing to

tolerate. We found a threshold of 0.85 on the propagated confidence score at the species level

classification was sufficient to reduce the false positive rate while maintaining high recall

rates. Here, the false positive rate was misleadingly high for *Candida* species in the clinical

sample and for *Aspergillus* species in the wheat sample. We naively assumed these species

were not present in our complex sample save for those reads that had been spiked in. *Candida*

species, including *C. albicans*, are common in humans, and similarly *A. flavus* is a common

fungus present on wheat. However, it also demonstrates the need to curate closely related

species for training the models, as other species from the *Candida* or *Aspergillus* genera may

have been misidentified as the target species from these complex samples.

Further, we found that training the machine learning classifiers using simulated reads, rather

than sequenced reads, did not disadvantage the model's ability to distinguish between taxa at

any level. It is useful for extending this approach to a larger training set with an increased

number of species, particularly for including additional taxa closely related to the target

species. We can simulate reads based on publicly available reference sequences to train the

classifiers, making this approach accessible even where reference cultures are not readily

available.

The taxa used to train the classifiers are flexible and can be changed to suit the user's need

including simulation based on publicly deposited genomes of unavailable species. For

example, additional species from a specific taxon could be added to reduce false positive

detections within that taxa. While many existing classifiers are designed for species

classification, and can falsely identify previously unknown species as existing species by

over-labelling [55], our approach focused on detection of known target fungi rather than

identifying all species present. While unknown taxa absent in the training dataset will be

assigned a label, the use of a confidence score threshold can aid in filtering these

misclassified unknowns out. The principles behind the application of machine learning to the

fungal ribosomal DNA region can be expanded to other barcoding regions, such as

cytochrome c oxidase I [56] or *elongation factor 1 alpha* [46]. Recent developments by

Oxford Nanopore Technologies to improve barcoding accuracy, cost-effectiveness and

scalability, such as the recently-released Q20+ chemistry, offers promise for expanding our

proof-of-concept study to more species using multiple barcodes to improve the species-level

resolution and overall classification accuracy [57].

CONCLUSIONS

Long-read sequencing can be more accurate for species identification and detection than short

reads, offering an advantage for future use [13, 14]. Here, we propose a tangible solution for

fungal classification and detection by applying a novel neural network-based machine

learning approach on extended fungal ribosomal DNA barcodes using nanopore long-read

sequencing. Our machine learning approach can identify target taxa with high accuracy from

complex samples of unknown origin, making it applicable to pathogen identification in

agriculture, biosecurity, and clinical settings. Our approach performs especially well on

closely related species, outcompeting current alignment-based or k-mer-based classification

methods for long reads. Future optimisations for real life applications are required in terms of

computational efficiency and size of reference training sets.

METHODS

Fungal pathogen sample collection, DNA extraction and ITS amplification

We collected different fungal tissue differently for DNA extractions. The tissue collection

processes for each fungal taxon are summarized in Supporting Information Table T1.

We used three different DNA extraction methods for all the species in the mock

communities. The methods for each species are listed in the Supporting Information Table

T1. Collectively, we used two commercially available kits: the Qiagen DNeasy Plant Mini

Kit (cat. no. 69106) for most plant pathogenic fungi, and the Quick-DNA Fungal/Bacterial

Miniprep Kit (cat. no. D6005, Zymo Research) for some human pathogenic fungi following

the manufacturer's protocol. We used a phenol chloroform-based DNA extraction method for

other human pathogenic and environmental fungi modified from Ferrer et al [58]. Briefly,

100 mg of leaf tissue was homogenized and cells were lysed using cetyl trimethylammonium

bromide (CTAB, Sigma-Aldrich) buffer (added RNAse T1, Thermo Fisher, 1,000 units per

1750 µl), followed by a phenol/chloroform/isoamyl alcohol (25:24:1, Sigma-Aldrich)

extraction to remove protein and lipids. DNA was precipitated with 700 µl of isopropanol,

washed with 1 ml of 70% ethanol, dried for 5 min at room temperature, and resuspended in

50 µl TE buffer containing 10 mM Tris and 1 mM EDTA at pH 8. For the human clinical

sample and the field infected wheat sample, we directly used the DNA described in the

original article [53, 54] for PCR amplification. Quality and average size of genomic DNA

was visualized by gel electrophoresis with a 1% agarose gel for 1 h at 100 volts. DNA was

quantified by NanoDrop and Qubit (Life Technologies) according to the manufacturer's

protocol.

We used the NS3 (5' GCAAGTCTGGTGCCAGCAGCC '3) and LR6 (5'

CGCCAGTTCTGCTTACC '3) primers [16] to generate the fungal ribosomal DNA fragment

of all samples, and the EF1-983F (5' GCYCCYGGHCAYCGTGAYTTYAT '3) and EF1-

2218R (5' ATGACACCRACRGCRACRGTYTG '3) primers [16] were used to sequence a

secondary region, the fungal elongation factor 1 alpha region, which was not used for

assessing the machine learning method. We used the New England Biolabs Q5 High-Fidelity

DNA polymerase (NEB #M0515) for the PCR reaction following the manufacturer's

protocol. Around 10 – 30 nanograms of DNA were used in each PCR reaction. After PCR,

DNA was purified with one volume of Agencourt AMPure XP beads (cat. No. A63881,

Beckman Coulter) according to the manufacturer's protocol and stored at 4°C.

Library preparation and DNA sequencing using the MinION

DNA sequencing libraries were prepared using Ligation Sequencing 1D SQK-LSK108 and

Native Barcoding Expansion (PCR-free) EXP-NBD103 Kits from ONT, as adapted by Hu

and Schwessinger [59] from the manufacturer's instructions with the omission of DNA

fragmentation and DNA repair. DNA was cleaned up using a 1x volume of Agencourt

AMPure XP beads (cat. No. A63881, Beckman Coulter), incubated at room temperature with

gentle mixing for 5 mins, washed twice with 200 µl fresh 70% ethanol, the pellet allowed to

dry for 2 mins, and DNA eluted in 51 µl nuclease free water and quantified using NanoDrop$^{®}$

(Thermo Fisher Scientific, USA) and Promega Quantus$^{™}$ Fluorometer (cat. No. E6150,

Promega, USA) following the manufacturer's instructions. All DNA samples showed

absorbance ratio A260/A280 > 1.8 and A260/A230 > 2.0 from the NanoDrop$^{®}$. DNA was

end-repaired using NEBNext Ultra II End-Repair/ dA-tailing Module (cat. No. E7546, New

England Biolabs (NEB), USA) by adding 7 µl Ultra II End-Prep buffer, 3 µl Ultra II End-

Prep enzyme mix. The mixture was incubated at 20°C for 10 mins and 65°C for 10 mins. A

1x volume (60 µl) Agencourt AMPure XP clean-up was performed, and the DNA was eluted

in 31 µl nuclease free water. Barcoding reaction was performed by adding 2 µl of each native

barcode and 20 µl NEB Blunt/TA Master Mix (cat. No. M0367, New England Biolabs

(NEB), USA) into 18 µl DNA, mixing gently and incubating at room temperature for 10

mins. A 1x volume (40 µl) Agencourt AMPure XP clean-up was then performed, and the

DNA was eluted in 15 µl nuclease free water. Ligation was then performed by adding 20 µl

Barcode Adapter Mix (EXP-NBD103 Native Barcoding Expansion Kit, ONT, UK), 20 µl

NEBNext Quick Ligation Reaction Buffer, and Quick T4 DNA Ligase (cat. No. E6056, New

England Biolabs (NEB), USA) to the 50 µl pooled equimolar barcoded DNA, mixing gently and incubating at room temperature for 10 mins. The adapter-ligated DNA was cleaned-up by adding a 0.4x volume (40 µl) of Agencourt AMPure XP beads, incubating for 5 mins at room temperature and resuspending the pellet twice in 140 µl ABB provided in the SQK-LSK108 kit. The purified-ligated DNA was resuspended by adding 15 µl ELB provided in the SQK-LSK108 (ONT, UK) kit and resuspending the beads. The beads were pelleted again, and the supernatant transferred to a new 0.5 ml DNA LoBind tube (cat. No. 0030122348, Eppendorf, Germany).

In total, four independent sequencing reactions were performed on a MinION flow cell (R9.4, ONT) connected to a MK1B device (ONT) operated by the MinKNOW software (version 2.0.2): 11 species for each flowcell. Each flow cell was primed with 1 ml of priming buffer comprising 480 µl Running Buffer Fuel Mix (RBF, ONT) and 520 µl nuclease free water. 12 µl of amplicon library was added to a loading mix including 35 µl RBF, 25.5 µl Library Loading beads (ONT library loading bead kit EXP-LLB001, batch number EB01.10.0012) and 2.5 µl water with a final volume of 75 µl and then added to the flow cell via the SpotON sample port. The "NC_48Hr_sequencing_FLOMIN106_SQK-LSK108" protocol was executed through MinKNOW after loading the library and run for 48 h. Raw fast5 files were processed using Albacore 2.3.1 software (ONT) for basecalling, barcode de-multiplexing and quality filtering (Phred quality (Q) score of > 7) as per the manufacturer's recommendations. Raw unfiltered fastq files were uploaded into NCBI Short Reads Archive under BioProject PRJNA725648.

Processing and manipulation of fungal pathogen reads

The read datasets obtained contained both the fungal ribosomal DNA sequence and that of

elongation factor 1 alpha. A two-step data filtration process was applied to remove the

elongation factor 1 alpha reads and outlier reads from the fungal ribosomal DNA read set.

Reads were mapped to an in-house database of fungal ribosomal DNA regions to select reads

of a similar general structure to the ITS region. This homology-based filter assumes the

structure of the fungal ribosomal DNA region is similar between species due to shared

ancestry, repeatedly shown to be true [60]. The in-house database was curated from 28 ITS

sequences from the NCBI Nucleotide database, from a range of genera across the fungal

kingdom. This process mapped reads using *minimap2* (v2.17), using the map-ont flag. Reads

that failed to map were discarded.

Remaining reads were filtered for read length. The expected read length for the fungal

ribosomal DNA region varied by species, averaging 2600-3200 bp. As the mean length and

spread of successfully filtered reads differed between samples, a 90% confidence interval cut-

off around the mean read length was applied. This interval was sufficient to exclude short or

very long reads resulting from incomplete or partial homology filtering or errors in the

sequencing or basecalling processes.

Augmenting read datasets

Some reads were simulated using a consensus sequence and MinION read error profile to

ensure all samples had at least 15,000 reads for use in the design of the machine learning

classifiers downstream. NanoSim (v2.0.0) [35] was used for one species, *Geotrichum*

candidum, to generate an additional 8,782 simulated cDNA reads. These reads were

generated using an identical error profile and length spread to the pre-existing non-simulated

reads.

An additional simulated dataset was later generated using NanoSim v3.0.0 for use in testing

the ability to train models using simulated data based on references available online, without

losing the ability to accurately classify reads from real-world data. A total of 35,000

additional reads were simulated for *Aspergillus flavus* to ensure the maximum number of

reads that could be processed using our approach was available. These reads were generated

using an error profile identical to the pre-existing non-simulated reads but were based on a

reference consensus sequence for *A. flavus*.

555 Generating consensus sequences for each species

The consensus sequence, an aggregate sequence formed from the comparison of multiple

sequences that represents the 'true' sequence, was generated using 200 randomly subsampled

filtered reads for each sample. Primer sequences were removed using *Mothur* v1.44.11 [61],

an alignment file was generated using *muscle* v3.8.1551 [62] and the consensus sequence was

generated from this file using *EMBOSS cons* v6.6.0.0 [63]. These consensus sequences were

used to confirm taxonomy when species was initially unclear by mapping to the UNITE,

SILVA and NCBI databases.

563 Determining the relationships between samples

Using the taxonomic information available for each sample in MycoBank and the results of a

BLAST search with the generated consensus sequences, a cladogram was designed to show

the relationships between samples based on major taxonomic ranks. A machine learning

classifier would be required at each point where two or more samples split on the cladogram

(a node) to distinguish between samples for each read, with the cladogram functioning as a

decision tree with the node-situated classifiers determining the path of tree descent.

Individual strains of the same species were counted as separate species for this cladogram.

571 Creation of neural network classifiers to distinguish between samples

A convolutional neural network (CNN) was chosen as the most appropriate type of machine

learning classifier due to its ability to use the spatial relationships between data features in the

reads, such as the distance between ITS and other variable groups. CNNs are capable of

learning from both minor variation and higher-order features, which is of particular

importance given the high read error of nanopore reads. While we did compare a naïve

Bayesian and a fully-connected multilayer perceptron model to the CNN approach, these

produced quite poor results in comparison, and previous studies using short-read k-mers had

shown CNNs to provide an advantage over the existing Bayesian Ribosomal Database Project

and other machine learning classifier types [34]. Given this, we selected CNNs to be the basis

of our decision tree moving forward.

CNNs work best when there is a balanced number of items in each classification class. As

such, for each multiclass node on the cladogram, an equal number of reads were subsampled

from each group of samples that would be represented in the node. So, for machine learning

classifiers distinguishing between species, each species present contributes an equal number

of reads, while at the kingdom level, each phylum contributes an equal number of reads, with

said reads being distributed equally amongst all species belonging to that phylum. The

number of reads subsampled was based on the largest number of reads available for each

sample, with a maximum of 35,000 reads due to computational processing limitations. For

each read subsampled, the nucleotide sequence was converted to a numeric sequence, where

A, C, G, and T became 0, 1, 2, and 3, respectively. This integer encoding produced the same

result as using one-hot encoding to multiple dimensions. As not all sequences were of equal

length, but an equal length was required to avoid sequence length being a distinguishing

factor in the classifier, all sequences were padded out to a length of 5,000 bp. The padding

used a value of 4 to avoid the padding data from affecting the identification of key features

for classification.

Each read was assigned a label representing the output class it would belong to in the one-hot

format. Labelled reads were then separated into a training set and a test set. The training set

contained 85% of the reads, and was used to train the machine learning classifiers, while the

test set contained the remaining 15% of labelled reads and was used to test the efficacy of

said classifiers on similar data that the classifier had not previously encountered. This was

done using the leave out N sequences approach rather than leaving out N taxa, which is more

appropriate to represent the 'dark matter' taxa, as we wanted to focus on detecting the known

knowns rather than the potential unknowns [55]. The neural network was created using the

Sequential classifier of the *Keras* framework for neural networks [64], containing five layers

of neurons and trained across 10 epochs.

Specific details for the design of the machine learning classifiers and the required software

packages for machine learning and other analyses can be found at

https://github.com/teenjes/fungal_ML.

Evaluation of the machine learning classifiers

The test set was used to assess the accuracy of the various machine learning classifiers. As

the test set data was labelled, the expected outcome for each read was known, and could be

compared to the output of the machine learning classifier. The accuracy, or classification rate,

of these classifiers was the proportion of reads in the test set for whom the prediction of the

machine learning classifier, as determined by the highest confidence score, matched the

expected outcome. This is equivalent to the recall rate [1], where matches to the expected

outcome were true positives and matches outside this outcome were false negatives.

$$Recall\ Rate = \frac{True\ Positives}{True\ Positives + False\ Negatives} \qquad [\ 1\ ]$$

Chaining machine learning classifiers into a decision tree

When seeking to identify members of a specific taxon in a community, where the members

are not immediately obvious from the species name, it is useful to have samples classified at

each taxonomic rank. A singular classifier would require excessive computational power to

do this. As such, we chained the machine learning classifiers together into a decision tree

with a tree descent approach, based on the cladogram of the species present in our sample.

The most confident outcome of the machine learning classifier at one taxonomic rank would

be used to decide the path along the decision tree. This path could either lead into another

machine learning classifier, if the path diverged again, or lead all the way down to the species

level with the same confidence.

Alternative methods for fungal pathogen read classification

We used two different commonly used methods for fungal pathogen metabarcode

classification to benchmark the linked machine learning model approach: an alignment-based

method in *minimap2*; and a k-mer-based method in *Kraken2*. To compare these methods, we

generated an *in silico* mock community from our labelled sequencing data for which we

know the ground truth classification for each sequencing read. This mock community

contained 13 of the 44 species used to generate the original machine learning decision tree,

randomly subsampling 1000 reads from those not previously used for training the machine

learning classifiers. Species were selected to focus on species for whom multiple machine

learning classifiers would be required, in particular species with populous genera.

For this *minimap2*-based alignment method, two separate databases were used for

identification. Firstly, a gold standard database was created in-house to represent the best-

case scenario for identification, when all the species present in a sample are also present in

the database. This contained the labelled consensus sequences of all 44 species present in the

machine learning decision tree, using the consensus sequences already generated from 200

randomly selected filtered reads. The second was a publicly available database of fungal ITS

sequences from NCBI

(ftp://ftp.ncbi.nlm.nih.gov/refseq/TargetedLoci/Fungi/fungi.ITS.fna.gz, downloaded Feb

2021). *Minimap2* was applied to each of these databases using the map-ont flag. As the

alignment tool can return multiple hits if alignment is good enough, only the best hit was

taken for each read.

We used *Kraken2* (v2.0.8) to assign the NCBI taxonomic ID for the same 1000 reads of each

species as used in the machine learning decision tree. We generated a *Kraken2* NCBI ITS

database with the same fasta file downloaded from above. We used the *Kraken2*-build

command with the --add-to-library and --build flag. We used the Python pandas module to

modify the *Kraken2* output file and the numpy module to calculate the accuracy.

Identifying a key species from a complex sample using machine learning

To assess the suitability of machine learning for this problem, we utilised the two complex

datasets sampled from fungi-infected sources of unknown compositions: the field infected

wheat dataset [53] and the human clinical dataset [54], to create *in silico* mock communities.

We randomly subsampled 950 reads from these datasets, after initial processing as done on

the data for machine learning, and spiked in 50 reads from one of two target species with

known ground truth: *Aspergillus flavus*, a crop pathogen; and *Candida albicans*, an

opportunistic human pathogen present in the human microbiome. This created a total of four

1000-read synthetic communities, two of which paired a target species and dataset from the

same source (*A. flavus* with the wheat dataset and *C. albicans* with the clinical dataset) and

two communities where the target species would not be expected to be present in the complex

dataset unless it had been spiked in. We used the propagated confidence scores for assessing

the recall rate for these spiked datasets, where the confidence score at each taxonomic rank

was multiplied to give a final overall confidence at the species level.

We created an additional four *in silico* mock communities to assess the change in recall rate

and false positive rate [2] as a confidence threshold was applied.

$$False\ Positive\ Rate = \frac{False\ Positives}{False\ Positives + True\ Negatives} \qquad [\,2\,]$$

Each mock community was created by randomly subsampling 1000 reads from one of *A.*

flavus or *C. albicans* samples with known ground truth and adding an additional 1000

randomly subsampled reads from one of the wheat or clinical datasets containing reads of

unknown origin. In total, this resulted in four 2000-read *in silico* mock communities. We

assumed the datasets with reads of unknown origin did not contain any reads for the target

species tested, placing an upper bound on the false positive rate and a lower bound on the true

positive rate. Any positive identifications of the target species *A. flavus* or *C. albicans* with a

propagated confidence score below the confidence threshold were instead classified as

negative identifications.

Identifying a key species from a complex sample using classifiers trained on simulated

reads

We used the augmented simulated read dataset from *Aspergillus flavus* generated by

NanoSim to retrain those five models involved in the decision tree path leading to *A. flavus*,

with an identical process to the initial model training. These models were incorporated into

the decision tree in place of the original classifiers to test the ability of the decision tree to

identify key species from complex samples when trained on simulated data. This used an

identical method to the above method for identifying a key species from a complex sample.

DECLARATIONS

ETHICS APPROVAL AND CONSENT TO PARTICIPATE

Not Applicable.

CONSENT FOR PUBLICATION

Not Applicable.

AVAILABILITY OF DATA AND MATERIALS

The code generated and used for machine learning during the current study is available in the

GitHub repository, available at https://github.com/teenjes/fungal_ML. The single-species

datasets generated and/or analysed during the current study are available in SRA under

BioProject PRJNA725648, available at http://www.ncbi.nlm.nih.gov/bioproject/725648. The

complex mixed-species 'clinical' and 'wheat' datasets analysed during the current study are

available in the same BioProject as SRX10704261 and SRX10704260, respectively.

COMPETING INTERESTS

The authors declare that they have no competing interests.

FUNDING

This work was supported by computational resources provided by the Australian Government

through the National Computational Infrastructure (NCI) under the ANU Merit Allocation

Scheme. YH, ES, JR and BS are supported by The Hermon Slade Foundation grant

HSF_17_04, and WM is supported by an Australian NHMRC grant (#APP1121936).

714 AUTHOR CONTRIBUTIONS

715 TE, YH, BM, and BS designed the experiments and performed the analysis. YH extracted

716 fungal DNA and performed all sequencing reactions. LI, MTV, LMS, CCL, and WM

717 provided fungal material and/or DNA. ES and JR provided feedback on experimental design

718 and data analysis. WM, ES, JR, and BS provided funding for the project. TE, YH and BS

719 wrote the manuscript. All authors commented on the manuscript and approved submission.

721 ACKNOWLEDGEMENTS

We thank Jen Taylor, and Peter Solomon for suggestions on improving the machine learning

models and determining statistics for identifying a species from a complex sample. We thank

Peter Solomon and David Jones for providing fungal samples. We thank Andrew Milgate for

providing infected wheat leaf material. This work was supported by computational resources

provided by the Australian Government through the National Computational Infrastructure

(NCI) under the ANU Merit Allocation Scheme.

REFERENCES

1.   Kennedy PG, Cline LC, Song Z: **Probing promise versus performance in longer**

read fungal metabarcoding. 2018, **217**(3):973-976.

2.   Seifert KA: **Progress towards DNA barcoding of fungi**. 2009, **9**(s1):83-89.

3.   Valentini A, Pompanon F, Taberlet P: **DNA barcoding for ecologists**. *Trends in*

734   *Ecology & Evolution* 2009, **24**(2):110-117.

735   4.   Schoch CL, Seifert KA, Huhndorf S, Robert V, Spouge JL, Levesque CA, Chen W:

736   **Nuclear ribosomal internal transcribed spacer (ITS) region as a universal DNA**

737   **barcode marker for Fungi**. 2012, **109**(16):6241-6246.

738   5.   Xu J: **Fungal DNA barcoding**. *Genome* 2016, **59**(11):913-932.

739   6.   Badotti F, de Oliveira FS, Garcia CF, Vaz ABM, Fonseca PLC, Nahum LA, Oliveira

740   G, Góes-Neto A: **Effectiveness of ITS and sub-regions as DNA barcode markers**

741   **for the identification of Basidiomycota (Fungi)**. *BMC Microbiology* 2017, **17**(1):42.

742   7.   James TY, Stajich JE, Hittinger CT, Rokas A: **Toward a Fully Resolved Fungal**

743   **Tree of Life**. 2020, **74**(1):291-313.

744   8.   Mafune KK, Godfrey BJ, Vogt DJ, Vogt KA: **A rapid approach to profiling diverse**

745   **fungal communities using the MinION™ nanopore sequencer**. 2020, **68**(2):72-78.

746   9.   Tedersoo L, Anslan S: **Towards PacBio-based pan-eukaryote metabarcoding**

747   **using full-length ITS sequences**. 2019, **11**(5):659-668.

748   10.   Vilgalys R, Hester M: **Rapid genetic identification and mapping of enzymatically**

749   **amplified ribosomal DNA from several Cryptococcus species**. *J Bacteriol* 1990,

750   **172**(8):4238-4246.

751   11.   White TJ, Bruns T, Lee S, Taylor J: **38 - AMPLIFICATION AND DIRECT**

752   **SEQUENCING OF FUNGAL RIBOSOMAL RNA GENES FOR**

753   **PHYLOGENETICS**. In: *PCR Protocols*. Edited by Innis MA, Gelfand DH, Sninsky

754   JJ, White TJ. San Diego: Academic Press; 1990: 315-322.

755   12.   Gardes M, Bruns TD: **ITS primers with enhanced specificity for basidiomycetes -**

756   **application to the identification of mycorrhizae and rusts**. 1993, **2**(2):113-118.

757   13.   Castaño C, Berlin A, Brandström Durling M, Ihrmark K, Lindahl BD, Stenlid J,

758   Clemmensen KE, Olson Å: **Optimized metabarcoding with Pacific biosciences**

759   **enables semi-quantitative analysis of fungal communities**. 2020, **228**(3).

760   14.   Tedersoo L, Tooming-Klunderud A, Anslan S: **PacBio metabarcoding of Fungi and**

761   **other eukaryotes: errors, biases and perspectives**. 2018, **217**(3):1370-1385.

762   15.   Loit K, Adamson K, Bahram M, Puusepp R, Anslan S, Kiiker R, Drenkhan R,

763   Tedersoo L: **Relative Performance of MinION (Oxford Nanopore Technologies)**

764   **versus Sequel (Pacific Biosciences) Third-Generation Sequencing Instruments in**

765   **Identification of Agricultural and Forest Fungal Pathogens**. 2019, **85**(21):e01368-

766   01319.

767   16.   Raja HA, Miller AN, Pearce CJ, Oberlies NH: **Fungal Identification Using**

768   **Molecular Tools: A Primer for the Natural Products Research Community**.

769   *Journal of Natural Products* 2017, **80**(3):756-770.

770   17.   Nilsson RH, Kristiansson E, Ryberg M, Hallenberg N, Larsson K-H: **Intraspecific**

771   **ITS variability in the kingdom fungi as expressed in the international sequence**

772   **databases and its implications for molecular species identification**. *Evol Bioinform*

773   *Online* 2008, **4**:193-201.

774   18.   UNITE Community: **UNITE QIIME release for Fungi. Version 18.11.2018**. In.:

775   UNITE Community; 2019.

776   19.   Choi J, Kim S-H: **A genome Tree of Life for the Fungi kingdom**. *Proc Natl Acad*

777   *Sci U S A* 2017, **114**(35):9391-9396.

778   20.   van der Heijden MGA, Martin FM, Selosse M-A, Sanders IR: **Mycorrhizal ecology**

779   **and evolution: the past, the present, and the future**. 2015, **205**(4):1406-1423.

780   21.   Chen M, Arato M, Borghi L, Nouri E, Reinhardt D: **Beneficial Services of**

781   **Arbuscular Mycorrhizal Fungi – From Ecology to Application**. 2018, **9**(1270).

22.   Ning Q, Chen L, Zhang C, Ma D, Li D, Han X, Cai Z, Huang S, Zhang J:

Saprotrophic fungal communities in arable soils are strongly associated with soil

fertility and stoichiometry. *Applied Soil Ecology* 2021, **159**:103843.

23.   Almeida F, Rodrigues ML, Coelho C: **The Still Underestimated Problem of Fungal**

Diseases Worldwide. *Front Microbiol* 2019, **10**:214-214.

24.   Powell D, Jones A, Kent N, Kaur P, Bar I, Schwessinger B, Frère CH: **Genome**

Sequence of the Fungus Nannizziopsis barbatae, an Emerging Reptile Pathogen.

2021, **10**(1):e01213-01220.

25.   Lips KR: **Overview of chytrid emergence and impacts on amphibians**. *Philos*

Trans R Soc Lond B Biol Sci 2016, **371**(1709):20150465.

26.   Fensham RJ, Carnegie AJ, Laffineur B, Makinson RO, Pegg GS, Wills J: **Imminent**

Extinction of Australian Myrtaceae by Fungal Disease. *Trends in Ecology &*

Evolution 2020, **35**(7):554-557.

27.   Birren B, Fink G, Lander EJC, MA: Whitehead Institute Center for Genome

Research: **Fungal Genome Initiative: white paper developed by the fungal**

research community. 2002.

28.   Tarca AL, Carey VJ, Chen X-w, Romero R, Drăghici S: **Machine learning and its**

applications to biology. *PLoS computational biology* 2007, **3**(6):e116-e116.

29.   Libbrecht MW, Noble WS: **Machine learning applications in genetics and**

genomics. *Nat Rev Genet* 2015, **16**(6):321-332.

30.   Boža V, Brejová B, Vinař T: **DeepNano: Deep recurrent neural networks for base**

calling in MinION nanopore reads. *PLoS One* 2017, **12**(6):e0178751.

31.   Flagel L, Brandvain Y, Schrider DR: **The Unreasonable Effectiveness of**

Convolutional Neural Networks in Population Genetic Inference. *Mol Biol Evol*

2019, **36**(2):220-238.

32.   Arratia A, Sepúlveda E: **Convolutional Neural Networks, Image Recognition and**

808   **Financial Time Series Forecasting**. In*: 2020; Cham*: Springer International

809   Publishing; 2020: 60-69.

810   33.   Ji S, Xu W, Yang M, Yu K: **3D Convolutional Neural Networks for Human Action**

811   **Recognition**. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 2013,

812   **35**(1):221-231.

813   34.   Vu D, Groenewald M, Verkley G: **Convolutional neural networks improve fungal**

814   **classification**. *Sci Rep* 2020, **10**(1):12628-12628.

815   35.   Yang C, Chu J, Warren RL, Birol I: **NanoSim: nanopore sequence read simulator**

816   **based on statistical characterization**. *Gigascience* 2017, **6**(4):1-6.

817   36.   Schoch CL, Robbertse B, Robert V, Vu D, Cardinali G, Irinyi L, Meyer W, Nilsson

818   RH, Hughes K, Miller AN *et al*: **Finding needles in haystacks: linking scientific**

819   **names, reference specimens and molecular data for Fungi**. *Database (Oxford)*

820   2014, **2014**:bau061.

821   37.   Robbertse B, Strope PK, Chaverri P, Gazis R, Ciufo S, Domrachev M, Schoch CL:

822   **Improving taxonomic accuracy for fungi in public sequence databases: applying**

823   **'one name one species' in well-defined genera with Trichoderma/Hypocrea as a**

824   **test case**. *Database (Oxford)* 2017, **2017**:bax072.

825   38.   D'Andreano S, Cuscó A, Francino O: **Rapid and real-time identification of fungi**

826   **up to species level with long amplicon nanopore sequencing from clinical**

827   **samples**. *Biology Methods and Protocols* 2020, **6**(1).

828   39.   Juul S, Izquierdo F, Hurst A, Dai X, Wright A, Kulesha E, Pettett R, Turner DJ:

829   **What's in my pot? Real-time species identification on the MinION™**.

830   2015:030742.

40.   Heeger F, Bourne EC, Baschien C, Yurkov A, Bunk B, Spröer C, Overmann J,

Mazzoni CJ, Monaghan MT: **Long-read DNA metabarcoding of ribosomal RNA in**

the analysis of fungi from aquatic environments. 2018, **18**(6):1500-1514.

41.   Murali A, Bhargava A, Wright ES: **IDTAXA: a novel approach for accurate**

taxonomic classification of microbiome sequences. *Microbiome* 2018, **6**(1):140.

42.   Hofstetter V, Buyck B, Eyssartier G, Schnee S, Gindro K: **The unbearable lightness**

of sequenced-based identification. *Fungal Diversity* 2019, **96**(1):243-284.

43.   Marcolungo L, Passera A, Maestri S, Segala E, Alfano M, Gaffuri F, Marturano G,

Casati P, Bianco PA, Delledonne M: **Real-Time On-Site Diagnosis of Quarantine**

Pathogens in Plant Tissues by Nanopore-Based Sequencing. *Pathogens* 2022,

11(2):199.

44.   Zou J, Huss M, Abid A, Mohammadi P, Torkamani A, Telenti A: **A primer on deep**

learning in genomics. *Nature Genetics* 2019, **51**(1):12-18.

45.   Luchi N, Ioos R, Santini A: **Fast and reliable molecular methods to detect fungal**

pathogens in woody plants. *Applied Microbiology and Biotechnology* 2020,

104(6):2453-2468.

46.   Ching T, Himmelstein DS, Beaulieu-Jones BK, Kalinin AA, Do BT, Way GP, Ferrero

E, Agapow P-M, Zietz M, Hoffman MM *et al*: **Opportunities and obstacles for**

deep learning in biology and medicine. 2018, **15**(141):20170387.

47.   Bulman SR, McDougal RL, Hill K, Lear G: **Opportunities and limitations for DNA**

metabarcoding in Australasian plant-pathogen biosecurity. *Australasian Plant*

Pathology 2018, **47**(5):467-474.

48.   Hu Y, Wilson S, Schwessinger B, Rathjen JP: **Blurred lines: integrating emerging**

technologies to advance plant biosecurity. *Current Opinion in Plant Biology* 2020,

56:127-134.

49.   Pearman WS, Freed NE, Silander OK: **Testing the advantages and disadvantages**

857   **of short- and long- read eukaryotic metagenomics using simulated reads**. *BMC*

858   *bioinformatics* 2020, **21**(1):220-220.

859   50.   Hu Y, Irinyi L, Vi Hoang MT, Eenjes T, Graetz A, Stone E, Meyer W, Schwessinger

860   B, Rathjen JP: **Inferring species compositions of complex fungal communities**

861   **from long- and short-read sequence data**. *bioRxiv* 2021:2021.2005.2002.442318.

862   51.   Sanford RA, Lloyd KG, Konstantinidis KT, Löffler FE: **Microbial Taxonomy Run**

863   **Amok**. *Trends in Microbiology* 2021, **29**(5):394-404.

864   52.   Lücking R, Aime MC, Robbertse B, Miller AN, Aoki T, Ariyawansa HA, Cardinali

865   G, Crous PW, Druzhinina IS, Geiser DM *et al*: **Fungal taxonomy and sequence-**

866   **based nomenclature**. *Nature Microbiology* 2021, **6**(5):540-548.

867   53.   Hu Y, Green GS, Milgate AW, Stone EA, Rathjen JP, Schwessinger B: **Pathogen**

868   **Detection and Microbiome Analysis of Infected Wheat Using a Portable DNA**

869   **Sequencer**. 2019, **3**(2):92-101.

870   54.   Irinyi L, Hu Y, Hoang MTV, Pasic L, Halliday C, Jayawardena M, Basu I, McKinney

871   W, Morris AJ, Rathjen J *et al*: **Long-read sequencing based clinical metagenomics**

872   **for the detection and confirmation of Pneumocystis jirovecii directly from**

873   **clinical specimens: A paradigm shift in mycological diagnostics**. *Medical*

874   *mycology* 2019, **58**(5):650-660.

875   55.   Edgar RC: **Accuracy of taxonomy prediction for 16S rRNA and fungal ITS**

876   **sequences**. *PeerJ* 2018, **6**:e4652.

877   56.   Rodrigues MS, Morelli KA, Jansen AM: **Cytochrome c oxidase subunit 1 gene as a**

878   **DNA barcode for discriminating Trypanosoma cruzi DTUs and closely related**

879   **species**. *Parasites & Vectors* 2017, **10**(1):488.

57.   Srivathsan A, Lee L, Katoh K, Hartop E, Kutty SN, Wong J, Yeo D, Meier R:

MinION barcodes: biodiversity discovery and identification by everyone, for

everyone. 2021:2021.2003.2009.434692.

58.   Ferrer C, Colom F, Frasés S, Mulet E, Abad JL, Alió JL: **Detection and**

identification of fungal pathogens by PCR and by ITS2 and 5.8S ribosomal DNA

typing in ocular infections. *J Clin Microbiol* 2001, **39**(8):2873-2879.

59.   **Amplicon sequencing using MinION optimized from 1D native barcoding**

genomic DNA

60.   Narutaki S, Takatori K, Nishimura H, Terashima H, Sasaki T: **Identification of fungi**

based on the nucleotide sequence homology of their internal transcribed spacer 1

(ITS1) region. *PDA journal of pharmaceutical science and technology* 2002,

56(2):90-98.

61.   Schloss PD, Westcott SL, Ryabin T, Hall JR, Hartmann M, Hollister EB, Lesniewski

RA, Oakley BB, Parks DH, Robinson CJ *et al*: **Introducing mothur: Open-Source,**

Platform-Independent, Community-Supported Software for Describing and

Comparing Microbial Communities. 2009, **75**(23):7537-7541.

62.   Edgar RC: **MUSCLE: multiple sequence alignment with high accuracy and high**

throughput. *Nucleic acids research* 2004, **32**(5):1792-1797.

63.   Madeira F, Park YM, Lee J, Buso N, Gur T, Madhusoodanan N, Basutkar P, Tivey

ARN, Potter SC, Finn RD *et al*: **The EMBL-EBI search and sequence analysis**

tools APIs in 2019. *Nucleic acids research* 2019, **47**(W1):W636-W641.

64.   Chollet F: **Keras**. In.: GitHub; 2015.

TABLE AND FIGURE LEGENDS

Figure 1: Visualisation of the fungal ribosomal DNA region and machine learning decision

tree. (**a**) The fungal ribosomal DNA region between the NS3 and LR6 primers covers around

~2900 bp. Shown is the alignment of consensus sequences (created with Geneious Prime),

with highly conserved regions in green and variable regions in red. (**b**) Taxonomic

information for 44 species was used to create a decision tree showing the relationship

between samples at each taxonomic rank. Where two or more species shared a common

taxon, a machine learning classifier (node) was created to distinguish between those taxa.

These classifiers were chained together to create a decision tree, whereby the classification of

a read was undertaken by a cascade of classifiers. An example path down the decision tree is

shown for Candida albicans.

Figure 2: Machine learning based species identification performs especially well for closely

related species. Recall rates of the alignment-based *minimap2* technique, k-mer-based

Kraken2 method and the machine learning decision tree across different taxonomic ranks (**a-**

f). The *minimap2* technique, as applied to the gold standard database, was successful across

most taxonomic ranks, but lower recall rates were recorded for closely related species at the

species level (**f**). Both the *minimap2* and *Kraken2* methods were applied to the NCBI

database, and while the minimap2 NCBI alignment was more accurate across most

taxonomic ranks, both showed comparable recall at the species level. The machine learning

decision tree approach provided the greatest classification power for closely related species,

despite lower recall rates for some distantly-related species than the gold standard alignment

method.

Figure 3: Varying the confidence score threshold affects the recall rate and false positive rate

when identifying target species from complex samples of unknown composition. The plots

show the recall rate (left axis, blue dots) and false positive rate (right axis, orange or green

dots) at varying propagated confidence score thresholds for Aspergillus flavus (a) and

Candida albicans (b) when spiked into clinical (orange) or wheat (green) datasets. Both plots

are based on 2000-read in silico spiked samples containing 1000 reads with known labels (A.

flavus or C. albicans) and 1000 reads of unknown origin. For A. flavus, a confidence

threshold of 0.85 maintains a recall rate of 91.7%, while reducing the false positive rate to

1% for both datasets. For C. albicans, the same confidence threshold of 0.85 has a recall rate

of 72.4% and reduces the false positive rate below 2% for both datasets.

(a) *Aspergillus flavus*

Legend: *Aspergillus flavus*, clinical dataset, wheat dataset

Axes: Recall Rate / Confidence threshold / False Positive rate

(b) *Candida albicans*

Legend: *Candida albicans*, clinical dataset, wheat dataset

Axes: Recall Rate / Confidence threshold / False Positive rate

Aspergillus flavus in wheat dataset

(a)

Candida albicans in wheat dataset

(b)

Aspergillus flavus in clinical dataset

(c)

Candida albicans in clinical dataset

(d)

Spiked
Unknown origin

Confidence Score

n=50

n=23

n=927

n=44

n=6

n=950

Aspergillus flavus   other

Candida albicans   other

n=48

n=2

n=950

n=40

n=88

n=10

n=862

Aspergillus flavus   other

Candida albicans   other