Title: Minian an Open-source Miniscope Analysis Pipeline

Authors: Zhe Dong[1], William Mau[1], Yu Feng[1], Zachary T. Pennington[1], Lingxuan Chen[1], Yosif
Zaki[1], Kanaka Rajan[1], Tristan Shuman[1], Daniel Aharoni*[2], Denise J. Cai*[1]

*Corresponding Authors

[1]Nash Family Department of Neuroscience, Icahn School of Medicine at Mount Sinai

[2]Department of Neurology, David Geffen School of Medicine, University of California, Los
Angeles

Abstract

Miniature microscopes have gained considerable traction for *in vivo* calcium imaging in freely
behaving animals. However, extracting calcium signals from raw videos is a computationally
complex problem and remains a bottleneck for many researchers utilizing single-photon *in*
vivo calcium imaging. Despite the existence of many powerful analysis packages designed to
detect and extract calcium dynamics, most have either key parameters that are hard-coded or
insufficient step-by-step guidance and validations to help the users choose the best parameters.
This makes it difficult to know whether the output is reliable and meets the assumptions
necessary for proper analysis. Moreover, large memory demand is often a constraint for setting
up these pipelines since it limits the choice of hardware to specialized computers. Given these
difficulties, there is a need for a low memory demand, user-friendly tool offering interactive
visualizations of how altering parameters at each step of the analysis affects data output. Our
open-source analysis pipeline, Minian (Miniscope Analysis), facilitates the transparency and
accessibility of single-photon calcium imaging analysis, permitting users with little computational
experience to extract the location of cells and their corresponding calcium traces and
deconvolved neural activities. Minian contains interactive visualization tools for every step of the
analysis, as well as detailed documentation and tips on parameter exploration. Furthermore,
Minian has relatively small memory demands and can be run on a laptop, making it available to
labs that do not have access to specialized computational hardware. Minian has been validated
to reliably and robustly extract calcium events across different brain regions and from different
cell types. In practice, Minian provides an open-source calcium imaging analysis pipeline with
user-friendly interactive visualizations to explore parameters and validate results.

Introduction

Overview of related works

Open-source projects—hardware, software, training curricula—have changed science and
enabled significant advances across multiple disciplines. Neuroscience, in particular, has
benefitted tremendously from the open-source movement. Numerous open-source projects
have emerged [1,2], including various types of behavioral apparatus facilitating the design of
novel experiments [3,4,5,6,7], computational tools enabling the analysis of large scale datasets
[8,9,10,11,12,13,14,15,16,17,18,19,20,21], and recording devices allowing access to large
populations of neurons in the brain [22,23,24,25,26,27,28,29,30,31]. Miniature microscopy has
been an area of particular importance for the open-source movement in neuroscience. To
increase the usability, accessibility, and transparency of this remarkable technology originally
developed by Schnitzer and colleagues [32,33], a number of labs innovated on top of the
original versions with open-source versions [26,27,28,29,30,31]. The UCLA Miniscope project, a
user-friendly miniature head-mounted microscope for *in vivo* calcium imaging in freely behaving
animals, is one such project that has been accessible to a large number of users [22,34,35,36].

With the increasing popularity of miniature microscopes, there is a growing need for analysis
pipelines that can reliably extract neuronal activities from recording data. To address this need,
numerous algorithms have been developed and made available to the neuroscience community.
The principal component analysis or independent component analysis (PCA-ICA)-based
approach [13], and region-of-interest (ROI)-based approach [34] were among the earliest

algorithms that reliably detected the locations of neurons and extract their overall activities
across pixels. However, one of the limitations of these approaches is that activities from cells
that are spatially overlapping cannot be demixed. A subsequent constrained non-negative
matrix factorization (CNMF) approach was shown to reliably extract neuronal activity from both
two-photon and single-photon calcium imaging data [37], and demix the activities of overlapping
cells. The CNMF algorithm models the video as a product of a 'spatial' matrix containing
detected neuronal footprints (locations of cells) and a 'temporal' matrix containing the temporal
calcium traces of each detected cell. This approach is particularly effective at addressing
crosstalk between neurons, which is of particular concern in single-photon imaging, where the
fluorescence from overlapping or nearby cells contaminates each other. Moreover, by
deconvolving calcium traces, the CNMF algorithm enables a closer exploration of the underlying
activity of interest, action potentials [19,38]. Originally developed for two-photon data, the CNMF
algorithm did not include an explicit model of the out-of-focus fluorescence which is often
present in single-photon miniature microscope recordings. This issue was addressed via the
CNMF-E algorithm [11], where a ring-model is used as a background term to account for out-of-
focus fluorescence. Later, an open-source python pipeline for calcium imaging analysis,
CaImAn, was published, which included both the CNMF and CNMF-E algorithms, as well as
many other functionalities [16]. The latest development in analysis pipelines for *in vivo* miniature
microscope data is MIN1PIPE [12], where a morphological operation is used to
remove background fluorescence during pre-processing of the data, and a seed-based
approach is used for initialization of the CNMF algorithm. Other approaches have also been
used to extract signals from calcium imaging data including an online approach [20], $\ell 0$-
penalization approach to infer spikes [14,21], robust modeling of noise [39], and source
detection using neural networks [15].

The open sharing of the algorithms necessary for the computation of neural activity has been
exceptionally important for the field. However, implementation of these tools can be complex as
many algorithms have numerous free parameters (those that must be set by the user) that can
influence the outcomes, without clear guidance on how these parameters should be set or to
what extent they affect results. Moreover, there is a lack of ground-truth data for *in*
vivo miniature microscope imaging, making it hard to validate algorithms and/or parameters.
Together, these obstacles make it challenging for neuroscience labs to adopt the analysis
pipelines, since it is difficult for researchers to adjust parameters to fit their data, or to trust the
output of the pipeline for downstream analysis. Thus, the next challenge in open-source
analysis pipelines for calcium imaging is to make the analysis tools more user-friendly and
underlying algorithms more accessible to neuroscience researchers so that they can more
easily understand the pipeline and interpret the results.

Contributions of Minian

To increase the accessibility of the mathematical algorithms, transparency into how altering
parameters alters the data output, and usability for researchers with limited computational
resources and experience, we developed Minian, an open-source analysis pipeline for single-
photon calcium imaging data inspired by previously published algorithms. We based Minian on
the CNMF algorithm [16,37], but also leverage methods from other pipelines, including those
originally published by Cai et al. [34] and MIN1PIPE [12]. To enhance compatibility with different
types of hardware, especially laptops or personal desktop computers, we implemented an

approach that supports parallel and out-of-core computation (i.e., computation on data that are
too large to fit a computer's memory). We then developed interactive visualizations for every
step in Minian and integrated these steps into annotated Jupyter Notebooks as an interface for
the pipeline. We have included detailed notes and discussions on how to adjust the parameters
from within the notebook and have included all free parameters in the code for additional
flexibility. The interactive visualizations will help users to intuitively understand and visually
inspect the effect of each parameter, which we hope will facilitate more usability, transparency,
and reliability in calcium imaging analysis.

Minian contributes to three key aspects of calcium image data analysis:

1. **Visualization.** For each step in the pipeline, Minian provides visualizations of inputs and
results. Thus, users can proceed step-by-step with an understanding of how the data are
transformed and processed. In addition, all visualizations are interactive and support
simultaneous visualization of the results obtained with different parameters. This feature
provides users with knowledge about the corresponding outcome for each parameter
value, and allow the users to choose the outcome that fits best with their expectation.
Hence, the visualizations also facilitate parameter exploration for each step, which is
especially valuable when analyzing data from heterogeneous origins that may vary by brain
region, cell type, species, and the extent of viral transfection.

2. **Memory demand.** One of the most significant barriers in adopting calcium imaging
pipelines is the memory demand of algorithms. The recorded imaging data usually take up
tens of gigabytes of space when converted to floating-point datatypes and often cannot fit
into the RAM of standard computers without spatially and/or temporally down-sampling.
CaImAn [16] addresses this issue by splitting the data into overlapping patches of pixels,
processing each patch independently, and merging the results together. This enables out-
of-core computation since at any given time only subsets of data are needed and loaded
into memory. In Minian, we extend this concept further by flexibly splitting the data either
spatially (split into patches of pixels) or temporally (split into chunks of frames). In this way,
we avoid the need to merge the results based on overlapping parts. The result is a pipeline
that supports out-of-core computation at each step, which gives nearly constant memory
demand with respect to input data size. Minian can process more than 20min of recording
(approximately 12.6 GB of raw data) with 8GB of memory, which makes Minian suitable to
be deployed on modern personal laptops.

3. **Accessibility.** Minian is an open-source Python package. In addition to the codebase,
Minian distributes several Jupyter Notebooks that integrate explanatory text with code and
interactive visualizations of results. For each step in the notebook, detailed instructions, as
well as intuition about the underlying mathematical formulation are provided, along with
code, which can be directly executed from within the notebook. Upon running a piece of
code within the notebook visualizations appear directly below. In this way, the notebooks
serve as a complement to traditional API documentations of each function. In addition,
users can easily rearrange and modify the pipeline notebook to suit their needs without
diving into the codebase and modifying the underlying functions. The notebooks distributed
by Minian can simultaneously function as a user guide, template, and production tool. We
believe the inclusion of these notebooks, in combination with Minian's other unique

features, can increase understanding of the underlying functioning of the algorithms and
greatly improve the accessibility of miniature microscopy analysis pipelines.

Paper organization

The paper is organized as follows: Since Minian's major contribution is usability and
accessibility, we first present the detailed steps in the analysis pipeline in Materials and
Methods section. Following a step-by-step description of the algorithms Minian adopted from
existing works, we present novel visualizations of the results, as well as how users can utilize
these visualizations. In the Results section, we benchmark Minian across two brain regions and
show that spatial footprints and the temporal activity of cells can be reliably extracted. We also
show that the cells extracted by Minian in hippocampal CA1 exhibit stable spatial firing
properties consistent with the existing literature.

Materials and Methods

Here, we present a detailed description of Minian. We begin with an overview of the Minian
pipeline. Then, we provide an explanation of each step, along with the visualizations. Lastly, we
provide information regarding hardware and dependencies.

Overview of Minian

Minian comprises five major stages, as shown in Figure 1. Raw videos are first passed into a
pre-processing stage. During pre-processing, the background caused by vignetting (in which the
central portion of the field of view is brighter) is corrected by subtracting a minimum projection of
the movie across time. Sensor noise, evident as granular specks, is then corrected with a
median filter. Finally, background fluorescence is corrected by the morphological process
introduced in MIN1PIPE [12]. The pre-processed video is then motion-corrected with a standard
template-matching algorithm based on cross-correlation between each frame and a reference
frame [40]. The motion-corrected and pre-processed video then serves as the input to
initialization and CNMF algorithms. The seed-based initialization procedure looks for local
maxima in max projections of different subsets of frames and then generates an over-complete
set of seeds, which are candidate pixels for detected neurons. Because this process is likely to
produce many false positives, seeds are then further refined based on various metrics, including
the amplitude of temporal fluctuations and the signal-to-noise ratio of temporal signals. The
seeds are transformed into an initial estimation of cells' spatial footprints based on the
correlation of neighboring pixels with each seed pixel, and the initial temporal traces are in turn
estimated based on the weighted temporal signal of spatial footprints. Finally, the processed
video, initial spatial matrix, and temporal matrix are fed into the CNMF algorithm. The CNMF
algorithm first refines the spatial footprints of the cells (spatial update). The algorithm then
denoises the temporal traces of each cell while simultaneously deconvolving the calcium trace
into estimated 'spikes' (temporal update). CNMF spatial and temporal updates are performed
iteratively and can be repeated until a satisfactory result is reached through visual inspection.
Typically, this takes two cycles of spatial, followed by temporal, updates. Minian also includes a
demo dataset which allows the user to run and test the pipeline comprised of the pre-made
Jupyter Notebook immediately after installation.

*Figure 1: **Overview of the analysis pipeline.** The analysis is divided into five stages: Pre-*
processing, where sensor noise and background fluorescence from scattered light are removed;
Motion-correction, where rigid motion of the brain is corrected; Seeds-initialization, where the
initial spatial and temporal matrices for later steps are generated from a seed-based approach;
Spatial update, where the spatial footprints of cells are further refined; Temporal update, where
the temporal signals of cells are further refined. The last two steps of the pipeline are iterative
and can be repeated multiple times until a satisfactory result is reached.

Setting up

The first section in the pipeline includes house-keeping scripts to import packages and
functions, defining parameters, and setting up parallel computation and visualization. Most
notably, the distributed cluster that carries out all computations in Minian are set up in this
section. By default, the cluster runs locally with multi-core CPUs, however it can be easily
scaled up to run on distributed computers. The computation in Minian is optimized such that in
most cases the memory demand for each process/core can be as low as 2GB. However, in
some cases depending on the hardware, the state of operating system and data locality, Minian
might need more than 2GB per process to run. If a memory error (KilledWorker) is encountered,
it is common for users to increase the memory limit of the distributed cluster to get around the
error. Regardless of the exact memory limit per process, the total memory usage of Minian
roughly scales linearly with the number of parallel processes. The number of parallel processes
and memory usage of Minian are completely limited and managed by the cluster configuration
allowing users to easily change them to suit their needs.

Pre-processing

Loading data and down-sampling

Currently Minian supports .avi movies, the default output from the UCLA Miniscopes, and .tif
stacks, the default output from Inscopix miniscopes. This functionality can be easily extended to
support more formats if desired. Users are required to organize their data so that each recording
session is contained in a single folder. Because Minian can extract relevant metadata from
folder nomenclature (e.g., animal name, group, date), we suggest organizing the video folders
based upon animal and other experiment-related groupings to facilitate the incorporation of
metadata into Minian output files.

Minian supports down-sampling on any of the three video dimensions (height, width, and
frames). Two down-sampling strategies are currently implemented: either sub-setting data on a
regular interval or calculating a mean for each interval. At this stage, users are required to
specify (1) the path to their data, (2) a pattern of file names to match all the videos to be
processed (e.g., all files containing 'msCam', a typical pattern resulting from Miniscope
recordings), (3) a Python dictionary specifying whether and how metadata should be pulled from
folder names, (4) another Python dictionary specifying whether and on which dimension down-
sampling should be carried out, and (5) the down-sampling strategy, if desired.

Once specified, the data can be immediately visualized through an interactive viewer, as shown
in Figure 2. Along with a player to visualize every frame in the video, the viewer also plots
summary values such as mean, maximum, or minimum fluorescence values across time. This
helps users to check their input data and potentially exclude any artifacts caused by technical
faults during experiments (e.g., dropped frames). Users can further subset data to exclude
specified frames, if necessary. Finally, restricting the analysis to a certain sub-region of the field
of view during specific steps could be beneficial. For example, if the video contains anchoring
artifacts resulting from dirt on the lenses, it is often better to avoid such regions during motion
correction. To facilitate this, the viewer provides a feature where users can draw an arbitrary
box within the field of view and have it recorded as a mask. This mask can be passed into later
motion correction steps to avoid the biases resulting from the artifacts.

*Figure 2: **Interactive visualization of raw input video.** One frame is shown in the central panel of the visualization which can be interactively updated with the player toolbar on the top. A histogram of fluorescence intensity of the current frame is shown on the right and will update in response to zooming in on the central frame. A line plot of summary values across time is shown on the bottom. Here the maximum, mean, and minimum fluorescence values are plotted. These summaries are useful in checking whether there are unexpected artifacts or gaps in the recording. Finally, the user can draw an arbitrary box in the central frame, and the position of this boxed region can be recorded and used as a mask during later steps. For example, during motion correction a sub-region of the data containing a stable landmark might provide better information on the motion.*

Vignetting correction

Single-photon miniature microscope data often suffer from a vignetting effect in which the central portion of the field of view appears brighter than the periphery. Vignetting is deleterious to subsequent processing steps and should be removed. We find that the effect can be easily extracted by taking the minimum fluorescence value across time for each pixel and subtracting this value from each frame, pixel-wise. One of the additional benefits of subtracting the minimum is that it preserves the raw video's linear scale.

The result of this step can be visualized with the same video viewer used in the previous step. In addition to visualizing a single video, the viewer can also show multiple videos side-by-side (e.g., the original video and the processed video), as shown in Figure 3. The

operation/visualization is carried out 'on-the-fly' upon request for each frame, and users do not
have to wait for the operation to finish on the whole video to view the results.

*Figure 3: **General visualization of pre-processing.** The same visualization of input video can*
be used to visualize the whole video before and after specific pre-processing steps side-by-side.
The effect of vignetting correction is visualized here. The image and accompanying histogram
on the left side show the original data; the data after vignetting correction are shown on the right
side. Any frame of the data can be selected with the player toolbar and histograms are
responsive to all updates in the image.

Denoising

Next, we correct for salt-and-pepper noise on each frame, which usually results from electronic
pixel noise. By default, we pass each frame through a median filter, which is generally
considered particularly effective at eliminating this type of noise, though other smoothing filters
like Gaussian filters and anisotropic filters can also be implemented. The critical parameter here
is the window size of the median filter. A window size that is too small will make the filter
ineffective at correcting outliers, while a window size that is too large will remove finer gradient
and edges that are much smaller than the window size, and can result in a failure to distinguish
between adjacent cells.

The effect of the window size can be checked with an interactive visualization tool used across
the pre-processing stage, as shown in Figure 4. Additionally, here we show an example of the
effect of window size on the resulting data in Figure 5. Users should see significantly reduced
amount of salt-and-pepper noise in the images, which should be made more obvious by the
contour plots. At the same time, users should keep the window size below the extent where
over-smoothing occurs. As a heuristic, the average cell radius in pixel units works well, since a
window of the same size as an average cell is unlikely to blend different cells together, while still
being able to adequately smooth the image.

*Figure 4: **Visualization of denoising.** Here, a single frame from the data is passed through the background removal and both the image and a contour plot are shown for the frame before and after the process. The contour plots show the iso-contour of 5 intensity levels spaced linearly across the full intensity range of the corresponding image. The plots are interactive and responsive to the slider of the window size on the right, thus the effect of different window sizes for denoising can be visualized.*

*Figure 5: **Effect of window size on denoising.** One example frame is chosen from the data, and the resulting images (top row) and contour plots (bottom row) are shown to demonstrate the effect of window size on denoising. Here, a window size of 11 (middle column) is appropriate while both smaller and larger window sizes result in artifacts.*

Morphological background removal

Next, we remove any remaining background presumably caused by out-of-focus and tissue
fluorescence. To accomplish this we estimate the background using a morphological opening
process first introduced for calcium imaging analysis in MIN1PIPE [12], which acts as a size
filter that removes cell bodies. The morphological opening is composed of two stages: erosion
followed by dilation. In morphological erosion the image is passed through a filter where each
pixel will be substituted by the minimum value within the filter window. The effect of this process
is that any bright 'feature' that is smaller than the filter window will be 'eroded' away. Then the
dilation process accomplishes the reverse by substituting each pixel with the maximum value in
the window, which 'dilates' small bright features to the extent of the filter window size. The
combined effect of these two stages is that any bright 'feature' that is smaller than the filter
window is removed from the image. If we choose the window size to match the expected cell
diameter, performing a morphological opening will likely remove cells and provide a good
estimation of background. Hence, each frame is passed through the morphological opening
operation and the resulting image is subtracted from the original frame.

Although the window size parameter for the morphological opening can be pre-determined by
the expected cell diameter, it is helpful to visually inspect the effect of morphological
background removal. The effect of different window sizes can be visualized with the same tool
used in denoising, as shown in Figure 6. Additionally, here we show an example of the effect of
window size on the resulting data in Figure 7. In this case, a window size of 20 pixels is
considered appropriate because the resulting cells are appropriately sized and sharply defined.
In contrast, a smaller window results in limiting both the size and intensity of the cells. On the
other hand, residual out-of-focus fluorescence becomes visible when the window size is set too
large.

*Figure 6: **Visualization of background removal.** Here, a single frame from the data is passed*
through background removal and both the image and a contour plot are shown for the frame
before and after the process. The plots are interactive and responsive to the slider of the
window size on the right, thus the effect of different window sizes for background removal can
be visualized.

*Figure 7: **Effect of window size on background removal.** One example frame is chosen from*
the data, and the resulting images (top row) and contour plots (bottom row) are shown to
demonstrate the effect of window size on background removal. The contour plots show the iso-
contour of 5 intensity levels spaced linearly across the full intensity range of the corresponding
image. Here a window size of 20 pixels (middle column) is appropriate while both smaller and
larger window sizes produce unsatisfactory results: a window size too small (left column)

artificially limits the size of cells, and a window size too large (right column) does not remove the
background effectively.

Motion correction

Estimate and apply translational shifts

We use a standard template-matching algorithm based on cross-correlation to estimate and
correct for translational shifts [40]. In practice, we found that this approach is sufficient to correct
for motion artifacts that could have a significant impact on the final outcome. Briefly, for a range
of possible shifts, a cross-correlation between each frame and a template frame is calculated.
The shift producing the largest cross-correlation is estimated to reflect the degree of movement
from the template and is corrected by applying a shift to the frame in that direction. We apply
this operation to the whole movie in a divide-and-conquer manner. We split the movie into
chunks of frames, within which we register both the first and last frame to the middle frame. We
then take the max projections of the three frames that have been registered in each chunk and
group every 3 chunks together and register them using the max projections as templates. After
the registration, the 3 chunks that have been registered are treated as a new single chunk and
we again take the max projection to use as a template for further registration. In this way, the
number of frames registered in each chunk keeps increasing in powers of three (3, 9, 27, 81
etc.), and we repeat this process recursively until all the frames are covered in a single chunk
and the whole movie is registered. Since the motion correction is usually carried out after
background removal, we essentially use cellular activity as landmarks for registration.
Sometimes this can be problematic when cellular activity is very sparse and different across two
chunks (for example, when only two different cells fired in two chunks), leading to false
estimation of shifts. To overcome this problem, every time shift is estimated using a max
projection from two chunks, we also estimate a shift with the two consecutive frames bordering
the chunks (that is, the last frame from the earlier chunk and the first frame from the latter
chunk). In most cases the shifts estimated with these two sets of templates should be close, in
which case we use the shifts estimated with the max projection as the final output. However,
when the two estimated shifts differ too much from each other, we use the shifts estimated with
consecutive frames as the final output. The reason we still favor using max projections in most
cases is that registering with consecutive frames can lead to very fast accumulation of error and
a slow drifting artifact in the estimated shifts. In practice, we find that such a process can
account for almost all motion in the brain, so currently we only implemented estimation of
translational shifts. If the user would like to take advantage of anatomical landmarks (such as
blood vessels) within the field of view and would like to implement motion correction before all
background subtraction steps have been performed, the pipeline can be easily modified to do
so. After the estimation of shifts, the shift in each direction is plotted across time and
visualization of the data before and after motion correction is displayed in Minian (see Figure 1,
top right).

Seed initialization

Generation of an over-complete set of seeds

The CNMF algorithm is a powerful approach to extract cells' spatial structure and corresponding
temporal activity. However, the algorithm requires an initial estimate of cell locations/activity,
which it then refines. We use a seed-based approach introduced in MIN1PIPE [12] to initialize
spatial and temporal matrices for CNMF. The first step is to generate an over-complete set of
seeds, representing the potential centroids of cells. We iteratively select a subset of frames,
compute a maximum projection for these frames, and find the local maxima on the projections.
This workflow is repeated multiple times and we take the union of all local maxima across
repetitions to obtain an over-complete set of seeds. In this way, we avoid missing cells that only
fire in short periods of time that might be masked by taking a maximum projection across the
whole video.

During seed initialization, the first critical parameter is the spatial window for defining local
maxima. Intuitively, this should be the expected diameter of cells. The other critical parameter is
an intensity threshold for a local maximum to be considered a seed. Since the spatial window
for local maxima is small relative to the field of view, a significant number of local maxima are
usually false positives and do not actually reflect the location of cells. Thresholding the
fluorescence intensity provides a simple way to filter out false local maxima, and usually a very
low value is enough to produce satisfactory results. We have found a value of 3 usually works
well (recall that the range of fluorescence intensity is usually 0-255 for unsigned 8-bit data). An
alternative strategy to thresholding the intensity is to model the distribution of fluorescence
fluctuations and keep the seeds with relatively higher fluctuations. This process is described
in Seeds refinement with a Gaussian-Mixture-Model, and is accessible if the user prefers explicit
modeling over thresholding.

Finally, the temporal sampling of frames for the maximum projections also impacts the result.
We provide two implementations here: either taking a rolling window of frames across time, or
randomly sampling frames for a user-defined number of iterations. For the rolling window
approach, users can specify a temporal window size (the number of successive frames for each
subset) and a step size (the interval between the start of subsets). For the random approach,
users can specify the number of frames in each subset and the total number of repetitions. We
use the rolling window approach as the default.

The resulting seeds are visualized on top of a maximum projection image (plot not shown).
Although the spatial window size of local maxima can be pre-determined, the parameters for
either the rolling window or random sampling of frames are hard to estimate intuitively. We
provide default parameters that generally provide robust results. However, the user is also free
to vary these parameters to obtain reasonable seeds. As long as the resulting seeds are not too
dense (populating almost every pixel) or too sparse (missing cells that are visible in the max
projection), subsequent steps can be performed efficiently and are fairly tolerable to the specific
ways the seeds are initialized.

Refinement with peak-to-noise ratio

Next, we refine the seeds by looking at what we call the peak-to-noise ratio of the temporal
traces and discard seeds with low peak-to-noise ratios. To compute this ratio, we first separate
the noise from the presumed real signal. Calcium dynamics are mainly composed of low
frequency fluctuations (from the slow kinetics of the calcium fluctuations) while noise is
composed of higher frequency fluctuations. Thus, to separate the noise from the calcium
dynamics we pass the fluorescence time trace of each seed through a low-pass and a high-
pass filter to obtain the 'signal' and 'noise' of each seed. We then compute the difference
between the maximum and minimum values (or peak-to-peak values) for both 'signal' and
'noise', and the ratio between the two difference values defines the peak-to-noise ratio. Finally,
we filter out seeds whose peak-to-noise value falls below a user-defined threshold.

The first critical parameter here is the cut-off frequency that separates 'signal' from 'noise'. This
parameter is also important for subsequent steps when implementing the CNMF algorithm. We
provide a visualization tool, shown in Figure 8, to help users determine cut-off frequency. In the
visualization, 6 seeds are randomly selected, and their corresponding 'signal' and 'noise' traces
are plotted. The user is then able to use a dynamic slider on the right side of the plots to adjust
the cut-off frequency and view the results. The goal is to select a frequency that best separates
signal from noise. A cut-off frequency that is too low will leave true calcium dynamics absorbed
in 'noise' (left panel in Figure 9), while a frequency that is too high will let 'noise' bleed into
'signal' (right panel in Figure 9). A suitable frequency is therefore the one where the 'signal'
captures all of the characteristics of the calcium indicator dynamics (i.e., large, fast rise, and
slow decay), while the 'noise' trace remains relatively uniform across time (middle panel in
Figure 9). The interactive plots make this easy to visualize. We also provide an example in
Figure 9 to show how cut-off frequency influences the separation of 'signal' from 'noise'. The
second parameter is the threshold of peak-to-noise ratio value. In practice, we have found a
threshold of 1 works well in most cases. An additional advantage of using 1 is that it reflects the
intuitive interpretation that fluctuations in a real 'signal' should be larger than fluctuations in
'noise'.

*Figure 8: **Visualization of noise frequency cut-off.** The cut-off frequency for noise is one of the critical parameters in the pipeline that affects both the seed initialization process and CNMF's temporal update steps. Here we help the user determine that parameter by plotting temporal traces from six example seeds. In each plot the raw signal is passed through a high-pass and low-pass filter at the chosen frequency, and the resulting signals are plotted separately as "noise" and "signal". The plots are responsive to the chosen frequency controlled by the slider on the right. In this way, the user can visually inspect whether the chosen frequency can effectively filter out high frequency noise without deforming the calcium signal.*

*Figure 9: **Example of filtered traces with different frequency cut-offs.** Here the temporal
dynamics of three example seeds are chosen, and the low-pass and high-pass filtered traces
with different frequency cut-offs are shown. The low-pass filtered trace corresponds to 'signal',
while the high-pass filtered trace corresponds to 'noise'. Here a 1 Hz cut-off frequency is
considered appropriate, since calcium dynamics and random noise are cleanly separated. A
cut-off frequency smaller than 1 Hz left the calcium dynamics in the 'noise' trace, while a cut-off
frequency larger than 1 Hz let random noise bleed into the 'signal' trace (i.e., high frequency
fluctuations are presented in periods where the cells seem to be inactive).*

Refinement with Kolmogorov-Smirnov tests

Finally, we refine the seeds with a Kolmogorov-Smirnov test. The Kolmogorov-Smirnov test
assesses the equality of two distributions and can be used to check whether the fluctuation of
values for each seed is non-normally distributed. We expect the noisy fluorescence values when
a cell is not firing to form a gaussian distribution with small mean value, and the fluorescence
values when a cell is firing should have a much higher mean value and frequency than expected
by the null gaussian distribution. Therefore, seeds corresponding to cells should be non-
normally distributed. We use a default significance threshold of 0.05. In some cases, this might
be too conservative or too liberal. Users can tweak this threshold or skip this step altogether
depending on the resulting seeds.

Merge seeds

There will usually be multiple seeds for a single cell and it is best to merge them whenever
possible. We implement two criteria for merging seeds: first, the distance between the seeds
must be below a given threshold, and second, the correlation coefficient of the temporal traces
between seeds must be higher than a given threshold. To avoid bias in the correlation due to
noise, we implement a smoothing operation on the traces before calculating the correlation. The
critical parameters are the distance threshold, the correlation threshold, and the cut-off

frequency for the smoothing operation. While the distance threshold is arbitrary and should be
explored, often the average radius of cells provides a good starting point. The cut-off frequency
should be the same as that used during the peak-to-noise-ratio refinement described above,
and the correlation should be relatively high (we typically use 0.8, but this can be refined by the
user). The resulting merged seeds can be visualized on the max projection. Since the main
purpose of this step is to alleviate computation demands for downstream steps, it is fine to have
multiple seeds for a single visually distinct cell. However, users should make sure each of the
visually distinct cells still has at least one corresponding seed after the merge.

Initialize spatial and temporal matrices from seeds

The last step before implementing CNMF is to initialize the spatial and temporal matrices for the
CNMF algorithm from the seeds. These matrices are generated with one dimension
representing each putative cell and the other representing each pixel or time, respectively. In
other words, the spatial matrix represents the spatial footprint for each cell at each pixel location
and the temporal matrix represents the temporal fluorescence value of each cell on each frame.
We assume each seed is the center of a potential cell, and we first calculate the spatial footprint
for each cell by taking the cosine similarity between the temporal trace of a seed and the pixels
surrounding that seed. In other words, we generate the weights in the spatial footprint by
computing how similar the temporal activities of each seed are to the surrounding pixels. Then,
we generate the temporal activities for each potential cell by taking the input video and
weighting the contribution of each pixel to the cell's temporal trace by the spatial footprint of the
cell. The final products are a spatial matrix and a temporal matrix.

Besides the two matrices representing neuronal signals, there are two additional terms in the
CNMF model that account for background fluorescence modeled as a spatial footprint for the
background and a temporal trace of background activity. To estimate these terms, we subtract
the matrix product of our spatial and temporal matrices, which represent cellular activities, from
the input data. We take the mean projection of this remainder across time as an estimation of
the spatial footprint of the background, and we take the mean fluorescence for each frame as
the temporal trace of the background.

Users can tweak two parameters to improve the outcome and performance of this step: a
threshold for cosine similarity and a spatial window identifying pixels on which to perform this
computation. To keep the resulting spatial matrix sparse and keep irrelevant pixels from
influencing the temporal traces of cells, we set a threshold for the cosine similarity of temporal
traces compared to the seed, where pixels whose similarity value falls below this threshold will
be set to zero in the spatial footprint of the cell. Cosine similarity is, in essence, a correlation
(the scale is 0-1) and thresholds of 0.5 and higher work well in practice. Computing many pair-
wise similarity measurements is computationally expensive, and it is unnecessary to compute
the similarities between pixels that are far apart because they are unlikely to have originated
from the same cell. We therefore set a window size to limit the number of pixel pairs to be
considered. This size should be set large enough so that it does not limit the size of spatial
footprints, but not unnecessarily large to the extent where it will impact performance. In practice,
a window size equal to the maximum expected cell diameter is reasonable.

CNMF

Estimate spatial noise

CNMF requires that we first estimate the spatial noise over time for each pixel in the input video.
The spatial noise of each pixel is simply the power of the high frequency signals in each pixel.
The critical parameter here is again the cut-off frequency for 'noise', and users should employ
the visualization tools as described above during peak-to-noise ratio refinement to determine
this frequency (see Refinement with peak-to-noise ratio).

Spatial update

Next, we proceed to the spatial update of the CNMF algorithm. The original paper describing
this algorithm [37] contains a detailed theoretical derivation of the model. Here, we provide only
a conceptual overview of the process so that users can understand the effect of each
parameter. The CNMF framework models the input video to be the product of the spatial and
temporal matrices representing signals contributed by real cells, a background term, and
random noise. In equation form, this is $\mathbf{Y} = \mathbf{AC} + \mathbf{B} + \mathbf{E}$, where $\mathbf{Y}$ represents the input video, $\mathbf{A}$
represents the spatial matrix containing the spatial footprints for all putative cells, $\mathbf{C}$ represents
the temporal matrix containing the calcium dynamics for all putative cells, $\mathbf{B}$ represents the
spatial-temporal fluctuation of background, and $\mathbf{E}$ represents error or noise. Since the full
problem of finding proper $\mathbf{A}$ and $\mathbf{C}$ matrices is hard (non-convex), we break down the full
process into spatial update and temporal update steps, where iterative updates of $\mathbf{A}$ and $\mathbf{C}$ are
carried out, respectively. Each iteration will improve on previous results and eventually converge
on the best estimation.

During the spatial update, given an estimation of the temporal matrix and the background term,
we seek to update the spatial matrix so that it best fits the input data, along with the
corresponding temporal traces. To do so, we first subtract the background term from the input
data so that the remainder is composed only of signals from cells and noise. Then, for each
pixel, the algorithm attempts to find the weights for each cell's spatial footprint that best
reproduces the input data ($\mathbf{Y}$) with the constraint that individual pixels should not weigh on too
many cells (controlled through what is called a sparseness penalty). To reduce computational
demand, we do this for each pixel independently and in parallel to improve performance, while
retaining the 'demixing' power of the CNMF algorithm by updating the weights for all cells
simultaneously. In the optimization process, the function to be minimized contains both
a squared error term to assess error, and an $\ell 1$-norm term to promote sparsity [16]. The
optimization process can be expressed formally as:

538
$$\underset{\mathbf{A},\mathbf{b}}{\text{minimize}} \quad \parallel \mathbf{Y}(p,:) - \mathbf{A}(p,:)\mathbf{C} - \mathbf{bf} \parallel + \lambda \parallel \mathbf{A}(p,:) \parallel_1$$
$$\text{subject to} \quad \mathbf{A}, \mathbf{b} \geq 0$$

Where $\mathbf{Y}(p,:)$ denotes the input movie data indexed at p-th pixel, $\mathbf{A}(p,:)$ denotes the spatial
matrix indexed at p-th pixel across all putative cells, and $\mathbf{C}$, $\mathbf{b}$, $\mathbf{f}$ denotes the temporal matrix, the
spatial footprint of background term, and the temporal fluctuation of background term,

respectively. The scalar λ represents the sparse penalty that controls the balance between the
error term and sparsity term.

Lastly, the spatial footprint of the background term is updated in the exact same way, together
with other putative cells. However, the background term the temporal activity used in the spatial
update is not constrained by the autoregressive model. After the spatial footprint of the
background term is updated, we subtract the neural activity ($\mathbf{AC}$) from the input data to get
residual background fluctuations. Then the temporal activity of background term is calculated as
the projection of residual onto the new background spatial footprint, where the raw activities of
each pixel is weighted by the spatial footprint.

In other CNMF implementations, the estimated spatial noise is used to determine the scaling of
the $\ell 1$-norm term in the target function and control the balance between error and sparsity of the
result. However, in practice we find that it does not always give the best result for all types of
datasets. For example, sometimes the estimated spatial noise is too large, which results in an
overly-conservative estimation of spatial footprints. Hence, we have introduced a sparseness
penalty on top of the estimated scaling factor for the $\ell 1$-norm term. This parameter gives users
more control over how sparsity should be weighted in the updating process. The higher the
number, the higher the penalty imposed by the $\ell 1$-norm, and the more sparse the spatial
footprints will become. The effect of this parameter can be visualized with the tool shown in
Figure 10. Users can employ this tool to determine the best sparseness penalty for their data,
where the binarized spatial footprint representing non-zero terms should approach the visible
part of the spatial footprint as much as possible, without reducing the amplitude of spatial
footprints to the extent that cells are discarded in the spatial update. Figure 11 shows an
example of the effect of changing the sparseness penalty on the resulting spatial footprints. A
sparseness penalty of 0.1 is considered appropriate in this case. When the sparseness penalty
is set much lower, many of the additional 'fragments' begin to appear in the binarized spatial
footprint, even if they are not part of the cell. On the other hand, when the sparseness penalty is
set too high, some cells are discarded. In the interactive visualization tool, users can inspect the
temporal dynamics of these discarded cells. In general, however, we do not recommend
exploiting the sparseness penalty during the spatial update to filter cells since this step does not
have an explicit model of the temporal signal and thus has no power to differentiate real cells
from noise.

In addition, a dilation window parameter must be specified by the user. To reduce the amount of
computation when calculating how each pixel weighs onto each cell, we only update weights for
cells that are close to each pixel. For each cell, an ROI is computed by performing a
morphological dilation process on the previous spatial footprints of that cell. If a pixel lies outside
of a cell's region of interest, this cell will not be considered when updating the pixel's weight.
Thus, the dilation window parameter determines the maximum distance a cell is allowed to grow
during the update compared to its previous spatial footprints. This parameter should be set large
enough so that it does not interfere with the spatial update process, but at the same time not so
large as to impact performance. The expected cell diameter in pixels is a good starting point.

Figure 10: **Visualization of spatial updates.** *Here 10 cells are randomly chosen to pass through spatial update with different parameters. The resulting spatial footprints, as well as binarized footprints, are plotted. In addition, the corresponding temporal traces of cells are plotted. The user can visually inspect the size and shape of the spatial footprints and at the same time easily determine whether the results are sparse enough by looking at the binarized footprints.*

Figure 11: **Effect of sparseness penalty in spatial update.** *Here the sum projection of the spatial matrix and binarized spatial matrix are shown for 3 different sparse penalties. A sparseness penalty of 0.1 is considered appropriate in this case. When the sparseness penalty is set lower, artifacts begin to appear. On the other hand, when the sparseness penalty is set higher, cells are dropped out.*

Temporal update

Next, we proceed to the temporal update of the CNMF algorithm. Please refer to the original
paper for the detailed derivation [37]. Here, given the spatial matrix and background terms,
we update the temporal matrix so that it best fits the input data ($\mathbf{Y}$). First, we subtract the
background term from the input data, leaving only the noisy signal from cells. We then project
the data onto the spatial footprints of cells, obtaining the temporal activity for each cell. Next we
estimate a contribution of temporal activity from neighboring overlapping cells using the spatial
footprints of cells, and subtract it from the temporal activity of each cell. This process results in a
two-dimensional matrix representing the raw temporal activity of each cell [41].

The CNMF algorithm models the relationship between the underlying 'spiking' and the calcium
dynamics of a cell as an auto-regressive (AR) process. It should be noted that although the
underlying process that drives calcium influx is presumably cell firing, the 'spiking' signal is
modeled as a continuous variable rather than a binary variable, and strictly speaking, it is only a
de-convolved calcium signal. Following convention, we will refer to this variable as 'spike signal',
an approximation of the underlying cellular activity that drives calcium influx. It should be
understood, however, that the exact relationship between this variable and the actual firing rate
of cells is unclear, since the absolute amount of fluorescence generated by a single spike, as
well as the numerical effect of integrating multiple spikes on the resulting calcium signal, is
unknown.

We first estimate the coefficients for the AR model. The coefficients of the AR model can be
conveniently estimated from the autocorrelation of the estimated temporal activity. In addition,
noise power for each cell is also estimated directly from the signal. In practice, we find that
during the estimation of the AR model parameters, it is helpful to first smooth the signal,
otherwise the time constant of the AR model tends to be biased by high frequency noise. Users
should again use the peak-to-noise-refinement cut-off frequency for both estimation of the noise
power and smoothing of the signals. Finally, we update the temporal matrix by minimizing a
target function for different cells, similar to what was done with the spatial matrix. Again, the
target function contains a squared error term and a $\ell 1$-norm term. We also introduce a
sparseness penalty parameter to control the balance between the two terms. The squared error
term contains the difference between input signal and estimated calcium dynamics, while
the $\ell 1$-norm term regulates the sparsity of the "spiking" signal. Pre-estimated AR coefficients
allow for a determined relationship between the 'spiking' signal and calcium dynamics for a
given cell. Thus, the problem can be transformed and simplified as minimizing the target
function over 'spiking' signals of different cells.

In practice, it is computationally more efficient to break down the minimization problem into
smaller pieces and update subsets of cells independently and in parallel. To do so, we first
identify non-overlapping cells using a Jaccard index, which measures the amount of overlap
between the spatial footprints of different cells. Once we identify these individual cells, we can
update them independently so that an optimization problem and target function are formulated
for each cell independently. Here, we set a cutoff Jaccard index where cells above this amount
of overlap are updated in parallel. During the updating process, two additional terms are
introduced: a baseline term to account for constitutive non-zero activity of cells and an initial
calcium concentration to account for a 'spiking' that started just prior to recording. The initial

calcium concentration term is a scalar that is recursively multiplied by the same AR coefficient
estimated for the cell. The resulting time trace, modeling the decay process of a 'spiking' event
prior to the recording, is added on top of the calcium trace. The baseline activity term is also a
scalar that is simply added on top of all the modeled signals. Both terms are often zero, but they
are nevertheless saved and visualized. For each cell, the optimization process can be
expressed formally as:

644
$$\underset{\mathbf{c},\mathbf{b_0},c_0}{\text{minimize}} \quad \| \mathbf{yra} - \mathbf{c} - b_0 - c_0\mathbf{d} \| + \lambda \| \mathbf{Gc} \|_1$$
$$\text{subject to} \quad \mathbf{c}, \mathbf{Gc} \geq 0$$

Where $\mathbf{yra}$ denotes the input movie data projected onto the spatial footprint of the given cell, $\mathbf{c}$
denotes the estimated calcium dynamic of the given cell, b_0 denotes the constant baseline
fluorescent activity, c_0 denotes the initial calcium concentration, G represent a matrix of AR
coefficients such that $\mathbf{Gc}$ is the estimated 'spike' signal, $\mathbf{d}$ is a vector representing the temporal
decay of a single spike based on the estimated AR coefficients, such that the term $c_0\mathbf{d}$
represent the contribution of initial calcium concentration. Similar to spatial update, the scalar λ
represents the sparse penalty and controls the balance between the error term and sparsity
term.

The $\ell 1$-norm in the optimization problem is known to reduce not only the number of non-zero
terms (i.e., promotes sparsity), but also the amplitude/value of non-zero terms. This effect is
unwanted, since in some cases the numerical the spatial update step in CNMF algorithm
andvalue of the resulting 'spike' signal can become too small as a side-effect of promoting
sparsity, making it hard to interpret and compare the 'spike' signal for downstream analysis. To
counteract this phenomenon, we introduce a *post hoc* scaling process. After the temporal
update, each cell is assigned a scaling factor to scale all the fitted signals to the appropriate
values. The scaling factor is solved by least square minimizing the error between the fitted
calcium signal and the projected raw signal.

The critical parameters in temporal updates are as follows: (1) The order of the AR model,
usually 1 or 2. Users should choose 1 if near-instantaneous rise time is presented in the calcium
dynamics of the input data (i.e., from the relatively slow sampling rate) and should choose 2
otherwise. (2) The cut-off frequency for noise used for both noise power estimation and pre-
smoothing of the data during AR coefficients estimation. Users should use the values set during
peak-to-noise ratio refinement. (3) The threshold for the Jaccard index determining which cells
can be updated independently. Users should use a value as low as possible, as long as the
speed of this step is acceptable (with large amounts of cells packed closely together, a low
threshold may dramatically slow down this step), or visually inspect how sparse the spatial
footprints are and determine what amount of overlap between spatial footprints results in
significant crosstalk between cells. (4) The sparseness penalty is best set through visualization
tools. The effect of any parameter on the temporal update can be visualized through the tool
shown in Figure 12, where the result of the temporal update for 10 randomly selected cells are
plotted as traces. There are a total of 4 traces shown for each cell: the calcium signal, the
deconvolved 'spiking' signal, the projected raw signal, and the 'fitted signal'. The 'fitted signal' is
very similar to the calcium signal and is often indistinguishable from the latter. The difference
between them is that the 'fitted signal' also includes the baseline term and the initial calcium

concentration term. Hence, the 'fitted signal' should better follow the projected raw signal, but it may be less interesting for downstream analysis. Toggling between different parameters triggers the dynamic update of the plots, helping the user to determine the best parameters for their data. Additionally, we highlight the effect of the sparseness penalty on resulting fitted calcium signals and spike signals in Figure 13. The effect is most evident in the 'fitted spikes' trace, which corresponds to the spike signal and can arguably be interpreted as a measure of the underlying neural activity per frame scaled by an unknown scalar. Here, a sparseness penalty of 0.008 is considered most appropriate. A lower sparseness penalty will introduce many false positive signals which do not correspond to real calcium dynamics, as can be seen in the plots. On the other hand, too high a sparseness penalty will produce false negatives where clear rises in the raw signal are not accompanied by spikes.

*Figure 12: **Visualization of temporal update.** Here, a subset of cells is randomly chosen to pass through temporal updates with different parameters. Only one cell is visualized at a given time and the cell can be selected using the slider on the right. The raw signal, the fitted signal, the fitted calcium traces, and the spike signals are overlaid in the same plot. In addition, a simulated pulse-response based on the estimated auto-regressive parameters is plotted with the same time scale. Furthermore, the corresponding spatial footprint of the cell is plotted for cross-reference. With a given set of parameters, the user can visually inspect whether the pulse-response captures the typical calcium dynamics of the cell, and whether the timing and sparsity of the spike signal fit well with the raw data. The data shown here was acquired with a framerate of 30 fps.*

*Figure 13: **Effect of the sparseness penalty in temporal update.** Here, 3 example cells are*
selected and passed to the temporal update with different sparseness penalties. The "Raw
Signal" corresponds to the input video projected onto predetermined spatial footprints. The
"Fitted Calcium" and "Fitted Spikes" correspond to the resulting model-fitted calcium dynamics
and spike signals. A sparseness penalty of 0.008 (middle column) is considered appropriate in
this case. The data shown here was acquired with a framerate of 30 fps.

Merging cells

The CNMF algorithm can sometimes misclassify a single cell as multiple cells. To counteract
this phenomenon, we implement a step to merge cells based on their proximity and temporal
activity. All cells with spatial footprints sharing at least one pixel are considered candidates for
merging, and the pair-wise correlation of their temporal activity is computed. Users can then
specify a threshold where cell pairs with activity correlations above the threshold are merged.
Merging is done by taking the sum of the respective spatial footprints and the mean of all of the
temporal traces for all cells to be merged. Since this is only a simple way to correct for the
number of estimated cells and does not fit numerically with what the model CNMF assumes,
merging is only done between iterations of CNMF, but not at the end.

Manual curation

Minian provides an interactive visualization to help the users manually inspect the quality of
putative cells and potentially merge or drop cells. At any given time, the visualization shows
spatial temporal activities (top row, middle panel in Figure 14) and temporal dynamics of a
selected subset of cells (bottom row in Figure 14). The spatial temporal activities are shown side
by side with the spatial footprints of all cells and the pre-processed movie (input to CNMF
algorithm) at a given frame (top row of Figure 14). The field of view is synchronized across the

three images on the top, so that the users can easily zoom in and compare the estimated spatial
footprints of cells to the input data. The spatial temporal images in the middle show the product
of spatial footprints and calcium dynamics, which represent the model estimated image of a
subset of cells at a given frame. This spatial temporal product is calculated on-the-fly and
synchronized with the frame indicators on the temporal dynamic plots. In this way users can
easily pick times of interest (for example, when a cell has a calcium event), and validate
whether the estimated spatial temporal activities match the input data. Lastly, this interactive
visualization allows the user to either drop false positive cells or merge multiple cells together
via dropdown menus. The result of manual curation is saved as an array with a label for each
unit indicating whether a cell should be discarded or how several cells should be merged. In this
way, only the new label is saved and no data is modified, allowing the user to repeat or correct
the manual curation process if needed.

Figure 14: ***Interactive visualization of Minian output.*** *The three images on the top show the*
spatial footprints of all the cells (left), the spatial temporal activities of selected subset of cells
(middle), and the pre-processed data. The bottom row shows the display control panel (left), the
temporal dynamics of selected subset of cells (middle), and the manual curation panel (right).
The field of view, current frame, and selection of cells are all synced across different plots to
help user focus on a specific region and time. The users can use the control panel to select
groups of cells, change display options for temporal dynamics and spatial temporal activities,
change the current frame or play the movie. In addition, the users can directly select cells from
the spatial footprints plot on the top left. The users can also directly jump to frames by double-
clicking on the temporal dynamic plots. These interactive features help the users quickly focus
on region and time of interests. The manual curation menu on bottom right can be used to
assign unit labels to each cell, which indicate whether a cell should be dropped or merged.

Cross registration

After completing the analysis of individual recording sessions, users can register cells across
sessions. While more complex approaches are proposed in other pipelines [16,17], here, our
intention is simplicity. To account for shifts in the field of view from one session to the next, we
first align the field of view from each session based upon a summary frame. Users can either
choose a max projection of each pre-processed and motion-corrected video, or a summed
projection of the spatial footprints of all cells. Users can also choose which session should be
used as the template for registration, to which every other session should be aligned. We use a
standard cross-correlation based on a template-matching algorithm to estimate the translational
shifts for each session relative to the template and then correct for this shift. The weighted
centroid of each cell's spatial footprint is then calculated and pair-wise centroid distances are
used to cross-register cells. A distance threshold (maximum pixel distance) is set. Users should
choose this threshold carefully to reflect the maximum expected displacement of cells across
sessions after registration. We found that a threshold of 5 pixels works well. Finally, a pair of
cells must be the closest cells to each other in order to be considered the same cell across
sessions.

To extend this method to more than two sessions, we first cross-register all possible session
pairs. We then take the union of all these pair-wise results and transitively extend the cross-
registration across more than two sessions. At the same time, we discard all matches that result
in conflicts. For example, if cell A in the first session is matched with cell B in the second
session, and cell B is in turn matched with cell C in the third session, but cells A and C are not
matched when directly registering the first and third sessions, all of these matches are
discarded and all three cells are treated as individual cells. We recognize that this approach
might be overly conservative. However, we believe that this strategy provides an easy-to-
interpret result that does not require users to make decisions about whether to accept cell pairs
that could conflict across sessions.

To save computation time, we implement a moving window where centroid distances are only
calculated for cell pairs within these windows. Users should set the size of windows to be much
larger than the expected size of cells.

Hardware and dependencies

Minian has been tested using OSX, Linux, and Windows operating systems. Additionally,
although we routinely use Minian on specialized analysis computers, the pipeline works on
personal laptops for many common length (~30min) miniature microscope experiments.
Specifications of all of the computers that have been tested can be found in Tested hardware
specifications. We anticipate that any computer with at least 16GB of memory will be capable of
processing at least 20 minutes of recording data, although increased memory and CPU power
will speed up processing. Moreover, due to the read-write processes involved in out-of-core
computation, we recommend that the videos to be processed are held locally at the time of
analysis, preferably on a solid-state drive. The relatively slow speed of transfer via ethernet
cables, Wi-Fi, or USB cables to external drives will severely impair analysis times.

Minian is built on top of project Jupyter [42], and depends heavily on packages provided by the
open-source community, including numpy [43], scipy [44], xarray [45], holoviews [46],
bokeh [47], opencv [48], and dask [49]. A complete list of direct dependencies for Minian can be
found in List of dependencies. Of note, the provided install instructions handle the installation of
all dependencies.

Results

To validate the accuracy as well as benchmark the performance of Minian, we ran the Minian
pipeline on a series of simulated and experimental datasets and compare the output and
performance to those obtained with CaImAn, which is one of most widely-adopted calcium
imaging analysis pipeline in the field. In addition, we also validated the full workflow of Minian by
applying the pipeline to several recordings of animals running on a linear track and looked at the
stability of place cells. These results are presented in sections below.

Validation with simulated datasets

We first validated Minian with simulated datasets. We synthesized different datasets with
varying number of cells and signal levels based on existing works [11,12]. The simulated
datasets contain local background fluctuations, noise, and motions similar to experimental
datasets (See Generation of simulated datasets for details). The field of view contains 512 x 512
pixels and 20000 frames, corresponding to roughly 10 minutes of recording at 30 fps. We
processed the data with both Minian and CaImAn. For Minian, we utilized the visualization
described here to optimize the parameters. For CaImAn, we used the same parameters as
Minian whenever the implementations were equivalent. Otherwise, we followed the suggested
parameters and tweaked them based on the knowledge of simulated ground truth.

To compare the results objectively, we first matched the resulting putative cells from the output
of Minian or CaImAn to the simulated ground truth (See Matching neurons for validation for
details). We then calculated three metrics to measure the quality of output: F1 score, spatial
footprints correlation, and temporal dynamics correlation. The F1 score is defined as the
harmonic mean of precision (proportion of detected neurons that are true) and recall (proportion
of ground truth neurons that has been detected). Hence the F1 score measures the overall
accuracy of neuron detection. For each detected neuron that has been matched to ground truth,
we compute Pearson correlation between the estimated and ground truth spatial footprint, as
well as the Pearson correlation between the estimated calcium dynamic and the ground truth
calcium dynamic. We then take the median correlation across all the matched neurons to
measure the overall quality of estimated spatial footprints and temporal dynamics.

As shown in Figure 15, both Minian and CaImAn achieve similar and near perfect levels (> 0.95)
of F1 score across all conditions. Similarly, the spatial footprints remain nearly perfect (> 0.95)
for both pipelines across all conditions. At the lowest signal level (0.2), both pipelines suffer from
decreased correlation of temporal dynamics. This is likely due to noise and background
contaminating the true signal. Overall, these results show that the Minian and CaImAn pipelines
perform similarly well in terms of output accuracy on simulated datasets.

Additionally, we want to validate the deconvolved signal from Minian output, since this is usually
the most important output for downstream analysis. Our ground truth spikes are simulated as
binary signals. However, in reality calcium activity often reflect the integration of several spikes,
and the deconvolved signals from Minian output are real-valued. Because of this, we down-
sampled both the ground truth spikes and deconvolved signals by 5 times, and then calculated
Pearson correlation for all matched cells. The resulting correlation is summarized in Figure 16
A. Our results indicate that the deconvolved output from Minian is highly similar to ground truth
spikes when signal level is high, and the correlation asymptote and approach 1 when signal
level is higher than 1. The lower correlation corresponding to low signal level is likely due to the

background and noise contamination being stronger than signal. In line with this idea, the
detected "spikes" from the deconvolved signals closely match those from ground truth, as
shown by the example traces in Figure 16 B. The main difference between the two traces is the
amplitude of the deconvolved signals, which is prone to be influenced by local background and
noise. Overall, these results suggest that Minian can produce deconvolved signals that are
faithful to ground truth and suitable for downstream analysis.

*Figure 16: **Validation of deconvolved signal from Minian. (A)** Correlation of deconvolved*
signals from Minian output with simulated ground truth. The mean correlation across all cells
(blue line) and the standard deviation (light blue shade) are shown separately for different signal
levels and number of cells. The correlation asymptote and approach 1 when signal level is
*higher than 1. **(B)** Example deconvolved traces from Minian output overlaid with simulated*
ground truth. One representative cell is drawn from each signal level. The binary simulated
spikes are shown in green, with the real-valued Minian deconvolved output overlaid on top in
blue. The deconvolved signals closely match the ground truth and the main difference between

the two signals is in the amplitude of the deconvolved signals, which tend to be influenced by
local background.

Validation with experimental datasets

We next validated Minian with experimental datasets. The data was collected from hippocampal
CA1 regions in animals performing a spatial navigation task. 6 animals with different density of
cells were included in the validation dataset. The recordings are collected with 608 x 608 pixels
at 30 fps and lasts 20 min (~36000 frames). Due to difficulties in obtaining ground truth for
experimental data, we choose to validate Minian with CaImAn, which has been established as
one of the most accurate existing pipelines. To evaluate the results objectively, we matched
resulting ROIs from Minian with those from CaImAn using the same approach as in the
Validation with simulated datasets section. We then calculated correlation of spatial footprints
and temporal activity between matched ROIs from the two pipelines. Across the 6 datasets, the
mean F1 score is 0.73 (sem +/-0.03). The mean spatial footprints correlation is 0.84 (sem +/-
0.02), and the mean temporal activity correlation is 0.86 (sem +/-0.02). An example field of view
and temporal activity from matched ROIs are shown in Figure 17. Our results indicate that most
of the ROIs detected by Minian and CaImAn correspond to the same population of putative
cells, and the resulting spatial footprints and temporal activity are nearly identical. These cells
tend to cluster near the center of the field of view, which usually have better signal-to-noise
ratio. However, the cells near the edge of the field of view usually have low intensity and spatial
consistency due to the optical property of GRIN lens. As a consequence, Minian and CaImAn
might detect different population of cells near the border of field of view, due to differences in
pre-processing and initialization between the two pipelines. We have chosen to use the same
set of parameters across all datasets so that the results are easier to interpret, hence the
parameters we used were relatively conservative. In practice, the users can further fine-tune the
parameters for each recording so that Minian would be able to capture all the low signal cells in
the field of view. Overall, these results suggest that the output of Minian is highly similar to
CaImAn when analyzing experimental datasets.

A

B

30 sec

Figure 17: **Example output of Minian and CalmAn with experimental datasets. (A)** *An*
example field-of-view from one of the experimental datasets. The spatial footprints from Minian
and CalmAn are colored as blue and red respectively, and overlaid on top of each other. Most
of the spatial footprints from both pipelines overlap with each other. **(B)** *5 example matched*
temporal activity from Minian and CalmAn overlaid on top of each other. The extracted temporal
activity are highly similar across the two pipelines.

Benchmarking computational performance

To see how the performance of Minian scales with different input data size, we synthesized
datasets with varying number of cells and number of frames (recording length). The field of view
contains 512 x 512 pixels (same as those used in validation of accuracy), and the signal level
was held constant at 1 to make sure both Minian and CaImAn can detect roughly equal number
of neurons during the pipeline. To this end, we tracked two metrics of performance: the total
running time of the pipeline and the peak memory usage during running. The running time was
obtained by querying operating system time during the pipeline. The memory usage was
tracked with an independent process that queries memory usage of the pipeline from the
operating system on a 0.5 seconds interval. Both pipelines were set to utilize 4 parallel
processes during the run across all conditions. All benchmarking are carried out on a custom-
built linux machine (Model "Carbon" under Tested hardware specifications)

As shown in Figure 18, the run time of both Minian and CaImAn scales linearly as a function of
input recording length. The exact running times vary depending on number of cells as well as
whether visualization is included in the processing, but in general the running time is similar
across both pipelines. On the other hand, the peak memory usage of CaImAn scales linearly
with recording length when the number of parallel processes was set to be constant. At the
same time, the peak memory usage of Minian stays mostly constant across increasing number
of frames. This is likely due to the flexible chunking implementation of Minian (See Parallel and
out-of-core computation with dask), where Minian was able to break down computations into
chunks in both the spatial and the temporal dimensions depending on which way is more
efficient. In contrast, CaImAn only splits data into different spatial chunks (patches), resulting in
a linear scaling of memory usage with recording length for each chunk-wise computation.
Additionally, we run Minian and CaImAn with different number of parallel processes on the
simulated dataset with 28000 frames and 500 cells. As expected, with more parallel processes
the performance improves and the run time decreases but at the same time the total peak
memory usage increases. The tradeoff between run time and peak memory usage are shown in
Figure 19. In conclusion, these results show that in practice, Minian is able to perform as fast as
CaImAn, while maintaining near constant memory usage regardless of input data size. This
allows the users to process much longer recordings with limited RAM resources.

*Figure 18: **Benchmarking of computational performance.** Data with varying number of cells and frames were processed through Minian and CaImAn. The run time (top) and peak memory usage (bottom) were recorded and plotted as a function of frame number. For both pipelines, the run time scales linearly as a function of the number of frames and remains similar across the pipelines. However, the peak memory usage for CaImAn also scales linearly as the number of frames increases, while Minian maintains a relatively constant peak memory usage across different frame numbers and cell numbers.*

*Figure 19: **Tradeoff between run time and memory usage.** Simulated data with 500 cells and 28000 frames were processed through Minian and CaImAn with different numbers of parallel processes. We varied the number of parallel processes from 2 to 10, and the resulting memory usage is plotted as a function of run time. For both pipelines, the curve takes a hyperbola shape, showing the tradeoff between run time and memory usage.*

Validation with hippocampal CA1 place cells

In addition to direct validation of the output for single session, we wanted to validate the scientific significance of the spike signal, as well as the quality of the cross-session registration, and ensure that Minian is capable of generating meaningful results consistent with the existing

literature. We leveraged the extensively documented properties of place cells in rodent
hippocampal CA1 [50]. Place cells have been shown to have consistent place fields across at
least two days [33,51] with only a minority of detected cells undergoing place field remapping.
Here, we looked at place field stability across two linear track sessions (Figure 20 A). Briefly,
animals were trained to run back and forth on a 2 m linear track while wearing a Miniscope to
obtain water rewards available at either end [35]. The time gap between each session was 2
days. We record calcium activity in dorsal CA1 region with a FOV of 480 x 752 pixels collected
at 30 fps. Each recording session lasts 15 min (~27000 frames). Calcium imaging data were
analyzed with Minian, while the location of animals was extracted with an open-source
behavioral analysis pipeline ezTrack [18]. The resulting calcium dynamics and animal behavior
were aligned with the timestamps recorded by Miniscope data acquisition software
(miniscope.org). We used the spike signal for our downstream analysis. To calculate average
spatial activity rate, we binned the 2-meters long track into 100 spatial bins. In addition,
we separated the epochs when the animals are running in opposite directions, resulting in a
total of 200 spatial bins. We then smoothed both the binned activity rate and animal's
occupancy with a Gaussian kernel with a standard deviation of 5 cm. We classified place cells
based on three criteria: a spatial information criterion, a stability criterion, and a place field size
criterion [35]. (See Classification of place cells for more detail.) Finally, we analyzed cells that
are cross-registered by Minian and are classified as place cells in both sessions. We then
calculated the Pearson correlation for the average spatial firing rate for each cross-registered
cell. We found that, on average, place cells have a correlation of ~0.6, which is consistent with
the existing literature [35].

Next, we validated the cross-session registration to verify that the correct cells were being
matched across days. We translated the spatial footprints of the second session in both
directions up to 50 pixels and registered the cells with the shifted spatial footprints. We then
carried out the same analysis with the registration results from shifted spatial footprints. We
found that the average correlations between spatial firing patterns have higher values when the
shifts are close to zero (Figure 20 B).

In conclusion, Minian can reliably process *in vivo* calcium imaging data and produce results that
are in agreement with the known properties of rodent CA1. Minian can thus help neuroscience
labs easily implement and select the best parameters for their calcium analysis pipeline by
providing detailed instructions and visualizations.

*Figure 20: **Validation of Minian with hippocampal CA1 place cells. (A)** Matching place cells from two recording sessions. The cells are matched from one session to the other using the cross-session registration algorithm and sorted based on place field in the first session. In both sessions, animals run on a 2-meter-long linear track with water reward at both ends. The track is divided into 200 spatial bins. The mean "firing" rate calculated from the spike signal for each cell is shown. Cell IDs are assigned by Minian when each session is analyzed independently.*
***(B)** Averaged correlations of spatial firing rates with different artificial shifts. We artificially shifted the spatial footprints of the second linear track session, then carried out registration and calculated a mean correlation of spatial firing rates for all place cells. The artificial shifts were relative to the aligned spatial footprints and range from -50 to 50 pixels.*

Discussion

Making open science more accessible

Neuroscience has benefitted tremendously from open-source projects, ranging from do-it-yourself (DIY) hardware [1] to sophisticated algorithms [2]. Open-source projects are impactful because they make cutting-edge technologies available to neuroscience labs with limited resources, as well as opening the door for innovation on top of previously established methods. We believe that openly sharing knowledge and tools is just the first step. Making knowledge accessible even to non-experts should be one of the ultimate goals of open-source projects.

With the increasing popularity of miniaturized microscopes [36], there has been significant interest in analysis pipelines that can reliably extract neural activities from the data. Numerous algorithms have been developed to solve this problem [11,13,15,19,20,37], and many of them are implemented as open-source packages that can function as a one-stop pipeline [12,14,16]. However, one of the biggest obstacles for neuroscience labs in adopting analysis pipelines is the difficulty in understanding the exact operation of the algorithms, leading to two notable challenges: first, researchers face difficulties adjusting the parameters when the data they have collected are out of the expected scope of the pipeline's default parameters. Second, even after neural activity data is obtained, it is hard for researchers to be sure that they have chosen the best approaches and parameters for their dataset. Indeed, it has been found that depending on the features of the data and the metric used, more sophisticated algorithms do not always out-perform simpler algorithms [52], making it even harder for researchers to interpret the results obtained from some analysis pipelines. Researchers therefore often have to outsource data analysis to experts with strong computational backgrounds or simply trust the output of the algorithms being used. Minian was created to address these challenges. By providing not only detailed documentation of all functions, but also by providing rich interactive visualizations, Minian helps researchers to develop an intuitive understanding of the operations of algorithms without expertise in mathematics or computer science. These insights help researchers choose the best parameters, as well as to become more confident in their interpretation of results. Furthermore, transparency regarding the underlying algorithms enables researchers to develop in-house modifications of the pipeline, which is a common practice in neuroscience labs. We believe that Minian will contribute to the open science community by making the analysis of calcium imaging data more accessible and understandable to neuroscience labs.

Limitations

Although Minian provides users with insights into the parameter tuning process across different brain regions, these insights are achieved mainly through visual inspection. However, the performance of an analysis pipeline should be measured objectively. While calcium imaging has been validated with electrophysiology under *ex vivo* settings [53], ground-truth data for single-photon *in vivo* calcium imaging are lacking, making objective evaluation of the algorithms difficult. Therefore, here we have provided only indirect validations of the pipeline by recapitulating well-established biological findings.

 Supplemental information

 Parallel and out-of-core computation with dask

In Minian, we use a modern parallel computing library called dask to implement parallel and out-
of-core computation. Dask divides the data into small chunks along all dimensions, then flexibly
merges the data along some dimensions in each step. We leverage the fact that each step in
our pipeline can be carried out chunk by chunk independently along either the temporal (frame)
dimension or the spatial (height and width) dimensions, thus requiring no interpolation or special
handling of borders when merged together, producing results as if no chunking had been done.
For example, motion correction and most pre-processing steps that involve frame-wise filtering
can be carried out on independent temporal chunks, whereas computation of pixel correlations
can be carried out on independent spatial chunks. Similarly, during the core CNMF computation
steps, spatial chunking can be used during update of spatial footprints, since spatial update is
carried out pixel by pixel. Meanwhile, temporal chunking can be used when projecting the input
data onto spatial footprints of cells, which is usually the most memory-demanding step.
Although the optimization step during the temporal update is computed across all frames and no
temporal chunking can be used, we can still chunk across cells, and in practice the memory
demand in this step is much smaller comparing to other steps involving raw input data.
Consequently, our pipeline fully supports out-of-core computation, and memory demand is
dramatically reduced. In practice, a modern laptop can easily handle the analysis of a full
experiment with a typical recording length of up to 20 minutes. Dask also enables us to carry out
lazy evaluation of many steps where the computation is postponed until the result is needed, for
example, when a plot of the result is requested. This enables selective evaluation of operations
only on the subset of data that will become part of the visualization and thus helps users to
quickly explore a large space of parameters without committing to the full operation each time.

 Seeds refinement with a Gaussian-Mixture-Model

As described in the main text, an alternative strategy to thresholding fluorescence intensity
during seeds initialization is to explicitly model the distribution of fluorescence fluctuations of all
candidate seeds and select those with relatively higher fluctuation. Here, we describe this
process and the rationale. Since the seeds are generated from local maxima, they include noise
from relatively empty regions with no actual cells. The seeds from these regions usually have
low fluctuations in fluorescence across time and can be classified as spurious. To identify these
cases, we compute a range of fluctuation for each seed (range of min-max across time), and
model these ranges with a Gaussian-Mixture-Model of two components. The fluctuations from
'noise' seeds compose a Gaussian distribution with low fluctuation, while seeds from actual cells
assume a higher degree of fluctuation and form another Gaussian distribution with a higher
mean. Any seed whose fluctuations belong to the lower Gaussian distribution is discarded in
this step. To compute the range of fluctuation for each seed, we compute the difference
between the 99.9 and 0.1 percentile of all fluorescence values across time, which is less biased
by outliers than the actual maximum and minimum values.

Normally, this step is parameter-free. In rare cases, there are regions containing noise while
other regions are almost completely dark. Thus, seeds from these two regions will form two
peaks in the distribution of what the user would consider 'bad seeds', and a Gaussian-Mixture-

Model with two components will no longer be valid. In such cases users can tweak the number
of components (number of modeled Gaussian distributions), as well as the number of
components to be considered as composed of real signal. However, because the two noise
distributions are likely to overlap to some degree, using two components will likely suffice. The
distribution of fluctuations, the Gaussian-Mixture-Model fit, and the resulting seeds, are
visualized, enabling the user to judge the appropriateness and accuracy of this step. It should
be noted that in practice, we have found this process to depend heavily on the relative
proportion of the 'good' and 'bad' seeds and can easily result in a significant amount of false
negatives if the proportion of the 'bad' seed is too low. This makes the Gaussian-Mixture-Model
approach less stable and in general less preferable to simple thresholding unless a good
threshold of fluorescence intensity cannot be easily determined.

Generation of simulated datasets

We use a pipeline modified from [11] and [12] to generate simulated data for validation and
benchmarking of Minian. Specifically, we generate a 512 x 512 pixels field of view with varying
number of frames and neurons. The neurons are simulated as spherical 2-D Gaussian. The
center of neurons are drawn uniformly from the whole field of view, and the Gaussian widths σ_x
and σ_y for each neuron are drawn from $\mathcal{N}(15, 5^2)$, with a minimum value of 3. Spikes are
simulated from a Bernoulli process with a 0.01 probability of spiking per frame. Calcium
dynamics are simulated by convolving the spikes with a temporal kernel $g(t) = exp(-t/\tau_d) -$
$exp(-t/\tau_r)$, with rise time $\tau_r = 5$ frame and decay time $\tau_d = 60$ frame. We simulate the spatial
footprints of backgrounds as spherical 2-D Gaussian distributed uniformly across field of view.
In total 300 independent background terms are used for all simulation. The Gaussian widths are
drawn from $\mathcal{N}(900, 50^2)$ The temporal dynamic of backgrounds are simulated from a
constrained Gaussian random walk process with steps drawn from $\mathcal{N}(0, 2^2)$, then clipped to be
non-negative and gaussian smoothed temporally with a variance of 60 frames. We also simulate
motion of the field of view as 2-D translations. The translational shift in each direction is
simulated from a constrained Gaussian random walk process with steps drawn from
$\mathcal{N}(-0.2d, 1)$, where d is the current amount of shift. Lastly, we add a $\mathcal{N}(0, 0.1^2)$ Gaussian noise
to the entire simulated data. The activity of neurons are multiplied by a scalar before combining
with the background activity and noise. We call this scalar 'signal level'.

To validate the accuracy of Minian output, we simulate data with different signal level and
number of cells. The signal levels we use are 0.2, 0.4, 0.6, 1.0, 1.4, 1.8. The number of cells we
use are 100, 300, 500. On the other hand, to benchmark the performance of Minian, we
simulate data with different number of frames and cells. The number of frames vary from 4000
to 28000 with a step size of 8000. The number of cells we use are 100, 300, 500.

Matching neurons for validation

To compute different metrics of the accuracy of Minian output, we first need to match the
putative neurons from Minian output with neurons from ground truth. To obtain this mapping we
first compute the max projection of spatial footprints across all neurons. We then register the
max projection of putative spatial footprints to the max projection of ground truth spatial
footprints, by estimating a translational shift between the two max projection images. After
correcting for translational shifts, we compute the center-of-mass for all neurons, from which we

obtain a N x M pairwise distance matrix, where N and M are number of neurons detected by
Minian and number of ground truth neurons, respectively. We then calculate an optimal
mapping by solving the linear assignment problem of minimizing the total cost (distance) of a
particular cell mapping. Lastly, we threshold the resulting mapping by discarding any matched
cells that has a distance larger than 15 pixels.

Classification of place cells

We use the spatially-binned averaged 'firing' rate calculated from spike signals to classify
whether each cell is a place cell. A place cell must simultaneously satisfy three criteria: a spatial
information criterion, a stability criterion, and a place field size criterion. To determine whether a
cell has significant spatial information or stability, we obtain a null distribution of the
measurements (spatial information and stability) with a bootstrap strategy, where we roll the
timing of activity by a random amount for each cell 1000 times. The observed spatial information
or stability is defined as significant if it exceeds the 95th percentile of its null distribution ($p <$
0.05). For the spatial information criterion, we use the joint information between 'firing' rate and
an animal's location measured in bits per 'spike'. For the stability criterion, we calculate the
Fisher z-transformation of the Pearson correlation coefficient between spatial 'firing' patterns
across different trials within a recording session. A trial is defined as the time which the animal
runs from one end of the linear track to the other and returns to the starting location. We
calculate the z-transformed correlation between the odd number of trials and the even number
of trials, as well as between the first half of the trials and the second half of the trials. We then
average these two measures of correlations and use that as the measure of stability for a cell.
Lastly, For the place field size criterion, we define the place field of each cell as the longest
contiguous spatial bin where the averaged 'firing' rate exceeded the 95th percentile of all
averaged firing rate bins. A cell must have a place field larger than 4 cm (i.e., 2 spatial bins) to
pass the place field size criterion.

Animals

Adult male C57/BL6J mice from Jackson Laboratories were used for all testing. Animals were
housed in a temperature, humidity and light controlled vivarium down the hall from the
experimental testing rooms with lights on at 7 a.m. and off at 7 p.m. Water was restricted to
maintain a body weight of 85–90%. Water deprivation consisted of allotting the animal ~1 mL of
water per day, including water obtained during testing. Water not obtained during testing was
given after the testing period. Animals were acclimated to handling for 5–7 days prior to
training/testing. All experiments were performed in accordance with relevant guidelines and
regulations approved by the Institutional Animal Care and Use Committee of Icahn School of
Medicine at Mount Sinai (Reference #: IACUC-2017-0361, Protocol #: 17-1994).

Tested hardware specifications

1145 The hardware specifications of computers that have effectively run Minian are summarized in
1146 the table below.

1147 *Table 1: **A list of computers tested with Minian with specifications.** Listed roughly by*
1148 *increasing computation power.*

Manufacture	Model	CPU	RAM	Storage	Operating System
custom-built	Carbon	AMD Ryzen Threadripper 2950X 4.4GHz x 16	128GB	2TB SSD	Ubuntu 18.04
Microsoft	Surface Pro 6	Intel Core i5-8250U 1.6GHz x 4	8GB	256GB SSD	Windows 10
Dell	Precision 5530	Intel Core i5-8400H 2.5GHz x 4	16GB	256GB SSD	Ubuntu 18.04
Apple	MacBook Pro 152	Intel Core i7-8559U 2.7GHz x 4	16GB	1TB SSD	macOS 10.14 Mojave
custom-built	Amethyst	Intel Xeon E5-1650 3.6GHz x 6	128GB	6TB HDD	Ubuntu 17.1

1149 *List of dependencies*

1150 *Table 2: **A list of open-source packages and the specific versions on which Minian***
1151 *depends.*

Package	Version
av	7.0
bokeh	1.4
bottleneck	1.3
cairo	1.16
cvxpy	1.0
dask	2.11
datashader	0.1
distributed	2.11
ecos	2.0
ffmpeg	4.1
fftw	3.3
holoviews	1.12
ipython	7.12
ipywidgets	7.5
jupyter	1.0
matplotlib	3.1
natsort	7.0
netcdf4	1.5
networkx	2.4
nodejs	13.9
numba	0.48

numpy	1.18
opencv	4.2
pandas	1.0
panel	0.8
papermill	2.0
param	1.9
pip	20.0
pyfftw	0.12
python	3.8
scipy	1.4
scs	2.1
statsmodels	0.11
tifffile	2020.2
tqdm	4.43
xarray	0.15
zarr	2.4
medpy	0.4
simpleitk	1.2

1152 *Comparison of algorithms in related pipelines*

1153 *Table 3: **List of algorithm implementations in different pipelines.** For a lot of steps different*
1154 *algorithm implementation can be chosen by the user based on features of the data. In such*
1155 *cases we only list the default and most commonly used algorithms here.*

Step	Minian implementation	CalmAn implementation	MIN1PIPE implementation	Critical parameters
Denoising	Median filter	None	Anistropic filter	Spatial window size of the filter
Background removal	Morphological top-hat transform	None	Morphological top-hat transform	Spatial window size of the top-hat transform
Motion correction	FFT-based translational motion correction	Non-rigid patch-wise translational motion correction (NoRMCorre)	Mix of translational motion correction and Demons diffeomorphic motion correction	Different
Initialization	Seed-based with peak-noise-ratio and KS-test refinement	Pixel-wise correlation and peak-noise-ratio thresholding	Seed-based with GMM, peak-noise-ratio and KS-test refinement	Threshold for correlation and peak-noise-ratio
Spatial and temporal updates	CNMF with cvxpy as deconvolution backend	CNMF-E with oasis as deconvolution backend	CNMF with cvx matlab package as deconvolution	Noise cut-off frequency. Expected size of

			backend	neurons. Sparse penalty

1156   *Source data*

1157   *Table 4:* **List of source data related to validation figures.**

Title	Description
Figure 15 - source data 1	Raw validation performance with simulated data.
Figure 16 - source data 1	Raw correlations between Minian deconvolved traces and simulated ground truth.
Figure 16 - source data 2	Raw example traces from Minian and simulated ground truth. Filenames indicate signal level and source of trace.
Figure 17 - source data 1	Raw spatial footprint values shown in the overlay plot.
Figure 17 - source data 2	Raw example traces from Minian and Caiman. Filenames indicate cell id and source of trace.
Figure 18 - source data 1	Raw memory usage and running time with different datasets for both pipelines.
Figure 19 - source data 1	Raw memory usage and running time with different parallel processes for both pipelines.
Figure 20 - source data 1	Raw correlation of spatial firing pattern with different shifts in field-of-view.
Figure 20 - source data 2	Raw spatial firing activity for the two sessions shown.

1158

Conflict of interest

The authors declare that they have no competing financial interests.

Funding

NIH F32AG067640

•   William Mau

NIH BRAIN Initiative (R01 EB028166)

•   Kanaka Rajan

James S. McDonnell Foundation's Understanding Human Cognition Scholar Award

•   Kanaka Rajan

NSF FOUNDATIONS Award (NSF1926800)

•   Kanaka Rajan

CURE Epilepsy Taking Flight Award

•   Tristan Shuman

American Epilepsy Society Junior investigator Award

•   Tristan Shuman

R03 NS111493

•   Tristan Shuman

R21 DA049568

•   Tristan Shuman

R01 NS116357

•   Tristan Shuman

U01 NS094286-01

•   Daniel Aharoni

1700408 Neurotech Hub

•   Daniel Aharoni

NIH DP2MH122399

• Denise J. Cai

R01 MH120162

• Denise J. Cai

Botanical Center Pilot Award from P50 AT008661-01 from the NCCIH and the ODS (Pasinetti
PI)

• Denise J. Cai

One Mind Otsuka Rising Star Award

• Denise J. Cai

McKnight Memory and Cognitive Disorders Award

• Denise J. Cai

Klingenstein-Simons Fellowship Award in Neuroscience

• Denise J. Cai

Mount Sinai Distinguished Scholar Award

• Denise J. Cai

Brain Research Foundation Award

• Denise J. Cai

NARSAD Young Investigator Award

• Denise J. Cai

Acknowledgements

We thank Eftychios A Pnevmatikakis, Andrea Giovannucci, and Liam Paninski for establishing
the theoretical foundation and providing helpful insights for the pipeline. We thank Pat Gunn for
helping with benchmarking with CaImAn pipeline. We thank Taylor Francisco and Denisse
Morales-Rodriguez for helping with data analysis and revision. We thank MetaCell (Stephen
Larson, Giovanni Idili, Zoran Sinnema, Dan Knudsen, and Paolo Bazzigaluppi) for contributing
to the documentation and continuous integration of the pipeline. We thank Brandon Wei, Mimi
La-Vu, and Christopher Lee for contributing to the dataset used in Minian development and
testing. The authors acknowledge support from following funding sources: WM is supported by
NIH F32AG067640. KR is supported by NIH BRAIN Initiative (R01 EB028166), James S.
McDonnell Foundation's Understanding Human Cognition Scholar Award, and NSF

FOUNDATIONS Award (NSF1926800). TS is supported by CURE Epilepsy Taking Flight
Award, American Epilepsy Society Junior investigator Award, R03 NS111493, R21 DA049568,
and R01 NS116357. DA is supported by U01 NS094286-01, and 1700408 Neurotech Hub. DJC
is supported by NIH DP2MH122399, R01 MH120162, Botanical Center Pilot Award from P50
AT008661-01 from the NCCIH and the ODS (Pasinetti PI), One Mind Otsuka Rising Star Award,
McKnight Memory and Cognitive Disorders Award, Klingenstein-Simons Fellowship Award in
Neuroscience, Mount Sinai Distinguished Scholar Award, Brain Research Foundation Award,
and NARSAD Young Investigator Award.

References

1. **The Future Is Open: Open-Source Tools for Behavioral Neuroscience Research**
Samantha R. White, Linda M. Amarante, Alexxai V. Kravitz, Mark Laubach
eneuro (2019-07) https://doi.org/ggcmcv
DOI: 10.1523/eneuro.0223-19.2019 · PMID: 31358510 · PMCID: PMC6712209

2. **Open source tools for large-scale neuroscience**
Jeremy Freeman
Current Opinion in Neurobiology (2015-06) https://doi.org/ghqn37
DOI: 10.1016/j.conb.2015.04.002 · PMID: 25982977

3. **Open source modules for tracking animal behavior and closed-loop stimulation based
on Open Ephys and Bonsai**
Alessio Paolo Buccino, Mikkel Elle Lepperød, Svenn-Arne Dragly, Philipp Häfliger, Marianne
Fyhn, Torkel Hafting
Journal of Neural Engineering (2018-10-01) https://doi.org/ggp3mh
DOI: 10.1088/1741-2552/aacf45 · PMID: 29946057

4. **An open source automated two-bottle choice test apparatus for rats**
Jude A. Frie, Jibran Y. Khokhar
HardwareX (2019-04) https://doi.org/ghr3cd
DOI: 10.1016/j.ohx.2019.e00061 · PMID: 31245655 · PMCID: PMC6594565

5. **Bonsai: an event-based framework for processing and controlling data streams**
Gonçalo Lopes, Niccolò Bonacchi, João Frazão, Joana P. Neto, Bassam V. Atallah, Sofia
Soares, Luís Moreira, Sara Matias, Pavel M. Itskov, Patrícia A. Correia, … Adam R. Kampff
Frontiers in Neuroinformatics (2015-04-08) https://doi.org/ggbj87
DOI: 10.3389/fninf.2015.00007 · PMID: 25904861 · PMCID: PMC4389726

6. **Feeding Experimentation Device (FED): A flexible open-source device for measuring
feeding behavior**
Katrina P. Nguyen, Timothy J. O'Neal, Olurotimi A. Bolonduro, Elecia White, Alexxai V. Kravitz
Journal of Neuroscience Methods (2016-07) https://doi.org/f8rcmm
DOI: 10.1016/j.jneumeth.2016.04.003 · PMID: 27060385 · PMCID: PMC4884551

7. **An open-source device for measuring food intake and operant behavior in rodent
home-cages**

Bridget A Matikainen-Ankney, Thomas Earnest, Mohamed Ali, Eric Casey, Justin G Wang, Amy
K Sutton, Alex A Legaria, Kia M Barclay, Laura B Murdaugh, Makenzie R Norris, … Alexxai V
Kravitz
eLife (2021-03-29) https://doi.org/gj6mqj
DOI: 10.7554/elife.66173 · PMID: 33779547 · PMCID: PMC8075584

8. **JAABA: interactive machine learning for automatic annotation of animal behavior**
Mayank Kabra, Alice A Robie, Marta Rivera-Alba, Steven Branson, Kristin Branson
Nature Methods (2013-01) https://doi.org/gg66kh
DOI: 10.1038/nmeth.2281 · PMID: 23202433

9. **DeepLabCut: markerless pose estimation of user-defined body parts with deep
learning**
Alexander Mathis, Pranav Mamidanna, Kevin M. Cury, Taiga Abe, Venkatesh N. Murthy,
Mackenzie Weygandt Mathis, Matthias Bethge
Nature Neuroscience (2018-09) https://doi.org/gd249k
DOI: 10.1038/s41593-018-0209-y · PMID: 30127430

10. **Automated classification of self-grooming in mice using open-source software**
Bastijn J. G. van den Boom, Pavlina Pavlidi, Casper J. H. Wolf, Adriana H. Mooij, Ingo Willuhn
Journal of Neuroscience Methods (2017-09) https://doi.org/gb2wxk
DOI: 10.1016/j.jneumeth.2017.05.026 · PMID: 28648717

11. **Efficient and accurate extraction of in vivo calcium signals from microendoscopic
video data**
Pengcheng Zhou, Shanna L Resendez, Jose Rodriguez-Romaguera, Jessica C Jimenez, Shay
Q Neufeld, Andrea Giovannucci, Johannes Friedrich, Eftychios A Pnevmatikakis, Garret D
Stuber, Rene Hen, … Liam Paninski
eLife (2018-02-22) https://doi.org/gfxbdp
DOI: 10.7554/elife.28728 · PMID: 29469809 · PMCID: PMC5871355

12. **MIN1PIPE: A Miniscope 1-Photon-Based Calcium Imaging Signal Extraction Pipeline**
Jinghao Lu, Chunyuan Li, Jonnathan Singh-Alvarado, Zhe Charles Zhou, Flavio Fröhlich,
Richard Mooney, Fan Wang
Cell Reports (2018-06) https://doi.org/gdpc2z
DOI: 10.1016/j.celrep.2018.05.062 · PMID: 29925007 · PMCID: PMC6084484

13. **Automated Analysis of Cellular Signals from Large-Scale Calcium Imaging Data**
Eran A. Mukamel, Axel Nimmerjahn, Mark J. Schnitzer
Neuron (2009-09) https://doi.org/bhwqvc
DOI: 10.1016/j.neuron.2009.08.009 · PMID: 19778505 · PMCID: PMC3282191

14. **Suite2p: beyond 10,000 neurons with standard two-photon microscopy**
Marius Pachitariu, Carsen Stringer, Mario Dipoppa, Sylvia Schröder, L. Federico Rossi, Henry
Dalgleish, Matteo Carandini, Kenneth D. Harris
Cold Spring Harbor Laboratory (2017-07-20) https://doi.org/ggdxxm
DOI: 10.1101/061507

15. **Fast, Simple Calcium Imaging Segmentation with Fully Convolutional Networks**
Aleksander Klibisz, Derek Rose, Matthew Eicholtz, Jay Blundon, Stanislav Zakharenko
Lecture Notes in Computer Science (2017) https://doi.org/ghm58x
DOI: 10.1007/978-3-319-67558-9_33

16. **CalmAn an open source tool for scalable calcium imaging data analysis**
Andrea Giovannucci, Johannes Friedrich, Pat Gunn, Jérémie Kalfon, Brandon L Brown, Sue
Ann Koay, Jiannis Taxidis, Farzaneh Najafi, Jeffrey L Gauthier, Pengcheng Zhou, … Eftychios
A Pnevmatikakis
eLife (2019-01-17) https://doi.org/gf4v82
DOI: 10.7554/elife.38173 · PMID: 30652683 · PMCID: PMC6342523

17. **Tracking the Same Neurons across Multiple Days in Ca2+ Imaging Data**
Liron Sheintuch, Alon Rubin, Noa Brande-Eilat, Nitzan Geva, Noa Sadeh, Or Pinchasof, Yaniv
Ziv
Cell Reports (2017-10) https://doi.org/ghdnqz
DOI: 10.1016/j.celrep.2017.10.013 · PMID: 29069591 · PMCID: PMC5670033

18. **ezTrack: An open-source video analysis pipeline for the investigation of animal**
behavior
Zachary T. Pennington, Zhe Dong, Yu Feng, Lauren M. Vetere, Lucia Page-Harley, Tristan
Shuman, Denise J. Cai
Scientific Reports (2019-12-27) https://doi.org/ghm6dp
DOI: 10.1038/s41598-019-56408-9 · PMID: 31882950 · PMCID: PMC6934800

19. **Fast online deconvolution of calcium imaging data**
Johannes Friedrich, Pengcheng Zhou, Liam Paninski
PLOS Computational Biology (2017-03-14) https://doi.org/f9tsn9
DOI: 10.1371/journal.pcbi.1005423 · PMID: 28291787 · PMCID: PMC5370160

20. **OnACID: Online Analysis of Calcium Imaging Data in Real Time***
Andrea Giovannucci, Johannes Friedrich, Matt Kaufman, Anne Churchland, Dmitri Chklovskii,
Liam Paninski, Eftychios A. Pnevmatikakis
Cold Spring Harbor Laboratory (2017-10-02) https://doi.org/ghqn38
DOI: 10.1101/193383

21. **Exact spike train inference via ℓ_{0} optimization**
Sean Jewell, Daniela Witten
The Annals of Applied Statistics (2018-12-01) https://doi.org/ghm589
DOI: 10.1214/18-aoas1162 · PMID: 30627301 · PMCID: PMC6322847

22. **All the light that we can see: a new era in miniaturized microscopy**
Daniel Aharoni, Baljit S. Khakh, Alcino J. Silva, Peyman Golshani
Nature Methods (2019-01) https://doi.org/ghdnvz
DOI: 10.1038/s41592-018-0266-x · PMID: 30573833 · PMCID: PMC8320687

23. **An open-source control system for in vivo fluorescence measurements from deep-brain structures**
Scott F. Owen, Anatol C. Kreitzer
Journal of Neuroscience Methods (2019-01) https://doi.org/ghvk8p
DOI: 10.1016/j.jneumeth.2018.10.022 · PMID: 30342106 · PMCID: PMC6258340

24. **Open Ephys: an open-source, plugin-based platform for multichannel electrophysiology**
Joshua H Siegle, Aarón Cuevas López, Yogi A Patel, Kirill Abramov, Shay Ohayon, Jakob Voigts
Journal of Neural Engineering (2017-08-01) https://doi.org/gfvmzq
DOI: 10.1088/1741-2552/aa5eea · PMID: 28169219

25. **Open Source Tools for Temporally Controlled Rodent Behavior Suitable for Electrophysiology and Optogenetic Manipulations**
Nicola Solari, Katalin Sviatkó, Tamás Laszlovszky, Panna Hegedüs, Balázs Hangya
Frontiers in Systems Neuroscience (2018-05-15) https://doi.org/gdns24
DOI: 10.3389/fnsys.2018.00018 · PMID: 29867383 · PMCID: PMC5962774

26. **A wireless miniScope for deep brain imaging in freely moving mice**
Giovanni Barbera, Bo Liang, Lifeng Zhang, Yun Li, Da-Ting Lin
Journal of Neuroscience Methods (2019-07) https://doi.org/ghtkfs
DOI: 10.1016/j.jneumeth.2019.05.008 · PMID: 31116963 · PMCID: PMC6636826

27. **A Compact Head-Mounted Endoscope for In Vivo Calcium Imaging in Freely Behaving Mice**
Alexander D. Jacob, Adam I. Ramsaran, Andrew J. Mocle, Lina M. Tran, Chen Yan, Paul W. Frankland, Sheena A. Josselyn
Current Protocols in Neuroscience (2018-07) https://doi.org/gdr76d
DOI: 10.1002/cpns.51 · PMID: 29944206

28. **An open source, wireless capable miniature microscope system**
William A Liberti, L Nathan Perkins, Daniel P Leman, Timothy J Gardner
Journal of Neural Engineering (2017-08-01) https://doi.org/gf73sj
DOI: 10.1088/1741-2552/aa6806 · PMID: 28514229 · PMCID: PMC5955387

29. **NINscope, a versatile miniscope for multi-region circuit investigations**
Andres de Groot, Bastijn JG van den Boom, Romano M van Genderen, Joris Coppens, John van Veldhuijzen, Joop Bos, Hugo Hoedemaker, Mario Negrello, Ingo Willuhn, Chris I De Zeeuw, Tycho M Hoogland
eLife (2020-01-14) https://doi.org/ghsb8m
DOI: 10.7554/elife.49987 · PMID: 31934857 · PMCID: PMC6989121

30. **High-speed volumetric imaging of neuronal activity in freely moving rodents**
Oliver Skocek, Tobias Nöbauer, Lukas Weilguny, Francisca Martínez Traub, Chuying Naomi Xia, Maxim I. Molodtsov, Abhinav Grama, Masahito Yamagata, Daniel Aharoni, David D. Cox, … Alipasha Vaziri

Nature Methods (2018-06) https://doi.org/gf2n7z
DOI: 10.1038/s41592-018-0008-0 · PMID: 29736000 · PMCID: PMC7990085

31. **Imaging Cortical Dynamics in GCaMP Transgenic Rats with a Head-Mounted Widefield Macroscope**
Benjamin B. Scott, Stephan Y. Thiberge, Caiying Guo, D. Gowanlock R. Tervo, Carlos D. Brody, Alla Y. Karpova, David W. Tank
Neuron (2018-12) https://doi.org/gfgk25
DOI: 10.1016/j.neuron.2018.09.050 · PMID: 30482694 · PMCID: PMC6283673

32. **Miniaturized integration of a fluorescence microscope**
Kunal K Ghosh, Laurie D Burns, Eric D Cocker, Axel Nimmerjahn, Yaniv Ziv, Abbas El Gamal, Mark J Schnitzer
Nature Methods (2011-10) https://doi.org/cv75qh
DOI: 10.1038/nmeth.1694 · PMID: 21909102 · PMCID: PMC3810311

33. **Long-term dynamics of CA1 hippocampal place codes**
Yaniv Ziv, Laurie D Burns, Eric D Cocker, Elizabeth O Hamel, Kunal K Ghosh, Lacey J Kitch, Abbas El Gamal, Mark J Schnitzer
Nature Neuroscience (2013-02-10) https://doi.org/gdh98h
DOI: 10.1038/nn.3329 · PMID: 23396101 · PMCID: PMC3784308

34. **A shared neural ensemble links distinct contextual memories encoded close in time**
Denise J. Cai, Daniel Aharoni, Tristan Shuman, Justin Shobe, Jeremy Biane, Weilin Song, Brandon Wei, Michael Veshkini, Mimi La-Vu, Jerry Lou, … Alcino J. Silva
Nature (2016-06) https://doi.org/f8pp28
DOI: 10.1038/nature17955 · PMID: 27251287 · PMCID: PMC5063500

35. **Breakdown of spatial coding and interneuron synchronization in epileptic mice**
Tristan Shuman, Daniel Aharoni, Denise J. Cai, Christopher R. Lee, Spyridon Chavlis, Lucia Page-Harley, Lauren M. Vetere, Yu Feng, Chen Yi Yang, Irene Mollinedo-Gajate, … Peyman Golshani
Nature Neuroscience (2020-02) https://doi.org/ghm6dn
DOI: 10.1038/s41593-019-0559-0 · PMID: 31907437 · PMCID: PMC7259114

36. **Circuit Investigations With Open-Source Miniaturized Microscopes: Past, Present and Future**
Daniel Aharoni, Tycho M. Hoogland
Frontiers in Cellular Neuroscience (2019-04-05) https://doi.org/ghqn39
DOI: 10.3389/fncel.2019.00141 · PMID: 31024265 · PMCID: PMC6461004

37. **Simultaneous Denoising, Deconvolution, and Demixing of Calcium Imaging Data**
Eftychios A. Pnevmatikakis, Daniel Soudry, Yuanjun Gao, Timothy A. Machado, Josh Merel, David Pfau, Thomas Reardon, Yu Mu, Clay Lacefield, Weijian Yang, … Liam Paninski
Neuron (2016-01) https://doi.org/f8g23x
DOI: 10.1016/j.neuron.2015.11.037 · PMID: 26774160 · PMCID: PMC4881387

38. **Fast Nonnegative Deconvolution for Spike Train Inference From Population Calcium**
Imaging
Joshua T. Vogelstein, Adam M. Packer, Timothy A. Machado, Tanya Sippy, Baktash Babadi,
Rafael Yuste, Liam Paninski
Journal of Neurophysiology (2010-12) https://doi.org/fpddqn
DOI: 10.1152/jn.01073.2009 · PMID: 20554834 · PMCID: PMC3007657

39. **Fast and statistically robust cell extraction from large-scale neural calcium imaging**
datasets
Hakan Inan, Claudia Schmuckermair, Tugce Tasci, Biafra O. Ahanonu, Oscar Hernandez,
Jérôme Lecoq, Fatih Dinç, Mark J. Wagner, Murat A. Erdogdu, Mark J. Schnitzer
Neuroscience (2021-03-25) https://doi.org/gjs4d5
DOI: 10.1101/2021.03.24.436279

40. **Template matching techniques in computer vision: theory and practice**
Roberto Brunelli
Wiley (2009)
ISBN: 9780470517062

41. **Online analysis of microendoscopic 1-photon calcium imaging data streams**
Johannes Friedrich, Andrea Giovannucci, Eftychios A. Pnevmatikakis
PLOS Computational Biology (2021-01-28) https://doi.org/gp2fsj
DOI: 10.1371/journal.pcbi.1008565 · PMID: 33507937 · PMCID: PMC7842953

42. **Jupyter Notebooks – a publishing format for reproducible computational workflows**
Thomas Kluyver, Benjamin Ragan-Kelley, Pé, Fernando Rez, Brian Granger, Matthias
Bussonnier, Jonathan Frederic, Kyle Kelley, Jessica Hamrick, Jason Grout, … Jupyter
Development Team
Positioning and Power in Academic Publishing: Players, Agents and Agendas (2016)
https://ebooks.iospress.nl/doi/10.3233/978-1-61499-649-1-87
DOI: 10.3233/978-1-61499-649-1-87

43. **Array programming with NumPy**
Charles R. Harris, K. Jarrod Millman, Stéfan J. van der Walt, Ralf Gommers, Pauli Virtanen,
David Cournapeau, Eric Wieser, Julian Taylor, Sebastian Berg, Nathaniel J. Smith, … Travis E.
Oliphant
Nature (2020-09-17) https://doi.org/ghbzf2
DOI: 10.1038/s41586-020-2649-2 · PMID: 32939066 · PMCID: PMC7759461

44. **SciPy 1.0: fundamental algorithms for scientific computing in Python**
Pauli Virtanen, Ralf Gommers, Travis E. Oliphant, Matt Haberland, Tyler Reddy, David
Cournapeau, Evgeni Burovski, Pearu Peterson, Warren Weckesser, Jonathan Bright, … Yoshiki
Vázquez-Baeza
Nature Methods (2020-03-02) https://doi.org/ggj45f
DOI: 10.1038/s41592-019-0686-2 · PMID: 32015543 · PMCID: PMC7056644

45. **xarray: N-D labeled Arrays and Datasets in Python**
Stephan Hoyer, Joseph J. Hamman
Journal of Open Research Software (2017-04-05) https://doi.org/gdqdmw
DOI: 10.5334/jors.148

46. **holoviz/holoviews: Version 1.13.3**
Philipp Rudiger, Jean-Luc Stevens, James A. Bednar, Bas Nijholt,, Andrew, Chris B, Achim
Randelhoff, Jon Mease, Vasco Tenner, Maxalbert, … Kbowen
Zenodo (2020-06-23) https://doi.org/ghm6dq
DOI: 10.5281/zenodo.3904606

47. **Bokeh: Python library for interactive visualization**
Bokeh Development Team
(2020) https://bokeh.org/

48. **The OpenCV Library**
G. Bradski
Dr. Dobb's Journal of Software Tools (2000)

49. **Dask: Library for dynamic task scheduling**
Dask Development Team
(2016) https://dask.org

50. **The hippocampus as a spatial map. Preliminary evidence from unit activity in the freely-moving rat**
J. O'Keefe, J. Dostrovsky
Brain Research (1971-11) https://doi.org/bwdqcb
DOI: 10.1016/0006-8993(71)90358-1

51. **Long-term stability of the place-field activity of single units recorded from the dorsal hippocampus of freely behaving rats**
L. T. Thompson, P. J. Best
Brain Research (1990-02) https://doi.org/cp6bjf
DOI: 10.1016/0006-8993(90)90555-p

52. **Robustness of Spike Deconvolution for Neuronal Calcium Imaging**
Marius Pachitariu, Carsen Stringer, Kenneth D. Harris
The Journal of Neuroscience (2018-09-12) https://doi.org/gd9mcx
DOI: 10.1523/jneurosci.3339-17.2018 · PMID: 30082416 · PMCID: PMC6136155

53. **Ultrasensitive fluorescent proteins for imaging neuronal activity**
Tsai-Wen Chen, Trevor J. Wardill, Yi Sun, Stefan R. Pulver, Sabine L. Renninger, Amy Baohan,
Eric R. Schreiter, Rex A. Kerr, Michael B. Orger, Vivek Jayaraman, … Douglas S. Kim
Nature (2013-07) https://doi.org/gcz68k
DOI: 10.1038/nature12354 · PMID: 23868258 · PMCID: PMC3777791