₁ RESEARCH

Optimizing network neuroscience computation of individual differences in human spontaneous brain activity for test-retest reliability

Chao Jiang[1], Ye He[2], Richard F. Betzel[3], Yin-Shan Wang[4,5], Xiu-Xia Xing[6] and Xi-Nian Zuo[4,5,7,8]

[1] School of Psychology, Capital Normal University, Beijing, China

[2] School of Artificial Intelligence, Beijing University of Posts and Telecommunications, Beijing, China

[3] Department of Psychological and Brain Sciences, Indiana University, Bloomington, Indiana, United States

[4] State Key Laboratory of Cognitive Neuroscience and Learning, Beijing Normal University, Beijing, China

[5] Developmental Population Neuroscience Research Center, International Data Group/McGovern Institute for Brain Research, Beijing Normal University, Beijing, China

[6] Department of Applied Mathematics, College of Mathematics, Faculty of Science, Beijing University of Technology, Beijing, China

[7] National Basic Science Data Center, Beijing, China

[8] Institute of Psychology, Chinese Academy of Sciences, Beijing, China

Keywords: individual difference, reliability, open science, spontaneous brain activity, connectome

ABSTRACT

A rapidly emerging application of network neuroscience in neuroimaging studies has provided useful tools to understand individual differences in intrinsic brain function by mapping spontaneous brain activity, namely intrinsic functional network neuroscience (ifNN). However, the variability of methodologies applied across the ifNN studies - with respect to node definition, edge construction, and graph measurements- makes it difficult to directly compare findings and also challenging for end users to select the optimal strategies for mapping individual differences in brain networks. Here, we aim to provide a benchmark for best ifNN practices by systematically comparing the measurement reliability of individual differences under different ifNN analytical strategies using the test-retest design of the Human

Connectome Project. The results uncovered four essential principles to guide ifNN studies: 1) use a whole brain parcellation to define network nodes, including subcortical and cerebellar regions, 2) construct functional networks using spontaneous brain activity in multiple slow bands, 3) optimize topological economy of networks at individual level, 4) characterise information flow with specific metrics of integration and segregation. We built an interactive online resource of reliability assessments for future ifNN (`ibraindata.com/research/ifNN`).

AUTHOR SUMMARY

It is an essential mission for neuroscience to understand the individual differences in brain function. Graph or network theory offer novel methods of network neuroscience to address such a challenge. This article documents optimal strategies on the test-retest reliability of measuring individual differences in intrinsic brain networks of spontaneous activity. The analytical pipelines are identified to optimize for highly reliable, individualized network measurements. These pipelines optimize network metrics for high inter-individual variances and low inner-individual variances by defining network nodes with whole-brain parcellations, deriving the connectivity with spontaneous high-frequency slow-band oscillations, constructing brain graphs with topology-based methods for edge filtering, and favoring multi-level or multi-modal metrics. These psychometric findings are critical for translating the functional network neuroscience into clinical or other personalized practices requiring neuroimaging markers.

INTRODUCTION

Over the past two decades, network neuroscience has helped transform the field of neuroscience (D. Bassett et al., 2020), providing a quantitative methodology framework for modeling brains as graphs (or networks) composed of nodes (brain regions) and edges (their connections), namely connectomics (Sporns, 2013a). The organization and topology of macro-scale brain networks can be characterized by a growing suite of connectomic measurements including efficiency, centrality, clustering, small-word topology, rich-club, etc (Craddock et al., 2013). In parallel, resting-state fMRI (rfMRI) has opened up new avenues towards understanding the intrinsic human brain function (Biswal et al., 2010). In conjunction with network neuroscience, rfMRI has led to the emergence of a multidisciplinary field,

intrinsic functional connectomics or network neuroscience (ifNN), in which the brain's intrinsic, interregional connectivity is estimated from rfMRI recordings. It has been widely used to investigate the system-level organization of the human brain function and its relationship with individual differences (Dubois & Adolphs, 2016) in developmental (Zuo et al., 2017), socio-cultural (Pessoa, 2018) and clinical conditions (Fornito, Zalesky, & Breakspear, 2015).

Highly reliable measurements are essential for studying individual differences. In general, reliability characterises a proportion of measurement variability between different subjects relative to the overall variability including both between-subject and within-subject (i.e., random) components (Xing & Zuo, 2018). It is commonly used to assess the consistency or agreement between measurements, or the ability to obtain consistent measures over time. Beyond that, it can also serve as a measure of discriminablity (Xing & Zuo, 2018; Zuo, Biswal, & Poldrack, 2019; Zuo, Xu, & Milham, 2019). For example, if a measurement can more sufficiently capture individual characteristics (i.e., better differentiate a group of individuals), it will produce higher between-subject variability and thus higher reliability than a measurement underestimating the between-subject variability. Such reliability concept has well-established statistical theory and applications in fields such as psychology (Elliott, Knodt, Caspi, Moffitt, & Hariri, 2021) and medicine (Kraemer, 2014) where it is used in psychometric theory and diagnosis theory, respectively. Specifically, in psychology, reliability is important for assessing the validity of psychological tests, and in medicine, it is important for accurately diagnosing and treating patients. In the field of human brain mapping, more recent studies have demonstrated that the measurement reliability is equivalent to the "fingerprint" or discriminability of the measurement under the Gaussian distribution (Bridgeford et al., 2021; Milham, Vogelstein, & Xu, 2021). Therefore, the optimization of measurement reliability of the individual differences can help guide ifNN processing and analysis pipelines for individualized or personalized (e.g., neurodevelopmental (Herting, Gautam, Chen, Mezher, & Vetter, 2018) or clinical (Matthews & Hampshire, 2016)) research.

Previous studies have demonstrated that many functional network measurements with rfMRI have limited reliability (Noble, Scheinost, & Constable, 2019; Zuo & Xing, 2014). These low levels of reliability could be an indication of failure in handling individual variability at different levels (Elliott, Knodt, & Hariri, 2021; Hallquist & Hillary, 2019). In particular, experimental design and processing decisions related to scan duration, determining frequency range, and regressing global signal have

impacts on rfMRI measurements and thus their reliability (Noble et al., 2019; Zuo et al., 2013). Although

less focused on reliability, existing network neuroscience studies revealed that their findings are

influenced by choices of parcellation templates (Bryce et al., 2021; Wang et al., 2009), edge construction

and definition, and choice of graph metrics (Liang et al., 2012). How these decisions affect the

measurement reliability in ifNN deserves further investigation. These analytical choices have been

implemented in different software packages but can vary from one package to another, and thus introduce

more analytic variability (Botvinik-Nezer et al., 2020). Beyond limited examinations on reliability

(Aurich, Filho, da Silva, & Franco, 2015; Braun et al., 2012; Termenon, Jaillard, Delon-Martin, &

Achard, 2016), a systematic investigation into the measurement reliability is warranted to guide ifNN

software use and analyses.

We conducted a systematic ifNN reliability analysis using the test-retest rfMRI data from the Human

Connectome Project (HCP). The HCP has developed its imaging acquisition and data pre-processing

(Glasser et al., 2013) by integrating various strategies optimized for reliability in previous studies (Noble

et al., 2019; Noble, Scheinost, & Constable, 2021; Zuo & Xing, 2014; Zuo et al., 2013). We thus analyzed

the minimally pre-processed HCP rfMRI data and focused our work on four key post-analytic stages:

node definition, edge construction, network measurement, and reliability assessments. In the end, we

propose a set of principles to guide researchers in performing reliable ifNN, advancing the field-standard

call for the best practices in network neuroscience. We released all the codes and reliability data by

building an online platform for sharing the data and computational resources to foster future ifNN.

MATERIALS AND METHODS

A typical analysis pipeline in ifNN includes steps for node definition (parcellations) and edge

construction (frequency bands, connectivity estimation and filtering schemes) (Fig. 1a). To determine an

optimal pipeline, we combine the most reliable strategies across different parts of the analysis by

comparing the reliability of derived global network metrics. The HCP test-retest data were employed for

reliability evaluation (Fig. 1b) using the intraclass correlation (ICC) statistics on the measurement

reliability. Overall reliability assessments associated with the various analytic strategies as well as their

impact on between- and within-subject variability (Fig. 1c) are investigated. We calculated the

between-subject variability (V_b) and within-subject variability (V_w) and normalized them to values

Figure 1. Analytical pipelines for reliable ifNN. a) There are five stages during our analyses: (1) test-retest dataset (white box) downloaded from HCP

website, (2) node definition (green box) defining nodes using a set of brain areas of 24 different partitions of the human brain, (3) edge construction (yellow

box) estimating individual correlation matrices using the six frequency bands (slow 1-6) from Buzsaki's theoretical framework on the brain oscillations as

well as the widely used empirical frequency band (Slow-emp) and transferring these matrices into adjacency matrices using $7 \times 4 \times 12$ different strategies on

edge construction including band-pass filtering, connectivity estimation and edge filtering, (4) network analysis (blue box) systematically calculating various

brain graph metrics on measurements of information flow, and (5) reliability assessment (red box) evaluating test-retest reliability with massive linear mixed

models. b) The test-retest data shared multimodal MRI datasets of 46 subjects in the HCP S1200 release and the HCP Retest release. Each subject underwent

the first four test scans on two days (two scans per day: Rest1 and Rest2) and return several months later to finish the four retest scans on another two

days. c) Measurement reliability refers to the inter-individual or between-subject variability V_b relative to the intra-individual or within-subject variability V_w.

Variability of both between-subject (V_b) and within-subject (V_w) are normalized into between 0 and 1 by the total sample variances. Their changes (ΔV_b and

ΔV_w) introduce a reliability gradient as represented by the vector (the black arrow). The length of the arrow reflects the amplitude of reliability changes when

the reliability assessment from one choice (pink circle, J) to another choice (red circle, K). Further, the arrow's direction (**JK**) indicates the sources of this

reliability change. Here the reliability becomes from moderate to substantial level with increases of between-subject variability ($\Delta V_b > 0$) and decreases of

within-subject variability ($\Delta V_w < 0$).

between 0 and 1 by the total sample variances. The changes in these variability measures, ΔV_b and ΔV_w,

were used to create a reliability gradient represented by a vector. The length of the arrow reflects the

amplitude of the change in reliability when comparing one choice (pink circle, J) to another choice (red

circle, K). The direction of the arrow, **JK**, indicates the sources of the change in reliability. In this case,

the reliability increases from a moderate to a substantial level with an increase in between-subject

variability ($\Delta V_b > 0$) and a decrease in within-subject variability ($\Delta V_w < 0$). We then determine the

optimized pipelines based on the highest reliability measurements, while documenting the derived both

global and local network metrics and both their reliability and variability at an individual level.

Specifically, using the HCP test-retest dataset, our analytic procedure implemented the four

post-analytic stages: node definition, edge construction, network measurement and reliability

assessments. The test-retest rfMRI dataset underwent the standardized preprocessing pipeline developed

by the HCP team (Glasser et al., 2013). The second step defines nodes (green box) using sets of brain

areas based on 24 partitions, and then extracts the nodal time series. During the third step (yellow box),

individual correlation matrices are first estimated based upon the six frequency bands derived from

Buzsaki's theoretical framework on brain oscillations (Buzsaki & Draguhn, 2004) along with the

classical band widely used (0.01 - 0.08 Hz). These matrices are then converted into adjacency matrices

using $4 \times 12 = 48$ strategies on edge filtering. In the fourth step, we performed graph analyses (blue box)

by systematically calculating the brain graph metrics at global, modular and nodal scales. Finally,

test-retest reliability was evaluated (red box) as ICCs with the linear mixed models. We present details of

these analyses in the following sections.

Test-Retest Dataset

The WU-Minn Consortium in HCP shared a set of test-retest multimodal MRI datasets of 46 subjects

from both the S1200 release and the Retest release. These subjects were retested using the full HCP 3T

multimodal imaging and behavioral protocol. Each subject underwent the four scans on two days (two

scans per day: Rest1 versus Rest2) during the first visit and returned several months later to finish the

four scans on another two days during the second visit (Fig. 1b). The test-retest interval ranged from 18

to 328 days (mean: 4.74 months, standard deviation: 2.12 months). Only 41 subjects (28 females, age

range: 26-35 years; 13 males, age range: 22-33 years) had full length rfMRI data across all the eight

scans, 2 visits $\times$ 2 days $\times$ 2 (LR and RL ecoding directions), and were included in the subsequent

analyses. Then we averaged across the RL and LR encodings for each day, so each subject had 4 repeated

measurements in the ICC estimation. This sample size is larger that the minimal sample size ($N = 35$)

for fair reliability with 80% power and significance level of 0.05 based on the above mentioned test-retest

design (4 observations per subject) (Bujang & Baharum, 2017). The HCP rfMRI protocols for scanning

and preprocessing images have been optimized for reliability .

During the scanning, participants were instructed to keep their eyes open and to let their mind wander

while fixating on a cross-hair projected on a dark background. Data were collected at the 3T Siemens

Connectome Skyra MRI scanner with a 32-channel head coil. All functional images were acquired using

a multiband gradient-echo EPI imaging sequence (2mm isotropic voxel, 72 axial slices, TR = 720ms, TE

= 33.1ms, flip angle = $52°$, field of view = 208×180 mm^2, matrix size = 104×90 and a multiband factor

of 8). A total of 1200 images was acquired for a duration of 14 min and 24 s. Details on the imaging

protocols can be found in (Smith et al., 2013).

The protocols of rfMRI image preprocessing and artifact-removal procedures are documented in detail

elsewhere and generated the minimally preprocessed HCP rfMRI images. Artifacts were removed using

the ICA-based X-noiseifier (ICA + FIX) procedure, followed by MS-MAll for inter-subject registration.

The preprocessed rfMRI data were represented as a time series of grayordinates (4D), combining both

cortical surface vertices and subcortical voxels (Glasser et al., 2013).

Node Definition

A brain graph defines a node as a brain area, which is generally derived by an element of brain

parcellation (parcel) according to borders or landmarks of brain anatomy, structure or function as well as

an element of volume (voxel) in imaging signal acquisition or a cluster of voxels (Sporns, 2013b). Due to

the high computational demand of voxel-based brain graph, in this study we defined nodes as parcels

according to the following brain parcellation strategies (Fig. 2a). A surface-based approach has been

demonstrated to outperform other approaches for fMRI analysis (Coalson, Van Essen, & Glasser, 2018;

Zuo et al., 2013) and thus the nodes are defined in the surface space (total 24 surface parcellation

choices). Of note, we adopted a naming convention for brain parcellations as follows:

'*ParcAbbr-NumberOfParcels*' (e.g., LGP-100 or its whole-brain version wbLGP-458).

HCP Multi-Modal Parcellation (MMP) A cortical parcellation generated from multi-modal images of 210 adults from the HCP database, using a semi-automated approach (Glasser et al., 2016). Cortical regions are delineated with respect to their function, connectivity, cortical architecture, and topography, as well as, expert knowledge and meta-analysis results from the literature (Glasser et al., 2016). The atlas contains 180 parcels for each hemisphere.

Local-Global Parcellation (LGP) A gradient-weighted Markov Random Field model integrating local gradient and global similarity approaches produces the novel parcellations (Schaefer et al., 2018). The final version of LGP comes with a multi-scale cortical atlas including 100, 200, 300, 400, 500, 600, 700, 800, 900, and 1000 parcels (equal numbers across the two hemispheres). One benefit of using LGP is to have nodes with almost the same size, and these nodes are also assigned to the common large-scale functional networks (Thomas Yeo et al., 2011).

Brainnetome Parcellation (BNP) Both anatomical landmarks and connectivity-driven information are employed to develop this volumetric brain parcellation (Fan et al., 2016). Specifically, anatomical regions defined as in (Desikan et al., 2006) are parcellated into subregions using functional and structural connectivity fingerprints from HCP datasets. Cortical parcels are obtained by projecting their volume space to surface space. It is noticed that the original BNP contains both cortical (105 areas per hemisphere) and subcortical (36 areas) regions but only the 210 cortical parcels are included for the subsequent analyses.

Whole-Brain Parcellation (wb) Inclusion of subcortical areas has been shown unignorable influences on brain graph analyses (D. Greene et al., 2020; Noble et al., 2019), and we thus also constructed brain graphs with subcortical structures in volume space as nodes by adding these nodes to the cortical brain graphs. To get a high-resolution subcortical parcellation, we adopted the 358 subcortical parcels in (Ji et al., 2019). The authors employed data of 337 unrelated HCP healthy volunteers and extended the MMP cortical network partition into subcortex. This results a set of whole-brain parcellations by combining these subcortical parcels with the aforementioned cortical parcellations, namely **wbMMP**,**wbLGP** and **wbBNP**. We noticed that the wbMMP-718 has been named by the authors of (Ji et al., 2019) as the Cole-Anticevic Brain-wide Network Partition, and we thus renamed the wbMMP-718 as wbCABP-718 for consistency.

Edge Construction

After defining the node with each parcellation, in each parcel, regional mean time series were estimated

by averaging the vertex time series at each time point. To construct an edge between a pair of nodes, their

representative time series entered into the following steps in order: *band-pass filtering*, *inter-node*

connectivity transformation, and *edge filtering*.

Band-Pass Filtering   Resting-state functional connectivity studies have typically focused on fluctuations

below 0.08 Hz or 0.1 Hz (Biswal, Zerrin Yetkin, Haughton, & Hyde, 1995; Fox & Raichle, 2007), and

assumed that only these frequencies contribute significantly to inter-regional functional connectivity (FC)

while other frequencies are artifacts (Cordes et al., 2001). In contrast, however, other studies have found

that specific frequency bands of the rfMRI oscillations make unique and neurobiologically meaningful

contributions to resting-state functional connectivity (Salvador et al., 2005; Zuo & Xing, 2014). More

recently, with fast fMRI methods, some meaningful FC patterns were reported across much higher

frequency bands (Boubela et al., 2013). These observations motivate exploring a range of frequency

bands beyond those typically studied in resting-state functional connectivity studies.

Buzsaki and Draguhn (Buzsaki & Draguhn, 2004) proposed a hierarchical organization of frequency

bands driven by the natural logarithm linear law. This offers a theoretical template for partitioning rfMRI

frequency content into multiple bands (Fig. 3a). The frequencies occupied by these bands have a

relatively constant relationship to each other on a natural logarithmic scale and have a constant ratio

between any given pair of neighboring frequencies (Buzsáki, 2009). These different oscillations are

linked to different neural activities, including cognition, emotion regulation, and memory (Achard,

Salvador, Whitcher, Suckling, & Bullmore, 2006; Buzsáki, 2009; Fox & Raichle, 2007). Advanced by

the fast imaging protocols offered by the HCP scanner, the short scan interval (TR = 720ms) allows us to

obtain more oscillation classes that the traditional rfMRI method. We incorporate the Buzsaki's

framework (Buzsaki & Draguhn, 2004; Penttonen & Buzsáki, 2003) with the HCP fast-TR datasets by

using the DREAM toolbox (Gong et al., 2021) in the Connectome Computation System (Xing, Xu, Jiang,

Wang, & Zuo, 2022; Xu, Yang, Jiang, Xing, & Zuo, 2015). It decomposed the time series into the six

slow bands as illustrated in Fig. 3a.

Connectivity Transformation   For each scan, individual nodal representative time series were band-pass

filtered with each of the six frequency bands, and another empirical frequency band, slow-emp

(0.01-0.08Hz). The Pearson's correlation $r_{ij} \in [-1, 1]$ between the filtered time series of each pair of

nodes $i = 1, ..., N, j = 1, ..., N$ was calculated (N is the number of nodes). These correlation values

provided an estimation on the edge strengths between the two nodes, and formed a $N \times N$ symmetric

correlation matrix $R = (r_{ij})$ for each given subject, scan, parcellation, and frequency band.

Many network metrics are not well defined for negatively weighted connections. In order to ensure that

the connection weights are positive only, we applied four types of transformations to the symmetric

correlation matrix: the **positive** (Eq.pos), **absolute** (Eq.abs), **exponential** (Eq.exp) and **distance-inverse**

(Eq.div) functions, respectively. This avoids the negative values in the inter-node connectivity matrix

$W = (w_{ij})$ where $z_{ij} = \tanh^{-1}(r_{ij})$ is Fisher's $z-$transformation.

$$w_{ij} = \frac{z_{ij} + |z_{ij}|}{2} \in [0, \infty) \tag{pos}$$

$$w_{ij} = |z_{ij}| \in [0, \infty) \tag{abs}$$

$$w_{ij} = \mathbf{e}^{z_{ij}} \in [0, \infty) \tag{exp}$$

$$w_{ij} = \frac{2}{\sqrt{2 \times (1 - r_{ij})}} \in (0, \infty) \tag{div}$$

The connectivity matrix represents a set of the node parcels and relational quantities between each pair

of the nodes, and will serve as the basis of following edge filtering procedure for generation of the final

brain graphs.

Edge Filtering   In a graph, edges represent a set of relevant interactions of crucial importance to obtain

parsimonious descriptions of complex networks. Filtering valid edges can be highly challenging due to

the lack of 'ground truth' of the human brain connectome. To provide a reliable way of building

candidate edges, we sampled the following 12 schemes on edge filtering and applied them to the

connectivity matrices.

Absolute Weight Thresholding (ABS) This approach selects those edges that exceed a manually defined absolute threshold (e.g., correlations higher than 0.5), setting all correlations smaller than 0.5 to 0 (ABS_{05}). This is a simple approach to reconstruct networks Hagmann et al. (2007).

Proportional Thresholding (PROP) It is a common step in the reconstruction of functional brain networks to ensure equal edge density across subjects (D. Bassett et al., 2009; Rubinov, Sporns, van Leeuwen, & Breakspear, 2009; van den Heuvel et al., 2017). It keeps the number of connections fixed across all individuals to rule out the influence of network density on the computation and comparison of graph metrics across groups. This approach includes the selection of a fixed percentage of the strongest conncections as edges in each individual network or brain graph. Compared to ABS, PROP has been argued to reliably separate density from topological effects (Braun et al., 2012; Ginestet, Nichols, Bullmore, & Simmons, 2011) and to result in more stable network metrics (Garrison, Scheinost, Finn, Shen, & Constable, 2015). This makes it a commonly used approach for network construction and analysis in disease-related studies. Here, we focused on two threshholds that are commonly reported in the literature: 10% ($PROP_{10}$) and 20% ($PROP_{20}$).

Degree Thresholding (DEG) The structure of a graph can be biased by the number of existing edges. Accordingly, statistical measures derived from the graph should be compared against graphs that preserve the same average degree, K. A threshold of the degree can be chosen to produce graphs with a fixed mean degree (e.g., $K = 5$, DEG_5), which is the average nodal degrees of an individual graph from a single subject's scan. Many network neuroscience studies have taken this choice for $K = 5$ (S. I. Dimitriadis, Laskaris, Del Rio-Portilla, & Koudounis, 2009; Micheloyannis et al., 2006; Milo et al., 2002; Stam, Jones, Nolte, Breakspear, & Scheltens, 2006). We also include the DEG_{15} for denser graphs of the brain networks.

Global Cost Efficiency Optimization (GCE) Given a network with a cost ρ, its global efficiency is a function of the cost $E_g(\rho)$, and its GCE is $J(\rho) = E_g(\rho) - \rho$. Several studies suggested that brain networks, in particular those with small-world topology, maximize their global-cost efficiency (D. S. Bassett et al., 2008), i.e., $J^{max} = \max_\rho J(\rho)$. Computationally, this scheme is implemented by looping all network costs (e.g., adding edges with weights in order) to find the J^{max} (see Fig. 2b) where the corresponding edge weight was determined as the threshold for edge filtering. In this

sense, GCE is an individualised and optimised version of ABS, PROP and DEG while the latter

three are commonly employed with a fixed threshold for all individuals.

Overall Efficiency Cost Optimization (ECO) Both global and local efficiency are important graph

features to characterize the structure of complex systems in terms of integration and segregation of

information (Latora & Marchiori, 2001). ECO was proposed to determine a network density

threshold for filtering out the weakest links (De Vico Fallani, Latora, & Chavez, 2017). It maximizes

an extension of J^{max}, the ratio between the overall (both global and local) efficiency and its wiring

cost $\max_\rho J^{ext}(\rho) = (E_g(\rho) + E_{loc}(\rho))/\rho$ where E_{loc} denotes the network local efficiency. The

study (Latora & Marchiori, 2001) also demonstrated that, to maximize J, these networks have to be

sparse with an average node degree $K \simeq 3$.

Minimum Spanning Tree (MST) This is an increasingly popular method for identifying the smallest

and most essential set of connections while ensuring that the network forms a fully connected graph

(Guo, Qin, Chen, Xu, & Xiang, 2017; Meier, Tewarie, & Van Mieghem, 2015; Otte et al., 2015; van

Nieuwenhuizen et al., 2018). The tenet of using MST is to summarize information and index

structure of the graph, and thus remove edges with redundant information (Mantegna, 1999).

Specifically, an MST filtered graph will contain N nodes connected *via* $N - 1$ connections with

minimal cost and no loops. This addresses key issues in existing topology filtering schemes that rely

on arbitrary and user-specified absolute thresholds or densities.

Orthogonal Minimum Spanning Tree (OMST) This topological filtering scheme was proposed

recently (S. Dimitriadis, Antonakakis, Simos, Fletcher, & Papanicolaou, 2017) to maximize the

information flow over the network *versus* the cost by selecting the connections via the OMSTs. It

samples the full-weighted brain network over consecutive rounds of MST that are orthogonal to

each other (see Fig. 2b). Practically, we extracted the 1st MST, and then we cleared their

connections and we tracked the 2nd MST from the rest of the network connections, etc. Such an

iterative procedure (stopped by the Mth MST) can get orthogonal MSTs and topologically filter

brain network by optimizing the GCE under the constrains by the MST, leading to an integration of

both GCE and MST

$$\max_{n \in [1,M]} J(\rho(n\text{MSTs})) = E_g(\rho(n\text{MSTs})) - \rho(n\text{MSTs})$$

Planar Maximally Filtered Graph (PMFG) The idea underneath PMFG (Tumminello, Aste, Di Matteo, & Mantegna, 2005) is to filter a dense matrix of weights by retaining the largest possible subgraph while imposing global constraints on the derived network topology. Edges with the strong connection weights are retained while constraining the subgraph to be a (spanning) tree globally. Similarly, during the PMFG construction, the largest weights are retained while constraining the subgraph to be a planar graph globally. The PMFG algorithm searches for the maximum weighted planar subgraph by adding edges one by one. The resulting matrix is sparse with $3(N-2)$ edges. It starts by sorting all the edges of a dense matrix of weights in non-increasing order and tries to insert every edge in the PMFG. Edges that violate the planarity constraint are discarded.

Triangulated Maximally Filtered Graph (TMFG) The algorithm for implementing PMFG is computationally expensive, and is therefore impractical when applied to large brain networks (Massara, Di Matteo, & Aste, 2016). A more efficient algorithms, TMFG, was developed that exhibited greatly reduced computational complexity compared to PMFG. This method captures the most relevant information between nodes by approximating the network connectivity matrix with the endorsement association matrix and minimizing spurious associations. The TMFG derived network contains 3-node (triangle) and 4-node (tetrahedron) cliques, imposing a nested hierarchy and automatically generates a chordal network (Massara et al., 2016; Song, Di Matteo, & Aste, 2012). Although TMFG is not widely applied in network neuroscience studies, it as been applied elsewhere and proven to be a suitable choice for modeling interrelationships between psychological constructs like personality traits (Christensen, Kenett, Aste, Silvia, & Kwapil, 2018).

Orthogonal TMF Graph (OTMFG) To combine both the TMFG's efficiency and OMST's accuracy, we propose OTMFG to maximize the information flow over the network *versus* the cost by selecting the connections of the orthogonal TMFG. It samples the full-weighted brain network over consecutive rounds of TMFG that are orthogonal to each other.

In summary, as illustrated in Fig. 4a, the 12 edge filtering schemes transform a fully weighted matrix into a sparse matrix to represent the corresponding brain network. They can be categorized into two classes: threshold-based *versus* topology-based schemes. ABS_{05}, $PROP_{10}$, $PROP_{20}$, DEG_5, DEG_{15}, ECO and GCE rely on a threshold for filtering and retaining edges with higher weights than the threshold. These schemes normally ignore the topological structure of the entire network and can result in isolated

³¹⁶ nodes. In contrast, the topology-based methods including MST, OMST, PMFG, TMFG and OTMFG, all

³¹⁷ consider the global network topology in determining which edges to retain. As illustrated in Fig. 4b, all

³¹⁸ the schemes are plotted in the $\rho - J^{max}$ plane for their network economics.

³¹⁹

Table 1. A list of the employed network metrics derived with graph theory

Scale	Measure	Attribute	Symbol	Reference
		global efficiency of the network	Eg	Latora & Marchiori, 2001
	integration	average shortest path length of the network	Lp	Watts & Strogatz, 1998
		pseudo diameter of the network	D	Bouttier, Di Francesco, & Guitter, 2003
Global		clustering coefficient of the network	Cp	Watts & Strogatz, 1998
		local efficiency of the network	E_{local}	Latora & Marchiori, 2001
	segregation	modularity of the network	Q	Newman, 2004
		transitivity of the network	Tr	Newman, 2003
		local characteristic path length of nodes	Lp_i	Watts & Strogatz, 1998
		efficiency of nodes	$E_{nodal,i}$	Latora & Marchiori, 2001
		local efficiency of nodes	$E_{local,i}$	Latora & Marchiori, 2001
		clustering coefficient of nodes	Cp_i	Watts & Strogatz, 1998
		pagerank centrality of nodes	Pc_i	Page, Brin, Motwani, & Winograd, 1999
Nodal	centrality	degree centrality of nodes	Dc_i	Pastor-Satorras, Vázquez, & Vespignani, 2001
		eigenvector centrality of nodes	Ec_i	Newman, 2008
		resolvent centrality of nodes	Rc_i	Estrada & Higham, 2010
		subgraph centrality of nodes	Sc_i	Estrada & Rodriguez-Velazquez, 2005
		betweenness centrality of nodes	Bc_i	Freeman, 1978

³²⁰ ***Network Analysis***

³²¹ We performed graph-theory-driven network analysis by calculating several common graph-based metrics

³²² for the resulting graphs. These measures, broadly, can be interpreted based on whether the characterize

the extent to which network structure allows for integrated or segregation information flow. Examples of integrative measures include average shortest path length (L_p), global efficiency (E_g), and pseudo diameter (D). Segregation measures include clustering coefficient (C_p), local efficiency (E_{local}), transitivity (Tr), modularity (Q), and a suite of nodal centrality measures (Table 1). All the metrics are calculated using the Brain Connectivity Toolbox (Rubinov & Sporns, 2010). We employed **graph-tool** (`https://graph-tool.skewed.de`) and **NetworKit** (`https://networkit.github.io`) to achieve high performance comparable (both in memory usage and computation time) to that of a pure C/C++ library. We treated these metrics as the network measurements for subsequent reliability analysis.

Reliability Assessments

Measurement reliability is defined as the extent to which measurements can be replicated across multiple repeated measures. Test-retest reliability is the closeness of the agreement between the results of successive measurements of the same measure and carried out under the same conditions of measurement.

Linear mixed models   As a group-level statistic, reliability refers to the inter-individual or between-subject variability V_b relative to the intra-individual or within-subject variability V_w. Both the intra- and inter-individual variances can be estimated using linear mixed model (LMM). In this study, given a functional graph metric ϕ, we considered a random sample of P subjects with N repeated measurements of a continuous variable in M visits. ϕ_{ijk} (for $i = 1, \cdots, N$ and $j = 1, \cdots, M$, and $k = 1, \cdots, P$) denotes the metric from the k^{th} subject's j^{th} visit and i^{th} measurement occasions. The three-level LMM models ϕ_{ijk} as the following equations:

$$\overbrace{\phi_{ijk}}^{\text{Graph metric}} = \underbrace{\gamma_{000}}_{\substack{\text{fixed} \\ \text{intercept}}} + \underbrace{p_{0k}}_{\substack{\text{random intercepts} \\ \text{level 3, subjects}}} + \underbrace{v_{0jk}}_{\substack{\text{random intercepts} \\ \text{level 2, visits}}} + \underbrace{e_{ijk}}_{\substack{\text{random} \\ \text{residuals}}}$$

where γ_{000} is a fixed parameter (the group mean) and p_{0k}, v_{0jk} and e_{ijk} are independent random effects normally distributed with a mean of 0 and variances σ_{p0}^2, σ_{v0}^2, and σ_e^2. The term p_{0k} is the subject effect, v_{0jk} is the visit effect and e_{ijk} is the measurement residual. Age, gender and interval (Δt) between two visits are covariants.

ICC Estimation   These variances are used to calculate the test-retest reliability, which is measured by the dependability coefficient and reflects the absolute agreement of measurements. The dependability coefficient is a form of ICC commonly, which is the ratio of the variances due to the object of measurement versus sources of error. To avoid negative ICC values and obtain more accurate estimation of the sample ICC, the variance components in model are usually estimated with the restricted maximum likelihood (ReML) approach with the covariance structure of an unrestricted symmetrical matrix (Zuo et al., 2013).

$$\text{Reliability}(\phi) = \frac{V_b}{V_b + V_w} = \frac{\sigma_{p0}^2}{\sigma_{p0}^2 + \sigma_e^2} \tag{ICC}$$

The ICC statistics on the measurement reliability are categorized into five common levels:

$0 < \text{ICC} \leq 0.2$ (**slight**); $0.2 < \text{ICC} \leq 0.4$ (**fair**); $0.4 < \text{ICC} \leq 0.6$ (**moderate**); $0.6 < \text{ICC} \leq 0.8$

(**substantial**); and $0.8 < \text{ICC} < 1.0$ (**almost perfect**). A metric with moderate to almost perfect

test-retest reliability ($\text{ICC} \geq 0.4$) is commonly expected in practice. The ICC level should not be judged

only based upon the point statistical estimation of ICC but its confidence intervals (CI) (Koo & Li, 2016).

We employed the nonparametric conditional bootstrap method for 1000 times to estimate their 95% CIs.

Statistics Evaluation   Our analyses can produce big data of 524,160 ICCs (419,328 for the global

network metrics). These ICCs are grouped into four categories (parcellation, frequency band,

connectivity transformation and edge filtering scheme), each of which has different choices. Given each

choice of a category, we estimated its density distributions of ICCs and calculated two descriptive

statistics: 1) mean ICC values, which measures the *general reliability* under the given choice; 2) number

of almost perfect (noap) ICC values, which measures the *potential reliability* under the given choice.

We further perform Friedman rank sum test to evaluate whether the location parameters of the

distribution of ICCs are the same in each choice. Once the Friedman test is significant, we employ the

pairwise Wilcoxon signed rank test for post-hoc evaluations to compare ICCs between each pair of the

distributions under different choices. The statistical significance levels are corrected with Bonferroni

method for controlling the family wise error rate at a level of 0.05. We develop a method to visualize and

evaluate the change of ICCs (i.e., reliability gradient) between different choices (Fig. 1c). Specifically,

the reliability can be plotted as a function of V_b and V_w in its anatomy plane (Xing & Zuo, 2018; Zuo, Xu,

& Milham, 2019). The gradient of reliability between two choices is modeled by the vector (i.e., the

black arrow), and decomposed into changes of individual variability. The systematic evaluation on the

reliability of the global network metrics determines the optimal network neuroscience by combining the

most reliable pipeline choices, which further generated the nodal metrics' reliability.

RESULTS

Whole brain networks are more reliable than cortical networks

We evaluated reliability based on 24 different parcellation choices (Fig. 2a). In the following parts of the

paper, we name a parcellation as '*ParcAbbr-NumberOfParcels*' (e.g., LGP-100 or its whole-brain version

wbLGP-458). We found significant differences in ICC distributions across the 24 parcellation choices

(Fig. 2b, Friedman rank sum test: $\chi^2 = 20379.07, df = 23, p < 2.2 \times 10^{-16}$, effect size

$W_{\text{Kendall}} = 0.377$). The mean ICCs range from slight (LGP-1000) to substantial (wbLGP-458). Given a

particular parcellation and definition of nodes, we illustrate the density distribution of its ICCs under all

other strategies (edge definition and metric derivation). Notably, whole-brain parcellations yield higher

measurement reliability than parcellations of cerebral cortex on their own (the effect sizes > 0.65). This

improvement in reliability seems not simply a bi-product of having more parcels. We chose the

parcellations in which the number of parcels ($400 \leq n \leq 1000$) almost overlapped between the cortex

and the whole brain, and found no correlation between the number of parcels and the median ICCs

($r = -0.11, p = 0.7$). We report the mean ICC and the number of almost perfect (noap) ICCs (≥ 0.8) as

the descriptive statistics for the density distributions. The wbLGP-458 (mean ICC: 0.671; noap ICC:

519), wbLGP-558 (mean ICC: 0.671; noap ICC: 540) and The wbBNP-568 (mean ICC: 0.664; noap

ICC: 511) are the three most reliable choices (see more details of the post-hoc Wilcoxon signed rank test

in Table S7). Among the cortical parcellations, the LGP-500 (mean ICC: 0.362; noap ICC: 0), LGP-400

(mean ICC: 0.342; noap ICC: 0) and LGP-600 (mean ICC: 0.340; noap ICC: 0) are the three most

reliable choices (Table S3).

394   To better understand the effect of introducing 358 subcortical parcels into the cortical parcellations, we

395 decomposed the reliability changes into a two-dimensional representation of changes of individual

396 variability (Fig. 2c,d). This idea was motivated by the analysis of reliability derived with individual

397 variability (Xing & Zuo, 2018; Zuo, Xu, & Milham, 2019) as in Fig. 1c. For each ICC under a given

398 parcellation choice, we calculated the related between-subject variability V_b and within-subject variability

Figure 2. Parcellation choices impact measurement reliability and individual variability. a) Node definitions are derived from the process of spatially partitioning the human cortex and whole brain (including both cortical and subcortical nodes) at various resolutions, see more details of these name abbreviations in **Methods**. b) Density plots are visualized for distributions of the ICCs under the various parcellation choices on node definition. These density distributions are ranked from top to bottom according to decreases of the mean ICCs while the four colors depict the four quantiles. c) Reliability gradient between any one whole-brain parcellation choice and its corresponding cortical parcellation choice is decomposed into the axis of changes of the between-subject variability (ΔV_b) and the axis of changes of the within-subject variability (ΔV_w). This gradient can be represented as an vector, which is the black arrow from the origin with an angle θ with the x−axis while the color encodes this angle and the transparency or the length reflects the magnitude of the degree of ICC improvement. According to the anatomy of reliability, the optimal space is in the second quadrant (quadII) while the first and third quadrant (quadI and quadIII) are suboptimal for reliability. d) The improvement in the reliability of the pipeline, which is defined from the cortical parcellations to the corresponding whole-brain parcellations (including the subcortex), is illustrated by gradient arrows in the plane of individual variability, while controlling for all other processing steps. Each arrow represents a specific global metric, while controlling for all other processing steps. The position of the arrows reflects the magnitude of between- and within-subject variability changes (ΔV_b, ΔV_w), and the size of the arrows indicates the magnitude of ICC changes.

V_w. Changes in the individual variability associated with the reliability improvements from cortical to whole-brain pipelines were plotted along with ΔV_b and ΔV_w as arrows. These arrows are distributed across the three quadrants (quadI: 0.94%; quadII: 59.99%; quadIII: 39.07%). We noticed that most of these arrows were distributed into the optimal quadrant where the improvements of test-retest reliability by the whole-brain parcellation choices largely attributing to the increases of between-subject variability and decreases of within-subject variability. The decreases of both between-subject and within-subject variability may also strengthen the measurement reliability (the suboptimal quadIII in Fig. 2).

Spontaneous brain activity portrays more reliable networks in higher slow bands

Brain oscillations are hierarchically organized, and their frequency bands were theoretically driven by the natural logarithm linear law (Buzsaki & Draguhn, 2004). By analogy, rfMRI oscillations can, similarly, be partitioned into distinct frequency bands. Advanced by the fast imaging protocols (TR = 720ms), HCP test-retest data allows to obtain more oscillation classes than traditional rfMRI acquisitions (typical TR = 2s). We incorporate the Buzsaki's framework with the HCP dataset using the DREAM toolbox (Gong et al., 2021) in the Connectome Computation System to decompose the time series into the six slow bands (Fig. 3a): **slow-6** (0.0069-0.0116 Hz),**slow-5** (0.0116-0.0301 Hz), **slow-4** (0.0301-0.0822 Hz), **slow-3** (0.0822-0.2234 Hz), **slow-2** (0.2234-0.6065 Hz), **slow-1⁻** (0.6065-0.6944 Hz).

We noticed that, due to the limited sampling rate (TR), this **slow-1⁻** only covers a small part of the full **slow-1** band (0.6065-1.6487 Hz) – we indicate this above. We also included the frequency band, **slow-emp** (0.01-0.08 Hz) for the sake of comparison, as it is covers a range commonly used in rfMRI studies. A significant effect on order ($\chi^2 = 9283.536, df = 6, p < 2.2 \times 10^{-16}, W_{\text{Kendall}} = 0.192$) across the frequency bands was revealed based on the density distributions of ICC (Fig. 3b): slow-2, slow-1⁻, slow-3, slow-emp, slow-4, slow-5, slow-6. Post-hoc paired tests indicated that any pairs of neighbouring bands are significantly different from one another, with measurement reliability increasing with faster frequency bands. Note, however, that slow-1⁻ (mean ICC: 0.564) did not fit into this trend, possibly due to its limited coverage of the full band. But remarkably, slow-1⁻ exhibited the largest number of almost prefect ICCs for potential reliability (noap ICC: 1746). Slow-emp (mean ICC: 0.519; noap ICC: 434) contains overlapping frequencies with both slow-4 (mean ICC: 0.560; noap ICC: 441) and slow-5 (mean ICC: 0.494; noap ICC: 285), and higher ICCs than the two bands but the effect sizes are small to

Figure 3. Reliability gradient across the slow bands and changes of related individual variability. a) Classes of frequency bands for slow oscillations

derived from the natural logarithm linear law. b) Density plots are visualized for the ICC distributions under the various frequency bands. These density

distributions are ranked from top to bottom according to decreases of the mean ICCs while the vertical lines depict the four quartiles. c) Network measurements

are projected onto the reliability anatomy plane coordinated by both between- and within-subject variability. These dot plots are fitted into the topographic

(contour) maps where the local maxima for each band is labeled as a circle. To highlight the trend of increasing reliability as the frequency band increases,

a fourth-order polynomial curve (represented by a red line) is fitted to the frequency contour plot peak points, tracing the reliability flow along slow-to-fast

oscillations in the cortex and whole brain.

moderate (slow-emp vs. slow-4: 0.193; slow-emp vs. slow-5: 0.485). Slow-6 is the choice with the

lowest ICCs (mean ICC: 0.331; noap ICC: 154) compared to other bands (large effect sizes: $r > 0.57$).

To visualize reliability variation across frequency bands, we plotted a trajectory tracing reliability flow

along the five full (slow-6 to slow-2) bands in the reliability plane, whose axes correspond to between-

versus within-subject variability (Fig. 3c). As expected, this nonlinear trajectory contains two stages of

almost linear changes of the network measurement reliability from slow to fast oscillations: whole brain

versus cortex. In each case, the reliability improvements attribute to both increases of between-subject

variability and decreases of within-subject variability while the improvements of whole-brain network

measurement reliability were largely driven by the increased variability between subjects.

Topological economics individualize highly reliable functional brain networks

Estimating functional connections can be highly challenging due to the absence of a 'ground truth'

human functional connectome. To provide a reliable way of building candidate edges of the connections,

we sampled the 12 schemes on graph edge filtering (Fig. 4a), which turn a fully connected matrix into a

sparse graphical representation of the corresponding brain network. These schemes can be categorized

into two classes: threshold-based *versus* topology-based schemes. Threshold-based schemes usually use

a threshold to preserve those edges whose strengths are above a cutoff value, such as ABS_{05}, $PROP_{10}$,

$PROP_{20}$, DEG_5, DEG_{15}. Threshold-based schemes are widely used in network neuroscience and ignore

the intrinsic topological structure of the entire brain network (e.g, leading to multiple connected

components or isolated nodes). In contrast, topology-based schemes such as MST, OMST, PMFG and

TMFG come from other scientific disciplines and are optimized based on the entire network topology

(see **Materials and Methods**). To combine both the TMFG's efficiency and OMST's accuracy, we

proposed the OTMFG. All the schemes are plotted in the plane of cost *versus* global-cost efficiency to

better visualize the economical properties of the derived networks (Fig. 4b). These plots are fitted into

the topographic (contour) maps where the local maxima for each filtering choice is labeled as a circle.

The human brain networks achieve higher global efficiency with lower cost using topology-based

schemes compared to threshold-based schemes, suggesting increasingly optimal economics.

Significant differences in test-retest reliability were detectable across these 12 edge-filtering schemes

($\chi^2 = 9784.317, df = 11, p < 2.2 \times 10^{-16}, W_{\text{Kendall}} = 0.189$, see Fig. 4c). Among the topology-based

schemes, OMST (mean ICC: 0.608; noap ICC: 765), OTMFG (mean ICC: 0.602; noap ICC: 781) and

TMFG (mean ICC: 0.570; noap ICC: 767) were the three most reliable choices. They showed

significantly greater reliability than the three most reliable threshold-based, respectively: $PROP_{20}$ (mean

ICC: 0.593; noap ICC: 632), $PROP_{10}$ (mean ICC: 549; noap ICC: 445) and GCE (mean ICC: 0.533; noap

ICC: 352). Mean reliability of MST are slight to fair (mean ICC: 0.309) but its number of almost perfect

reliability (noap ICC:362) is still higher than all threshold-based schemes except $PROP_{10}$ and $PROP_{20}$.

Figure 4. Edge filtering schemes and their networking performance. (a) Twelve schemes of filtering edge are applied to an individual connectivity

matrix, resulting in the 12 brain networks with their nodes colored as the Yeo2011-7Networks (Thomas Yeo et al., 2011). (b) Global cost efficiency are plotted

against network wiring costs of all the brain networks derived with the 12 edge filtering schemes from all the individual rfMRI scans. Red dots represent the

topology-based while blue dots are for threshold-based networks. These dot plots are fitted into the topographic (contour) maps where the local maxima for

each filtering choice is labeled as a circle. (c) Density plots are for ICC distributions under various the 12 edge filtering schemes. These density distributions are

ranked from top to bottom according to decreases of the mean ICCs while the two colors depict the topology-based and threshold-based schemes. Four quartiles

were indicated by vertical lines. (d) Network measurements are projected onto the reliability anatomy plane coordinated by both between- and within-subject

variability. Red dots represent the topology-based while blue dots are for threshold-based networks. The topographic (contour) maps fit the dots and label the

local maxima as a circle for each scheme and the global maxima as a triangle for the topology and threshold groups, respectively.

Network measurements are labeled based on topology and threshold groups and projected onto the

reliability anatomy plane, whose axes represent between- and within-subject variability (Fig. 4d). The

contour maps are reconstructed for each scheme based upon the individual variability of all the related

network measurements. The topology-based methods (red) showed overall higher ICCs than the

threshold-based methods (blue), improvements that could be attributed to increases in between-subject

variability and decreases of within-subject variability. These observations are consistent between cortex

and whole brain networks while topology-based whole brain network are almost perfectly reliable

(meaning almost perfect reliability, i.e., $ICC \geq 0.8$).

We also explored connection transformation and edge weights, two factors included in edge filtering,

the choices of connectivity transformation and weighing edges, regarding their measurement reliability.

Positive (Eq.pos) (mean ICC: 0.512; noap ICC: 1,031) and exponential (Eq.exp) transformation (mean

ICC: 0.509; noap ICC: 1,855) were the two most reliable choices. Comparing to the positive and absolute

(Eq.abs) (mean ICC: 0.508; noap ICC: 1,050) transformation, the exponential and distance-inverse

(Eq.div) (mean ICC: 0.500; noap ICC: 1,031) transformation show larger number of almost perfect ICCs.

Weighted graphs are also more reliable than the binary graphs while the normalized weighted graphs

demonstrated the highest ICCs, reflecting both the increased between-subject variability and decreased

within-subject variability.

Network integration and segregation can serve reliable metrics of information flow

The previous extensive data analysis suggests that the optimally reliable pipeline should: 1) define

network nodes using a whole-brain parcellation, 2) filter the time series with higher frequency bands, 3)

transform the connectivity using positive transformation, 4) construct network edges using

topology-based methods and normalized weights. Using the optimal pipelines, we evaluated the

reliability levels of various metrics from network neuroscience and their differences across individuals.

Focusing on the optimized pipeline with the highest ICCs of the various choices (wbLGP-458, slow-2,

pos, normalized weights, OMST), we reported test-retest reliability of the measurements as well as their

corresponding individual variability. In Fig. 5a, we found that the global network measurements of

information segregation and integration are at the level of almost perfect reliability except for the

modularity Q (ICC=0.46, 95% CI = [0.252,0.625]). These high-level ICCs are derived with large

between-subject variability and small within-subject variability (Fig. 5b). These findings are

reproducible across the other two parcellation choices (wbCABP-718, wbBNP-458). In consideration of

"Ease-of-Use" for researchers and higher cortical resolution, we mapped the "Out-of-the-Box"

Cole-Anticevic Brain-wide Network Partition (wbCABP-718) for nodal metrics visualization.

Similar to the global metrics, shortest path length L_p and nodal efficiency E_{nodal} exhibited the highest

ICCs (almost perfect test-retest reliability) while ICCs of other nodal metrics remained less than 0.6. To

visualize node-level network metrics, we reported results derived from the wbCABP-718 choice. To

improve spatial contrasts of reliability, we ranked the parcels according to their ICCs and visualized the

ranks in Fig. 5c. Most nodal metrics are more reliable across the 360 cortical areas than the 358

subcortical areas (Wilcoxon tests: all p-values less than 0.001, corrected for multiple comparisons).

However, L_p, E_{nodal} and B_c exhibited higher across subcortical areas than cortical areas (corrected

$p < 0.001$). Across the human cerebral cortex, the right hemispheric areas demonstrated more reliable C_p

(corrected $p < 0.0036$) than the left hemispheric areas. Interesting patterns of the reliability gradient are

also observable along large-scale anatomical directions (dorsal>ventral, posterior>anterior) across the

nodal metrics of information segregation and centrality. These spatial configuration profiles on the

reliability reflected their correspondence on inter-individual variability of these metrics, characterising

the network information flow through the slow-2 band.

Building an open resource for reliable network neuroscience

The results presented here represent huge costs in terms of computational resources (more than 1,728,000

core-hours on **CNGrid**, supported by Chinese Academy of Sciences (`http://cscgrid.cas.cn`).

Derivations of the ICCs and their linear mixed models were implemented in **R** and **Python**. As our

practice in open science, we have started to provide an online platform on the reliability assessments

(`http://ibraindata.com/research/ifNN/reliabilityassessment`). The big

reliability data were designed into an online database for providing the community a resource to search

reliable choices and help the final decision-making. The website for this online database provided more

details of the reliability data use. We shared all the codes, figures and other reliability resources via the

website (`http://ibraindata.com/research/ifNN/database`).

Figure 5.   Measurement reliability and variability of global/nodal network metrics under the optimized pipeline. (a) Spider plots are visualized for ICCs (test-retest) with the 95% confidence intervals (CIs, shadow bands) for the global metrics of network integration, segregation. Integrative measures include average shortest path length (L_p), global efficiency (E_g), and pseudo diameter (D). Segregation measures include clustering coefficient (C_p), local efficiency (E_{loc}), transitivity (Tr), modularity (Q). (b) The reliability anatomy was plotted as a function of between-subject variability (V_b) and within-subject variability (V_w). (c) Ranks of ICCs across the 360 cortical parcels and the 358 subcortical parcels in the optimal pipeline (wbCABP-718, slow-2, pos, OMST) are depicted. Ten nodal metrics are assessed including local characteristic path length of node (Lp_{lcoal}), nodal efficiency (E_{nodal}), local efficiency of nodes (E_{local}), nodal clustering coefficient (C_p), pagerank centrality (P_c), degree centrality (D_c), eigenvector centrality (E_c), resolvent centrality (R_c), subgraph centrality (S_c) and betweeness centrality (B_c).

DISCUSSION

This study examined the series of processing and analysis decisions in constructing graphical representations of brains' intrinsic spontaneous activity. The focus, here, was on identifying the pipeline that generated reliable, individualized networks and network metrics. The results of our study suggest that to derive reliable global network metrics showing higher inter-individual variances and lower intra-individual variances, one should use whole-brain parcellations to define network nodes, focus on higher frequencies in the slow band for time-series filtering to derive the connectivity, and use the topology-based methods for edge filtering to construct sparse brain graphs. Regarding network metrics, multi-level or multi-modal metrics appear more reliable than single-level or single-model metrics. Derive reliable measurements is critical in network neuroscience, especially for translating network neuroscience into personalized practice. Based on these results, we provide four principles towards optimal functional network neuroscience for reliability of measuring individual differences.

Principle I: Use a whole brain parcellation to define network nodes

The basic unit of a graph is the node. However, variability across brain parcellations can yield different graphs, distorting network metrics and making it difficult to compare findings across studies (Wang et al., 2009; Zalesky et al., 2010). In many clinical applications (Fornito et al., 2015; Matthews & Hampshire, 2016), researchers aim to identify disease-specific connectivity profiles of the whole brain, including cortical and subcortical structures, as well as cerebellum. A recent review has raised the concern that many studies have focused on restricted sets of nodes, e.g., cortex only, and called a field standard for the best practices in clinical network neuroscience (Hallquist & Hillary, 2019), which requires almost perfectly reliable measurements (Xing & Zuo, 2018). Our meta-reliability assessments revealed such high reliability of measurements made involving functional brain networks can be achieved, through the inclusion of high-resolution subcortical nodes. This provides strong evidences that the whole-brain node use should be part of the standard analysis pipeline for network neuroscience applications. These improvements of reliability can be attributed to increases in between-subject variability coupled with reductions in within-subject variability relative to networks of cortical regions alone. One possible neuroanatomical explanation is that distant areas of cerebral cortex are interconnected by the basal ganglia and thalamus while also communicating with different regions of the cerebellum *via* polysynaptic circuits, forming an integrated connectome (Bostan & Strick, 2018). These subcortical structures have

been suggested to play a role in both primary (e.g., motor) and higher-order function (e.g., learning and

memory) while studies using rfMRI have delineated the resting-state functional connectivity (RSFC)

maps between these subcortical structures and cortical networks of both primary and high-order

functions. Interestingly, a recent work revealed that inter-individual variance in cerebellar RSFC

networks exceeds that of cortex (Marek et al., 2018). Meanwhile, these RSFC maps are highly

individualized and stable within individuals (D. Greene et al., 2020), indicating that they possess reliable

characteristics. In line with our observations, we argue that inclusion of the subcortical structures as

network nodes can enhance the between-subject variability and stabilize the within-subject variability by

providing a more comprehensive measurements on the entirety of the brain connectivity.

Principle II: Generate functional networks using spontaneous brain activity in multiple slow bands

It has been a common practice in rfMRI research to estimate the RSFC profile based on BOLD time

series of the intrinsic spontaneous brain activity from the low-frequency (0.01 - 0.1 Hz or 0.01 - 0.08 Hz).

However, the test-retest reliability of RSFC measurements derived from this frequency band has been

limited, with ICCs less than 0.4 (Noble et al., 2019; Zuo & Xing, 2014). Still existing studies, however,

have advocated adopting a multi-frequency perspective to examine the amplitude of brain activity at rest

(Zuo et al., 2010) and its network properties (Achard et al., 2006). This approach has been spurred along

by recent advances in multi-banded acquisitions and fast imaging protocols, offering rfMRI studies a way

to examine spontaneous brain activity at much higher frequencies that may contain neurobiologically

meaningful signals (Gong et al., 2021). Our study provides strong evidence of highly reliable signals

across higher slow-frequency bands, which are derived with the hierarchical frequency band theory of

neuronal oscillation system (Buzsaki & Draguhn, 2004). Specifically, a spectrum of reliability increases

was evident from slow bands to fast bands. This reflects greater variability of the network measurements

between subjects and less measurement variability within subject between the higher and lower bands of

the slow frequencies. In theory, each frequency band has an independent role in supporting brain

function. Lower frequency bands are thought to support more general or global computation with

long-distance connections to integrate specific or local computation, which are driven by higher slow

bands based on short-distance connections (Buzsáki, 2009). Our findings of high reliability

(inter-individual differences) are perfectly consistent with this theory from a perspective of individual

variability. Previous findings have found that high-order associative (e.g., default mode and cognitive

control) networks are more reliable than the primary (e.g., somatomotor and visual) networks (Noble et

al., 2019; Zuo & Xing, 2014; Zuo, Xu, & Milham, 2019). A novel frequency-based perspective on these

network-level individual differences can be inspired directly by our observations on the multiple bands.

Principle III: Optimize topological economy to construct network connections at individual level

There is no gold standard on for human functional connectomes, leading to plurality of approaches for

inferring and constructing brain network connections. Threshold-based methods focus on the absolute

strength of connectivity, retaining connections that are above some user-defined threshold and oftentimes

involve applying the same threshold to all subjects. Although this approach mitigate potential biases in

network metrics associated with differences in network density, it may inadvertently also lead to

decreased variability between subjects. This is supported by our results showing that threshold-based

method yield low reliability of network measurements. On the other hand, the human brain is a complex

network that is also near-optimal in terms of connectional economy, balancing tradeoffs of cost with

functionality (Bullmore & Sporns, 2012). In line with this view, certain classes of topology-based

methods for connection definition may hold promise for individualized network construction.

Specifically, each individual brain optimizes its economic wiring in terms of cost and efficiency, reaching

a trade-off between minimizing costs and allowing the emergence of adaptive topology. Our results

demonstrate that such highly individualized functional connectomes generated by the topology-based

methods are more reliable than those by the threshold-methods. This reflects the increases of individual

differences in functional connectomes attributing to the optimal wiring economics at individual level.

The topological optimization also brings other benefits such as ensuring that a graph forms a single

connected component and preserving weak connections. Indeed ,there is increasing evidence supporting

the hypothesis that weak connections are neurobiologically meaningful and explain individual

differences in mind, behavior and demographics as well as disorders (Santarnecchi, Galli, Polizzotto,

Rossi, & Rossi, 2014). Weak connections in a graph may be consistent across datasets and reproducible

within the same individual over multiple scanning sessions and therefore be reliable. Weak connections

might also play non-trivial roles in transformed versions of the original brain network, e.g. so-called

"edge-based functional connectivity" (Faskowitz, Esfahlani, Jo, Sporns, & Betzel, 2020). Among these

topology-based methods, MST is the simplest and promising filtering method if computational efficiency

is the priority. MST can obtain a graph with the same number of nodes and edges, and it is not sensitive

to scaling effects, because its structure only depends on the order rather than the absolute values of the

edges. Although MST loses some local network measurements due to the limited number of edges, it has

some other unique metrics that can be calculated (e.g., leaf fraction, tree hierarchy). A better alternative

might be TMFG which is computationally very efficient and statistically robust, while the OMST and

OTMFG are the most reliable choices by prioritizing significant individual differences.

Principle IV: Characterise information flow with both network integration and segregation metrics

Intrinsic functional networks reflect the outcomes of communication processes and information flows

between pairs of brain regions. How the information and other signals propagate between pairs of brain

regions can be assayed using network neuroscientific metrics and is essential to understanding normative

connectome function and its variation in clinical settings. While the ground truth of functional

connectome remains unknown (and may not exist), network models can help validate the imaging-based

reconstructions of human functional networks (D. Bassett et al., 2020). From a perspective of individual

differences, reliable network measures are the basis of achieving valid ifNN measurements (Zuo, Xu, &

Milham, 2019). Our findings indicated that both the brain network segregation and integration could be

reliably measured with functional connectomics using rfMRI by the optimized pipelines. At the global

level, measures of information integration, e.g. characteristic path length and efficiency, were more

reliable than those of information segregation, e.g. modularity and clustering coefficient. Our results also

revealed that measures of integration were more stable across different scan sessions (i.e., the test-retest)

for an individual subject than the segregation measurements while the inter-individual variability are

measured at the similar level for both integration and segregation metrics. At nodal level, mapping

reliability of the network measurements revealed interesting spatial patterns. Specifically, we found that

cortical areas were generally associated with more reliable local measurements compared to subcortical

areas. This may reflect different functional roles for human cortex and subcortex. For example, the

differences in reliability of path-based metrics might reflect the fact that there are more cortical

within-community paths while between-community paths are more common in subcortex. Beyond this

cortical-subcortical gradient, reliability of the nodal information flow also fit the left-right asymmetry and

dorsal-ventral as well as posterior-anterior gradient, implying the potential validity of individual

differences in information flow attributing to evolutionary, genetic and anatomical factors (Chen et al.,

2013; Rakic, 2009). To facilitate the utility of reliable network integration and segregation metrics in

ifNN, we integrated all the reliability resources into an online platform for reliability queries on specific

metrics of information flow (http://ibraindata.com/research/ifNN).

REPRODUCIBILITY, GENERALIZABILITY AND CONCLUSION

Both reproducibility and generalizability are cornerstones of modern sciences, and remain challenging as

a scientific research frontier (Munafo et al., 2017; Yarkoni, 2022). In this research, we adopt a big data

approach by deeply sampling the parameters (more than 524k parametric settings) of various steps in the

network construction and analysis pipeline to systematically explore the reliability of functional brain

network measurements. This provided robust experimental evidence supporting four key principles that

will foster optimal ifNN research and application. These principles can serve as the base for building

guidelines on the use of ifNN to map individual differences. Standard guidelines are essential for

improvements of reproducibility and generalizability in the research practice, and our work provide basic

resources initiating such standardization in future network neuroscience. We note, however, that while

our approach was extensive, it was not exhaustive (likely impossible) – the analytical sampling procedure

could miss many other existing choices. The processing decisions that yield reliable connectomic

measurements may yield the most reliable network statistics, but there may be another way to process

data that yields overall a higher level of reliability in network measures. Regarding the statistical benefits

of our sampling analytics in the parametric space of the ifNN pipelines, we discuss about the implications

of the present research for reproducible and generalizable network neuroscience as following.

The rfMRI datasets minimally preprocessed by the HCP pipeline are employed for our study while

many different pipelines are available for rfMRI data preprocessing (see a list of pipelines in (Xu et al.,

2015)). These different pipelines vary across parametric settings and orders of various steps of

preprocessing, and thus can have different impacts on the reliability of measuring spontaneous brain

activity (Li et al., 2022). Therefore, it is very important to validate whether the present findings are

reproducible under another preprocessing pipeline. Accordingly, we repeated our analyses by leveraging

another widely-accepted preprocessing pipeline, fMRIPrep (Esteban et al., 2019). As documented in the

supplementary materials, the major findings supporting the principal guidelines are reproducible while

the measurement reliability derived with fMRIPrep are generally lower than those with the HCP pipeline.

Various within-pipeline parametric settings also exist other choices not sampled by our experimental

design but remain potentials for further investigation. For example, edge filtering methods are commonly

used to identify and retain only the most important edges in a graph, based on criteria such as statistical

significance or functional relevance. However, this approach has the potential to introduce bias and

subjectivity in the selection process, and may not fully capture the higher-order structure of a network

system. Algebraic topology, as demonstrated by Giusti, Ghrist, and Bassett (2016) and other recent

studies, offers a promising alternative for high-order edge filtering. By representing relationships

between objects as higher-dimensional simplices instead of edges, simplicial complexes can characterize

polyadic interactions and capture more nuanced aspects of the complex network organization. With the

increasing availability of computational tools for the application of algebraic topology to real data, this

framework has the potential to surpass graph theory in understanding the complexities of neural systems.

Pipelines of generating highly reliable measurements are central to experimental design of studying

individual differences (Matheson, 2019; Zuo, Xu, & Milham, 2019). Given a statistical power, for a fixed

sample size, experiments designed with more reliable pipelines can detect bigger effects of interests. On

the other side, to detect a fixed effect size, experiments designed with more reliable pipelines would be

more powerful or logistically economical (e.g., need less samples). This has very important implications

on the recent arguments about 'big data versus small data' (Marek et al., 2022; Rosenberg & Finn, 2022;

Tibon, Geerligs, & Campbell, 2022), which must take the reliability into account at first place of

designing an experiment (Gratton, Nelson, & Gordon, 2022), and has been increasingly appreciated by

the field of network neuroscience (Helwegen, Libedinsky, & van den Heuvel, 2023). From a perspective

of experimental design, reliability is more straightforward to reproducibility but validity is related to

generalizability. Therefore, we clarify that the measurement reliability is not the final goal but the

validity (Finn & Rosenberg, 2021; Noble et al., 2021), which is not easily ready for a direct examination

as reliability assessment (Zuo, Xu, & Milham, 2019). The reliable pipeline we proposed produced

biologically plausible findings according to the four principles as we discussed, likely reflecting its

potential validity of measuring individual differences in intrinsic brain functional organization.

Validation on the use of our proposed principles represents a promising arena for fostering future network

neuroscience studies such as personality (Hilger & Markett, 2021) or brain developmental charts

(Bethlehem et al., 2022), with potential novel fMRI paradigms (Elliott, Knodt, & Hariri, 2021; Finn,

Glerean, Hasson, & Vanderwal, 2022) or more precise neuroimaging technology (Toi et al., 2022).

Reliability does not necessarily equate to but indeed provides an up bound of validity. In some cases,

increasing reliability may cause a decrease in validity, particularly if the sources of reliability are not

related to the underlying construct of interests. For example, physiological noise and head motion can be

highly reliable as biological traits, but may not be involved in the investigated cognitive processes.

Previous studies have shown that head motion can introduce artifacts into the fMRI data, which can affect

the reliability of functional connectivity measures (Power et al., 2014). In particular, head motion may

have a non-uniform impact on different edge filtering methods and network metrics. Certain methods that

rely on the strength of functional connections, such as threshold-based approaches, may be more

sensitive to head motion artifacts than topology-based methods that focus on the overall structure of the

network. Measures that are highly reliable due to the inclusion of these contaminants may not be valid

indicators of the underlying construct. However, head motion may not always be purely noise and may

contain some neurobiologically meaningful signals (Zeng et al., 2014; Zhou et al., 2016). Therefore, it is

important to carefully consider the potential impact of head motion when choosing an edge filtering

method and interpreting the resulting functional connectivity measures, as well as the trade-off between

controlling for motion artifacts and preserving potentially meaningful signal in the data. In the context of

graph theory, noise can affect both the reliability and validity of graph metrics. For example, noise in the

data can result in higher reliability of certain graph metrics, but this may not necessarily reflect the true

underlying network structure. This is because noise may lead to inflated correlations between certain

regions, resulting in over-estimations of network connectivity and thus higher reliability. However, these

measurements may not be valid indicators of the true network structure and may not accurately reflect the

underlying cognitive processes being studied. On the other hand, the removal of noise may lead to

decreased reliability, but may improve the validity of the measurement by reducing the influence of

unrelated sources of variance. The optimal choices for maximizing reliability in our study may also have

implications for interpretability and generalizability. For example, the inclusion of subcortical structures

in the parcellation scheme may increase the interpretability of the results, as these structures play a key

role in the functional organization of the brain. On the other hand, the choice of connectivity

transformation and edge weighting may have implications for the generalizability of the results, as

different methods may produce different results depending on the specific characteristics of the data.

Further research is warranted to fully understand the consequences of these choices on interpretability,

generalizability, and other aspects of the measurement process.

The guidelines we proposed for rfMRI-based network neuroscience may also provide insights for
network neuroscience computation by leveraging task-fMRI or movie-fMRI. These two paradigms have
gained increasing attention in recent years as a means of measuring functional connectomes (Cole,
Bassett, Power, Braver, & Petersen, 2014; Cole et al., 2013; Finn et al., 2022). The reliability and
predictive power of these measures have been the subject of a number of studies. For instance, a study by
Gao et al. (2020) found that the reliability of movie-fMRI connectivity was influenced by the complexity
and duration of the movie stimulus, with more complex and longer stimuli resulting in higher test-retest
reliability. The results support the notion that task-fMRI and movie-fMRI can produce more reliable
connectivity measures with greater predictive power for individual differences in cognitive and mental
health measures compared to rfMRI, particularly for tasks and stimuli that elicit strong and sustained
activation. According to the relationships among rest, task and movie as well as other naturalistic states
of the human brain as a systems entity (Cole, Ito, Bassett, & Schultz, 2016; Finn, 2021; McCormick,
Arnemann, Ito, Hanson, & Cole, 2022), we speculate that the four principles are generalizable to
functional network neuroscience based on these non-rest brain states. However, we note that more
research is warranted to fully understand the underlying mechanisms and generalizability of these
findings to different task and movie paradigms as well as their translational applications (Eickhoff,
Milham, & Vanderwal, 2020; Finn & Rosenberg, 2021).

Population diversity plays a critical factor of assuring the generalizability in studying individual
differences (A. S. Greene et al., 2022; Ricard et al., 2023). This has been responded by the emerging new
stage of cognitive neuroscience, namely population neuroscience (Falk et al., 2013; Paus, 2010).
Psychometric studies are particularly required for population neuroscience due to the core aim of
measuring individual differences in brain and mind developmental during the life span (Zuo et al., 2017,
2018). The design of a psychometric study is normally recommended to recruit a group of participants
who are stable across the duration of investigation. This makes the interpretation of within-subject
variability straightforward as the subject-independent random noise, and the reliability assessment more
precisely; and also is why most psychometric studies were done in adults although some in children (but
with very short duration). When studying the lifespan development, one must consider the specific
research aims and the underlying assumptions of the study for addressing the reliability trade-off between
maximizing between-individual variability and minimizing within-individual variability. For example, if

the goal of the study is to identify developmental or lifespan-related trajectories, it may be more important to prioritize maximizing between-individual variability in order to capture the full range of individual differences. In this case, techniques such as motion scrubbing or outlier detection may be employed to minimize within-individual variance, even if this leads to a decrease in overall reliability. On the other hand, if the focus of the study is on assessing within-subject changes over time, it may be more important to minimize within-individual variance in order to accurately capture changes in brain function. In this case, techniques such as temporal smoothing or denoising may be employed to increase reliability, even if this leads to a decrease in between-individual variability. It is also important to consider the potential impacts of these choices on the validity of the measurement. For example, if motion scrubbing or outlier detection leads to the exclusion of a large number of subjects or time points, this may introduce bias and reduce the generalizability of the results regarding the limited diversity. Careful consideration of these trade-offs is therefore essential in order to ensure that the chosen approach is appropriate for the specific research aims and assumptions of the study, especially the population neuroscience research.

ACKNOWLEDGMENTS

The neuroimaging data were provided by the HCP WU-Minn Consortium, which is funded by the 16 NIH institutes and centers that support the NIH Blueprint for Neuroscience Research 1U54MH091657 (PIs: David Van Essen and Kamil Ugurbil), the McDonnell Center for Systems Neuroscience at Washington University. The institutional Research Ethics Boards approved their HCP WU-Minn Consortium studies. Written informed consent was obtained from all participants.

COMPETING INTERESTS

The authors declare that they have no conflicts of interest in relation to this manuscript.

AUTHOR CONTRIBUTION

Chao Jiang: Conceptualization; Data curation; Formal analysis; Methodology; Software; Visualization; Writing - original draft; Writing - review & editing. Richard F. Betzel: Funding acquisition; Writing - review & editing. Ye He: Writing - review & editing; Conceptualization. Yin-Shan Wang: Conceptualization; Writing - review & editing. Xiu-Xia Xing: Conceptualization; Software; Resources;

793 Supervision; Writing - review & editing. Xi-Nian Zuo: Conceptualization; Funding acquisition;

794 Resources; Supervision; Visualization; Writing - original draft; Writing - review & editing.

FUNDING INFORMATION

795 This study is supported by the STI 2030 - Major Project 2021ZD0200500. We thank the *Chinese*

796 *Data-sharing Warehouse for In-vivo Imaging Brain* at National Basic Science Data Center for informatics

797 resources, the *Research Program on Discipline Direction Prediction and Technology Roadmap* of China

798 Association for Science and Technology, and *Learning: Brains, Machines and Children* from the Indiana

799 University Office of the Vice President for Research Emerging Area of Research Initiative.

REFERENCES

Achard, S., Salvador, R., Whitcher, B., Suckling, J., & Bullmore, E. (2006). A resilient, low-frequency, small-world human

brain functional network with highly connected association cortical hubs. *The Journal of Neuroscience*, *26*(1), 63-72.

Aurich, N., Filho, J., da Silva, A., & Franco, A. (2015). Evaluating the reliability of different preprocessing steps to estimate

graph theoretical measures in resting state fMRI data. *Frontiers in Neuroscience*, *9*, 48.

Bassett, D., Bullmore, E., Meyer-Lindenberg, A., Apud, J., Weinberger, D., & Coppola, R. (2009). Cognitive fitness of

cost-efficient brain functional networks. *Proceedings of the National Academy of Sciences of the United States of*

America, *106*(28), 11747–11752.

Bassett, D., Cullen, K., Eickhoff, S., Farah, M., Goda, Y., Haggard, P., . . . Ueda, H. (2020). Reflections on the past two

decades of neuroscience. *Nature Reviews Neuroscience*, *21*(10), 524-534.

Bassett, D. S., Bullmore, E., Verchinski, B. A., Mattay, V. S., Weinberger, D. R., & Meyer-Lindenberg, A. (2008).

Hierarchical organization of human cortical networks in health and schizophrenia. *The Journal of Neuroscience*, *28*(37),

9239-9248.

Bethlehem, R., Seidlitz, J., White, S., Vogel, J., Anderson, K., Adamson, C., . . . VETSA (2022). Brain charts for the human

lifespan. *Nature*, *604*, 525-533.

Biswal, B., Mennes, M., Zuo, X.-N., Gohel, S., Kelly, C., Smith, S., . . . Milham, M. (2010). Toward discovery science of

human brain function. *Proceedings of the National Academy of Sciences of the United States of America*, *107*(10),

4734-4739.

Biswal, B., Zerrin Yetkin, F., Haughton, V., & Hyde, J. (1995). Functional connectivity in the motor cortex of resting human

brain using echo-planar MRI. *Magnetic Resonance in Medicine*, *34*(4), 537-541.

Bostan, A., & Strick, P. (2018). The basal ganglia and the cerebellum: Nodes in an integrated network. *Nature Reviews*

Neuroscience, *19*(6), 338-350.

Botvinik-Nezer, R., Holzmeister, F., Camerer, C., Dreber, A., Huber, J., Johannesson, M., . . . Schonberg, T. (2020).

Variability in the analysis of a single neuroimaging dataset by many teams. *Nature*, *582*(7810), 84-88.

Boubela, R., Kalcher, K., Huf, W., Kronnerwetter, C., Filzmoser, P., & Moser, E. (2013). Beyond noise: Using temporal

ICA to extract meaningful information from high-frequency fMRI signal fluctuations during rest. *Frontiers in Human*

Neuroscience, *7*, 168.

Bouttier, J., Di Francesco, P., & Guitter, E. (2003). Geodesic distance in planar graphs. *Nuclear physics B*, *663*(3), 535–567.

Braun, U., Plichta, M., Esslinger, C., Sauer, C., Haddad, L., Grimm, O., . . . Meyer-Lindenberg, A. (2012). Test-retest

reliability of resting-state connectivity network characteristics using fMRI and graph theoretical measures. *NeuroImage*,

59(2), 1404-1412.

Bridgeford, E., Wang, S., Wang, Z., Xu, T., Craddock, C., Dey, J., . . . Vogelstein, J. (2021). Eliminating accidental

deviations to minimize generalization error and maximize replicability: Applications in connectomics and genomics.

PLoS Computational Biology, *17*(9), e1009279.

Bryce, N., Flournoy, J., Guassi Moreira, J., Rosen, M., Sambook, K., Mair, P., & McLaughlin, K. (2021). Brain parcellation

selection: An overlooked decision point with meaningful effects on individual differences in resting-state functional

connectivity. *NeuroImage*, *243*, 118487.

Bujang, M., & Baharum, N. (2017). A simplified guide to determination of sample size requirements for estimating the

value of intraclass correlation coefficient: A review. *Archives of Orofacial Sciences*, *12*(1), 1-11.

Bullmore, E., & Sporns, O. (2012). The economy of brain network organization. *Nature Reviews Neuroscience*, *13*(5),

336-349.

Buzsaki, G., & Draguhn, A. (2004). Neuronal oscillations in cortical networks. *Science*, *304*(5679), 1926-1929.

Buzsáki, G. (2009). *Rhythms of the brain*. Oxford University Press.

Chen, C.-H., Fiecas, M., Gutiérrez, E., Panizzon, M., Eyler, L., Vuoksimaa, E., . . . Kremen, W. (2013). Genetic topography
of brain morphology. *Proceedings of the National Academy of Sciences of the United States of America*, *110*(42),
17089-17094.

Christensen, A., Kenett, Y., Aste, T., Silvia, P., & Kwapil, T. (2018). Network structure of the wisconsin schizotypy
scales-short forms: Examining psychometric network filtering approaches. *Behavior Research Methods*, *50*(6),
2531-2550.

Coalson, T., Van Essen, D., & Glasser, M. (2018). The impact of traditional neuroimaging methods on the spatial
localization of cortical areas. *Proceedings of the National Academy of Sciences of the United States of America*, *115*(27),
E6356-E6365.

Cole, M. W., Bassett, D. S., Power, J. D., Braver, T. S., & Petersen, S. E. (2014). Intrinsic and task-evoked network
architectures of the human brain. *Neuron*, *83*(1), 238 – 251.

Cole, M. W., Ito, T., Bassett, D. S., & Schultz, D. H. (2016). Activity flow over resting-state networks shapes cognitive task
activations. *Nature Neuroscience*, *19*(12), 1718 – 1726.

Cole, M. W., Reynolds, J. R., Power, J. D., Repovs, G., Anticevic, A., & Braver, T. S. (2013). Multi-task connectivity
reveals flexible hubs for adaptive task control. *Nature Neuroscience*, *16*(9), 1348 – 1355.

Cordes, D., Haughton, V., Arfanakis, K., Carew, J., Turski, P., Moritz, C., . . . Meyerand, M. (2001). Frequencies
contributing to functional connectivity in the cerebral cortex in "resting-state" data. *American Journal of Neuroradiology*,
22(7), 1326-1333.

Craddock, R., Jbabdi, S., Yan, C.-G., Vogelstein, J., Castellanos, F., Di Martino, A., . . . Milham, M. (2013). Imaging human
connectomes at the macroscale. *Nature Methods*, *10*(6), 524-539.

Desikan, R., Ségonne, F., Fischl, B., Quinn, B., Dickerson, B., Blacker, D., . . . Killiany, R. (2006). An automated labeling
system for subdividing the human cerebral cortex on mri scans into gyral based regions of interest. *NeuroImage*, *31*(3),
968-980.

De Vico Fallani, F., Latora, V., & Chavez, M. (2017). A topological criterion for filtering information in complex brain

networks. *PLoS Computational Biology*, *13*(1), e1005305.

Dimitriadis, S., Antonakakis, M., Simos, P., Fletcher, J., & Papanicolaou, A. (2017). Data-driven topological filtering based

on orthogonal minimal spanning trees: Application to multigroup magnetoencephalography resting-state connectivity.

Brain Connectivity, *7*(10), 661-670.

Dimitriadis, S. I., Laskaris, N. A., Del Rio-Portilla, Y., & Koudounis, G. C. (2009). Characterizing dynamic functional

connectivity across sleep stages from EEG. *Brain Topography*, *22*(2), 119-133.

Dubois, J., & Adolphs, R. (2016). Building a science of individual differences from fMRI. *Trends in Cognitive Sciences*,

20(6), 425-443.

Eickhoff, S. B., Milham, M., & Vanderwal, T. (2020). Towards clinical applications of movie fmri. *NeuroImage*, *217*.

Elliott, M., Knodt, A., Caspi, A., Moffitt, T., & Hariri, A. (2021). Need for psychometric theory in neuroscience research

and training: Reply to Kragel et al. (2021). *Psychological Science*, *32*(4), 627-629.

Elliott, M., Knodt, A., & Hariri, A. (2021). Striving toward translation: strategies for reliable fMRI measurement. *Trends in*

Cognitive Sciences, *25*(9), 776-787.

Esteban, O., Markiewicz, C., Blair, R., Moodie, C., Isik, A., Erramuzpe, A., . . . Gorgolewski, K. (2019). fmriprep: a robust

preprocessing pipeline for functional mri. *Nature Methods*, *16*(1), 111-116.

Estrada, E., & Higham, D. J. (2010). Network properties revealed through matrix functions. *SIAM review*, *52*(4), 696–714.

Estrada, E., & Rodriguez-Velazquez, J. A. (2005). Subgraph centrality in complex networks. *Physical Review E*, *71*(5),

056103.

Falk, E. B., Hyde, L. W., Mitchell, C., Faul, J., Gonzalez, R., Heitzeg, M. M., . . . others (2013). What is a representative

brain? Neuroscience meets population science. *Proc. Natl. Acad. Sci. U.S.A.*, *110*(44), 17615–17622.

Fan, L., Li, H., Zhuo, J., Zhang, Y., Wang, J., Chen, L., . . . Jiang, T. (2016). The Human Brainnetome Atlas: A new brain

atlas based on connectional architecture. *Cerebral Cortex*, *26*(8), 3508-3526.

Faskowitz, J., Esfahlani, F., Jo, Y., Sporns, O., & Betzel, R. (2020). Edge-centric functional network representations of

human cerebral cortex reveal overlapping system-level architecture. *Nature Neuroscience*, *23*(12), 1644-1654.

Finn, E. (2021). Is it time to put rest to rest? *Trends in Cognitive Sciences*, *25*(12), 1021-1032.

Finn, E., Glerean, E., Hasson, U., & Vanderwal, T. (2022). Naturalistic imaging: The use of ecologically valid conditions to
study brain function. *NeuroImage*, *247*, 118776.

Finn, E., & Rosenberg, M. (2021). Beyond fingerprinting: Choosing predictive connectomes over reliable connectomes.
NeuroImage, *239*, 118254.

Fornito, A., Zalesky, A., & Breakspear, M. (2015). The connectomics of brain disorders. *Nature Reviews Neuroscience*,
16(3), 159-172.

Fox, M., & Raichle, M. (2007). Spontaneous fluctuations in brain activity observed with functional magnetic resonance
imaging. *Nature Reviews Neuroscience*, *8*(9), 700-711.

Freeman, L. C. (1978). Centrality in social networks conceptual clarification. *Social networks*, *1*(3), 215–239.

Gao, J., Chen, G., Wu, J., Wang, Y., Hu, Y., Xu, T., . . . Yang, Z. (2020). Reliability map of individual differences reflected
in inter-subject correlation in naturalistic imaging. *Neuroimage*, *223*, 117277.

Garrison, K. A., Scheinost, D., Finn, E. S., Shen, X., & Constable, R. T. (2015). The (in)stability of functional brain
network measures across thresholds. *NeuroImage*, *118*, 651-661.

Ginestet, C. E., Nichols, T. E., Bullmore, E. T., & Simmons, A. (2011). Brain network analysis: separating cost from
topology using cost-integration. *PLoS One*, *6*(7), e21570.

Giusti, C., Ghrist, R., & Bassett, D. S. (2016). Two's company, three (or more) is a simplex. *Journal of computational*
neuroscience, *41*(1), 1–14.

Glasser, M., Coalson, T., Robinson, E., Hacker, C., Harwell, J., Yacoub, E., . . . Van Essen, D. (2016). A multi-modal
parcellation of human cerebral cortex. *Nature*, *536*(7615), 171-178.

Glasser, M., Sotiropoulos, S., Wilson, J., Coalson, T., Fischl, B., Andersson, J., . . . Jenkinson, M. (2013). The minimal
preprocessing pipelines for the Human Connectome Project. *NeuroImage*, *80*, 105-124.

Gong, Z.-Q., Gao, P., Jiang, C., Xing, X.-X., Dong, H.-M., White, T., . . . Zuo, X.-N. (2021). DREAM: A toolbox to decode
rhythms of the brain system. *Neuroinformatics*, *19*(3), 529-545.

Gratton, C., Nelson, S., & Gordon, E. (2022). Brain-behavior correlations: Two paths toward reliability. *Neuron*, *110*(9),

1446-1449.

Greene, A. S., Shen, X., Noble, S., Horien, C., Hahn, C. A., Arora, J., ... others (2022). Brain–phenotype models fail for

individuals who defy sample stereotypes. *Nature*, *609*(7925), 109–118.

Greene, D., Marek, S., Gordon, E., Siegel, J., Gratton, C., Laumann, T., ... Dosenbach, N. (2020). Integrative and

network-specific connectivity of the basal ganglia and thalamus defined in individuals. *Neuron*, *105*(4), 742-758.e6.

Guo, H., Qin, M., Chen, J., Xu, Y., & Xiang, J. (2017). Machine-learning classifier for patients with major depressive

disorder: Multifeature approach based on a high-order minimum spanning tree functional brain network. *Computational*

and Mathematical Methods in Medicine, *2017*, 4820935.

Hagmann, P., Kurant, M., Gigandet, X., Thiran, P., Wedeen, V., Meuli, R., & Thiran, J.-P. (2007). Mapping human

whole-brain structural networks with diffusion MRI. *PLoS One*, *2*(7), e597.

Hallquist, M. N., & Hillary, F. G. (2019). Graph theory approaches to functional network organization in brain disorders: A

critique for a brave new small-world. *Network Neuroscience*, *3*(1), 1-26.

Helwegen, K., Libedinsky, I., & van den Heuvel, M. P. (2023). Statistical power in network neuroscience. *Trends in*

Cognitive Sciences. doi: https://doi.org/10.1016/j.tics.2022.12.011

Herting, M., Gautam, P., Chen, Z., Mezher, A., & Vetter, N. (2018). Test-retest reliability of longitudinal task-based fmri:

Implications for developmental studies. *Developmental Cognitive Neuroscience*, *33*, 17-26.

Hilger, K., & Markett, S. (2021). Personality network neuroscience: Promises and challenges on the way toward a unifying

framework of individual variability. *Network Neuroscience*, *5*(3), 631-645.

Ji, J., Spronk, M., Kulkarni, K., Repovš, G., Anticevic, A., & Cole, M. (2019). Mapping the human brain's

cortical-subcortical functional network organization. *NeuroImage*, *185*, 35-57.

Koo, T., & Li, M. (2016). A guideline of selecting and reporting intraclass correlation coefficients for reliability research.

Journal of Chiropractic Medicine, *15*(2), 155-163.

Kraemer, H. (2014). The reliability of clinical diagnoses: State of the art. *Annual Review of Clinical Psychology*, *10*,

111-130.

Latora, V., & Marchiori, M. (2001). Efficient behavior of small-world networks. *Physical Review Letters*, *87*(19), 198701.

Li, X., Ai, L., Giavasis, S., Jin, H., Feczko, E., Xu, T., ... Milham, M. P. (2022). Moving beyond processing and

analysis-related variation in neuroscience. *bioRxiv*. doi: 10.1101/2021.12.01.470790

Liang, X., Wang, J., Yan, C., Shu, N., Xu, K., Gong, G., & He, Y. (2012). Effects of different correlation metrics and

preprocessing factors on small-world brain functional networks: A resting-state functional MRI study. *PLoS One*, *7*(3),

e32766.

Mantegna, R. (1999). Hierarchical structure in financial markets. *European Physical Journal B*, *11*(1), 193-197.

Marek, S., Siegel, J., Gordon, E., Raut, R., Gratton, C., Newbold, D., ... Dosenbach, N. (2018). Spatial and temporal

organization of the individual human cerebellum. *Neuron*, *100*(4), 977-993.e7.

Marek, S., Tervo-Clemmens, B., Calabro, F., Montez, D., Kay, B., Hatoum, A., ... Dosenbach, N. (2022). Reproducible

brain-wide association studies require thousands of individuals. *Nature*, *603*(7902), 654-660.

Massara, G., Di Matteo, T., & Aste, T. (2016). Network filtering for big data: Triangulated maximally filtered graph.

Journal of Complex Networks, *5*(2), 161-178.

Matheson, G. (2019). We need to talk about reliability: Making better use of test-retest studies for study design and

interpretation. *PeerJ*, *2019*(5), e6918.

Matthews, P., & Hampshire, A. (2016). Clinical concepts emerging from fMRI functional connectomics. *Neuron*, *91*(3),

511-528.

McCormick, E. M., Arnemann, K. L., Ito, T., Hanson, S. J., & Cole, M. W. (2022). Latent functional connectivity

underlying multiple brain states. *Network Neuroscience*, *6*(2), 570 – 590.

Meier, J., Tewarie, P., & Van Mieghem, P. (2015). The union of shortest path trees of functional brain networks. *Brain*

Connectivity, *5*(9), 575-581.

Micheloyannis, S., Pachou, E., Stam, C. J., Breakspear, M., Bitsios, P., Vourkas, M., ... Zervakis, M. (2006). Small-world

networks and disturbed functional connectivity in schizophrenia. *Schizophrenia Research*, *87*(1-3), 60-66.

Milham, M., Vogelstein, J., & Xu, T. (2021). Removing the reliability bottleneck in functional magnetic resonance imaging

research to achieve clinical utility. *JAMA Psychiatry*, *78*(6), 587-588.

Milo, R., Shen-Orr, S., Itzkovitz, S., Kashtan, N., Chklovskii, D., & Alon, U. (2002). Network motifs: simple building

blocks of complex networks. *Science*, *298*(5594), 824-827.

Munafo, M., Nosek, B., Bishop, D., Button, K., Chambers, C., Percie Du Sert, N., . . . Ioannidis, J. (2017). A manifesto for

reproducible science. *Nature Human Behaviour*, *1*(1).

Newman, M. E. (2003). The structure and function of complex networks. *SIAM review*, *45*(2), 167–256.

Newman, M. E. (2004). Fast algorithm for detecting community structure in networks. *Physical review E*, *69*(6), 066133.

Newman, M. E. (2008). The mathematics of networks. *The new palgrave encyclopedia of economics*, *2*(2008), 1–12.

Noble, S., Scheinost, D., & Constable, R. (2019). A decade of test-retest reliability of functional connectivity: A systematic

review and meta-analysis. *NeuroImage*, *203*, 116157.

Noble, S., Scheinost, D., & Constable, R. (2021). A guide to the measurement and interpretation of fmri test-retest

reliability. *Current Opinion in Behavioral Sciences*, *40*, 27-32.

Otte, W., van Diessen, E., Paul, S., Ramaswamy, R., Subramanyam Rallabandi, V., Stam, C., & Roy, P. (2015). Aging

alterations in whole-brain networks during adulthood mapped with the minimum spanning tree indices: The interplay of

density, connectivity cost and life-time trajectory. *NeuroImage*, *109*, 171-189.

Page, L., Brin, S., Motwani, R., & Winograd, T. (1999). *The pagerank citation ranking: Bringing order to the web.* (Tech.

Rep.). Stanford InfoLab.

Pastor-Satorras, R., Vázquez, A., & Vespignani, A. (2001). Dynamical and correlation properties of the internet. *Physical

review letters*, *87*(25), 258701.

Paus, T. (2010). Population neuroscience: why and how. *Hum. Brain Mapp.*, *31*(6), 891–903.

Penttonen, M., & Buzsáki, G. (2003). Natural logarithmic relationship between brain oscillators. *Thalamus and Related

Systems*, *2*(2), 145-152.

Pessoa, L. (2018). Understanding emotion with brain networks. *Current Opinion in Behavioral Sciences*, *19*, 19-25.

Power, J. D., Mitra, A., Laumann, T. O., Snyder, A. Z., Schlaggar, B. L., & Petersen, S. E. (2014). Methods to detect,

characterize, and remove motion artifact in resting state fmri. *NeuroImage*, *84*(Supplement C), 320-341.

Rakic, P. (2009). Evolution of the neocortex: A perspective from developmental biology. *Nature Reviews Neuroscience*,

10(10), 724-735.

Ricard, J., Parker, T., Dhamala, E., Kwasa, J., Allsop, A., & Holmes, A. (2023). Confronting racially exclusionary practices

in the acquisition and analyses of neuroimaging data. *Nature Neuroscience*, *26*(1), 4-11.

Rosenberg, M., & Finn, E. (2022). How to establish robust brain-behavior relationships without thousands of individuals.

Nature Neuroscience, *25*(7), 835-837.

Rubinov, M., & Sporns, O. (2010). Complex network measures of brain connectivity: Uses and interpretations.

NeuroImage, *52*(3), 1059-1069.

Rubinov, M., Sporns, O., van Leeuwen, C., & Breakspear, M. (2009). Symbiotic relationship between brain structure and

dynamics. *BMC Neuroscience*, *10*, 55.

Salvador, R., Suckling, J., Coleman, M., Pickard, J., Menon, D., & Bullmore, E. (2005). Neurophysiological architecture of

functional magnetic resonance images of human brain. *Cerebral Cortex*, *15*(9), 1332-2342.

Santarnecchi, E., Galli, G., Polizzotto, N., Rossi, A., & Rossi, S. (2014). Efficiency of weak brain connections support

general cognitive functioning. *Human Brain Mapping*, *35*(9), 4566-4582.

Schaefer, A., Kong, R., Gordon, E., Laumann, T., Zuo, X.-N., Holmes, A., ... Yeo, B. (2018). Local-global parcellation of

the human cerebral cortex from intrinsic functional connectivity MRI. *Cerebral Cortex*, *28*(9), 3095-3114.

Smith, S., Beckmann, C., Andersson, J., Auerbach, E., Bijsterbosch, J., Douaud, G., ... Glasser, M. (2013). Resting-state

fMRI in the Human Connectome Project. *NeuroImage*, *80*, 144-168.

Song, W.-M., Di Matteo, T., & Aste, T. (2012). Hierarchical information clustering by means of topologically embedded

graphs. *PLoS One*, *7*(3), e31929.

Sporns, O. (2013a). Making sense of brain network data. *Nature Methods*, *10*(6), 491-493.

Sporns, O. (2013b). Network attributes for segregation and integration in the human brain. *Current Opinion in*

Neurobiology, *23*(2), 162-171.

Stam, C., Jones, B., Nolte, G., Breakspear, M., & Scheltens, P. (2006). Small-world networks and functional connectivity in

Alzheimer's disease. *Cerebral Cortex*, *17*(1), 92-99.

Termenon, M., Jaillard, A., Delon-Martin, C., & Achard, S. (2016). Reliability of graph analysis of resting state fMRI using

test-retest dataset from the Human Connectome Project. *NeuroImage*, *142*, 172-187.

Thomas Yeo, B., Krienen, F., Sepulcre, J., Sabuncu, M., Lashkari, D., Hollinshead, M., . . . Buckner, R. (2011). The

organization of the human cerebral cortex estimated by intrinsic functional connectivity. *Journal of Neurophysiology*,

106(3), 1125-1165.

Tibon, R., Geerligs, L., & Campbell, K. (2022). Bridging the big (data) gap: levels of control in small- and large-scale

cognitive neuroscience research. *Trends in Neurosciences*, *45*(7), 507-516.

Toi, P., Jang, H., Min, K., Kim, S.-P., Lee, S.-K., Lee, J., . . . Park, J.-Y. (2022). In vivo direct imaging of neuronal activity at

high temporospatial resolution. *Science*, *378*(6616).

Tumminello, M., Aste, T., Di Matteo, T., & Mantegna, R. (2005). A tool for filtering information in complex systems.

Proceedings of the National Academy of Sciences of the United States of America, *102*(30), 10421-10426.

van den Heuvel, M. P., de Lange, S. C., Zalesky, A., Seguin, C., Yeo, B. T., & Schmidt, R. (2017). Proportional thresholding

in resting-state fMRI functional connectivity networks and consequences for patient-control connectome studies: Issues

and recommendations. *NeuroImage*, *152*, 437–449.

van Nieuwenhuizen, D., Douw, L., Klein, M., Peerdeman, S., Heimans, J., Reijneveld, J., . . . Hillebrand, A. (2018).

Cognitive functioning and functional brain networks in postoperative WHO grade I meningioma patients. *Journal of

Neuro-Oncology*, *140*(3), 605-613.

Wang, J., Wang, L., Zang, Y., Yang, H., Tang, H., Gong, Q., . . . He, Y. (2009). Parcellation-dependent small-world brain

functional networks: A resting-state fMRI study. *Human Brain Mapping*, *30*(5), 1511-1523.

Watts, D. J., & Strogatz, S. H. (1998). Collective dynamics of 'small-world' networks. *nature*, *393*(6684), 440–442.

Xing, X.-X., Xu, T., Jiang, C., Wang, Y., & Zuo, X.-N. (2022). Connectome Computation System: 2015-2021 updates.

Science Bulletin, *67*(5), 448-451.

Xing, X.-X., & Zuo, X.-N. (2018). The anatomy of reliability: a must read for future human brain mapping. *Science

Bulletin*, *63*(24), 1606-1607.

Xu, T., Yang, Z., Jiang, L., Xing, X.-X., & Zuo, X.-N. (2015). A Connectome Computation System for discovery science of brain. *Science Bulletin*, *60*(1), 86-95.

Yarkoni, T. (2022). The generalizability crisis. *Behavioral and Brain Sciences*, *45*, e1.

Zalesky, A., Fornito, A., Harding, I., Cocchi, L., Yücel, M., Pantelis, C., & Bullmore, E. (2010). Whole-brain anatomical networks: Does the choice of nodes matter? *NeuroImage*, *50*(3), 970-983.

Zeng, L.-L., Wang, D., Fox, M., Sabuncu, M., Hu, D., Ge, M., . . . Liu, H. (2014). Neurobiological basis of head motion in brain imaging. *Proceedings of the National Academy of Sciences of the United States of America*, *111*(16), 6058-6062.

Zhou, Y., Chen, J., Luo, Y. L., Zheng, D., Rao, L.-L., Li, X., . . . Zuo, X.-N. (2016). Genetic overlap between in-scanner head motion and the default network connectivity. *bioRxiv*. doi: 10.1101/087023

Zuo, X.-N., Biswal, B., & Poldrack, R. (2019). Editorial: Reliability and reproducibility in functional connectomics. *Frontiers in Neuroscience*, *13*, 117.

Zuo, X. N., Di Martino, A., Kelly, C., Shehzad, Z. E., Gee, D. G., Klein, D. F., . . . Milham, M. P. (2010). The oscillating brain: Complex and reliable [Journal Article]. *NeuroImage*, *49*(2), 1432-1445.

Zuo, X.-N., He, Y., Betzel, R., Colcombe, S., Sporns, O., & Milham, M. (2017). Human connectomics across the life span. *Trends in Cognitive Sciences*, *21*(1), 32-45.

Zuo, X.-N., He, Y., Su, X., Hou, X.-H., Weng, X., & Li, Q. (2018). Developmental population neuroscience: emerging from ICHBD. *Sci. Bull.*, *63*(6), 331–332.

Zuo, X.-N., & Xing, X.-X. (2014). Test-retest reliabilities of resting-state FMRI measurements in human brain functional connectomics: A systems neuroscience perspective. *Neuroscience and Biobehavioral Reviews*, *45*, 100-118.

Zuo, X.-N., Xu, T., Jiang, L., Yang, Z., Cao, X.-Y., He, Y., . . . Milham, M. (2013). Toward reliable characterization of functional homogeneity in the human brain: Preprocessing, scan duration, imaging resolution and computational space. *NeuroImage*, *65*, 374-386.

Zuo, X.-N., Xu, T., & Milham, M. (2019). Harnessing reliability for neuroscience research. *Nature Human Behaviour*, *3*(8), 768-771.