Generalizing predictions to unseen sequencing profiles via deep generative models

Min Oh[1] and Liqing Zhang[1, *]

[1]Department of Computer Science, Virginia Tech, Blacksburg, VA, USA

[*]Correspondence: lqzhang@cs.vt.edu

Abstract

Predictive models trained on sequencing profiles often fail to achieve expected performance when

externally validated on unseen profiles. While many factors such as batch effects, small data sets, and

technical errors contribute to the gap between source and unseen data distributions, it is a challenging

problem to generalize the predictive models across studies without any prior knowledge of the unseen

data distribution. Here, this study proposes DeepBioGen, a sequencing profile augmentation procedure

that characterizes visual patterns of sequencing profiles, generates realistic profiles based on a deep

generative model capturing the patterns, and generalizes the subsequent classifiers. DeepBioGen

outperforms other methods in terms of enhancing the generalizability of the prediction models on unseen

data. The generalized classifiers surpass the state-of-the-art method, evaluated on RNA sequencing tumor

expression profiles for anti-PD1 therapy response prediction and WGS human gut microbiome profiles

for type 2 diabetes diagnosis.

Introduction

Predictive models relying on genomic signatures and biomarkers often suffer significantly inferior

performance in the independent validation on external data sets in biomedical research such as disease

diagnostics, prognostics, drug discovery, and precision medicine, resulting in a contribution to

reproducibility crisis[1-4]. Irreproducible models can lead to not only invalid conclusions misleading

subsequent studies but also a substantial waste of time and effort for researchers trying to commercialize

the models to benefit patients[5]. A major factor behind these failures is the lack of generalizability across

studies, in each of which the number of the heterogeneous data points is insufficient to obtain statistical

power to overcome the generalization barrier. In addition to the sample size, usually, there is a significant

gap between source data that are used to train classifiers and target data that are used to evaluate the

classifiers. One possible cause of the gap is the batch effect such as different sample cohorts, different lab

environments, and differences in experimental protocols across studies[4,6], which violates the assumption

that source and target data are drawn from the same distribution.

In many real-world applications, trained systems fail to produce accurate predictions for unseen data with

the shifted distribution. For example, illumination or viewpoint changes in data acquisition for an object

detection system and noisier environments for a speech-to-text translation system could easily disrupt the

desired outcome. To address this issue, domain adaptation algorithms have been proposed to better align

source and target data in a domain-invariant feature space when knowledge of target domains is available

during the training phase[7-9]. However, in practice, it is common that no clue on the target domain is

provided. As a more ambitious goal, domain generalization studies focus on training a model generalizing

to the unseen domain without any foreknowledge of the unseen domain. Recent studies proposed different

ways of domain generalization such as extracting domain-invariant features[10-12], leveraging self-

supervised tasks to guide and learn robust representation[13], simulating domain shift in meta-learning[14],

and adding perturbed samples[15,16]. Although these methods achieved promising performance on

benchmark data sets, their requirements, such as having datasets from multiple source domains or

sufficient enough for splitting and simulating domain shift, are often not satisfied in biomedical research

where only a limited number of heterogeneous data points in a single source domain is available.

Data augmentation techniques in the computer vision field show promising potential in improving

classifiers by reducing overfitting to source data[17-19]. Especially, recent advances in deep generative

models such as generative adversarial networks (GAN)[20] allow generating visual contents that are

indistinguishable from real ones and also augmenting image data to guide in finding better decision

boundaries[17,19]. More recently, generative models have been utilized to augment medical images,

including Magnetic Resonance Images (MRI)[21], computed tomography (CT)[22], and X-ray images[23].

However, there has been little effort in transferring the success in computer vision to biomedical

sequencing data[24], although some studies tried to leverage computer vision techniques by regarding non-

image data as image data[25-29]. Furthermore, it is unclear whether augmentation of sequencing data could

overcome the generalization barrier across different studies.

In this study, DeepBioGen, a data augmentation procedure that establishes visual patterns from

sequencing profiles and generates new sequencing profiles capturing the visual patterns based on

conditional Wasserstein GAN, is proposed to enhance the generalizability of the prediction models to

unseen data. DeepBioGen outperforms other augmentation methods in generalizing classifiers to unseen

data. Also, the classifiers generalized by DeepBioGen surpass state-of-the-art classifiers that are designed

to work on unseen profiles when tested on two scenarios: devising a prediction model for immune

checkpoint blockade (anti-PD1) responsiveness in melanoma patients based on RNA sequencing (RNA-

seq) data and building a diagnostic model for type 2 diabetes based on whole-genome metagenomic

sequencing data. DeepBioGen source code is free and available at

https://github.com/minoh0201/DeepBioGen.

Results

Formation and augmentation of visual patterns of sequencing profiles

Sequencing profiles, such as RNA-seq measurements of gene expression levels, consist of numerical

values that indicate the activity of thousands of genes in different samples or patients. While many

statistical methods such as multivariate linear regression assume that variables are independent of one

another, in reality, genes' activities are highly correlated[30]. In DeepBioGen, to take into account and

visually formalize the interactivity of related genes, similar features in the profiles were clustered together,

presenting visible patterns after converting numerical values to colors (Figure 1a; See Methods section).

Subsequently, a conditional Wasserstein GAN equipped with convolutional layers to capture the local

visual patterns was implemented to augment the sequencing profiles conditioned on class labels. During

the augmentation phase, multiple GANs were initialized and trained with different random seeds to

promote diversity in the augmented data points (Figure 1b).

To inspect the visual quality of augmented data, two different sequencing profiles were used to train the

generative models: one is RNA-seq expression profiles of melanoma patients, and the other is gut

microbiome profiles of type 2 diabetes patients (See 'sequencing profiles and pre-processing' in Methods

section and Supplementary Table S1 for details). Visual assessment showed that the augmented profiles

preserved the boundaries of the clustered features and within-cluster color patterns in the same manner as

source data. It is also difficult to distinguish an augmented profile from source data without the original

tag (Supplementary Figure S1 and S2).

87
Figure 1. DeepBioGen, a sequencing profile augmentation procedure that generalizes classifiers to

enhance prediction performance on unseen data. **a**, Feature-wise clustering of sequencing profiles to form

perceptible visual patterns. **b**, Training multiple conditional Wasserstein GANs equipped with up-

convolutional and convolutional layers. **c**, Generating augmented data from the multiple generators of

GAN models and learning classifiers based on the augmented data along with source data to predict

unseen data. **d-e**, Results of anti-PD1 therapy response prediction on unseen data by the state-or-the-art

and baseline classifiers (gray) and by classifiers generalized with DeepBioGen (red), SMOTE (green),

GMM (yellow), and Random augmentation (blue); Classification algorithms: Support Vector Machine

(SVM) and Neural network (NN) which is a multi-layer perceptron; Evaluation metric: Area under the

receiver operating characteristics (AUROC). **f-g**, Results of type 2 diabetes prediction on unseen data.

Generalized classification on unseen sequencing profiles

The augmented data derived from the multiple generators of GANs was injected into training data along

with the source data. The training data was used to train three machine learning classifiers, support vector

machine (SVM), an artificial neural network (NN), and random forest (RF) (Figure 1c). The classifiers

were trained to predict non-responders of cancer immunotherapy (anti-PD1) based on RNA-seq gene

expression profiles or type 2 diabetes based on human gut microbiome profile (See method section and

Supplementary Table S1).

To validate the generalizability of the classifiers, test (unseen) data were secured from studies that are

independent of the source studies. Classification performances on test data were evaluated using an area

under the receiver operating characteristics (AUROC) and an area under the precision-recall curve

(AUPRC). State-of-the-art predictors, TIDE[31] and IMPRES[32] for predicting patient response to anti-PD1

therapy, and DeepMicro[33] for using deep representations of microbiome data to predict disease states,

were compared to DeepBioGen. Besides, widely-used data augmentation techniques, such as Gaussian

Mixture Model (GMM)[34] and Synthetic Minority Over-sampling Technique (SMOTE)[35], were used to

generate augmented data for comparison. The classifiers trained only on source data were used as the

baseline comparison.

Remarkably, DeepBioGen-based classifiers surpass not only state-of-the-art classifiers but also classifiers

that are trained on augmented data generated by different augmentation methods in both immunotherapy

response (Figure 1d-e, Supplementary Figure S3, and Supplementary Table S4) and diabetes predictions

(Figure 1f-g, Supplementary Figure S3, and Supplementary Table S5). Notably, even though

DeepBioGen-based classifiers have no clue of test data, it outperforms Gide et al.'s immune marker

classifier (AUROC=0.77) that directly leverages the test data through differential expression analysis[36].

Especially, DeepBioGen provides a stable performance boost to SVM and NN classifiers for both

problems as the augmentation rate increases. RF classifiers partially benefit from DeepBioGen, showing

generally worse performance than SVM and NN classifiers (Supplementary Figure S4). Consistently,

DeepBioGen reduces $\mathcal{H}$-divergence between the source data and the test data more than other

augmentation methods, which explains its better generalizability over others (Table 1).

Table 1. $\mathcal{H}$-divergence between source and test data

Data type	DeepBioGen	SMOTE	GMM	Random
RNA-seq tumor expression profile	**0.368**	0.688	0.512	0.888
WGS human gut microbiome profile	**0.268**	0.288	0.352	0.858

Impact of visualized clusters and multiple generators

DeepBioGen uses the elbow method[37] to estimate the optimal number of clusters and GANs (See

'Formation of visual patterns from sequencing profiles' in Methods section). To assess the ability of the

approach in inferring the ideal parameters based on source data only, DeepBioGen models with a varying

number of clusters or GANs were used to generate the augmented data for training classifiers. The

classification results of unseen data show that the elbow method elicits an optimal or nearly optimal

number of clusters and GANs in both immunotherapy response and diabetes prediction problems

(Supplementary Figure S5-S8).

Notably, the number of clusters has more impact on classification performance than the number of GANs,

suggesting that how sequencing data are clustered and thus presented visually plays a major role in

improving the generalizability of DeepBioGen (Supplementary Figure S5-S8). Results also show that

diverse generators of multiple Wasserstein GANs are more effective in diversifying the augmented

sequencing data than a single generator, thus leading to better generalizability (Supplementary Table S3).

Augmentations beyond the boundary of source data

To visualize how DeepBioGen augmented data to generalize classifiers, the source, augmented and test

data were embedded to 2-dimensional space with t-distributed stochastic neighbor embedding (t-SNE)

algorithm[38]. We note that t-SNE embedding preserves pairwise Euclidean distance in the 256-D space in

both melanoma patient profiles and microbiome profiles (Pearson correlation r = 0.881 and r = 0.807).

In melanoma patient profiles, the source and test data are placed distantly, while within-cluster data points

with different anti-PD1 responses are located closely in both data clusters (Figure 2a). The data

embeddings were plotted separately for two classes, and an empirical outer boundary of the source data

based on the outermost data points heading toward the test data was drawn with a red dotted line (Figure

2c and 2e). Interestingly, DeepBioGen generated data points (Figure 2b) beyond the outer boundaries of

the source data cluster (Figure 2d and 2f), whereas other augmentation methods rarely produced data

points that cross the boundaries (Supplementary Figure S7-S9).

In microbiome profiles of healthy controls and diabetic patients, the test data cluster resides in the side

region of the source data cluster, thus depicting a moderately shifted distribution (Supplementary Figure

S12). DeepBioGen produced augmented microbiome profiles across boundaries of the source data cluster.

Particularly, the outermost augmented data points beyond the source boundaries are closely placed with

test data points that cross the border (Supplementary Figure S12), while other methods rarely generate

data points overpassing the boundaries (Supplementary Figure S13-S15).

Figure 2. t-SNE visualization of augmented tumor expression profiles derived from DeepBioGen along with the source (grey), augmented (green), and test (unseen, red) data of melanoma patients treated with anti-PD1 therapy. **a**, The source and test data. **b**, The source, test, and augmented data. **c**, Responders of

the source and test data; An empirical boundary of responders of source data (red dotted line). **d**,

Responders of the source, test, and augmented data. **e**, Non-responders of the source and test data; An

empirical boundary of non-responders of source data (red dotted line). **f**, Non-responders of the source,

test, and augmented data.

Progression-free survival analysis of predicted anti-PD1 treatment responders

For the predicted responder (PR) and non-responder (PNR) patients to anti-PD1 treatment determined by

DeepBioGen-supported SVM classifier, progression-free survival analysis was conducted to estimate the

clinical outcome. For comparison, state-of-the-art classifiers based on genomic signatures, IMPRES and

TIDE, were evaluated with the same analysis. With the DeepBioGen classifier or IMPRES, the PR group

has a significantly longer progression-free survival rate compared to the PNR group (Figure 3a and 3b),

whereas the two TIDE predicted groups do not show a significant difference.

Importantly, the median survival time of PRs classified by the DeepBioGen classifier was 755 days (95%

CI [335, N/A]), compared to 440 days (95% CI [125, N/A]) for the IMPRES classified PRs . Also, the

DeepBioGen classifier tends to be more sensitive in predicting responders than IMPRES, likely posing a

lower risk of unnecessary treatment suggestions often accompanied by unnecessary side effects (Figure 3

and Table 2).

Figure 3. Kaplan-Meier plots of progression-free survival for predicted responder (PR) and non-

responder (PNR) patients determined by three classifiers. **a**, generalized SVM classifier with DeepBioGen

augmentations. **b**, IMPRES. **c**, TIDE.

Table 2. Summary statistics for progression-free survival analysis

Classifier	Prediction	N	Median survival time (days)	95% CI	MR*	HR**	95% CI	*P*-value
DeepBioGen-SVM	PR	27	755	[335, NA]	9.21	3.72	[1.88, 7.36]	< 0.001
	PNR	23	82	[76, 125]				
IMPRES	PR	40	440	[125, NA]	5.71	3.47	[1.66, 7.49]	0.002
	PNR	10	77	[58, NA]				
TIDE	PR	40	231	[82, 870]	0.76	0.99	[0.45, 2.17]	> 0.9
	PNR	10	303	[96, NA]				

192   *Median ratio; **Hazard ratio

Discussion

DeepBioGen provides a framework for effective data augmentation in sequencing profiles that can be used to boost the training data and improve the performance of prediction models on unseen data. It adversarially learns multiple generative models that capture visual signals from source data. With multiple generators, DeepBioGen generates realistic augmented data beyond the boundary of the source domain. The augmented data can be used to amplify training data and train classifiers resilient to unknown domain shifts. Consequently, DeepBioGen can improve the transferability and reproducibility of the prediction models without any knowledge of unseen data.

The stable performance over augmentation rate with DeepBioGen was observed with SVM and NN applications but not in RF. One of the possible reasons might be related to the fact that SVM and NN are the methods approximating decision boundary, while RF is aggregating results from bootstrapping. Augmentations could introduce relatively fewer variations on smoothing decision boundaries as source data always preserves its contribution to the decision boundaries, whereas augmentation together with bootstrapping could have a negative impact on performance because bootstrapped samples may have too little purity to reasonably optimize the best split.

DeepBioGen is unique as it takes input sequencing profiles in machine-understandable visual form, while visualization of sequencing data (e.g. heatmap of differentially expressed genes) has been typically used to present findings in a human-understandable manner. One potential advantage of feeding DeepBioGen with visually recognizable data is that visual patterns difficult to be identified with human eyes may be captured and characterized in embedding space.

Even with a limited amount of source data, DeepBioGen can alleviate batch effects of independent studies without details for batch correction such as sample cohorts, lab environments, and experimental protocol, by reducing the gap between the source and unseen data. Also, DeepBioGen is highly extensible to other biological data whose feature dependency is not negligible.

One limitation of this study is that there is no theoretical guarantee of improvement for other datasets

except the ones tested in this paper. For example, if domain shift is severe enough so that there is no

similarity between source and test data at all, the augmentations may not be helpful to improve

performance. Also, depending on how hard the classification problem is and how stable the optimization

of hyper-parameters in the experiment is, given the limited data, the performance on unseen data could be

impacted. Conducting cross-validation for different splits within source data or combined source and test

data could be a good way to fathom these properties. We conducted 5-fold cross-validation on source data

and repeated ten times with different random splits to evaluate the prediction performance (Table S6 and

S7). We also conducted 5-fold cross-validation on the combined source and test data with random splits

for ten times (Table S8 and S9). We found that the performance of different classification models was

significantly better than random guessing and the performance variations could be reduced by adding

more data points.

It is also worth mentioning that there should be some sort of similarity between the source and unseen

data for classifiers to take the advantage of the augmentations. Without similarity, it is hard to expect an

improvement of performance on unseen data. We tried to find underlying common properties of source

and unseen data to understand the reason that classifiers perform relatively well on unseen data with

limited data points in high-dimensional space. We extracted the most important 25 features out of the 256

features from both the source and test data (based on Gini index with decision tree algorithm to predict

class labels) and checked the number of overlapping features. Interestingly, we found statistical

significance in the overlaps: 12 features are overlapping for the tumor expression data set (one-tailed

fisher's exact test $p = 0.00001$) and 6 features for microbiome data (one-tailed fisher's exact test $p =$

0.0231). This reveals that there are some shared properties between the source and test data which may in

turn contribute to the success of using augmented data for improving classification performance.

In the future study, it is envisioned that the process of forming visual patterns from sequencing profiles

can be learned with cutting-edge machine learning models toward the better formation of machine-

understandable patterns.

Methods

Sequencing profiles and pre-processing

Clinical genomic data containing RNA-seq tumor expression profiles of melanoma patients and their

responsiveness to anti-PD1 therapy were secured from three independent studies[36,39,40] (Supplementary

Table S1). Fifty samples in the most recent study[31] were used as test data and the others were used as

source data. RNA-seq read counts were normalized to transcripts per million (TPM) and then log2-

transformed. To focus on genes related to primary mechanisms of tumor immune evasion, recently

identified T cell signature genes[31], such as regulators of T cell dysfunction and suppressors of T cell

infiltration into the tumor, were selected out of 18,570 common genes across the studies. In total, 702

genes were considered as features of initial inputs.

Human gut metagenomic sequencing reads of type 2 diabetic patients and healthy controls were acquired

from two independent studies: one on the Chinese cohort[41] and the other on the European women cohort[42]

(Supplementary Table S1). Using MetaPhlAn2[43], strain-level marker profiles were extracted from the

metagenomic samples. In total, the number of common strain-level markers that are considered as initial

features was 74,240. The European samples in the more recent study were used as test data and Chinese

samples as source data.

Formation of visual patterns from sequencing profiles

Each measurement in source data was standardized by subtracting the mean and dividing by the standard

deviation. The same standardization was applied to test data using the mean and standard deviation of

source data. To meet the dimensional requirement of the pre-defined input layer, the extremely

randomized trees[44] feature selection algorithm was applied to the source data to select 256 features. The

k-means clustering algorithm was used to cluster features, minimizing squared Euclidean distances

between centroid and within-cluster features. Based on the elbow point where the within-cluster sum of

squared errors (WSS) starts to decrease significantly, the optimal number of clusters was determined to be

4 for RNA-seq tumor expression profiles and 6 for human gut microbiome profiles (Supplementary

Figure S16). The selected features were then sorted and rearranged by cluster labels so that similar

features are placed nearby. The features of test data were also rearranged in the same order.

Augmentation of sequencing profiles based on their visual patterns

DeepBioGen captures local visual patterns of sequencing profiles by training conditional Wasserstein

GAN, whose generator and critic networks are composed of up-convolutional and convolutional layers,

respectively. The generator tries to generate realistic images enough to fool the critic, whereas the critic

tries to assign higher values for real images than for generated images. During training, the generator and

the critic progressively become better at their jobs by competing against each other. This adversarial

training can be conducted by optimizing a minimax objective. Wasserstein distance (or Earth Mover)

formulated by Kantorovich-Rubinstein duality is used in the objective term for better reaching Nash

equilibrium[45]. Also, the gradient penalty is applied to the objective function to enforce the Lipschitz

constraint, alleviating potential instability in the critic[46]. Generator function G and critic function C are

conditioned on the class label y and the final objective function of conditional Wasserstein GAN is as

follows:

$$\min_{G} \max_{C} \mathbb{E}_{z \sim p(z)}\big[C\big(G(z|y)\big)\big] - \mathbb{E}_{x \sim P_r}[C(x|y)] - \mathbb{E}_{\hat{x} \sim P_{\hat{x}}}[(\|\nabla_{\hat{x}} C(\hat{x}|y)\|_2 - 1)^2]$$

where z denotes a random noise vector derived from random noise distribution $p(z)$, x a real profile

derived from the real data distribution P_r, and $\hat{x} \sim P_{\hat{x}}$ sampling uniformly along straight lines connecting

the real data distribution P_r and the output distribution of generator $P_g = G(z|y)$. The gradient penalty

term directly constrains the norm of the critic's output concerning its input, enforcing the Lipschitz

constraint along the straight lines.

The architecture of neural networks that approximate generator function G and critic function C is

illustrated in Supplementary Figure S17. The generator begins with two input layers, one for receiving a

random noise vector and the other for a class label, followed by dense (64 units) and embedding layers

(50 units). Embedded random noise vector and label vector are reshaped and concatenated. Subsequently,

two up-convolutional blocks, composed of an up-convolutional layer, batch normalization layer, and

Leaky ReLU activation layer, perform inverse convolution operations. Lastly, the final up-convolutional

layer produces generated sequencing profile. Note that each sequencing profile is considered as a 1x256

pixel image in a single channel. Similarly, the critic has two input layers, one for sequencing profile and

the other for a class label, which is embedded, reshaped, and concatenated onto the sequencing profile

vector. The two consecutive convolutional blocks, each of which consists of a convolutional layer, Leaky

ReLU activation, and dropout layer, are followed by the output layer with a single unit. Across the

generator and critic, the alpha value of Leaky ReLU is set as 0.3, and the dropout rate is set at 0.3.

To achieve better generalization, multiple clones of the GAN are trained in the same way except for initial

weights in the neural networks. The number of desired GANs is estimated by approximating modes of

samples with the elbow method under the assumption that most modes are generated if the number of

generators is at least as many as the number of modes in source data (Supplementary Figure S18).

Individual generators produce the same number of augmented data points.

Generalized predictions on unseen sequencing profiles

To generalize classifiers predicting clinical outcomes or disease states to unseen data, three classifiers,

SVM, NN, and RF, were built on training data composed of source and augmented sequencing profiles.

Hyper-parameters of the classifiers were optimized based only on source data with a 5-fold cross-

validation scheme. Grid search was applied to explore hyper-parameter space (see details in

Supplementary Table S2). With the best hyper-parameters, prediction models were trained on the pooled

source and augmented data. The generalizability and performance of the prediction models were

evaluated on the unseen test data using AUROC and AUPRC. The performance evaluation was repeated

by gradually changing the augmentation rate indicating how many times the size of augmented data is of

the source data.

For comparison, state-of-the-art classifiers designed to work on unseen data, including TIDE[31], IMPRES[32],

and DeepMicro[33], were evaluated on test data. TIDE predicts anti-PD1 responsiveness of melanoma

patients based on genome-wide expression signatures of T cell dysfunction and exclusion. To satisfy its

requirement, the test data without filtering out any genes from the original data was submitted to the

TIDE response prediction web service. IMPRES is a predictor of anti-PD1 response in melanoma patients,

which is a rule-based classifier manually built based on gene expression relationships between immune

checkpoint gene pairs. Its source code was utilized to evaluate the performance of IMPRES on the test

data. DeepMicro is a deep representation learning framework for improving predictors based on

microbiome profiles. The source data was utilized to learn a low-dimensional representation of the

microbiome data, and classifiers were then trained on the representation and evaluated on the test data.

Furthermore, as an alternative to DeepBioGen, widely-used data augmentation approaches, including

GMM[34] and SMOTE[35], as well as statistics-based random augmentation were evaluated. An independent

GMM model was fitted for each class label, and the optimal number of components in the GMM model

was estimated with the Bayesian information criterion (BIC). SMOTE derives the generated samples from

linear combinations of nearest neighboring samples. Random augmentation draws data points from the

normal distribution whose mean and standard deviation are the same as those of the source data, assigning

an arbitrary class label. Also, as a baseline comparison, machine learning classifiers that are trained only

on source data (i.e., no augmented data) were evaluated on test data.

To understand the impact of generalization on reducing the discrepancy between the source and test data,

a classifier-induced divergence measure, $\mathcal{H}$-divergence, was determined with various classifiers. For a

given set of binary hypotheses $\mathcal{H} \subseteq \{h\colon X \to \{0,1\}\}$, $\mathcal{H}$-divergence is the largest possible difference

between probabilities of being classified as 1 in source and test distributions[47,48]. More formally, the

empirical $\mathcal{H}$-divergence can be written as:

$$d_{\mathcal{H}}(D_S, D_T) = 2 \sup_{h \in \mathcal{H}} \left| P_{x \sim D_S}[h(x) = 1] - P_{x \sim D_T}[h(x) = 1] \right|$$

347   where D_S and D_T are the source and test data, respectively, and

$$P_{x \sim D}[h(x) = 1] = \frac{|\{x\colon x \in D, h(x) = 1\}|}{|D|}$$

As a proxy of $\mathcal{H}$ for each augmentation method, all classifiers trained on the augmented training data by

varying an augmentation rate and classification algorithms were included in a set of binary hypotheses.

Impact of multiple generators on the diversity of generated sequencing profiles

Wasserstein GAN may suffer less from mode collapse than infant GAN relying on Jensen-Shannon

divergence in its loss term[45]. However, a single Wasserstein GAN may not be able to produce all modes

of data, and it can be hypothesized that multiple Wasserstein GANs may increase the diversity of

augmented sequencing profiles. To evaluate the diversity of the augmented profiles generated with

multiple Wasserstein GANs, the adapted inception score is used. Originally, the inception score was

introduced to evaluate the quality and diversity of generated images based on the predicted class

probability distributions derived from a pre-trained Inception v3 model[49]. More recently, Gurumurthy et

al. suggested a modified inception score considering within-class diversity of the generated data[50], and

this scoring method is used in the current evaluation. Also, according to the note that non-ImageNet data

generator should not be evaluated by the Inception v3 classifier[51], it is replaced with the best performing

baseline-classifier trained only on source data. Consequently, the adapted inception score ranges from 1 to

2, and the higher the score, the better the diversity and quality of the augmented profiles.

t-SNE visualization of the augmented data

To visualize how augmented data is arranged in a high-dimensional space, the augmented data along with

source and test data was embedded into a 2-dimensional space using t-SNE. Also, a class-specific

boundary of the source data cluster facing the test data cluster in the embedded space was drawn with one

or two straight lines through the outermost data points of the source data cluster.

Progression-free survival analysis

The Kaplan-Meier plots were drawn to conduct progression-free survival analysis for predicted responder

and non-responder patients. For each classifier, a receiver operating characteristic (ROC) curve was used

to determine the cut-off value of predictions. The closest point from (0, 1) on the ROC curve was chosen,

at which the threshold well balancing true positive rate and false-positive rate is identified. The log-rank

test was used to validate statistical significance.

References

1.   Baker, M. 1,500 scientists lift the lid on reproducibility. *Nature* **533**(2016).

2. Bernau, C. *et al.* Cross-study validation for the assessment of prediction algorithms. *Bioinformatics* **30**, i105-i112 (2014).

3. Castaldi, P.J., Dahabreh, I.J. & Ioannidis, J.P. An empirical assessment of validation practices for molecular classifiers. *Briefings in bioinformatics* **12**, 189-202 (2011).

4. Collins, F.S. & Tabak, L.A. Policy: NIH plans to enhance reproducibility. *Nature* **505**, 612-613 (2014).

5. Mattsson-Carlgren, N., Palmqvist, S., Blennow, K. & Hansson, O. Increasing the reproducibility of fluid biomarker studies in neurodegenerative studies. *Nature communications* **11**, 1-11 (2020).

6. Leek, J.T. *et al.* Tackling the widespread and critical impact of batch effects in high-throughput data. *Nature Reviews Genetics* **11**, 733-739 (2010).

7. Ganin, Y. *et al.* Domain-adversarial training of neural networks. *The Journal of Machine Learning Research* **17**, 2096-2030 (2016).

8. Hoffman, J. *et al.* Cycada: Cycle-consistent adversarial domain adaptation. in *Proceedings of the International Conference on Machine Learning* 1989-1998 (ICML, 2018).

9. Saenko, K., Kulis, B., Fritz, M. & Darrell, T. Adapting visual category models to new domains. in *Proceedings of the European Conference on Computer Vision* 213-226 (ECCV, 2010).

10. Li, H., Jialin Pan, S., Wang, S. & Kot, A.C. Domain generalization with adversarial feature learning. in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition* 5400-5409 (CVPR, 2018).

11. Li, Y. *et al.* Deep domain generalization via conditional invariant adversarial networks. in *Proceedings of the European Conference on Computer Vision* 624-639 (ECCV, 2018).

12. Matsuura, T. & Harada, T. Domain Generalization Using a Mixture of Multiple Latent Domains. in *Proceedings of the Thirty-Fourth AAAI Conference on Artificial Intelligence* 11749-11756 (AAAI, 2020).

13. Carlucci, F.M., D'Innocente, A., Bucci, S., Caputo, B. & Tommasi, T. Domain generalization by solving jigsaw puzzles. in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition* 2229-2238 (CVPR, 2019).

14. Li, D., Yang, Y., Song, Y.-Z. & Hospedales, T. Learning to generalize: Meta-learning for domain generalization. in *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence* 3490-3497 (AAAI, 2018).

15. Shankar, S. *et al.* Generalizing Across Domains via Cross-Gradient Training. in *Proceedings of the International Conference on Learning Representations* (ICLR, 2018).

16. Volpi, R. *et al.* Generalizing to unseen domains via adversarial data augmentation. in *Proceedings of the 32nd International Conference on Neural Information Processing Systems* 5339-5349 (2018).

17. Antoniou, A., Storkey, A. & Edwards, H. Data augmentation generative adversarial networks. *arXiv preprint arXiv:1711.04340* (2017).

18. Wong, S.C., Gatt, A., Stamatescu, V. & McDonnell, M.D. Understanding data augmentation for classification: when to warp? in *Proceedings of the International Conference on Digital Image Computing: techniques and applications* 1-6 (IEEE DICTA, 2016).

19. Zhang, X., Wang, Z., Liu, D. & Ling, Q. Dada: Deep adversarial data augmentation for extremely low data regime classification. in *Proccedings of the International Conference on Acoustics, Speech and Signal Processing* 2807-2811 (IEEE ICASSP, 2019).

20. Goodfellow, I. *et al.* Generative adversarial nets. *Advances in neural information processing systems* **27**, 2672-2680 (2014).

21. Calimeri, F., Marzullo, A., Stamile, C. & Terracina, G. Biomedical data augmentation using generative adversarial neural networks. in *International conference on artificial neural networks* 626-634 (Springer, 2017).

22. Sandfort, V., Yan, K., Pickhardt, P.J. & Summers, R.M. Data augmentation using generative
adversarial networks (CycleGAN) to improve generalizability in CT segmentation tasks. *Scientific*
reports **9**, 1-9 (2019).
23. Madani, A., Moradi, M., Karargyris, A. & Syeda-Mahmood, T. Chest x-ray generation and data
augmentation for cardiovascular abnormality classification. in *Proccedings of the International*
Society for Optics and Photonics Vol. 10574 105741M (2018).
24. Marouf, M. *et al.* Realistic in silico generation and augmentation of single-cell RNA-seq data
using generative adversarial networks. *Nature communications* **11**, 1-12 (2020).
25. Dovhalets, D., Kovalerchuk, B., Vajda, S. & Andonie, R. Deep learning of 2-d images representing
nd data in general line coordinates. in *International Symposium on Affective Science and*
Engineering ISASE2018 1-6 (Japan Society of Kansei Engineering, 2018).
26. Sharma, A., Vans, E., Shigemizu, D., Boroevich, K.A. & Tsunoda, T. DeepInsight: A methodology
to transform a non-image data to an image for convolution neural network architecture.
Scientific reports **9**, 1-7 (2019).
27. Sharma, A. & Kumar, D. Non-image data classification with convolutional neural networks. *arXiv*
preprint arXiv:2007.03218 (2020).
28. Rodrigues, N.M. *et al.* Plotting time: on the usage of CNNs for time series classification. *arXiv*
preprint arXiv:2102.04179 (2021).
29. Kovalerchuk, B., Agarwal, B. & Kall, D.C. Solving non-image learning problems by mapping to
images. in *2020 24th International Conference Information Visualisation (IV)* 264-269 (IEEE,
2020).
30. Emilsson, V. *et al.* Genetics of gene expression and its effect on disease. *Nature* **452**, 423-428
(2008).
31. Jiang, P. *et al.* Signatures of T cell dysfunction and exclusion predict cancer immunotherapy
response. *Nature medicine* **24**, 1550-1558 (2018).
32. Auslander, N. *et al.* Robust prediction of response to immune checkpoint blockade therapy in
metastatic melanoma. *Nature medicine* **24**, 1545-1549 (2018).
33. Oh, M. & Zhang, L. DeepMicro: deep representation learning for disease prediction based on
microbiome data. *Scientific reports* **10**, 1-9 (2020).
34. Reynolds, D.A., Quatieri, T.F. & Dunn, R.B. Speaker verification using adapted Gaussian mixture
models. *Digital signal processing* **10**, 19-41 (2000).
35. Chawla, N.V., Bowyer, K.W., Hall, L.O. & Kegelmeyer, W.P. SMOTE: synthetic minority over-
sampling technique. *Journal of artificial intelligence research* **16**, 321-357 (2002).
36. Gide, T.N. *et al.* Distinct immune cell populations define response to anti-PD-1 monotherapy and
anti-PD-1/anti-CTLA-4 combined therapy. *Cancer cell* **35**, 238-255. e6 (2019).
37. Thorndike, R.L. Who belongs in the family? *Psychometrika* **18**, 267-276 (1953).
38. Maaten, L.v.d. & Hinton, G. Visualizing data using t-SNE. *Journal of machine learning research* **9**,
2579-2605 (2008).
39. Hugo, W. *et al.* Genomic and transcriptomic features of response to anti-PD-1 therapy in
metastatic melanoma. *Cell* **165**, 35-44 (2016).
40. Riaz, N. *et al.* Tumor and microenvironment evolution during immunotherapy with nivolumab.
Cell **171**, 934-949. e16 (2017).
41. Qin, J. *et al.* A metagenome-wide association study of gut microbiota in type 2 diabetes. *Nature*
490, 55-60 (2012).
42. Karlsson, F.H. *et al.* Gut metagenome in European women with normal, impaired and diabetic
glucose control. *Nature* **498**, 99-103 (2013).
43. Truong, D.T. *et al.* MetaPhlAn2 for enhanced metagenomic taxonomic profiling. *Nature methods*
12, 902-903 (2015).

44.   Geurts, P., Ernst, D. & Wehenkel, L. Extremely randomized trees. *Machine learning* **63**, 3-42
478   (2006).
479   45.   Arjovsky, M., Chintala, S. & Bottou, L. Wasserstein generative adversarial networks. in
480   *International conference on machine learning* 214-223 (PMLR, 2017).
481   46.   Gulrajani, I., Ahmed, F., Arjovsky, M., Dumoulin, V. & Courville, A. Improved training of
482   wasserstein gans. *arXiv preprint arXiv:1704.00028* (2017).
483   47.   Ben-David, S., Blitzer, J., Crammer, K. & Pereira, F. Analysis of representations for domain
484   adaptation. *Advances in neural information processing systems* **19**, 137 (2007).
485   48.   Kifer, D., Ben-David, S. & Gehrke, J. Detecting change in data streams. in *VLDB* Vol. 4 180-191
486   (Toronto, Canada, 2004).
487   49.   Salimans, T. *et al.* Improved techniques for training GANs. in *Proceedings of the 30th*
488   *International Conference on Neural Information Processing Systems* 2234-2242 (2016).
489   50.   Gurumurthy, S., Kiran Sarvadevabhatla, R. & Venkatesh Babu, R. Deligan: Generative adversarial
490   networks for diverse and limited data. in *Proceedings of the IEEE conference on computer vision*
491   *and pattern recognition* 166-174 (2017).
492   51.   Barratt, S. & Sharma, R. A note on the inception score. *arXiv preprint arXiv:1801.01973* (2018).

493