de novo identification of maximally deregulated subnetworks based on multi-omics data with DeRegNet

Sebastian Winkler[1,2]*, **Ivana Winkler**[2,3,4], **Mirjam Figaschewski**[1], **Thorsten Tiede**[1], **Alfred Nordheim**[2,3,4,5], **Oliver Kohlbacher**[1,2,6,7]

*For correspondence:
sebastian.winkler@dereg.net (SW)

[1]Applied Bioinformatics, Dept. of Computer Science, University of Tübingen, Tübingen, Germany; [2]International Max Planck Research School (IMPRS) "From Molecules to Organisms", Tübingen, Germany; [3]Interfaculty Institute for Cell Biology (IFIZ), University of Tübingen, Tübingen, Germany; [4]German Cancer Consortium (DKTK), German Cancer Research Center (DKFZ), Heidelberg, Germany; [5]Leibniz Institute on Aging (FLI), Jena, Germany; [6]Institute for Bioinformatics and Medical Informatics, University of Tübingen, Tübingen, Germany; [7]Translational Bioinformatics, University Hospital Tübingen, Tübingen, Germany

Abstract   With a growing amount of (multi-)omics data being available, the extraction of knowledge from these datasets is still a difficult problem. Classical enrichment-style analyses require predefined pathways or gene sets that are tested for significant deregulation to assess whether the pathway is functionally involved in the biological process under study. *De novo* identification of these pathways can reduce the bias inherent in predefined pathways or gene sets. At the same time, the definition and efficient identification of these pathways *de novo* from large biological networks is a challenging problem. We present a novel algorithm, DeRegNet, for the identification of maximally deregulated subnetworks on directed graphs based on deregulation scores derived from (multi-)omics data. DeRegNet can be interpreted as maximum likelihood estimation given a certain probabilistic model for de-novo subgraph identification. We use fractional integer programming to solve the resulting combinatorial optimization problem. We can show that the approach outperforms related algorithms on simulated data with known ground truths. On a publicly available liver cancer dataset we can show that DeRegNet can identify biologically meaningful subgraphs suitable for patient stratification. DeRegNet is freely available as open-source software.

Introduction

Modern high-throughput technologies, in particular massively parallel sequencing (*Wang et al., 2009*) and high-resolution mass spectrometry (*Altelaar et al., 2013*), enable omics technologies, i.e. the determination of bioanalytes on the genome-wide scale. Many of of these omics technologies are increasingly being applied in clinical settings and publicly available large-scale data resources such as The Cancer Genome Atlas (TCGA) (*Tomczak et al., 2015*) provide ample opportunity for research. These resources can provide valuable reference data sets in the analysis of molecular profiles of individual patients and patient groups. However, one of the biggest challenges in the analysis of omics data remains functional annotation/interpretation. The interpretation of the experimental read-outs with the goal of understanding the underlying known or unknown biological

processes and functions is a vital step in providing personalized, precise, and focused molecular therapies.

One of the most widely used approaches for functional annotation of large omics datasets is Gene Set Enrichment (GSE) (*Maciejewski, 2014*). In its most basic form, GSE entails hypergeometric and Fisher test-based approaches to detect the overrepresentation of differentially expressed genes. GSE requires a set of predefined gene sets (typically obtained from pathway databases (*D'Eustachio, 2013*) such as KEGG (*Kanehisa et al., 2017*), WikiPathways (*Kutmon et al., 2016*) or Reactome (*Fabregat et al., 2018*)) and a measure of "deregulation" (e.g., a binary indication of differential gene expression). The goal of the GSE analysis is to identify those gene sets from the collection which show "high" deregulation. Here, the term "high" is defined by the method's specific underlying statistical model. In the simplest case, the method examines if each gene set contains a higher number of differentially expressed genes than would be expected by chance, under the assumption that differentially expressed genes are represented uniformly across all genes. Many adaptations and variations of GSE exist (*Maciejewski, 2014*; *Subramanian et al., 2005*).

Classical GSE methods treat pathways as an unstructured collection of genes and do not explicitly account for the extensive biological knowledge encoded in biological networks. Networks as an abstraction for biological knowledge can be represent signaling networks, metabolic networks (*Caspi et al., 2013*), gene regulatory networks (*Biggin, 2011*), or protein-protein interaction networks (*Li et al., 2017*; *Szklarczyk et al., 2017*), and more.

There has been extensive research into the possibility of designing enrichment methods which take into account the topology of the pathways (*Jaakkola and Elo, 2016*; *Mitrea et al., 2013*; *Ihnatova et al., 2018*). An example of such approach is the calculation of topology-dependent perturbation scores for each gene (*Tarca et al., 2009*). A further aspect usually ignored by GSE methods is the issue of pathway crosstalks. While 'textbook pathways' have a solid base in biological findings and can provide useful guidance for functional interpretation of omics experiments, molecular and cellular events are often more complicated and involve the direct interaction of molecular entities across predefined pathway boundaries. Correspondingly, a range of methods were proposed which aim to extract "deregulated" patterns from larger regulatory networks without relying on predefined pathways (*Mitra et al., 2013*; *Batra et al., 2017*). These methods are often referred to as *de novo* pathway enrichment (de novo pathway identification, de novo subnetwork/subgraph enrichment/identification/detection) methods, emphasizing that the pathways are defined/extracted from the data itself and are not given as fixed gene sets. Here, we also call algorithms of this flavor deregulated subnetwork/subgraph detection/identification/enrichment methods.

A way to categorize these methods is based on how they handle undirected or directed interaction networks. A lot of biomolecular interactions are directed in nature, e.g. protein A phosphorylates protein B, enzyme A precedes enzyme B in a metabolic pathway in contrast to symmetric interactions such as physical interactions of proteins in protein complexes.

Some methods designed for undirected networks are described in the following studies: *Ideker et al.* (*2002*); *Patil and Nielsen* (*2005*); *Ulitsky and Shamir* (*2007*); *Dittrich et al.* (*2008*); *Zhao et al.* (*2008*); *Ulitsky and Shamir* (*2009*); *Ulitsky et al.* (*2010*); *Dao et al.* (*2011*); *Bailly-Bechet et al.* (*2011*); *Alcaraz et al.* (*2012*, 2014, 2016). More detailed review of these method is available in *Batra et al.* (*2017*). These methods, while achieving similar results on an abstract level, vary greatly in terms of suitable underlying networks, interpretation of outcomes and algorithmic strategies employed. Algorithmic approaches employed include ant colony optimization (*Alcaraz et al., 2016*), dynamic programming (*Dao et al., 2011*), simulated annealing (*Ideker et al., 2002*), integer programming (*Zhao et al., 2008*; *Dittrich et al., 2008*), Markov random fields (*Vaske et al., 2010*) or message passing approaches (*Bailly-Bechet et al., 2011*).

Also, some methods are tailored to the characteristics of a particular data type. An example are methods attempting to find significantly mutated pathways/networks (*Vandin et al., 2016*, *2012a*; *Zhang and Zhang, 2018*; *Cerami et al., 2010*; *Hofree et al., 2013*; *Vandin et al., 2012b*), trying to factor in the pecularities of mutation data in a network context.

While methods which work natively with directed networks are rarer (*Keller et al., 2009*; *Backes*
et al., 2012; *Atias and Sharan, 2013*; *Gaire et al., 2013*), it seems instrumental to be able to cap-
ture the effects of directed biomolecular interactions in the process of discovering deregulated
networks. One particular approach is the one described in *Backes et al.* (*2012*) which utilized an in-
teger programming approach in order to find deregulated subnetworks. It uncovers deregulated
subnetworks downstream or upstream of a so called root node where the latter can be fixed *a*
priori or determined by the algorithm itself.
In this paper, we present an algorithm for de novo subnetwork identification which can con-
ceptually be characterized as a mixture of the approach presented by (*Backes et al., 2012*) and the
price-collecting Steiner tree methods proposed in (*Huang and Fraenkel, 2009*; *Huang et al., 2013*;
Gosline et al., 2012; *Tuncbag et al., 2013*, *2016*). Our method natively handles directed interac-
tion networks and adapts from *Backes et al.* (*2012*) the general integer programming approach
in such a way that it can encapsulate the general idea of sources and targets as put forward in
the price-collecting Steiner tree/forest (PCST/PCSF) approaches (*Huang and Fraenkel, 2009*; *Huang*
et al., 2013; *Gosline et al., 2012*; *Tuncbag et al., 2013*, *2016*) which capture the idea of deregu-
lated networks starting or ending at certain types of nodes, for example membrane receptors and
transcription factors. Methodologically, we extend the integer programming approach of (*Backes*
et al., 2012) to fractional integer programming to allow for the necessary flexibility to incorporate
sources and targets. Furthermore, we show that our algorithm, DeRegNet, can be interpreted as
maximum likelihood estimation under a certain natural statistical model. We demonstrate DeReg-
Net's suitability as an exploratory hypothesis generation tool by applying it to TCGA liver cancer
data. We introduce a personalized approach to interpreting cancer data and introduce the notion
of network-defined cancer genes which allow to identify patient groups based on their similarity
of their detected personalized subgraphs.[1]

Methods and Materials

DeRegNet: a de-novo subnetwork identification algorithm

Formal setting and definitions
Formally, it is given a directed graph $G = (V, E)$, i.e. $E \subset V \times V$, representing knowledge about
biomolecular interactions in some way. To avoid certain pathologies in the models defined below,
it is assumed that G has no self-loops, i.e. $(v, v) \notin E \ \forall v \in V$. For a subset $S \subset V$, one defines
$\delta^+(S) = \{u \in V \setminus S : \exists v \in S : (v, u) \in E\}$ and $\delta^-(S) = \{u \in V \setminus S : \exists v \in S : (u, v) \in E\}$, i.e. the sets
of outgoing nodes from and incoming nodes into a set of nodes S. For a node $v \in V$ one writes
$\delta^\pm(v) := \delta^\pm(\{v\})$. Furthermore, it is given a score function $s : V \to \mathbb{R}$, describing some summary
of experimental data available for the biomolecular entities represented by the nodes. For a given
graph $G = (V, E)$ any node labeling function $f : V \to \mathbb{R}$ is implicitly implied to be a vector $f \in \mathbb{R}^{|V|}$,
subject to an arbitrary but fixed ordering of the nodes (shared across all node labeling functions).
In particular, with $f_v := f(v)$ for $v \in V$, given $f, g : V \to \mathbb{R}$, one can write $f^T g = \sum_{v \in V} f_v g_v$. For $S \subset V$
and $f : V \to \mathbb{R}$ one defines $f_S : V \to \mathbb{R}$ via $f_S(v) := 0$ for all $v \in V \setminus S$ and $f_S(v) := f(v)$ for
all $v \in S$. Defining $e : V \to \mathbb{R}$ with $e(v) := 1$ for all $v \in V$, one further can write $e_S^T f = \sum_{v \in S} f_v$ for
$S \subset V$ and $f : V \to \mathbb{R}$. Comparison of node labeling functions f, g are meant to be understood
element-wise, e.g. $f \leq g$ means $f_v \leq g_v$ for all $v \in V$. Apart from the graph G and node scores s,
there are given possibly empty subsets of nodes $R \subset V$ and $T \subset V$. It is referred to R as *receptors*
(or sometimes *sources*) and to T as *terminals* (or sometimes *targets*), independent of the biological
semantics underlying the definition of these sets (see below). For enforcing the topology of the
subnetworks later on, strongly connected components will play a decisive role and it is said that a

---

[1]The appendix *Supplementary File 1* furthermore contains a demonstration of the usefulness of subgraph-derived features for survival prediction. In particular, these features outperform comparable features derived from gene set enrichment indicated pathways and also improve classifiers based on clinical data alone.

Figure 1. DeRegNet's inputs are a biomolecular network (A), such as a signaling or gene regulatory network, and omics measurements (B), such as gene expression data. The latter are mapped onto the nodes of the network acting as node-level measures of deregulation. DeRegNet then extracts the most deregulated subnetwork from the larger regulatory network according to some definition of *most deregulated*. For a conceptual view of the progression from set enrichment to de novo subnetwork methods we refer to the listed supplementary figures.

Figure 1–Figure supplement 1. Conceptual view of classical pathway/gene set analysis.

Figure 1–Figure supplement 2. Conceptual view of topological pathway/analysis.

Figure 1–Figure supplement 3. Conceptual view of topological pathway/analysis with pathway crosstalks.

Figure 1–Figure supplement 4. Conceptual view of de-novo pathway analysis.

137 subset of nodes $V' \subset V$ induces a strongly connected subgraph (V' *iscs*, for short) if the subgraph
138 induced by V' is strongly connected.

Probabilistic model

The mathematical optimization model which is at the heart of the DeRegNet algorithm and pre-
sented in the next subsection amounts to maximum likelihood estimation under a certain canoni-
cal statistical model. The model assumes binary node scores $s : V \rightarrow \{0, 1\}$ which are realizations
of random variables $\mathbf{S} = (S_v)_{v \in V}$. Here, $S_v = 1$ is interpreted as node $v \in V$ being *deregulated*. Fur-
ther it is assumed the existence of a subset of vertices $V' \subset V$ such that $S_v | v \in V' \sim Ber(p')$ and
$S_v | v \in V \backslash V' \sim Ber(p)$ with $p, p' \in (0, 1)$ denoting probabilites of deregulation outside and inside
of the deregulated subgraph encoded by V' respectively. It is assumed that $p' > p$ to reflect the
idea of *higher* deregulation (probability) in the *deregulated* subgraph, whereas p represents a cer-
tain amount of background deregulation. The network context (dependency) is introduced via the
restriction that $V' \in \mathcal{C}(V) \subset \mathcal{P}(V)$. Here, $\mathcal{C}(V)$ denotes the set of feasible substructures and should
(can) reflect topologies inspired by known biomolecular pathway topologies like the one described
in *Backes et al.* (*2012*) and the next subsection. Furthermore it is assumed, that the (S_v), given a
network context and deregulation probabilities p, p', are independent. We show in the appendix
that under this model and the constraints given by the fractional integer programming problem
formulated in the next subsection (defining $\mathcal{C}(V)$ in the above notation) DeRegNet amounts to max-
imum likelihood estimation. Furthermore, we also show that the model put forward in *Backes et al.*
(*2012*) amounts to maximum likelihood estimation only under the assumption of a fixed subgraph
size.

Fractional integer programming model

Given the definitions of the preceding sections, we can now formulate the main model underlying
DeRegNet. The DeRegNet model and also the model of (*Backes et al., 2012*) can be placed in the
context of the so called *Maximum Weight Connected Subgraph Problem (MWCSP)*, see Supplemen-
tary File 1. Note, that in the following we formulate all problems as maximization problems and
minimization may, depending on the semantics of the node score, be the proper choice[2]. As in
(*Backes et al., 2012*) we model the problem of finding deregulated subnetworks in terms of indica-
tor variables $x_v = \mathbf{I}(v \in V')$[3] and $y_v = \mathbf{I}(v$ is the root node) where $V' \subset V$ is a set of nodes inducing a
subgraph such that one can reach every node in that subgraph by means of a directed path from
the root node. In addition the root is supposed to be a source node and all nodes in the subgraph
with no outgoing edges are supposed to be terminal nodes. The proposed model then reads like

---

[2]Minimization may for example be prudent in case the node scores represent p values originating from some statistical
significance test.
[3]$\mathbf{I}(P) = 1$ if P, $\mathbf{I}(P) = 0$ if not P for some predicate P.

169 this:

$$\max_{x,\, y \,\in\, \{0,1\}^V} \quad \frac{s^T x}{e^T x} \tag{1a}$$

$$\text{s.t.} \qquad y \leq x \tag{1b}$$

$$e^T y = 1 \tag{1c}$$

$$k_{min} \leq e^T x \leq k_{max} \tag{1d}$$

$$x_v - y_v - e^T_{\delta^-(v)} x \leq 0 \quad \forall v \in V \tag{1e}$$

$$e^T_S(x - y) - e^T_{\delta^-(S)} x \leq |S| - 1 \quad \forall S \subset V \; iscs, \; |S| > 1 \tag{1f}$$

$$y_v = 0 \quad \forall v \in V \setminus R \quad \text{if } R \neq \varnothing \tag{1g}$$

$$x_v - e^T_{\delta^+(v)} x \leq 0 \quad \forall v \in V \setminus T \quad \text{if } T \neq \varnothing \tag{1h}$$

$$e^T_{\mathbf{Inc}} x = |\mathbf{Inc}| \tag{1i}$$

$$e^T_{\mathbf{Ex}} x = 0 \tag{1j}$$

The model derives from the corresponding integer linear programming model in (***Backes et al.,***
2012) and adapts it for the fractional case, most notably here are the constraints involving the the
receptors R (1g) and the terminals T (1h). (1g) just ensures that the root node is a receptor[4], while
(1h) ensures that any node in the subgraph with no outgoing edges is a terminal node. (1b) means
that a node can only be the root if it is included in the subgraph, (1c) means that there is exactly one
root, (1d) means that the size of subgraph has to be within the bound given by $k_{min}, k_{max} \in \mathbb{N}$, (1e)
says that a node $v \in V$ in the subgraph is either the root node or there is another node $u \in V$ in the
subgraph such that there is an edge $(u, v) \in E$. Moreover, the the constraints (1i) and (1j) trivially
allow to include and exclude specific nodes from given node sets $\mathbf{Inc} \subset V$ and $\mathbf{Ex} \subset V$ respectively[5].
The constraint (1f) is the most involved one and actually describes exponentially many constraints
which ensure that there are no disconnected directed circles (***Backes et al.*** (***2012***)) by requiring
that any strongly connected component in the subgraph either contains the root node or has an
incoming edge from another node which is part of the subgraph but not part the given strongly
connected component. Finally, the objective (2.1a) describes the notion of maximizing the average
score of the subgraph. This is crucial for allowing the model the flexibility to connect source nodes
to target nodes and also is at the heart of DeRegNet being able to do Maximum Likelihood estima-
tion given the presented statistical model. We summarize some crucial terminology next, before
proceeding in the next subsection to describe the solution algorithms for DeRegNet.
188

Definition 1 (DeRegNet instances, data, and subgraphs)
A tuple $(G, R, T, \mathbf{Ex}, \mathbf{Inc}, s)$ *is called an **instance of DeRegNet** (a **DeRegNet instance**, an **instance of***
***the DeRegNet model**). Here,* $G = (V, E)$ *is the **underlying graph**,* $R \subset V$ *is the **receptor set**,* $T \subset V$ *is*
*the **terminal set**,* $\mathbf{Ex} \subset V$ *is the **exclude set**,* $\mathbf{Inc} \subset V$ *is the **include set** and* $s : V \to \mathbb{R}$ *is the **node score***
*(the **score**). Further,* $x_v : V \to \{0, 1\}$ *is called a **subgraph** with the understanding that it is referred to the*
subgraph of G induced by $V^* = \{v \in V : x_v = 1\}$. *Equivalently to* $x_v : V \to \{0, 1\}$, *it is also referred to*
the corresponding $V^* = \{v \in V : x_v = 1\}$ *as a subgraph. A subgraph is **feasible for DeRegNet** (for the*
DeRegNet instance), if it satisfies DeRegNet's constraints (1b-j). A subgraph satisfying these constraints
*is called a **feasible subgraph**. A feasible subgraph which optimizes problem (1) is called an **optimal***
***subgraph**.

---

[4]Of course, for practical implementation one can also just introduce variables $y_v \in \{0, 1\}$ only for nodes $v \in T$ in the first place. In terms of formulation one would need to make a difference for constraints (1e,f) as well and formulate them differently (with or without y) for nodes in R on the one hand and for nodes not in R on the other.

[5]In many situations specific nodes, i.e. genes in the case of gene regulatory networks, may be of interest in other topological positions than in a receptor or terminal role. In that case just requiring a certain gene to be part of the subgraph without any special constraints on its inclusion in topological terms can be of value.

(a)   **(b)**

Figure 2. Conceptual view of subgraphs extracted by DeRegNet. (a) From a receptor node/root node (green cube) one can reach any node in the subnetwork. Nodes without any edges leading to other nodes (red triangles) of the subnetwork need to be elements of the so called terminal nodes. Generally, all nodes in the subgraph can be reached from the root node. **(b)** By reversing the the orientation of the underlying network before applying DeRegNet, one can find subgraphs with only one terminal "root" node and multiple receptor nodes such that the terminal node can be reached from any other node in the subgraph. See *Supplementary File 1* for further details on applying DeRegNet in reverse mode.

199 Some formal properties of DeRegNet and its solutions can be found in the *Supplementary File 1*. A
200 high-level depiction of the overall logic of DeRegNet can be found in figure 1. A conceptual view of
201 the types of subgraphs determined by DeRegNet can be seen in figure 2.

Solving the fractional integer programming model

We solve the integer fractional linear programming problems introduced in the previous sections
by one out of two implemented methods. Firstly, a generalization of the Charnes-Cooper transfor-
mation (***Charnes and Cooper, 1962***) for fractional linear programs described by (***Yue et al., 2013***)
and secondly an iterative scheme as introduced generally by Dinkelbach (***Dinkelbach, 1962***, ***1967***)
and subsequently applied in the context of integer fractional programming by (***Anzai, 1974***; ***You***
et al., 2009). While the Dinkelbach-type algorithm solves the problem by iteratively solving certain
non-fractional versions of the original problem until some convergence criterion is met, the gener-
alization of the Charnes-Cooper method is based on reformulation of the entire fractional model
to a quadratic problem and requires subsequent linearization of artifically introduced quadratic
constraints. The latter is implemented in terms of the methods described by (***Glover, 1975***; ***Adams***
and Forrester, 2005; ***Adams et al., 2004***).

As in (***Backes et al., 2012***) the exponentially many constraints forbidding any strongly connected
components not containing the root and with no incoming edges are handled by lazy constraints.
Every time an integer solution is found the Kosaraju–Sharir algorithm (***Sharir, 1981***) is employed
(as implemented by the Lemon graph library) to check for violoting components and, in the case
of violating components, the corresponding constraints are added to the model. Both solution ap-
proaches, the generalized Charnes-Cooper method and the Dinkelbach-type algorithm, allow for
the lazy constraints to be handled in terms of the original formulation since both retain the rele-
vant variables of the model within the transformed model(s).

For more details on the theoretical underpinnings and the practical implementation of DeRegNet's

solution algorithms consult *Supplementary File 1*.

Assessment of inference quality for known ground truths

The evaluation and benchmarking of *de novo* pathway enrichment or deregulated subnetwork de-
tection algorithms and implementations remains a big challenge. While many of the methods cited
in the introduction can be applied to reveal useful biological insight, there are limited studies con-
cerning the comparison of formal and statistical properties of the methods. The two main obstacles
are a lack of well-defined gold standard datasets as well as the differences concerning the exact
output of the methods. For example, it is not immediately clear how to compare algorithms which
produce undirected subnetworks to those which elicit directed networks of a certain structure. An
important first step toward atoning the issue in general is described in (*Batra et al., 2017*) which
focuses on benchmarking approaches for undirected networks. For the purposes of this paper,
we designed and performed benchmarks of DeRegNet relative to its closest relative, namely the
algorithm described in *Backes et al.* (*2012*). Note however, while we are comparing the integer
programming based algorithm of *Backes et al.* (*2012*) to the fractional integer programming algo-
rithm of DeRegNet, we are using the former as implemented in the DeRegNet software package.
This renders the benchmark less dependent on implementation technology since both algorithms
have been implemented with the same general stack of languages and libraries. For the bench-
mark we always utilize the human KEGG network as the underlying regulatory network. We then
repeatedly simulate subgraphs which match the structure of both models (DeRegNet and *Backes*
et al. (*2012*)). The simulation procedure is described more formally in *Supplementary File 1*. Initially,
the simulated subgraph consists of one randomly selected root node, to which we iteratively add
a random "outgoing" neighbor of a randomly selected current node in the subgraph until the size
of the subgraph matches a randomly chosen value. The latter is uniformly chosen to be an integer
between a given lower and an upper bound. "Outgoing" neighbors of $v \in V$ are any nodes from
the set $\delta^+(v) = \{u \in V \backslash \{v\} : (v, u) \in E\}$. All nodes in the simulated "real" subgraph are assigned
a node score of 1, while all nodes which are not contained in the subgraph are assigned a node
score of 0. These node scores are then flipped with a certain probability p_f to emulate noise in the
measurements of deregulation. In summary, we obtain random "real" subgraphs and simulated
scores. In terms of the probabilistic interpretation of DeRegNet presented above, the simulation
scheme corresponds to a deregulation probability of $1 - p_f$ for nodes in the "real" subgraph and
of p_f for nodes not part of the "real" subgraph. Hence, under the assumptions outlined for the
statistical model for DeRegNet the simulations are restricted to values $p_f \in [0, \frac{1}{2})$. The appendix in
Supplementary File 1 provides further details on the simulation of benchmark instances.

Given a sequence of $N \in \mathbb{N}$ of these simulated instances, the algorithms are run in order to find
subgraphs which can then be compared to the known simulated real subgraph. Here, a *hit* (*true*
positive, *tp*) is defined as a node appearing in a subgraph calculated by some algorithm which is
also an element of the real subgraph. A *false positive* (*fp*) is a node which appears in a subgraph
calculated by an algorithm but is not part of the real subgraph. A *false negative* is defined as a node
which is part of the true subgraph but not part of the subgraph detected by an algorithm. Further-
more, we can compare the sizes of the calculated subgraphs with the size of the real subgraph. In
more formal terms, given an algorithm $\mathcal{A}$, which on a given instance with true subgraph $V' \subset V$
finds a subgraph $V_{\mathcal{A}}$, one defines:

• *true positive rate* **TPR** $:= \frac{|V' \cap V_{\mathcal{A}}|}{V'}$, i.e. the number of actual hits divided by the number of
possible hits
• *false positive rate* **FPR** $:= \frac{|V_{\mathcal{A}} \backslash V'|}{V_{\mathcal{A}}}$, i.e. the proportion of nodes in the subgraph found by the
algorithms which are not part of the true subgraph
• *size efficiency* **SE** $:= \frac{|V_{\mathcal{A}}|}{|V'|}$, i.e. the proportion algorithm subgraph size to real subgraph size

Another comparison metric is the running time of the algorithms. Further, the benchmark is based
on the realistic assumption that we do not know the exact size of the real subgraph and that one can

only assume lower and upper bounds on the subgraph size instead. Since the *Backes et al.* (*2012*)
algorithm does need a fixed a priori specified subgraph size we employ a strategy suggested by
Backes et al. (*2012*) to circumvent that fact. Namely, we iterate from the lower to the upper bound,
find a subgraph for each subgraph size and then regard the union graph of all found subgraphs as
the one subgraph emitted by the algorithm. DeRegNet natively requires only a lower and an upper
bound on subgraph size as parameters. See *Supplementary File 1* for more formal details.
All benchmarks have been carried out with the following setup: software: Ubuntu 18.04, Gurobi
8.1.1, hardware: 12x Intel i7-8750H @ 4.1 GHz, 32 GB RAM, Samsung SSD 970 EVO Plus.

Network and omics data

KEGG network

284 While many sources for directed biomolecular networks are available, e.g. (*Cerami et al., 2011*), in
285 this paper we here utilize a directed gene-level network constructed from the KEGG database with
286 the KEGGgraph R-package (*Zhang and Wiemann, 2009*). The script used to generate the network
287 as well as the network itself can be found in the DeRegNet GitHub repository. See the subsection
288 on Software Availability for details.

TCGA-LIHC data and RNA-Seq derived node scores

Gene expression data was downloaded for hepatocellular carcinoma TCGA project from the Ge-
nomic Data Commons Portal [6]. Raw quantified RNA-Seq counts were normalized with DESeq2
(*Love et al., 2014*) which was also used for calculating log2 fold changes for every gene with re-
spect to the entire cohort. Personalized log2 fold changes were calculated by dividing a patients
tumor sample expression by the mean of all available control samples (adding a pseudo count of
1) before taking the log. The following node scores are defined.

• *Global RNA-Seq score s*: $s_v =$ RNASeq log2-fold change for a gene $v \in V$ as calculated by DESeq2
for the TCGA-LIHC cohort
• *Trinary personalized RNA-Seq score s^c for case c*:
299

$$
s_v^c = \begin{cases} +1 & \text{if personalized log2 fold} > 2 \\ -1 & \text{if personalized log2 fold} < -2 \\ 0 & \text{else} \end{cases} \tag{2}
$$

Global and personalized deregulated subgraphs

We refer to subgraphs found with the global RNA-Seq score s as *global subgraphs*. A global sub-
graph can further be subdivided as being *upregulated* or *downregulated* depending on whether the
subgraphs were found by employing a maximization or minimization objective respectively. For
(any) node score $s : V \to \mathbb{R}$ we define $|s| : V \to \mathbb{R}$ by $|s|(v) := |s(v)|$ for all $v \in V$. *Dysregu-*
lated global subgraphs are those which were found by using the score $|s|$ under a maximization
objective. Similarily subgraphs found with any of the scores s^c with a maximization objective are
called *upregulated* while those found with minimization objective are called *downregulated* (person-
alized subgraphs for case/patient c). Subgraphs found with a $|s^c|$ score under maximization are
called *dysregulated* (personalized subgraphs for case/patient c). Any of the above subgraph types
is called a *deregulated* subgraph. The optimal and four next best suboptimal global subgraphs were
calculated for every modality. The subgraphs were then summarized as a subgraph of the union
graph of optimal and suboptimal subgraphs in order to allow streamlined interpretation. See the
supplementary figures referenced in the respective figures for references to the direct output of
DeRegNet.

---

[6] https://portal.gdc.cancer.gov/projects/TCGA-LIHC

Network-defined cancer genes

Genes, gene products or biomolecular agents are likely to bring about their various phenotypic effects only in conjunction with other agents via their shared biomolecular network context. By that token, one can search for genes which convey phenotypic differences by means of some defined network context. Here, we propose DeRegNet subgraphs as network context for a given case/patient in order to find genes whose inclusion into a case's deregulated subgraph associates with a significant difference in overall survival. Algorithm 1 describes the procedure more formally. Genes implicated by the outlined procedure are termed *network-defined cancer genes*. The next section provides details on a specific network-defined cancer gene obtained by application of the procedure to personalized upregulated subgraphs in the TCGA-LIHC cohort.

Algorithm 1: Finding subnetwork-defined cancer genes. After finding subgraphs for individual cases/patients the procedure partitions a set of cases/patients according to whether they contain a given gene in their determined subnetwork and tests whether the thus defined partition conveys a significant survival difference. Note, that in the described setting, the DeRegNet instances only differ in terms of their case-dependent node score s^c.

Data: A set of cases C, DeRegNet instances $I_c = (G = (V, E), R, T, \mathbf{Ex}, \mathbf{Inc}, s^c)$ for every $c \in C$, a subset of *nodes of interest* $V_I \subset V$ and a *survival mapping* $p : C \to [0, \infty)$.

Result: A mapping $pval : V_I \to [0, 1]$ associating each $v \in V_I$ with a p-value.

for $c \in C$ **do**
  Solve the DeRegNet instance I_c to obtain the nodes V_c contained in c's subgraph
for $v \in V_I$ **do**
  $C_v := \{c \in C : v \in V_c\}$
  Obtain the Kaplan-Meier estimate ***Kaplan and Meier*** (***1958***) for p w.r.t groups C_v and $C \setminus C_v$.
  $pval(v) :=$ p-value of log rank test ***Aalen et al.*** (***2008***) between groups C_v and $C \setminus C_v$
Carry out multiple testing correction of *pval*
return *pval*

Results and discussion

In the following we present multiple results relating to the application of the DeRegNet algorithm. Firstly, we present benchmark results for synthetic data which compares DeRegNet to its closest methodological relative ***Backes et al.*** (***2012***). Next, we present applications of DeRegNet on a TCGA liver cancer dataset. More specifically, we present global subgraphs for the TCGA representing deregulated subnetworks summarizing the cohort under study as a whole, as well as a personalized application of DeRegNet, i.e. the derivation of patient-specific subgraphs.

Performance comparison on data with a known ground truth

As outlined in the introduction, the field of statistical functional annotation needs adequate known ground truths (gold standards) against which one can evaluate corresponding methods, see for example ***Batra et al.*** (***2017***). Since actual ground truths are hard to come by for fundamental reasons, research for functional annotation algorithms justifiably focuses on simulated/synthetic ground truths. The latter are then generated such that they represent the assumed or postulated data-generating process. We compared DeRegNet to its closest methodological relative introduced in ***Backes et al.*** (***2012***) based on simulated instances as described in *Material and Methods*.

Figure 3 shows results of simulation runs carried out according to the described procedure. As can be seen in Figure 3, DeRegNet outperforms ***Backes et al.*** (***2012***) in terms of false positive rate

Figure 3. Benchmark patterns for DeRegNet and *Backes et al.* **(***2012***). (A)** Running time (in seconds) of
DeRegNet (Dinkelbach algorithm) and $k_{max} - k_{min} + 1$ ($k_{max} = 50$, $k_{min} = 25$) runs of the *Backes et al.* (*2012*)
algorithm: DeRegNet at least matches and for some metrics also beats the performance of *Backes et al.*
(*2012*) on our test instances **(B)** Size efficiency: the size DeRegNet subgraphs is closer to the true size of the
subgraph **(C)** TPR: *Backes et al.* (*2012*) finds more of the true subgraph nodes than DeRegNet with a mean of
100 % possible hits, while DeRegNet still achieves always more than 90 % of possible hits with a mean well
above 95 % **(D)** FPR: DeRegNet is less noisy than *Backes et al.* (*2012*) in that it finds less false positive nodes.
Moreover, DeRegNet is more consistent with respect to that metric while the variance of *Backes et al.* (*2012*)'s
FPR is considerable.

At https://github.com/KohlbacherLab/deregnet/tree/0.99.999/benchmark you can find benchmark results and
code. The results shown here correspond to the file *benchmark.25.30.50.45.0.01.100.600.json*, corresponding
to lower and upper bounds provided to the algorithms of 25 and 50, lower and upper bound of the simulated
real subgraph sizes of 30 and 45, as well as a deregulation noise $p_f = 0.1$. We simulated 100 instances and set
a run time limit of 600 seconds. Other parameter combinations for the simulation procedure showed the
same performance patterns. See *Supplementary File 1* for further formal details on the simulation procedure.

(FPR), runtime and size efficiency, while the true positive rate of *Backes et al.* (*2012*) is hard to beat.
Nonetheless DeRegNet achieves solid performance also in terms of TPR.
Less quantitatively, note that DeRegNet allows for subgraphs which originate from so called source
(root, receptor) nodes and *end* at so called terminal nodes. This is not readily possible with the
Backes et al. (*2012*) algorithm due to the necessity to specify a fixed subgraph size *a priori* and the
resulting lack of flexibility to connect receptors to targets. Also note that DeRegNet is available as
open-source software and also provides an open-source implementation of the *Backes et al.* (*2012*)
algorithm[7]. Furthermore, given the statistical model introduced in *Material and Methods*, *Backes*
et al. (*2012*) solves only a special case of the maximum likelihood estimation problem which is
solved by DeRegNet in its general form.

Global deregulated subgraphs for TCGA-LIHC

Using the DeRegNet algorithm we determined the upregulated global subgraphs obtained from
running the algorithm with the global RNA-Seq score defined above. The optimal and four next
best suboptimal subgraphs were calculated for every modality. The subgraphs were then sum-
marized as a subgraph of the union graph of optimal and suboptimal subgraphs in order to al-
low streamlined interpretation. The global subgraph comprised of upregulated genes as nodes is
shown in Figure 4.

Reconstruction of transcriptional activation of WNT signaling

The subgraphs shows the activation of the *WNT* signaling pathway by means of over-expressed
Glypican-3 (*GPC3*), which represents a membrane-bound heparin sulphate proteoglycan (*Arzu-*
manyan et al., 2013). *GPC3* has been extensively researched as a early biomarker and potential
therapy target in HCC (*Zhou et al., 2018*; *Wu et al., 2016*; *Feng and Ho, 2014*; *Filmus and Capurro,*
2013; *Ho and Kim, 2011*; *Bertino et al., 2012*) (See figure 1).
Genomic analysis conducted over the past decade have identified mutations affecting Telom-
ere Reverse Transcriptase (*TERT*), β-catenin (*CTNNB1*) and cellular tumor antigen *p53 (TP53)* (*Llovet*
et al., 2016) as common driver mutations in HCC. Mutations in the *TERT* promoter are a well-studied
factor in liver cancer development (*Nault and Zucman-Rossi, 2016*; *Quaas et al., 2014*) and lead to
TERT overexpression while mutations in *CTNNB1*, activate *CTNNB1* and result in activation of *WNT*
signaling. Previous studies have determined that *TERT* promoter mutations significantly co-occur
with *CTNNB1* alternation and both mutations represent events in early HCC malignant transforma-
tion (*Totoki et al., 2014*). In agreement, the DeRegNet algorithm recatures the importance of a
CTNNB1:*TERT* connection on a transcriptional level.
The subgraphs further show a possible alternative mechanism of *CTNNB1* activation through
upregulated *GPC3*, an early marker of HCC, as well as Wnt Family member 3a (*WNT3A*) and Frizzled
10 (*FZD10*). *WNT3A* promotes the stablization of *CTNNB1* and consequently expression of genes
that are important for growth, proliferation and survival (*Anastas and Moon, 2013*) through activ-
ity of transcription factor Lymphoid Enhancer-Binding Factor 1 (*LEF1*). As shown in the subgraph
figure 4, *LEF1*'s known targets SRY-box 2 (*SOX2*)[8] and Baculoviral IAP Repeat Containing 5 (*BIRC5*)
are likely important contributers to *WNT* pathway driven *WNT* proliferation. *SOX2* is a pluripotency-
associated transcription factor with known role in HCC development (*Sun et al., 2013*; *Wen et al.,*
2013; *Liu et al., 2016a*) and *BIRC5* (survinin) is an anti-apoptotic factor often implicated in chronic
liver disease and liver cancer (*Min et al., 2012*; *Montorsi et al., 2007*; *Su, 2016*).
In summary, our algorithm reconstructed important components of the canonical *WNT* signal-
ing pathway activation in liver cancer (*Takigawa and Brown, 2008*; *Liu et al., 2016b*; *Vilchez et al.,*
2016; *Clevers and Nusse, 2012*; *Nusse and Clevers, 2017*) from TCGA-LIHC RNA-Seq data and pair-
wise gene-gene interaction information from KEGG.

---

[7]Currently the implementation only supports the commercial Gurobi ILP solver as a solver backend. Gurobi readily provides free academic licenses though.
[8]Sex-Determining Region Y (*SRY*)

Figure 4. Global upregulated subgraph for TCGA-LIHC reconstructs transcriptional activation of *WNT* signaling. The Color of nodes indicates the average log$_2$ fold change of tumor samples compared to controls as represented in the color bar. The color of rims around nodes indicates genes contained in the integrin pathway (blue), the *WNT* pathway (yellow) and diverse other pathways (no rim). The color of edges indicates following interactions: activation (red), inhibition (dark blue), compound (brown), binding/association (yellow), indirect effect (dashed grey), phosphorylation (pink), dephosphorylation (light green), expression (green) and ubiquitination (light purple).

Figure 4–Figure supplement 1. GPC3-mediated activation of WNT signaling.

Figure 4–Figure supplement 2. Optimal upregulated global subgraph for TCGA-LIHC

Figure 4–Figure supplement 3. 1^{st} suboptimal upregulated global subgraph for TCGA-LIHC.

Figure 4–Figure supplement 4. 2^{nd} suboptimal upregulated global subgraph for TCGA-LIHC

Figure 4–Figure supplement 5. 3^{rd} suboptimal upregulated global subgraph for TCGA-LIHC

Figure 4–Figure supplement 6. 4^{th} suboptimal upregulated global subgraph for TCGA-LIHC

388

389 ## Crosstalk between integrin and WNT signaling

390 Another interesting pattern emerging in the upregulated subgraphs is the crosstalk between the
391 *WNT* signaling cascade and integrin signaling. Over-expression of Secreted Phosphoprotein 1 (*SPP1*)
392 has been shown to be a common feature for most known human malignancies and it is commonly
393 associated with poor overall survival (***Bellahcene et al., 2008***). The binding of *SPP1* to integrins
394 (e.g. integrin $\alpha V \beta 3$) leads to further activation of kinases associated with proliferation, epithelial-
395 mesenchymal-transition, migration and invasion in HCC, such as Mitogen Activated Kinase-like Pro-
396 tein (*MAPK*), Phosphatidylinositol-4,5-bisphosphate 3-kinase (*PI3K*), Protein Tyrosine Kinase (*PTK2*),
397 and SRC proto-oncogene/Non-receptor tyrosine kinase (*SRC*) (***Wen et al., 2016***). Further captured
398 by the subgraphs is that elevated expression of *PTK2* and *MAPK12* are accompanied with elevated
399 expression of cell cycle related genes (Cell Division Cycle 25 Homolog C / M-phase inducer phos-
400 phatase 1 (*CDC25C*), Cyclin-dependent Kinase 1 (*CDK1*) and Polo-like Kinase 1 (*PLK1*)), thus connect-
401 ing over-expression of kinases with cell proliferation.

402 Although KEGG lists the interaction between *SRC* and *CTNNB1* as inhibitory in nature, other
403 studies have concluded that activated Src enhances the accumulation of nuclear beta-catenin and
404 therefore through their interaction contributes to an oncogenic phenotype (***Karni et al., 2005***).

405 In conclusion, the upregulated subgraphs capture the interaction of *SPP1* with integrin and con-
406 sequent activation of *PTK2* and *SRC* together with their connection to the *WNT* signaling pathway
407 (via *CTNNB1*) and cell cycle genes.

408

409 ## Downregulated oncogenes FOS and JUN and drug metabolism

410 The global downregulated subgraphs are centered around down-regulation of transcription fac-
411 tors *FOS* and *JUN*. The subgraph summary is depicted in figure 5. *FOS* and *JUN*, which form *AP-1*
412 transcription complex are considered to be oncogenic factors and necessary for development of
413 liver tumors (***Eferl and Wagner, 2003***). Considering their prominent role in liver tumorigenesis, fur-
414 ther experimental study of the significance of Jun and Fos downregulation on HCC development
415 could be of great interest. Interestingly, RNA-seq data show that all *FOS* (*FOS*, *FOSB*, *FOSL1*, *FOSL2*)
416 and *JUN* (*JUN*, *JUNB*, *JUND*) isoforms are downregulated in a majority of liver tumors of the TCGA
417 cohort (See figure 5, Supplementary figure 1).

418 Furthermore, the subgraphs show a number of downregulated Cytochrome P450 (*CYP*) en-
419 zymes as part of the most downregulated network of genes. *CYP3A4* is mainly expressed in the
420 liver and has an important role in the conversion of carcinogens, such as aflatoxin B_1 toward their
421 ultimate DNA-reactive metabolites (***Luch, 2005***), as well as, in detoxification of anticancer drugs
422 (***Undevia et al., 2005***). Although the downregulation of *CYP* enzymes could potentially render HCC
423 tumors sensitive to chemotherapy, liver tumors are notoriuosly irresponsive to chemotherapy
424 (***Llovet et al., 2016***). Therefore, it is unclear how the gene pattern of *CYP* enzymes captured by
425 the presented subgraphs could influence the HCC response to therapy and which compensatory
426 mechanism is employed to counteract *CYP* downregulation.

427 ## Personalized deregulated subgraphs for TCGA-LIHC

428 Finding deregulated subgraphs in a patient-resolved manner enables steps toward personalized
429 medicine. In this section we introduce a case study where we employed our algorithm to find an
430 upregulated subgraph for every TCGA-LIHC patient. Stratifying patients according to whether their
431 subgraph contains a gene or not, one can identify genes whose inclusion into a patient's inferred
432 subgraph provides a survival handicap or advantage. The supplementary figure of figure 7 shows
433 the effect for some of those *network-defined cancer genes*. Here, we concentrate on one particular
434 such gene, namely Spleen Tyrosine Kinase (*SYK*).

Figure 5. Global downregulated subgraph for TCGA-LIHC are centered on *FOS* and *JUN* transcription factors and drug metabolism. Color of nodes indicates the average log$_2$ fold change of tumor samples compared to controls as represented by the color bar. The color of edges indicates the following interactions: activation (red), compound (brown), binding/association (yellow), indirect effect (dashed grey) and expression (green). Also noteworthy it the general connection of transcriptional activators and inhibitors to signaling as well as metabolic networks. Transcription regulators have been highlighted with an orange rim.

Figure 5–Figure supplement 1. Expression of FOS and JUN isoforms in tumor of TCGA-LIHC. cohort.

Figure 5–Figure supplement 2. Optimal downregulated global subgraph for TCGA-LIHC

Figure 5–Figure supplement 3. 1^{st} suboptimal downregulated global subgraph for TCGA-LIHC

Figure 5–Figure supplement 4. 2^{nd} suboptimal downregulated global subgraph for TCGA-LIHC

Figure 5–Figure supplement 5. 3^{rd} suboptimal downregulated global subgraph for TCGA-LIHC

Figure 5–Figure supplement 6. 4^{th} suboptimal downregulated global subgraph for TCGA-LIHC

Figure 6. SYK signaling indicates poor survival. TCGA-LIHC cases TCGA-5C-AAPD, TCGA-CC-A3MA, TCGA-ED-A5KG, TCGA-DD-AACH, TCGA-YA-A8S7, TCGA-CC-5261, TCGA-CC-A3M9 show activated SYK signaling and poor survival. Survival difference is significant at p=0.0002 (Kaplan-Meier estimates and log-rank test).

Figure 6–Figure supplement 1. Further identified genes whose inclusion into a patient's inferred subgraph indicates a poor survival.

Spleen tyrosine kinase (SYK) as a network-defined cancer gene

Patients whose subgraph contained the spleen tyrosine kinase (SYK) showed comparatively bad survival outlook (see Figures 6, 7).

SYK is most commonly expressed in immune cells and its deregulation has been originally associated with hematopoietic cancers (*Lowell, 2011*; *Krisenko and Geahlen, 2015*; *Mocsai et al., 2010*). However, it has been shown that *SYK* plays a role in various other cancer types and its respective roles seem to vary significantly depending on the molecular (i.e. ultimately network) context (*Krisenko and Geahlen, 2015*). *SYK* comes in the form of two splice variants, *SYK*(*L*) and *SYK*(*S*) (*Hong et al., 2014*). In the context of liver cancer, *SYK* promoter hypermethylation and corresponding *SYK* downregulation has been associated with poor survival (*Shin et al., 2014*). Furthermore, Checkpoint Kinase 1 (*CHK1*) mediated phosphorylation of *SYK*(*L*) and associated *SYK* degradation has been considered an oncogenic process (*Hong et al., 2012*), associating low levels of *SYK* as a factor of poor survival. On the other hand, (*Hong et al., 2014*) *SYK*(*S*) expression promotes metastasis development in HCC and thus leads to poor survival outcome. Furthermore, high *SYK* expression has been shown to promote liver fibrosis (*Qu et al., 2018*). The development of HCC is closely related to formation and progression of fibrosis. Fibrosis represents excessive accumulation of extracellular matrix (ECM) and scarring tissue in an organ. A fibrotic environment promotes development of dysplastic nodules which can gradually progress to liver tumors (*Bataller and Brenner, 2005*). In short, a somewhat inconsistent role of *SYK* as a tumor supressor or oncogene can be observed in many cancers (*Krisenko and Geahlen, 2015*), including liver cancer.

By employing DeRegNet, we identified by means of the approach defined as algorithm 1 a subgroup of HCC patients from the TCGA-LIHC cohort which show poor survival and a distinguished *SYK*-signaling pattern shown in Figure 7. The depicted network is manually extracted from the union graph of all the patient's subgraphs which contained *SYK*. The network shows *SRC-SYK*-mediated activation of PI3K-Akt signaling via B-lymphocyte antigen CD19 (*CD19*) and Phosphatidylinositol 4,5-bisphosphate 3-kinase catalytic subunit delta (*PI3KCD*)[9] (*Thorpe et al., 2015*). Furthermore, *SYK* also feeds into mitogen-activated protein kinase 11-13 (p38) signaling (only *MAPK*13 shown) through GTPase Hras (*HRAS*) and aspase recruitment domain-containing protein 9 (*CASP9*). p38 signaling

---

[9]p110δ

Figure 7. Consistent upregulation of SYK signaling components and downstream targets in subgraph of patients with poor survival. Inner node color represents the average log$_2$ fold change across the "SYK-positive" patients and node rim color represent average log2 fold change across the rest of the TCGA-LIHC cohort. Color of edges indicates following interactions: activation (red), inhibition (dark blue), compound (brown), indirect effect (dark grey) and expression (blue green).

promotes cytokine expression via Growth-regulated alphaprotein (*CXCL1*). Increased cytokine expression and activation is another canonical effect of *SYK* signaling (**Mocsai et al., 2010**). This in turn, activates JAK signaling through Januskinase 3 (*JAK3*) activity, thereby reinforcing PI3K activation. Interestingly, *SYK* signaling is consistently linked to the upregulation of the guanine nucleotide exchange factors *VAV1* and *VAV3* (**Mocsai et al., 2010**; **Lowell, 2011**)[10]. The proto-oncogene *VAV3* is associated to adverse outcomes in colorectal (**Uen et al., 2015**) and breast cancer (**Citterio et al., 2012**; **Chen et al., 2015**). Furthermore *VAV3* mutations have been profiled to be potential drivers for liver cancer (**Li et al., 2018**). *VAV* signaling is mediated by forming a complex with Lymphocyte cytosolic protein 2 (*LCP2*)[11] upon activation of *SYK* signaling. *VAV*-meditated Ras-related C3 botulinum toxin substrate 2 (*RAC2*) activation may play a role in intravastation and motility (**Roussos et al., 2011**). Additionally, the subgraph shows upregulation of the B-cell lymphoma 2 (*BCL2*) gene, a known regulator of apoptosis (**Hardwick and Soane, 2013**), and vascular endothelial growth factor-C (*VEGGC*) which can promote metastasis (**Mandriota et al., 2001**) and angiogenesis (**Tammela et al., 2008**; **Tvorogov et al., 2010**).

Conclusion

We have shown DeRegNet's capability to infer relevant patterns to a high degree of accuracy based on simulation benchmarks and showed that it compares favorably to related algorithms. Furthermore, application of DeRegNet to publically available data in a global fashion identified driving factors of liver cancer such as a transcriptionally activated WNT-pathway, thus showing that DeRegNet can provide valuable insight into a given omics experiment and may lead to novel and so far uncharacterized discoveries of gene/pathways involved in carcinogenesis and other biological contexts. An example of such discovery is the already outlined insights into the global interaction of integrin and WNT signaling, as well as drug metabolism in liver cancer. In fact, profiling of such interaction between pathways is one of the main strengths of our algorithm over classical gene enrichment methods. Additionally, the application of our subgraph algorithm in a patient-specific manner could identify a consistent subgroup of patients showing poor prognosis potentially due to aberrant SYK signaling and therefore can generate meaningful hypotheses suitable for further experimental follow-up. Given that the SYK example is just one example case of a network-defined cancer gene, this indicates that DeRegNet is a useful hypothesis generation tool for network-guided personalized cancer research. In addition, further modes of application of the DeRegNet algorithm increase the spectrum of meaningful exploratory directions. Note, for example, that we only presented and discussed network-defined cancer genes (i.e. SYK in our subgraph example) for upregulated subgraphs, while we have not presented the results of an analysis based on downregulated or generically deregulated (either up- or downregulated) subgraphs which would lead to similar opportunities. Together with a solid underlying statistical model for which DeRegNet is shown to infer Maximum Likelihood estimates and its open-source implementation, this makes DeRegNet a viable option for any researcher interested in network interactions in an high-throughput omics context.

Software Availability

Our implementation is written in C++ and Python and utilizes the Gurobi optmization libary (http://www.gurobi.com/index) and the Lemon graph library (https://lemon.cs.elte.hu/trac/lemon). Our software is open source under a BSD-3-Clause OSI-approved license and is available at https://github.com/KohlbacherLab/deregnet where you can also find installation instructions and usage examples. The algorithm can be run either by using a Python package or a command line tool via Docker images. The Docker images *sebwink/deregnet* are available at Docker Hub (https://hub.docker.com/repository/docker/sebwink/deregnet) and bundle all necessary dependencies. Additionaly Docker

---

[10]Guanine nucleotide exchange factor (*VAV*)

[11]SLP-76

images are also provided via https://github.com/orgs/KohlbacherLab/packages?repo_name=deregnet.
Furthermore, in order to run DeRegNet, a license for the Gurobi optimization library is required. For
academic purposes these licences are readily obtained at https://www.gurobi.com/downloads/. The
applications of DeRegNet to TCGA data appearing in this paper can be found at https://github.com/
KohlbacherLab/deregnet-tcga. DeRegNet depends on a C++ library called *libgrbfrc* (https://github.com/
KohlbacherLab/libgrbfrc) to solve fractional integer programs with Gurobi which was implemented
by the authors of DeRegNet which is also available under the BSD-3-Clause open source license.
Finally, to run the synthetic benchmarks presented in this paper, one can follow the instructions
at https://github.com/KohlbacherLab/deregnet/tree/master/examples/custom-python-script. The bench-
mark code and results as obtained by the authors and presented in figure 3 are available here:
https://github.com/KohlbacherLab/deregnet/tree/0.99.999/benchmark.

Supplementary Files
This paper is accompanied by the following supplementary materials:

• *Supplementary File 1*: Appendix

Supplementary File 1 provides additional details and formalized exposition of many aspects of
DeRegNet. In particular, it provides details on directions on how to run the DeRegNet software,
definition and derivation of the probabilistic model underlying DeRegNet, as well as the proof that
DeRegNet corresponds to maximum likelihood estimation under outlined model, DeRegNet in the
context of the general optimization problem referred to as the *Maximum Average Weight Connected*
Subgraph Problem and its relatives, proofs of certain structural properties of DeRegNet solutions,
different application modes of the DeRegNet algorithms, fractional mixed-integer programming
as it relates to the solution of DeRegNet instances, lazy constraints in branch-and-cut MILP solvers
as it relates to DeRegNet, further solution technology employed for solving DeRegNet instances,
DeRegNet benchmark simulations and use of DeRegNet subgraphs as a basis for feature engineer-
ing for survival prediction on the TCGA-LIHC dataset.

Acknowledgments

We would like to thank all members of the Chair for Applied Bioinformatics at the University of
Tübingen for valuable discussions and comments. Also we especially would like to thank Fabian
Aicheler, Marc Rurik and Nico Weber for testing various components of the software at various
stages and providing useful feedback. SW, IW, AN and OK acknowledge support from the *Inter-*
national Max Planck Research School (IMPRS) "From Molecules to Organisms". AN received funding
from the DFG under Germany´s Excellence Strategy (EXC 2180-390900677, project 10076-1) and
the SFB/TR 209 (project B02).

Declaration of Interest
543 The authors declare no competing interests.

References

Aalen O, Borgan O, Gjessing H. Survival and Event History Analysis: A Process Point of View. Springer; 2008.

Adams WP, Forrester RJ. A simple recipe for concise mixed 0-1 linearizations. Operations Research Letters.
2005; 33:55–61.

Adams WP, Forrester RJ, Glover F. Comparison and enhancement strategies for linearizing mixed 0-1 quadratic
programs. Discrete Optimization. 2004; 1:99–120.

Alcaraz N, Friedrich T, Kotzing T, Krohmer A, Muller J, Pauling J, Baumbach J. Efficient key pathway mining:
combining networks and OMICS data. Integr Biol (Camb). 2012 Jul; 4(7):756–764.

Alcaraz N, List M, Dissing-Hansen M, Rehmsmeier M, Tan Q, Mollenhauer J, Ditzel HJ, Baumbach J. Robust de novo pathway enrichment with KeyPathwayMiner 5. F1000Res. 2016; 5:1531.

Alcaraz N, Pauling J, Batra R, Barbosa E, Junge A, Christensen AG, Azevedo V, Ditzel HJ, Baumbach J. KeyPathwayMiner 4.0: condition-specific pathway analysis by combining multiple omics studies and networks with Cytoscape. BMC Syst Biol. 2014 Aug; 8:99.

Altelaar AFM, Munoz J, Heck AJR. Next-generation proteomics: towards an integrative view of proteome dynamics. Nat Rev Genet. 2013; 14:35–48.

Anastas JN, Moon RT. WNT signalling pathways as therapeutic targets in cancer. Nat Rev Cancer. 2013 Jan; 13(1):11–26.

Anzai Y. On integer fractional programming. J Operations Research Soc of Japan. 1974 March; 17(1):49–66.

Arzumanyan A, Reis HM, Feitelson MA. Pathogenic mechanisms in HBV- and HCV-associated hepatocellular carcinoma. Nat Rev Cancer. 2013 Feb; 13(2):123–135.

Atias N, Sharan R. iPoint: an integer programming based algorithm for inferring protein subnetworks. Mol Biosyst. 2013 Jul; 9(7):1662–1669.

Backes C, Rurainski A, Klau GW, Muller O, Stockel D, Gerasch A, Kuntzer J, Maisel D, Ludwig N, Hein M, Keller A, Burtscher H, Kaufmann M, Meese E, Lenhof HP. An integer linear programming approach for finding deregulated subgraphs in regulatory networks. Nucleic Acids Res. 2012 Mar; 40(6):e43.

Bailly-Bechet M, Borgs C, Braunstein A, Chayes J, Dagkessamanskaia A, Francois JM, Zecchina R. Finding undetected protein associations in cell signaling by belief propagation. Proc Natl Acad Sci USA. 2011 Jan; 108(2):882–887.

Bataller R, Brenner DA. Liver fibrosis. J Clin Invest. 2005 Feb; 115(2):209–218.

Batra R, Alcaraz N, Gitzhofer K, Pauling J, Ditzel HJ, Hellmuth M, Baumbach J, List M. On the performance of de novo pathway enrichment. NPJ Syst Biol Appl. 2017; 3:6.

Bellahcene A, Castronovo V, Ogbureke KU, Fisher LW, Fedarko NS. Small integrin-binding ligand N-linked glycoproteins (SIBLINGs): multifunctional proteins in cancer. Nat Rev Cancer. 2008 Mar; 8(3):212–226.

Bertino G, Ardiri A, Malaguarnera M, Malaguarnera G, Bertino N, Calvagno GS. Hepatocellualar carcinoma serum markers. Semin Oncol. 2012 Aug; 39(4):410–433.

Biggin MD. Animal transcription networks as highly connected, quantitative continua. Dev Cell. 2011 Oct; 21(4):611–626.

Caspi R, Dreher K, Karp PD. The challenge of constructing, classifying, and representing metabolic pathways. FEMS Microbiol Lett. 2013 Aug; 345(2):85–93.

Cerami E, Demir E, Schultz N, Taylor BS, Sander C. Automated network analysis identifies core pathways in glioblastoma. PLoS ONE. 2010 Feb; 5(2):e8918.

Cerami EG, Gross BE, Demir E, Rodchenkov I, Babur O, Anwar N, Schultz N, Bader GD, Sander C. Pathway Commons, a web resource for biological pathway data. Nucleic Acids Res. 2011 Jan; 39(Database issue):D685–690.

Charnes A, Cooper WW. Programming with linear fractional functionals. Naval Research Logistics Quaterly. 1962; 9:181–186.

Chen X, Chen SI, Liu XA, Zhou WB, Ma RR, Chen L. Vav3 oncogene is upregulated and a poor prognostic factor in breast cancer patients. Oncol Lett. 2015 May; 9(5):2143–2148.

Citterio C, Menacho-Marquez M, Garcia-Escudero R, Larive RM, Barreiro O, Sanchez-Madrid F, Paramio JM, Bustelo XR. The rho exchange factors vav2 and vav3 control a lung metastasis-specific transcriptional program in breast cancer cells. Sci Signal. 2012 Oct; 5(244):ra71.

Clevers H, Nusse R. Wnt/β-catenin signaling and disease. Cell. 2012 Jun; 149(6):1192–1205.

Dao P, Wang K, Collins C, Ester M, Lapuk A, Sahinalp SC. Optimally discriminative subnetwork markers predict response to chemotherapy. Bioinformatics. 2011 Jul; 27(13):i205–213.

598 **D'Eustachio P**. Pathway databases: making chemical and biological sense of the genomic data flood. Chem
599   Biol. 2013 May; 20(5):629–635.

600 **Dinkelbach W**. Die Maximierung eines Quotienten zweier linearer Funktionen unter linearen Nebenbedingun-
601   gen. Z Wahrscheinlichkeitstheorie. 1962; 1:141–145.

602 **Dinkelbach W**. On nonlinear fractional programming. Managment Science. 1967 March; 13(7):492–498.

603 **Dittrich MT**, Klau GW, Rosenwald A, Dandekar T, Muller T. Identifying functional modules in protein-protein
604   interaction networks: an integrated exact approach. Bioinformatics. 2008 Jul; 24(13):i223–231.

605 **Eferl R**, Wagner EF. AP-1: a double-edged sword in tumorigenesis. Nat Rev Cancer. 2003 Nov; 3(11):859–868.

606 **Fabregat A**, Jupe S, Matthews L, Sidiropoulos K, Gillespie M, Garapati P, Haw R, Jassal B, Korninger F, May B,
607   Milacic M, Roca CD, Rothfels K, Sevilla C, Shamovsky V, Shorser S, Varusai T, Viteri G, Weiser J, Wu G, et al. The
608   Reactome Pathway Knowledgebase. Nucleic Acids Res. 2018 Jan; 46(D1):D649–D655.

609 **Feng M**, Ho M. Glypican-3 antibodies: a new therapeutic target for liver cancer. FEBS Lett. 2014 Jan; 588(2):377–
610   382.

611 **Filmus J**, Capurro M. Glypican-3: a marker and a therapeutic target in hepatocellular carcinoma. FEBS J. 2013
612   May; 280(10):2471–2476.

613 **Gaire RK**, Smith L, Humbert P, Bailey J, Stuckey PJ, Haviv I. Discovery and analysis of consistent active sub-
614   networks in cancers. BMC Bioinformatics. 2013; 14 Suppl 2:S7.

615 **Glover F**. Improved linear integer programming formulations of nonlinear integer problems. Managment
616   Science. 1975 December; 22(4):455–460.

617 **Gosline SJ**, Spencer SJ, Ursu O, Fraenkel E. SAMNet: a network-based approach to integrate multi-dimensional
618   high throughput datasets. Integr Biol (Camb). 2012 Nov; 4(11):1415–1427.

619 **Hardwick JM**, Soane L. Multiple functions of BCL-2 family proteins. Cold Spring Harb Perspect Biol. 2013 Feb;
620   5(2).

621 **Ho M**, Kim H. Glypican-3: a new target for cancer immunotherapy. Eur J Cancer. 2011 Feb; 47(3):333–338.

622 **Hofree M**, Shen JP, Carter H, Gross A, Ideker T. Network-based stratification of tumor mutations. Nat Methods.
623   2013 Nov; 10(11):1108–1115.

624 **Hong J**, Hu K, Yuan Y, Sang Y, Bu Q, Chen G, Yang L, Li B, Huang P, Chen D, Liang Y, Zhang R, Pan J, Zeng YX, Kang
625   T. CHK1 targets spleen tyrosine kinase (L) for proteolysis in hepatocellular carcinoma. J Clin Invest. 2012 Jun;
626   122(6):2165–2175.

627 **Hong J**, Yuan Y, Wang J, Liao Y, Zou R, Zhu C, Li B, Liang Y, Huang P, Wang Z, Lin W, Zeng Y, Dai JL, Chung
628   RT. Expression of variant isoforms of the tyrosine kinase SYK determines the prognosis of hepatocellular
629   carcinoma. Cancer Res. 2014 Mar; 74(6):1845–1856.

630 **Huang SS**, Clarke DC, Gosline SJ, Labadorf A, Chouinard CR, Gordon W, Lauffenburger DA, Fraenkel E. Linking
631   proteomic and transcriptional data through the interactome and epigenome reveals a map of oncogene-
632   induced signaling. PLoS Comput Biol. 2013; 9(2):e1002887.

633 **Huang SS**, Fraenkel E. Integrating proteomic, transcriptional, and interactome data reveals hidden components
634   of signaling and regulatory networks. Sci Signal. 2009 Jul; 2(81):ra40.

635 **Ideker T**, Ozier O, Schwikowski B, Siegel AF. Discovering regulatory and signalling circuits in molecular interac-
636   tion networks. Bioinformatics. 2002; 18 Suppl 1:S233–240.

637 **Ihnatova I**, Popovici V, Budinska E. A critical comparison of topology-based pathway analysis methods. PLoS
638   ONE. 2018; 13(1):e0191154.

639 **Jaakkola MK**, Elo LL. Empirical comparison of structure-based pathway methods. Brief Bioinformatics. 2016
640   Mar; 17(2):336–345.

641 **Kanehisa M**, Furumichi M, Tanabe M, Sato Y, Morishima K. KEGG: new perspectives on genomes, pathways,
642   diseases and drugs. Nucleic Acids Res. 2017 Jan; 45(D1):D353–361.

Kaplan EL, Meier P. Nonparametric Estimation from Incomplete Observations. Journal of the American Statistical Association. 1958; 53(282):457–481. URL https://www.tandfonline.com/doi/abs/10.1080/01621459.1958.10501452, doi: 10.1080/01621459.1958.10501452.

Karni R, Gus Y, Dor Y, Meyuhas O, Levitzki A. Active Src elevates the expression of beta-catenin by enhancement of cap-dependent translation. Mol Cell Biol. 2005 Jun; 25(12):5031–5039.

Keller A, Backes C, Gerasch A, Kaufmann M, Kohlbacher O, Meese E, Lenhof HP. A novel algorithm for detecting differentially regulated paths based on gene set enrichment analysis. Bioinformatics. 2009 Nov; 25(21):2787–2794.

Krisenko MO, Geahlen RL. Calling in SYK: SYK's dual role as a tumor promoter and tumor suppressor in cancer. Biochim Biophys Acta. 2015 Jan; 1853(1):254–263.

Kutmon M, Riutta A, Nunes N, Hanspers K, Willighagen EL, Bohler A, Melius J, Waagmeester A, Sinha SR, Miller R, Coort SL, Cirillo E, Smeets B, Evelo CT, Pico AR. WikiPathways: capturing the full diversity of pathway knowledge. Nucleic Acids Res. 2016 Jan; 44(D1):D488–494.

Li T, Wernersson R, Hansen RB, Horn H, Mercer J, Slodkowicz G, Workman CT, Rigina O, Rapacki K, St?rfeldt HH, Brunak S, Jensen TS, Lage K. A scored human protein-protein interaction network to catalyze genomic interpretation. Nat Methods. 2017 01; 14(1):61–64.

Li X, Xu W, Kang W, Wong SH, Wang M, Zhou Y, Fang X, Zhang X, Yang H, Wong CH, To KF, Chan SL, Chan MTV, Sung JJY, Wu WKK, Yu J. Genomic analysis of liver cancer unveils novel driver genes and distinct prognostic features. Theranostics. 2018; 8(6):1740–1751.

Liu L, Liu C, Zhang Q, Shen J, Zhang H, Shan J, Duan G, Guo D, Chen X, Cheng J, Xu Y, Yang Z, Yao C, Lai M, Qian C. SIRT1-mediated transcriptional regulation of SOX2 is important for self-renewal of liver cancer stem cells. Hepatology. 2016 09; 64(3):814–827.

Liu LJ, Xie SX, Chen YT, Xue JL, Zhang CJ, Zhu F. Aberrant regulation of Wnt signaling in hepatocellular carcinoma. World J Gastroenterol. 2016 Sep; 22(33):7486–7499.

Llovet JM, Zucman-Rossi J, Pikarsky E, Sangro B, Schwartz M, Sherman M, Gores G. Hepatocellular carcinoma. Nat Rev Dis Primers. 2016 04; 2:16018.

Love MI, Huber W, Anders S. Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2. Genome Biol. 2014; 15(12):550.

Lowell CA. Src-family and Syk kinases in activating and inhibitory pathways in innate immune cells: signaling cross talk. Cold Spring Harb Perspect Biol. 2011 Mar; 3(3).

Luch A. Nature and nurture - lessons from chemical carcinogenesis. Nat Rev Cancer. 2005 Feb; 5(2):113–125.

Maciejewski H. Gene set analysis methods: statistical models and methodological differences. Brief Bioinformatics. 2014 Jul; 15(4):504–518.

Mandriota SJ, Jussila L, Jeltsch M, Compagni A, Baetens D, Prevo R, Banerji S, Huarte J, Montesano R, Jackson DG, Orci L, Alitalo K, Christofori G, Pepper MS. Vascular endothelial growth factor-C-mediated lymphangiogenesis promotes tumour metastasis. EMBO J. 2001 Feb; 20(4):672–682.

Min L, Ji Y, Bakiri L, Qiu Z, Cen J, Chen X, Chen L, Scheuch H, Zheng H, Qin L, Zatloukal K, Hui L, Wagner EF. Liver cancer initiation is controlled by AP-1 through SIRT6-dependent inhibition of survivin. Nat Cell Biol. 2012 Nov; 14(11):1203–1211.

Mitra K, Carvunis AR, Ramesh SK, Ideker T. Integrative approaches for finding modular structure in biological networks. Nat Rev Genet. 2013 Oct; 14(10):719–732.

Mitrea C, Taghavi Z, Bokanizad B, Hanoudi S, Tagett R, Donato M, Voichita C, Draghici S. Methods and approaches in the topology-based analysis of biological pathways. Front Physiol. 2013 Oct; 4:278.

Mocsai A, Ruland J, Tybulewicz VL. The SYK tyrosine kinase: a crucial player in diverse biological functions. Nat Rev Immunol. 2010 Jun; 10(6):387–402.

Montorsi M, Maggioni M, Falleni M, Pellegrini C, Donadon M, Torzilli G, Santambrogio R, Spinelli A, Coggi G, Bosari S. Survivin gene expression in chronic liver disease and hepatocellular carcinoma. Hepatogastroenterology. 2007; 54(79):2040–2044.

Nault JC, Zucman-Rossi J. TERT promoter mutations in primary liver tumors. Clin Res Hepatol Gastroenterol. 2016 Feb; 40(1):9–14.

Nusse R, Clevers H. Wnt/Î²-Catenin Signaling, Disease, and Emerging Therapeutic Modalities. Cell. 2017 Jun; 169(6):985–999.

Patil KR, Nielsen J. Uncovering transcriptional regulation of metabolism by using metabolic network topology. Proc Natl Acad Sci USA. 2005 Feb; 102(8):2685–2689.

Qu C, Zheng D, Li S, Liu Y, Lidofsky A, Holmes JA, Chen J, He L, Wei L, Liao Y, Yuan H, Jin Q, Lin Z, Hu Q, Jiang Y, Tu M, Chen X, Li W, Lin W, Fuchs BC, et al. Tyrosine kinase SYK is a potential therapeutic target for liver fibrosis. Hepatology. 2018 Mar; .

Quaas A, Oldopp T, Tharun L, Klingenfeld C, Krech T, Sauter G, Grob TJ. Frequency of TERT promoter mutations in primary tumors of the liver. Virchows Arch. 2014 Dec; 465(6):673–677.

Roussos ET, Condeelis JS, Patsialou A. Chemotaxis in cancer. Nat Rev Cancer. 2011 Jul; 11(8):573–587.

Sharir M. A strong-connectivity algorithm and its applications to data flow analysis. Computers and Mathematics with applications. 1981; 7(1):67–72.

Shin SH, Lee KH, Kim BH, Lee S, Lee HS, Jang JJ, Kang GH. Downregulation of spleen tyrosine kinase in hepatocellular carcinoma by promoter CpG island hypermethylation and its potential role in carcinogenesis. Lab Invest. 2014 Dec; 94(12):1396–1405.

Su C. Survivin in survival of hepatocellular carcinoma. Cancer Lett. 2016 09; 379(2):184–190.

Subramanian A, Tamayo P, Mootha VK, Mukherjee S, Ebert BL, Gillette MA, Paulovich A, Pomeroy SL, Golub TR, Lander ES, Mesirov JP. Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. Proc Natl Acad Sci USA. 2005 Oct; 102(43):15545–15550.

Sun C, Sun L, Li Y, Kang X, Zhang S, Liu Y. Sox2 expression predicts poor survival of hepatocellular carcinoma patients and it promotes liver cancer cell invasion by activating Slug. Med Oncol. 2013 Jun; 30(2):503.

Szklarczyk D, Morris JH, Cook H, Kuhn M, Wyder S, Simonovic M, Santos A, Doncheva NT, Roth A, Bork P, Jensen LJ, von Mering C. The STRING database in 2017: quality-controlled protein-protein association networks, made broadly accessible. Nucleic Acids Res. 2017 Jan; 45(D1):D362–D368.

Takigawa Y, Brown AM. Wnt signaling in liver cancer. Curr Drug Targets. 2008 Nov; 9(11):1013–1024.

Tammela T, Zarkada G, Wallgard E, Murtomaki A, Suchting S, Wirzenius M, Waltari M, Hellstrom M, Schomber T, Peltonen R, Freitas C, Duarte A, Isoniemi H, Laakkonen P, Christofori G, Yla-Herttuala S, Shibuya M, Pytowski B, Eichmann A, Betsholtz C, et al. Blocking VEGFR-3 suppresses angiogenic sprouting and vascular network formation. Nature. 2008 Jul; 454(7204):656–660.

Tarca AL, Draghici S, Khatri P, Hassan SS, Mittal P, Kim JS, Kim CJ, Kusanovic JP, Romero R. A novel signaling pathway impact analysis. Bioinformatics. 2009 Jan; 25(1):75–82.

Thorpe LM, Yuzugullu H, Zhao JJ. PI3K in cancer: divergent roles of isoforms, modes of activation and therapeutic targeting. Nat Rev Cancer. 2015 Jan; 15(1):7–24.

Tomczak K, Czerwi?ska P, Wiznerowicz M. The Cancer Genome Atlas (TCGA): an immeasurable source of knowledge. Contemp Oncol (Pozn). 2015; 19(1A):68–77.

Totoki Y, Tatsuno K, Covington KR, Ueda H, Creighton CJ, Kato M, Tsuji S, Donehower LA, Slagle BL, Nakamura H, Yamamoto S, Shinbrot E, Hama N, Lehmkuhl M, Hosoda F, Arai Y, Walker K, Dahdouli M, Gotoh K, Nagae G, et al. Trans-ancestry mutational landscape of hepatocellular carcinoma genomes. Nat Genet. 2014 Dec; 46(12):1267–1273.

Tuncbag N, Braunstein A, Pagnani A, Huang SS, Chayes J, Borgs C, Zecchina R, Fraenkel E. Simultaneous reconstruction of multiple signaling pathways via the prize-collecting steiner forest problem. J Comput Biol. 2013 Feb; 20(2):124–136.

Tuncbag N, Gosline SJ, Kedaigle A, Soltis AR, Gitter A, Fraenkel E. Network-Based Interpretation of Diverse High-Throughput Datasets through the Omics Integrator Software Package. PLoS Comput Biol. 2016 Apr; 12(4):e1004879.

Tvorogov D, Anisimov A, Zheng W, Leppanen VM, Tammela T, Laurinavicius S, Holnthoner W, Helotera H, Holopainen T, Jeltsch M, Kalkkinen N, Lankinen H, Ojala PM, Alitalo K. Effective suppression of vascular network formation by combination of antibodies blocking VEGFR ligand binding and receptor dimerization. Cancer Cell. 2010 Dec; 18(6):630–640.

Uen YH, Fang CL, Hseu YC, Shen PC, Yang HL, Wen KS, Hung ST, Wang LH, Lin KY. VAV3 oncogene expression in colorectal cancer: clinical aspects and functional characterization. Sci Rep. 2015 Mar; 5:9360.

Ulitsky I, Krishnamurthy A, Karp RM, Shamir R. DEGAS: de novo discovery of dysregulated pathways in human diseases. PLoS ONE. 2010 Oct; 5(10):e13367.

Ulitsky I, Shamir R. Identification of functional modules using network topology and high-throughput data. BMC Syst Biol. 2007 Jan; 1:8.

Ulitsky I, Shamir R. Identifying functional modules using expression profiles and confidence-scored protein interactions. Bioinformatics. 2009 May; 25(9):1158–1164.

Undevia SD, Gomez-Abuin G, Ratain MJ. Pharmacokinetic variability of anticancer agents. Nat Rev Cancer. 2005 Jun; 5(6):447–458.

Vandin F, Raphael BJ, Upfal E. On the Sample Complexity of Cancer Pathways Identification. J Comput Biol. 2016 Jan; 23(1):30–41.

Vandin F, Upfal E, Raphael BJ. De novo discovery of mutated driver pathways in cancer. Genome Res. 2012 Feb; 22(2):375–385.

Vandin F, Upfal E, Raphael BJ. Finding driver pathways in cancer: models and algorithms. Algorithms Mol Biol. 2012 Sep; 7(1):23.

Vaske CJ, Benz SC, Sanborn JZ, Earl D, Szeto C, Zhu J, Haussler D, Stuart JM. Inference of patient-specific pathway activities from multi-dimensional cancer genomics data using PARADIGM. Bioinformatics. 2010 Jun; 26(12):i237–245.

Vilchez V, Turcios L, Marti F, Gedaly R. Targeting Wnt/Î²-catenin pathway in hepatocellular carcinoma treatment. World J Gastroenterol. 2016 Jan; 22(2):823–832.

Wang Z, Gerstein M, Snyder M. RNA-Seq: a revolutionary tool for transcriptomics. Nat Rev Genet. 2009; 10:57–63.

Wen W, Han T, Chen C, Huang L, Sun W, Wang X, Chen SZ, Xiang DM, Tang L, Cao D, Feng GS, Wu MC, Ding J, Wang HY. Cyclin G1 expands liver tumor-initiating cells by Sox2 induction via Akt/mTOR signaling. Mol Cancer Ther. 2013 Sep; 12(9):1796–1804.

Wen Y, Jeong S, Xia Q, Kong X. Role of Osteopontin in Liver Diseases. Int J Biol Sci. 2016; 12(9):1121–1128.

Wu Y, Liu H, Ding H. GPC-3 in hepatocellular carcinoma: current perspectives. J Hepatocell Carcinoma. 2016; 3:63–67.

You F, Castro PM, Grossmann IE. Dinkelbach's algorithm as an efficient method to solve a class of MINLP models for large-scale cyclic scheduling problems. Computers & Chemical Engineering. 2009; 33:1879–1889.

Yue D, Guillén-Gosálbez G, You F. Global optimization of large-scale mixed-integer linear fractional programming problems: a reformulation-linearization method and process scheduling applications. AIChE Journal. 2013; 59(11):4255–4272.

Zhang J, Zhang S. The Discovery of Mutated Driver Pathways in Cancer: Models and Algorithms. IEEE/ACM Trans Comput Biol Bioinform. 2018; 15(3):988–998.

Zhang JD, Wiemann S. KEGGgraph: a graph approach to KEGG PATHWAY in R and bioconductor. Bioinformatics. 2009 Jun; 25(11):1470–1471.

Zhao XM, Wang RS, Chen L, Aihara K. Uncovering signal transduction networks from high-throughput data by integer linear programming. Nucleic Acids Res. 2008 May; 36(9):e48.

Zhou F, Shang W, Yu X, Tian J. Glypican-3: A promising biomarker for hepatocellular carcinoma diagnosis and treatment. Med Res Rev. 2018 03; 38(2):741–767.

Geneset A   **Geneset B**

Figure 1–Figure supplement 1. Conceptual view of classical pathway/gene set analysis. Gene sets/pathways are considered merely as sets of genes ignoring any explicit biomolecular interactions between the elements of a gene set/pathway. Here red nodes represent differentially regulated genes and a basic GSE analysis employing hypergeometric Over-representation analysis (ORA) would test for more red nodes than expected in any given gene set.

Pathway A   **Pathway B**

Figure 1–Figure supplement 2. Conceptual view of topological pathway/analysis. Biomolecular interaction are taken into account when calculating enrichment for any given pathway. Gene sets/pathways are still predefined though and interactions between pathways are usually not taken into account

Pathway A   Pathway B

Figure 1–Figure supplement 3. Conceptual view of topological pathway/analysis with pathway crosstalks. Pathway crosstalks happen when genes are part of multiple pathways. They can also happen if there are genes in two pathways with interactions between them from another pathway. Even with pathway crosstalks accounted for, the gene sets/pathways as such are still predetermined.

Figure 1–Figure supplement 4. Conceptual view of de-novo pathway analysis. De-novo pathway identification / deregulated subnetwork discovery drops the predetermined pathways and defines enriched subnetworks/pathways from the omics data itself.

788

Figure 4–Figure supplement 1. GPC3-mediated activation of WNT signaling is a well-documented process in liver cancer. The figure shows the relevent KEGG map (Proteoglycans in cancer: hsa05205) with TCGA-LIHC min-max-scaled $\log_2$ fold changes mapped onto the genes. This process was automatically recaptured by our upregulated subgraphs for TCGA-LIHC. Related to Figure 4.

789

Figure 4–Figure supplement 2. Optimal upregulated global subgraph for TCGA-LIHC

Figure 4–Figure supplement 3. 1^{st} **suboptimal upregulated global subgraph for** **TCGA-LIHC**

Figure 4–Figure supplement 4. 2^{nd} **suboptimal upregulated global subgraph for** **TCGA-LIHC**

Figure 4–Figure supplement 5. 3^{rd} **suboptimal upregulated global subgraph for** **TCGA-LIHC**

Figure 4–Figure supplement 6. 4^{th} **suboptimal upregulated global subgraph for** **TCGA-LIHC**

Figure 5–Figure supplement 1. Expression of FOS and JUN isoforms in tumor of TCGA-LIHC cohort. (A) Log_2-fold changes of FOS isoforms in individual tumors compared to the mean control value of the TCGA-LIHC dataset. (B) Log_2 fold changes of JUN isoforms in individual tumors compared to the mean control value of the TCGA-LIHC dataset. Bars in waterfall plot indicate mRNA downregulation $\geq$ 1.5-fold (blue),mRNA upregulation $\geq$ 1.5-fold (red). Related to Figure 5.

Figure 5–Figure supplement 2. Optimal downregulated global subgraph for TCGA-LIHC

796

Figure 5–Figure supplement 3. 1^{st} **suboptimal downregulated global subgraph for TCGA-LIHC**

797

Figure 5–Figure supplement 4. 2^{nd} **suboptimal downregulated global subgraph for TCGA-LIHC**

Figure 5–Figure supplement 5. 3^{rd} **suboptimal downregulated global subgraph for TCGA-LIHC**

Figure 5–Figure supplement 6. 4^{th} **suboptimal downregulated global subgraph for TCGA-LIHC**

800

Figure 6–Figure supplement 1. Subset of genes whose inclusion into a patient's inferred subgraph indicates a poor survival. Survival difference is calculated using Kaplan-Meier estimates and log-rank test. Related to Figure 6.

Supplementary File 1: Appendix

1   **Sebastian Winkler**[1,2*]**, Ivana Winkler**[2,3,4]**, Mirjam Figaschewski**[1]**, Thorsten Tiede**[1]**,**

2   **Alfred Nordheim**[2,3,4,5]**, Oliver Kohlbacher**[1,2,6,7]

*For correspondence:
sebastian.winkler@dereg.net (SW)

[1]Applied Bioinformatics, Dept. of Computer Science, University of Tübingen, Tübingen,

Germany; [2]International Max Planck Research School (IMPRS) "From Molecules to

Organisms", Tübingen, Germany; [3]Interfaculty Institute for Cell Biology (IFIZ), University

of Tübingen, Tübingen, Germany; [4]German Cancer Consortium (DKTK), German Cancer

Research Center (DKFZ), Heidelberg, Germany; [5]Leibniz Institute on Aging (FLI), Jena,

Germany; [6]Institute for Bioinformatics and Medical Informatics, University of Tübingen,

Tübingen, Germany; [7]Translational Bioinformatics, University Hospital Tübingen,

Tübingen, Germany

Abstract   This document contains details concerning the Material and Methods outlined in the

main paper ***de novo* identification of maximally deregulated subnetworks based on**

multi-omics data with DeRegNet. It provides details about the following topics:

• Directions on how to run the DeRegNet software

• Definition and derivation of the probabilistic model underlying DeRegNet, as well as the

proof that DeRegNet corresponds to maximum likelihood estimation under outlined model

• DeRegNet in the context of the general optimization problem referred to as the *Maximum*

Average Weight Connected Subgraph Problem and its relatives

• Proofs of certain structural properties of DeRegNet solutions

• Different application modes of the DeRegNet algorithms

• Fractional mixed-integer programming as it relates to the solution of DeRegNet instances

• Lazy constraints in branch-and-cut MILP solvers as it relates to DeRegNet

• Further solution technology employed for solving DeRegNet instances

• DeRegNet benchmark simulations

• Use of DeRegNet subgraphs as a basis for feature engineering for survival prediction on the

TCGA-LIHC dataset

How to use the DeRegNet software

DeRegNet Docker images and Gurobi setup

The main source code repository for DeRegNet is available here: https://github.com/sebwink/deregnet.

DeRegNet is licensed under the BSD 3-clause OSI-approved open source license. The primary

route to run DeRegNet is via Docker images which package DeRegNet and all its dependencies.

Hence, in terms running DeRegNet on a Linux host there are only two dependencies: Docker and a

Gurobi license. The official Docker images for DeRegNet can be found here: https://hub.docker.com/reposit

For instructions for setting up a Gurobi license for running DeRegNet it is referred to the source

code repository where one can always find up-to-date information. The *sebwink/deregnet* Docker

images support basically two modes of usage: command-line and Python package.

Running DeRegNet via Docker

Assuming you have Docker and a named-user Gurobi license configured, running DeRegNet in command-line mode is as easy as running

```
git clone https://github.com/sebwink/deregnet && cd deregnet
docker/named-user/run sebwink/deregnet:0.99.999 avgdrgnt.py --help
```

which would display all available command-line options for avgdrgnt.py (i.e. DeRegNet's main script):

```
usage: avgdrgnt.py [-h] [--include-file INCLUDE_FILE]
                   [--include-genesets INCLUDE_GENESETS] [--include INCLUDE]
                   [--include-id-type INCLUDE_ID_TYPE]
                   [--exclude-file EXCLUDE_FILE]
                   [--exclude-genesets EXCLUDE_GENESETS] [--exclude EXCLUDE]
                   [--exclude-id-type EXCLUDE_ID_TYPE] [--debug]
                   [--absolute-values] --graph GRAPH --scores SCORE_FILE
                   [--default-score DEFAULT_SCORE] [--score-column SCORE_COL]
                   [--score-file-without-header] [--id-column ID_COL]
                   [--sep SEP] [--biomap-mapper ID_MAPPER]
                   [--score-id-type SCORE_ID_TYPE]
                   [--graph-id-type GRAPH_ID_TYPE]
                   [--graph-id-attr GRAPH_ID_ATTR] [--suboptimal SUBOPTIMAL]
                   [--max-overlap-percentage MAX_OVERLAP] [--gap-cut GAP_CUT]
                   [--time-limit TIME_LIMIT] [--model_sense {min,max}]
                   [--output-path OUTPUT] [--flip-orientation]
                   [--min-size MIN_SIZE] [--max-size MAX_SIZE]
                   [--min-num-terminals MIN_NUM_TERMINALS]
                   [--algorithm {GeneralizedCharnesCooper,Dinkelbach,
                   ObjectiveVariableTransform}]
                   [--receptor-file RECEPTOR_FILE]
                   [--receptor-genesets RECEPTOR_GENESETS]
                   [--receptor RECEPTOR] [--receptor-id-type RECEPTOR_ID_TYPE]
                   [--terminal-file TERMINAL_FILE]
                   [--terminal-genesets TERMINAL_GENESETS]
                   [--terminal TERMINAL] [--terminal-id-type TERMINAL_ID_TYPE]

optional arguments:
  -h, --help            show this help message and exit
  --include-file INCLUDE_FILE
                        Path to GMT or GRP file containing genes defining the
                        include layer.
  --include-genesets INCLUDE_GENESETS
                        Comma seperated list of geneset names for include
                        layer, only applicable if GMT file provided.
  --include INCLUDE     Comma seperated list of IDs defining the include
                        layer.
  --include-id-type INCLUDE_ID_TYPE
                        Id-type for include layer genesets. Options: all
                        supported by chosen biomap mapper
  --exclude-file EXCLUDE_FILE
                        Path to GMT or GRP file containing genes defining the
                        exclude layer.
  --exclude-genesets EXCLUDE_GENESETS
                        Comma seperated list of geneset names for exclude
                        layer, only applicable if GMT file provided.
  --exclude EXCLUDE     Comma seperated list of IDs defining the exclude
                        layer.
  --exclude-id-type EXCLUDE_ID_TYPE
                        Id-type for exclude layer genesets. Options: all
                        supported by chosen biomap mapper
  --debug               Debug underlying C++ code with gdb.
```

```
 99    −−absolute−values    Whether to take absolute values of the scores.
100    −−graph GRAPH        A graphml file containing the graph you want to run
101                        drgnt with.
102    −−scores SCORE_FILE  A text file containing the scores. See further options
103                        below.
104    −−default−score DEFAULT_SCORE
105                        The score of nodes in the graph which are not scored
106                        in your score file. Default: 0.0
107    −−score−column SCORE_COL
108                        Column name of (gene) id in your score file. Default:
109                        score
110    −−score−file−without−header
111                        Flag to indicate whether the score file has a header
112                        or not.
113    −−id−column ID_COL   Column name of (gene) id in your score file. Default:
114                        id
115    −−sep SEP            The column seperator in your score file.Options:
116                        comma, tab. Default: \t
117    −−biomap−mapper ID_MAPPER
118                        biomap mapper you want to use for id mapping. Default:
119                        hgnc
120    −−score−id−type SCORE_ID_TYPE
121                        Which id type do you have in your score file? Options:
122                        all thosesupported by the biomap mapper you chose or
123                        unspecified. Default: same as graph id type
124    −−graph−id−type GRAPH_ID_TYPE
125                        Which id type does the graph have? Options: all those
126                        supportedby the biomap mapper you chose or
127                        unspecified. Default: unspecifed i.e. None
128    −−graph−id−attr GRAPH_ID_ATTR
129                        Node attribute which contains the relevant id in the
130                        graphml. Default: name
131    −−suboptimal SUBOPTIMAL
132                        Number of suboptimal subgraphs you want to find.
133                        (Increases runtime)
134    −−max−overlap−percentage MAX_OVERLAP
135                        How much can suboptimal subgraphs overlap with already
136                        found subgraphs. Default: 0
137    −−gap−cut GAP_CUT    Stop optimization prematurely if current solution
138                        within GAP of optimal solution. Default: None
139    −−time−limit TIME_LIMIT
140                        Set a time limit in seconds. Default: None
141    −−model_sense {min,max}
142                        Model sense. Default: max
143    −−output−path OUTPUT Folder to which output is written. (Does not have to
144                        exist.) Default : cwd
145    −−flip−orientation   Set −−flip−orientation when you want to flip the
146                        orientation of the underlying graph.
147    −−min−size MIN_SIZE  Minimal size of the resulting subgraph(s). Default :
148                        15
149    −−max−size MAX_SIZE  Maximal size of the resulting subgraph(s). Default :
150                        15
151    −−min−num−terminals MIN_NUM_TERMINALS
152                        Minimum number of terminals in the resulting
153                        subgraph(s). Default : 0
154    −−algorithm {GeneralizedCharnesCooper,Dinkelbach,ObjectiveVariableTransform}
155                        Algorithm to use to solve the fractional integer
156                        programming problem.Default: GeneralizedCharnesCooper.
157    −−receptor−file RECEPTOR_FILE
158                        Path to GMT or GRP file containing genes defining the
159                        receptor layer.
```

```
160    --receptor-genesets RECEPTOR_GENESETS
161                      Comma seperated list of geneset names for receptor
162                      layer,only applicable if GMT file provided.
163    --receptor RECEPTOR    Comma seperated list of IDs defining the receptor
164                      layer.
165    --receptor-id-type RECEPTOR_ID_TYPE
166                      Id-type for receptor layer genesets. Options: all
167                      supported by chosen biomap mapper
168    --terminal-file TERMINAL_FILE
169                      Path to GMT or GRP file containing genes defining the
170                      terminal layer.
171    --terminal-genesets TERMINAL_GENESETS
172                      Comma seperated list of geneset names for terminal
173                      layer,only applicable if GMT file provided.
174    --terminal TERMINAL    Comma seperated list of IDs defining the terminal
175                      layer.
176    --terminal-id-type TERMINAL_ID_TYPE
177                      Id-type for terminal layer genesets. Options: all
178                      supported by chosen biomap mapper
```

Still in the top-level of the repository, you can find your first subgraph like so:

```
180    docker/named-user/run sebwink/deregnet:latest avgdrgnt.py \
181      --graph test/kegg_hsa.graphml \
182      --scores test/data/score.csv \
183      --sep , \
184      --graph-id-attr ensembl
```

This will generate *deregnet.log* and finally *optimal.graphml* where the former is a log of the optimization procedure carried out by DeRegNet and the latter the resulting optimal subgraph in GraphML format. For more information on GraphML, the most prominent graph serialization format supported by DeRegNet, see: http://graphml.graphdrawing.org/.

DeRegNet Python package via Docker

For more custom analyses it is often necessary to work with the deregnet Python package directly. This is also supported by the *sebwink/deregnet* Docker images which come with all the relevant packages pre-installed and properly configured. E.g. in order to run the benchmarks presented in the main text, you can follow the directions given here: https://github.com/sebwink/deregnet/tree/master/e Running any Python script which uses the *deregnet* Python package is then as easy as:

```
195    docker/named-user/run sebwink/deregnet:0.99.999 python3 any_script.py
```

Results concerning the probabilistic model for DeRegNet

This subsection formalizes the notion that a *deregulated* subgraph satisfying given topological constraints should have higher/maximal probability of deregulation with respect to all possible subgraphs of that particular topological class. We present a basic probabilistic model yielding one possible formal probabilistic rationale for optimizing a model of form given in the main paper. Furthermore we provide a suitable interpretation of the model proposed in *Backes et al.* (*2012*) in terms of that model, showing that DeRegNet solves a more general problem in the statistical sense necessitated by the probabilistic model introduced in the main text.

For sake of locality of exposition we restate the statistical model as introduced in the main text. The model assumes binary node scores $s : V \rightarrow \{0,1\}$ which are realizations of random variables $\mathbf{S} = (S_v)_{v \in V}$. Further it is assumed the existence of a subset of vertices $V' \subset V$ such that $S_v | v \in V' \sim Ber(p')$ and $S_v | v \in V \setminus V' \sim Ber(p)$ with $p, p' \in (0,1)$ denoting probabilites of deregulation outside and inside of the deregulated subgraph respectively. It is assumed that $p' > p$ to reflect the idea of *higher* deregulation (probability) in the *deregulated* subgraph. The network context (dependency) is introduced via the restriction that $V' \in \mathcal{C}(V) \subset \mathcal{P}(V)$. Here, $\mathcal{C}(V)$ denotes the set of

feasible substructures and should (can) reflect topologies inspired by known biomolecular path-
way topologies like the one described in *Backes et al.* (*2012*) and the last subsection. Furthermore
it is assumed, that the (S_v), given a network context and deregulation probabilities p, p', are inde-
pendent. We further introduce the notation $\alpha(\tilde{V}) := |\{v \in \tilde{V} : S_v = 1\}|$ and considering V', p, p'
to be parameters, and a subgraph determined by indicator variables x as outlined in the previous
subsection, we can state:

Proposition 1

The log-likelihood $\mathcal{L}_s(\tilde{V}, p, p') = \log \mathbf{P}(\mathbf{S} = \mathbf{s}|V' = \tilde{V}, p, p')$ under above model is given by:

$$s^T x \log \frac{p'(1-p)}{p(1-p')} - e^T x \log \frac{1-p}{1-p'} + s^T e \log p + (e-s)^T e \log(1-p).$$

Proof.

$$\mathbf{P}(\mathbf{S} = \mathbf{s}|V' = \tilde{V}, p, p') = \prod_{v \in \tilde{V}} \mathbf{P}(S_v = s_v|V' = \tilde{V}, p') \cdot \prod_{v \in V \setminus \tilde{V}} \mathbf{P}(S_v = s_v|V' = \tilde{V}, p)$$

$$= p'^{\alpha(\tilde{V})}(1-p')^{|\tilde{V}|-\alpha(\tilde{V})} p^{\alpha(V \setminus \tilde{V})}(1-p)^{|V \setminus \tilde{V}|-\alpha(V \setminus \tilde{V})}$$

217 Employing decision variables $x_v = \mathbf{I}(v \in \tilde{V})$, we can write $\alpha(\tilde{V}) = s^T x, |\tilde{V}| = e^T x, \alpha(V \setminus \tilde{V}) = s^T(e-x)$
218 and $|V \setminus \tilde{V}| = e^T(e - x)$. It follows that the log-likelihood $\mathcal{L}_s(x, p, p') = \mathcal{L}_s(\tilde{V}, p, p') = \log \mathbf{P}(\mathbf{S} = \mathbf{s}|V' =$
219 $\tilde{V}, p, p')$ can be written as:

$$\mathcal{L}_s(\tilde{V}, p, p') = s^T x \log p' + (e-s)^T x \log(1-p')$$
$$+ s^T(e-x) \log p + (e-s)^T(e-x) \log(1-p)$$
$$= s^T x \log \frac{p'(1-p)}{(1-p')p} - e^T x \log \frac{1-p}{1-p'} + s^T e \log p + (e-s)^T e \log(1-p)$$

220 ∎

221 I call an optimization model maximizing the objective $s^T x$ subject to any constraints on x (the
222 subgraph topology) a *model of Backes-type* *Backes et al.* (*2012*). Note that the DeRegNet model
223 reduces to a Backes-type model in case of $k_{min} = k_{max}$.

Proposition 2

225 *Any subgraph model of Backes-type enforcing a fixed subgraph size can be interpreted as maximum*
226 *likelihood estimation with respect to subgraph structure given the above model.*

227 *Proof.* Given the log-likelihood as determined by proposition 1, ignoring the constant term with
228 respect to x, a maximum likelihood estimator V^* with respect to subgraph structure can be deter-
229 mined as follows:

$$V^* \in \underset{\tilde{V} \subset C(V)}{\operatorname{argmax}} \mathcal{L}_s(\tilde{V}, p, p') \tag{1}$$

$$= \underset{\tilde{V} \subset C(V)}{\operatorname{argmax}} \left\{ s^T x \log \frac{p'(1-p)}{p(1-p')} - e^T x \log \frac{1-p}{1-p'} \right\} \tag{2}$$

$$= \underset{\tilde{V} \subset C(V)}{\operatorname{argmax}} \left\{ s^T x \log \frac{p'(1-p)}{p(1-p')} \right\} \tag{3}$$

$$= \underset{\tilde{V} \subset C(V)}{\operatorname{argmax}} \ s^T x \tag{4}$$

Here, equality (2.4) follows from the assumption that the topological constraints of the opti-
mization model enforce a constant subgraphs size (i.e. $e^T x = k$ for some fixed $k \in \mathbb{N}$). The last
equality follows (by assumption $p' > p$) because $\log \frac{p'(1-p)}{p(1-p')} > 0$. Overall, a maximum likelihood es-
timator is given by a solution to a given Backes-type optimization model $\max \ s^T x$ with subgraph
topology restricted to subgraphs from $C(V)$.

∎

---

236   In particular, the specific model proposed by *Backes et al.* (*2012*) lends itself to the just justified
237 interpretation:

Corollary 1

The optimization model suggested by Backes et al. (2012) can be interpreted as maximum likelihood
estimation with respect to subgraph structure given the above probabilistic model.

I now proceed to provide a maximum likelihood interpretation for the DeRegNet model. Since
the DeRegNet model does not assume a fixed subgraph size, above conclusions do not apply. Un-
der the assumption that the parameter p is estimated external to the model and represents some
general base level of deregulation one can by (conceptual) reduction from the full log-likelihood
$\mathcal{L}_s(\tilde{V}, p, p')$ to $\mathcal{L}_s(\tilde{V}, p')$ state the following proposition.

Proposition 3

247 *Solving a DeRegNet instance amounts to maximum likelihood estimation under above model with re-*
248 *spect to subgraph structure and deregulation probability p' (assuming $p' > 0$).*

Proof. Given the log-likelihood as in proposition 1, one can differentiate with respect to p':

$$\frac{\partial}{\partial p'} \mathcal{L}_s(\tilde{V}, p, p') = \frac{\partial}{\partial p'} \mathcal{L}_s(\tilde{V}, p') \tag{5}$$

$$= \frac{\partial}{\partial p'} s^T x \log \frac{p'(1-p)}{(1-p')p} - \frac{\partial}{\partial p'} e^T x \log \frac{1-p}{1-p'} \tag{6}$$

249 By computing

$$\frac{\partial}{\partial p'} \log \frac{p'(1-p)}{(1-p')p} = \frac{\partial}{\partial p'} \log \frac{p'}{p} - \frac{\partial}{\partial p'} \log \frac{1-p'}{1-p} \tag{7}$$

$$= \frac{p}{p'} \cdot \frac{1}{p} - \frac{1-p}{1-p'} \cdot \frac{-1}{1-p} \tag{8}$$

$$= \frac{1}{p'} + \frac{1}{1-p'} \tag{9}$$

250 and

$$\frac{\partial}{\partial p'} \log \frac{1-p'}{1-p} = -\frac{1}{1-p'} \tag{10}$$

251 one obtains

$$\frac{\partial}{\partial p'} \mathcal{L}_s(\tilde{V}, p') = s^T x \frac{1}{p'} + s^T x \frac{1}{1-p'} - e^T x \frac{1}{1-p'} \tag{11}$$

252 Requiring $\frac{\partial}{\partial p'} \mathcal{L}_s(\tilde{V}, p'^*) = 0$ and with

$$\frac{\partial}{\partial p'} \mathcal{L}_s(\tilde{V}, p'^*) = 0 \Leftrightarrow \frac{1-p'^*}{p'^*} + 1 = \frac{e^T x}{s^T x} \tag{12}$$

$$\Leftrightarrow p'^* = \frac{s^T x}{e^T x} \tag{13}$$

253 and[1]

$$\frac{\partial^2}{\partial p'^2} \mathcal{L}_s(\tilde{V}, p') = s^T x \frac{-1}{p'^2} + s^T x \frac{1}{(1-p')^2} - e^T x \frac{1}{(1-p')^2} \leq -\frac{e^T x}{p'^2} < 0 \tag{14}$$

---

[1]Since $s^T x \leq e^T x$ and $e^T x > 0$ under the assumption that the subgraphs are constrained to have at least one node and $p' > 0$.

254 one arrives at

$$V^*_{MLE} \in \underset{\tilde{V} \subset \mathcal{C}(V)}{\operatorname{argmax}} \ p'^* = \underset{\tilde{V} \subset \mathcal{C}(V)}{\operatorname{argmax}} \ \frac{s^T x}{e^T x} \tag{15}$$

since no terms involving x were dropped in the derivation for p'^*.

∎

The propositions of this subsection show, that, given the introduced statistical model, solving
a DeRegNet instance instead of an instance of the optimization model proposed in *Backes et al.*
(*2012*) allows to carry out maximum likelihood estimation without the need to fix the subgraph
size in advance. Given the assumptions of the model, these results hold regardless of further
topological constraints and only relate to the respective objective functions.

Maximum Average Weight Connected Subgraph Problems

(Rooted) Maximum (Average) Weight Connected Subgraph Problems

In terms of mathematical optimization and up to minor modifications[2], *Backes et al.* (*2012*) solve
instances of the so called (Rooted) Maximum Weight Connected Subgraph Problem.

Definition 1 (Maximum Weight Connected Subgraph Problem (MWCSP))
Given a directed graph $G = (V, E)$ and node scores $s : V \rightarrow \mathbb{R}$, find a set of nodes $V' \subset V$ whose
induced subgraph (V', E') maximizes $e^T_{V'} s$ such that there is a node $r \in V'$ such that there is a directed
path from r to every other node $v \in V'$.

By fixing the root node in the MWCSP to a particular node in the underlying graph one arrvies at
the so called **Rooted Maximum Weight Connected Subgraph Problem (RMWCSP)**:

Definition 2 (Rooted Maximum Weight Connected Subgraph Problem (RMWCSP))
Given a directed graph $G = (V, E)$, node scores $s : V \rightarrow \mathbb{R}$, and a node $r \in V$ called the root node, find a
set of nodes $V' \subset V$ whose induced subgraph (V', E') maximizes $e^T_{V'} s$ such that there is a directed path
from r to every other node $v \in V'$.

The (R)MWCSP has found applications in network biology *Dittrich et al.* (*2008*), *Backes et al.* (*2012*).
It also attracted general computational and theoretical research in recent years *Buchanan et al.*
(*2017*), *Loboda et al.* (*2016*), from different integer programming formulations and problem-specific
branch-and-cut strategies *El-Kebir and Klau* (*2014*), *Álvarez-Miranda et al.* (*2013a*), *Álvarez-Miranda et al.*
(*2013b*), *Althaus and Blumenstock* (*2011*), to more recent research on computational strategies for
addressing large-scale instances *Álvarez Miranda and Sinnl* (*2017*) and problem reduction tech-
niques and heuristics *Rehfeldt et al.* (*2019*), *Rehfeldt and Koch* (*2019*).

The Maximum Average Weight Connected Subgraph Problem (MAWCSP)

Analogously to the (R)MWCSP one can define versions which strive to optimize the average score
in the subgraph.

Definition 3 (Maximum Average Weight Connected Subgraph Problem (MAWCSP))
Given a directed graph $G = (V, E)$ and node scores $s : V \rightarrow \mathbb{R}$, find a set of nodes $V' \subset V$ whose
induced subgraph (V', E') maximizes $\frac{e^T_{V'} s}{e^T e_{V'}}$ such that there is a node $r \in V'$ such that there is a directed
path from r to every other node $v \in V'$.

Definition 4 (Rooted Maximum Average Weight Connected Subgraph Problem (RMAWCSP))
Given a directed graph $G = (V, E)$, node scores $s : V \rightarrow \mathbb{R}$, and a node $r \in V$ called the root node, find
a set of nodes $V' \subset V$ whose induced subgraph (V', E') maximizes $\frac{e^T_{V'} s}{e^T e_{V'}}$ such that there is a directed
path from r to every other node $v \in V'$.

DeRegNet solves extended versions of the (Rooted) Maximum Average Weight Connected Sub-
graph Problem.

---

[2]For example the requirement of the subgraphs to be of a certain predefined size $k \in \mathbb{N}$.

Some formal properties of DeRegNet solutions

In terms of the notation and exact formulation provided in the main text, we will here formally spec-
ify certain topological characteristics of solutions of the above model which were hinted at before.
For similar proofs and also alternative formulations for the MWCSP it is referred to *Backes et al.*
(*2012*), *Álvarez-Miranda et al.* (*2013b*), *Álvarez-Miranda et al.* (*2013a*), *El-Kebir and Klau* (*2014*), *Althaus and*
(*2011*). I first formally recapture the defining topological feature of problems of (R)M(A)WCS flavour
for DeRegNet.

Proposition 4

*A feasible subgraph V^* of a DeRegNet instance has the property that any node in the subgraph can be
reached from the root of the subgraph.*

Proof. Any given node $v \in V^*$ of the subgraph is contained in a strongly connected component.
By constraints (2.1e) and (2.1f) this strongly connected component either contains the root node
or is reachable from some node $u \in V^*$ in the subgraph which is not in that strongly connected
component: Let $S \subset V$ be the vertex set inducing the strongly connected component. If the root
is not in S we have $e_S^T(x - y) = |S|$ and hence it need to hold $e_{\delta^-(S)}^T x \geq 1$, otherwise one would have
$e_S^T(x - y) - e_{\delta^-(S)}^T x \geq |S|$ in violation of constraints (2.1e) and (2.1f). If the root node is in S, it holds
that $e_S^T(x - y) = |S| - 1$ and hence constraints (2.1e) and (2.1f) always hold due to $e_{\delta^-(S)}^T x \geq 0$. In
the case, that the root node is in v's component, v is reachable from the root node. In the case the
component does not contain the root, repeat the argument with u instead of v. Again, the root is
in the strongly connected component of u or the component is reachable from some $u' \in V^*$, and
so on. Since the subgraph has a finite number of strongly connected components, one ultimately
will encounter the component containing the root in the above argument which proves the the
existence of a path to any arbitrary $v \in V^*$ from the root node. ∎

The terminals from the terminal set T represent terminals of a subgraph in the following sense.

Proposition 5

*A feasible subgraph V^* of a DeRegNet instance has the property that a node $v \in V*$ in the subgraph
with $v \notin T$ has to have an outgoing edge into the subgraph, i.e. only terminal nodes are allowed to have
no outgoing edges within the subgraph.*

Proof. Given a non-terminal node $v \notin T$ one has constraint (2.1h): $x_v - e_{\delta^+(v)}^T x \leq 0$, i.e. if $x_v = 1$ it
has to hold that $e_{\delta^+(v)}^T x \geq 1$. The latter inequality means that there exists another node $u \in V^*$ such
that $(v, u) \in E$, E being the edge set of the underlying graph. ∎

Further application modes of DeRegNet

Fixing the root node

Instead of the *root* being determined by the algorithm as outlined in the previous paragraph, one
can also specify a given node $r \in V$ as root *Backes et al.* (*2012*). In this case, one does not need the
y variables anymore and, since the constraint logic can be carried over analogously, we can write

332   the corresponding fractional integer problem as:

$$\max_{x \in \{0,1\}^V} \quad \frac{s^T x}{e^T x} \tag{16a}$$

$$\text{s.t.} \quad x_r = 0 \tag{16b}$$

$$k_{min} \le e^T x \le k_{max} \tag{16c}$$

$$x_v - e_{\delta^-(v)}^T x \le 0 \quad \forall v \in V \setminus \{r\} \tag{16d}$$

$$e_S^T x - e_{\delta^-(S)}^T x \le |S| - 1 \quad \forall S \subset V \ iscs, \ |S| > 1 \tag{16e}$$

$$x_v - e_{\delta^+(v)}^T x \le 0 \quad \forall v \in V \setminus T \ \text{ if } T \ne \varnothing \tag{16f}$$

$$e_{\textbf{Inc}}^T x = |\textbf{Inc}| \tag{16g}$$

$$e_{\textbf{Ex}}^T x = 0 \tag{16h}$$

333   Note, that the above formulation is a special case of the more general formulation of the pre-
334   vious section, namely $R = \{r\}$. It is nonetheless convenient to sometimes refer to the tuple
335    $(G, r, T, \textbf{Ex}, \textbf{Inc}, s)$ as a *rooted DeRegNet instance*. All other terminology from the general case carries
336   over without modification.

Reversing the orientation

The default version of the just outlined algorithm will find subnetworks which possess a "root"
node from which one can reach any other node in the subnetwork. This can be interpreted as the
subnetwork being deregulated downstream of that root. As outlined in the previous sections, this
root can either be determined by the algorithm or pre-determined by biological curiosity or insight.
By reversing the orientation of the graph one can easily obtain subnetworks where the "root" can
be reached from any node in the subnetwork. Such a subgraph can be interpreted as deregulated
upstream of the either algorithmically determined or user-defined "root" node. In that case a
more intuitive name for the "root" is "terminal" or "destination". Formally this difference in the
structure of the output can be achieved by substituting the original graph G with the transposed
graph $\tilde{G} = (V, \tilde{E})$, $\tilde{E} = \{(u, v) \in V \times V : (v, u) \in E\}$, and defining the models as before with the roles
of receptors and terminals exchanged.

Definition 5

A ***reverse solution*** of a DeRegNet instance $I = (G, R, T, \textbf{Ex}, \textbf{Inc}, s)$ with underlying graph $G = (V, E)$
is the (graph) transpose of an optimal subgraph of the DeRegNet instance $\tilde{I} = (\tilde{G}, T, R, \textbf{Ex}, \textbf{Inc}, s)$. The
latter is called the reverse instance of I. *Here,* $\tilde{G}$ *denotes the transposed graph of* G, *i.e.* $\tilde{G} = (V, \tilde{E})$,
$\tilde{E} = \{(u, v) \in V \times V : (v, u) \in E\}$.

After the algorithm found subnetworks with respect to the reversed graph the resulting subnet-
works have to be re-reversed to reflect physical reality. Also note, that the reversed instance ex-
changes the roles of receptors and terminal nodes to keep the intuitive notions associated with
these terms in line with the topology of the just defined reverse solutions.

Extracting suboptimal subnetworks

Although the strategy to optimize seems like a sensible heuristic, it is nonetheless just an heuris-
tic. There is no intrinsic need for a biological system at hand to behave consistently with this
optimization objective in the sense that it is not granted that the patterns found by the algorithm
actually correspond to what is biologically important in the given situation. Vice versa, something
(nodes, a particular pattern of nodes) not showing up in any subgraph does not mean that they
may not be important in the given context. While this cannot be mediated completely, it is sensi-
ble to find at least possible suboptimal patterns along with the optimal one. This can be seen as a
step to capture mathematically speaking slightly less optimal but biologically potentially similarly

or even more important patterns. I implement this notion by following the appproach found in
(*Dittrich et al., 2008*) and adapt it to DeRegNet. Given a specified *maximal overlap* $\alpha \in [0, 1)$ and
a (induced) subgraph $V^* \subset V$ one adds to the DeRegNet model as stated in the main part of the
paper the suboptimality constraint $e_{V^*}^T x \leq \alpha \cdot e^T x$ and reoptimizes, forcing any corresponding sub-
graph to be found to maximally have $100 \cdot \alpha$ % node overlap with the the nodes of the previously
found subgraph. One can iterate this theme. For example, given a set of subgraphs $V^{(1)}, ..., V^{(k)}$ for
some $k \in \mathbb{N}$ one can add the constraints $e_{V^{(j)}}^T x \leq \alpha \cdot e^T x$ for all $j = 1, ..., k$ to the DeRegNet instance to
obtain a optimal subgraph of that modified DeRegNet instance which is guaranteed to have node
overlap $\leq \alpha$ with any of the $V^{(j)}$. With $V^{(1)} = V^*$ being the original optimal subgraph of a DeRegNet
instance one thus obtains a series of suboptimal subgraphs $V^{(2)}, ..., V^{(k)}$. The question which k to
choose can be for example decided such that one chooses the k for which $\frac{e_{V^{(k+1)}}^T s}{|V^{(k+1)}|} < \beta \cdot \frac{e_{V^*}^T s}{|V^*|}$ for the
first time for some $\beta \in [0, 1]$. Here, β quantifies the degree of suboptimality one is willing to accept.

Fractional mixed-integer programming

Definition 6 (Fractional mixed-integer linear program; FMILP)

*A **Fractional mixed-integer linear program (FMILP)** is an optimization problem of the following struc-
ture:*

$$\max \quad \frac{c^T x + d}{p^T x + q} \tag{17a}$$

$$\text{s.t.} \quad x \in \mathbb{R}^{n_c} \times \mathbb{Z}^{n_i} \tag{17b}$$

$$Ax \leq b \tag{17c}$$

Here, $c, p \in \mathbb{R}^n$, $d, q \in \mathbb{R}$ define the objective, $A \in \mathbb{R}^{m \times n}$, $b \in \mathbb{R}^m$ define $m \in \mathbb{N}$ linear constraints and
$n_c \in \mathbb{N}$, $n_i \in \mathbb{N}$ denote the number of continuous and discrete (integer) variables.

We assume $\forall x \in \mathcal{F} : p^T x + q > 0$, $\mathcal{F} := \{x \in \mathbb{R}^n : Ax \leq b\}$. Fractional mixed-integer lin-
ear problems are hence mixed-integer problems except for the objective which is a rational func-
tion with linear enumerator and denominator instead. While a FMILP is non-convex, it turns out
that a FMILP is pseudolinear and hence quasilinear, rendering local optima to be globally optimal
You et al. (*2009*).

Proposition 6

388 *A FMILP is pseudoconvex and pseudoconcave.*

Proposition 7

390 *A FMILP is strictly quasiconvex and strictly quasiconcave.*

Proposition 8

A local optimum of a FMILP is also a global optimum.

The latter facts render FMILP solvable by any generic mixed-integer nonlinear programming
(MINLP) solver which can handle pseudolinear objective functions *You et al.* (*2009*). Empirically,
it was shown that iterative schemes *You et al.* (*2009*) or linearization-reformulation approaches
Yue et al. (*2013*) outperform generic MINLP solvers with respect to computing time and memory
footprint. These approaches rely on a mixed-integer linear programming (MILP) solver as their
optimization kernel, hence unlocking the power of modern MILP software, and rely on transform-
ing the original problem into a (sequence of) MILP problem(s). The DeRegNet software pack-
age discussed in the main text implements a Dinkelbach-type algorithm *You et al.* (*2009*) and
a reformulation-linearization method *Yue et al.* (*2013*) resembling the Charnes-Cooper method
Charnes and Cooper (*1962*) for solving fractional linear programs (FLP). The following sections pro-
vide algorithmic details on the these methods.

Dinkelbach-type algorithm (Dinkelbach algorithm)

Originating in the 1960's *Dinkelbach* (*1962*, 1967) and studied in the context of FMILP problems *Anzai* (*1974*); *You et al.* (*2009*) later on, the Dinkelbach algorithm relies on the iterative solution of linear problems only containing the original variables and an auxiliary iteration parameter. *Algorithm 1* details the procedure. In the following, as well as in the entire thesis, *Dinkelbach algorithm* and *Dinkelbach-type algorithm* are used synonymously to refer to *Algorithm 1*.

Algorithm 1: Dinkelbach-type algorithm

Data: FMILP with feasible set $\mathcal{S}$

Result: solution x^* of FMILP

Initialization:

$\pi = 0$

$\epsilon > 0$ (termination tolerance)

$F = \infty$

while $F > \epsilon$ **do**

$\quad\quad x^* = arg\,max\,\{c^T x + d - \pi\,(p^T x + q)\,:\,x \in \mathcal{S}\}$

$\quad\quad F = c^T x^* + d - r\,(p^T x^* + q)$

$\quad\quad \pi = \dfrac{c^T x^* + d}{p^T x^* + q}$

return x^*

The mixed-integer linear program appearing in the *while*-loop of *algorithm 1* is called a *Dinkelbach iteration problem*. Dinkelbach's algorithm iteratively solves a sequence Dinkelbach iteration problems until some convergence criterion is met. The follwing subsection shows that this procedure indeed solves the original FMILP.

Correctness of Dinkelbach's Algorithm (1) - based on You et al.*You et al.* (*2009*)

In order to facilitate the following exposition the functions $N\,:\,\mathcal{F} \to \mathbb{R}, N(x) := c^T x + d$ for the nominator and $D\,:\,\mathcal{F} \to \mathbb{R}, D(x) := p^T x + q$ for the denominator of the objective function are introduced. Without loss of generality one can set $d = q = 0$ since one can introduce dummy variables x_d and x_q with linear constraints $x_d = x_q = 1$ and corresponding coefficients $c_d = p_q = 1$ leading to $N(x) = c^T x + c_d x_d$ and $D(x) = p^T x + p_q x_q$. Furthermore, define $L_\pi(x) := N(x) - \pi D(x)$ and $F\,:\,\mathbb{R} \to \mathbb{R}, F(\pi) := \max\,\{L_\pi(x)\,:\,x \in \mathcal{F}\}$ be the optimal objective value of a Dinkelbach iteration problem as a function of the auxiliary parameter π. Without loss of generality we assume $D(x) > 0$ for all $x \in \mathcal{F}$.

The two main results concerning Dinkelbach's algorithm are the following:

Proposition 9 (Optimality criterion, *Yue et al.* (*2013*) Proposition 1)

$F(\pi^*) = \max\,\{N(x) - \pi D(x)\,:\,x \in \mathcal{F}\} = 0 \iff \pi^* = \frac{N(x^*)}{D(x^*)} = \max\,\{\frac{N(x)}{D(x)}\,:\,x \in \mathcal{F}\}$ *where* $x^* = \operatorname{argmax}\{\frac{N(x)}{D(x)}\,:\,x \in \mathcal{F}\}$

Proposition 10 (Convergence (rate), *Yue et al.* (*2013*) Proposition 2)

Dinkelbach's algorithm converges superlinearly to π^* *in where* $x^* \in \operatorname{argmax}\{\frac{N(x)}{D(x)}\,:\,x \in \mathcal{F}\}$ *and* $\pi^* = \frac{N(x^*)}{D(x^*)}$.

We follow *Yue et al.* (*2013*) in proving the above propositions via a series of lemmas.

Lemma 1 (*Yue et al.* (*2013*) Appendix, Lemma 4)

F is convex.

Proof. For $\lambda \in [0, 1]$, let $x_\lambda \in \mathcal{F}$ be $x_\lambda \in \operatorname{argmax}\{L_{\lambda\pi' + (1-\lambda)\pi''}(x)\,:\,x \in \mathcal{F}\}$ with $\pi', \pi'' \in \mathbb{R}$. Then:

$$F(\lambda\pi' + (1 - \lambda)\pi'') = \max\,\{L_\pi(x)\,:\,x \in \mathcal{F}\} \tag{18}$$

$$= N(x_\lambda) - [\lambda\pi' + (1 - \lambda)\pi'']D(x) \tag{19}$$

$$= \lambda[N(x_\lambda) - \pi'D(x_\lambda)] + (1 - \lambda)[N(x_\lambda) - \pi''D(x_\lambda)] \tag{20}$$

$$= \lambda F(\pi') + (1 - \lambda)F(\pi'') \tag{21}$$

434   ∎

Lemma 2 (*Yue et al.* (*2013*) Appendix, Lemma 5)

F is strictly monotonically increasing, i.e. $\pi' < \pi'' \implies F(\pi') < F(\pi'')$.

Proof. Given $\pi' < \pi''$ one obtains with $x' = \text{argmax}\{L_{\pi'}(x) : x \in \mathcal{F}\}$ and $x'' = \text{argmax}\{L_{\pi''}(x) : x \in \mathcal{F}\}$:

$$F(\pi'') = N(x'') - \pi'' D(x'') \tag{22}$$

$$< N(x'') - \pi' D(x'') \tag{23}$$

$$\leq N(x') - \pi' D(x') \tag{24}$$

$$= F(\pi') \tag{25}$$

437   ∎

Lemma 3 (*Yue et al.* (*2013*) Appendix, Lemma 6)

$F(\pi) = 0$ *has a unique solution.*

Proof. Follows from $\lim_{\pi \to \infty} F(\pi) = -\infty$ and $\lim_{\pi \to -\infty} F(\pi) = \infty$ and F being strictly monotonically increasing (Lemma 2).   ∎

Lemma 4 (*Yue et al.* (*2013*) Appendix, Lemma 7)

$\forall x' \in \mathcal{F} : F(\frac{N(x')}{D(x')}) \geq 0$

Proof. For any $x' \in \mathcal{F}$ one has:

$$F\left(\frac{N(x')}{D(x')}\right) = \max\left\{N(x) - \frac{N(x')}{D(x')} D(x) : x \in \mathcal{F}\right\} \tag{26}$$

$$\geq N(x') - \frac{N(x')}{D(x')} D(x') \tag{27}$$

$$= 0 \tag{28}$$

444   ∎

One can now prove proposition 1:

Proof of proposition 1. We have to show: $F(\pi^*) \iff \pi^* = \frac{N(x^*)}{D(x^*)} = max_{x \in \mathcal{F}} \frac{N(x)}{D(x)}$.

$\implies$: Given $F(\pi^*) = max_{x \in \mathbb{F}} N(x) - \pi^* D(x)$ it follows with $x^* := \text{argmax}\{N(x) - \pi^* D(x) : x \in \mathcal{F}\}$ for all $x \in \mathcal{F}$ $0 = N(x^*) - \pi^* D(x^*) \geq N(x) - \pi^* D(x)$. Hence $\frac{N(x)}{D(x)} \leq \pi^* = \frac{N(x^*)}{D(x^*)}$, i.e. $x^* = \text{argmax}\{\frac{N(x)}{D(x)} : x \in \mathcal{F}\}$.

$\impliedby$: With $x^* = \text{argmax}\{\frac{N(x)}{D(x)} : x \in \mathcal{F}\}$ one has $\pi^* = \frac{N(x^*)}{D(x^*)} \geq \frac{D(x)}{N(x)}$. Under our general assumption $D(x) > 0$ for all $x \in \mathcal{F}$ it follows $N(x) - \pi^* D(x) \leq 0 = N(x^*) - \pi^* D(x^*)$ for all $x \in \mathcal{F}$ which shows $x^* = \text{argmax}\{N(x) - \pi^* D(x) : x \in \mathcal{F}\}$.

452   ∎

From now onward, let π^* be the unique solution of $F(\pi) = 0$ and let $x^* \in \text{argmax}\{\frac{N(x)}{D(x)} : x \in \mathcal{F}\}$ with $\pi^* = \frac{N(x^*)}{D(x^*)}$.

Lemma 5 (*Yue et al.* (*2013*) Appendix, Lemma 8)

Let $x' \in \text{argmax}\{N(x) - \pi' D(x)\}$ and $x'' \in \text{argmax}\{N(x) - \pi'' D(x) : x \in \mathcal{F}\}$ with $\pi' < \pi''$, then $D(x') \geq D(x'')$.

Proof. Adding the inequalities $N(x') - \pi' D(x') \geq N(x'') - \pi' D(x')$ and $N(x'') - \pi'' D(x'') \geq N(x') - \pi'' D(x')$ leads to $(\pi'' - \pi')D(x') \geq (\pi'' - \pi')D(x'')$, i.e. $D(x') \geq D(x'')$ since $\pi'' \geq \pi'$ by assumption.   ∎

Lemma 6 (*Yue et al.* (*2013*) Appendix, Lemma 9)

Let $x' \in \text{argmax}\{N(x) - \pi' D(x)\}$ and $x'' \in \text{argmax}\{N(x) - \pi'' D(x) : x \in \mathcal{F}\}$, then $f(x'') - f(x') \geq \frac{F(\pi'')}{D(x'')} - \frac{F(\pi')}{D(x')}$

Proof. From $F(\pi'') = N(x'') - \pi'' D(x'') \geq N(x') - \pi'' D(x'')$ it follows $\frac{N(x'')}{D(x')} - \pi'' \frac{D(x'')}{D(x')} \geq \frac{N(x')}{D(x')} - \pi''$. This implies:

$$\frac{N(x'')}{D(x'')} - \frac{N(x')}{D(x')} \geq \frac{N(x'')}{D(x'')} + (-\pi'' + \frac{D(x'')}{D(x')}\pi'' - \frac{N(x'')}{D(x')}) \tag{29}$$

$$= \frac{N(x'')}{D(x'')} - \frac{N(x'')}{D(x')} + \pi''(\frac{D(x'')}{D(x')} - \frac{D(x'')}{D(x'')}) \tag{30}$$

$$= N(x'')(\frac{1}{D(x'')} - \frac{1}{D(x')}) + \pi'' D(x'')(\frac{1}{D(x'')} - \frac{1}{D(x'')}) \tag{31}$$

$$= -F(\pi'')(\frac{1}{D(x')} - \frac{1}{D(x'')}) \tag{32}$$

$$= \frac{F(\pi'')}{D(x'')} - \frac{F(\pi'')}{D(x')} \tag{33}$$

462 ■

Lemma 7 (*Yue et al.* (*2013*) Appendix, Lemma 10)

Let $x' \in \mathrm{argmax}\{N(x) - \pi' D(x)\}$ and $x'' \in \mathrm{argmax}\{N(x) - \pi'' D(x) : x \in \mathcal{F}\}$ and $F(\pi^*) = 0$, then if follows for $\pi' \leq \pi'' \leq \pi^*$, that $\frac{N(x')}{D(x')} \leq \frac{N(x'')}{D(x'')}$.

Proof.

$$\frac{N(x'')}{D(x'')} - \frac{N(x')}{D(x')} \geq \frac{F(\pi'')}{D(x'')} - \frac{F(\pi')}{D(x')} \tag{34}$$

$$\geq \frac{F(\pi'')}{D(x')} - \frac{F(\pi'')}{D(x')} \tag{35}$$

$$= 0 \tag{36}$$

The first inequality follows from lemma 9, the second from lemma 7 and 8. ■

Lemma 8 (*Yue et al.* (*2013*) Appendix, Lemma 11)

Let $x' \in \mathrm{argmax}\{N(x) - \pi' D(x)\}$ and $x'' \in \mathrm{argmax}\{N(x) - \pi'' D(x) : x \in \mathcal{F}\}$, then $f(x'') - f(x') \leq (-F(\pi'') + (\pi' - \pi'')D(x''))(\frac{1}{D(x')} - \frac{1}{D(x'')})$.

Proof. From $N(x') - \pi' D(x') \geq N(x'') - \pi'' D(x'')$ it follows $\frac{N(x')}{D(x')} - \pi' \geq \frac{N(x'')}{D(x')} - \pi' \frac{N(x'')}{D(x')}$ by dividing by $D(x') > 0$. It then follows:

$$f(x'') - f(x') = \frac{N(x'')}{D(x'')} - \frac{N(x')}{D(x')} \tag{37}$$

$$\leq \frac{N(x'')}{D(x'')} - \pi' - \frac{N(x'')}{D(x')} + \pi' \frac{D(x'')}{D(x')} \tag{38}$$

$$= \frac{N(x'')}{D(x'')} - \frac{N(x'')}{D(x')} - \pi'(\frac{D(x'')}{D(x'')} - \frac{D(x'')}{D(x')}) \tag{39}$$

$$= (-N(x'') + \pi' D(x''))(\frac{1}{D(x')} - \frac{1}{D(x'')}) \tag{40}$$

$$= (-F(\pi'') + (\pi' - \pi'')D(x''))(\frac{1}{D(x')} - \frac{1}{D(x'')}) \tag{41}$$

470 ■

Lemma 9 (*Yue et al.* (*2013*) Appendix, Lemma 12)

Let $x' \in \mathrm{argmax}\{N(x) - \pi' D(x)\}$ and $x'' \in \mathrm{argmax}\{N(x) - \pi'' D(x) : x \in \mathcal{F}\}$ with $F(\pi^*) = N(x^*) - \pi^* D(x^*) = 0$, then $\pi^* - f(x') \leq (\pi^* - \pi')(1 - \frac{D(x^*)}{D(x')})$.

Proof.

$$\pi^* - f(x') = f(x^*) - f(x') \tag{42}$$

$$\leq (-F(\pi^*) + (\pi' - \pi^*)D(x^*))(\frac{1}{D(x')} - \frac{1}{D(x^*)}) \tag{43}$$

$$= (\pi' - \pi^*)(\frac{D(x^*)}{D(x')} - 1) \tag{44}$$

$$= (\pi^* - \pi')(1 - \frac{D(x^*)}{D(x')}) \tag{45}$$

474 where the inequality follows from Lemma 11. ∎

475 Proposition 2 can now be demonstrated as follows:

476 *Proof of proposition 2.* Let $F(\pi^*) = 0$, i.e. $\pi^* = \max\{\frac{N(x)}{D(x)} : x \in \mathcal{F}\}$. For $i \in \mathbb{N}$, let $\pi_{i+1} = \frac{N(x_i)}{D(x_i)} = f(x_i)$
477 where $x_i \in \text{argmax}\{N(x) - \pi_i D(x) : x \in \mathcal{F}\}$ it follows with Lemma 9:

$$\frac{\pi^* - \pi_{i+1}}{\pi^* - \pi_i} = \frac{\pi^* - f(x_i)}{\pi^* - \pi_i} \leq 1 - \frac{D(x^*)}{D(x_i)}$$

Since $\pi_i \leq \pi^* = \max\{\frac{N(x)}{D(x)} : x \in \mathcal{F}\}$ it follows with Lemma 5 $\frac{D(x^*)}{D(x_i)} \leq 1$ and since $\frac{D(x^*)}{D(x_i)} > 0$ one obtains

$$0 \leq \frac{\pi^* - \pi_{i+1}}{\pi^* - \pi_i} < 1$$

478 for all $i \in \mathbb{N}$. The latter inequality demonstrates superlinear convergence. ∎

479 Correctness of Dinkelbach's algorithm for solving the DeRegNet model

Here, we prove that the fractional integer programming model for finding deregulated subgraphs
proposed in the main text can be solved via Dinkelbach's algorithm. The only points to clarify are
the suitability of Dinkelbach's algorithm for models with lazy constraints, the suitability of an initial
value for π of 0 and the positivity of the objective denominator, see last subsection.

Proposition 11 (Dinkelbach-type algorithm for DeRegNet)
The Dinkelbach algorithm is correct for the fractional integer programming problem of DeRegNet.

Proof. The first point to observe is that the objective of DeRegNet is always ≥ 0 hence the initial-
ization condition of the iteration parameter $\pi = 0$ statisfies $\pi \leq \pi^*$. Furthermore, for subgraphs
which are constrained to contain at least one node, the denominator of the objective is strictly pos-
itive. These two properties are enough to guarantuee convergence of Dinkelbach's algorithm as
detailed above. Also since the original decision variables are also part of the parameterized Dinkel-
bach iteration problems introducing lazy constraints is technically feasible. Since lazy constraints
can only decrease the maximum objective, after every iteration $\pi \leq \pi^*$ where π^* is the optimal
objective determined by the current constraints and hence lazy constraints do not interfere with
the correctness of Dinkelbach's algorithm since it requires a starting value of π which is a lower
bound of the optimal objective value. ∎

Note that lazy constraints effectively amount to restarting Dinkelbach's algorithm (in a valid initial-
ization state) every time a lazy constraint is added. Hence, convergence can also only be consid-
ered superlinear (see last subsection) with respect to the current optimal objective determined by
the lazy constraints.

Reformulation-Linearization methods

Generalized Charnes-Cooper method

The so called Generalized Charnes-Cooper transformation *Yue et al. (2013)* described in this sub-section derives its name and general idea from the classical Charnes-Cooper transformation *Charnes and Co* (*1962*) used to solve continuous fractional linear problems. Consider the above general form of a FMIP in the following slightly more detailed format:

$$\max \quad \frac{c_c^T x_c + c_i^T x_i + d}{p_c^T x_c + p_i^T x_i + q} \tag{46a}$$

$$\text{s.t.} \quad x = \begin{pmatrix} x_c \\ x_i \end{pmatrix} \in \mathbb{R}^{n_c} \times \mathbb{Z}^{n_i} \tag{46b}$$

$$A_c x_x + A_i x_i \leq b \tag{46c}$$

where we explicitly decomposed the variable x into its continuous and integer parts. Analogously we have $c = \begin{pmatrix} c_c \\ c_i \end{pmatrix}$ with $c_c \in \mathbb{R}^{n_c}$, $c_i \in \mathbb{R}^{n_i}$, and $p = \begin{pmatrix} p_c \\ p_i \end{pmatrix}$ with $p_c \in \mathbb{R}^{n_c}$, $p_i \in \mathbb{R}^{n_i}$, and $A = \begin{pmatrix} A_c & A_i \end{pmatrix}$ with $A_c \in \mathbb{R}^{m \times n_c}$, $A_i \in \mathbb{R}^{m \times n_i}$. As detailed in *Yue et al. (2013)* one can now define additional variables $u := \frac{1}{p_c^T x_c + p_i^T x_i + q}$ and $z := \frac{x_c}{p_c^T x_c + p_i^T x_i + q} = ux$. Note, since we assume that there exists some real $m > 0$ such that $p^T x + q > m$ for all feasible $x \in \mathbb{R}^n$, it follows that $u > 0$. After incorporating the definition of u as a further constraint and multiplying all constraints with u one arrives at the following quadratic mixed-integer problem:

$$\max \quad c_c^T z + c_i^T (u \cdot x_i) + d \tag{47a}$$

$$\text{s.t.} \quad x_i \in \mathbb{Z}^{n_i}, \ z \in \mathbb{R}^{n_c}, \ u \in \mathbb{R}_+ \tag{47b}$$

$$p_c^T z + p_i^T (u \cdot x_i) + qu = 1 \tag{47c}$$

$$A_c z + A_i (u \cdot x_i) - bu \leq 0 \tag{47d}$$

Note that the above problem is not a MILP but a quadratic mixed-integer problem due to the terms ux_i in the transformed constraints. This is addressed in the next subsection. With the notation of this subsection one can formulate the following propositions formalizing the equivalence of the two model formulations *Yue et al. (2013)*:

Proposition 12 (Feasible points of the generalized Charnes-Cooper transform)
A point (x_c, x_i) is a feasible solution of problem (A.30) if and only if (z, x_i, u) is a feasible solution of problem (A.31).

Proof. Because of $p_c^T x_c + p_i^T x_i + q > 0$ this is true by definition of u and z. ■

Proposition 13 (Equivalence of solutions of the generalized Charnes-Cooper transform)
An feasible point (x_c^*, x_i^*) of (A.30) is optimal if and only if (z^*, x_i^*, u^*) is optimal for (A.31). It holds that $z^* = u^* x_c^*$ and $u^* = \frac{1}{p_c^T x_c^* + p_i^T x_i^* + q}$.

Proof. By definition of u and z the objectives of (A.30) and (A.31) have the same value for all feasible points. The relations for the optimal points are also true by definition. ■

With respect to lazy constraints involving the integer variables x_i there do not arise any complications since they are part of both problem formulations. Lazy constraints for the continuous variables x_c require more care due to the necessity to transform the constraints correspondingly. The DeRegNet model does only contain integer (in fact, binary) variables and hence it is straight-forward to incorporate lazy constraints in the solution process in terms of the original model formulation.

Linearization of binary-continuous quadratic constraints

In contrast to the iterative Dinkelbach scheme, the reformulation-linearization method described
in the last section relies on the linearization of products of integer and continuous variables. Since
we only deal with binary variables in this paper, we assume from now on that all integer variables
are in fact binary. In case of a proper integer variable $x \in D \subset \mathbb{Z}$, one can introduce auxiliary binary
variables $x'_d \in \{0,1\}, d \in D$ with $x = \sum_{d \in D} d \cdot x'_d$ and $\sum_{d \in D} x'_d = 1$ in order to transform its product with
continuous variables into a sum of products between binary and continuous variables. There exist
variations on the theme of linearization *Adams et al.* (*2004*), *Adams and Forrester* (*2005*), but here
we will present the implemented most basic version going back to *Glover* (*1975*).
541
542 Given a continuous variable $v \in \mathbb{R}$ and a binary variable $x \in \{0,1\}$ one introduces a third (contin-
543 uous) variable $z \in \mathbb{R}$ corresponding to $z = vx$ and substitutes any appearance of the product vx
544 with z. Along with z one introduces the following constraints to ensure equivalence:

$$
\begin{aligned}
z &\leq Ux \\
z &\geq Lx \\
v - U(1-x) &\leq z \\
v - L(1-x) &\geq z
\end{aligned}
\tag{48}
$$

Here, $U \in \mathbb{R}$ is an upper and $L \in \mathbb{R}$ is a lower bound of v which are either given by the problem
formulation itself, can be inferred from manual insight into the problem or by solving a certain
MILP in some cases. See below.

Proposition 14 (Linearization binary-continuous products)
Let $v \in S \subset \mathbb{R}$ with bounded S and let $x \in \{0,1\}$ and $z \in \mathbb{R}$. Furthermore $U \geq \sup S$ and $L \leq \inf S$.
Then, the constraints (A.15) are statisfied if and only if $z = vx$.

Proof. Let $z = vx$, then $z = vx \leq Ux$ since U is an upper bound of v and $z = vx \geq Lx$ since L is a
lower bound of v. Also for the case $x = 1$ one has $v - U(1-x) = v = vx = z$ and $v - L(1-x) = v = vx = z$
and for the case $x = 0$ the two constraints $v - U(1-x) \leq z$ and $v - L(1-x) \geq z$ reduce to $v \leq U$
and $v \geq L$ respectively which is true by assumption. Conversely, let the constraints in (A.15) be
satisfied. Then in the case $x = 1$, the constraints $v - U(1-x) \leq z$ and $v - L(1-x) \geq z$ imply $v \leq z \leq v$
and hence $z = v = vx$. In the case $x = 0$ the first two constraints of (A.15) imply $z = 0 = vx$. ∎

The lower bound L and the upper bound U can generally be obtained by solving suitable MILPs
Yue et al. (*2013*) involving the denominator of the original objective. To obtain the (tightest possi-
ble) lower bound one can solve the following problem:

$$
\max \quad p_c^T x_c + p_i^T x_i + q
\tag{49a}
$$

$$
\text{s.t.} \quad x = \begin{pmatrix} x_c \\ x_i \end{pmatrix} \in \mathbb{R}^{n_c} \times \mathbb{Z}^{n_i}
\tag{49b}
$$

$$
A_c x_x + A_i x_i \leq b
\tag{49c}
$$

560 Analogously to obtain the (tightest possible) upper bound one can solve the following mini-
561 mization problem:

$$
\min \quad p_c^T x_c + p_i^T x_i + q
\tag{50a}
$$

$$
\text{s.t.} \quad x = \begin{pmatrix} x_c \\ x_i \end{pmatrix} \in \mathbb{R}^{n_c} \times \mathbb{Z}^{n_i}
\tag{50b}
$$

$$
A_c x_x + A_i x_i \leq b
\tag{50c}
$$

Note however, that any lower and upper bound would work. The trade-off between less tight
bounds on the denominator variable and the necessity of solving up to two MILPs up front has to
be decided for every model.
In case of DeRegNet, lower and upper bound on the objective denominator are explicitly set
in the problem formulation in the form of minimal and maximal subgraph size. Hence one does
not have to solve any MILPs up front and has (optimal) lower and upper bounds for the inverse
denominator readily available due to the problem formulation.

Software for solving fractional integer programs: libgrbfrc

In order to solve the fractional integer programs formulated in the main text, a C++ library based
on the commercial Gurobi solver was implemented. libgrbfrc (https://sebwink.github.io/libgrbfrc/)
in particular implements the two solution methods from above: Dinkelbach's algorithm and the
generalized Charnes-Cooper transform. Due to the requirements of the developed optimization
models (see main text) the implementations support lazy constraints. Academic licenses for Gurobi
are readily obtained.

Lazy constraints in branch-and-cut MILP solvers

577 For reference this section contains an high-level outline of how lazy constraints fit into branch-and-
578 cut algorithms for solving mixed-integer programs. The exposition is adapted from *Conforti et al.*
579 (*2014*).
580 Let a MILP with $n_c \in \mathbb{N}$ continuous and $n_i \in \mathbb{N}$ integer variables of the following form be given:

$$\max \quad c^T x + d^T y \tag{51a}$$

$$\text{s.t.} \quad x \in \mathbb{R}^{n_c} \tag{51b}$$

$$y \in \mathbb{Z}^{n_i} \tag{51c}$$

$$Ax + By \le b \tag{51d}$$

$$x, y \ge 0 \tag{51e}$$

581 Here $c \in \mathbb{R}^{n_c}$, $d \in \mathbb{R}^{n_i}$, $A \in \mathbb{R}^{m \times n_c}$ and $B \in \mathbb{R}^{m \times n_i}$ for some $m \in \mathbb{N}$. The *(natural) linear programming*
582 *relaxation* of a MILP of the above form is the following:

$$\max \quad c^T x + d^T y \tag{52a}$$

$$\text{s.t.} \quad x \in \mathbb{R}^{n_c} \tag{52b}$$

$$y \in \mathbb{R}^{n_i} \tag{52c}$$

$$Ax + By \le b \tag{52d}$$

$$x, y \ge 0 \tag{52e}$$

583 Lazy constraints are constraints which are not initially explicitly part of the model formulation, the
584 reason usually being that it would require an infeasable exponential number of constraints (with
585 respect to the number of variables).
586 The classical branch-and-cut strategy for solving MILPs with lazy constraints can then be formu-
587 lated as the following algorithm 2.

Lazy constraints for the DeRegNet model

589 For DeRegNet the lazy constraint separation subroutine centers around finding the strongly con-
590 nected components of the given solution. This is generally considered an efficiently solvable prob-
591 lem.

Algorithm 2: Branch-and-cut for MILPs with lazy constraints

Data: MILP and lazy constraints

Result: Solution of MILP satisfying any lazy constraint

Initialization:

$\mathcal{L} = \{\text{MILP}\}$ (Set of MILP problems in search tree)

$\underline{z} = -\infty$ (Current best lower bound for optimal objective)

$(x^*, y^*) = (null, null)$ (Current best feasible solution)

while $\mathcal{L} \neq \varnothing$ **do**

    Choose P from $\mathcal{L}$ and remove P from $\mathcal{L}$

    (*) Solve linear programming relaxation of P

    Let z be the solution value and (x, y) be the solution of the relaxation

    if $z > \underline{z}$ **then**

        if (x, y) *feasible for P* **then**

            Find the set $\mathbf{V}$ of violated lazy constraints

            if $\mathbf{V} = \varnothing$ **then**

                $(x^*, y^*) := (x, y)$

                $\underline{z} := z$

            else

                Insert P back into $\mathcal{L}$

                Add lazy constraints from $\mathbf{V}$ to models in $\mathcal{L}$

        else

            if *you want to add cuts* **then**

                Add cuts and GOTO (*)

            else

                Branch and add created subproblems to $\mathcal{L}$

return (x^*, y^*), $\underline{z}$

₅₉₂ Strongly connected components

₅₉₃ Given a directed graph $G = (V, E)$ one says that G is strongly connected if and only if there is a
₅₉₄ directed path from every node $v \in V$ to every other node $u \in V$. A strongly connected component
₅₉₅ of a directed graph is any maximal subgraph which is strongly connected[3]. Sometimes one refers
₅₉₆ to $V' \subset V$ as inducing a strongly connected component if the subgraph induced by V' is a strongly
₅₉₇ connected component. One denotes the set of node sets inducing all strongly connected compo-
₅₉₈ nents of a graph $G = (V, E)$ by **SCC**$(G) \subset \mathcal{P}(V)$. The three classical algorithms which can be used
₅₉₉ to solve the problem of finding a directed graph's strongly connected components in $O(|V| + |E|)$
₆₀₀ time are the Kosarju-Sharir algorithm *Sharir* (*1981*), Tarjan's algorithm *Tarjan* (*1972*) and variants
₆₀₁ of the path-based strong component algorithm *Dijkstra* (*1972*). A strongly connected *subgraph* (in
₆₀₂ contrast to *component*) is a subgraph of a graph which is strongly connected.

₆₀₃ Lazy constraint separation subroutine of DeRegNet

₆₀₄ This subsection and algorithm 3 provide the details on the lazy constraint separation subroutine
₆₀₅ employed for the solution of the DeRegNet model. The formal details are given as algorithm 3.
₆₀₆ In short, given a (potential) incumbent solution to a DeRegNet instance not containing all strong-
₆₀₇ component constraints, the subroutine finds the strongly connected components of the corre-
₆₀₈ sponding subgraph and checks whether any such component either contains the root node itself
₆₀₉ or has at least one incoming edge from within the subgraph but from outside the component. If
₆₁₀ so, the (potential) incumbent is feasible, hence an actual incumbent solution. Otherwise the vi-
₆₁₁ olated constraint is added to the model in while the (potential) incumbent is declared infeasible.
₆₁₂ The general implementation strategy employed is based on the one given by *Backes et al.* (*2012*)
₆₁₃ where cycles are detected in order to avoid unconnected subgraphs.

Algorithm 3: Lazy constraint subroutine for DeRegNet. In case a potential incumbent is found all strongly connected components are checked to assess feasibility. In case any strongly connected component does not contain the root node and has no incoming edges from another component, a (lazy) constraint enforcing the requirement is added. **SCC**(G) denotes the set of all strongly connected components of a graph G.

Data: DeRegNet instance and $x, y : V \to \{0, 1\}$
Result: *True* if x and y do not violate any lazy constraints, *false* otherwise
$V^* = \{v \in V : x_v = 1\}$ (nodes implied by x)
$G^* = (V^*, E^*)$ the subgraph induced by V^*
$\mathcal{C} = $ **SCC**(G^*), $\mathcal{C} \in \mathcal{P}(V^*)$ (Find strongly connected components)
for C *in* $\mathcal{C}$ *with* $|C| > 1$ **do**
    if $e_C^T(x - y) - e_{\delta^-(C)}^T x > |C| - 1$ **then**
        return *false*
return *true*

₆₁₄ **Further technical aspects of solving DeRegNet models**

₆₁₅ **Primal heuristics for the DeRegNet model**

₆₁₆ Every feasible solution of a mixed-integer program provides a lower bound on the optimal solu-
₆₁₇ tion value (for maximization problems). The feasible solution which currently gives the best lower
₆₁₈ bound on the optimal value during a branch-and-bound procedure is called the *incumbent (solu-*
₆₁₉ *tion)*. Branch-and-bound (and hence branch-and-cut) for mixed-integer programs relies on pruning
₆₂₀ parts of the search tree of LP relaxation subproblems by assessing whether the optimal solution

---

[3]I.e. adding any node not in the subgraph would render the resulting subgraph to be not strongly connected anymore.

value of a given LP relaxation is less than the best lower bound provided by the incumbent. Primal heuristics *Berthold* (*2006*) aim at finding and/or improving feasible solutions during a branch-and-bound procedure. While some generic methods for primal heuristics exist *Glover and M.* (*1997a*), *Glover and M.* (*1997b*), *Fischetti et al.* (*2005*), *Balas et al.* (*2004*), *Balas and Martin* (*1980*), they tend to be highly problem-specific *Berthold* (*2006*). Of special interest in that context are primal heuristics for the MWCSP *Rehfeldt and Koch* (*2019*), *Álvarez-Miranda et al.* (*2013a*), *Álvarez-Miranda et* (*2013b*). In the following I describe start and improvement heuristics useful during the solution of DeRegNet instances.

Start heuristics

A priori there is no feasible solution known at the beginning of a branch-and-bound procedure for solving a mixed-integer program. Heuristics which try to find initial feasible solutions are called *start heuristics*. I outline two start heuristics which can be employed at the beginning of the branch-and-bound search for the solution of the DeRegNet model.

Greedy start heuristic. The first start heuristic is called *greedy start heuristic* and basically starts with the highest scoring node and greedily adds neighbors of already added nodes until the average score of the thus defined subgraph starts decreasing. If the currently selected subgraph is feasible upon termination, one has found a feasible solution. The formal procedure is outlined in algorithm 4. There are a number subtleties attached to this start heuristic. First and foremost the procedure only assures the reachability constraints regarding the root node. Most other constraints may or may not be satisfied at any given time during the procedure, mostly: subgraph size constraints and constraints ensuring the necessity of leaf nodes to be from the subset of terminal nodes. While the subgraph size constraint is relatively easily manageable by stopping the procedure when the maximal subgraph size is reached and by restarting in case the minimal subgraph size can not be achieved in the first place. In the latter case, one can restart the procedure from the best scoring node not already selected during earlier attempts of the greedy start heuristic. The issue of the terminal node constraints is not easily handled and hence the greedy start heuristic is in effect only usable in case $T = \varnothing$. Also instances with **Inc** $\neq \varnothing$ cannot be handled by this heuristic.

Receptor-terminal shortest path heuristic. The second start heuristic is more suitable in situations where there is a non-empty terminal set T. In short, it finds the shortest path between a pair of receptor and terminal nodes with high node scores. The **SHORTEST_PATH** subroutine referenced in algorithm 5 can be an implementation of any of the canonical algorithms to find single-source shortest paths with unit edge weights in directed graphs in polynomial time *Dijkstra* (*1959*), *Johnson* (*1977*), *Ahuja et al.* (*1990*). Subject to **Ex** = **Inc** = $\varnothing$ all connectivity constraints will be satisfied by construction. If the subgraph size constraints are met is up to chance however. Again, running multiple times with the, say K, highest scoring pairs of receptors and terminals, can help in this situation. Note, that the restriction of **Ex** = **Inc** = $\varnothing$ could be lifted by formulating the corresponding shortest path problem by canonical means in terms of integer programming problems *Taccari* (*2016*). This possibility is not explored further however since solving integer programs to get initial feasible solutions to integer program may be a slippery slope. In particular in the case of DeRegNet, where the main problem to solve is formulated in terms of decision variables corresponding to nodes while shortest path integer programming formulations usually introduce decision variables corresponding to the edges of the graph.

Improvement heuristics

In case a feasible solution is found at a particular branch-and-bound node (which may be a new incumbent or not), heuristics which try to improve that given feasible solution are called *improvement heuristics*. Here I describe a simple greedy improvement heuristic which can be applied to any feasible solution, either found during the branch-and-cut procedure or otherwise. It works

---

Algorithm 4: Greedy start heuristic for the DeRegNet model

Data: DeRegNet instance with $T = \mathbf{Inc} = \varnothing$

Result: Feasible solution of DeRegNet instance **or** *null*

if $R \neq \varnothing$ **then**
    $V_I = R$

else
    $V_I = V \setminus \mathbf{Ex}$

$v^* = \mathrm{argmax}_{v \in V_I}\, s_v$ (Select feasible root with highest score)

$V^* = \{v^*\}$ (Selected DeRegNet solution)

$N = \delta^+(v^*) \setminus \mathbf{Ex}$ (Candidate nodes to be potentially added next)

$A^* = s_{v^*}$ (Current average score of selected subgraph)

CONTINUE = **true**

while *CONTINUE* **and** $|V^*| < k_{max}$ **do**
    $v^* = \mathrm{argmax}_{v \in N}\, s_v$ (Highest scoring node in candidate set)
    if $s_{v^*} \geq A^*$ **then**
        $A^* = \frac{|V^*|A^* + s_{v^*}}{|V^*| + 1}$ (Update average score of selected subgraph)
        $V^* = V^* \cup \{v^*\}$ (Update current subgraphs)
        $N^* = (\delta^+(v^*) \setminus V^*) \setminus \mathbf{Ex}$ (New candidate nodes)
        $N = (N \setminus \{v^*\}) \cup N^*$ (Update candidate nodes)
    else
        CONTINUE = **false**

if V^* *feasible* **then**
    return V^* (Return feasible solution of DeRegNet instance)

else
    return *null* (Return nothing to indicate failure to find feasible solution)

Algorithm 5: Receptor-terminal shortest path start heuristic for the DeRegNet model

---

Data: DeRegNet instance with $\mathbf{Ex} = \mathbf{Inc} = \varnothing$

Result: Feasible solution of DeRegNet instance **or** *null*

if $R \neq \varnothing$ **then**
    $V_R = R$

else
    $V_R = V$

$r^* = \mathrm{argmax}_{v \in V_R}\, s_v$ (Receptor with highest score)

if $T \neq \varnothing$ **then**
    $V_T = T$

else
    $V_T = V$

$t^* = \mathrm{argmax}_{v \in V_T}\, s_v$ (Terminal with highest score)

$V^* = \{r^*, t^*\}$ (Selected DeRegNet solution)

$P = \mathbf{SHORTEST\_PATH}(G, r^*, t^*)$ (Find shortest path between receptor and terminal)

$V^* = V^* \cup P$ (Add nodes from shortest path)

if $k_{min} \leq |V^*| \leq k_{max}$ **then**
    return V^* (Return solution if it satisfies the subgraph size constraints)

else
    return *null* (Return nothing if size constraints are not met)

---

analogously to the greedy start heuristic (algorithm 4), the only difference being that one is already starting with a feasible solution. In particular, the heuristic can be applied to solutions constructed by the receptor-terminal shortest path start heuristic (algorithm 5) described in the previous section. Trying to improve the greedy start heuristic (algorithm 4) with the improvement strategy outlined below is futile however since by construction the former already added all potential subgraph nodes in a greedy fashion. During a branch-and-cut run any new feasible solution can potentially be improved by the heuristic. In case of an incumbent one can hope for an even better incumbent, in case of a feasible solution one can hope to improve it up to a point where it actually becomes a new incumbent. The description of the heuristic is provided as algorithm 6.

Algorithm 6: Greedy improvement heuristic for the DeRegNet model

Data: Feasible solution of a DeRegNet instance
Result: Another feasible solution of (the same) DeRegNet instance
$V^* = \{v \in V : x_v = 1\}$ (Selected DeRegNet solution)
$N = (\bigcup_{v \in V^*} \delta^+(v)) \setminus (V^* \cup \mathbf{Ex})$ (Candidate nodes to be added next)
$A^* = \frac{s^T x}{e^T x}$ (Current average score of selected subgraph)
CONTINUE = **true**
while *CONTINUE* **and** $|V^*| < k_{max}$ **do**
    $v^* = \mathrm{argmax}_{v \in N}\, s_v$ (Highest scoring node in candidate set)
    if $s_{v^*} \geq A^*$ **then**
        $A^* = \frac{|V^*|A^* + s_{v^*}}{|V^*| + 1}$ (Update average score of selected subgraph)
        $V^* = V^* \cup \{v^*\}$ (Update current subgraphs)
        $N^* = (\delta^+(v^*) \setminus V^*) \setminus \mathbf{Ex}$ (New candidate nodes)
        $N = (N \setminus \{v^*\}) \cup N^*$ (Update candidate nodes)
    else
        CONTINUE = **false**
return V^*

Approximate solutions via branch-and-bound gap cut

One can use a mixed-integer programming solver generically to obtain suboptimal solutions to a given (maximization) MILP with optimal objective value z^*. During the branch-and-cut search one obtains lower bounds on the optimal value by feasible solutions to the problem and an upper bound by the solution value of the initial LP relaxation of the problem. Let $\underline{z} \leq z^*$ be the best available lower bound and let $\bar{z} \geq z^*$ be the upper bound obtained by the relaxed problem. The *relative gap* λ_{rel} during a branch-and-cut search is defined as $\lambda_{rel} := \frac{z^*}{\bar{z}}$.[4] With the upper bound $\hat{\lambda}_{rel} := \frac{\bar{z}}{\underline{z}} \geq \frac{z^*}{\bar{z}}$ on the gap it follows that $z^* \leq \hat{\lambda}_{rel}\underline{z}$ and hence $\alpha z^* \leq \underline{z}$ with $\alpha := \hat{\lambda}_{rel}^{-1}$. Stopping the branch-and-cut procedure at the given gap upper bound value hence provides an approximate solution of a posteriori approximation guarantee of $\hat{\lambda}_{rel}^{-1}$. I refer to the strategy of stopping the branch-and-cut search once the gap upper bound is below a certain threshold as *gap cut* or *gap (cut) thresholding*. Employing the gap cut strategy can be useful in situations where the MILP solver can find reasonably good solutions in reasonable time but would take significantly more time to find the optimal solution. The option of to carry out gap cut thresholding is incorporated in the implementation of DeRegNet for this very reason.

Caching transformed model formulations

For DeRegNet's use cases it is quite common to optimize DeRegNet instances which just differ in terms of their node scores, i.e. share the same underlying graph. For example, finding dereg-

---

[4]While the *(absolute) gap* λ_{abs} is defined as $\lambda_{abs} := \bar{z} - z^*$.

ulated subgraphs for individual cases in a TCGA cohort with a fixed regulatory network derived
from KEGG will require to solve a model with the same structural properties but with differing
score data[5] In particular, in such a situation the reformulation and linearization procedure of the
generalized Charnes-Cooper transform only has to be carried out once and can be reused across
cases since it does not depend structurally on the objective data vector s. While solution time of a
DeRegNet instance with the generalized Charnes-Cooper transform tends to be dominated by the
time to solve the resulting integer linear program, reuse of the transformed model structure can
nonetheless result in significant computational savings.

Further details on benchmarking DeRegNet

706 Algorithm 7 details the benchmark instance simulation algorithm. Algorithm 8 details the mode of
707 application of *Backes et al.* (*2012*) in the context of the benchmarks described in the main part of
708 the paper. Figure 1 depicts the subgraphs simulation procedure conceptually.

Algorithm 7: Simulating DeRegNet instances with known "optimal" subgraph. Here, **Ber**(p_f) denotes a Bernoulli random variable with parameter p_f.

Data: A directed graph $G = (V, E)$, sets $T \subset V$, $p_f \in [0, \frac{1}{2})$
Result: A DeRegNet instance, a simulated *true* optimal subgraph $V' \subset V$ and the simulated root node r

Choose $r \in R$ with probability $\frac{1}{|R|}$ (Choose root node)
$V' := \{r\}$ (Initialize subgraph with root)
Choose $k \in [k_{min}, k_{max}]$ with probability $\frac{1}{k_{max}-k_{min}+1}$ (Choose subgraph size)
while $|V'| \neq k$ **do**
  if $(\bigcup_{v' \in V'} \delta^+(v)) \setminus V' = \varnothing$ **then**
    RESTART Algorithm 7
  Choose $v \in (\bigcup_{v' \in V'} \delta^+(v)) \setminus V'$ with probability $|(\bigcup_{v' \in V'} \delta^+(v)) \setminus V')|^{-1}$
  $V' = V' \cup \{v\}$ **for** $v \in V'$ **do**
    Sample $s(v) \sim$ **Ber**$(1 - p_f)$
  for $v \in V \setminus V'$ **do**
    Sample $s(v) \sim$ **Ber**(p_f)
return $(G, R, \varnothing, \varnothing, \varnothing, s), V', r$

DeRegNet subgraph derived features for predicting survival

Predicting phenotypes based on clinical and molecular data is one of the big challenges on the
road to personalized medicine. A frequently readily available phenotype for cancer patients is sur-
vival time (i.e. the time from disease onset/diagnosis to (possibly disease induced) death). Improv-
ing upon clinical predictors with molecular data often still poses significant challenges (*Yuan et al.,*
2014). Here, we provide an example of the suitability of deregulated subgraph-derived features
for predicting survival in the TCGA-LIHC dataset. In particular, we demonstrate that predictions
based on subgraphs is at least as good GSEA-based predictions obtained in a comparable manner.
Furthermore, subgraph derived features can improve upon predictions based on clinical features
alone.

[5]For example a omics-readout for every case in the cohort.

Algorithm 8: Applying *Backes et al.* (*2012*) **for benchmarking DeRegNet.** Here, **APPLY_BACKES**(k) refers to applying the algorithm of *Backes et al.* (*2012*) with fixed subgraph size k, understood to return a set of nodes corresponding to the induced subgraph found by the run.

Data: A DeRegNet instance with underlying graph $G = (V, E)$

Result: A set $V' \subset V$ (inducing a subgraph)

$V' := \varnothing$ (Initialize the final subgraph)

for $k = k_{min}$; $k \leq k_{max}$; k++ **do**
| $V' = V' \cup$ **APPLY_BACKES**(k)

end

return V'

      (a)   **(b)**   **(c)**

Figure 1. Simulating DeRegNet instances. See algorithm 7 for a formal outline of the simulation procedure. On a high level it proceeds like this: **(a)** Choose root node randomly. **(b)** Simulate a feasible subgraph by randomly choosing nodes maintaining the topological constraints of the model. Set the deregulation score of nodes in the subgraph to one. **(c)** Introduce noise by flipping node deregulation scores randomly.

Data preparation and feature engineering

Survival times were binarized by labeling all patients with survival less than three years (1095 days) as bad outlook patients ($y = 0$) and all patients with last follow-up time larger than three years as good outlook patients ($y = 1$). The resulting dataset consisted of 198 patients from the TCGA-LIHC cohort[6]. For every case the following features are derived:

- **clinical**: Features from clinical data comprising *age*, *gender*, *body mass index (BMI)*, *tumor stage* (!) and *tumor morphology*. Age (in years) and BMI were scaled via z-scores. Tumor stage and morphology where one-hot encoded.

- **gsea**: Features derived from (single sample) Gene Set Enrichment Analysis (GSEA) (*Subramanian et al., 2005*). Two lists of significantly enriched pathways w.r.t good outcomes vs. bad outcomes and vice versa were computed by (standard) GSEA. From every list I retained pathways with adjusted p-value less than 0.1, which resulted in a total of 14 KEGG pathways. After performing ssGSEA, every sample received the corresponding personalized ssGSEA enrichment scores for these pathways as a 14-dimensional feature vector. The above steps were carried out with *gseapy* [7]. For more information on single-sample GSEA, see *Foroutan et al.* (*2018*). The obtained features were scaled via z-scores.

- **subgraph_overlap**: Features based on up- and downregulated subgraphs for the good and bad outcome subgroups. Subgraphs were computed based on the global deregulation score

---

[6]Some cases dropped out due to incomplete or missing survival data.
[7]http://gseapy.rtfd.io/

Figure 2. Subgraph features vs. GSEA features across models. (A) Support Vector Classifier (SVC) with linear kernel (B) Support Vector Classifier (SVC) with radial basis function (RBF) kernel (C) Artificial Neural Network (ANN) (D) Random forest (E) Logistic Regression.

Figure 3. Subgraph features vs. clinical features across models. Clinical + subgraph features together outperform either in isolation. Subgraph features perform comparably to clinical features. (A) Support Vector Classifier (SVC) with linear kernel (B) Support Vector Classifier (SVC) with radial basis function (RBF) kernel (C) Artificial Neural Network (ANN) (D) Random forest (E) Logistic Regression.

for the good outcome and bad outcome patients respectively (on the respective training sets only, see below). Every sample is then associated with the regulation-aware node overlap[8] between its personalized de-, up- and downregulated subgraphs and up- and downregulated global subgraphs for the good and bad outcome subgroups respectively. This amounts to a 12-dimensional feature vector. Again, z-scores were applied.

- **ndcg**: Subgraph features derived from network-defined cancer genes. After identifying network-defined cancer genes (see previous subsection) for de-, up- and downregulated subgraphs one obtains a binary indicator for every case representing whether it contains any given such gene or not, leading to 15-dimensional feature vectors corresponding to 15 network-defined cancer genes.
- **subgraph**: *subgraph_overlap* and *ndcg* combined (concatenated).

Under a *feature combination* it is understood the combination of two or more of the just defined features. In the following, I use a plus sign to indicate feature combinations, e.g. *subgraph = subgraph_overlap + ndcg*. As another example, *subgraph + clinical* then denotes *subgraph* features combined with *clinical* features.

Survival prediction with clinical, pathway and subgraph features

The experiments described in the following were carried out with scikit-learn [9]. Every feature/feature combination was tested by training a Support Vector Machine, a simple artificial neural network, a random forest and a logistic regression. For every algorithm we performed an algorithm-specific grid search for model selection. The grid search was equivalent for different feature combinations in order to be able to assess the comparative suitability of the features. Final models were evaluated with 6-fold cross validation estimating mean Receiver Operating Characteristic (ROC) curves and Area under the curve (AUC) scores.

Features *gsea* and *subgraph_overlap* are roughly equivalent with respect to the underlying logic, with subgraphs or pathways as contextual data inputs respectively. Hence, comparing these two features may give an indication of the suitability of subgraph vs. pathway methods for feature engineering for survival prediction. Figure 2 shows that the *subgraph_overlap* features hold promise w.r.t *gsea* features.

Furthermore, it has been shown that improving upon clinical features with molecular features for survival prediction is not an easy task (*Yuan et al., 2014*). The experiments conducted here show that for the given setting, prediction models combining clinical and subgraph features (based on molecular interactions and data) provide performance gains compared to a purely clinical model. Also, the subgraph features achieve parity with classifiers based on clinical data alone. Figure 3 represents these findings.

---

[8]Given two (induced) subgraphs $V', V'' \subset V$ and node scores $s', s'' : V \rightarrow \{-1, 0, 1\}$ the deregulation-aware node overlap is defined as $\sum_{v \in V} (\mathbb{I}(v \in V') \ s'_v) \cdot (\mathbb{I}(v \in V'') \ s''_v)$.

[9]https://scikit-learn.org

References

Adams WP, Forrester RJ. A simple recipe for concise mixed 0-1 linearizations. Operations Research Letters. 2005; 33:55–61.

Adams WP, Forrester RJ, Glover F. Comparison and enhancement strategies for linearizing mixed 0-1 quadratic programs. Discrete Optimization. 2004; 1:99–120.

Ahuja RK, Mehlhorn K, Orlin J, Tarjan RE. Faster algorithms for the shortest path problem. Journal of the ACM. 1990; 37(2).

Althaus E, Blumenstock M. Algorithms for the Maximum Weight Connected Subgraph and Prize-collecting Steiner Tree Problems. 11th DIMACS Implementation Challenge in Collaboration with ICERM. 2011; URL http://dimacs11.zib.de/workshop/AlthausBlumenstock.pdf.

Álvarez-Miranda E, Ljubić I, Mutzel P. The Maximum Weight Connected Subgraph Problem. In: Jünger M, Reinelt G, editors. The Maximum Weight Connected Subgraph Problem Berlin, Heidelberg: Springer Berlin Heidelberg; 2013. p. 245–270. URL https://doi.org/10.1007/978-3-642-38189-8_11, doi: 10.1007/978-3-642-38189-8_11.

Álvarez-Miranda E, Ljubić I, Mutzel P. The Rooted Maximum Node-Weight Connected Subgraph Problem. In: Gomes C, Sellmann M, editors. *Integration of AI and OR Techniques in Constraint Programming for Combinatorial Optimization Problems* Berlin, Heidelberg: Springer Berlin Heidelberg; 2013. p. 300–315.

Anzai Y. On integer fractional programming. J Operations Research Soc of Japan. 1974 March; 17(1):49–66.

Backes C, Rurainski A, Klau GW, Muller O, Stockel D, Gerasch A, Kuntzer J, Maisel D, Ludwig N, Hein M, Keller A, Burtscher H, Kaufmann M, Meese E, Lenhof HP. An integer linear programming approach for finding deregulated subgraphs in regulatory networks. Nucleic Acids Res. 2012 Mar; 40(6):e43.

Balas E, Martin CH. Pivot-and-Complement: A Heuristic for 0-1 Programming. Management science. 1980; 26:86–96.

Balas E, Schmieta S, Wallace C. Pivot and shift - amixed integerprogramming heuristic. Discrete Optimization. 2004; 1:3–12.

Berthold T. Primal Heuristics for Mixed Integer Programs. PhD thesis, Technische Universität Berlin; 2006.

Buchanan A, Wang Y, Butenko S. Algorithms for node-weighted Steiner tree and maximum-weight connected subgraph. Networks. 2017 04; 72. doi: 10.1002/net.21825.

Charnes A, Cooper WW. Programming with linear fractional functionals. Naval Research Logistics Quaterly. 1962; 9:181–186.

Conforti M, Cornuéjols G, Zanbelli G. Integer Programming. Springer; 2014.

Dijkstra EW. A note on two problems in connexion with graphs. Numerische Mathematik. 1959; 1:269–271.

Dijkstra EW. A discipline of Programming. Prentice-Hall; 1972.

Dinkelbach W. Die Maximierung eines Quotienten zweier linearer Funktionen unter linearen Nebenbedingungen. Z Wahrscheinlichkeitstheorie. 1962; 1:141–145.

Dinkelbach W. On nonlinear fractional programming. Managment Science. 1967 March; 13(7):492–498.

Dittrich MT, Klau GW, Rosenwald A, Dandekar T, Muller T. Identifying functional modules in protein-protein interaction networks: an integrated exact approach. Bioinformatics. 2008 Jul; 24(13):i223–231.

El-Kebir M, Klau G. Solving the Maximum-Weight Connected Subgraph Problem to Optimality. 11th DIMACS implementation challenge. 2014 09; .

Fischetti M, Glover F, A L. The feasibility pump. Mathematical Programming. 2005; 104:91–104.

Foroutan M, Bhuva DD, Lyu R, Horan K, Cursons J, Davis MJ. Single sample scoring of molecular phenotypes. BMC Bioinformatics. 2018 Nov; 19(1):404.

Glover F. Improved linear integer programming formulations of nonlinear integer problems. Managment Science. 1975 December; 22(4):455–460.

Glover F, M L. General Purpose Heuristics forInteger Pro-gramming - Part I. Journal of Heuristics. 1997;
2:343–358.

Glover F, M L. General Purpose Heuristics forInteger Pro-gramming - Part II. Journal of Heuristics. 1997;
3:161–179.

Johnson DB. Efficient Algorithms for Shortest Paths in Sparse Networks. Journal of the ACM. 1977; 24(1).

Loboda AA, Artyomov MN, Sergushichev AA. Solving Generalized Maximum-Weight Connected Subgraph Prob-
lem for Network Enrichment Analysis. In: Frith M, Storm Pedersen CN, editors. *Algorithms in Bioinformatics*
Cham: Springer International Publishing; 2016. p. 210–221.

Álvarez Miranda E, Sinnl M. A Relax-and-Cut framework for large-scale maximum
weight connected subgraph problems. Computers & Operations Research. 2017;
87:63 – 82. URL http://www.sciencedirect.com/science/article/pii/S0305054817301272,
doi: https://doi.org/10.1016/j.cor.2017.05.015.

Rehfeldt D, Koch T. Combining NP-Hard Reduction Techniques and Strong Heuristics in an Exact Algorithm for
the Maximum-Weight Connected Subgraph Problem. SIAM Journal on Optimization. 2019; 29(1):369–398.
URL https://doi.org/10.1137/17M1145963, doi: 10.1137/17M1145963.

Rehfeldt D, Koch T, Maher SJ. Reduction techniques for the prize collecting Steiner tree problem
and the maximum-weight connected subgraph problem. Networks. 2019; 73(2):206–233. URL
https://onlinelibrary.wiley.com/doi/abs/10.1002/net.21857, doi: 10.1002/net.21857.

Sharir M. A strong-connectivity algorithm and its applications to data flow analysis. Computers and Mathe-
matics with applications. 1981; 7(1):67–72.

Subramanian A, Tamayo P, Mootha VK, Mukherjee S, Ebert BL, Gillette MA, Paulovich A, Pomeroy SL, Golub
TR, Lander ES, Mesirov JP. Gene set enrichment analysis: a knowledge-based approach for interpreting
genome-wide expression profiles. Proc Natl Acad Sci USA. 2005 Oct; 102(43):15545–15550.

Taccari L. Integer Programming Formulations for the Elementary Shortest Path Problem. European Journal of
Operational Research. 2016; 252(1).

Tarjan R. Depth-first search and linear graph algorithms. SIAM Journal on Computing. 1972; 1(2):146–160.

You F, Castro PM, Grossmann IE. Dinkelbach's algorithm as an efficient method to solve a class of MINLP
models for large-scale cyclic scheduling problems. Computers & Chemical Engineering. 2009; 33:1879–1889.

Yuan Y, Van Allen EM, Omberg L, Wagle N, Amin-Mansour A, Sokolov A, Byers LA, Xu Y, Hess KR, Diao L, Han
L, Huang X, Lawrence MS, Weinstein JN, Stuart JM, Mills GB, Garraway LA, Margolin AA, Getz G, Liang H.
Assessing the clinical utility of cancer genomic and proteomic data across tumor types. Nat Biotechnol.
2014 Jul; 32(7):644–652.

Yue D, Guillén-Gosálbez G, You F. Global optimization of large-scale mixed-integer linear fractional program-
ming problems: a reformulation-linearization method and process scheduling applications. AIChE Journal.
2013; 59(11):4255–4272.