Probabilistically Weighted Multilayer Networks disclose the link between default mode network instability and psychosis-like experiences in healthy adults

Simone Di Plinio[1,*], Sjoerd J H Ebisch[1,2]

1 Department of Neuroscience, Imaging, and Clinical Sciences, G D'Annunzio University of Chieti-Pescara, Chieti, Italy

2 Institute for Advanced Biomedical Technologies (ITAB), G D'Annunzio University of Chieti-Pescara, Chieti, Italy

* Corresponding author: simone.diplinio@unich.it

Short title: Probabilistically Weighted Multilayer Networks

Keywords: Multilayer networks; Dynamic connectivity; Default mode network; Psychotic experiences; Functional networks; Flexibility

ABSTRACT

The brain is a complex system in which the functional interactions among its subunits
vary over time. The trajectories of this dynamic variation contribute to inter-individual
behavioral differences and psychopathologic phenotypes. Despite many methodological
advancements, the study of dynamic brain networks still relies on biased assumptions in
the temporal domain. The current paper has two goals. First, we present a novel method
to study multilayer networks: by modelling intra-nodal connections in a probabilistic,
biologically driven way, we introduce a temporal resolution of the multilayer network
based on signal similarity across time series. This new method is tested on synthetic
networks by varying the number of modules and the sources of noise in the simulation.
Secondly, we implement these probabilistically weighted (PW) multilayer networks to
study the association between network dynamics and subclinical, psychosis-relevant
personality traits in healthy adults. We show that the PW method for multilayer networks
outperforms the standard procedure in modular detection and is less affected by
increasing noise levels. Additionally, the PW method highlighted associations between
the temporal instability of default mode network connections and psychosis-like
experiences in healthy adults. PW multilayer networks allow an unbiased study of
dynamic brain functioning and its behavioral correlates.

1 INTRODUCTION

Multilayer networks rely on the assumption that different network layers can be combined in
supramodal entities since elements (nodes) occupying the same place in each network can be
considered as naturally linked across time or experimental conditions of a task (Hutchinson et
al., 2013; Boccaletti et al., 2014; Kivela et al., 2014; De Domenico et al., 2017; Thompson et al.,
2018). Defining a supramodal structure allows us to investigate dynamic changes in a network
indexed by dynamic nodal measures such as promiscuity, flexibility, integration, and
recruitment (Bassett et al., 2011; Papadopoulos et al., 2016; Telesford et al., 2017; Pedersen et
al., 2018). Multilayer networks have increasingly been employed in both basic and clinical
neuroscience and highlighted interesting patterns of dynamic network rearrangement
underlying normal behavior (Braun et al., 2015; Telesford et al., 2016) as well as clinical
conditions such as depression (Zheng et al., 2018) and schizophrenia (Gifford et al., 2020).

However, actual models of multilayer brain networks lack an objective methodological
procedure to weight network parameters in a biologically-sound fashion. The topological and
modular properties of multilayer brain networks rely on two key parameters, namely *gamma*
(γ) and *omega* (ω). The former, γ, indicates the weight of the null models when computing
modularity (Lancichinetti and Fortunato, 2009, 2012; Betzel and Bassett, 2017). Thus,
increasing the value of γ results in a more fragmented network structure with many small
modules (Bassett et al., 2013; Gu et al., 2015; Nicolini and Bifone, 2016; Betzel et al., 2017). The
latter, ω, represents the empirical strength of connections that a node has toward itself in
consecutive (if multilayer networks are built across time) or alternative (if multilayer networks
are built across experimental conditions) time intervals (De Domenico et al., 2013; Muldoon et
al., 2016). Thus, ω essentially controls the intra-layer versus cross-layer modular architecture.
The current standard is to set ω to fixed numbers and to investigate the effect of varying these
"fixed-ω" on the modular architecture. However, as already noted by many scientists, such an
assumption may introduce strong biases in the analysis since it implies arbitrariness regarding
the values of the detection of the modular architecture. For example, by setting ω=1, dynamic
(temporal) oscillations of nodal activity over time may be non-efficiently integrated into the
cross-layer modular detection (Chai et al., 2016; Betzel and Bassett, 2017).

Probabilistically Weighted Multilayer Networks disclose the link between default mode network instability and psychosis-like experiences in healthy adults

Many studies that investigated dynamic evolutions of brain activity and functional

connectivity highlighted classes of brain regions with peculiar functional properties in the time

domain (Van de Ville et al., 2010; De Pasquale et al., 2016; Breakspear, 2017). For example,

regions in the inferior parietal lobule, medial premotor cortex, and posterior cingulate cortex

have been labelled as functional hubs (De Pasquale et al., 2018) since they dynamically link

regions in their modules (cingulo-opercular network, sensorimotor network, and default mode

network, respectively) with other brain modules (O'Neil et al., 2015; Preti et al., 2016). The

efficient integration of information across networks is crucial for controlling explicit, externally

directed actions (Spadone et al., 2019; Wens et al., 2019) and for implicit, self-related

information processing (Di Plinio et al., 2020a). Aberrant connectional profiles, especially in

regions related to the default mode network, seem to underlie many psychopathological

conditions (Brovd et al., 2009; Hua et al., 2019), and these characteristics may depend on

dysfunctional dynamic processes (Braun et al., 2015, 2016; Du et al., 2018). Thus, implementing

a degree of control over the temporal domain is necessary to increase the ability to detect true

transient module configurations during conscious experiences, which are naturally occurring

both during task execution and during task-free states (Liu et al., 2020).

Here, we introduce an original parametrization for detecting dynamic modular architectures

intending to improve the biological appropriateness of community detection in multilayer

networks. As described above, the current estimation of the modularity relies on a structural (γ)

and a pseudo-structural (ω) parameter. Instead, the parametrization proposed here accounts

for uncertainty in the temporal domain and replaces ω. We introduce beta (β), a parameter that

regulates the probability distributions of the strength of edges connecting nodes across multiple

layers of a multilayer network (intra-nodal, cross-layer connections). We also implement a

biologically driven way to assign strengths of intra-nodal (temporal) connections from these

probability distributions by employing spectral coherence (Bowyer, 2016; Mohanty et al., 2020)

to choose the appropriate configuration of probabilistic intra-nodal weights. In other words, our

method probabilistically regulates intra-nodal weights across layers based on the biological and

temporal properties of the node's signal.

Our approach allows different strengths of cross-layer connections to improve the

appropriateness of multilayer modular detection. The procedure mirrors the current

methodology for selecting structural resolutions through the parameter γ and aims to

investigate modular architectures of the brain by using multiple temporal resolutions and

multiple structural resolutions, to implement an unbiased methodology. The probabilistically

weighted (PW) multilayer community detection proposed in this paper is expected to increase

the accuracy toward the detection of physiologically plausible, dynamic modular structures by

eliminating the biases constrained by a fixed and "guessed" value of ω. The modulation of

temporal resolution in PW networks allows for uncertainties over temporal multilayer network

features in the same way as γ enables the control over spatial network features.

We test this new approach both on simulated data and on real resting-state fMRI acquisitions

of 39 healthy participants. The new method's performance was tested together with standard

(fixed-ω) methods. To compare the performances of the methods, we investigated synthetic,

weighted networks obtained by varying the number of modules, the weight of structured and

unstructured noise in the time series, the structural resolution parameter (γ), and the values

regulating the standard parameter (ω) and our proposed parameter for probabilistic weights

based on spectral coherence (β). Moreover, the association between multilayer network

properties and individual differences in behavior was tested, focusing on the neural correlates

of psychosis-relevant personality traits, which have been hypothesized to be related to self-

dysfunction and network segregation (Ebisch and Aleman, 2016; Humpston and Broome, 2020;

Di Plinio et al., 2020a). Subclinical, psychosis-relevant personality traits were evaluated, which

can be detected on a continuum in the general population below any threshold of a clinical

diagnosis (McGrath et al., 2015). Such traits can be considered critical from a clinical point of

view (Orr et al., 2014), as well as from a phenomenological perspective to provide insight into

the relationship between neurobiology and the sense of self (Humpston, 2014).

METHODS

Synthetic Networks

Three modules in a network of 100 nodes were simulated as follows in 10 consecutive time

windows. Each node was initially assigned to a specific module across all the time windows

(30% of the nodes were assigned to module A, 50% to module B, 20% to module C). Then, 40%

of the nodes were chosen at random to be fast/slow/random oscillators (15%, 15%, 10%

respectively) to simulate diverse physiological properties of brain hubs. Random, slow, and fast

oscillators switched between their module and another random module every 1, 3, and 5 layers,

respectively.

Once defined the modular time-varying structure, time series were created as follows. First,

for each time window, a prototype matrix of synthetic functional connections was simulated as

a 100x100 symmetric Lehmer matrix. Since in the Lehmer matrix the values of the functional

connections increase with proximity to the diagonal and with progressive node numbers, such

matrix allows the generation of modules with different degrees of intrinsic connections, thus,

avoiding biases related to connection strengths. A time series was simulated for each node from

the starting correlation structure, and, for each module, the nodes' time series were selectively

time-shifted to create modular structures.

Within each node, the time series of 100 voxels were simulated to simulate realistic voxels

within a parcel. Initially, for each node, the node's time series was assigned to each voxel within

the node. Then, two sources of noise were simulated to represent physiologically unrelated

noise (unstructured noise) and the "interference" of nearby biological units in the node signal

(structured noise). Unstructured noise was simulated - for each voxel - as a random time series

that was added to the voxel signal in a weighted manner. Structured noise was simulated by

choosing a random [2 to 5] number of attractors on the external surface of the node. A random

time series was simulated for each attractor. Then, each voxel in the node suffered each

attractor's interference depending on its closeness to the attractor. Finally, to mirror common

procedures in neuroimaging, each node time series was obtained by averaging the time series of

the voxels within it. Different weights were considered for the two noises (low, medium, high)

to investigate the impact of the signal-to-noise ratio to the module detection across the two

methods.

Once noisy time series were synthesized, the generalized Louvain function was used to

detect multilayer modules following the multilayer network quality function (Mucha et al.,

2010) implemented with codes from Jeub and colleagues ("A generalized Louvain method for

community detection implemented in MATLAB"

http://netwiki.amath.unc.edu/GenLouvain/GenLouvain). The generalized Louvain function was

implemented both in the "standard" form (fixed-ω) as well as using the probabilistically

weighted method (PW). The whole procedure was repeated for 100 independent cycles so that,

in each cycle, a new modular structure was randomly created. The three levels of

structured/unstructured noises were introduced for each cycle. As suggested by many relevant

studies, it is not only important to test inter-layer connectional strengths, but it is also crucial to

vary the structural resolution parameter of brain networks (Chai et al., 2016; Betzel et al., 2019;

Puxeddu et al., 2019; Yang et al., 2021; Tardiff et al., 2021). Accordingly, we investigated a range

of structural resolutions, modular structures, and inter-layer functional weights in the

estimation of multilayer networks. More specifically, the structural resolution parameter (γ)

was varied between 0.5 and 2.0 with steps of 0.1. Different values for the parameter establishing

fixed cross-layer connections (fixed-ω) were considered ([0.10 0.25 0.50 0.75 1.00]). Moreover,

the PW method was also implemented without assumptions about the average or median

connectional strengths (see below). Analyses were performed using MatLab version 2019a (The

MathWorks). The weighted approach is described in the next paragraphs. The procedure for

obtaining synthetic networks is schematised in Figure 1. To assess the independence of the

methods' performances from the number of modules in the network, the whole procedure was

repeated using five modules of equal size (20% of the nodes assigned to each module).

Probabilistically Weighted (PW) Multilayer networks

To implement control over nodal temporal features of the network, we introduced a matrix

of probability weights W. Values in W were controlled by the temporal resolution parameter β

and by the temporal features of the nodes. As probability weights, values in W basically

represent the probability of nodes to be self-connected among different layers of the network.

Thus, with temporal multilayer networks, W is a N by T-1 matrix in which T is the number of

time windows and N is the number of nodes in the network. By contrast, if working with task

multilayer networks, the matrix W would be a N by K matrix in which K represents within-node

cross-condition interconnections and is calculated as K = C! In which C is the number of

experimental conditions (e.g., in a classic two by two factorial psychology paradigm, there

would be four conditions, so that K = 4! = 24).

To control the strength of cross-layer connections and to mirror the weight of the null model

for the structural resolution parameter, values of W were defined using a probabilistic

approach. Initially, a set of Levy alpha-stable distributions, Ω, was generated. Stable

distributions rely on four parameters, allowing complete control over the shape and the scale of

the distribution. The rationale behind using stable distributions is to have reasonable values of

(positive) cross-layer functional connections between 0.0 and 1.0 which symmetrically vary

with a center in 0.5, reflecting the situation in intra-layer functional connections usually derived

using Pearson correlations. The beta parameter is particularly convenient since it allows to

regulate left-skewness and right-skewness of the distributions symmetrically. To reflect

correlation (functional connectivity), the values of W (probabilities) were sampled within the

interval [0 1]. Thus, the location parameter of the distributions, μ, was set to 0.50 and the scale

parameter, σ, was set to 0.75. The first shape parameter, α, was empirically set to 0.40, while the

second shape parameter, β, was modulated within the range [-1 1] to obtain a series of

distributions in which the head and the tails are arranged progressively in the interval [0 1]. In

other words, a set of probability distributions (Ω) was created in which the ratio of low vs high

probabilities was controlled through the parameter β: with higher, positive values of β, the head

and the fat tail of a specific distribution in Ω are located toward lower probability values (lower

probabilities of cross-layer connections); instead, with lower, negative values of β, the head and

the fat tail of a specific distribution in Ω are located toward higher probability values (higher

probabilities of cross-layer connections). Values used for β in this study were: [-.75 -.25 0 .25

.75].

The distributions in Ω were used to fill values in W based on the coherence between time

intervals. More specifically, we used spectral coherence, also known as magnitude-squared

coherence (Bowyer, 2016; Mohanty et al., 2020), across consecutive time windows of each node.

Coherence estimates the consistency of amplitude and phase between signals across

frequencies, and thus it is biologically appropriate grasping coherent signal fluctuations of a

node in two adjacent time windows (or in two experimental conditions) *i* and *j*. In other words,

coherence is appropriate to assess if two temporal fragments related to the same node have low

or high probability to be connected – i.e., to be "self-similar" – between the layers *i* and *j*. We

would like to note that many other alternatives to the coherence, like the simple correlation,

would be unsuitable except in the case in which temporal segments are aligned, or time-locked

to specific stimuli. This only occurs with task experiments using block-designs, with blocks of

even length. Instead, coherence works in the frequency domain and not in the time domain, and

thus is valid in any experimental design. To have an approach which does not theoretically

depend on the way data was acquired is a major advantage and is guaranteed only by using the

coherence. Using this procedure, the temporal resolution, β (the β shape parameter of the stable

distributions), regulated the probabilities of connections among adjacent time windows in a

way driven by the similarity of the node's signals in the two consecutive time intervals. The

procedure for estimating probabilistically weighted multilayer modules is illustrated in Figure

2.

Statistical Analyses of Simulated Data

The performance of the two methods was assessed by calculating the degree of similarity

between the true simulated modular structure and the estimated modular structure through

two commonly used indexes for calculating correlations across modular structures, namely the

adjusted mutual information index (AMI) and the Rand coefficient. These indices are commonly

employed in research and indicate the performance of a modular detection (i.e., clustering)

procedure when the ground truth is known (Vinh et al., 2010).

Application on resting-state data

The procedure described above for detecting PW multilayer networks, together with the

standard ω=1 procedure was implemented also on resting-state data from a sample of 39

healthy participants (19 females and 20 males, aged 23 ± 2; 35 right-handed and 4 left-handed)

without a history of psychiatric or neurological disease and contraindications for MRI scanning

participated in the experiment. The experiment was approved by the local ethics committee

(Comitato Etico per la Ricerca Biomedica delle province di Chieti e Pescara) and by the

Department of Neuroscience, Imaging and Clinical Sciences (DNISC) of the G. d'Annunzio

University of Chieti-Pescara. All participants had a normal or corrected-to-normal vision and

provided written informed consent before taking part in the study in accordance with the

Declaration of Helsinki (2013).

Resting-state Data acquisition

Each participant performed two consecutive task-free fMRI runs, each consisting of 376

volumes. The participants were instructed to watch a white fixation cross on a black screen

without performing a cognitive task. Each run lasted approximately 7.5 minutes. Functional

images were acquired using a Philips Achieva 3T scanner installed at the Institute for Advanced

Biomedical Technologies (Gabriele d'Annunzio University, Chieti-Pescara, Italy). Whole-brain

functional images were acquired with a gradient echo-planar sequence using the following

parameters: repetition time (TR) = 1.2 s, echo time (TE) = 30 ms, field of view = 240x240x142.5

mm, flip angle = 65°, in-plane voxel size = 2.5 mm^2, slice thickness = 2.5 mm. A high-resolution

T1-weighted whole-brain image was also acquired after functional sessions using the following

parameters: TR = 8 ms, TE = 3.7, FoV = 256x256x180 mm, flip angle = 8°, in-plane voxel size = 1

mm^2, slice thickness = 1 mm.

Resting-state Data analysis

Functional connectivity was calculated as the correlation among average parcels timeseries

for a total of 418 nodes using cortical and subcortical atlases from Joliot and colleagues (Joliot et

al., 2015) plus the cerebellar atlas from Diedrichsen and colleagues (Diedrichsen et al., 2009).

These atlases were chosen because of the integrative method used to define both cortical and

subcortical parcels without lateralization biases. The functional connectivity values, that is, the

edges of the connectomes, were obtained using the z Fisher transform of the Pearson

correlation among pre-processed time series and were used to create individual (subject-

specific) weighted graphs. The modular architecture was visualized using BrainNet Viewer

(www.nitrc.org/projects/bnv/). We used both the PW method and the standard "fixed-ω"

implemented to detect time-varying modular structures across 10 consecutive, non-overlapping

time windows of equal length. For consistency, the procedure implemented for the analysis of

multilayer networks in real data was the same as described above for the simulations.

We tested if brain-behavioral resting-state associations were differentially detected by the

standard approach with fixed-ω and by the PW method. Thus, nodal metrics of flexibility,

integration, promiscuity, and recruitment (Bassett et al., 2011; Papadopoulos et al., 2016;

Telesford et al., 2017; Pedersen et al., 2018; Sizemore and Bassett, 2018) were estimated for

each subject using both the fixed-ω and the PW methods. The *flexibility* of each node

corresponds to the number of times that it changes module allegiance, normalized by the total

possible number of changes. The *integration* coefficient of a node is the average probability over

time that it is in the same community as regions from other systems. The *promiscuity* of a node

indicates the fraction of all the communities in the network in which the node participates at

least once. Finally, the *recruitment* coefficient corresponds to the average probability that a

node is in the same network community as other regions from its own system.

The behavioral variables were represented by five latent, orthogonal psychosis-relevant

factors that have also been used in previous works to study the sense of self and the sense of

agency (Di Plinio et al., 2019, 2020a, 2020b). We investigated the relation between dynamic

multilayer metrics and psychosis-related personality traits with a focus on factors related to

psychotic disorders (Asai et al., 2011; Gallagher et al., 2016). These five factors were reliably

(Tucker congruence coefficient = 0.95) derived from a factor analysis with orthogonal

(orthomax) rotation on a series questionnaires that were administered to a larger sample

(N=101) including the present fMRI sample (see Di Plinio et al., 2019, 2020a, 2020b for the

complete factor analysis procedure) The questionnaires measured basic as well as psychosis-

relevant personality traits: the Big-Five Questionnaire (BFQ short version, Soto and John, 2017),

the tolerance of uncertainty scale (IUS-12, Carleton et al., 2007), the Schizotypal Personality

Questionnaire (SPQ, Raine et al., 1991), the Community Assessment of Psychic Experience

(CAPE, Konings et al., 2006), and the State-Trait Anxiety Inventory (STAI2, Spielberger et al.,

1983). The five factors showed the highest loadings in the following subscales: factor 1: STAI2,

IUS-inhibitory, CAPE-depression, BFI-neuroticism (negative affect); factor 2: SPQ-cognitive

perceptual, CAPE-positive, CAPE-negative (psychosis-like experiences); factor 3: IUS-

prospective, BFI-extraversion, BFI-agreeableness, BFI-openness (sociality); factor 4: SPQ-

interpersonal, SPQ-disorganizational (schizotypal); factor 5: BFI-conscientiousness.

Statistical Analyses of Real Data

Brain-behavioral relationships were investigated using whole brain, univariate mixed-effects

models in which the five psychometric factor scores were used as continuous predictors for

each multilayer metric of interest; random intercepts and slopes were added at the individual

node level to allow for ROI-specific weighting of brain-behavior correlations; random intercepts

were added at the subject level. To properly assess meaningful brain-behavior correlations, we

implemented a cross-γ comprehensive regression model by using γ as a further random

grouping factor. For this analysis, γ was varied in the interval [0.6 1.5] with steps of 0.1. A

separate model was built for each method (fixed-ω, PW) and for each parameter value used for

detecting multilayer networks and related theoretical measures. Major nodal contributions in

the brain-behavior associations were detected using best linear unbiased predictors (BLUPs) to

generate nodal conditional expectation (ICE) plots and to highlight nodes with the highest

contribution.

RESULTS

Simulations

The PW method outperformed the fixed-ω method by far as demonstrated by differences in the indices used to measure the correspondence between true modular structures and reconstructed modules (i.e., adjusted mutual information and Rand coefficient). The PW method outperformed the standard method with every noise combination and independently of the structural resolution parameter γ.

Regarding the three-modules structure, as shown in Figure 3a, the effect of the term *method* in the models was significant across structured and unstructured noise. The effect also tended to be stronger (larger effect size) for increasing levels of noise showing that the PW method is less affected by noise in the data. Furthermore, as shown in Figure 3b, the standard method does not efficiently detect oscillator regions with high fixed-ω values (e.g., ω=1.0); on the other hand, it fails to detect a module's stability with low fixed-ω values (e.g., ω=0.1).

The same results were obtained with the five-modules structure. Also in this case, the performance of the PW method was better than the performance of the standard fixed-ω method (Figure 4a). Moreover, also in this case the PW method was more resistant to increasing levels of noise. Similar to results for the three-modules structure, the standard method did not efficiently detect oscillator regions with high fixed-ω values and failed to detect module's stability with low fixed-ω values (Figure 4b).

A comprehensive list of cross-γ results is provided in Table I, which reports significance levels and effect sizes (estimates) for the factor *method* across the various simulations in the study. Results for the Rand coefficient are shown in supplementary Figure S1 and in Table S1.

As expected, results from our simulations indicated that the PW multilayer networks outperformed by far the standard fixed-ω method in detecting true synthetic multilayer networks. The performance achieved with PW multilayer networks on synthetic data was better across structural resolutions and with every teste combination of structured and unstructured noise. Moreover, this better performance using the PW method was permanent using both the three-module and the five-module multilayer structures.

Real Data

Two significant associations were detected through the analysis of multilayer measures and

latent behavioral dimensions. The first one was a positive association between nodal flexibility

and factor 2 (F2, psychosis-like experiences). This association was detected by using the

standard fixed-ω approach as well as by using PW multilayer modelling. However, the results

were not significant for the fixed ω approach with ω=1 (Figure 5a). The analysis of random

effects and of individual conditional expectation (ICE) plots showed a consistent heterogeneity

of results across nodes (Figure 5b). Nodes with the most prominent effects were located in

medial prefrontal, posterior cingulate, and anterior temporal cortices usually ascribed to the

default mode network (Figure 5c).

The second significant effect concerned a negative association between nodal recruitment

and factor 2. The effect was detected with both the standard fixed-ω method and the PW

multilayer networks (Figure 5d). Also in this case, there was a high degree of heterogeneity of

effect sizes across brain regions (Figure 5e) and nodes primarily involved were located in

anterior prefrontal, posterior cingulate, and anterior temporal regions of the default mode

network (Figure 5f).

No significant results were observed regarding promiscuity or integrity.

DISCUSSION

The primary aim of this study was to test the performance of the probabilistically weighted

(PW) method for detecting cross-layer communities. We implemented this method both in

synthetic, perturbated time series of a network and in real data from resting-state fMRI. When

applied to synthetic data, the PW method outperformed the standard method and was less

affected by increasing noise levels in the time series. The better performance of the PW method

was confirmed using the adjusted mutual information index and the Rand coefficient. Moreover,

a better performance was found for the PW method using modular structures with an

increasing number of modules. Importantly, standard fixed-ω approaches did not efficiently

detect oscillator regions with high fixed-ω values (e.g., ω=1.0) and failed to detect modular

stability with low fixed-ω values (e.g., ω=0.1).

The improvement in accuracy brought by our PW method was consistent across different

structural resolution (γ) values. These results are the direct consequence of a reduced bias of

selection with respect to the strength of cross-layer intra-nodal connections in the PW method.

When applied to real data, the PW method was able to identify significant associations of two

dynamic metrics, namely flexibility and recruitment, with behavioral measures. We postulate

that probabilistically weighted multilayer networks are desirable for implementation in future

studies and should replace the standard, biased fixed-ω method.

To note, the method presented in this paper is intrinsically developed, and thus more

suitable, for weighted networks. However, it can also be applied to binarized graphs since the

intra-nodal weights can be directly transformed in a stochastic binary connection value. Of

course, binarizing cross-layer connections makes sense in a framework in which also intra-layer

functional connectivity is binarized. However, the focus of the present study is not on binarized

versus weighted procedures for network analysis.

The results on real resting-state fMRI data also deserve further discussion. Flexibility

indicates how frequently a node changes module allegiance over time. Instead, recruitment

indicates the probability of a node to belong to the same community as other nodes from its

own system. Thus, our results indicate that a decreased stability of nodes within the DMN

correspond to higher levels of psychosis-like experiences (F2) in healthy adults. These findings

are in line with the role of the fragmentation of the DMN in the predisposition toward

psychopathology involving psychosis and dysfunctional behavior (Braun et al., 2016; Hu et al.,

2017; Hua et al., 2019; Fan et al., 2019). Moreover, higher flexibility and less stable modular

organization have already been shown in patients with schizophrenia (Braun et al., 2015;

Gifford et al., 2020), whereas higher switching has been associated with impaired sleep and

decreased behavioral performances (Thompson et al., 2018; Pedersen et al., 2018). In this

framework, our findings also fit with DMN-specific network aberrancies observed in patients

with psychotic disorders (Ebisch and Aleman, 2016; Du et al., 2018; Di Plinio et al., 2020a;

Humpston and Broome, 2020), which also have genetic underpinnings (Scariati et al., 2014). We

contribute to this framework by showing for the first time an association between nodal

instability within the DMN (especially in medial prefrontal and in posterior cingulate cortices)

and psychosis-like experiences in a sample of healthy individuals. We remark that these findings

were possible due to the implementation of the PW method here presented. Considering that an

aberrant degree of psychosis-like experiences may imply difficulties in social interactions (De

Bézenac et al., 2015) and eventually impaired social functioning (Nelson et al., 2012), future

studies are needed to assess how the decreased stability of self-networks (DMN) may

predispose toward clinical self-disturbances in healthy populations (Nelson et al., 2012; Orr et

al., 2014; Humpston et al., 2014; McGrath et al., 2015).

When constructing and analyzing brain activity and functional connectivity, ground truths

are rare and unstable. However, advances in the understanding of dynamic brain networks

point toward the existence of multi-scale entities in the brain architecture (Hutchinson et al.,

2013; Boccaletti et al., 2014; Kivela et al., 2014; Braun et al., 2015; Telesford et al., 2016; De

Domenico et al., 2017; Betzel and Bassett, 2017; Zheng et al., 2018; Thompson et al., 2018;

Betzel et al., 2019; Gifford et al., 2020; Yang et al., 2021; Tardiff et al., 2021). These advances

followed recent developments in network science (Newman, 2003; Rubinov and Sporns, 2010;

Bassett and Sporns, 2017), and generally indicate the necessity to implement unbiased methods

for detecting communities (Newman and Girvan, 2004; Porter et al., 2009; Fortunato, 2010;

Lancichinetti et al., 2011; Fenn et al., 2012; Sporns and Betzel, 2016; Fortunato and Hric, 2016),

possibly controlling for multiple stochasticity in the community organization, like in multi-

resolution approaches (Rubinov et al., 2015; Chai et al., 2016; Puxeddu et al., 2019; Di Plinio et

al., 2020a; Malagruski et al., 2020). In fact, the choice of the resolution parameter γ is important

since it regulates the number and size of communities in a network (Lancichinetti and

Fortunato, 2009, 2012; Betzel and Bassett, 2017). However, in multilayer networks, the weight

of intra-nodal (cross-layer) links become crucial if we are interested in temporal features of the

network such as flexibility, recruitment, or promiscuity (Bassett et al., 2011; Papadopouolos et

al., 2016; Telesford et al., 2017; Pedersen et al., 2018). The implementation of PW multilayer

networks allows an unbiased approach to the study of brain networks through multiple

temporal resolutions and without a-priori guessing the strength of cross-layer connections.

Concluding, in the present study we introduce a probabilistic, biologically driven approach

for the unbiased selection of cross-layer weights in multilayer networks. Crucially, our study

does not only propose a way of optimizing cross-layer functional connections for accurate

modular detection, but also renovate the theoretical conception of multilayer brain networks,

favouring the shift toward a probabilistic and biologically-sound translation of timelines to

modules. Probabilistic multilayer networks allow the proper study of multiple temporal

resolutions, represented by multiple shape (β) values in the distribution of intra-node

connection weights. The PW method performs optimally despite modulations of β (probabilistic

weights), indicating that it can model a plurality of multilayer networks without suffering from

the biases previously described from fixed-ω approaches. Furthermore, it investigates multiple

temporal resolutions in multilayer networks that are biologically grounded since they are

assigned based on the coherence across time windows, paralleling the actual unbiased approach

commonly employed for spatial resolution (γ). However, we suggest to rely on the study of

several values of probabilistic connections including many β values in the analysis (or

equivalent modelling of probabilistic cross-layer weights). The ground truth in the brain

functioning is complex and cannot be achieved by searching for a single optimized value since

the brain probably functions at many levels of structural resolutions simultaneously. Thus, we

suggest relying on the analysis of multiple γ and β parameters to favour unbiased research. In

fact, as we shown in the present study, the use β modulations indeed combines well with the use

of multiple γ. The higher performance achieved by the PW method, together with the significant

associations with psychotic-like experiences detected, is a step forward towards an unbiased

approach in the study of dynamic brain functioning as well as its behavioral and cognitive

correlates.

FIGURES

Figure 1. Synthetic multilayer networks. (a) The matrix of synthetic node communities

was generated for ten consecutive timepoints. To note, the communities were different at each

cycle. (b) A Lehmer matrix was created. Values inside the matrix range from 0 to 1 to simulate

functional connectivity among brain regions. A time series was generated for each of the voxels

within each of the 100 nodes. Each voxel was affected by unstructured and structured noise. (c)

While the unstructured noise was a random time series generated independently for each voxel,

the structured noise was specific for each node. The subfigure depicts an example of "noisy

attractors" which differentially influenced node's voxels depending on the distance. (d) For each

module, nodes' time series were selectively time-shifted to create modular structures. After the

procedure, at each cycle, a series of 100 timeseries arranged with the desired modular structure

and with controlled signal-to-noise ratio was produced. These time series were used as input

for the calculation of functional connectivity matrices. The figure illustrates the three-modules

structure. The same procedure was used for the five-modules structure.

Probabilistically Weighted Multilayer Networks disclose the link between default mode network instability and psychosis-like experiences in healthy adults

Figure 2. Toy example with 4 nodes and 3 layers (a), illustrating the procedure for

estimating probabilistically weighted cross-layer links. Temporal (biological) features (e.g.,

frequencies amplitudes) are extracted for each node, in each layer (b). The similarity of

temporal features is calculated for each adjacent layer (c) using coherence, producing a N x L-1

matrix, where N is the number of nodes and L is the number of layers (HH=very high similarity;

LL= very low similarity). Concurrently, a vector of N x L-1 probability weights, W, is obtained

from a sample distribution for each value of β considered in the probabilistic analysis (d). For

example, with β = 0.75, most links will have a value between 0.1 and 0.2 (e), and high

similarities will be associated with higher values. Then, weights are assigned according to both

the values in W and the signal similarity over time (coherence), so that cross-layer links

connecting nodes with high self-similarity over time are higher (f). Weights can be eventually

used as probabilities for the linkage to occur in binary networks (g).

Figure 3. Results from simulated data with a three-modules structure. (a) The PW method (red) outperformed the standard fixed-ω method (blue) as shown by box plot reporting increased adjusted mutual information (AMI). The effect size (ES) for the term *method* in the mixed-effects model indicates, for each combination of noise levels, a performance increase of the PW method in contrast to the fixed-ω method. Significance levels are indicated by the asterisks (***: p<.001, **: p<.01, *: p<.05). (b) Differential community detection for medium noise levels. It is possible to appreciate that the standard method does not efficiently detect oscillator regions with high fixed-ω values (e.g., ω=1.0); on the other hand, it fails to detect module's stability with low fixed-ω values (e.g., ω=0.1). To note, results reported here are for γ=1.0. For a comprehensive list of cross-γ effects, see Table I.

Figure 4. Results from simulated data with a five-modules structure. (a) The PW method (red) outperformed the standard fixed-ω method (blue) as shown by box plots reporting increased adjusted mutual information (AMI). The effect size (ES) for the term *method* in the mixed-effects model indicates, for each combination of noise levels, a performance increase of the PW method in contrast to the fixed-ω method. Significance levels are indicated by the asterisks (***: p<.001, **: p<.01, *: p<.05). (b) Differential community detection for medium noise levels. As in figure 3b, it is possible to appreciate that the standard method does not efficiently detect oscillator regions with high fixed-ω values (e.g., ω=1.0); on the other hand, it fails to detect module's stability with low fixed-ω values (e.g., ω=0.1). To note, results reported here are for γ=1.0. For a comprehensive list of cross-γ effects, see Table I.

Figure 5. Significant associations between the behavioral factor F2 (psychosis-like experiences) and flexibility (left column) or recruitment (right column). (a) Flexibility was associated with F2 across all the investigated values of β (lower row, red). The association was significant also with four out of five of the fixed-ω values (higher row, blue) but not with ω=1.0. Significance is indicated by the asterisks (***: p<.001, **: p<.01, *: p<.05), whereas the bars without asterisks represent results not significant after correction for multiple comparisons. (b) Individual conditional expectation (ICE) plot representing predictions for flexibility in each brain node with varying levels of psychosis-like experiences (F2). (c) Brain topography of the association between flexibility and F2. Only nodes for which the slope was significantly higher than the average are represented. Colour intensity indicates the strength of the effect size. The subfigures (d-e-f) illustrate the corresponding results for the metric recruitment. For simplicity,

1   only results according to γ=1.0 and to the PW multilayer networks obtained with β=.25 are

2   shown in subfigures b, c, e, and f.

Probabilistically Weighted Multilayer Networks disclose the link between default mode network instability and psychosis-like experiences in healthy adults

	Unstructured Noise	3-modules network			5-modules network		
		Structured Noise			Structured Noise		
		low	med	high	low	med	High
γ = 0.6	low	.10	**.19***	**.20***	.03	**.09***	**.11***
	med	.11	**.20***	**.20***	.04	**.09***	**.11***
	high	.12	**.20***	**.20***	.06	**.10***	**.11***
γ = 0.8	low	.14	**.18***	**.24***	.05	.10	**.12***
	med	.14	**.18***	**.23***	.06	.10	**.12***
	high	.15	**.18***	**.24***	.06	**.10***	**.13***
γ = 1.0	low	**.18***	**.20***	**.21***	.06	**.09***	**.13***
	med	**.18***	**.18***	**.21***	.06	**.09***	**.14***
	high	**.19***	**.20***	**.21***	.06	**.09***	**.14***
γ = 1.2	low	**.15***	**.17***	**.15***	**.07***	**.11***	**.13***
	med	**.16***	**.18***	**.16***	**.07***	**.11***	**.13***
	high	**.15***	**.17***	**.16***	**.08***	**.12***	**.13***
γ = 1.4	low	**.14***	**.12***	**.09***	**.08***	**.12***	**.13***
	med	**.14***	**.12***	**.09***	**.09***	**.12***	**.13***
	high	**.13***	**.11***	**.09***	**.09***	**.12***	**.13***
γ = 1.6	low	**.08***	**.05***	**.04***	**.09***	**.11***	**.12***
	med	**.08***	**.05***	**.04***	**.10***	**.12***	**.12***
	high	**.08***	**.05***	**.04***	**.10***	**.12***	**.12***
γ = 1.8	low	**.04***	**.03***	**.03***	**.09***	**.10***	**.09***
	med	**.04***	**.03***	**.03***	**.10***	**.10***	**.09***
	high	**.03***	**.03***	**.02***	**.10***	**.10***	**.08***
γ = 2.0	low	**.02***	**.02***	**.02***	**.09***	**.07***	**.06***
	med	**.02***	**.02***	**.02***	**.08***	**.07***	**.07***
	high	**.02***	**.02***	**.02***	**.08***	**.07***	**.06***

Table I. Effects for the fixed term *method* in the linear mixed-effects models investigating the

global performance of the PW method versus standard fixed-ω values as indexed by the

adjusted mutual information index (AMI). The structural resolution parameter was tuned in the

range [0.6 2.0]. Since the table reports the effect size (coefficient) for the term *method* (contrast:

PW – fixed-ω), it can be interpreted as the increase in the AMI index when using PW methods

instead of fixed-ω methods. It is important to note that the greatest increase in performance

coincides with the structural resolution in which the two methods are globally more efficient,

showing a considerably better performance in the PW method. It can also be noticed how the

effect is greater with higher levels of noise, reflecting the resistance of the PW method (but not

of the fixed-ω method) against high noise in the data. Significant effects are highlighted in bold

(*: $p < .05$, **: $p < .01$, ***: $p < .001$).

1 REFERENCES

Asai, T., Sugimori, E., Bando, N., Tanno, Y. The hierarchic structure in schizotypy and the five-
factor model of personality. Psychiatry Research, 185(1-2), 78-83 (2011)

Bassett, D.S., Wymbs, N.F., Porter, M.A., Mucha, P.J., Carlson, J.M., Grafton, S.T. Dynamic
reconfiguration of human brain networks during learning. PNAS, 108(18), 7641-7646
(2011).

Bassett, D.S., Porter, M.A., Wymbs, N.F., Grafton, S.T., Carlson, J.M., Mucha, P.J. Robust detection of
dynamic community structure in networks. Chaos: An Interdisciplinary Journal of Nonlinear
Sciences, 23(1), 013142 (2013).

Bassett, D.S., Sporns, O. Network Neuroscience. Nature Neuroscience, 20, 353-364 (2017).

Betzel, R.F., Bassett, D.S. Multi-scale brain networks. NeuroImage, 160, 73-83 (2017).

Betzel, R.F., Medaglia, J.D., Papadopoulos, L., Baum, G., Gur, R., et al. The modular organization of
human anatomical networks: Accounting for the cost of wiring. Network Neuroscience, 1(1),
42-68 (2017).

Betzel, R. F., Bertolero, M. A., Gordon, E. M., Gratton, C., Dosenbach, N. U., & Bassett, D. S. The
community structure of functional brain networks exhibits scale-specific patterns of inter-
and intra-subject variability. Neuroimage, 202, 115990. (2019)

Boccaletti, S., Bianconi, G., Criado, R., et al. The structure and dynamics of multilayer networks.
Phys Rep, 544(1), 1-122 (2014).

Bowyer, S.M. Coherence as a measure of the brain networks: Past and present. Neuropsychiatric
Electrophysiology, 2(1) (2016).

Braun, U., Schafer, A., Walter, H., Erk, S., Romanczuk-Seiferth, N, et al. Dynamic reconfiguration of
frontal brain networks during executive cognition in humans. PNAS, 112(37), 11678-11683
(2015).

Braun, U., Schafer, A., Bassett, D.S., Rausch, F., Schweiger, J.J., et al. Dynamic brain network
reconfiguration as a potential schizophrenia genetic risk mechanism modulated by NMDA
receptor function. PNAS, 113(44), 12568-12573 (2016).

Breakspear, M. Dynamic models of large-scale brain activity. Nature Neuroscience, 20, 340-352
(2017).

Broyd, S.J., Demanuele, C., Debener, S., Helps, S.K, James, C.J., Sonuga-Barke, E.J.S. Default-mode
brain dysfunction in mental disorders: A systematic review. Neuroscience and Biobehavioral
Reviews, 33(3), 279-296 (2009).

Bullmore, E, Sporns, O. Complex brain networks: Graph theoretical analysis of structural and
functional systems. Nat Rev Neurosci, 10(3), 186-188 (2009).

Carleton, R.N., Norton, M.A., Asmundson, G.J.G. Fearing the unknown: A short version of the
intolerance of uncertainty scale. J Anxiety Disord, 21, 105-17 (2007).

Chai, L., Mattar, M.G., Blank, I.A., Fedorenko, E., Bassett, D.S. Functional network dynamics of the
language system. Cerebral Cortex, 26(11), 4148-4159 (2016).

De Bézenac, C.E., Sluming, V., O'Sullivan, N., Corcoran, R. Ambiguity between self and other:
Individual differences in action attribution. Consciousness and Cognition, 35, 1-15 (2015).

De Domenico, M., Solé-Ribalta, A., Cozzo, E., Kivela, M., Moreno, Y., et al. Mathematical
formulation of multilayer networks. Phys Rev X, 3(4), 041022 (2013).

De Domenico, M. Multilayer modelling and analysis of human brain networks. GigaScience, 6, 1-
8 (2017).

De Pasquale, F., Della Penna, S., Sporns, O., Romani, G.L, Corbetta, M. A dynamic core network
and global efficiency in the resting human brain. Cerebral Cortex, 26(10), 4015-4033 (2016).

De Pasquale, F, Corbetta, M, Betti, V, Della Penna, S. Cortical cores in network dynamics.
NeuroImage, 180, 370-382 (2018).

Probabilistically Weighted Multilayer Networks disclose the link between default mode network instability and psychosis-like experiences in healthy adults

Diedrichsen, J., Balster, J.H., Flavell, J., Ramnani, N. A probabilistic MR atlas of the human
cerebellum. NeuroImage, 46(1), 39-46 (2009).

Di Plinio, S., Arnò, S., Perrucci, M.G., Ebisch, S.J.H. Environmental control and psychosis-relevant
traits modulate the prospective sense of agency in non-clinical individuals. Consciousness
and Cognition, 73, 102776 (2019).

Di Plinio, S., Perrucci, M.G., Aleman, A., Ebisch, S.J.H. I am Me: Brain systems integrate and
segregate to establish a multidimensional sense of self. NeuroImage, 205, 116284 (2020a).

Di Plinio, S., Arnò, S., Perrucci, M.G., Ebisch, S.J.H. The evolving sense of agency: Context recency
and quality modulate the interaction between prospective and retrospective processes.
Consciousness and Cognition, 80, 102903 (2020b).

Du, Y., Fryer, S.L., Fu, Z., Lin, D., Sui, J., et al. Dynamic functional connectivity impairments in
early schizophrenia and clinical high-risk for psychosis. Brain Connectivity Dynamics, 180,
632–645 (2018).

Ebisch, S.J.H., Aleman, A. The fragmented self: imbalance between intrinsic and extrinsic self-
networks in psychotic disorders. The Lancet Psychiatry, 3(8), 784-790 (2016).

Fan, F., Tan, Y., Wang, Z., Yang, F., Fan, H., et al. Functional fractionation of default mode network
in first episode schizophrenia. Schizophrenia Research, 210, 115-121 (2019).

Fenn, D.J., Porter, M.A., McDonald, M., Williams, S., Johnson, N.F., Jones, N.S. Dynamical clustering
of exchange rates. Quant Financ, 12(10), 1493-1520 (2012).

Fortunato, S. Community detection in graphs. Phys Rep, 486(3), 75–174 (2010).

Fortunato, S., Hric, D. Community detection in networks: A user guide. Physics Reports, 659(11),
1-44 (2016).

Gallagher, S., Trigg, D. Agency and Anxiety: Delusions of control and loss of control in
Schizophrenia and Agoraphobia. Frontiers in Human Neuroscience, 10, 459 (2016).

Gifford, G., Crossley, N., Kempton, M.J., Morgan, S., Dazzan, P., Young, J., McGuire, P. Resting state
fMRI based multilayer network configuration in patients with schizophrenia. NeuroImage:
Clinical, 25, 102169 (2020).

Gu, S., Pasqualetti, F., Cieslak, M., Telesford, Q.K., Alfred, B.Y., et al. Controllability of structural
brain networks. Nature Communications, 6 (2015).

Hua, J.P.Y., Karcher, N.R., Merrill, A.M., O'Brien, K.J., Straub, K.T., Trull, T.J., Kenrs, J.G. Psychosis
risk is associated with decreased resting-state functional connectivity between the striatum
and the default mode network. Cognitive, Affective, & Behavioral Neuroscience, 19, 998-1011
(2019).

Hu, M.-L., Zong, X.-F., Mann, J.J., Zheng, J.-J., Liao, Y.-H., et al. A Review of the Functional and
Anatomical Default Mode Network in Schizophrenia. Neuroscience Bulletin, 33(1), 73-84
(2017).

Humpston, C.S. Perplexity and Meaning: Toward a Phenomenological "Core" of Psychotic
Experiences. Schizophrenia Bulletin, 40(2), 240-243 (2014).

Humpston, C.S., Broome, M.R. Thinking, believing, and hallucinating self in schizophrenia. The
Lancet Psychiatry, 7(7), 638-646 (2020).

Hutchinson, R.M., Womelsdorf, T., Allen, E.A., Bandettini, P.A., Calhoun, V.D., et al. Dynamic
functional connectivity: Promises, issues, and interpretations. NeuroImage, 80, 360-372
(2013).

Joliot, M., Jobard, G., Naveau, M., Delcroix, N., Petit, L.,et al. AICHA: An atlas of intrinsic
connectivity of homotopic areas. 254, 46-59 (2015).

Kivela, M., Arenas, A., Barthelemy, M. et al. Multilayer Networks. Journal of Complex Networks,
2(3), 203-271 (2014).

Probabilistically Weighted Multilayer Networks disclose the link between default mode network instability and psychosis-like experiences in healthy adults

Konings, M., et al. Validity and reliability of the CAPE: a self-report instrument for the measurement of psychotic experiences in the general population. Act Psychiat Scand, 114(1), 55-61 (2006).

Lancichinetti, A., Fortunato, S. Community detection algorithms: A comparative analysis. Phys Rev E (2009).

Lancichinetti, A., Radicchi, F., Ramasco, J.J., Fortunato, S. Finding statistically significant communities in networks. PLoS One, 6(4), e18961 (2011).

Lancichinetti, A., Fortunato, S. Consensus clustering in complex networks. Sci Rep (2012).

Liu, X., Wu, X., Zhong, M., Huang, H., Weng, Y., et al. Dynamic Properties of Human Default Mode Network in Eyes-Closed and Eyes-Open. Brain Topography, 33, 720-732 (2020).

Malagurski, B., Liem, F., Oschwald, J., Mérillat, S., Jancke, L. Longitudinal brain network reconfiguration in healthy aging. Human Brain Mapping, 41(17), 4829-4845 (2020).

McGrath, J.J., Saha, S., Al-Hamzawi, A., et al. Psychotic experiences in the general population: a cross-national analysis based on 31,261 respondents from 18 countries. JAMA Psychiatry, 72(7), 697-705 (2015).

Mohanty, R., Sethares, W.A., Nair, V.A., Prabhakaran, V. Rethinking measures of functional connectivity via feature extraction. Scientific Reports, 10(1298) (2020).

Mucha, P.J., Richardson, T., Macon, K., Mason, K., Porter, MA, Onnela, J.-P. Community structure in time-dependent, multiscale, and multiplex networks. Science, 328, 876-878 (2010).

Muldoon, S., Bassett, D.S. Network and multilayer network approaches to understanding human brain dynamics. Philosophy of Science, 83(5) (2016).

Nelson, B., Thompson, A., Yung, A.R. Basic self-disturbance predicts psychosis onset in the ultra high risk for psychosis "prodromal" population. Schizophrenia Bulletin, 38, 1277-1287 (2012).

Newman, M.E. The structure and function of complex networks. SIAM Rev, 45(2), 167-256 (2003).

Newman, M.E., Girvan, M. Finding and evaluating community structure in networks. Phys Rev E, 69(2), 026113 (2004).

Nicolini, C., Bifone, A. Modular structure of brain functional networks: breaking the resolution limit by surprise. Scientific reports 6 (2016).

O'Neil, G.C., Bauer, M., Woolrich, M.W., Morris, PG., Barnes, G.R., Brookes, M.J. Dynamic recruitment of resting state sub-networks. NeuroImage, 115, 85-95 (2015).

Orr, J.M., Turner, J.A., Mittal, V.A. Widespread brain dysconnectivity associated with psychotic-like experiences in the general population. NeuroImage: Clinical, 4, 343-351 (2014).

Papadopoulos, L., Puckett, J.G., Daniels, K.E., Bassett, D.S. Evolution of network architecture in a granular material under compression. Phys Rev E, 94, 032908 (2016).

Pedersen, M., Zalesky, A., Omidvarnia, A., Jackson, G.D. Multilayer network switching rate predicts brain performance. PNAS, 115(52), 13376-13381 (2018).

Porter, M.A., Onnela, J., Mucha, P.J. Communities in networks. Not Amer Math Soc, 56(9), 1082-1097 (2009).

Preti, M.G., Bolton, T.A., Van De Ville, D. The dynamic functional connectome: State-of-the-art and perspectives. NeuroImage, 160, 41-54 (2016).

Puxeddu M.G., Petti, M., Mattia, D., Astolfi, L. The Optimal Setting for Multilayer Modularity Optimization in Multilayer Brain Networks. 41st Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), pp. 624-627 (2019)

Raine, A. The SPQ: a scale for the assessment of schizotypal personality based on DSM-II-R criteria. Schizophrenia Bull, 17(4), 555-64 (1991).

Rubinov, M., Sporns, O. Complex network measures of brain connectivity: uses and
interpretations. NeuroImage, 52(3), 1050-1060 (2010).

Rubinov, M., Ypma, R.J., Watson, C., Bullmore, E.T. Wiring cost and topological participation of
the mouse brain connectome. PNAS, 112(32), 10032-10037 (2015).

Scariati, E., Schaer, M., Richiardi, J., Schneider, M., Debbané, M., Van De Ville, D., Eliez, S.
Identifying 22q11.2 Deletion Syndrome and Psychosis Using Resting-State Connectivity
Patterns. Brain Topography, 27, 808-821 (2014).

Sizemore, A.E., Bassett, D.S. Dynamic graph metrics: Tutorial, toolbox, and tale. NeuroImage,
180, 417-427 (2018)

Soto, C.J., John, O.P. Short and extra-short forms of the Big Five Inventory-2: The BFI-2-S and
BFI-2-XS. J Res Pers, 68, 69-81 (2017).

Spadone, S., Della Penna, S., Sestieri, C., Betti, V., Tosoni, A., et al. Dynamic reorganization of
human resting-state networks during visuospatial attention. PNAS, 112(26), 8112-8117
(2018).

Spielberger, C.D., et al. Manual for the State-Trait Anxiety Inventory. Consulting Psychologists
Press (1983).

Sporns, O., Betzel, R.F. Modular brain networks. Ann Rev Psychol, 67, 613-640 (2016).

Tardiff, N., Medaglia, J. D., Bassett, D. S., & Thompson-Schill, S. L. The modulation of brain
network integration and arousal during exploration. NeuroImage, 240, 118369. (2021)

Telesford, Q.K., Lynall, M.-E., Vettel, J.M., Miller, M.B., Grafton, S.T., Bassett, D.S. Detection of
functional brain network reconfiguration during task-driven cognitive states. NeuroImage,
142, 198-210 (2016).

Telesford, Q.K., Ashourvan, A., Wymbs, N.F., Grafton, S.T., Vettel, J.M., Bassett, D.S. Cohesive
network reconfiguration accompanies extended training. Human Brain Mapping, 38(9),
4744-4759 (2017).

Thompson, S.H., Falk, E.B., Vettel, J.M., Bassett, D.S. Network Approaches to Understand
Individual Differences in Brain Connectivity: Opportunities for Personality Neuroscience.
Personality Neuroscience, 1(e5), 1-12 (2018).

Van De Ville, D., Britz, J., Michel, C.M. EEG microstate sequences in healthy humans at rest reveal
scale-free dynamics. PNAS, 107, 181-79-18184 (2010).

Vinh, N.X., Epps, J., Bailey, J. Information Theoretic Measures for Clusterings Comparison:
Variants, Properties, Normalization and Correction for Chance. Journal of Machine Learning
Research, 11, 2837-2854 (2010).

Wens, V., Bourguignon, M., Vander Ghinst, M., Mary, A., Marty, B., et al. Synchrony, metastability,
dynamic integration, and competition in the spontaneous functional connectivity of the
human brain. NeuroImage, 199, 313-324 (2019).

Yang, Z., Telesford, Q. K., Franco, A. R., Lim, R., Gu, S., Xu, T., ... & Milham, M. P. Measurement
reliability for individual differences in multilayer network dynamics: Cautions and
considerations. NeuroImage, 225, 117489. (2021)

Zheng, H., Li, F., Bo, Q., Li, X., Yao, L., et al. The dynamic characteristics of the anterior cingulate
cortex in resting-state fMRI of patients with depression. J Affect Disord, 227, 391-397 (2018).