A practical guide for estimating animal density using camera

traps: Focus on the REST model

HONGO, Shun

The Center for African Area Studies, Kyoto University

hongo.shun.8s@kyoto-u.ac.jp

NAKASHIMA, Yoshihiro

College of Bioresource Sciences, Nihon University

yosshi1215jp@yahoo.co.jp

YAJIMA, Gota

College of Bioresource Sciences, Nihon University

wildlife.hunter0712@gmail.com

Short running title: Camera trap methods for density estimation

Person to whom correspondence:

Hongo, Shun

46, Yoshida Shimoadachi-cho, Sakyo-ku, Kyoto, 606 8501, Japan

Phone: +81 75 753 7359

Email: hongo.shun.8s@kyoto-u.ac.jp

Abstract

Estimating animal density and finding the factors that influence it are central in wildlife

conservation and management but challenging to achieve, particularly in forested areas.

Camera trapping is a pervasive method in forest mammal survey and a plausible

technique to overcome this challenge. This report provides a practical guide for

conducting a camera trap survey to estimate the density of forest mammals applying the

random encounter and staying time (REST) model. We firstly provide a brief

explanation about the structure and assumptions of the REST model. Next, we describe

essential points during different steps in planning a survey: determination of objectives,

design of camera placement, choice of camera models, camera setting, the layout of the

camera station, and list of covariates. We then develop detail-oriented instruction for

conducting a survey and analysing the obtained video data. We encourage camera trap

surveyors to provide the practised protocols of their surveys, which will be helpful to

other camera trappers.

Keywords

Camera placement design; camera station layout; forest mammals; survey plan; trail

camera; video analysis; wildlife monitoring

Introduction

How can we accurately estimate the population density of wild animals? How can we reliably assess the factors influencing their density? These two questions are of common importance to field ecologists, conservationists and wildlife managers working with animal taxa (Elliot & Gopalaswamy 2017; Burgar et al. 2018; Santini et al. 2018; Cavada et al. 2019). Forested areas, which host many biodiversity hotspots (Myers et al. 2000; Marchese 2015; Hu et al. 2021), are particularly challenging to effectively address the above issues due to poor accessibility and visibility compared to open landscapes such as woodlands and grasslands (Kamgaing et al. 2018).

Camera traps—motion-triggered automatic cameras with (often passive infrared) sensors (Apps & McNutt 2018b)—have been introduced into forest animal surveys as a powerful tool to solve this conundrum (O'Connell et al. 2011; Burton et al. 2015). Although the camera trap survey requires a relatively high initial investment, it has a major advantage in labour costs: No one has to work in the survey area except for the installation, regular operation checks and retrieval. And camera trapping is less invasive for both vegetation and animals than most conventional methods. For example, there's no need to cut many transects in the forest or observe animals directly, as is required in the line-transect distance sampling (Buckland et al. 2001; Buckland et al. 2015). Hence, camera trapping has become a standard method for forest mammal surveys (McCallum 2013).

With a sufficient number of camera traps, surveyors may already be sitting on a gold mine of "reliable density estimates"—but they still have to dig. In this case, they don't need a pickax or shovel but a dedicated statistical model and a survey plan tailored to the model. Many models are available for animal density estimation (Iijima

2020). Some are applicable for "marked", i.e., individually identifiable, populations;

others can be used for "unmarked" populations. And some can be implemented using

camera traps (Gilbert et al. 2021), others not. Among them, the random encounter and

staying time (REST) model (Nakashima et al. 2018) estimates the density of unmarked

population from camera trap data alone. We believe that, together with several

alternatives (Chandler & Royle 2013; Howe et al. 2017), the REST model is one of the

most promising methods for this purpose.

As with any models, the REST model has several assumptions to ensure

unbiased, accurate density estimation. Surveyors need to carefully plan the survey to

meet them. Surveyors can refer to previous studies applying the REST model (Garland

et al. 2020; Yokoyama et al. 2020), but research papers usually describe the survey

method details only briefly. This makes it difficult for them to prepare plans with

confidence. A more practical guide for the density estimation survey is necessary to

avoid falling into unexpected pitfalls. Here, we provide detailed instruction for

conducting density estimation surveys of forest animals using camera traps and the

REST models. We develop detail-oriented discussions of the complications that need to

be taken into account when actually conducting the survey. After briefly introducing the

theory, structure and assumptions of the REST model, we discuss various aspects to be

kept in mind when preparing for and conducting the survey and analysing the camera-

trap data.

REST model: a brief explanation

The REST model was devised following the ideas of the random encounter model

(REM) (Rowcliffe et al. 2008). It formulated the number of animal passes as a function

of the animal density, "detection zone" (the area that cameras can capture all animals

passing through), survey period and travel speed. The REM, however, requires

measuring the animal travel speed independently to camera trapping, which makes the

model difficult to implement in wildlife surveys. The REST model has overcome this

problem by focusing on "staying time"—the inverse of travel speed—in the detection

zone (Nakashima et al. 2018). To understand it, let's consider how we can express the

expected value of the total staying time of animals passing through a camera's detection

zone. For the sake of simplicity, we consider here a solitary mammal species, although

Nakashima et al. (2018) showed that the REST model could also be applied to pair-

living mammals.

There are two approaches (Fig. 1). The first one thinks that only one camera

trap is placed and operates in the "continuous shooting mode" (Fig. 1a). It takes a series

of pictures at very short intervals (say 0.1 s) for the entire survey period (from

installation to retrieval of this camera). If we knew the animal density (D), the expected

success rate of photographing the animal would be expressed as Ds, where s is the area

of the detection zone. If the survey period (H) is sufficiently long, then the expected

total staying time would be DsH.

The second approach assumes that many camera traps work in the "video

mode" to take videos throughout when an animal is in the detection zone (Fig. 1b).

From the videos, we can count each camera's number of times that animals passed

through the detection zone (Y). And we can measure the staying time of each pass (T).

We can, therefore, simply represent the total staying time in a camera as a product of

their expected values, $E(Y) \cdot E(T)$.

Total staying time per camera: $DsH = E(Y) \cdot E(T)$

Fig. 1. Pattern diagrams of two parallel cases—(a) continuous shooting mode and (b)

video mode—for estimating the total staying time of animals passed through a camera

trap's detection zone. In both cases, solitary animals passed twice through the detection

zone of s km² during a survey period (H) of 10 days (= 864,000 s). A red circle on the

right hind toe indicates the focal point for determining the entry of animals in the

detection zone and measure their staying time.

Having expressed the total staying time in two different ways, we now have the

following equation:

129                          $DsH = \text{E}(Y) \cdot \text{E}(T)$ (1)

130 Thus,

131                          $D = (\text{E}(Y)/H) \cdot (\text{E}(T)/s)$ (2)

Equation 2 formulates the animal density as a product of the expected detection rate and

the expected staying time in a detection zone. One can predetermine s and H but have to

estimate $\text{E}(Y)$ and $\text{E}(T)$ from the data. To do so, Nakashima et al. (2018) proposed a

negative-binomial distribution to model the number of passes; they used exponential,

gamma, log-normal and Weibull distributions for staying time. As in generalised linear

models (GLMs), we can estimate the distribution parameters using the maximum

likelihood estimators (for frequentists) or as the posterior probability distributions (for

Bayesians). Nakashima et al. (2018) also described how to deal with the right-censored

staying time, where leaves from the detection zone were not observed due to the

camera's time interval setting.

Incorporate habitat covariates

As we saw above, animal density can be expressed as a mixture of two GLMs. So it's

now possible to model differences in density due to various environmental and

anthropogenic effects. Nakashima et al. (2020) expanded the basic REST model to

incorporate the habitat covariates—such as altitude, slopeness, distance from human

settlements—into the model as the linear predictors of the expected staying time and the

density. When φ and D represent the expected staying time and density, respectively, we

can consider that they are specific to camera stations with the following form:

153
$$\log(\varphi_i) = \alpha_0 + \sum_{k=1}^{K} x_{ik}\alpha_k \qquad (3)$$

154
$$\log(D_i) = \beta_0 + \sum_{k=1}^{K} x_{ik}\beta_k \qquad (4)$$

156 where x_{ik} is the kth habitat covariates at camera station i. We can also include random

157 effects in the linear predictors to explain, for example, station-specific random

158 differences in staying time. The relationship between these parameters and the expected

159 number of detections at station i, θ_i, with the form below:

161
$$\log(\theta_i) = \log(D_i) - \log(\varphi_i) + \log(s) + \log(H_i) \qquad (5)$$

Nakashima et al. (2020) proposed that habitat covariates and random effects affect rate

parameter for exponential and gamma distributions, mean log parameter for log-normal

distribution, and scale parameter for Weibull distribution.

Constructing a model for each of the different hypotheses, analysts have many

models with different combinations of covariates. If they intend to compare the models

in terms of better prediction of animal density, analysts can use information criteria,

such as Akaike Information Criterion (AIC; Akaike 1973, 1974) or Watanabe–Akaike

Information Criterion (WAIC; Watanabe 2010). If you intend, by contrast, to examine

the presence of habitat effects, they may choose an appropriate statistical test.

Assumptions and limitations

Every model has its own assumptions and limitations, and the REST model is no

exception. The REST model has four major assumptions (Nakashima et al. 2018) (Table

1). Surveyors have to carefully plan the survey to meet them.

178 **Table 1** Assumptions of the random encounter and staying time (REST) model.

Assumption	Description	Insights
I. Closed population	The population density must not vary over the survey period.	The survey period should be sufficiently short that the density does not change significantly.
II. Random sampling	Camera traps must be placed randomly with respect to the animal's spatial distribution.	Surveyors must not arbitrarily select animal trails or mineral licks as camera stations.
III. Animal unresponsiveness	Cameras or camera stations must not change animal movement and behaviour.	Use of lure and baits must be avoided, and vegetation clearing around cameras must be minimised.
IV. Perfect detection	Camera traps must detect all animals that entered the detection zone, and analysts must correctly identify the species from images.	The detection zone has to be carefully determined after rigorous tests.

180   A further practical limitation is that cameras can hardly observe the animal

181 staying time during the long rest. In a simple example, a strictly diurnal species is

182 rarely detected at night unless we place millions of cameras. There are two choices

183 here: purchase and installation of millions of cameras to obtain sufficient data of

184 staying time during the night rest; or post hoc exclusion of night time—when

185 detectable animals are "absent"—from the survey period. Realists would take the

186 latter, and we recommend it. Rowcliffe et al. (2014) developed a method to estimate

187 the proportion of time that animals are on the move (referred to as "activity level")

188 with time-of-detection data from camera traps. Multiplying the survey period by the

189 activity level can correct the survey period to represent only when the animals are

190 moving. Accordingly, we can rewrite equations 2 and 5 as follows:

192       $$D = \mathrm{E}(Y) \cdot \mathrm{E}(T)/(sH \cdot p) \tag{6}$$

193   $$\log(\theta_i) = \log(D_i) - \log(\varphi_i) + \log(s) + \log(H_i) + \log(p) \tag{7}$$

195 where p is the activity level of the focal population. Nevertheless, this method assumes

196 that all animals in the population are active at the peak of the activity cycle (Rowcliffe

197 et al. 2014). Species whose activity rhythm doesn't synchronise between individuals,

198 including many cathemeral mammals, do not meet this assumption, and so their

199 density will be underestimated.

201 **Planning a survey**

203 **Set objectives**

204 Field surveys need firm objectives to be carried out. The following two points need

mature consideration. First, the two different objectives are often confounded: (i)

estimating the mean population density and (ii) examining the effects of covariates on

the density. In implementing the REST model, we can categorise these two objectives

in terms of the absence (Nakashima et al. 2018) or inclusion (Nakashima et al. 2020)

of explanatory variables in the linear predictors for the staying time and density. When

surveyors aim to estimate the mean density, the coordinates of camera-trap stations

should ideally be generated at random in the study area, without regard to the distance

between the stations. There's also principally no need to quantify habitat conditions.

On the other hand, if surveyors want to find some factors explaining the variation in

animal density, they have to carefully plan the camera placement design so that each

candidate explanatory variable has sufficient variation. Factors of interest can vary

widely, so they may place cameras from the foot to the top of the mountain, from the

vicinity of villages to remote forests, or in both logging and protected zones.

Moreover, sampling from each camera should be independent, so they have to set the

distance between the stations larger than the radius of the home range of focal animal

species.

Second, a good survey objective must explicitly define the scope of the

inference: The plan has to clearly explain your choices regarding the focal species, the

survey area and the survey period. Moreover, these choices should be justified in terms

of both convincingness and feasibility. Suppose a surveyor has set up a survey area of

100 km^2 in the south part of a 1000-km^2 national park and discussed the mean density

of the whole park from the results. This would hardly convincing because the survey

area is not necessarily representative of the entire park. She has two ways to solve this

problem: Extend the survey for the whole park, or, if this isn't feasible, change the

survey objectives. Also, surveys should usually be carried out in the dry season, when

the risk of camera failure due to rain or humidity is low. But if the focal species are

known to exhibit seasonal migratory behaviour, rainy-season surveys may also be

necessary to make convincing conclusions.

234   Decide on the camera placement design

Once you set suitable objectives, focal species and areas and periods of the survey,

decide how positioning the cameras. To do so, we can easily generate numerous points

on a computer-displayed map using free geographic information system (GIS)

software such as QGIS (QGIS Development Team 2021). Because of its easiness,

however, we are sometimes lost in the face of a massive number of options. To help

surveyors out of this quandary, we introduce some suitable camera placement designs

and some to be avoided.

Suitable designs

Random placement (Fig. 2a) is the first choice when estimating the mean density. It's

easy to draw—all we have to do is select the survey area and let the computer generate

random points for a number of camera stations. This placement is the most reliable in

ensuring random and unbiased sampling from the survey area. In a large survey area,

however, this placement may be impractical as the deployment is too labour-intensive

and time-consuming. Moreover, if you aim to identify covariates relating to the

density, this placement may cause problems because randomly placed cameras cannot

specify the range of target explanatory variables.

Fig. 2 Schematic maps of four suitable camera placement designs: (a) random placement, (b) systematic grid placement, (c) systematic transect placement, and (d) stratified-random placement. In each panel, 25 points for camera trap stations (red circles) are generated in a 100-km^2 survey area (blue square).

Systematic placement is an elegant way to find factors explaining variations in the density. When this placement is adopted, surveyors typically set up a square grid over the survey area, setting camera stations at each grids' centre. In this "grid design" (Fig. 2b), camera station points are evenly spaced throughout the survey area. To ensure data independence, the length of the grids' sides should be greater than the radius of the subject animals' home range. It may be possible to estimate the mean

density using the grid placement, but there is a risk of bias in the estimated density and

confidence intervals. In a survey area where logging roads or other structures are built

at nearly equal intervals, for example, equally-spaced cameras may bias the estimates

because particular environmental areas are sampled disproportionately.

Alternatively, surveyors may set line transects evenly over the survey area and

then set camera stations at regular intervals along the transects. This "transect design"

(Fig. 2c) is more effortless when installing and managing cameras than the grid design.

This design needs, however, hierarchical modelling in statistical analysis because

stations are nested within and between transects. One step further, this design allows

comparisons of density between different zones in a survey area by deliberately

placing transects in each zone. It should be noted, however, that the transect method

does not provide an accurate estimation of the mean density for the whole area.

Random placement is too labour-intensive; systematic designs risk biased

sampling. A good compromise to solve this dilemma is *stratified-random placement*

(Fig. 2d). This is a mixture of the above two placements: Like a systematic placement,

set up a coarse square grid but generate a random point per grid for camera stations. If

one wishes to avoid cameras coming too close to each other, draw a circle of an

appropriate size in each grid's centre and generate a random point within it. Cameras

will not be placed out of the circles, so data independence is guaranteed. By carefully

planning this placement, the two objectives (mean density estimation and examination

of covariates) may be set simultaneously. Furthermore, this placement has many

possible variations. For example, stratify the survey area according to vegetation types

on a GIS map and then generate random station points so that the number of points is

proportional to the area covered by each vegetation type. In this way, one can estimate

the mean density of the entire area with a small bias and test the differences in density

between vegetation types.

Methods to be avoided

Targeted placement should be avoided when working for the population density

estimation, although it may be suitable for other objectives, such as the compilation of

a reliable mammal species list (Tobler et al. 2008; Vanthomme et al. 2013; Cusack et

al. 2015) or the remote observation of specific behaviours or interactions (Pebsworth

et al. 2012; Boesch et al. 2017; Smith et al. 2020). This design violates the assumption

that cameras are placed randomly to the animal's spatial distribution. Suppose we

placed all cameras along animal trails. In that case, the estimated staying time may be

shorter, and the number of passes may be much larger compared to the survey area's

average. Surveyors may, therefore, obtain a severely biased density estimate.

Opportunistic placement refers to a sampling design where cameras are

placed solely based on surveyors' own experience and intuition—this is not a design.

If the design isn't explicitly determined or reported, one cannot judge the survey's

reliability or replicate it.

Select a camera trap model

With the rise of camera trap research, many companies offer a vast range of camera

models. The overwhelming choice leaves us at a loss as to which model from which

company to buy. Some websites, such as "trailcampro.com"

(https://www.trailcampro.com/), offer data comparing and evaluating many camera

trap models and can help you choose camera models. Research papers often specify

the model used. Some studies compared the performance of different cameras (Apps &

McNutt 2018a). Informal advice from colleagues and social networking sites may also

be useful. Here, we focus on the minimum requirements for our purposes.

The video mode is an essential feature when using the REST model, which

requires measuring animal staying time in the detection zone. High video quality is not

necessary since the REST model doesn't need individual identification. Alternatively,

continuous still photography may be used to measure the staying time, but with fast-

moving species, the entry and exit of the detection zone are often missed. Videos are

also helpful for species recognition among similar species (Hongo et al. 2020).

Fast trigger speed and minimum (<1 s) time interval option are highly

recommended to avoid many censored staying time. Right-censored staying time data

can be incorporated into the model (Nakashima et al. 2018), but the less such data, the

better. Moreover, it is challenging to manage left-censored data—staying time where

the entry into the detection zone was not observed—so we prefer cameras that start

recording instantly on detection.

A small built-in display is very useful for checking a camera's field of view

and adjusting its angle and position. The REST model assumes the perfect detection of

the focal species within the detection zone (Table 1), so standardising the camera angle

and position in relation to the detection zone is crucial.

Infrared flash LEDs, particularly "low-glow" and "no-glow" LEDs, are highly

recommended to avoid altering the behaviour of detected animals. White LEDs are

suitable for capturing clear images but may disturb animal behaviour and bias the

staying time.

If it's possible to use the time-lapse mode simultaneously as the motion-

trigger mode, one should do so. This is not mandatory, but analysts can accurately

calculate the survey period if cameras automatically take one video every day at

midnight.

Configure camera setting

We have now selected and purchased camera traps best suited to the survey. The next

step is to make some settings as described below. Once you have completed these

settings, we strongly recommend testing the cameras before going to the field with

them.

As discussed in the previous section, cameras need to be set to the video and

motion-trigger modes. If your cameras allow using the time-lapse function

concurrently with the motion-trigger mode, please set to take one video footage every

day at 00:00. Video length should cover the whole staying time: A length of 20–30 s

seems sufficient for many species. Moreover, the time interval from the previous video

must be minimal. Lastly, it is better to make your cameras work 24 hours even your

subjects are strictly diurnal or nocturnal, as animals often exhibit some extent of

cathemerality, which may be not yet known even by experts.

Lay out the camera station

The data quality in the camera-trap survey strongly depends on the layout of camera-

trap stations. Even if we have carefully planned the placement design and selected a

suitable camera model and configuration, a major mistake in the layout can render all

the efforts worthless. This section discusses the layout considerations and two

recommended examples.

There are three basic rules. Firstly, modification of the environment around

the stations should be as minimal as possible. Placing baits or lure isn't an option, and

you should try to leave as little human scent as possible around the stations. The

undergrowth in front of cameras should be cleared to ensure perfect detection. But it

may also alter the behaviour of sensitive species, so the clearing area should be

standardised and kept minimal.

Secondly, the detection zone needs to be standardised so that every camera

detect the focal species with certainty. Therefore, surveyors have to determine the zone

within which the focal species can be certainly detected by testing with animals of

comparable weight. This test should be carried out before the start of your survey. The

zone can be any shape, as long as it ensures certain detection, but we recommend an

equilateral or isosceles triangle. The zone's appropriate shape, size and distance from

the camera depend on the camera model.

Lastly, it is advisable to orient cameras to the north or south. Easting and

westing cameras will cause sensors to trigger morning or evening sunlight, resulting in

plentiful "empty" videos.

Below, we present two examples of station layouts that will be useful for

surveys in forested areas. The first example is the most typical and commonly used;

the second one may be more suitable if there's a concern that animals avoid cameras or

camera stations or destruct cameras.

Horizontal layout

The most general layout involves fixing a camera trap at the shoulder height, or

slightly lower (Apps & McNutt 2018a), of focal species and orienting the camera so

that its view is parallel to the ground (Fig. 3a). Note that we should adjust the camera

height and angle based on the ground at the detection zone, not the ground directly

below the camera (Fig. 3a-iii, 3a-iv). When setting the detection zone's size and

distance to the camera, you have to make sure the two points (Fig. 3a-ii): Does the

camera's view cover the entire detection zone?; Does the animal always trigger the

camera sensor, no matter which direction it enters the zone?

In this layout, the horizontal orientation of camera traps leads to a long

detection range. This allows us to set a wide detection zone, which increases the

sample size of staying time. Although the sample size of the number of passes doesn't

depend on the detection zone's size, the mean density may be estimated more precisely

if the number of cameras with zero detection is reduced. This layout, however,

possibly have a large impact on animal behaviour. The camera height has to be low

because of the horizontal orientation, typically 30–50 cm above the ground. So,

surveyors have to clear a considerable area—from the camera to in and around the

detection zone—of undergrowth almost from the base (Fig. 3a-i). This may discourage

vigilant animals from entering the zone or alter their travel speed within the zone

(Caravaggi et al. 2020). Moreover, the detection zone may be squashed vertically flat

in the video images, making it difficult to measure the staying time in subsequent

video analysis.

Depression-angle layout

In areas where animals are sensitive to the presence of camera traps, human odours on

the cameras, or cleared undergrowth, the horizontal design may alter their behaviours

and cause considerable bias in sampling. When surveying in such areas, the best way

is to adopt another station layout where the cameras are fixed at a higher position and

face downwards at an angle (Fig. 3b). When surveying a mammal with a shoulder

height of about 50 cm, for example, it may be suitable to set cameras at 100–120 cm

above the ground to keep them out of sight. As with the horizontal design, we have to

standardise the camera's position relative to the detection zone and test for perfect

detection within the zone (Fig. 3b-iii, 3b-iv).

In this depression-angle layout, the detection zone triangle will be more

visible in videos than in the horizontal layout (Fig. 3b-ii), allowing analysts to measure

the staying time accurately. It also results in minor vegetation disturbance because

there's no need to uproot the grass and vines that block the space between the camera

and the detection zone (Fig. 3b-i). This layout is, however, more difficult to be

standardised to guarantee perfect detection. Hence, surveyors have to carefully test the

detection certainty and receive training to replicate the same layout at all the stations.

Fig. 3 Schematic images of (a) horizontal and (b) depression-angle layouts of a camera station. Images (a-i) and (b-i) show views from the back of the camera trap. Images (a-ii) and (b-ii) depict images on the built-in display. Images (a-iii) and (b-iii) represent side views of the stations where the ground is level; images (a-iv) and (b-iv) represent those where the ground is tilted. In each image, the dashed blue triangles show the detection zone.

List the covariates

If the objective is simply to estimate the mean density of the survey area, this section can be skipped. By contrast, if the aim is to incorporate habitat covariates into the model, which potentially explain variations in staying time and density, you need to obtain them for each station. These covariates have to be extrapolatable to entire the survey area; otherwise, it will be impossible to predict the density distribution over the entire survey area. Therefore, the covariates will not be measured at the station when the camera is installed but should be obtained in advance from appropriate maps and GIS databases. Environmental covariates include elevation, slopeness, vegetation types, and the distance from the forest edge; anthropogenic ones include the distance from settlements, human population size in the settlements, and administrative zones (e.g., logging zone, natural reserve). A set of covariates influencing staying time and density will vary between the species and survey area. Thus, to decide on candidate covariates and methods to measure them, surveyors have to wade through the literature to know the ecology of the focal species and the history and characteristics of the survey area.

Carry out the survey

Good survey plan developed—let's go out into the field. Before entering the forest, the survey team should establish a proper schedule. An unrealistic field plan will lead to mistakes and, above all, unexpected illness and injury. Prepare the survey equipment carefully. List all the necessary supplies (e.g., ropes for marking the detection zone, measuring tapes, camping stuff, food, first aid kit, among others) and number each

camera after the operation check. Batteries and SD cards should be installed in the

camera before going to the field to save labour at the camera stations—don't forget to

turn off the power.

In the field, surveyors use handheld GPS devices to reach predetermined

camera station points. Arriving at a point, we should take care not to arbitrarily

determine the camera place. The GPS devices have a positioning error of 5–10 m, so

there is a risk that we unintentionally choose an open area. To avoid this, we have to

mechanically select the point where the GPS navigation system first indicates that the

distance to the destination became 0 m. Instead of fixing a camera to a tree nearest the

point (this would also bias the sampling), it's better to drive a picket into the point and

strap the camera to it.

Establish the camera station according to the layout you planned. On your

datasheet, record the time and date of installation and the required measurements.

Then check if the camera station is appropriately prepared as you planned: Is the

detection zone well within the camera's field of view (Fig. 4a, b)?; Is the camera

appropriately triggered when an animal enters the zone?; Are there no obstructions—

herbs, vines or tree brunches—between the camera and the detection zone (Fig. 4c, d)?

If even a tiny leaf is right in front of the camera, it will be exposed to the infrared

flash, probably making night-time videos completely dark (Fig. 4e, f). Even if the

camera view is unobstructed at the time of placement, over time, herbs will grow, and

vines will hand down due to wind and rain, which should be anticipated and removed

beforehand. When all checks are complete, take one "empty" video (or photo) with the

detection zone string in place, after which we remove the string and leave for the next

station.

Fig. 4 Captured images of camera trap videos. Camera stations with ropes defining the

detection zone in (a) a horizontal and (b) a depression-angle layout. Analysts use

photos of this kind to measure the staying time. If the camera's field of view is

obstructed by (c) leaves or (d) a tree branch, the perfect detection assumption is not

met, and the staying time also cannot be correctly measured. Besides, if a tiny vine is

in front of the camera, (e) daytime videos are recorded without problem, but (f) night-

time videos are darkened by the flashes illuminating the vine, making it very difficult

to observe detected animals—there is an Emin's giant pouched rat, *Cricetomys emini*,

in the centre of the image.

What if we can't reach the station because of a river or a cliff? The first option

is to find a diversion and manage to get there. But sometimes, the point indicated by

the GPS is in a large river or a deep valley. In that case, we need to shift the point, but

there's again a risk of introducing arbitrariness. To prepare for such cases, it might be a

good idea to have second points for all the stations in advance or make a rule such as

"place the camera at the point 100 m north of the original".

Analyse the data

Data acquisition from videos

Species identification

Faced with the obtained data set containing thousands, or tens of thousands of videos,

analysts first have to do "tagging" (identification of animal species recorded). Many

recent researchers develop image recognition programs using deep learning

(Norouzzadeh et al. 2018; Willi et al. 2018). There are also projects, such as Wildlife

Insights (https://www.wildlifeinsights.org), which automatically tag animal images

uploaded to websites. Most of these programs, however, work only for photos and not

for videos. Therefore, at least for the moment, this task has to be done manually by

analysts, one by one. If you only want to estimate the density of particular species,

videos of the other species may be skipped. But you may think that this is a terrible

waste of data. In that case, analysts have to identify species of each video using

appropriate nomenclatures, such as Kingdon (2015) and Francis (2019).

512   Brave analysts may be planning to complete this painful task using a media

player (such as VLC media player) and a spreadsheet (such as Microsoft Excel or

Apple Numbers). But this will result in dubious datasheets, contaminated by numerous

human errors, after hundreds of hours of work. We should avoid this risky "media

player–spreadsheet" approach; otherwise, our careful planning and hard fieldwork may

go to waste. Instead, analysts can use software that supports video tagging. Among

several alternatives, including Aardwolf (Krishnappa & Turner 2014) and ViXeN

(Ramachandran et al. 2018), we recommend Timelapse (Greenberg et al. 2019;

Greenberg 2021). This free software is fast, accepts videos (.mp4, .avi and .asf), has

flexible tagging options, easily converts the tags to a CSV file, and is still being

updated, although it only works on Windows OS.

After the necessary species identification work has been completed, it's

advisable to publish, if possible, a video list of the identified animals—this is

important to ensure the validity of the analysis results and as a reference for those

working in the same area. We provide a video list of mammal videos recorded in

southeast Cameroon on our YouTube channel

(https://www.youtube.com/playlist?list=PLAxagdZwt_bmmYkZlcDjnpCaBm1Nvk1a

Y).

Measurement of necessary values

Once the hard work of species identification is done, analysts have to dive into another

hard work—the measurement of values required in the REST model. The values are:

(1) survey period (number of camera working days),

(2) the number of animal passes at each station,

(3) staying time of each detection, and

(4) time of animal passes.

We can calculate the survey period of each camera station from the field note and the

camera recording history. The other three values are obtained from videos, so analysts

can use Timelapse or equivalent software to record them. The time of animal passes is

automatically recorded in the video files. In contrast, the number of passes and staying

time must be visually recorded from videos. For this purpose, we need to make the

window showing the detection zone photo semi-transparent and superimpose it on the

animal video images on a computer display (Fig. 6). The authors use TranspWnds

(https://code.google.com/archive/p/transpwnds/downloads) to transparentise windows,

but there appear several alternatives. For measuring these values, analysts have to

define, in advance, the reference body part (e.g., the right hind leg toe).

Statistical modelling

After the data acquisition from camera trap videos, statistical modelling using the

data—the most exciting but often depressing part of the wildlife survey—awaits you.

The statistical analysis details on the REST model are provided in previous papers

(Nakashima et al. 2018; Nakashima et al. 2020), so we give here only several essential

points.

First, before struggling with the modelling, carefully check the data

organisation to remove human error from the data. Are staying time values calculated

correctly, particularly when one stay spans several videos? Do the numbers of passes

match the number of staying time data for all the stations? Did you exclude periods

when the camera was malfunctioning from the survey period?

Second, we recommend constructing the REST model as a Bayesian statistical

model, rather than a frequentist model, using Stan (Stan Development Team 2021) or

JAGS (Plummer 2017). Bayesian modelling is much more flexible, and we can easily

estimate the expected values and their credible intervals of the population density and

its covariates.

Discussion

Discussion

Estimating animal density is central in population ecology and wildlife management,

yet difficult to achieve, particularly in forested areas. Camera traps have the potential

to overcome this challenge but need to be used with an appropriate method to get

accurate estimates. In this report, we overviewed the practical steps involved in

estimating the density using camera traps. We have described the steps assuming the

use of the REST model, but many parts of the report will also be helpful when

applying other models. The keys are to correctly understand the structure and

assumptions of the model we use and to plan a survey accordingly. Generate a

placement design that meets the assumptions, select a suitable camera model, check

the setting, and finalise the camera station layout after tests in the laboratory. Once you

have finished a detailed research plan in place, then carry out the survey as closely as

possible to the plan. After retrieving cameras, a large amount of video data awaits the

analysts. Analyse the videos efficiently and perform the statistical modelling

accurately.

Planning a camera trap survey can sometimes be a lonely task. In the planning

process, however, we are often confronted with details that cannot be decided alone.

God is in the details, but so is the devil. So share and discuss your draft with your

collaborators and colleagues, then revise the plan. Moreover, we hope more camera

trappers share their survey plans in their articles and reports (Meek et al. 2014). If it's

not possible to include the detailed methods in a research paper, it may be shared on

open access platforms, such as preprint repositories (e.g., bioRxiv,

https://www.biorxiv.org/) and social networking sites (e.g., ResearchGate,

https://www.researchgate.net/). These practised protocols will undoubtedly be helpful

to others planning new surveys, as well as proving that your findings are robust. We

hope that our practical guide will not remain isolated but rapidly becomes "one of

many".

Acknowledgements

Acknowledgements

We thank the following institutions and project teams for allowing us to carry out the

camera trap surveys, which gave us the essential experience to write this paper. In

Gabon, the Centre National de la Recherche Scientifique et Technologique

(CENAREST) and the Agence Nationale des Parcs Nationaux (ANPN) permitted and

collaborated with our research, and the PROCOBHA research team helped our work in

the field and laboratory. In Cameroon, we had the full cooperation of the Institute of

Agricultural Research for Development (IRAD) and the Coméca project team. In

Japan, Chiba prefecture approved our research. This paper is a product of an

international joint research initiative between Cameroon and Japan funded by

JST/JICA SATREPS (JPMJSA1702) and was also supported by JSPS KAKENHI

Grant Numbers JP15K07487, JP18K14803 and JP20KK0015). The authors declare

that there is no conflict of interest.

Literature Cited

611   **Literature Cited**

613   Akaike, H. (1973). Information theory and an extension of the maximum likelihood

614   principle. In B. N. Petrovand, and F. Caski (Eds.), *Proceeding of the Second*

615   *International Symposium on Information Theory* (pp. 267–281). Akademiai

Kiado, Budapest.

Akaike, H. (1974). A new look at the statistical model identification. *IEEE*

Transactions on Automatic Control, *19*(6), 716–723.

Apps, P. & McNutt, J. W. (2018a). Are camera traps fit for purpose? A rigorous,

reproducible and realistic test of camera trap performance. *African Journal of*

Ecology, *56*(4), 710–720.

Apps, P. J. & McNutt, J. W. (2018b). How camera traps work and how to work them.

African Journal of Ecology, *56*(4), 702–709.

Boesch, C., Kalan, A. K., Agbor, A., Arandjelovic, M., Dieguez, P., Lapeyre, V. &

Kuhl, H. S. (2017). Chimpanzees routinely fish for algae with tools during the

dry season in Bakoun, Guinea. *American Journal of Primatology*, *79*(3), 1–7.

Buckland, S. T., Anderson, D. R., Burnham, K. P., Laake, J. L., Borchers, D. L. &

Thomas, L. (2001). *Introduction to distance sampling: estimating abundance of*

biological populations.

Buckland, S. T., Rexstad, E. A., Marques, T. A. & Oedekoven, C. S. (2015). *Distance*

sampling: methods and applications. Cham, Switzerland: Springer

International.

Burgar, J. M., Stewart, F. E. C., Volpe, J. P., Fisher, J. T. & Burton, A. C. (2018).

Estimating density for species conservation: Comparing camera trap spatial

count models to genetic spatial capture-recapture models. *Global Ecology and*

Conservation, *15*, e00411.

Burton, A. C., Neilson, E., Moreira, D., Ladle, A., Steenweg, R., Fisher, J. T., Bayne,

E. & Boutin, S. (2015). Wildlife camera trapping: a review and

recommendations for linking surveys to ecological processes. *Journal of*

Applied Ecology, *52*(3), 675–685.

Caravaggi, A., Burton, A. C., Clark, D. A., Fisher, J. T., Grass, A., Green, S., Hobaiter,

C., Hofmeester, T. R., Kalan, A. K., Rabaiotti, D. & Rivet, D. (2020). A review

of factors to consider when using camera traps to study animal behavior to

inform wildlife ecology and conservation. *Conservation Science and Practice*,

2(8), e239.

Cavada, N., Tenan, S., Barelli, C. & Rovero, F. (2019). Effects of anthropogenic

disturbance on primate density at the landscape scale. *Conservation Biology*,

33(4), 873–882.

Chandler, R. B. & Royle, J. A. (2013). Spatially explicit models for Inference about

density in unmarked or partially marked populations. *Annals of Applied*

Statistics, *7*(2), 936–954.

Cusack, J. J., Dickman, A. J., Rowcliffe, J. M., Carbone, C., Macdonald, D. W. &

Coulson, T. (2015). Random versus Game Trail-Based Camera Trap Placement

Strategy for Monitoring Terrestrial Mammal Communities. *PLoS One*, *10*(5),

e0126373.

Elliot, N. B. & Gopalaswamy, A. M. (2017). Toward accurate and precise estimates of

lion density. *Conservation Biology*, *31*(4), 934–943.

Francis, C. M. (2019). *Field guide to the mammals of south-east Asia*. London, UK:

Bloomsbury Wildlife.

Garland, L., Neilson, E., Avgar, T., Bayne, E. & Boutin, S. (2020). Random encounter

and staying time model testing with human volunteers. *The Journal of Wildlife*

Management, *84*(6), 1179–1184.

Gilbert, N. A., Clare, J. D. J., Stenglein, J. L. & Zuckerberg, B. (2021). Abundance

estimation of unmarked animals based on camera-trap data. *Conservation*

Biology, *35*(1), 88–100.

Greenberg, S., (2021). Timelapse: An Image Analyser for Camera Traps.

http://saul.cpsc.ucalgary.ca/timelapse/.

Greenberg, S., Godin, T. & Whittington, J. (2019). Design patterns for wildlife‐

related camera trap image analysis. *Ecology and Evolution*.

Hongo, S., Dzefack, Z. s. C. B., Vernyuy, L. N., Minami, S., Nakashima, Y., Djiéto-

Lordon, C. & Yasuoka, H. (2020). Use of multi-layer camera trapping to

inventory mammals in rainforests in southeast Cameroon. *African Study*

Monographs, *Suppl. 60*, 21–37.

Howe, E. J., Buckland, S. T., Després-Einspenner, M.-L., Kühl, H. S. &

Matthiopoulos, J. (2017). Distance sampling with camera traps. *Methods in*

Ecology and Evolution, *8*(11), 1558–1565.

Hu, X., Huang, B., Verones, F., Cavalett, O. & Cherubini, F. (2021). Overview of

recent land‐cover changes in biodiversity hotspots. *Frontiers in Ecology and*

the Environment, *19*(2), 91‐97.

Iijima, H. (2020). A review of wildlife abundance estimation models: comparison of

models for correct application. *Mammal Study*, *45*(3), 177–188.

Kamgaing, T. O. W., Bobo, K. S., Djekda, D., Azobou, K. B. V., Hamadjida, B. R.,

Balangounde, M. Y., Simo, K. J. & Yasuoka, H. (2018). Population density

estimates of forest duikers (*Philantomba monticola* & Cep*halophus spp*.) differ

greatly between survey methods. *African Journal of Ecology*, *56*(4), 908–916.

Kingdon, J. (2015). *The Kingdon field guide to African mammals*. London, UK:

Bloomsbury Publishing.

Krishnappa, Y. S. & Turner, W. C. (2014). Software for minimalistic data management

in large camera trap studies. *Ecological Informatics*, *24*, 11–16.

Marchese, C. (2015). Biodiversity hotspots: A shortcut for a more complicated

concept. *Global Ecology and Conservation*, *3*, 297–309.

McCallum, J. (2013). Changing use of camera traps in mammalian field research:

habitats, taxa and study types. *Mammal Review*, *43*(3), 196–206.

Meek, P. D., Ballard, G., Claridge, A., Kays, R., Moseby, K., O'Brien, T., O'Connell,

A., Sanderson, J., Swann, D. E., Tobler, M. & Townsend, S. (2014).

Recommended guiding principles for reporting on camera trapping research.

Biodiversity and Conservation, *23*(9), 2321–2343.

Myers, N., Mittermeier, R. A., Mittermeier, C. G., da Fonseca, G. A. & Kent, J. (2000).

Biodiversity hotspots for conservation priorities. *Nature*, *403*(6772), 853–858.

Nakashima, Y., Fukasawa, K. & Samejima, H. (2018). Estimating animal density

without individual recognition using information derivable exclusively from

camera traps. *Journal of Applied Ecology*, *55*(2), 735–744.

Nakashima, Y., Hongo, S. & Akomo-Okoue, E. F. (2020). Landscape-scale estimation

of forest ungulate density and biomass using camera traps: Applying the REST

model. *Biological Conservation*, *241*, 108381.

Norouzzadeh, M. S., Nguyen, A., Kosmala, M., Swanson, A., Palmer, M. S., Packer, C.

& Clune, J. (2018). Automatically identifying, counting, and describing wild

animals in camera-trap images with deep learning. *Proceedings of the National*

Academy of Sciences of the United States of America, *115*(25), E5716–E5725.

O'Connell, A. F., Nichols, J. D. & Karanth, K. U. (2011). *Camera traps in animal*

ecology: methods and analyses. Tokyo: Springer.

Pebsworth, P. A., Bardi, M. & Huffman, M. A. (2012). Geophagy in chacma baboons:

patterns of soil consumption by age class, sex, and reproductive state.

American Journal of Primatology, *74*(1), 48–57.

Plummer, M., (2017). JAGS: Just Another Gibbs Sampler, version 4.3.0.

https://sourceforge.net/projects/mcmc-jags/.

QGIS Development Team, (2021). QGIS Geographic Information System. Open

Source Geospatial Foundation Project. http://qgis.osgeo.org.

Ramachandran, P., Devarajan, K. & Poisot, T. (2018). ViXeN: An open-source package

for managing multimedia data. *Methods in Ecology and Evolution*, *9*(3), 785–

792.

Rowcliffe, J. M., Field, J., Turvey, S. T. & Carbone, C. (2008). Estimating animal

density using camera traps without the need for individual recognition. *Journal*

of Applied Ecology, *45*(4), 1228–1236.

Rowcliffe, J. M., Kays, R., Kranstauber, B., Carbone, C., Jansen, P. A. & Fisher, D.

(2014). Quantifying levels of animal activity using camera trap data. *Methods*

in Ecology and Evolution, *5*(11), 1170–1179.

Santini, L., Isaac, N. J. B., Maiorano, L., Ficetola, G. F., Huijbregts, M. A. J., Carbone,

C. & Thuiller, W. (2018). Global drivers of population density in terrestrial

vertebrates. *Global Ecology and Biogeography*, *27*(8), 968–979.

Smith, J. A., Suraci, J. P., Hunter, J. S., Gaynor, K. M., Keller, C. B., Palmer, M. S.,

Atkins, J. L., Castaneda, I., Cherry, M. J., Garvey, P. M., Huebner, S. E., Morin,

D. J., Teckentrup, L., Weterings, M. J. A. & Beaudrot, L. (2020). Zooming in

on mechanistic predator-prey ecology: Integrating camera traps with

experimental methods to reveal the drivers of ecological interactions. *Journal*

of Animal Ecology, *89*(9), 1997–2012.

Stan Development Team, (2021). Stan modeling language users guide and reference

manual, version 2.26.

Tobler, M. W., Carrillo-Percastegui, S. E., Leite Pitman, R., Mares, R. & Powell, G.

(2008). An evaluation of camera traps for inventorying large- and medium-

sized terrestrial rainforest mammals. *Animal Conservation*, *11*(3), 169–178.

Vanthomme, H., Kolowski, J., Korte, L. & Alonso, A. (2013). Distribution of a

community of mammals in relation to roads and other human disturbances in

Gabon, central Africa. *Conservation Biology*, *27*(2), 281–291.

Watanabe, S. (2010). Asymptotic equivalence of Bayes cross validation and widely

applicable information criterion in singular learning theory. *Journal of Machine*

Learning Research, *11*(116), 3571–3591.

Willi, M., Pitman, R. T., Cardoso, A. W., Locke, C., Swanson, A., Boyer, A., Veldthuis,

M., Fortson, L. & Gaggiotti, O. (2018). Identifying animal species in camera

trap images using deep learning and citizen science. *Methods in Ecology and*

Evolution, *10*(1), 80–91.

Yokoyama, Y., Nakashima, Y., Yajima, G. & Miyashita, T. (2020). Simultaneous

estimation of seasonal population density, habitat preference and catchability of

wild boars based on camera data and harvest records. *Royal Society Open*

Science, *7*(8), 200579.