Title: The misleading certainty of uncertain data in biological network processes.

Authors: Michael W. Irvin, Arvind Ramanathan, and Carlos F. Lopez

Keywords: *cellular processes, network mechanism, data types, quantitative data, qualitative data, model calibration, parameter inference, high performance computing, model prediction, model certainty, model accuracy.*

Abstract

Mathematical models are often used to study the structure and dynamics of network-driven cellular processes. In cell biology, models representing biochemical reaction networks have provided significant insights but are often plagued by a dearth of available quantitative data necessary for simulation and analysis. This has in turn led to questions about the usefulness of biochemical network models with unidentifiable parameters and high-degree of parameter sloppiness. In response, approaches to incorporate highly-available non-quantitative data and use this data to improve model certainty have been undertaken with various degrees of success. Here we employ a Bayesian inference and Machine Learning approach to first explore how quantitative and non-quantitative data can constrain a mechanistic model of apoptosis execution, in which all models can be identified. We find that two orders of magnitude more ordinal data measurements than those typically collected are necessary to achieve the same accuracy as that obtained from a quantitative dataset. We also find that ordinal and nominal non-quantitative data on their own can be combined to reduce model uncertainty and thus improve model accuracy. Further analysis demonstrates that the accuracy and certainty of model predictions strongly depends on accurate formulations of the measurement as well as the size and make-up of the nonquantitative datasets. Finally, we demonstrate the potential of a data-driven Machine Learning measurement model to identify informative mechanistic features that predict or define nonquantitative cellular phenotypes, from a systems perspective.

Introduction

The combination of systems approaches and quantitative data promised a novel understanding of cellular mechanisms that would spur science-driven innovation in biology and medicine – as happened in physics, chemistry, and engineering[1-3]. Despite massive research efforts and data accumulation, our understanding of cellular regulation, signaling and many other processes as biomolecular *systems* remains rudimentary. The systems and quantitative biology fields continue to employ strategies from physics and engineering to construct models of biological mechanism from first principles[4,5]. However, these strategies are incompatible with the types of measurements and observations that predominate biological investigations. Observations from biological experiments investigating cell fate outcomes (apoptosis, necroptosis, etc.) are collected as categorical values, which are hard to define in terms of variables encoded in mathematical mechanistic models of biological processes[6]. Therefore, the connection of mechanistic models to corresponding biological measurements is subject to practitioner interpretation. As a result, vast amounts of existing nonquantitative data in cell biology have led to mechanistic formulations based on simple inference and informal reasoning. Noise, complexity and the hierarchical organization of biology limits how we can experimentally perturb and measure biological systems[7,8]. Therefore, a relative dearth of quantitative data exists that reveals itself in mechanistic models with poor parameter constraints. Unfortunately, both non-quantitative and quantitative data, collected in an unplanned manner, results in missed opportunities to quantitatively explain complex cellular mechanisms[9].

This data-to-knowledge problem in biology has prompted researchers to incorporate nonquantitative data as a complement or substitute for quantitative data in the development of mechanistic models[10-13]. The traditional workflow employed to train mechanistic models to data comprises mechanistic models and experimental measurements linked through a calibration method (Box 1)[14, 15]. Such workflows have been adapted to incorporate nonquantitative data into mechanistic models and have revealed their intrinsic value in mechanistic hypothesis exploration. For example, pioneering work by Pargett and co-workers

employed optimal scaling and multi-objective optimization for training mechanistic models to large
ordinal datasets[10]. Schmiester et al. incorporated this strategy into PyPESTO, a model parameter
estimation framework[11]. Their formulation imposes discrete boundaries on the mechanistic model to
reflect discrete ordinal values in the data, but this approach limits their ability to integrate multiple
datatypes or use Bayesian methods for training and uncertainty estimation of mechanistic models. More
recently, Mitra et al. applied predefined constraint-based models of categorical data and modified their
approach to allow definition of a likelihood function within a Bayesian formalism.[12, 13] However, the *ad*
hoc nature of their constraint models leaves room for biasing assumptions. Given the limited application
of Bayesian methods and biases introduced by *ad hoc* assumptions, the field still has a limited
understanding of the contribution of nonquantitative and quantitative data to mechanistic knowledge in
biological systems.
63
In this work, we tackle the data-to-knowledge challenge by introducing the concept of a *measurement*
model, a statistical construct, into systems modeling approaches, which aims to rigorously define
measurements and observations in terms of an underlying mechanisms[16]. This definition entails
formulation of a function that maps variables encoded in a mechanistic model to values in the
nonquantitative data. Our approach departs from previous work in that it uses machine-learning based
classifiers whose free parameters are estimated to accomplish data-driven identification of measurement
model properties. It also uses a probabilistic formulation that lends itself to Bayesian methods and can
therefore provide an unbiased evaluation of the predictive power of models trained to nonquantitative
data. In what follows, we present our findings about common types of biological measurements, followed
by a presentation of our methodology. In this work we use a mechanistic model of apoptosis execution to
demonstrate how the amount and type of data applied to a mechanistic model can affect its predictive
power. It is well established that apoptosis signaling is involved in many cellular processes in health,
disease, and development[17]. Its biological importance is further underscored by available quantitative and
nonquantitative empirical data[18]. We also establish how an *ad hoc* formulation of a measurement model
can lead to spurious results and further show how these *a priori* assumptions can be examined within a
Bayesian, data-driven context. Finally, we demonstrate the potential of a machine learning measurement
model formulation to identify phenomenological links between features (e.g. predictors and drivers) of a
biomolecular mechanism and emergent biological phenotype. We expect our approach to improve our
understanding of the data-to-knowledge relationship in biological processes, leading to a probabilistic
understanding of biochemical mechanisms, and accelerated identification of systems-level interactions
that drive biological network dynamics.
85
Results
Contributions and biases from different data types to mechanistic models
We first explored how experimental data measurements are used to constrain mathematical models of
cellular processes. Mechanistic models typically employ physical chemistry formalisms comprised of
reaction rates and chemical species concentrations to represent networks of biochemical reactions. Direct
quantitative measurement of all chemical reactions and species would provide needed model parameters
to carry out simulations and *in silico* experiments. However, these measurements are typically not
available and likely untenable for real systems, thus leading to indirect measurements used to infer model
parameter values using an objective function (Eq. 7) or a likelihood function (Eq. 8). When these
functions are optimized, the resulting mathematical model can provide valuable new predictions and
insights about the cellular process. Measurements from cell biology experiments comprise four broad
types, namely, nominal, ordinal, semiquantitative, and quantitative (Figure 1); each data type reveals
different insights about the cellular process. In apoptosis signaling, for instance, nominal observations
supported early research where it helped identify key components in the apoptosis signaling pathway[19].
Apoptosis and survival outcomes – as indicated by nominal nuclear fragmentation data (Figure 1 *top row*)
– helped determine two parallel signaling arcs that proceed following initiator caspase activation:
mitochondria-dependent and -independent pathways[19]. These pathways trigger apoptosis by activating

effector caspases[19]. We built an abridged Extrinsic Apoptosis Reaction Model (aEARM)[20], which
represents these extrinsic apoptosis execution mechanisms as biomolecular reactions (Figure 2A).
Nominal observations do not provide a definitive estimation of their quantity of interest (i.e. their
measurand) and instead, encode weak constraints on the measurand values (Eq. 1). They can guide
mechanistic modeling by revealing salient structural elements of a cellular process but provide limited
insight into the dynamics and complex regulatory cues of apoptosis signaling. Ordinal measurements
have featured prominently in works investigating apoptosis signaling. They have uncovered clues about
the dynamics and complex regulatory mechanisms of apoptosis. For instance, ordinal measurements of
DISC (i.e. a ligand-dependent membrane bound 'death inducing signaling complex') components,
initiator and effector caspases (Figure 1 *second row*), bid, etc. revealed how cells resist apoptosis by
limiting (but not totally eliminating) pro-apoptotic cues[21]; the sub-maximal pro-apoptotic signaling
presents as delay in the dynamics of caspase activation[22]. To better understand caspase activation
dynamics and its effect on apoptosis and survival, we need mathematical models of the apoptosis
signaling dynamics. Ordinal measurements, however, do not readily support a mathematical description
of apoptosis signaling dynamics. Emerging work has leveraged ordinal and nominal measurements in the
development of mathematical models of biological signaling but the weak constraints encoded by these
measurements (Eq. 1 and Eq. 2) add uncertainty and bias to the modeling process.
120
Technical challenges confine our quantitative and semi-quantitative measurement to just a few apoptotic
signaling proteins. Fluorescence indicators of caspase activity[18] (and by proxy, caspase substrate
cleavage) enabled time course measurements of Bid and PARP cleavage dynamics (Figure 1 *third row*)[18].
They revealed pro-apoptotic activation of Bid and PARP, in TRAIL induced apoptotic HeLa cells,
follows sigmoidal dynamics with delays and switch times that are sensitive to various regulatory factors.
These measurements provide the details necessary for a mathematical description of apoptosis signaling
dynamics and complexity. Our mathematical model aEARM captures the events from initial death ligand
cue, initiator caspase activation, BID truncation (tBID), mitochondrial outer membrane permeabilization
(MOMP) and eventual PARP cleavage (cPARP), as shown schematically on Figure 2[23-27]. The model was
calibrated to above fluorescence data, as described in *Methods*[28]. Semi-quantitative measurements like
fluorescence, like non-quantitative measurements lack a definitive estimation of the measurand because
their interpretation requires mathematical manipulation, typically through scaling (Eq. 3), which can also
add uncertainty and bias. Quantitative measurements can be used directly in a model without further
modifications (Figure 1, *fourth row*) thus minimizing the uncertainty and bias introduced in the model
from measurement interpretation. Therefore, the specific type of measurement and its interpretation could
add significant uncertainty and bias to the mechanistic explanation of a given process.
137
To study the bias and uncertainty originating from different types of measurements, we introduce a
concept from statistics, and social sciences: the *measurement model* (Box 1)[29]. Briefly, a measurement
model is a function (Eq. 6) that describes the relationship between the measurement and its measurand.
This function maps variables from the mechanistic model x to the values expressed in the data $\hat{y}$. This
function is often assumed or implied, particularly for semi-quantitative data that can more readily be
applied to the model calibration. However, the application of nominal and ordinal datatypes to
mechanistic models is not straightforward, because their interpretation (as we show in the following
sections) can significantly bias model-derived insights. Consequently, modeling efforts have relied almost
exclusively on quantitative and semi-quantitative data. By contrast, the much more abundant non-
quantitative datatypes are often ignored or used inappropriately.
148
Early modeling efforts interpreted nonquantitative data as a series of arbitrary surrogate quantities for the
ordinal or nominal values in a corresponding dataset[14]. More recently, discrete boundaries on the values
of the measurand were imposed along with a distance metric to describe how well the mechanistic model
satisfies nominal or ordinal constraints in the non-quantitative data[10-13]. These approaches reveal the value
of nonquantitative data for mechanistic model calibration, but the often-ad hoc nature of these constraint-

based measurement models has been an overlooked source of model bias. To minimize biases from the
interpretation of non-quantitative datatypes and apply Bayesian inference methods for model calibration,
we developed a data-driven probabilistic measurement model (Box 2). Our measurement model is data-
driven in that it possesses free parameters that are calibrated to match data; this lets us replace *a priori*
assumptions about the measurement with a data-driven parametrization, and thereby calibrate mechanistic
models whose accuracy and precision better reflect the information contained in the data. Our
measurement model is probabilistic as it replaces discrete boundary-based measurement models and
distance metrics with a *probability* (Box 2, Eq. 9) of the ordinal or nominal value, which enables easy
formulation of a likelihood function and application of Bayesian optimization methods that utilize
MCMC sampling. In our approach, the measurement model is a mathematical construct that represents
the measurand through a Machine-Learning probabilistic classifier whose free parameters are
simultaneously estimated with the free parameters of the mathematical model during calibration (Box 2).
As a probabilistic classifier, the measurement model effectively describes the probability of the categories
encoded in the non-quantitative data given values of the measurand (Eq. 9). The measurand, in our case,
is encoded in the mechanistic model. For example, the measurement model (Eq. 9, Box 2) can use ordinal
logistic classifiers to model the probability of a categorical value as a function of variable(s) encoded by
the mechanistic model. Also, the probability that a cell death or survival observations represents a specific
state of the mechanistic model. In the calibration process, the measurement model is an explicit
intermediate step between simulation of the mechanistic model dynamics and calculation of the likelihood
(Box 2). As described in the *Methods* section, this approach uses the Python based PySB models-as-
programs framework and PyDREAM, a Python implementation of the DREAM$_{(ZS)}$ algorithm to sample
posterior values of models' free parameters. However, other model building and parameter sampling (or
optimization) algorithms could be employed by the user. In what follows, we examine the impact of
different measurement modalities and interpretations on mechanistic model constraints in apoptosis
execution. This work motivates an approach that could be generalized to any mathematical model to
rigorously integrate quantitative and nonquantitative data types.
180
Uncertainty associated with different data types in model calibration
To date, molecular biology investigations of intracellular signaling processes and their mechanisms
predominantly report nonquantitative measurements. However, it is unclear exactly how well these
measurements support the development of mechanistic models. We therefore asked how various
measurement datatypes impact the certainty and accuracy of model calibrations. Specifically, we explored
how to adjust the size and make-up of nonquantitative datasets to better support mechanistic inferences.
The resulting posterior predictive region for tBID dynamics of aEARM calibrated to (semi-quantitative)
fluorescence data is shown in Figure 2 (B, top row). As expected, the data can effectively constrain the
model and the 95% credible region of posterior predictions for tBid dynamics falls within the data
uncertainty region. We then extracted a parameter vector from the fluorescence optimized data and used it
as a baseline (reference) to generate ordinal datasets for tBID and other aEARM variables as described in
Methods and shown Figures 2 (B, bottom four rows). These synthetic datasets could be considered as
numerical representations of a time-course western blot dataset. We then calibrated aEARM kinetic rate
and measurement model parameters to the ordinal and nominal datasets.
195
As shown in Figure 2B, ordinal datasets accurately predicted quantitative predictions of "ground truth"
dynamics for tBID. The 95% credible region of posterior predictions of tBID dynamics of aEARM
trained to these ordinal datasets each contained "ground truth" dynamics for tBID. We also use the area
bounded by the 95% credible region of posterior predictions of tBID as a measure of model certainty;
with a smaller area indicating higher certainty. The ordinal dataset containing measurements at every 25-
minute interval (i.e. typical of time-dependent western blot datasets), however, did not significantly
constrain the posterior predictive regions of these dynamics (Figure 2D). Increasing the number of
measurements, however, increases the certainty of the posterior predictions of tBID dynamics; this
certainty approaches that of the typical semi-quantitative (fluorescence) dataset, which has an area of 2.7,

when then the number of ordinal measurements is increased threefold, which had an area of 6.2. The areas
bounded by the 95% credible region for each ordinal time-course dataset is described in the Figure 2B
(Bottom two rows).
208
To explore the impact of nominal data on model optimization, we again extracted a parameter vector from
the fluorescence optimized data and used it as a baseline (reference) to generate nominal datasets akin to
an apoptosis execution observation as described in Methods. Previous work has described how features of
apoptosis signaling dynamics can predict cell death vs survival[18]. The generated nominal dataset describes
binary cell-fate outcomes that emerge as a consequence of extrinsic apoptosis signaling dynamics. We
encode this information in a nominal measurement model as described in *Methods.* Parameters of
aEARM and the free-parameters encoded in the measurement model were jointly calibrated to a
synthetically generated dataset of 400 survival vs death outcomes as shown in Figure 3A (left). As shown
in Figure 3A (right), the binary cell-fate data minimally constrain the posterior predictive region of tBID
dynamics relative to the prior constraints on the model. This is expected as the binary cell-fate data-type
essentially condenses complex apoptotic signaling dynamics to a single categorical value.
220
In lieu of its limited ability to constrain mechanistic models, modeling efforts understandably disregard
nominal data. However, we hypothesized that combining nonquantitative datatypes and covering multiple
variables in the model could improve model certainty. To explore the effect of multiple data type
combinations on model calibration, we again optimized the aEARM model parameters, but this time to a
dataset containing nominal and ordinal measurements. As described in *Methods*, we added a synthetic
dataset containing 61 ordinal time-course measurements for the DISC complex to the nominal dataset
described above (Figure 3B (left)). We modeled the likelihood of this combined dataset as the product of
the likelihoods of the individual constituent datasets (see *Methods* for details). In Figure 3A and 3B
(right), we see the nominal and ordinal datasets yields larger 95% credible regions for the posterior
predictions of tBID dynamics. However, (in Figure 3C) the combined dataset better constrained the
posterior predictions of normalized tBID dynamics than either dataset alone, with a 95% credible region
area of 26.5 (compared to 55.0 and 56.4 for the ordinal and nominal datasets alone). Therefore, the model
uncertainty stemming from only using tBID nominal data was decreased by including more detailed
upstream measurements. However, the contribution of DISC ordinal data alone was comparable to that of
the tBID nominal data in isolation (Figure 3B (right)). This data suggests that distributed measurements
across multiple variables in a pathway yield synergistic effects on calibrated model accuracy and
certainty.
238
Data-driven measurement model as an indicator of model bias
Traditionally, applying quantitative or semi-quantitative data to a mechanistic model has been relatively
straightforward as they typically follow a well-establish and simple relationship between the measurement
and the measurand. However, for non-quantitative data, measurement uncertainty can prompt researchers
to make assumptions about the relationship between measurement and measurand, which may negatively
impact in the resulting mechanistic model. We therefore asked how the encoding of assumptions into our
models of non-quantitative measurements could impact mechanistic model calibrations. To attain this
goal, we calibrated aEARM kinetic rate parameters to the ordinal dataset, but this time we replaced the
free parameters in the measurement model fixed *a priori* parameterizations or we encoded our
assumptions as priors on the measurement model's free-parameters. We tested four situations: (*i*) fixed
parameters, a case where the measurement model is pre-parameterized by the user, presumably reflecting
full confidence in their assumptions about the measurement; (*ii*) strong prior knowledge, a case where
there is strong belief in the assumed values of the measurement model parameters; (*iii*) weak prior
knowledge, a case where there is only weak belief in the assumed values of the measurement model
parameters; and (*iv*) no prior knowledge, that is no constraints on the measurement model parameters.
254

Figures 4A and 4B show the ordinal class probabilities for tBID as modeled by (i) two distinct pre-
parameterized measurement models. In case 1, lowest and highest categories correspond to a narrow
range of tBID values, while the three internal categories each account for roughly $1/3^{rd}$ of the tBID range.
This parameterization might aim to account for effects of sensitivity and saturation on the measurement.
In case 2, all five ordinal categories each account for $1/5^{th}$ of the range of tBID values. The right panels in
Figures 4A and 4B show the assumed relationship between tBID concentration and probability of each
ordinal category. Figures 4A and 4B (left plots) also show posterior predictions of tBID dynamics by
aEARM calibrated to the ordinal dataset using these fixed pre-parameterized measurement models. The
different measurement model pre-parameterization produced markedly different posterior predictions of
tBID dynamics by the resulting aEARM calibrations. This raises potential concerns that assumptions in
our interpretation of the measurement can artificially influence our interpretation of the mechanism.
266
In Figure 4B, the 50% probability boundary between adjacent categories occurs at every 0.2 interval;
essentially dividing the [0,1] range of tBID values into five equally spaced ordinal categories. Shown in
Figure 4C-E, we represent this as a *flexible* assumption by encoding it in our priors (ii – iv) i.e., Cauchy
distributions centered at every 0.2 interval (as detailed in *Methods*). The smaller the scale – more
narrowly focused – prior distributions reflect less flexibility in the free-parameter and a stronger belief in
our prior assumptions. Figure 4C-E shows the posterior predictions of tBID dynamics of aEARM
calibrated to the ordinal dataset using increasingly more constrained priors on the measurement model
parameters. The resulting posterior predictions of tBID dynamics were all less constrained than that of
aEARM calibrated using fixed pre-parameterized measurement models (Figure 4A and 4B) but, they were
more accurate as they contained the "ground-truth" tBID dynamics. Strongly constrained priors on the
measurement model parameters (ii) produced a less certain mechanistic model; as indicated by its wider
95% credible region of posterior predictions of tBID dynamics (Figure 4E). The posterior distributions of
measurement model parameters were spread out enough to give significant support of both the "ground
truth" and the *a priori* assumed parameter values. This uncertainty in the measurement model parameter
distributions translated into a less certain measurement model and less certain predictions of tBID
dynamics. Weaker constraints on the measurement model parameters were encoded via larger scale prior
distribution (Figure 4D). In Figure 4D we see these prior distributions, while centered on our *a priori*
assumptions, includes the "ground truth" parameters. The posterior distributions of the measurement
model parameters were therefore more constrained; likewise, the measurement model and posterior
predictions of tBID dynamics had more certainty. This is also observed, in Figure 4C, the case where no
prior assumptions were applied to the measurement model parameters (iv). The accuracy of the
predictions of tBID dynamics comes from the flexibility of the data-driven measurement models'
parameters. This flexibility enables optimization (or prediction) of key properties of the measurement
given the data. Figure 4 (right panels) shows the predicted probabilities of the ordinal categories (as a
function predicted cellular tBID content); these predictions are accurate in that they contain "ground
truth" probabilities. Using this approach, we calibrated more accurate models of mechanism by
simultaneously learning a more accurate model of the measurement. This motivates us to further explore
the data-driven measurement model as a potential new avenue for insights.
295
Mechanistic insights from data-driven measurement models
We have shown thus far how a machine-learning measurement model can reduce uncertainty and increase
accuracy in model calibration. Through mechanistic model calibration to categorical data, we effectively
employ machine-learning classifiers to constrain mechanistic model dynamics to a corresponding
categorical phenotype. We can then employ the measurement model in reverse, to better understand how
properties of a biological mechanism predict, drive and define a particular phenotype. This kind of
knowledge would be essential for model-driven experimental data acquisition and model-guided
validation.
304

To demonstrate this concept, we calibrated aEARM to nominal cell survival vs death data using a
measurement model that estimated the contribution of variables in aEARM to the cell survival vs. death
predition. The survival vs death dataset was synthesized based on maximum log-rate of change of tBID
and the time at which the rate of change maximized; these features were encoded into the measurement
model, but their contribution was represented as a free parameter. In addition, the measurement model
also considered the potential contribution of an unrelated variable (i.e. concentration of a reactants in
reactions that occurred independently of the cell death ligand). Jointly calibrating aEARM and this
measurement model to cell survival vs death data allowed data-driven predictions of how variables
encoded in aEARM relate to cell survival vs death. Figure 5 shows posterior predictions of the values of
potential predictors of cell survival vs death. The shade region marks the 95% credible interval for the
line marking 50% cell survival probability. Figure 5 (bottom row) provides the posterior distribution of
weight coefficients for each the features encoded in the measurement model. (Larger absolute values of
the weight coefficient indicate greater importance of the feature.) The calibrated measurement model
correctly identified time at maximum Bid truncation as the most important predictor of cell survival; and
the unrelated variable as the least important predictor. Calibration of aEARM to the mixed dataset,
described in the previous section, yielded a measurement model that equivalently predicted identified
time at maximum Bid truncation as the most important predictor of cell survival; and the unrelated
variable as the least important predictor. Calibration of a mechanistic model to categorical phenotype
data, using data-driven measurement models, enabled correct identification of predictors (and potentially
drivers or markers) of categorical phenotypes. The data-driven probabilistic measurement model we
propose in this research was essential to this finding.
326
Discussion
We used data-driven probabilistic measurement models to calibrate, using Bayesian methods, a dynamical
model of biological mechanism to quantitative and nonquantitative data. Our approach allowed us to
estimate posterior predictive regions for the calibrated models and to observe how the size of a dataset, its
different measurement types, and our assumptions about the measurements affect model accuracy and
certainty. Our findings support results from previous studies that suggest nonquantitative data are
valuable for mechanistic modeling efforts[10-13]. For instance, a sufficiently large ordinal dataset can
constrain the posterior predictions of a mechanistic model as much as quantitative dataset. However, we
far more nonquantitative data than is typically generated would be necessary for nonquantitative assays to
match the information content of quantitative assays. In Figure 2B (second row), fourteen ordinal
measurements of tBID – typical of common immunoblot measurements of intracellular biology – did not
constrain the model around an accurate prediction of tBID dynamics. Instead, it took 24x as many ordinal
measurements of tBID (336 measurements) to constrain the mechanistic model of apoptosis as well as the
fluorescence dataset (112 measurements). We also found that datasets that combined categorical
measurements of multiple variables in aEARM out-perform the datasets with measurements of an
individual variable. These findings suggest one could overcome challenges posed by a dearth of
quantitative data by devising experiments that, while nonquantitative, produce a larger number of diverse
measurements that can cover multiple variables.
345
We also found the posterior predictions of our mechanistic model were sensitive to the assumptions, we
encode in the measurement model, about the relationship between measurement and measurand. All
measurements possess uncertain (or unknown) properties, but this uncertainty has a pronounced presence
in nonquantitative measurements. The limitations of nonquantitative data exist because they impose less
informative constraints on models, and this leaves room for biasing assumptions and/or uncertainty.
Uncertainty in nonquantitative measurements drives the, often unacknowledged and implicit, assumptions
about the relationship between measurement and measurand (i.e. between data and model). With the
proposed Bayesian calibration framework, we are able to observe how assumptions about measurement
affected the uncertainty and accuracy of the posterior predictions, in essence providing a measurable
quality of how well the model can make mechanistic predictions. We found that inaccurate *ad hoc*

assumptions about the measurement could produce models that suggested, with a higher degree certainty,
an inaccurate prediction (Figure 4B). This finding suggests that *ad hoc* assumptions about measurements
can lull practitioners into a false sense of confidence about the model and the data. This concern also
motivated Schmiester and co-workers to avoid certain *ad hoc* assumption in their model calibration
approach[11].
361
Having a measurement model whose attributes are determined by data creates an opportunity to learn new
details about the relationship between a measurement and its measurand(s). For instance, could a model
of biological mechanism plus cell phenotype observations data enable identification of cell phenotype
predictors? To explored this, we encoded a small number of suspected cell-fate predictors into our
measurement model and let the data (and the mechanistic model) determine, through model calibration,
their respective contribution to phenotype. In doing so, model calibration using our data-driven
measurement model performed feature selection to correctly identify the most important predictor of cell
death. In general, this kind of measurement model, which relates mechanism to cellular phenotype, can be
used to predict phenotype outcomes and identify potentially informative experimental conditions from *in*
silico perturbation experiments.
372
The present work presents an analysis and a proof-of-concept that can be improved upon in future work.
We chose linear logistic classifiers, as they enable easy formulation of a likelihood function and
application of Bayesian calibration methods, but other probabilistic classifiers could be used. We
constrained our measurement representation to small number of potential features to avoid complications
of high dimensionality to our machine learned measurement model. However, dimensionality reduction
and feature learning (e.g. PCA) can, in theory, be integrated into the measurement model's preprocessing
and/or model calibration workflow. Possibilities for integrating more complex machine learning into
models of measurement will depend on dataset size, computational power, and modeling goals.
381
Our work introduces the concept of measurement models to the mechanistic modeling paradigm.
Measurement models have their origin in social sciences and statistics[29]. They also appear in more
quantitative applications; some recent examples include management, manufacturing, and computer
vision[30-32]. These measurement models can take on more complexity than the examples we provided,
depending on the unique needs of the problems in these areas. The use of measurement models in these
areas is motivated by a desire to define and quantify observations of nuanced and/or subjective
phenomena; and connect those observations to an underlying theory. Biology, being "harder" than social
sciences, but arguably "softer" than physics will straddle the technical domains of both. As a field, we
face the same challenge as these social sciences given that our mechanistic models are situated within a
larger context of explaining nuanced and subjective biological phenomena (e.g. cell-fate, morphology,
physiology and overall health vs. pathology). As practitioners, we never encode *everything* into our
mechanistic models; instead there is always some aspect of the model (or its interpretation) that aims to
connect back to these relevant biological phenomena. This fact ultimately motivates our application of
data-driven probabilistic measurement models in our mechanistic models of intracellular biology.
396
Methods
Extrinsic Apoptosis Reaction Model
We built an abridged extrinsic apoptosis reaction model (aEARM) and trained it using PyDREAM to
normalized fluorescence time-course data[20]. We built this abridged version of EARM to simplify
convergence of Bayesian calibration algorithms and thus make feasible probability-based predictions on
the model-data relationship[20]. The aEARM abstracts detailed mitochondrial reactions from the original
model as two sequential mitochondrial outer membrane pore (MOMP) "signal" activation steps. In
addition, apoptosome formation and effector caspase activation reactions take place in a single activation
step. The aEARM does capture key dynamic characteristics, such as the snap-action delay dynamics of
apoptotic effector molecules that is observed empirically[28]. For this work, three additional non-apoptotic

species were encoded and linked via feedback activation and inactivation loops to test whether our data-
driven measurement model could discriminate between drivers and non-drivers of apoptosis.
(Supplemental Table 2). These additional species and reactions do not interact with any species or
reaction in the aEARM model. The aEARM was encoded using rule-based modeling python package
PySB[33].

412
The aEARM parameters – initial conditions and rate coefficients – were adapted from the previously
developed EARM and/or calibrated to fit available fluorescence data. Initial conditions parameters were
lifted from the previously developed EARM (Supplemental Table 1). Previous work characterized
extrinsic heterogeneity in the expression of proteins and its effect on apoptosis. To model extrinsic
heterogeneity in apoptosis signaling, initial values of certain species (marked in table 1) were sampled
from a log-normal distribution such that its mean equaled that in Supplemental Table 1 and coefficient of
variation was 0.20. Rate coefficients were calibrated (described below) to fit normalized fluorescence
time-course measurements of initiator and effector caspase reporter proteins (IC-RP and EC-RP
respectively).

422
Integrating aEARM Dynamics
Snap-action delay dynamics present challenges for Ordinary Differential Equation (ODE)-based models,
as they feature rapid non-stiff to stiff transitions during integration. For this work we employed the
LSODA integrator (from scipy, via the PySB solver suite), suitable for non-stiff/stiff systems[34]. However,
we found that particularly poorly behaved parameter vectors could prolong integration evaluations in
LSODA. Integrator settings were adjusted for efficiency and accuracy of integration as follows: `mxstep`
(2^20), `atol` (1e-6 default), `rtol` (1e-3 default). The aEARM was integrated over a linear space of 100
time-points spanning 0 to 20160 seconds, in direct correspondence with the fluorescence time-course
data[28]. Additional time-points in the data were obtained via linear interpolation.

432
Measurement Models and Likelihood Functions
Likelihood formulations incorporated a measurement model and resulting distance metric for each
datatype in the study: fluorescence time-course data, synthetic ordinal time-course data, and synthetic
survival vs death binary data for a sample of 400 initial conditions. These likelihood functions were used
to calibrate the models to each dataset. In addition to their use in the likelihood formulation, the
measurement models, were also used to generate synthetic non-quantitative datasets.

439
We first trained the aEARM to normalized fluorescence time-course data for IC-RP and EC-RP, i.e.
fluorescent proxies for substrates of initiator and effector caspase, respectively (i.e. Bid and PARP,
respectively). Consistent with previous work, we defined a likelihood that assume an i.i.d. Gaussian-noise
component $\epsilon \sim N(0, \sigma^2)$ on normalized tBID and cPARP predictions of the aEARM; where σ^2 assumedly
equals the variance of the data[20,35]. This yields a log-likelihood function (Eq. 11) where data the, $\hat{y}$, and
normalized aEARM predictions, y, are compared for each time-point, t, and observable, i (i.e. tBID/IC-
RP and cPARP/EC-RP). The aEARM trained to these fluorescence data served as the starting point in the
synthesis of ordinal, nominal, mixed, etc. datasets, below.

448
449 $$\log \mathcal{L}(\hat{\boldsymbol{y}}|\boldsymbol{\theta}) = \sum_1^N \sum_t^T -1/2\sigma_i(t)^2 \times \left(\hat{y}_i(t) - y_i(t, \boldsymbol{\theta})\right)^2 \qquad (11)$$

450
To train the aEARM to synthetic ordinal time-course data, a measurement model (i.e. that models the
probability of each ordinal category as a function of an aEARM variable) was defined and applied in the
formulation of a likelihood function[36]. The ordinal logistic regression python package, MORD, applies
empirical ordering constraints to Scikit-Learn's logistic regression class; this class then calculates a
probability for each ordinal category[36]. The ordinal logistic model, encoded in MORD, defines ordinal
constraints as a linear function of predicted values of an aEARM variable (e.g. $p\left(y_{tBID} \geq c_j | x_{tBID}\right) =$

$\varphi(\alpha x_{tBID} + \beta_j)$ for aEARM variable, x_{tBID}) where each ordinal constraint, j, is a logistic function $\varphi(z)$
with a different offset coefficient, β_j, but shared slope coefficient, α, for each of the ordinal categories.
Each ordinal constraint function is combined, using the *sequential model* (i.e. the product of the logistic
functions), to give a probability of each ordinal category, $P(y_i(t) = c_j | x_i(t, \boldsymbol{\theta}), \alpha_i, \beta_{i,j})$[37, 38]. These offset
and slope coefficients are additional free parameters to be inferred in the model calibration. For example,
a measurement model with K categories can be defined using $K - 1$ ordinal constraints and will therefore
add a total of K free parameters (i.e. $K - 1$ offset coefficients and 1 shared slope coefficient) to the
model. We also encoded error in our synthetic ordinal data by defining a 5% misclassification probability;
i.e. we assume 95% probability the reported ordinal category, $c_j = \hat{y}$, and 2.5% probability of adjacent
categories, $c_j = \hat{y} \pm 1$, (5% for adjacent terminal categories). We model this by the marginal probability
that the observation classified into the category predicted by the model: $\sum_j^K P(\hat{y}_i(t) | y_i(t) = c_j)$[38].
Together, this yields a log-likelihood function (Eq. 12) where the probability of each category c_j is
calculated for each time-point, t, and observable, i; and applied toward a likelihood of the data $\hat{y}$ given
the model. Where noted, we also trained the aEARM using measurement models with preset fixed
parameters (Supplemental Table 3).

$$\log \mathcal{L}(\hat{\boldsymbol{y}} | \boldsymbol{\theta}, \boldsymbol{\alpha}, \boldsymbol{\beta}) = \sum_i^N \sum_t^T \log \sum_j^K P(\hat{y}_i(t) | y_i(t) = c_j) P(y_i(t) = c_j | x_i(t, \boldsymbol{\theta}), \alpha_i, \beta_{i,j}) \qquad (12)$$

We trained aEARM to synthetic binary (survival vs death) data by incorporating a measurement model
(i.e. logistic model of the probability of each categorical outcome) similar to that used for the ordinal data.
We used the Scikit-Learn logistic regression class to model the probability of a cell-death outcome, $y =$
c_1, as a linear function of features, x_l, derived from the aEARM simulation: $p(y = c_1 | \boldsymbol{x}) =$
$\varphi\left(\alpha\left(\beta + \sum_l^L \beta_l x_l\right)\right)$, where α is a slope term, β is an intercept and β_l are weight coefficients for each of
the L features[39]. Previous studies used *a priori* knowledge and assumptions about which features of a cell-
fate marker's dynamics to associate with the binary outcome. For instance, recent work delineates
necrotic and survival cell fate outcomes using a threshold in the concentration of a known necroptosis
marker (this assumption enabled models of necroptosis in the absence of an established relationship
between the dynamics of the marker and commitment to necroptosis). Roux et al, investigated an
empirical relationship between initiator caspase reporter protein (IC-RP), a fluorescent indicator of
caspase activity or proxy for caspase substrate cleavage, and apoptosis in TRAIL stimulated HeLa cells[18].
They found, instead of concentration, the maximum rate of change in IC-RP and the time when that rate
of change maximized better predicted the apoptosis-survival decision[18]. The features we use in our study
are based on findings by Roux et al[18]. The features are derived from aEARM simulated tBID dynamics,
$x_{tBID}(t, \boldsymbol{\theta})$: time at maximum rate of change, and log-maximum rate of change. To test the measurement
model's ability to discriminate between predictors and non-predictors of cell death, we encoded an
additional feature: the concentration of an unrelated non-apoptotic species (USM2 in Table 2) when bid
truncation maximizes. Together this totals three features. We interpret each observation in the dataset as
an independent Bernoulli random variable. Each cell death vs survival observation is compared with these
three features, $x_{l,m}$, extracted from an aEARM trajectory that was simulated from a unique vector of
initial conditions. There were 400 observations; 2 sets of 200 observations corresponding to 10 and
50ng/mL initial ligand concentration. Together, this yields a log-likelihood function (Eq. 13) where each,
m, of the M aEARM simulated trajectories corresponds to an observation $\hat{y}_m$. Given the definitiveness of
observed surviving vs dead outcomes, we considered the chance of misclassification to be zero (i.e.
$P(\hat{y}_m | y_m = c_1) = 0$ when $\hat{y}_m \neq c_1$).

$$\log \mathcal{L}(\hat{\boldsymbol{y}} | \boldsymbol{\theta}, \boldsymbol{\alpha}, \boldsymbol{\beta}) = \sum_m^M P(\hat{y}_m | y_m = c_1) \log \varphi\left(\alpha\left(\beta + \sum_l^L \beta_l x_{l,m}\right)\right)$$
$$+ \sum_m^M (1 - P(\hat{y}_m | y_m = c_1)) \log\left[1 - \varphi\left(\alpha\left(\beta + \sum_l^L \beta_l x_{l,m}\right)\right)\right] \qquad (13)$$

504
Generating Synthetic Datasets
The calibration of aEARM to IC-RP and EC-RP fluorescence time-course data provided an optimally fit
vector of rate coefficient parameters, which served as the "ground truth" parameter vector in the synthesis
of the nonquantitative datasets (Supplemental Table 5). These parameters were applied to aEARM, and
the resulting aEARM was used simulate time-courses for variables to be indicated in the nonquantitative
data: truncated BID (tBID), initiator caspase localization to the death inducing signaling complex (IC-
DISC), and cleaved PARP (cPARP).
512
These time-courses were converted to ordinal time-course datasets. The effective bit resolution of a
measurement technology dictates how many unique values it can distinguish[40]. The total number of
ordinal categories, K, was set such that resulting dataset had less than 70% of the effective bit resolution,
EBR, (Eq. 14) of the IC-RP of EC-RP data. The signal to noise ratio, SNR, (Eq. 15) assumes the data, d,
were subject to Gaussian noise and a 0.10 misclassification rate between adjacent values; modeled as the
0.95 quantile of a unit normal distribution[40]. Therefore, the number of ordinal categories were 5 and 4 for
tBID and cPARP, respectively. The number of ordinal categories for IC-DISC were arbitrarily set to 4.
Arbitrary values of slope and offset coefficients (Supplemental Table 3) were designated "ground truth"
and applied to ordinal measurement models (described above). The resulting measurement models map
the values in the aEARM simulated time-courses to probabilities of each ordinal category. These
probabilities were used to simulate random class assignments for synthetic ordinal datasets (see Fig 2).
The aEARM was trained to time-course ordinal values of tBID and cPARP or time-course ordinal values
of IC-DISC and nominal data described below.
526
527 $$K \leq 0.7 \times 2^{EBR}, \quad EBR = -(SNR + 1.76)/6.02 \tag{14}$$
528 $$SNR = 20 \log_{10} q_{0.95} \text{rms}(d)/(\max d - \min d) \tag{15}$$
529
To generate synthetic nominal (binary cell survival vs death) data, two heterogeneous populations of 200
aEARM tBID (and an unrelated non-apoptotic species, USM2) trajectories were simulated from ground
truth parameters. The populations had distinct initial ligand concentrations (10 or 50 ng/mL).
Heterogeneity was modeled by a log-normal random sample of certain initial conditions (described
above). These time-courses were preprocessed to yield values of the features encoded in nominal
measurement model, above. This measurement model (which was encoded with preset "ground truth"
values of slope, intercept and weight coefficients – See Supplemental Table 4) maps these features to
probabilities of the binary outcomes. These probabilities were used to simulate random class assignments
for synthetic nominal datasets (Fig 3b).
539
540 To generate a synthetic distribution of times at which Bid truncation was half-maximal, two heterogenous
541 populations of 200 aEARM tBID time-courses, corresponding to 10 and 50ng/mL initial ligand
542 concentrations, were simulated from ground truth parameters (as above). Time at half-maximal tBID was
543 calculated via linear interpolation and rounded to the nearest 3-minute time-point (i.e. to reflect temporal
544 resolution of common time-series intracellular experiments) (Fig 3a).
545
Model Calibration via Bayesian Inference
The aEARM was calibrated using DREAM(ZS) algorithm for all datasets[41]. Rate parameters in aEARM
were given independent log-normal distribution prior probability functions with a location equal to the
ground-truth parameter vector and a scale term of 1.5. The nominal (cell death vs survival) dataset
features a heterogeneous population of values. We modeled this heterogeneity with a random sample of
initial conditions (described above). This random sample was shifted and scaled according to inferred
values of the model mean and variance. The mean (if estimated) was given a log-normal distribution prior
probability function with a location equal to ground-truth and a scale term of 1.5. The extrinsic noise (or

variance) was given inverse gamma distribution with a and b terms such that the resulting coefficient of
variation had a prior mean and standard deviation of 0.20 and 0.015 respectively.
556
Prior probability functions were also applied to the measurement models' free-parameters. To in encode
empirical ordering constraints on the ordinal measurement model, the slope terms, α, were greater than
zero; they were given independent exponential distribution prior probability functions (with location of
0.0 and scale of 100.0). To insure monotonically increasing offset terms, each offset, β_j, was defined by
the distance, θ_j, from its preceding offset term; $\beta_j = \beta_{j-1} + \theta_j$. The first offset, $\beta_0 = \theta_0$, and
subsequent distance, θ_j, terms were given independent exponential distribution prior probability functions
(with location of 0.0 and scale of 0.25). We explored the effect of increasingly biased priors on the
ordinal measurement model parameters. Where noted, the slope terms, α, were given increasingly
constrained independent prior probability functions: uniform (0.0 - 100.0 bounds), Cauchy (50.0 location
and 10.0 scale) and Cauchy (50.0 location and 1.0 scale). The offset, β_0, and distance, θ_j, terms were
similarly given independent uniform (0.0 - 1.0 bounds), Cauchy (0.2 location and 0.05 scale) and Cauchy
(0.2 location and 0.005 scale) distribution prior probability functions. Parameters for the measurement
model were given independent Laplace distribution prior probability functions with a location of 0.0 and
scale of 1.0 for the slope, α, and 0.10 for the intercept and weighting coefficients, β and β_l.
571
The likelihood functions were described above. Additional settings applied to the DREAM(ZS) algorithm
were: number of chains (4) number of crossover points (nCR=25), adaptive gamma (TRUE), probability
of gamma=1 (p_gamma_unity=0.10), gamma term resolution (gamma_levels=8). A burn-in period
wherein crossover weights are adapted was set to 50,000-step burn-in for ordinal datasets and 100,000+
step burn-in. The calibration algorithm continued until it reached the stopping criterion: when the
Gelman-Rubin metric (calculated on the latter 50% of the traces) was less than or equal to 1.2 for all free-
parameters in the model; at which point the parameter traces were considered converged[32]. Gelman-Rubin
metrics for each calibration are listed in Supplemental Table 6. Model calibrations were run on a x64 Intel
with 32 total CPU threads (256GB RAM) and x64 AMD with 256 threads (1024GB RAM). Run times
varied widely given the stochastic nature of the optimization algorithm but were typically one to seven
days for simple model calibrations. Random samples of 1000 parameter were taken from the latter 50% of
the resulting parameter-traces were used in subsequent analyses. Source code for the model calibrations
as well as code for downloading the resulting parameter-traces is found at https://github.com/LoLab-
VU/Opt2Q.
586
Model Predictions
We simulated the equal-tailed 95% credible region of the posterior predictions of aEARM via samples of
the model parameters posterior distribution. This was done by randomly generating 1000 parameter sets
sub-sampled from the posterior sample of parameters generated via PyDREAM. For each parameter set,
tBID time-courses (and/or cPARP, IC-DISC) were simulated from aEARM. The 95% credible region of
the predictions was then determined via 0.025 and 0.975 quantile bounds on the tBID (or other variables)
values for each time-point in the simulated time-course. The area bounded in the 95% posterior credible
interval was determined by summing the difference between the 0.025 and 0.975 quantile bounds across
100 equally spaced time points on the trajectory. The 95% posterior credible intervals on the
measurement model predictions were similarly the described by calculating 0.025 and 0.975 quantile
boundaries on the predictions of the measurement model parameterized via 1000 parameter set samples
from a posterior. This includes the posterior probability distributions of the feature coefficients encoded
in the nominal measurement model. To model predictions of the nominal dataset, however, we randomly
generated 100 parameter sets via sub-sampling of the posterior parameter distribution. For each parameter
set, we simulate tBID dynamics from the set of 400 initial conditions as described above; from that we
compute maximum BID truncation rate and time at maximum BID truncation rate for each of the 400

trajectories. The 0.05 contour of the KDE of the resulting 400 values of maximum BID truncation rate
and time at maximum BID truncation rate was plotted for each of the 100 parameter sets.
605
<u>Figure Legends:</u>
Figure 1: Measurements encountered in cell biology. *Nominal* measurements (top) can help
understand intracellular signaling activity as it relates to broader cellular and physiological
behaviors. With cellular phenotype markers or drivers, we can attribute different nominal
observations to distinct (intra)cellular states. This is often modeled as in Eq. 1, where each
observable measurement (y_{obs}) corresponds to a given state. *Ordinal* measurements (second
row) can be graded cellular phenotype observations (e.g., cell state transitions in cellular
differentiation) or measurements of intracellular contents where noise can obscure intervals
between values (e.g. Western Blots). Ordinal measurements imply a relative ordering of
quantities along an axis but not their relative distance; i.e. we may know $y_i \leq y_j$ without
knowing $y_i - y_j$ (Eq. 2). Semi-quantitative measurements (third row) typically arise when an
investigation has progress toward a more quantitative understanding of the intracellular
signaling. Semi-quantitative measurements (e.g. fluorescent intracellular markers) imply a
quantitative relationship but a scaling function is necessary for true quantitation (Eq. 3). True
quantitative measurements (bottom row) do not imply assumptions and the quantity measured
can be used directly in the model (Eq. 4), such as mass-spectrometry protein concentration
measurements. As shown schematically on the left triangle schematic, ordinal and nominal
measurements are more abundant in biology due to their ease of production but are more difficult
to interpret, whereas semiquantitative and quantitative measurements are less common but have
a more straightforward interpretation.
626
Figure 2. Predicted Bid truncation dynamics of aEARM trained to different sized ordinal
datasets. Multiple Bayesian optimizations were run on the A.) abridged Extrinsic Apoptosis
Reaction Model (aEARM) using different sized ordinal dataset to probe how dataset size
influenced certainty of aEARM predictions. B.) Initiator caspase reporter (IC-RP) fluorescence
time-course measurements (at 180s intervals) were measured (top left) as a proxy for truncated
tBid (data from Albeck et al[28]). The plot shows the mean (dotted line) +/- 1 standard deviation
(shaded region) for each time point. The 95% credible region (top right) of posterior predictions
(shaded region) for tBID concentration in aEARM, calibrated to fluorescence measurements of
IC-RP and EC-RP (See also supplemental figure 3). The median prediction (solid-line) and true
(dotted line) tBID concentration trajectories are shown. In the next four rows (from top to
bottom), Ordinal measurements of tBID (left) at every 1500, 300, 180 and 60s interval,
respectively. The 95% credible region of predictions (shaded region), median prediction (solid
line) and true (dotted line) tBID dynamics for aEARM calibrated to ordinal measurements of
tBID and cPARP occurring at every 1500, 300, 180 and 60s timepoint are plotted in plots on the
right. The plots for cPARP ordinal measurements and predictions are found in Supplemental
Figure 3.
643
Figure 3. Predicted Bid truncation dynamics of aEARM trained to nominal and ordinal
datasets. A.) Nominal cell death (x) vs survival (o) outcomes data for cells treated with 10ng/mL
(orange) and 50ng/mL (grey) of TRAIL and with known relative values of DISC formation (x-
axis). The 95% credible region (shaded region) of posterior predictions of tBID dynamics of
aEARM calibrated to nominal data (right plot). The median prediction (solid-line) and true

(dotted line) are also plotted. B.) Ordinal measurements for initiator caspase-DISC colocalization
(IC-DISC) at 300s intervals (left plot). The 95% credible region (shaded region) of posterior
predictions of tBID dynamics of aEARM calibrated to ordinal IC-DISC data (right plot), and C.)
of aEARM calibrated to nominal *and* ordinal IC-DISC data. The median prediction (solid-line)
and true (dotted line) were also plotted. The fit to IC-DISC data are shown in Supplemental
Figure 9.
655
Figure 4: Predicted Bid truncation dynamics of aEARM trained to ordinal data using
different measurement model parameterizations. A.) and B.) The 95% credible region of
posterior predictions (shaded region) of tBID dynamics for aEARM calibrated to ordinal
measurements two fixed parameterizations for the measurement model (see Supplemental Table
3). The adjacent panels plot the measurement models predicted probability of class membership
(x-axis) as a function of normalized tBID concentration (y-axis). C.) D.) and E.) The 95%
credible region of posterior predictions (shaded region) of tBID dynamics of aEARM calibrated
to ordinal measurements uniform, Cauchy (scale=0.05) and Cauchy (scale=0.005) prior
distributions for the parameterizations for the measurement model, respectively. In each, the
median prediction (solid line) and true (dotted line) tBID dynamics are also shown. The adjacent
panels give the 95% credible region of posterior predictions of the probability of class
membership (x-axis) as a function of normalized tBID concentration (y-axis). Four
accompanying plots show the prior (blue), posterior (orange) and true (dashed line) values of
measurement model parameters.
670
Figure 5: Measurement model predicts features of cell death vs. survival using aEARM
calibrated to cell death datasets.
Normalized predicted values of the features used in the cell death vs. survival measurement
model – the x-axis is the maximum Bid truncation rate, and the y-axis is the time at maximum
Bid truncation rate (top row) or an unrelated non-apoptotic signal (middle row) – for
corresponding to observed cell death (x) and survival (o) outcomes. These feature values are
modeled by aEARM parameterized by 100 parameter vectors randomly drawn from the
posterior; for each parameterization, 5 out of the total simulated population of 400 cells were
plotted. The grey and orange curves, in these plots, are 0.05 contours for the estimated density of
simulated cell populations produced for each of the 100 parameter vectors – grey and orange
correspond to 50 and 10ng/ml TRAIL treatments, respectively. The measurement model predicts
a probability of cell death vs survival based on simulated values of the above features. The lower
right region of the plots in the top row. (i.e., early maximization of Bid truncation and higher
maximal Bid truncation rates) is associated with higher probability of cell death. The shaded
region is the 95% credible region of the posterior prediction of the line marking 50% probability
of cell death or survival. The black and blue lines are the median predicted and true 50%
probability lines, respectively. The bottom row plots the posterior distributions of the weight for
each feature (i.e. the product of the slope term and feature coefficient encoded in the
measurement model): maximum Bid truncation rate (green), time at maximum Bid truncation
(orange) and unrelated non-apoptotic signal (blue). Plots in the left column are predictions of
aEARM calibrated to the cell death vs. survival dataset. Plots right column were those of
aEARM calibrated to the cell death vs survival + ordinal IC-DISC combined dataset.
693

Box 1: Objective functions and the role of a measurement model. Mechanistic models of
biological processes are typically encoded as systems of (ordinary) differential equations (Eq. 5).
Model calibration relies on an objective function (Eq. 7) -- or in a Bayesian setting, a likelihood
function (Eq. 8) -- quantifies the degree of dissimilarity or similarity between model variables
and corresponding measurements. Note, the objective or likelihood function uses measurement
model (Eq. 6) which converts modeled variables $x(t)$ to a quantity $y(t_i, \theta)$ that can be
compared to data $\hat{y}(t_i)$. In physics and engineering, where measurements are typically
quantitative, the measurement model can be neglected. For nonquantitative measurements and
observations, the measurement model takes more consideration.
703
Box 2: Model calibration with the data-driven probabilistic measurement model. A.) The
measurement model is an intermediate step between the mechanistic model and likelihood
function of the measurement/observations. It receives variables from the mechanistic model and
transforms for use in the likelihood function. This probabilistic machine-learning measurement
model estimates *probabilities* of class membership as a function of the mechanistic model
variables (Eq. 9). This measurement model is data-driven in that it contains free-parameters that
are evaluated via the likelihood function (Eq. 10). B.) The measurement model uses values of
e.g. tBID (grey curve) to estimate the probability of membership in an ordinal category (dotted
data). C.) Plots a posterior ensemble of estimates of the probability of membership into 5 ordinal
categories (x-axis) as a function of normalized tBID concentration (y-axis). The plot shows the
median (solid line) and 95% credible region (shaded region) of the predictions (Category colors
match data plotted in B). **Algorithm)** The mechanistic model and measurement model are
calibrated simultaneously using Bayesian sampling methods through stepwise operations as
described in each numeral.
718
719
720
721

References:

1. Woltosz, Walter S. "If we designed airplanes like we design drugs…." *Journal of computer-aided molecular design* 26.1 (2012): 159-163.
2. Butcher, E. C. "Can cell systems biology rescue drug discovery?." *Systems Biology*. Springer, Berlin, Heidelberg, 2007. 153-172.
3. Hagan, T., & Pulendran, B. (2018). Will systems biology deliver its promise and contribute to the development of new or improved vaccines? From data to understanding through systems biology. *Cold Spring Harbor perspectives in biology*, *10*(8), a028894.
4. Kitano, H. (2001). *Foundations of systems biology*. The MIT Press Cambridge, Massachusetts London, England.
5. Kitano, H. (2002). Computational systems biology. *Nature*, *420*(6912), 206-210.
6. Green, D. R. (2019). The coming decade of cell death research: five riddles. *Cell*, *177*(5), 1094-1107
7. Villaverde, A. F., & Banga, J. R. (2014). Reverse engineering and identification in systems biology: strategies, perspectives and challenges. *Journal of the Royal Society Interface*, *11*(91), 20130505.
8. Villaverde, A. F. (2019). Observability and structural identifiability of nonlinear biological systems. *Complexity*, *2019*.
9. Macklin, P. (2019). Key challenges facing data-driven multicellular systems biology. *Gigascience*, *8*(10), giz127.
10. Pargett, M., Rundell, A. E., Buzzard, G. T., & Umulis, D. M. (2014). Model-based analysis for qualitative data: an application in drosophila germline stem cell regulation. *PLoS Comput Biol*, *10*(3), e1003498.
11. Schmiester, L., Weindl, D., & Hasenauer, J. (2020). Parameterization of mechanistic models from qualitative data using an efficient optimal scaling approach. *Journal of Mathematical Biology*, *81*(2), 603-623.
12. Mitra, E. D., & Hlavacek, W. S. (2020). Bayesian Inference Using Qualitative Observations of Underlying Continuous Variables. *Bioinformatics (Oxford, England)*, *36*(10), 3177-3184.
13. Mitra, E. D., Dias, R., Posner, R. G., & Hlavacek, W. S. (2018). Using both qualitative and quantitative data in parameter identification for systems biology models. *Nature communications*, *9*(1), 1-8.
14. Chen KC, Csikasz-Nagy A, Gyorffy B, Val J, Novak B, Tyson JJ:Kinetic analysis of a molecular model of the budding yeastcell cycle.Mol Biol Cell2000,11:369–391.59.
15. Chen KC, Calzone L, Csikasz-Nagy A, Cross FR, Novak B,Tyson JJ:Integrative analysis of cell cycle control in buddingyeast.Mol Biol Cell2004,15:3841–3862.
16. Houle, D., Pélabon, C., Wagner, G. P., & Hansen, T. F. (2011). Measurement and meaning in biology. *The quarterly review of biology*, *86*(1), 3-34.
17. Solano-Gálvez, S. G., Abadi-Chiriti, J., Gutiérrez-Velez, L., Rodríguez-Puente, E., Konstat-Korzenny, E., Álvarez-Hernández, D. A., ... & Vázquez-López, R. (2018). Apoptosis: activation and inhibition in health and disease. *Medical Sciences*, *6*(3), 54.
18. Roux, J., Hafner, M., Bandara, S., Sims, J. J., Hudson, H., Chai, D., & Sorger, P. K. (2015). Fractional killing arises from cell-to-cell variability in overcoming a caspase activity threshold. *Molecular systems biology*, *11*(5), 803.
19. Kuwana, T., Smith, J. J., Muzio, M., Dixit, V., Newmeyer, D. D., & Kornbluth, S. (1998). Apoptosis induction by caspase-8 is amplified through the mitochondrial release of cytochrome c. *Journal of Biological Chemistry*, *273*(26), 16589-16594.
20. Ortega, O. O., Wilson, B. A., Pino, J. C., Irvin, M. W., Ildefonso, G. V., Garbett, S. P., & Lopez, C. F. (2021). Probability-based mechanisms in biological networks with parameter uncertainty. *bioRxiv*.

21. Flusberg, D. A., Roux, J., Spencer, S. L., & Sorger, P. K. (2013). Cells surviving fractional killing by TRAIL exhibit transient but sustainable resistance and inflammatory phenotypes. *Molecular biology of the cell*, *24*(14), 2186-2200.

22. Laussmann, M. A., Passante, E., Hellwig, C. T., Tomiczek, B., Flanagan, L., Prehn, J. H., ... & Rehm, M. (2012). Proteasome inhibition can impair caspase-8 activation upon submaximal stimulation of apoptotic tumor necrosis factor-related apoptosis inducing ligand (TRAIL) signaling. *Journal of Biological Chemistry*, *287*(18), 14402-14411.

23. Corazza, N., Kassahn, D., Jakob, S., Badmann, A., & Brunner, T. (2009). TRAIL-induced apoptosis. *Annals of the New York Academy of Sciences*, *1171*(1), 50.

24. Elmore, S. (2007). Apoptosis: a review of programmed cell death. *Toxicologic pathology*, *35*(4), 495-516.

25. Kantari, C., & Walczak, H. (2011). Caspase-8 and bid: caught in the act between death receptors and mitochondria. *Biochimica et Biophysica Acta (BBA)-Molecular Cell Research*, *1813*(4), 558-563.

26. Özören, N., & El-Deiry, W. S. (2002). Defining characteristics of Types I and II apoptotic cells in response to TRAIL. *Neoplasia*, *4*(6), 551-557.

27. Kaufmann, S. H., Desnoyers, S., Ottaviano, Y., Davidson, N. E., & Poirier, G. G. (1993). Specific proteolytic cleavage of poly (ADP-ribose) polymerase: an early marker of chemotherapy-induced apoptosis. *Cancer research*, *53*(17), 3976-3985.

28. Albeck, J. G., Burke, J. M., Aldridge, B. B., Zhang, M., Lauffenburger, D. A., & Sorger, P. K. (2008). Quantitative analysis of pathways controlling extrinsic apoptosis in single cells. *Molecular cell*, *30*(1), 11-25.

29. Sajtos, L., & Magyar, B. (2016). Auxiliary theories as translation mechanisms for measurement model specification. *Journal of Business Research*, *69*(8), 3186-3191.

30. Zubair, M. U., & Zhang, X. (2020). Hybrid Performance-Measurement Model of Elevators. *Journal of Performance of Constructed Facilities*, *34*(2), 04020013.

31. Kamble, S. S., Gunasekaran, A., Ghadge, A., & Raut, R. (2020). A performance measurement system for industry 4.0 enabled smart manufacturing system in SMMEs-A review and empirical investigation. *International Journal of Production Economics*, *229*, 107853.

32. Xia, Y., Wang, P., Berntorp, K., Boufounos, P., Orlik, P., Svensson, L., & Granström, K. (2020, September). Extended Object Tracking with Automotive Radar Using Learned Structural Measurement Model. In *2020 IEEE Radar Conference (RadarConf20)* (pp. 1-6). IEEE.

33. Lopez, C. F., Muhlich, J. L., Bachman, J. A., & Sorger, P. K. (2013). Programming biological models in Python using PySB. *Molecular systems biology*, *9*(1), 646.

34. Hindmarsh, A. C., & Petzold, L. R. (2005). LSODA, ordinary differential equation solver for stiff or non-stiff system.

35. Eydgahi, H., Chen, W. W., Muhlich, J. L., Vitkup, D., Tsitsiklis, J. N., & Sorger, P. K. (2013). Properties of cell death models calibrated and compared using Bayesian approaches. *Molecular systems biology*, *9*(1), 644.

36. Antoniuk, K., Franc, V., & Hlaváč, V. (2013, September). Mord: Multi-class classifier for ordinal regression. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases* (pp. 96-111). Springer, Berlin, Heidelberg.

37. Bürkner, P. C., & Vuorre, M. (2019). Ordinal regression models in psychology: A tutorial. *Advances in Methods and Practices in Psychological Science*, *2*(1), 77-101.

38. Poon, W. Y., & Wang, H. B. (2010). Analysis of ordinal categorical data with misclassification. *British Journal of Mathematical and Statistical Psychology*, *63*(1), 17-42.

39. Hackeling, G. (2017). *Mastering Machine Learning with scikit-learn*. Packt Publishing Ltd.

40. Ziemer, R. E., Tranter, W. H., & Fannin, D. R. (1984). Signals and systems: continous and discrete.

41. Shockley, E. M., Vrugt, J. A., & Lopez, C. F. (2018). PyDREAM: high-dimensional parameter inference for biological models in python. *Bioinformatics*, *34*(4), 695-697.

822
823
824
825

Figure 1

Nominal
• e.g. cell staining.
• Early biomolecular investigation.
• Pathway features.
• Identify phenotype drivers.
• Difficult to characterize complex
  mechanisms.

$$y_{obs} \in \{0, 1, ... J\}$$
$$y_{obs,i} \neq y_{obs,j} \rightarrow y_i \neq y_j \quad (1)$$

Ordinal
• e.g. Western Blot / Immunoblot
• Reveals mechanistic details.
• Identify features and complexity
  in signaling pathways.
• Not quantitative.

$$y_{obs} \in \{0, 1, ... J\}$$
$$y_{obs,i} \lessapprox y_{obs,j} \rightarrow y_i \leq y_j \quad (2)$$

Semi-quantitative
• e.g. molecular fluorescence
  reporters.
• Direct process measurement.
• Clear connection between
  mechanistic models and data.
• Requires mathematical
  manipulation for use.

$$y_{obs} = f_M(y, c) \quad (3)$$

Quantitative
• e.g. absolute quantification mass
  spectrometry
• Can use in mechanistic models
  directly.
• Difficult to obtain.

$$y_{obs} = y \quad (4)$$

Figure 2

Figure 3

A. Nominal data

B. Ordinal data

C. Nominal and ordinal data

Figure 4

Figure 5

Box 1

Implicit measurement model
Useful for quantitative and semiquantitative measurements. Can be an overlooked source of bias for non-quantitative measurements.

Explicit measurement model
Enable use of a wider range of measurements across multiple data types. Can be formulated to avoid measurement interpretation bias.

Mechanistic Models of dynamic cellular processes are often *encoded* as systems of ordinary differential equations (eq. 5). Models are typically calibrated to one or many observables.

$$\boldsymbol{x}(t) = f(t, \boldsymbol{\theta}). \quad (5)$$

The **Measurement Model** translates measurements and observations into mechanistic model variables. The measurement model encodes understanding of the measurement as it relates to mechanistic knowledge. The measurement model is most often implied (left box), which can introduce significant biases for non-quantitative measurements. An explicit, adaptive measurement model (right box) can significantly alleviate this potential bias.

$$y(t_i, \boldsymbol{\theta}) = f_M\big(\boldsymbol{x}(t)\big) \quad (6)$$

Calibration minimizes the distance(d) between observed data ($\hat{\boldsymbol{y}}$) and related model predictions. Bayesian methods maximize likelihood functions $\log \mathcal{L}(\hat{\boldsymbol{y}}|\boldsymbol{\theta})$ to optimize this distance. Calibration can include a measurement model to minimize bias between measurements/observations and the model measurands.

$$d = \sum_{i=1}^{n} w_i\big(\hat{y}(t_i) - y(t_i, \boldsymbol{\theta})\big)^2 \quad (7)$$

$$\log \mathcal{L}(\hat{\boldsymbol{y}}|\boldsymbol{\theta}) = c + \sum_{i=1}^{n} \frac{-1}{2\sigma_i^2}\big(\hat{y}(t_i) - y(t_i, \boldsymbol{\theta})\big)^2 \quad (8)$$

Box 2

A.

Bayesian MCMC Sampler

B.

C.

Algorithm

1. Draw dynamical and measurement model parameters, $\boldsymbol{\theta}$ and $\boldsymbol{\theta}_M$, from their respective priors.
2. Simulate the dynamics $\boldsymbol{x}(t) = f(t, \boldsymbol{\theta})$ using a numerical solver.
3. Predict the probability of each of the measurement categories using the measurement model.

$$\{P(y_i = c_1|x_i(t)), P(y_i = c_2|x_i(t)), \dots P(y_i = c_K|x_i(t))\} = f_M(\boldsymbol{\theta}_M, x_i(t)) \tag{9}$$

4. Evaluate the Likelihood.

$$P(\hat{\boldsymbol{y}}|\boldsymbol{\theta}, \boldsymbol{\theta}_M)$$
$$= \prod_{i=1}^{N} \sum_{j=1}^{K} P(\hat{y}_i|y_i = c_j) P(y_i = c_j|x_i(t)) \tag{10}$$

5. Use MCMC-MH sampling to draw new $\boldsymbol{\theta}$ and $\boldsymbol{\theta}_M$ from their respective priors.
6. Repeat 2-5 until convergence criteria are met.