12 **An enhanced inverted encoding model for neural reconstructions**

13 Paul S. Scotti[1], Jiageng Chen[2], & Julie D. Golomb[2]

14
15 1. Princeton Neuroscience Institute, Princeton University, Princeton, NJ, USA
16 2. Department of Psychology, The Ohio State University, Columbus, Ohio, USA
Please address correspondence to:
Paul S. Scotti
Princeton University
Princeton Neuroscience Institute
Washington Road
Princeton, NJ 08544
Email: scottibrain@gmail.com
35
36
37 Abstract word count: 146
38 Main text word count: 4,995
39 Figures: 4
40

Abstract

Here we present a more interpretable and versatile approach for reconstructing the

contents of perception, attention, and memory from neuroimaging data. Our enhanced

inverted encoding model (eIEM) incorporates theoretical and methodological

improvements including proper accounting of population-level tuning functions and a

trial-by-trial prediction error-based metric where reconstruction quality is measured in

meaningful units. Added functionality and improved flexibility is further gained via

eIEM's novel goodness-of-fit feature: for trial-by-trial reconstructions, goodness-of-fits

are obtained independently (non-circularly) to prediction error and can be applied to any

IEM procedure or decoding metric, resulting in improved reconstruction quality and

brain-behavior correlations, and more creative applications. We validate eIEM from

methodological principles, simulated neuroimaging datasets, and three pre-existing

fMRI datasets spanning perception, attention, and working memory. Notably, eIEM is

easy to apply and broadly accessible – our Python package

(https://pypi.org/project/inverted-encoding) implements eIEM in one line of code – and is

easily modifiable to compare performance metrics and/or scale up to more complex

models.

1. Introduction

A mental representation can be defined as the "systematic relationship between

features of the natural world and the activity of neurons in the brain"[1]. An increasingly

common approach to study mental representations using neuroimaging data is to

employ encoding models, which describe this relationship computationally, typically by

reducing the complexity of the input data with a set of functions that, when combined,

roughly approximate the neural signal.

Encoding and decoding models (aka voxelwise modeling or stimulus-model

based modeling) have become a standard method for investigating neural

representational spaces and predicting stimulus-specific information from brain activity[2–

4]. The key advantages of such models over other computational approaches such as

multivariate pattern classification or representational similarity analysis are typically

touted as the following: (1) Encoding models can take inspiration from single-unit

physiology by consisting of tuning functions in stimulus space (aka feature space),

allowing both the maximally receptive feature and the precision/sensitivity of the tuning

to be estimated across a population of neurons. (2) Encoding models (which transform

presented stimuli into predicted brain activity) are easily inverted into decoding models

(which transform observed brain activity into predicted stimuli), and this process can be

applied to a wide range of stimuli, including oriented Gabor patches[5,6], colors[7], acoustic

musical features[8], and human faces[9]. (3) The decoding model can predict, or

reconstruct, novel stimuli or experimental conditions not used in the training of the

model, with reconstructions offering interpretational advantages beyond classification-

based decoding by yielding measures of activity across the full stimulus space and

facilitating research questions exploring representational schemes for brain regions of

interest[4,7].

The inverted encoding model (IEM), sometimes also referred to as forward

modeling, is one example of an encoding and decoding model that has quickly risen to

prominence in the cognitive neuroscience community (see Supplemental Figure 1)[10–36].

The basic idea behind IEMs is illustrated in Figure 1A. First, an encoding model is

trained to associate patterns of brain activity with specific stimuli. The model uses

simple linear regression and a basis set representing the hypothesized population-level

tuning functions, consisting of several channels that are modeled as cosines (or von

Mises functions) equally separated across stimulus space (e.g., orientation, color,

spatial location). Each channel in the basis set can be assigned a weight per voxel (we

adopt fMRI nomenclature here, but IEMs can be applied to any modality like EEG,

MEG, etc.) and hence a model can be trained to predict the activity of each voxel using

the weights of each channel as predictors (i.e., the regressors in a linear regression).

Then, this trained encoder is inverted such that it becomes a decoder capable of

reconstructing a trial's stimulus when provided with a novel set of voxel activations (see

Methods for mathematical implementation).

IEM is popular due to its simplicity, robust performance, and grounding in single-

unit physiology principles. Over recent years, several variations, improvements, and

additional features have been proposed for IEMs, resulting in various approaches and

evaluation metrics (Supplemental Figure 1). This malleability is both an advantage and

a challenge of IEM, as there is sometimes ambiguity over which metric is best,

particularly for less experienced users. Moreover, as discussed more below, certain

implementations of IEM can produce misleading or difficult to interpret results, and do

not account for the shape of the basis channels (as recently pointed out in some high-

profile debates in the literature[37–40]). While this is not to suggest that previous papers

have made incorrect scientific interpretations, there are several aspects of IEM that can

be improved upon.

Here we propose a variation of IEM which improves the interpretability of

stimulus reconstructions, addresses some key issues inherent in the IEM procedure as

commonly applied, and provides trial-by-trial stimulus predictions and goodness-of-fit

estimates. Our proposed approach serves two main functions: first, it can be thought of

as a set of recommended best-practices based on theoretical principles, and second, it

offers some novel enhancements to the IEM procedure, including a focus on trial-by-trial

predictions that includes a built-in measure of uncertainty. For simplicity and ease of

communication, we refer to this approach as "enhanced inverted encoding modeling"

(eIEM). In this manuscript we provide theoretical justification for each of the

recommended aspects of eIEM, along with real and simulated data confirming that

eIEM produces results at least as good as – and in several cases better than – a

commonly implemented alternative. We also share a publicly available Python package

that can apply eIEM to neuroimaging data in a single line of code. While advanced

researchers may have reason for adopting some aspects of eIEM without others (using

either our code or their own), more novice users may find this pre-packaged set of

recommendations and enhanced functionality particularly useful.

Figure 1 depicts the eIEM procedure. In essence, eIEM is a combination of

several modifications and improvements (some previously employed, some novel).

First, with eIEM, the core encoder and decoder steps described above (i.e., least-

squares linear regression for estimating channel weights and responses, using a basis

set of hypothesized population-level tuning functions) remain the same, but the

encoding model is repeatedly fitted with slightly shifted basis sets such that subsequent

reconstructions are in stimulus space rather than channel space. This "iterative shifting"

of the basis set has been employed in a few previous papers[41–43], but it is not yet

common practice. Iterative shifting allows for more accurate reconstructions spanning

the full stimulus space (allowing the remaining eIEM steps to be optimally applied), and

aids more generally in reducing potential interpretation flaws and bias associated with

impoverished basis sets, as illustrated and explained in Supplemental Figure 2. We also

include a Jupyter notebook that illustrates the advantages of iterative shifting across

various simulated neuroimaging data on OSF (https://osf.io/vf3n6).

More critically, the core difference of eIEM is that we analyze reconstructions at

the trial-by-trial level, using a procedure that can obtain stimulus predictions, prediction

error, and goodness-of-fits for each trial. In contrast, most existing implementations of

IEM typically employ an align-and-average approach (Figure 1B), where each trial's

reconstruction is circularly shifted along the x-axis such that it is centered on the

"correct" channel (closest to the ground truth stimulus feature), and then these aligned

reconstructions are averaged together to result in a single reconstruction, typically

quantified using metrics such as slope, amplitude, etc. As we show in the Results, this

align-and-average approach is susceptible to information loss, outlier bias, and

interpretation issues.

Figure 1. An overview of the steps involved in eIEM using a toy example of an fMRI experiment reconstructing stimulus colors. (a) Basic encoder and decoder steps common to all variations of IEM. The prerequisites for implementing an IEM are the feature value of the stimulus for every trial (here 8 trials of colored squares), a trial-by-voxel matrix of brain activations for every voxel per trial (here simulated beta weights from a six-voxel brain region, and a basis set representing hypothesized population-level tuning functions; see Methods for details). The encoder models

each voxel's response as the weighted sum of the channels. Given that the trial-by-voxel matrix
and the basis set are already given, the weights matrix can be estimated via least-squares
linear regression. Once the weights matrix is estimated from the training dataset, it can be
inverted such that the encoder becomes a decoder for the test dataset. Now, instead of
estimating the weights matrix via least-squares linear regression, the weights matrix and the
trial-by-voxel matrix are given and the channel responses (i.e., reconstructions) are estimated.
The resulting estimated channel responses, or simply *reconstructions*, is a trial-by-channel
matrix where each trial has its own reconstruction composed of weighted cosines. For simplicity,
this example shows the encoder trained on the first half of trials and the decoder used to predict
the color of the remaining trials, but in most applications cross-validation should be used such
that every trial may be decoded while avoiding circularity/double-dipping. (b) The commonly
applied align-and-average procedure, which involves aligning and averaging reconstructions
across trials and measuring the result according to a variety of possible metrics (e.g., amplitude,
slope; see Supplemental Figure 1). (c) eIEM deviates from this step by evaluating trial-by-trial
reconstructions rather than an averaged reconstruction. We use iterative shifting of the basis set
to allow channel space to equal stimulus space, correlate the reconstructions with the full set of
basis channels to estimate each trial's predicted stimulus (and then average prediction error),
and also estimate goodness-of-fits for each trial's reconstruction.
19

With eIEM, these aligned-and-averaged reconstructions can still be obtained for

visualization purposes, but eIEM offers several novel advantages for evaluating,

quantifying, and interpreting reconstructions. eIEM obtains trial-by-trial stimulus

predictions using a correlation table approach[a] (previously used in a small number of

papers[7,42]) that adapts to the shape of the basis channel (Figure 1C). For each trial, a

set of correlation coefficients is computed, each reflecting the correlation between that

trial's reconstruction and a basis channel (i.e., "perfect reconstruction") centered at

every integer in stimulus space (e.g., resulting in 360 correlation coefficients for a

stimulus space ranging from 0-359°). The highest of these correlation coefficients is

determined to be the best fit for that trial, and the predicted stimulus feature for that trial

is simply the center of that best-fitting basis channel. As described below in the Results,

evaluating reconstructions using stimulus predictions obtained via this approach is more

methodologically sound than, say, taking the location of highest amplitude as the

---

[a] There are other techniques besides the correlation table approach that have been used to obtain trial-by-trial stimulus predictions within the IEM framework, which we refer to as "non-standard approaches" in Supplemental Figure 1. We directly compare mean absolute error calculated via these different non-standard approaches using real fMRI datasets in Supplemental Figure 3. No approach was conclusively better than the others, and we picked the correlation table based on the fact that it that accounts for the shape of the encoder's basis channels and is parsimonious with goodness-of-fit calculations which rely on the correlation table approach, as described below.

stimulus prediction[25,44], because the shape of the basis functions is automatically taken

into account.

To quantify reconstruction quality, eIEM naturally lends itself to prediction error

based summary metrics. The difference between the predicted and actual stimulus

feature is that trial's prediction error; this error can be averaged across trials to obtain

mean absolute error (MAE), mean signed error, etc. Here we adopted MAE (specifically

circular mean absolute error when using circular feature spaces) as a default metric for

evaluating reconstruction quality, because of its simplicity and grounding in meaningful

units (average prediction error), particularly compared to other IEM metrics such as

slope, amplitude, reconstruction fidelity, etc which use arbitrary units. However, MAE

itself is not a necessary component of eIEM — trial-by-trial prediction errors can be

evaluated in any manner the researcher sees fit.

The final and most novel advantage that eIEM offers is the automatic calculation

of trial-by-trial goodness-of-fit values. Recall that each trial's stimulus prediction is

determined as the center of the best-fitting basis function. Because this is calculated

independently of the actual correct stimulus, the goodness-of-fit values themselves

(correlation coefficients) can also be recorded and optionally leveraged to estimate trial-

by-trial confidence of predictions. Individual trials in a neuroimaging study can vary

substantially in signal quality (driven by attentional fluctuations, alertness, head motion,

scanner noise, etc.) but typically the IEM procedure does not incorporate uncertainty

into decoding performance. The lack of uncertainty information has been noted in other

contexts, with some recent alternatives to IEM proposed to incorporate uncertainty[45,46].

eIEM has the advantage of easily and automatically producing a trial-by-trial measure of

prediction uncertainty within the IEM framework itself. This enhancement adds

substantial flexibility to the IEM procedure. For example, as depicted in Figure 1C,

goodness-of-fit can be used to set thresholds in a non-circular manner, such that less

reliable trials are excluded from reconstructions. As we demonstrate in the Results

using real and simulated fMRI datasets, goodness-of-fit thresholding can substantially

increase statistical power and performance in versatile ways. A caveat to this increased

flexibility is that a researcher cannot try varying cutoff thresholds and then cherry-pick

the threshold that provides desirable results; thresholds need to be determined before

data collection or according to some sort of a priori, independent criteria.

Here we define eIEM as an encoding model that uses the combination of iterative

shifting (or any technique which allows reconstructions to reside in stimulus space),

evaluating reconstructions using the basis channel defined for the encoder (via the

correlation table approach or other constrained model fitting), calculating trial-by-trial

prediction errors, and calculating goodness-of-fits independently from stimulus

predictions. Researchers can easily implement eIEM on their own through our publicly

available Python package (https://pypi.org/project/inverted-encoding; see Methods for

more information). Of course, researchers can choose to implement eIEM without our

Python package or choose to only implement some but not all aspects of eIEM. The

value of eIEM is primarily in terms of evaluating IEM results: using both real and

simulated data, we show below that eIEM can be beneficial in terms of interpretability,

flexibility, functionality, and robustness to methodological concerns.

15   **2. Results**

We first validate eIEM by implementing it on three existing fMRI datasets[43,47,48]

spanning the research topics of perception, attention, and memory. We then

demonstrate the ways eIEM can go beyond the more standard IEM approaches,

offering practical advantages and additional functionality. Finally, we use simulated

reconstructions to illustrate some additional theoretical issues and methodological

limitations that eIEM addresses. See the Methods for information regarding each

dataset and how data were processed.

2.1 Validating eIEM on real fMRI data

First, as initial validation, we confirmed that across all three datasets eIEM

replicated the overall pattern of results obtained previously with IEM (Figure 2). To do

this in a rigorous and consistent way, we reanalyzed all datasets ourselves using a

"standard" align-and-average IEM approach with slope as the decoding metric, even if

the original paper did not employ this exact same procedure. We chose slope as it is a

commonly used decoding metric across IEM papers (see Supplemental Figure 1). For

the purposes of testing eIEM, we selected a single primary analysis from each of the

three datasets, as detailed in the Methods.

In the Perception dataset[48], we used both techniques to decode the horizontal

position of a stimulus in V1, V4, and IPS. The "standard" align-and-average procedure

revealed significant decoding performance in all 3 ROIs, with the strongest decoding

(greatest slope) in V1, followed by V4, and then IPS. eIEM replicated this pattern. In the

Attention dataset[47], we used both techniques to decode the attended orientation within a

multi-item, multi-feature stimulus array, in the same three ROIs. The "standard" IEM

procedure revealed significant decoding in V1 and V4, but not IPS. eIEM again

replicated this pattern. Finally, in the Memory dataset[43], we used both techniques to

decode the remembered orientation of a stimulus over two types of working memory

delays: blank delay and distractor delay. With the "standard" procedure, the

remembered orientation was successfully decoded in V1, V4, and IPS, with significantly

greater decoding in V1 and V4 during the blank delay compared to the distractor delay.

With eIEM, we replicated each of those results, with the additional finding of significantly

greater decoding during the blank vs distractor delay in IPS.

Figure 2. Application of eIEM to three real fMRI datasets spanning the topics of perception (a), attention (b), and memory (c). For each dataset, we show results obtained from a representative "standard" IEM align-and-average approach (orange boxes, see Methods for details), our eIEM procedure without thresholding (purple boxes, 'Validation' plots), and eIEM using increasingly stringent cutoffs based on goodness-of-fit (purple boxes, 'Improved Flexibility' plots). Bar plots depict the reconstruction quality, using average slope for the "standard" procedure (higher values are better) and MAE for eIEM (lower values are better) across subjects, with individual

subjects overlaid as colored dots, for each of 3 ROIs (V1, V4, IPS). For the Attention dataset,
the 'Brain-behavior correlation' plot additionally plots the trial-by-trial correlation between
absolute behavioral error and absolute decoding error for each ROI and goodness-of-fit
threshold. Error bars depict standard error of the mean, dotted black lines represent chance
decoding, and asterisks represent statistically significant decoding (p<.05, no corrections for
multiple comparisons). Overall results show that conclusions are similar between the "standard"
align-and-average IEM approach and eIEM, but MAE is more interpretable (not based in
arbitrary units) and not prone to the methodological concerns we discuss later in the Results. In
addition, each dataset showed that MAE consistently improved with increasing exclusion
thresholds, demonstrating the flexibility of goodness-of-fit to exclude noisy trials. Increasing
exclusion thresholds also appeared to strengthen brain-behavior correlations in the Attention
dataset. See Supplementary Table 1 for test statistics and p values.
13

2.2 Demonstrating the improved interpretability and versatility of eIEM

Having validated our method across three diverse fMRI datasets, we next use

these same datasets to illustrate the practical advantages and additional features of

eIEM.

Improved interpretability. eIEM lends itself to metrics that are easily interpretable

and comparable across datasets due to decoding performance being measured in

terms of prediction error. In contrast, the arbitrary units typical of the more standard

aligned-and-averaged reconstructions are not easily interpretable. For example, in the

Memory dataset, the "standard" procedure results in an average slope of .006 for the

blank delay condition and .004 for the distractor delay condition in V1 (or cosine fidelity

values of .100 and .098 as reported in the original paper[43]); eIEM replicates this pattern,

but now with a more interpretable and meaningful metric: orientation can be decoded

with an average error of 27.9 degrees in the blank delay and 32.5 degrees in the

distractor condition. Note that the eIEM procedure can evaluate trial-by-trial

reconstructions using any metric, not just the MAE metric, if a different metric better

aligns with the researcher's goals.

Incorporating the additional trial-by-trial uncertainty feature. Next, we tested the

flexibility of eIEM to make use of the trial-by-trial goodness-of-fit information. The eIEM

approach produces a best-fitting stimulus prediction and associated goodness-of-fit

value (correlation coefficient) for each trial. It is important to emphasize that the

correlation coefficient reflects the degree to which the reconstruction matches the *best-*

fitting basis channel, not the basis channel centered on the correct stimulus. In other

words, this goodness-of-fit information is obtained without circularity. It is obtained

independently and prior to any calculation of prediction error.

To test the impact of using goodness-of-fit information on decoding performance,

we performed an analysis where we excluded trials with the lowest 5%, 10%, 25%, and

50% of goodness-of-fit values ("Improved flexibility" subplots of Figure 2). This resulted

in visible improvements in MAE (i.e., smaller decoding error) with increasing exclusion

thresholds for all three datasets (linear regression revealed significant negative slope in

all cases except for IPS in the Attention dataset). Notably, in the Attention dataset, MAE

improved with increasing thresholds in V1 and V4 (where decoding was significant in

the unthresholded analysis) but not in IPS (where decoding was at chance in the

unthresholded analysis). Thus, the goodness-of-fit information can be used to improve

decoding performance when a brain region contains reliable information about a

stimulus, but does not produce false positives in the absence of observable stimulus-

specific brain activity.

This trial-by-trial prediction uncertainty information could be used in several

ways. One suggestion we put forth is that goodness-of-fit can be used to threshold

reconstructions, such that worse-fitting trials may be excluded from analysis. This

principle is analogous to the phase-encoded retinotopic mapping and population

receptive field modeling techniques, where a set of models spanning the full stimulus

space is evaluated for every voxel, and the parameters of the best-fitting model are

selected as that voxel's preferred stimulus, with the goodness-of-fit values then used to

threshold the results[49–51]. Note that although r-squared is the more commonly used

statistic for goodness-of-fit using regression, squaring the correlation coefficient loses

potentially critical information about the sign of the correlation coefficient (e.g., a

perfectly inverted reconstruction should *not* be assigned equal confidence as a perfect

reconstruction in most cases), so we recommend the use of the r-statistic. For data

scrutiny purposes or for experiments where an inverted reconstruction is theoretically

informative, then researchers are free to adopt r-squared values or to not calculate

goodness-of-fit values entirely. Alternative approaches to trial thresholding also exist,

including weighting trials based on their goodness-of-fit (see Discussion).

Goodness-of-fits obtained using eIEM can also be applied more broadly, beyond

the MAE decoding metric. That is, one could use eIEM goodness-of-fits to threshold

trials while using any of the commonly employed metrics of slope, amplitude, cosine

fidelity, etc. Goodness-of-fit thresholding can also be applied directly to (aligned-and-

averaged) reconstruction curves. This could be particularly useful when one wants to

use eIEM and quantify results with MAE, but also visualize reconstruction curves. We

illustrate this point in Figure 3 using the above 3 fMRI datasets along with a simulated

dataset. As increasingly strict goodness-of-fit thresholds were applied, the

reconstruction curves were visibly improved. All of the quantification metrics similarly

showed improvements with increasing goodness-of-fit thresholds. For the real fMRI

datasets, these improvements generalized across all datasets, subjects (within-subjects

and across-subjects), brain regions, and experimental conditions (mirroring the

performance benefits shown in the "Increased flexibility" subplots of Figure 2). For the

simulated dataset, these improvements generalized across the full range of simulation

parameters tested, including number of trials, number of voxels, number and shape of

basis channels, shape of voxel tuning functions, amount of noise, etc. A sampling of 78

eIEM simulations with randomly determined ground truth parameters across varying

goodness-of-fit thresholds is depicted in Supplemental Figure 4, demonstrating the

robustness of goodness-of-fit thresholding to improve reconstructions (code available to

stimulate your own reconstructions on OSF: https://osf.io/et7m2/).

1
Figure 3. Simulated and real datasets show how eIEM goodness-of-fits can be applied to more
traditional aspects of IEM, particularly visualization of reconstruction curves. Different colors
reflect different goodness-of-fit thresholds, implemented by exclusion of the X% worst fitting
trials. Dotted black reconstruction denotes the original basis channel at the aligned point (i.e.,
"perfect" possible reconstruction). Visual inspection of the reconstructions shows clear
improvements with increasing thresholds. (a) Depiction shows the aligned-and-averaged
reconstructions across 300 trials within a simulated brain region of 50 voxels, using a basis set
of nine equally spaced channels. Several decoding metrics are shown below the curve, color-
coded for each threshold level; all similarly benefitted from this trial thresholding, demonstrating
the versatility of eIEM goodness-of-fits to benefit modeling outside of the eIEM framework.
Results generalized across a wide variety of simulation parameters; a random sampling of 78
more eIEM simulations with randomly determined ground truth parameters are depicted in
Supplemental Figure 4. Note that MAE typically, but not always, followed a monotonic function
across thresholds. The code to reproduce these results and simulate reconstructions with
varying parameters is available on OSF (https://osf.io/et7m2/). (b) We demonstrate the
robustness of this approach to improve aligned-and-averaged reconstructions at the single-
subject level across all three real fMRI datasets. Due to space limitations, we depict just three
plots using the first subject of each dataset across three different ROIs, but this general pattern
of stricter thresholds leading to improved reconstructions held across all datasets, subjects,
brain regions, and experimental conditions.

22
23
Brain-behavior correlations. Finally, having trial-by-trial prediction error and

goodness-of-fit values lends itself to analyses correlating neural measures with

behavior. We demonstrate this in the Attention dataset (the Perception dataset did not

collect behavioral responses, and in the Memory dataset behavioral performance was

too close to ceiling [~3° avg. error]). In V1 and V4, we observed a significant correlation

between a trial's behavioral error magnitude and neural prediction error. Moreover, the

strength of these correlations increased with higher goodness-of-fit thresholds, as

depicted in the "Brain-behavior" subplot of Figure 2 (Fisher z-transformed correlation

test: V1: $t(6)=6.85$, p<.001; V4: $t(6)=5.31$, p<.001). We note that behavioral error itself

did not noticeably change across these thresholds, suggesting that the goodness-of-fit

information seemed to be reflecting noise at the level of the fMRI signal, not simply

fluctuations in behavior or cognitive focus.

Altogether, these findings demonstrate several tangible benefits of using eIEM.

Not only does eIEM produce robust, reliable results, but it can do so using a prediction

error framework and metric that is more interpretable and intuitive. Moreover, the novel

addition of trialwise goodness-of-fit values offers increased flexibility to improve both

neural decoding power and brain-behavior correlations. Further, researchers can use

the visualization approach depicted in Figure 3, where reconstructions are visually

scrutinized alongside an overlaid perfect reconstruction, which we recommend to clarify

interpretations and ensure data are scrutinized before relying on a numerical decoding

metric.

2.3 Additional methodological concerns addressed by eIEM

The three real fMRI datasets analyzed above are useful validation cases

because they contain robust findings (as may be more likely with published, publicly

available datasets), allowing us to convey the improved interpretability and flexibility of

eIEM in cases where the overall pattern of decoding is consistent with a "standard"

align-and-average IEM approach. Crucially, however, there are also cases where we

would expect eIEM results to diverge from the "standard" IEM results due to various

methodological concerns inherent in the align-and-average approach. Below we

illustrate some hypothetical cases susceptible to specific methodological concerns and

limitations that are addressed by eIEM. These hypothetical cases are based on

theoretical principles and illustrated by cherry-picked visualizations to showcase some

ways that eIEM could meaningfully diverge from standard align-and-average steps;

while it remains unclear how pragmatically relevant such divergences would be in real

neuroimaging experiments, even less extreme versions of these patterns could produce

misleading data via other IEM approaches.

Potential information loss due to the align-and-average step. Figure 4 depicts a

few examples of how aligning and averaging reconstructions across trials could obscure

important information. The hypothetical cases illustrate one case where every trial is

accurately reconstructed (i.e., centered on the correct stimulus feature with minimal

error, panel 4a) and one case where every trial produces inaccurate reconstructions

(panel 4b). These two cases would be interpreted identically if a researcher were relying

on standard aligned-and-averaged reconstruction metrics. In contrast, eIEM correctly

identifies the first case as superior (lower MAE). Because eIEM evaluates prediction

error on a trial-by-trial level and then averages the result, it avoids the pitfall of

interpreting Figures 4a and 4b as reflecting the same quality of stimulus-specific brain

signal.

Figure 4. Visual depiction of how reconstructions with the standard align-and-average procedure
can produce spurious results because of not considering the variability of trial reconstructions or
the shape of the basis channel. For each of the 3 hypothetical examples (where data points
were manually defined), the top row depicts four single-trial reconstructions, and the row below
depicts the aligned-and-averaged reconstruction. In (a) each individual trial's reconstruction
accurately predicts the correct channel (i.e., the correct stimulus feature), appropriately reflected
in the averaged reconstruction. In (b) each individual trial's reconstruction predicts an incorrect
channel. Averaging across trials leads to a misleading result, i.e., the standard align-and-
average approach would consider (b) to reflect the same level of decoding performance as (a).
In (c) each individual trial's reconstruction is essentially noise, such that the averaged
reconstruction results in a false peak around the aligned point; the "standard" procedure using
align-and-average metrics results in spuriously superior decoding performance than both (a)
and (b), with (c) having a higher amplitude, steeper slope, improved cosine fidelity, and
narrower standard deviation when fit with a gaussian distribution. The eIEM procedure,
calculating MAE from trial-wise prediction error, correctly concludes that case (a) shows the
best decoding performance.
17
18
Another advantage of eIEM is that MAE is also less prone to bias from outlier

trials compared to any of the align-and-average metrics. When using the align-and-

average IEM approach, a single outlier reconstruction can disproportionately bias the

shape of the averaged reconstruction, potentially completely flipping the averaged

reconstruction in the most extreme cases. In contrast, the influence of an outlier is

naturally capped for eIEM: Consider a hypothetical experiment composed of 300 trials

where 299 trials predict the correct stimulus and one trial predicts the stimulus 180°

away (assuming 360° stimulus space); because prediction error is calculated at the trial

level and then averaged, an outlier trial could only increase MAE by a maximum 0.6°.

Falsely assuming a monotonic relationship between decoding performance and

neural signal. In addition to providing preferred solutions to the potential concerns of

outlier bias and information loss, there are other advantages to evaluating trialwise

reconstructions using eIEM. As described earlier, our trialwise goodness-of-fit metric

allows the researcher to predict which trials will likely produce better reconstructions

(and hence better stimulus predictions). While other complementary approaches exist,

for example using trial-by-trial decoding error to help extract top-down spatial signals[44]

or to correlate trial-by-trial decoding with memory-guided behavior across trials[24],

critically, eIEM's approach to calculating trialwise predictions avoids another known

issue.

As has been recently highlighted in the literature, IEMs produce reconstructions

that depend on the choice of basis set[38,39]. If the IEM procedure does not explicitly take

this observation into account, this can result in faulty interpretations. Supplemental

Figure 2 illustrates a rudimentary example of this issue that can be addressed with

iterative shifting, but a more fundamental problem remains. That is, intuition – and

standard practice – wrongly assume that a monotonic relationship exists between

reconstruction quality measured by metrics such as slope, amplitude, and bandwidth,

and the amount of stimulus-specific information in the brain signal. However, if the basis

set consists of equally spaced and identical basis channels (which is typically the case),

then a "perfect" reconstruction returns the exact shape of the basis channel[b]. Yet, the

standard align-and-average IEM steps can produce reconstructions from noisy neural

data that appear *better* than this "perfect" benchmark. We argue that it makes more

sense to directly compare the shape of the reconstruction to the shape of the basis

channel to make predictions and evaluations. The correlation table step we implement

in eIEM automatically adjusts to consider the shape of the basis channel because it is

the basis channel itself that is being used to obtain predictions, providing a more direct

relationship between IEM performance and stimulus-specific brain signal.

Simply put, amplitude, slope, bandwidth, cosine fidelity, etc. are inferior metrics

compared to the correlation table metric because they do not adapt to the choice of

basis set. This is true even if a researcher were to skip the align-and-average step by

evaluating reconstructions at the trial-by-trial level. For instance, using the amplitude

metric, a higher amplitude at the aligned point is thought to reflect improved

performance. If the basis channel ranges from 0 to 1, a perfect reconstruction should

have an amplitude of exactly 1 at the aligned point, but reconstructions can feasibly

have amplitudes far greater than 1. Likewise, the cosine fidelity (aka vector mean)

approach of evaluating reconstructions by taking the dot product of the reconstruction

---

[b] There are some cases where the basis channel is not representative of the perfect reconstruction. For instance, if training a model with intermixed experimental conditions, or if using basis channels that are not identical or are unequally spaced. In these cases, one can simulate what a perfect reconstruction looks like at each stimulus feature and use these tuning functions in the same manner as the correlation table approach. We also note that there may be cases where visual comparison of reconstructions is the goal and numerical reconstruction evaluations are unnecessary.

and a cosine function could favor reconstructions with a wider width than expected

under ideal conditions. Figure 4C illustrates an extreme example of this problem, where

standard align-and-average IEM metrics would produce spuriously high values,

potentially leading one to falsely interpret the neural signal from Figure 4C as producing

a better reconstruction than the signal from Figure 4A.

Note that to avoid this pitfall, it is important to preserve the exact shape of the

basis channel defined by the encoding model when fitting reconstructions. While some

prior approaches partially account for the shape of the basis channel by, for example,

fitting the aligned-and-averaged reconstruction with a curve of the same general shape

as the basis function (e.g., Henderson et al., 2019[48]), such fitting procedures (1) operate

on the aligned-and-averaged reconstruction, and (2) allow the model parameters to be

flexible. This process could still produce misleading conclusions (e.g., fitting Figure 4c

with a cosine and taking the amplitude would result in the appearance of superior

decoding performance compared to Figure 4a). Meanwhile, eIEM evaluates the

reconstructions at a trial-by-trial level, using a fixed basis channel shape (i.e., the only

parameter that changes is the mean location in stimulus space). Our eIEM package

implements this using the correlation table approach, which can be considered as a

constrained version of curve-fitting, in the sense of optimizing the best location of the

basis channel, but any approach that fits the trial-by-trial reconstructions via comparison

to the exact basis channel shape used in the original encoder would also be

appropriate.

3. Conclusions

Inverted encoding modeling has become a popular method for predicting stimuli

and investigating neural representations because of its robust performance, simplicity of

linear modeling, ability to predict untrained classes, and grounding in single-unit

physiology. Our new eIEM technique operates under the same general scope of

experimental scenarios as other IEM approaches while fixing important methodological

concerns surrounding some standard IEM procedures, and offering increased

functionality, flexibility, and interpretability of results. In other words, when it comes to

whether significant stimulus-specific information can be reconstructed from a brain

region, eIEM performs comparably to (i.e. at least as good as) other IEM approaches.

The core advantages of eIEM are that it can also do more, increasing the types of

analyses that can be conducted, as well enhancing the interpretability of results.

Namely, eIEM's benefits are due to the following modifications: (1) iterative

shifting of the basis channel returns reconstructions in stimulus space rather than

impoverished channel space, (2) evaluating reconstruction quality using the same

tuning function used to build the encoder is more theoretically sound than assuming a

monotonic relationship between reconstruction shape and neural signal, (3) calculating

trial-by-trial prediction errors can be used to evaluate in meaningful units when decoding

stimulus features, improving interpretability (compared to an align-and-averaged

reconstruction) and allowing comparison of decoding performance across different

model specifications, and (4) calculating goodness-of-fits independently from stimulus

predictions allows a trial-by-trial uncertainty measure that can be used to flexibly

improve reconstruction quality and applications.

It is worth noting that while some prior papers have presented alternative IEM

procedures that implement some of the modifications above, eIEM is unique in terms of

its comprehensiveness and accessibility/simplicity. Moreover, the eIEM procedure is

flexible: while our default eIEM procedure can be executed with a single line of code

from our openly available software package, this code can be also modified to

selectively adopt aspects of the eIEM pipeline while customizing others. For example, a

researcher could choose to not to use the goodness-of-fit information, or to use

measures other than MAE. Alternatively, a researcher could customize the basis sets or

other model parameters to test more advanced questions.

We demonstrated the above advantages of eIEM using three fMRI datasets. Our

validations demonstrated how our eIEM approach can be applied to both circular and

non-circular stimulus spaces, is sensitive to variations in decoding performance across

brain regions and experimental conditions, and can be used to accurately decode the

contents of perception, attention, and working memory. Our modifications further

allowed for decoding performance of each dataset to be directly compared to each other

in intuitive units, allowed us to meaningfully link neural reconstructions with behavior,

and demonstrated how uncertainty, measured via goodness-of-fit, can be leveraged to

increase statistical power. Note that just because these three datasets produced

consistent overall results (in terms of significance testing) across procedures does not

ensure this will always be the case, as illustrated by the cases in Figure 4 where eIEM

carries less of a risk of misinterpretation than other implementations.

One of the more novel aspects of eIEM is that researchers have the flexibility to

exclude trials with noisier reconstructions based on our goodness-of-fit scores, which

reflect how similar in shape each reconstruction is to the basis channel at the predicted

stimulus. This flexibility can be used alongside *any* computational model or evaluation

metric because researchers could first threshold trials using goodness-of-fits obtained

from our eIEM approach before proceeding to implement non-eIEM steps. A core

difference between goodness-of-fits obtained using eIEM compared to other IEM

metrics that evaluate the shape of a reconstruction is that eIEM goodness-of-fits are

obtained independently from prediction error—they are obtained without reference to

the correct, ground truth stimulus (other metrics first center reconstructions at the

correct stimulus and then evaluate the result, which is circular if used for trial

thresholding). Note that we do not prescribe a specific cutoff for determining goodness-

of-fit thresholds in this paper, rather, we simply offer that such an approach is possible

for improving IEM performance. For example, a researcher could a priori decide to more

heavily weight trials with higher confidences or simply exclude the noisiest 20% of trials.

We depict examples of varying goodness-of-fit thresholds across a variety of simulation

parameters in Supplemental Figure 3. We also stress that goodness-of-fit thresholds

need to be determined before data collection or according to some sort of a priori,

independent criteria.

Our method also improves interpretability by evaluating reconstructions in terms

of prediction error. For example, "V1 showed 10° average prediction error and V4

showed 20° average prediction error" is more interpretable than "V1 showed .02

amplitude and V4 showed .01 amplitude" because the latter is in arbitrary units,

whereas MAE is in meaningful units. Further, unlike amplitude or slope, the magnitude

of prediction error can be directly compared to other experiments using the same

stimulus space. This allows researchers to compare the quality of decoding across

experiments or experimental conditions with differing model specifications.

In this paper we have referred to IEMs as a specific kind of encoding and

decoding model that involves simple linear regression with population-level tuning

functions. An advantage of eIEM is that improvements are accomplished without

sacrificing this simplicity—the encoding model weights and the decoding model channel

responses are simply estimated via least-squares estimation. There are more complex

neuroimaging methods that can similarly be used to produce reconstructions via

hypothesized tuning functions. For instance, Kay et al., (2008)[5] decoded natural images

from brain activity via voxel-level receptive field models that describe tuning functions

across space, orientation, and spatial frequency. Naselaris et al. (2009)[3] further

produced Bayesian reconstructions of natural images via the combination of encoding

models meant to estimate structural and semantic content. Van Bergen and

colleagues[46,52,53] introduced models where voxels with similar tuning account for shared

noise and which produce trial-by-trial probability distributions such that uncertainty can

be obtained similarly to our procedure (although the researchers discuss this in terms of

testing Bayesian theories of neural computation rather than trial thresholding). Further

work will be necessary to compare all these approaches, and we acknowledge that

these more complex modeling approaches may be more useful than eIEM depending

on the research question and the extent to which the researcher prefers model

complexity over simplicity. For now, given the ample and broad interest in the cognitive

neuroscience community towards implementing relatively more simplistic IEM

procedures, we offer eIEM as an accessible means to improve reconstructions within

the same familiar framework already popularized by IEM.

In summary, inverted encoding modeling has become increasingly popular in

recent years, and yet the proper method for evaluating and interpreting IEMs has

become increasingly uncertain. Our eIEM method is advantageous for both theoretical

and practical reasons. From theoretical principles, we argue that eIEM is less

susceptible to methodological and interpretational pitfalls than other typical

implementations of IEM. We also demonstrate clear and practical advantages for

evaluating reconstructions according to our eIEM method: as validated with real fMRI

datasets, researchers can use eIEM to obtain improved reconstructions via thresholding

with goodness-of-fits, compare decoding performance across experiments and varying

basis sets using a metric grounded in meaningful units, evaluate performance in

stimulus space rather than impoverished channel space, and obtain concrete stimulus

predictions (with corresponding goodness-of-fits) for every trial rather than rely on a

summary statistic based in arbitrary units. While there already exist approaches capable

of addressing some of these concerns, our approach represents a suite of best

practices that can be adopted by researchers in future work. Our procedure can be

easily implemented with just one line of code using our accessible Python package

(https://pypi.org/project/inverted-encoding; see Methods)[c], and can be applied to

investigate a vast range of research questions that involve reconstructing the contents

of perception, attention, and memory from neuroimaging data.

Funding

This work was funded by the National Institutes of Health (R01-EY025648 to JDG) and

the National Science Foundation (NSF DGE-1343012 to PSS, NSF BCS-1848939 to

JDG).

References

1. Poldrack, R. A. The physics of representation. *Synthese* 1–19 (2020).

2. Naselaris, T., Kay, K. N., Nishimoto, S. & Gallant, J. L. Encoding and decoding in

fMRI. *Neuroimage* **56**, 400–410 (2011).

3. Naselaris, T. & Kay, K. N. Resolving ambiguities of MVPA using explicit models of

representation. *Trends Cogn. Sci.* **19**, 551–554 (2015).

4. Popov, V., Ostarek, M. & Tenison, C. Practices and pitfalls in inferring neural

representations. *NeuroImage* **174**, 340–351 (2018).

---

[c] Note that while our Python package greatly simplifies inverted encoding modeling, we caution users to still scrutinize and visualize their data (e.g., averaged reconstructions can sometimes falsely look good as depicted in Figure 4, and reconstructions should always be visualized before relying on numerical decoding metrics).

5. Kay, K. N., Naselaris, T., Prenger, R. J. & Gallant, J. L. Identifying natural images from human brain activity. *Nature* **452**, 352–355 (2008).

6. Naselaris, T., Prenger, R. J., Kay, K. N., Oliver, M. & Gallant, J. L. Bayesian reconstruction of natural images from human brain activity. *Neuron* **63**, 902–915 (2009).

7. Brouwer, G. J. & Heeger, D. J. Decoding and reconstructing color from responses in human visual cortex. *J. Neurosci.* **29**, 13992–14003 (2009).

8. Casey, M., Thompson, J., Kang, O., Raizada, R. & Wheatley, T. Population codes representing musical timbre for high-level fMRI categorization of music genres. in *Machine Learning and Interpretation in Neuroimaging* 34–41 (Springer, 2012).

9. Lee, H. & Kuhl, B. A. Reconstructing perceived and retrieved faces from activity patterns in lateral parietal cortex. *J. Neurosci.* **36**, 6069–6082 (2016).

10. Ester, E. F., Anderson, D. E., Serences, J. T. & Awh, E. A neural measure of precision in visual working memory. *J. Cogn. Neurosci.* **25**, 754–761 (2013).

11. Ester, E. F., Sprague, T. C. & Serences, J. T. Parietal and frontal cortex encode stimulus-specific mnemonic representations during visual working memory. *Neuron* **87**, 893–905 (2015).

12. Ester, E. F., Sprague, T. C. & Serences, J. T. Categorical biases in human occipitoparietal cortex. *J. Neurosci.* **40**, 917–931 (2020).

13. Foster, J. J., Sutterer, D. W., Serences, J. T., Vogel, E. K. & Awh, E. Alpha-band oscillations enable spatially and temporally resolved tracking of covert spatial attention. *Psychol. Sci.* **28**, 929–941 (2017).

14. Foster, J. J., Bsales, E. M. & Awh, E. Covert spatial attention speeds target individuation. *J. Neurosci.* **40**, 2717–2726 (2020).

15. Garcia, J. O., Srinivasan, R. & Serences, J. T. Near-real-time feature-selective modulations in human cortex. *Curr. Biol.* **23**, 515–522 (2013).

16. Kok, P. & Turk-Browne, N. B. Associative prediction of visual shape in the hippocampus. *J. Neurosci.* **38**, 6888–6899 (2018).

17. Samaha, J., Sprague, T. C. & Postle, B. R. Decoding and reconstructing the focus of spatial attention from the topography of alpha-band oscillations. *J. Cogn. Neurosci.* **28**, 1090–1097 (2016).

18. Sprague, T. C. & Serences, J. T. Attention modulates spatial priority maps in the human occipital, parietal and frontal cortices. *Nat. Neurosci.* **16**, 1879–1887 (2013).

19. Sprague, T. C., Ester, E. F. & Serences, J. T. Reconstructions of information in visual spatial working memory degrade with memory load. *Curr. Biol.* **24**, 2174–2180 (2014).

20. Sprague, T. C., Ester, E. F. & Serences, J. T. Restoring latent visual working memory representations in human cortex. *Neuron* **91**, 694–707 (2016).

21. Yu, Q. & Shim, W. M. Temporal-order-based attentional priority modulates mnemonic representations in parietal and frontal cortices. *Cereb. Cortex* **29**, 3182–3192 (2019).

22. Cai, Y., Sheldon, A. D., Yu, Q. & Postle, B. R. Overlapping and distinct contributions of stimulus location and of spatial context to nonspatial visual short-term memory. *J. Neurophysiol.* **121**, 1222–1231 (2019).

23. Chen, N., Bi, T., Zhou, T., Li, S., Liu, Z., & Fang, F. Sharpened cortical tuning and enhanced cortico-cortical communication contribute to the long-term neural mechanisms of visual motion perceptual learning. *Neuroimage* **115**, 17–29 (2015).

24. Hallenbeck, G. E., Sprague, T. C., Rahmati, M., Sreenivasan, K. K. & Curtis, C. E. Working memory representations in visual cortex mediate distraction effects. *Nat. Commun.* **12**, 4714 (2021).

25. Kok, P., Brouwer, G. J., van Gerven, M. A. & de Lange, F. P. Prior expectations bias sensory representations in visual cortex. *J. Neurosci.* **33**, 16275–16284 (2013).

26. Kok, P., Mostert, P. & De Lange, F. P. Prior expectations induce prestimulus sensory templates. *Proc. Natl. Acad. Sci.* **114**, 10473–10478 (2017).

27. Kok, P., Rait, L. I. & Turk-Browne, N. B. Content-based dissociation of hippocampal involvement in prediction. *J. Cogn. Neurosci.* **32**, 527–545 (2020).

28. Lorenc, E. S., Sreenivasan, K. K., Nee, D. E., Vandenbroucke, A. R. & D'Esposito, M. Flexible coding of visual working memory representations during distraction. *J. Neurosci.* **38**, 5267–5276 (2018).

29. Mostert, P. *et al.* Eye movement-related confounds in neural decoding of visual working memory representations. *Eneuro* **5**, (2018).

30. Oh, B.-I., Kim, Y.-J. & Kang, M.-S. Ensemble representations reveal distinct neural coding of visual working memory. *Nat. Commun.* **10**, 1–12 (2019).

31. Sprague, T. C., Itthipuripat, S., Vo, V. A. & Serences, J. T. Dissociable signatures of visual salience and behavioral relevance across attentional priority maps in human cortex. *J. Neurophysiol.* **119**, 2153–2165 (2018).

32. Sutterer, D. W., Foster, J. J., Adam, K. C., Vogel, E. K. & Awh, E. Item-specific delay activity demonstrates concurrent storage of multiple active neural representations in working memory. *PLoS Biol.* **17**, e3000239 (2019).

33. Tang, M. F., Arabzadeh, E. & Mattingley, J. B. Forward modelling reveals dynamics of neural orientation tuning to unconscious visual stimuli during binocular rivalry. *bioRxiv* (2019) doi:10.1101/574905.

34. Van Moorselaar, D. *et al.* Spatially selective alpha oscillations reveal moment-by-moment trade-offs between working memory and attention. *J. Cogn. Neurosci.* **30**, 256–266 (2018).

35. Vo, V. A., Sprague, T. C. & Serences, J. T. Spatial tuning shifts increase the discriminability and fidelity of population codes in visual cortex. *J. Neurosci.* **37**, 3386–3401 (2017).

36. Yu, Q., Teng, C. & Postle, B. R. Different states of priority recruit different neural representations in visual working memory. *PLoS Biol.* **18**, e3000769 (2020).

37. Gardner, J. L. & Liu, T. Inverted Encoding Models Reconstruct an Arbitrary Model Response, Not the Stimulus. *eNeuro* **6**, ENEURO.0363-18.2019 (2019).

38. Liu, T., Cable, D. & Gardner, J. L. Inverted encoding models of human population response conflate noise and neural tuning width. *J. Neurosci.* **38**, 398–408 (2018).

39. Sprague, T. C., Boynton, G. M. & Serences, J. T. The importance of considering model choices when interpreting results in computational neuroimaging. *Eneuro* **6**, (2019).

40. Sprague, T. C. *et al.* Inverted Encoding Models Assay Population-Level Stimulus Representations, Not Single-Unit Neural Tuning. *eNeuro* **5**, ENEURO.0098-18.2018 (2018).

41. Ho, T. *et al.* The optimality of sensory processing during the speed–accuracy tradeoff. *J. Neurosci.* **32**, 7992–8003 (2012).

42. Kim, I., Hong, S. W., Shevell, S. K. & Shim, W. M. Neural representations of perceptual color experience in the human ventral visual pathway. *Proc. Natl. Acad. Sci.* **117**, 13145–13150 (2020).

43. Rademaker, R. L., Chunharas, C. & Serences, J. T. Coexisting representations of sensory and mnemonic information in human visual cortex. *Nat. Neurosci.* **22**, 1336–1344 (2019).

44. Rahmati, M., Saber, G. T. & Curtis, C. E. Population Dynamics of Early Visual Cortex during Working Memory. *J. Cogn. Neurosci.* **30**, 219–233 (2018).

45. Li, H.-H., Sprague, T. C., Yoo, A., Ma, W. J. & Curtis, C. E. Joint representation of working memory and uncertainty in human cortex. *bioRxiv* (2021) doi:10.1101/2021.04.05.438511.

46. Van Bergen, R. S. & Jehee, J. F. TAFKAP: An improved method for probabilistic decoding of cortical activity. *bioRxiv* (2021) doi:10.1101/2021.03.04.433946.

47. Chen, J., Scotti, P. S., Dowd, E. W. & Golomb, J. D. Neural Representations of Task-relevant and Task-irrelevant Features of Attended Objects. *bioRxiv* (2021) doi:10.1101/2021.05.21.445168.

48. Henderson, M., Vo, V., Chunharas, C., Sprague, T. & Serences, J. Multivariate analysis of BOLD activation patterns recovers graded depth representations in human visual and parietal cortex. *Eneuro* **6**, (2019).

49. Dumoulin, S. O. & Wandell, B. A. Population receptive field estimates in human visual cortex. *Neuroimage* **39**, 647–660 (2008).

50. Engel, S. A., Glover, G. H. & Wandell, B. A. Retinotopic organization in human visual cortex and the spatial precision of functional MRI. *Cereb. Cortex N. Y. NY 1991* **7**, 181–192 (1997).

51. Sereno, M. I. *et al.* Borders of multiple visual areas in humans revealed by functional magnetic resonance imaging. *Science* **268**, 889–893 (1995).

52. Van Bergen, R. S. & Jehee, J. F. Modeling correlated noise is necessary to decode uncertainty. *Neuroimage* **180**, 78–87 (2018).

53. Van Bergen, R. S., Ma, W. J., Pratte, M. S. & Jehee, J. F. Sensory uncertainty decoded from visual cortex predicts behavior. *Nat. Neurosci.* **18**, 1728–1730 (2015).

54. Brouwer, G. J. & Heeger, D. J. Cross-orientation suppression in human visual

cortex. *J. Neurophysiol.* **106**, 2108–2119 (2011).

55. Wandell, B. A., Dumoulin, S. O. & Brewer, A. A. Visual field maps in human cortex.

Neuron **56**, 366–383 (2007).

56. Destrieux, C., Fischl, B., Dale, A. & Halgren, E. Automatic parcellation of human

cortical gyri and sulci using standard anatomical nomenclature. *Neuroimage* **53**, 1–

15 (2010).

57. Mumford, J. A., Turner, B. O., Ashby, F. G. & Poldrack, R. A. Deconvolving BOLD

activation in event-related designs for multivoxel pattern classification analyses.

Neuroimage **59**, 2636–2643 (2012).

Materials & Methods

We performed analyses on both real and simulated data. For the real fMRI

datasets, we used two publicly available published datasets[43,48] and one unpublished

dataset from our lab[47]. Note that we only analyzed a subset of the data from each

dataset, picking a single key analysis and analyzing one or two conditions across three

brain regions for the sake of simplicity. The experimental paradigms and conditions /

regions chosen are described more in each dataset's respective section below.

Inverted encoding model procedures

22   For all datasets, we performed a set of analyses using both a standard align-and-

23 average IEM approach and the eIEM approach (as depicted in Figure 1, with the

24 exception that we used iterative shifting for both approaches to facilitate more direct

25 comparison). For both procedures, we used the same basis set. Basis channels can be

26 modeled as

27
$$\cos\left((\theta - \mu)\frac{\pi}{stimulus\_range}\right)^{num\_channels-1}$$

where θ is degrees in stimulus space, μ is the center of each channel, and

stimulus_range is the range of stimulus space (e.g., 360° hues on a color wheel). The

reasoning behind raising cosines to the *num_channels*-1 is to make the tuning curves

narrower and more comparable to physiological findings[54]. Our eIEM Python package

actually approximates this cosine with a gaussian function; this allows the user to

experiment with different widths for their tuning functions via the optional parameter

channel_sd. For the encoder, each voxel's response was modeled as the weighted sum

of the channels such that the observed trial-by-voxel fMRI activation matrix is equal to

the dot product of the basis set and the weight matrix,

$basis\_set[trial\_features, :] \cdot channel\_by\_voxel\_weights = trial\_by\_voxel\_activation$

where *trial_features* is the feature (e.g., orientation) of the stimulus and *basis_set* is the

matrix of channels with shape (*stimulus_range, num_channels*).

Once the weights matrix is estimated from the training dataset, it is inverted such

that the weights matrix and the trial-by-voxel matrix are given and the channel

responses (i.e., reconstructions) are estimated.

$trial\_by\_voxel\_activation \cdot channel\_by\_voxel\_weights^{-1} = reconstructions$

For all datasets, we used a basis set composed of nine equidistant channels

each modeled as the gaussian approximation of $\cos\left((\theta - \mu)\frac{\pi}{180}\right)^{8}$. We used 10-fold (no

shuffling) cross-validation, such that each iteration trained the model on 90% of the data

and tested the model on the remaining 10%, repeated such that all trials were at one

point decoded as part of the testing set.

For the 'standard' align-and-average approach, we aligned and averaged the

single trial reconstructions into an average reconstruction and calculated slope as a

traditional decoding metric. For the eIEM procedure, we calculated absolute prediction

error for each trial via the correlation table metric and then calculated MAE. We

performed these steps for each subject, ROI, and condition, and then we calculated the

average slopes and MAEs across subjects.

For each condition and ROI, we assessed significance via permutation testing.

Significance tests were one-sided and uncorrected, calculated by comparing the t-

statistic calculated from the actual data against the permuted null distribution of t-

statistics (one t-statistic per each of 5,000 permutations). For eIEMs, we also repeated

this analysis pipeline using varying levels of goodness-of-fit thresholds. That is, we

discarded a certain percent of trials based on the worst goodness-of-fits and then

calculated MAE using the remaining trials. The full list of t-statistics and corresponding

p-values for the tests performed in Figure 2 are displayed in Supplementary Table 1.

Perception dataset: Henderson, Vo, Chunharas, Sprague, and Serences (2019)

Data were obtained by downloading post-processed fMRI data associated with

Henderson et al. (2019)[48], publicly available on OSF (https://osf.io/j7tpf/). In this

experiment, nine participants attended to a central fixation while a sphere (multicolored

flickering dots positioned on the shell of a 3D sphere with radius 3.4°) was presented at

varying positions along the horizontal and depth axes (depth achieved through

stereoscopic MR-compatible goggles). The task was to detect a brief luminance change

of the fixation point. Participants completed between 7 and 21 runs, where each run of

36 trials began with a sphere presented for 3s followed by a jittered intertrial interval (2-

6s). There were also runs where participants covertly attended to the sphere, but we did

not include these runs in the analysis. We only reconstructed horizontal position for

simplicity and because position-in-depth was only sampled across six unique locations

(varied sampling across the entire stimulus space is more appropriate for inverted

encoding models) whereas horizontal position was sampled across 36 unique locations

(from 0.9° to 9.8° eccentricity in both directions, collapsing across position-in-depth). We

analyzed V1, V4, and IPS regions of interest which were defined via retinotopic

mapping protocols where participants viewed rotating wedges and bowtie stimuli [55]

while performing a covert attention task of detecting contrast dimming on a row of the

checkerboard for the rotating wedge stimulus. We applied IEMs (following the

procedures outlined earlier) to the post-processed data conducted by the authors of the

original paper: Single-trial activation estimates consisted of averaged z-scored BOLD

signal of the 3rd and 4th TRs following stimulus presentation. For more methods

information, please refer to the original paper[48].

Attention dataset: Chen, Scotti, Dowd, & Golomb (2021)

Data were previously collected in our lab for another study Chen et al. (2021)[47].

In this experiment, seven participants completed a visual attention task. Each trial

started with a central fixation cross. After 700ms, three circle outlines were displayed at

equidistant locations surrounding the fixation cross for 200ms. One outline was thicker

than the others, representing the spatial cue. Participants were instructed to covertly

attend to the spatial cue location while maintaining fixation at the fixation cross. After

1100ms, three colored and oriented gratings were briefly displayed for 100ms, followed

by a 200ms mask and a continuous orientation report. Participants were instructed to

report the orientation of the grating that appeared at the location of the spatial cue.

There were also trials where participants were asked to shift attention to a different

spatial location before the onset of the gratings, and entire runs where participants were

asked to attend and report the color of the grating (instead of orientation), but we did not

include these in our analysis. Participants completed at least 440 trials of each condition

across multiple runs and sessions. We analyzed V1, V4, and IPS regions of interest: V1

and V4 were defined via retinotopic mapping protocols where participants viewed

rotating wedges and bowtie stimuli[55], while IPS was defined from the Destrieux atlas[56]

in Freesurfer (parcel labelled "S_intrapariet_and_P_trans"). To obtain single-trial neural

activations for IEM, we modified a commonly used single-trial general linear model

(GLM) approach[57] to improve the model sensitivity and account for the large number of

trials. Specifically, we conducted 40 GLMs per subject, where each GLM includes one

regressor per run for one of the 40 trials in that run and one regressor per run for all the

other remaining trials in that run. In this way, across the 40 GLMs, each trial in the

experiment had an estimated single-trial beta weight. For more methods information,

please refer to the original paper[47].

Memory dataset: Rademaker, Chunharas, and Serences (2019)

Data were obtained by downloading post-processed fMRI data publicly available

on OSF (https://osf.io/dkx6y)[43]. We reanalyzed Experiment 1 where six participants

underwent a visual working memory task. For each trial, a cue indicating the distractor

condition was shown for 1.4s, followed by a target grating shown for .5s where

participants were instructed to memorize its orientation, followed by a 1s blank delay,

and then an 11s delay where 3 possible distractor conditions were possible: blank

delay, Fourier-filtered noise, or distractor grating of a pseudo-random orientation.

Following an additional 1s blank delay, participants had 3s to report the orientation of

the target grating, and finally a variable intertrial interval (3/5/8s). Each participant

completed 108 trials per distractor condition. We reconstructed the remembered

orientation based on the average activation patterns 5.6–13.6 s after target onset, as in

Figure 1c in their paper, but only used the blank delay and distractor grating conditions

for simplicity. To maintain consistency across procedures and datasets, we used the 10-

fold cross-validation described earlier, with the blank delay and distractor grating

conditions trained/modeled/evaluated separately from each other. We analyzed V1, V4,

and IPS regions of interest which were defined via retinotopic mapping protocols where

participants viewed rotating wedges and bowtie stimuli[55]. We applied IEMs to the post-

processed data conducted by the authors of the original paper: Single-trial activation

estimates consisted of averaged BOLD signal between 5.6-13.6s (7-17 TRs) after target

onset. For more methods information, please refer to the original paper[43].

Simulated datasets

We used Python to simulate fMRI data from hypothetical brain region of interests

with arbitrarily chosen numbers of voxels, where each voxel's ground truth tuning

function was the same shape as the basis channel. For Figure 1 and Figure 3, we

injected random noise from a gaussian distribution into the trial by voxel matrix to

produce noisier data as would be expected from a real fMRI experiment. Simulated

fMRI data were subjected to the IEM procedures described above to depict the contents

of Figure 1, Figure 3, and Supplemental Figures 2 and 4. Our Jupyter notebook on OSF

(https://osf.io/et7m2/) contains Python code to reproduce Figures 1, 3, and

Supplemental Figure 4, and can also be used to simulate reconstructions with varying

parameters including number of trials, number of voxels, number and shape of basis

channels, shape of voxel tuning functions, amount of noise, etc.

Python package: inverted-encoding

We have released the Python 3 package "inverted-encoding" on PyPi

(https://pypi.org/project/inverted-encoding/) and GitHub

(https://github.com/paulscotti/inverted_encoding) for easy implementation of our eIEM

procedure. The package contains two main functions, "IEM" and "permutation."

For the "IEM" function, the only necessary inputs are an array of the stimulus

features for every trial, the trial by voxel activations matrix (note: inputs other than

voxels may be used for other modalities), the given stimulus range (e.g., stim_max=180

for stimulus values ranging from 0°-179°), and the number of folds to use for cross-

validation. The basis set can be specified as an optional parameter and will otherwise

default to a basis set composed of nine equidistant channels each modeled using

gaussian functions that approximate $cos\left((\theta - \mu)\frac{\pi}{180}\right)^8$. We use gaussian approximation

because this allows the user additional flexibility to vary the width of the basis channel

tuning functions via the standard deviation parameter. The stimulus space defaults to a

circular space but can be optionally set to be non-circular via the Boolean parameter

"is_circular." We advise researchers to be careful regarding cross-validation, such that

training and test data do not come from the same functional runs due to timepoints not

being independent (autocorrelation, z-scoring, etc.). The final outputs are an array of

each trial's predicted stimulus, an array of each trial's corresponding goodness-of-fit,

each trial's unaligned stimulus reconstruction, and each trial's aligned stimulus

reconstruction (aligned such that the correct stimulus is at zero in channel space). The

user can then compute MAE (or any decoding metric that they prefer). MAE can be

computed by averaging the (circular) absolute error between the predicted stimulus

features and the actual stimulus features. We provide a convenience function,

"circ_diff", for computing circular error. The user can decide whether they want to

threshold any trials using the provided goodness-of-fit values prior to calculating

decoding performance.

For the "permutation" function, the only necessary input is an array of the actual

stimulus features. For each iteration, the stimulus features are randomly shuffled and

used as the predicted stimuli to compute the MAE. The function outputs a null

distribution of MAE values for the user to compare against the MAE obtained from the

"IEM" function. A more exact and computationally intensive method would be to rerun

the entire IEM pipeline with shuffled stimulus labels on every iteration to obtain the null

distribution. This can also be performed using our package by simply repeating the IEM

function with a different shuffling of the stimulus features for every iteration. Our

exploratory comparisons of null distributions obtained using both approaches across the

three fMRI datasets discussed in the main text yielded no obvious differences.

Data availability

The Perception dataset[48] is publicly available on OSF (https://osf.io/j7tpf/). The Memory

dataset[43] is publicly available on OSF (https://osf.io/dkx6y). The Attention dataset[47] will

be made publicly available upon final publication of the original study; researchers may

contact the authors to obtain this dataset before then.

Code availability

Code to implement eIEM is available as a Python package

(https://pypi.org/project/inverted-encoding). Code to reproduce Figures 1 and 3 are

available on OSF (https://osf.io/et7m2/).

11 **Supplemental Information**
12
13
14 An enhanced inverted encoding model for neural reconstructions
15
16 Paul S. Scotti, Jiageng Chen, & Julie D. Golomb
17

1 # Table of Contents

5
6

1 **Supplemental figures 1 - 4.**

2
3
4

Metrics used to evaluate inverted encoding models

Standard approach (aligned and averaged reconstruction)
- Amplitude: Measure the height of the aligned x-axis location of the reconstruction.
- Slope: Fold the reconstruction in half (vertically), average the two halves and then take the resulting slope.
- Fit amplitude: Fit a gaussian distribution to the reconstruction and then measure the resulting amplitude at the aligned x-axis location.
- Fit bandwidth: Fit a gaussian distribution to the reconstruction and then measure the resulting standard deviation.
- Cosine fidelity: Multiply the reconstruction by a cosine (with height ranging from -1 to 1) and then average the amplitudes across all points.

Non-standard approach (individual trial estimates)
- Maximum point: The point in stimulus space with the highest amplitude becomes that trial's predicted stimulus.
- Circular mean: The circular mean of each trial reconstruction becomes that trial's predicted stimulus.
- Correlation table: For each trial, correlate the reconstruction with a basis channel centered at every integer in stimulus space. Select the channel with the largest correlation coefficient. Predicted stimulus = center of this channel.

5
Supplemental Figure 4. Summary of metrics used to evaluate IEM reconstructions in a
sampling of published paper[1–31]. Note that the methodological concerns raised in the Results
apply to the metrics labeled under the "standard" align-and-average approach. The non-
standard approaches can be quantified with a single value (like the standard approach metrics)
by taking the mean absolute error between predicted and actual stimuli. Note that not all papers
used the exact same procedure to obtain their listed IEM metric(s), and that the reader should
investigate the individual papers of interest for more exact methodological details.

Supplemental Figure 5. Simulation depicting iterative shifting and its benefits for IEM
reconstructions. The simulated neuroimaging data (trial by voxel activations) are identical for all
three cases shown, and the underlying voxel tuning functions for this hypothetical brain region
are known (simulated ground truth). The trial by voxel activations were constructed to reflect
perfect (zero noise) information with identical train and test sets, such that the resulting
reconstructions should also be perfect. (a) Basis set happens to perfectly reflect the underlying
voxel tuning functions (simulated ground truth). (b) Reconstruction of the same data, now with a
slightly altered basis set (channel means circularly shifted by 20°). Note that in a real
experiment, the ground truth actual voxel tuning functions are not known, so the experimenter's
arbitrary choice of channel centers could substantially alter resulting reconstructions, even if the
same signal is present in all cases. This could result in misleading conclusions using the
standard align-and-average IEM approach. (c) By combining the results of both basis sets, the
channel space changes from *num_channels* to *num_channels**2, leading to a fuller
reconstruction. This is the principle of iterative shifting: In eIEM, we repeatedly fit the encoding
model with every possible (circular) shift of the basis set (i.e. 1° shifts) and then combine all of
these iterations together. This produces a fuller reconstruction that is no longer impoverished by
a limited number of *num_channels* points (i.e., the range of channel space becomes equal to
the range of stimulus space) and allows the correlation table metric to be optimally applied. This
iterative shifting procedure also aids more generally in producing more interpretable and less
biased reconstructions, as it allows our decoding model to be capable of predicting any possible
feature in stimulus space (that is, not solely the stimuli that are located at the centers of the
basis channels). Note that iterative shifting does not change the fact that different basis sets
result in different reconstructions, rather, it simply allows for the most accurate reconstruction
given a set number of channels with defined bandwidths.

(a) **Perception** (Henderson, Vo, Chunharas, Sprague, & Serences, 2019)
Decode horizontal position

(b) **Attention** (Chen, Scotti, Dowd, & Golomb, in prep.)
Decode attended color

(c) **Memory** (Rademaker, Chunharas, & Serences, 2019)
Decode orientation during WM delay

Blank Delay

Distractor Grating

Supplemental Figure 3. Comparison of MAE across varying goodness-of-fit thresholds using three possible techniques for calculating single-trial stimulus estimates (see Supplemental Figure 1): maximum point (blue), correlation table (red), and circular mean (green). In terms of improved MAE, "circular mean" appears to have performed best, but overall results are similar regardless of the single-trial estimation technique. As discussed in the main text, for the eIEM package we employ the correlation table measure based on the fact that it that accounts for the

1 shape of the encoder's basis channels and is parsimonious with goodness-of-fit calculations
2 which rely on the correlation table approach.

3
4
5 **Supplemental Figure 4.** Random sampling of 78 eIEM simulations with varying ground truth
6 parameters across 4 goodness-of-fit thresholds demonstrates the robustness of goodness-of-fit

thresholding to improve reconstructions. Similar to Figure 3 in the main text, colored lines reflect
different goodness-of-fit thresholds (red:50% green:30% orange:15% blue:0%), the dotted
curved line depicts the basis channel (i.e., "perfect" reconstruction), and the vertical dotted line
denotes the aligned point in channel space. Text on the left-side of each plot denotes the
ground truth simulation parameters. "v" refers to the number of voxels, which was a random
integer between 50 and 1000. "c" refers to the number of equally spaced basis channels, which
was a random integer between 5 and 30. "vsd" and "bsd" refer to the standard deviation of the
underlying voxel tuning functions (vsd) and basis channels (bsd), which were random integers
between 10 and 120. "σ" was a random floating-point number between 0 and 5 and refers to the
standard deviation of a normal distribution (mu=0) from which random noise was injected into
the trial by voxel matrix. Colored text denotes the MAE for each thresholded reconstruction.
Subplots were automatically removed and replaced if the reconstructions showed near-chance
performance or near-perfect performance, where differences from thresholding would not be
expected to be visible. Code to reproduce this figure is available on OSF (https://osf.io/et7m2/).
15
16

1 **Supplemental table.**

Dataset	Procedure	Test description	T-stat	P-
Perception	IEM	V1	106.06	.000
		V4	53.33	.000
		IPS	27.70	.000
	eIEM	V1	-13.58	.000
		V4	-6.61	.000
		IPS	-5.12	.000
		V1 (5% excluded)	-13.73	.000
		V1 (10% excluded)	-15.79	.000
		V1 (25% excluded)	-22.06	.000
		V1 (50% excluded)	-29.65	.000
		V4 (5% excluded)	-7.11	.000
		V4 (10% excluded)	-7.97	.000
		V4 (25% excluded)	-9.18	.000
		V4 (50% excluded)	-13.63	.000
		IPS (5% excluded)	-5.54	.000
		IPS (10% excluded)	-5.86	.000
		IPS (25% excluded)	-6.78	.000
		IPS (50% excluded)	-8.54	.000
Attention	IEM	V1	16.02	.000
		V4	7.65	.001
		IPS	-0.16	.601
	eIEM	V1	-9.93	.000
		V4	-7.29	.000
		IPS	-0.11	.535
		V1 (5% excluded)	-9.64	.000
		V1 (10% excluded)	-9.79	.000
		V1 (25% excluded)	-10.08	.000
		V1 (50% excluded)	-11.49	.000
		V4 (5% excluded)	-7.36	.000
		V4 (10% excluded)	-7.42	.000
		V4 (25% excluded)	-7.88	.000
		V4 (50% excluded)	-7.86	.000
		IPS (5% excluded)	-1.15	.208
		IPS (10% excluded)	-1.06	.234
		IPS (25% excluded)	-0.87	.281
		IPS (50% excluded)	0.98	.842
	eIEM – brain-behavior	V1	7.02	.000
		V4	5.18	.002
		IPS	-1.06	.330
		V1 (5% excluded)	6.50	.001

		V1 (10% excluded)	6.30	.001
		V1 (25% excluded)	7.25	.000
		V1 (50% excluded)	6.69	.001
		V4 (5% excluded)	4.48	.003
		V4 (10% excluded)	4.81	.003
		V4 (25% excluded)	5.18	.002
		V4 (50% excluded)	7.03	.000
		IPS (5% excluded)	-0.85	.427
		IPS (10% excluded)	-1.38	.218
		IPS (25% excluded)	-0.70	.508
		IPS (50% excluded)	-0.41	.693
Memory	IEM – blank delay	V1	6.21	.001
		V4	6.38	.002
		IPS	4.70	.004
	IEM – distractor delay	V1	4.07	.008
		V4	5.55	.001
		IPS	5.57	.001
	IEM – blank vs. distractor	V1	4.18	.013
		V4	4.18	.011
		IPS	-0.53	.659
	eIEM – blank delay	V1	-4.88	.006
		V4	-5.79	.003
		IPS	-5.22	.005
		V1 (5% excluded)	-4.94	.006
		V1 (10% excluded)	-4.99	.006
		V1 (25% excluded)	-4.86	.006
		V1 (50% excluded)	-4.75	.007
		V4 (5% excluded)	-5.77	.003
		V4 (10% excluded)	-5.76	.003
		V4 (25% excluded)	-5.70	.003
		V4 (50% excluded)	-6.21	.002
		IPS (5% excluded)	-5.15	.005
		IPS (10% excluded)	-5.43	.004
		IPS (25% excluded)	-4.95	.006
		IPS (50% excluded)	-5.00	.006
	eIEM – distractor delay	V1	-4.07	.012
		V4	-4.26	.010
		IPS	-5.65	.002
		V1 (5% excluded)	-4.26	.010
		V1 (10% excluded)	-4.25	.010
		V1 (25% excluded)	-4.08	.012
		V1 (50% excluded)	-4.50	.008
		V4 (5% excluded)	-4.25	.010
		V4 (10% excluded)	-4.30	.010

		V4 (25% excluded)	-3.65	.019
		V4 (50% excluded)	-4.09	.012
		IPS (5% excluded)	-5.18	.005
		IPS (10% excluded)	-5.35	.004
		IPS (25% excluded)	-5.92	.002
		IPS (50% excluded)	-6.11	.001
	eIEM – blank vs. distractor	V1	-7.55	.000
		V4	-2.85	.049
		IPS	-3.03	.041
		V1 (5% excluded)	-7.14	.001
		V1 (10% excluded)	-7.08	.001
		V1 (25% excluded)	-9.32	.000
		V1 (50% excluded)	-2.73	.056
		V4 (5% excluded)	-2.89	.048
		V4 (10% excluded)	-3.13	.038
		V4 (25% excluded)	-6.21	.019
		V4 (50% excluded)	-3.57	.021
		IPS (5% excluded)	-2.68	.060
		IPS (10% excluded)	-2.48	.076
		IPS (25% excluded)	-0.94	.437
		IPS (50% excluded)	0.20	.862

1
2   **Supplemental Table 1.** Statistics from tests depicted in Figure 2 from the main text.

Supplemental references.

1. Cai, Y., Sheldon, A. D., Yu, Q. & Postle, B. R. Overlapping and distinct contributions of stimulus location and of spatial context to nonspatial visual short-term memory. *Journal of neurophysiology* **121**, 1222–1231 (2019).

2. Chen, N. *et al.* Sharpened cortical tuning and enhanced cortico-cortical communication contribute to the long-term neural mechanisms of visual motion perceptual learning. *Neuroimage* **115**, 17–29 (2015).

3. Ester, E. F., Anderson, D. E., Serences, J. T. & Awh, E. A neural measure of precision in visual working memory. *Journal of cognitive neuroscience* **25**, 754–761 (2013).

4. Ester, E. F., Sprague, T. C. & Serences, J. T. Parietal and frontal cortex encode stimulus-specific mnemonic representations during visual working memory. *Neuron* **87**, 893–905 (2015).

5. Foster, J. J., Sutterer, D. W., Serences, J. T., Vogel, E. K. & Awh, E. Alpha-band oscillations enable spatially and temporally resolved tracking of covert spatial attention. *Psychological science* **28**, 929–941 (2017).

6. Foster, J. J., Bsales, E. M. & Awh, E. Covert spatial attention speeds target individuation. *Journal of Neuroscience* **40**, 2717–2726 (2020).

7. Garcia, J. O., Srinivasan, R. & Serences, J. T. Near-real-time feature-selective modulations in human cortex. *Current Biology* **23**, 515–522 (2013).

8. Hallenbeck, G. E., Sprague, T. C., Rahmati, M., Sreenivasan, K. K. & Curtis, C. E. Working memory representations in visual cortex mediate distraction effects. *Nat Commun* **12**, 4714 (2021).

9. Henderson, M., Vo, V., Chunharas, C., Sprague, T. & Serences, J. Multivariate analysis of BOLD activation patterns recovers graded depth representations in human visual and parietal cortex. *Eneuro* **6**, (2019).

10. Ho, T. *et al.* The optimality of sensory processing during the speed–accuracy tradeoff. *Journal of Neuroscience* **32**, 7992–8003 (2012).

11. Kim, I., Hong, S. W., Shevell, S. K. & Shim, W. M. Neural representations of perceptual color experience in the human ventral visual pathway. *Proceedings of the National Academy of Sciences* **117**, 13145–13150 (2020).

12. Kok, P. & Turk-Browne, N. B. Associative prediction of visual shape in the hippocampus. *Journal of Neuroscience* **38**, 6888–6899 (2018).

13. Kok, P., Brouwer, G. J., van Gerven, M. A. & de Lange, F. P. Prior expectations bias sensory representations in visual cortex. *Journal of Neuroscience* **33**, 16275–16284 (2013).

14. Kok, P., Mostert, P. & De Lange, F. P. Prior expectations induce prestimulus sensory templates. *Proceedings of the National Academy of Sciences* **114**, 10473–10478 (2017).

15. Kok, P., Rait, L. I. & Turk-Browne, N. B. Content-based dissociation of hippocampal involvement in prediction. *Journal of Cognitive Neuroscience* **32**, 527–545 (2020).

16. Liu, T., Cable, D. & Gardner, J. L. Inverted encoding models of human population response conflate noise and neural tuning width. *Journal of Neuroscience* **38**, 398–408 (2018).

17. Lorenc, E. S., Sreenivasan, K. K., Nee, D. E., Vandenbroucke, A. R. & D'Esposito,

M. Flexible coding of visual working memory representations during distraction.

Journal of Neuroscience **38**, 5267–5276 (2018).

18. Mostert, P. *et al.* Eye movement-related confounds in neural decoding of visual

working memory representations. *Eneuro* **5**, (2018).

19. Oh, B.-I., Kim, Y.-J. & Kang, M.-S. Ensemble representations reveal distinct neural

coding of visual working memory. *Nature communications* **10**, 1–12 (2019).

20. Rademaker, R. L., Chunharas, C. & Serences, J. T. Coexisting representations of

sensory and mnemonic information in human visual cortex. *Nature neuroscience* **22**,

1336–1344 (2019).

21. Rahmati, M., Saber, G. T. & Curtis, C. E. Population Dynamics of Early Visual

Cortex during Working Memory. *Journal of Cognitive Neuroscience* **30**, 219–233

(2018).

22. Samaha, J., Sprague, T. C. & Postle, B. R. Decoding and reconstructing the focus of

spatial attention from the topography of alpha-band oscillations. *Journal of cognitive*

neuroscience **28**, 1090–1097 (2016).

23. Sprague, T. C. & Serences, J. T. Attention modulates spatial priority maps in the

human occipital, parietal and frontal cortices. *Nature neuroscience* **16**, 1879–1887

(2013).

24. Sprague, T. C., Ester, E. F. & Serences, J. T. Reconstructions of information in

visual spatial working memory degrade with memory load. *Current Biology* **24**,

2174–2180 (2014).

25. Sprague, T. C., Ester, E. F. & Serences, J. T. Restoring latent visual working memory representations in human cortex. *Neuron* **91**, 694–707 (2016).

26. Sprague, T. C., Itthipuripat, S., Vo, V. A. & Serences, J. T. Dissociable signatures of visual salience and behavioral relevance across attentional priority maps in human cortex. *Journal of neurophysiology* **119**, 2153–2165 (2018).

27. Sutterer, D. W., Foster, J. J., Adam, K. C., Vogel, E. K. & Awh, E. Item-specific delay activity demonstrates concurrent storage of multiple active neural representations in working memory. *PLoS biology* **17**, e3000239 (2019).

28. Tang, M. F., Arabzadeh, E. & Mattingley, J. B. Forward modelling reveals dynamics of neural orientation tuning to unconscious visual stimuli during binocular rivalry. *bioRxiv* (2019) doi:10.1101/574905.

29. Van Moorselaar, D. *et al.* Spatially selective alpha oscillations reveal moment-by-moment trade-offs between working memory and attention. *Journal of cognitive neuroscience* **30**, 256–266 (2018).

30. Vo, V. A., Sprague, T. C. & Serences, J. T. Spatial tuning shifts increase the discriminability and fidelity of population codes in visual cortex. *Journal of Neuroscience* **37**, 3386–3401 (2017).

31. Yu, Q., Teng, C. & Postle, B. R. Different states of priority recruit different neural representations in visual working memory. *PLoS biology* **18**, e3000769 (2020).