A neural network account of memory replay and knowledge consolidation

Running title: Category replay in deep neural networks

Daniel N. Barry[1] and Bradley C. Love[1,2]

1. Department of Experimental Psychology, University College London, 26 Bedford Way, London,

WC1H0AP, UK

2. The Alan Turing Institute, 96 Euston Road, London, NW12DB, UK

Corresponding author: daniel.barry@ucl.ac.uk, ORCID ID: 0000-0002-2474-5651

Abstract

Replay can consolidate memories through offline neural reactivation related to past experiences.

Category knowledge is learned across multiple experiences, and its subsequent generalisation is

promoted by consolidation and replay during rest and sleep. However, aspects of replay are difficult

to determine from neuroimaging studies. We provided insights into category knowledge replay by

simulating these processes in a neural network which approximated the roles of the human ventral

visual stream and hippocampus. Generative replay, akin to imagining new category instances,

facilitated generalisation to new experiences. Consolidation-related replay may therefore help to

prepare us for the future as much as remember the past. Generative replay was more effective in later

network layers functionally similar to the lateral occipital cortex than layers corresponding to early

visual cortex, drawing a distinction between neural replay and its relevance to consolidation. Category

replay was most beneficial for newly acquired knowledge, suggesting replay helps us adapt to changes

in our environment. Finally, we present a novel mechanism for the observation that the brain

selectively consolidates weaker information; a reinforcement learning process in which categories

were replayed according to their contribution to network performance. This reinforces the idea of

consolidation-related replay as an active rather than passive process.

Keywords: consolidation, learning, memory, network, replay

1. Introduction

1.1 Memory consolidation-related replay

Memory replay refers to the reactivation of experience-dependent neural activity during resting periods. First observed in rodent hippocampal cells during sleep (Wilson and McNaughton 1994), the phenomenon has since been detected in humans during rest (Tambini and Davachi 2013; Hermans et al. 2017; Schapiro et al. 2018; Liu et al. 2019; Wittkuhn and Schuck 2021), and sleep (Schönauer et al. 2017; Zhang et al. 2018). These investigations have revealed replayed experiences are more likely to be subsequently remembered, therefore replay has been proposed to strengthen the associated neural connections and to protect memories from being forgotten. This memory consolidation-related replay can be viewed as distinct from task-related replay, the neural reactivation observed during task performance which supports cognitive processes such as memory recall (Jafarpour et al. 2014; Michelmann et al. 2019; Wimmer et al. 2020), visual understanding (Schwartenbeck et al. 2021), decision making (Liu et al. 2021), planning (Momennejad et al. 2018) and prediction (Ekman et al. 2017). While traditional perspectives view memory consolidation as a gradual process of fixation whereby memories are stabilised (Squire and Alvarez 1995; McGaugh 2000), in this paper we advocate the more contemporary view that offline consolidation-related replay is more dynamic in nature (Mattar and Daw 2018). Using a computational approach, we test hypotheses that offline replay may be a creative process to serve future goals, that it matters exactly where in the brain replay occurs, that it helps us at particular stages of learning, and that the brain might actively choose the optimal experiences to replay.

1.2 Generative replay of category knowledge

Neural replay which supports memory consolidation during rest and sleep has been traditionally assumed to be veridical, such that we commit the events of that day to long-term memory by replaying the episodes as they were originally experienced. However, there are circumstances in which this may be suboptimal or impractical. For example, a desirable outcome of category knowledge consolidation

is to generalise to new experiences rather than recognise past instances. This phenomenon has been

observed after sleep in infants (Gómez et al. 2006; Friedrich et al. 2015; Horváth et al. 2016), and in

adults (Lau et al. 2011). Sleep also recovers the generalisation of phonological categories (Fenn et al.

2003), preserves generalisation performance in perceptual category learning (Graveline and Wamsley

2017), and assists in the abstraction of gist-like prototype representations (Lutz et al. 2017). It is still

not understood how the brain consolidates and replays memory in the service of generalisation. In

addition, although sleep benefits category learning for a limited number of well-controlled

experimental stimuli (Schapiro et al. 2017), in the real world category learning takes place over many

thousands of experiences, and storing each individual experience for replay is an impractical

proposition. For these reasons, we propose the replay of novel, prototypical category instances would

be a more efficient and effective solution. In fact, given the role of the hippocampus in both replay

(Zhang et al. 2018) and the generation of prototypical concepts (Hassabis et al. 2007), we consider this

the most likely form of category replay. While evidence for such generative replay of category

knowledge has yet to be discovered in the human brain, replay of sequences immediately following

task performance in humans has been shown to be flexible, in that items can be re-ordered based on

previously learned rules (Liu et al. 2019). This is reminiscent of "pre-play" observed during task

performance in rodents, where hippocampal "place cells" observed to fire in specific locations

reactivate in a different order to represent a route which has not been taken before (Gupta et al.

2010).

Drawing inspiration from these observations, here we test the idea that replay which

facilitates memory consolidation, occurring over extended offline time periods including sleep, might

also be generative in nature, and that it's flexibility may not just apply to the reorganisation of learned

sequences, but the creation of entirely new instances of a category. While decoding the re-ordering

of stimuli or route knowledge from brain data during replay has been shown to be a tractable

approach, detecting entirely new instances of complex categories from the brain represents a

significant challenge, and has yet to be demonstrated.

One approach to address this question is to simulate these processes in an artificial neural

network. Prior research with artificial neural networks has modelled the replay of generated image

stimuli (van de Ven et al. 2020). While revealing a promising avenue of investigation, the results of

this study cannot be easily extrapolated to the brain or human visual experience. For example, the

structure of only five convolutional layers in the network employed represents just a fraction of the

size of larger models which have been shown to extract visual representations similar in nature to

those processed by the brain (Schrimpf et al. 2018), whose complex structure can be compared to the

ventral visual stream processing pathway, indicating a possible correspondence in functional

architecture (Khaligh-Razavi and Kriegeskorte 2014; Güçlü and van Gerven 2015; Devereux et al.

2018), and whose object recognition performance approaches that of humans (He et al. 2015).

Further, the networks employed by van de Ven et al. (2020) had limited visual experience, having been

pre-trained on just 10 categories of objects. In contrast, an adult human brain will harbour a lifetime

of visual knowledge which facilitates the learning of novel concepts. Therefore, to simulate the

learning and generative replay of new categories realistically in adults, using an experienced network

which contains a pre-existing vast body of knowledge about a range of other categories is an essential

starting point. Another feature of the aforementioned study which limits the comparison to humans,

is that the stimuli used were low-resolution photographs measuring 32 x 32 pixels, which do not reflect

the complexity of human visual experience. To accurately simulate human learning and replay, much

larger, high-resolution images which go some way towards approaching the complexity and richness

of everyday human visual experience are required as training stimuli. Finally, prior attempts at replay

in neural networks, whether generative (Kemker and Kanan 2017; van de Ven et al. 2020) or veridical

(Hayes et al. 2021) have been deployed to address the "catastrophic forgetting" problem; the

tendency of artificial networks to forget old categories when new ones are learned (Robins 1995;

French 1999). While this has been proposed as a potential mechanism for why biological agents do

not suffer from catastrophic forgetting, empirical evidence in support of this hypothesis has not been

forthcoming to date. In addition, other solutions have been put forward on how brains and models

may avoid catastrophic interference, such as Adaptive Resonance Theory (Grossberg 2013), and elastic

weight consolidation (Kirkpatrick et al. 2017).

In this study, we investigated whether offline generative replay of novel concepts facilitated

subsequent generalisation to new experiences using models which attempt to simulate the human

brain and approximate more closely the visual environment in which it learns. To do this, we

implemented generative replay in a well-studied deep convolutional neural network (DCNN), which

consists of a complex architecture organised into five blocks of convolutional layers and boasts a high

"brain-score" indicating the representations it extracts bear a similarity to those extracted by the brain

and it performs favourably to humans in a categorisation task (Schrimpf et al. 2018). The network had

prior experience of learning 1000 diverse categories of objects from over a million high-resolution

complex naturalistic images, a process which is the network equivalent of a lifetime of visual

experience and which yields within the model an optimised, high-functioning visual system. We tasked

the model with learning 10 novel categories it had not seen before, using similarly high-resolution

naturalistic images to those it has seen before, with an average resolution of around 400 x 350 pixels

(Deng et al. 2009), representing an approximate 140-fold increase in visual details from stimuli used

in prior work. The analogue in humans would be coming across 10 new categories we had not seen

before and using our lifelong experience in processing visual information to extrapolate the relevant

identifying features. After learning periods, we then simulated generative replay in the network, which

attempted to mimic human consolidation during sleep, and monitored the network's performance

when it "woke up" the next day, to ascertain if we could provide computational support for the theory

that such a process underlies the overnight improvements in generalisation observed in humans.

1.3 Effective neural loci of replay

Another outstanding question regarding replay, is despite being associated with subsequent memory

(Zhang et al. 2018), it is not clear where in the brain replay makes a demonstrable contribution

towards generalisation. Replay has been observed throughout the brain, early in the ventral visual

stream (Ji and Wilson 2007; Deuker et al. 2013; Wittkuhn and Schuck 2021), in the ventral temporal

cortex (Tambini et al. 2010; de Voogd et al. 2016), the medial temporal lobe (Staresina et al. 2013;

Schapiro et al. 2018) the amygdala, (Girardeau et al. 2017; Hermans et al. 2017), motor cortex

(Eichenlaub et al. 2020) and prefrontal cortex (Peyrache et al. 2009). It is not known if replay in lower-

level brain regions actually contributes to the observed memory improvements or whether the key

neural changes are made in more advanced areas, and this question cannot be answered using current

neuroimaging approaches. One prior study has implemented replay within an artificial neural network

from a single location at the end of the network (van de Ven et al. 2020). However, because the

compact architecture of this network did not have a clear functional correspondence with information

processing pathways in the brain, and because replay from other locations within the network was

not also implemented for comparison, it is difficult to yield predictions from these results regarding

effective replay locations in the human brain. In the current study, because we simulated replay in a

neural network which processes images in a manner reflective of the human ventral visual stream, we

could compare the effectiveness of replay from different layers with a purported representational

correspondence to specific regions in the brain. In doing so, we aimed to make predictions about the

effective cortical targets of offline memory consolidation in humans.

1.4 A time-dependent role for replay

Another open question regarding human replay is the duration of its involvement throughout the

learning of novel concepts. It can take humans years to learn and consolidate semantic or conceptual

knowledge (Manns et al. 2003), but neuroimaging studies of replay are limited to a time-span of a day

or two, therefore it is still not known how long replay contributes to this process. Humans are thought

to "reconsolidate" information every time it is retrieved (Dudai 2012), suggesting replay might play a

continual role in the lifespan of memory. However recordings in rodents have shown that replay

diminishes with repeated exposure to an environment over multiple days (Giri et al. 2019), suggesting

the brain may only replay recently learned, vulnerable information. Answering this question in

humans remains a challenge because of the impracticalities of tracking replay events for extended

periods. Simulation in a human-like neural network represents a possible alternative to predict the

relative contribution of replay to consolidation over long time-periods, an approach which has not

been attempted to date. Here, we interleaved daily learning with nights of offline replay in a neural

network which simulates the brain to understand at what stage in learning replay may be most

effective in humans.

1.5 Replay of weakly-learned knowledge

An additional poorly understood principle of replay which we investigated in this study is why

consolidation tends to selectively benefit weakly-learned over well-learned information (Kuriyama et

al. 2004; Drosopoulos et al. 2007; McDevitt et al. 2015; Schapiro et al. 2018). Here, we modelled a

candidate mechanism for how this occurs in the brain, by adding an auxiliary model (theoretically

analogous to the hippocampus) to the neocortical-like model, which could autonomously learn the

best consolidation strategy, determining what to replay and when.

1.6 Hypotheses

In addressing these outstanding questions regarding replay in the brain, we made a number of

predictions. Because earlier brain regions are thought to extract equivalent basic features from all

categories, we predicted replay of experience would be more effective in promoting learning at

advanced stages of the network. We hypothesised the replay of "imagined" prototypical replay events

would be as effective as veridical replay in helping us to generalise to new, unseen experiences, thus

supporting our conceptualization of replay as a creative process. We predicted that the benefits of

replay may be confined to early in the learning curve when novel category knowledge is being

acquired. Finally, we hypothesised that a dynamic interaction between hippocampal and neocortical-

like models would result in the prioritisation of weakly-learned items, in line with behavioural studies

of memory consolidation.

2. Materials and Methods

2.1 Neural network

To simulate the learning of novel concepts in the brain, and test a number of hypotheses regarding replay, we trained a DCNN on 10 new categories of images. The neural network was VGG-16 (Simonyan and Zisserman 2014). This network is trained on a vast dataset of 1.3 million high-resolution complex naturalistic photographs known as the ImageNet database (Deng et al. 2009), which contains recognisable objects from 1000 categories in different contexts. The network learns to associate the visual features of an object with its category label, until it can recognise examples of that object which it has never seen before, simulating the human ability to generalise prior knowledge to new situations. The network takes a photograph's pixels as input, and sequentially transforms this input into more abstract features. It learns to perform these transformations by adjusting 138,357,544 connection weights across many layers. Its convolutional architecture reduces the number of possible training weights by searching for informative features in any area of the photographs.

In these experiments, we task the VGG-16 network with learning 10 new categories of images. To do this, we retained the pre-trained "base" of this network, which consisted of 19 layers, organised into five convolutional blocks. Within each block there were convolutional layers and a pooling layer, with nonlinear activation functions. To this base, we attached two fully connected layers, each followed by a "dropout" layer, which randomly zeroed out 50% of units to prevent overfitting to the training set (Srivastava et al. 2014). At the end of the network a SoftMax layer was attached, which contained just 10 outputs rather than the original 1000, and predicted which of 10 classes an image belonged to. To facilitate the learning of 10 new classes, the weights of layers attached to the pre-trained base were randomly initialised. All model parameters were free to be trained. In total, 10 new models were trained, each learning 10 new and different classes.

2.2 Stimuli

Photographic stimuli for new classes were drawn randomly from the larger ImageNet 2011 fall

database (Russakovsky et al. 2015), and were screened manually by the experimenter to exclude

classes which bore a close resemblance to classes which VGG-16 was originally trained on. In total,

100 new classes were selected, and randomly assigned to the 10 different models to be trained. Within

each class, a set of 1,170 training images, 130 validation images, and 50 test images were selected.

The list of the selected classes is available in Supplementary Table 1.

2.3 Baseline training

We first trained a model without implementing replay, to serve as a baseline measure of network

performance, and compare with other conditions which implemented replay. Ten models were

trained on 10 new and different classes. To further prevent overfitting to the training set, images were

augmented before each training epoch. This is similar to a human viewing an object at different

locations, or from different angles, and facilitates the extraction of useful features rather than rote

memorisation of experience. Augmentation could include up to 20-degree rotation, 20% vertical or

horizontal shifting, 20% zoom, and horizontal flipping. Any blank portions of the image following

augmentation were filled with a reflection of the existing image. Images were then pre-processed in

accordance with Simonyan and Zisserman (2014). Depending on the experiment, the network was

trained for 10 or 30 epochs. We used the Adam optimiser (Kingma and Ba 2014) with a learning rate

of 0.0003. A small learning rate was chosen to reflect the fact that learning new categories in an adult

human reflects a "fine-tuning" of an already highly-trained visual system. The training batch size was

set to 36. The training objective was to minimise the categorical cross-entropy loss over the 10 classes.

Training parameters were optimised based on validation set performance. We report the model's

performance metrics from the test set only. This is a collection of novel images from each category

which the network does not learn nor is it tuned on, therefore reflecting the model's ability to

generalise to new stimuli after training, and is thus termed "generalisation performance" in the

figures. Training was performed using TensorFlow version 2.2.

2.4 Replay

Replay was conducted between training epochs, to simulate "days" of learning and "nights" of offline consolidation. We conceptualised replay representations as generative, in other words they represented a prototype of that category never seen before, from a particular point in the network. To generate these representations, the network activations induced by the training images from the preceding epoch were extracted from a particular layer in the network using the Keract toolbox (Remy 2020). For each class separately, a multivariate distribution of activity was created from these activations using the SciPy toolbox (https://scipy.org/). This multivariate normal distribution is an extension of the one-dimensional normal distribution to higher dimensions, and is specified by its mean and covariance matrix. This resulted in a single unique distribution for each specific class, which represented the relationship between units of the layer which had been previously observed for that class. We then sampled randomly from this distribution, creating novel activation patterns for that class at that point in the network (Fig 1A). These novel activation patterns represented a prototype of that category. The end result was a representation that was a rough approximation of the layer's representations of that category if a real image was processed, but novel in nature (see supplementary Fig 1). The human brain equivalent would be the approximate pattern of neural activity which is representative of that category at a particular stage in the ventral visual stream. In the brain, these hypothetical prototypical concepts would be likely generated from more high-level regions such as the hippocampus and prefrontal cortex (Hassabis et al. 2007; Bowman et al. 2020). Our model was generative as it could create new samples, however it offered several advantages over traditional generative models. We were not limited by a bottleneck symmetrical architecture, and our procedure allowed the model to learn generative samples at multiple levels of representation. Further, our model represented a proper vision model which showed parallels with the functional architecture of the ventral visual stream in the brain, whereas current generative models do not show this correspondence or scale well to such a deep architecture. Finally, our model is specialised for object recognition, with the resulting generated representations shaped by these task pressures.

The number of novel representations created for replay was equivalent to the number of

original training images (1,170). To test where in the network replay is most effective, this process was

performed at one of five different network locations, namely the max pooling layers at the end of each

block (Fig 1A). For the first four pooling layers, creating a multivariate distribution from such a large

number of units was computationally intractable, therefore activations for each filter in these layers

were first down-sampled by a factor of eight for layer one, by four for layers two and three and two

for layer four. The samples drawn from the resulting distribution were then up-sampled back to their

original resolution. These lower-resolution samples are also theoretically relevant, in that they were

created to mimic the schematic nature of mental and dream imagery which takes place during rest

and sleep. To replay these samples through the network, the VGG-16 network was temporarily

disconnected at the layer where replay was implemented, and a new input layer was attached which

matched the dimensions of the replay representations. This truncated network was trained on the

replay samples using the same parameters as regular training. We assume that the brain actively

chooses to replay each concept learned that day, by reactivating the prototypical representations

extracted from many experiences and the associated category label together during sleep. After each

epoch of replay training, the replay section of the network was reattached to the original base, and

training on real images through the whole network resumed. To assess the effects of generative replay

on stimuli disambiguation, we took 10 classes from the 100 which were highly similar (plants, see

supplementary table 2), and trained an additional network on these categories. We then assessed

whether replaying similar classes in the same model led to a greater relative increase in class

performance from baseline accuracies. We did this by dividing the increase in generalisation

performance resulting from replay by the original baseline performance. To find out how many

exemplars are needed for generative replay to have a beneficial effect on category learning we trained

the same models with 20, 40, 60, 80 and 100 images, again for ten "days", and replayed an equivalent

number of generated representations in each case. To simulate veridical replay, in other words the

replay of each individual experience as it happened, rather than the generation of new samples, we

used the activations for each object at that layer in the network during replay periods. These were not

down-sampled during the process. Given how many examples of a concept we generally encounter,

veridical replay of all experience is not a realistic prospect, which is why prior attempts to simulate

replay in smaller-scale networks have also avoided this scenario in their approaches (Kemker and

Kanan 2017; van de Ven et al. 2020). To additionally demonstrate the improvements that replay

affords on each day relative to the previous day, we calculated the performance improvement from

day n to day n+1, divided by the difference between model performance on day n and 1, which

represents the potential room for improvement.

2.5 Replay within a reinforcement learning framework

We tested a process through which items which are most beneficial for replay might be selected in

the brain. We proposed that such selective replay may involve an interaction between the main

concept learning network (VGG-16), and a smaller network which learned through reinforcement

which concepts are most beneficial to replay through the main network during offline periods. The

neural analogue of such a network could be thought of as the hippocampus, as the activity of this

structure precedes the widespread reactivation of neural patterns observed during replay (Zhang et

al. 2018). This approach is similar to the "teacher-student" meta-learning framework which has been

shown to improve performance in deep neural networks (Fan et al. 2018). The side network was a

simple regression network with 10 inputs, one for each class, and one output, which was the predicted

value for replaying that class through the main network. Classes were chosen and replayed one at a

time, with a batch size of 36. To train the side network, a value of 1 was inputted for the chosen class,

with zeros for the others. The predicted reward for the side network was the change in performance

of the main network after each replay instance, which was quantified by a change in chi-square; a

contrast of the maximum number of possible correct predictions by the main network, versus its

actual correct predictions. A positive reward was therefore a reduction in chi-square, which resulted

in an increase in the side network's weight for that class. This led to the class being more likely to be

chosen in future, as the network's weights were converted into a SoftMax layer, from which classes

were selected probabilistically for replay. Through this iterative process, the side network learned

which classes were more valuable to replay, and continually updated its preferences based on the

performance of the main network. Reducing the chi-square in this dynamic manner improves the

overall network accuracy as it progressively reduces the disparity between the network's

classifications and the actual class identities. To generate initial values for the side network, one batch

of each class was replayed through the main network. The Adam optimiser was used with a learning

rate of 0.001 and the objective was to minimise the mean squared error loss. The side network was

trained for 50 epochs with each replay batch. The assessment of network improvement was always

performed on the validation set, and the reported values are accuracy on the test set, reflecting the

ability of the network to generalise to new situations.

3. Results

3.1 Localising where in the ventral visual stream generative replay is likely to enhance

generalisation

We first sought to establish where in the visual brain the replay of category knowledge might be most

effective in helping to generalise to new experiences, as the functional relevance of replay observed

in many different brain regions has yet to be established. To obtain a baseline measure of how the

network would perform without replay, the network learned 10 new categories in the absence of

offline replay. Next, we implemented generative memory replay. To do this, we captured the "typical"

activation of the network for a category and sampled from this gist-like representation to create novel,

abstracted representations for replay (Fig 1A).

We simulated generative replay from different layers in the DCNN, equivalent to different

brain regions along the ventral stream. Specifically, we trained the network over 10 epochs, mimicking

10 days of learning in humans, and replayed prototypical representations after each training epoch,

simulating 10 nights of offline consolidation during sleep. In Fig 1B we show how replay affects the

ability of the network to generalise to new exemplars of the categories over the course of learning.

Replay substantially speeds up the learning process, with replay from layer four already reaching the

final baseline generalisation performance three days earlier. Fig 1C shows the final best performing

models in each replay condition. A one-way repeated-measures ANOVA on the final models revealed

a difference across conditions ($F_{(5,45)}$ = 7.23, p < 0.001), with planned Bonferroni-corrected post-hoc

comparisons revealing that only replay from layer 4 ($t_{(9)}$ = -4.31, p = 0.002) was significantly higher than

baseline. We performed an additional analysis to confirm that the down-sampling of earlier layers did

not explain this finding, by further down-sampling the replay representations in layer four by a factor

of seven, and generalisation performance in this layer was still significantly higher than baseline (see

supplementary Fig 2). Therefore, there is a differential benefit of replay throughout the network,

where replay in the early layers is of limited benefit, whereas replay in the later layers boosts

generalisation performance to a greater degree. This predicts that early visual areas in the brain may

not store sufficiently complex category-specific representations, curtailing the effectiveness of

generated replay representations, whereas areas further along the ventral visual stream, such as the

lateral occipital cortex, might be better positioned to support the generation of novel, prototypical

concepts which accelerates learning in the absence of real experience and helps us to generalise to

new situations. We further investigated if generative replay could benefit category learning where few

exemplars are available. In Figure 2D we show that generative replay from layer four could improve

generalisation when learning and replaying just 20, 40 or 60 exemplars (all t-tests below Bonferroni-

corrected threshold of p = 0.01). We also assessed the effects of replay on class disambiguation in this

layer, by training a model containing conceptually highly similar classes collated from all of the other

models, and comparing the relative increase in generalisation performance from the original class

accuracies. Figure 2E shows a replay-induced performance increase for conceptually similar items, but

this did not reach statistical significance ($t_{(9)}$ = -2.10, p = 0.065).

Fig 1. The effects of generative replay from different layers of a model of the human ventral visual stream on generalisation to new exemplars. (A) The VGG-16 network attempts to simulate the brain's visual system by looking at photographs and extracting relevant features to help categorise the objects within. We trained this network on 10 new categories of objects it had not seen before. In between learning episodes, to simulate sleep-facilitated consolidation in humans, we implemented offline

memory replay as a generative process. In other words, the network "imagined" new examples of a

category based on the distribution of features it has learned so far for that object (activation space),

and used these representations (novel representation) to consolidate its memory. The network did

not create an actual visual stimulus to learn from, rather it recreated the neuronal pattern of activity

that it would typically generate from viewing an object from that category. We display here an

example of replaying from a mid-point in the network, but all five locations where replay was

implemented are indicated by the coloured circles. The brain regions which have been reported to

contain functionally similar representations to different network layers, derived from Güçlü and van

Gerven (2015), are listed beneath. (B) The effects of memory replay from different layers on the

network's ability to generalise to new examples of the 10 categories, throughout the course of 10

learning episodes. Plotted values represent the mean accuracies from 10 different models which each

learned 10 new and different categories. (C) The final recognition accuracies (+/- S.E.M.), averaged

across 10 models, on the new set of photographs after 10 epochs of learning. We reveal the location

in a model of the ventral stream where replay maximally enhances generalisation performance is an

advanced layer which bears an approximate functional correspondence to the lateral occipital cortex

(LOC) in humans. The benefits of replay from other locations were less pronounced, with the earliest

layer showing the least benefit to generalisation. (D) The benefits of replay from layer four on

generalisation performance with limited numbers of exemplars (E) The effect of generative replay

from layer four on the generalisation performance of classes when learned alongside diverse

categories or where all are conceptually similar.

3.2 Tracking the benefits of replay across learning

In the second experiment, we extended training to 30 days of experience, interleaved with nights of

offline generative replay to simulate learning over longer timescales and predict when in learning

replay might be more effective (Fig 2A). Guided by the results of experiment one, we implemented

replay from an advanced layer corresponding to the lateral occipital cortex. A mixed between-within

ANOVA showed an interaction between condition and day ($F_{(29,522)}$ = 5.03, $p < 0.001$) with planned

post-hoc Bonferroni-corrected comparisons ($p < 0.00167$) revealing a difference between generative

replay and baseline for days two to six, and eight (Fig 2B). Visualising the network's improvement in

performance from day to day relative to the potential room for improvement from the previous day

confirmed that the benefits of generative replay were limited to early learning (Fig 2C). Therefore,

offline generative replay might be more effective at improving generalisation to new exemplars at the

earliest stages of learning. This suggests replay might facilitates rapid generalisation, which maximises

performance given a limited set of experiences with a category.

We were interested to compare generative replay with the unlikely veridical, high-resolution

scenario whereby humans could replay thousands of encounters with individual objects exactly as

they were experienced. We termed this "veridical replay" (Fig 2A), which involved capturing the exact

neural patterns associated with each experienced object during learning, and replaying these from

the same point in the network. A mixed between-within ANOVA did not reveal any difference

between generative and veridical replay in terms of generalisation performance ($F_{(1,18)}$ = 0.16, p =

0.696), nor was an interaction effect observed between day and condition ($F_{(29,522)}$ = 0.29, p = 0.999,

Fig 2B). Therefore, generative replay was comparably effective to veridical replay of experience in

consolidating memory, despite being entirely imagined from the networks prior experience. This

provides tentative support for the hypothesis that generative replay is a putative form of category

replay in humans, as it would appear vastly more efficient to imagine new concepts from an extracted

prototype.

The aforementioned results simulated the benefits of replay under optimal conditions where

humans encounter the same categories every day, however there are instances where exposure will

be limited. To what extent can offline replay compensate for this limited learning? We simulated this

in our model of the ventral stream by limiting the learning of actual category photographs to one day,

and substituted all subsequent learning experiences with offline replay, termed "continuous replay"

(Fig 2A). Despite the absence of further exposure to the actual objects, we found the network could

increase its generalisation accuracy from 32% to 83% purely by replaying imagined instances of

concepts it has partially learned. This result may inform our understanding of the human ability to

quickly learn from limited experience. However, a mixed-between ANOVA revealed a statistically

significant interaction effect between day and condition ($F_{(29,522)}$ = 3.78, $p < 0.001$), with planned

Bonferroni post-hoc comparisons revealing a difference between generative replay and continuous

replay from day nine onwards (all $p < 0.00167$). Therefore, replayed representations appear to be

dynamic in nature, as the prototypes generated from that first experience were not sufficient to train

the network to its maximum performance, as is observed when learning and replay are interleaved.

This suggests that replayed representations continue to improve as they are informed by ongoing

learning, therefore generative replay in the human brain throughout learning may be envisaged as a

constantly evolving "snapshot" of what has been learned so far about that category.

Fig 2. The facilitatory effects of memory replay across category learning. We simulate the long-

term consolidation of category memory by extending training to 30 days. (A) Schematic showing the

different experimental conditions. "No replay" involves the model of the visual system learning the

10 new categories without replay in between episodes. "Generative replay" simulates the brain

imagining and replaying novel instances of a category during "night" periods of offline consolidation,

from a layer bearing some functional approximation to the lateral occipital cortex. "Veridical replay"

simulates the hypothetical performance of a human who, each night, replays every single event

which has been experienced the preceding day. "Continuous replay" simulates a single day of

learning, followed by days and nights of replay, investigating the potential benefit afforded by replay

given only brief exposure to a category. For both day-time learning of real images and night-time

consolidation of generated representations, the number of training stimuli was always 1,170 for

each class. (B) The ability of the network to generalise to new exemplars of a category during each

day throughout the learning process. Generalisation performance is measured by the proportion (+/-

S.E.M.) of correctly recognised test images across 10 models. Generative replay maximally increases

performance early in training, suggesting it might be optimal for new learning and recent memory

consolidation. Despite being comprised of internally generated fictive experiences, generative replay

was comparably effective to veridical replay throughout the learning process, positing it as an

attractive, efficient and more realistic solution to memory consolidation which does not involve

remembering all experiences. Continuous replay after just one day of learning substantially

improved generalisation performance, but never reached the accuracy levels of networks which

engaged in further learning. (C) The improvement in performance that generative replay affords on

each day relative to the possible improvements from the previous day.

3.3 Determining how the brain might select experiences for replay

We proposed that replay may be a learning process in itself, whereby the hippocampus selects replay

items, and learns through feedback from the neocortex the optimal ones to replay. In our previous

simulations we selected all categories for replay in equal number, however to simulate the

autonomous nature of replay selection in the brain, we supplemented our model of the ventral visual

stream with a small reinforcement learning network, approximating the theoretical role of the

hippocampus in deciding what to replay (Fig 3A). The hippocampus-like model could choose one of

the 10 categories to replay, and received a reward from the main network for that action, based on

the improvement in network performance.

We trained our model of the visual system on 10 novel categories, implementing replay during

offline periods as before, and compared its generalisation performance with that of the dual

interactive hippocampal-cortical model. In terms of overall accuracy, although generative RL replay

appeared to lag briefly behind generative replay at the beginning of training, both approaches

performed similarly, with a mixed between-within ANOVA revealing no difference between the two

conditions in terms of generalisation performance ($F_{(1,18)}$ = 0.15, p = 0.704), nor was an interaction

effect observed between day and condition ($F_{(29,522)}$ = 1.28, p = 0.153, Fig 3B). Fig 3C plots the

difference between the two conditions across learning. However, the reinforcement learning network

which simulated the hippocampal replay systematically selected categories which were originally

relatively weakly learned more often (R^2 = 0.24, $F_{(1, 98)}$ = 31.15, p < 0.001, Fig 3D), which resulted in

their selective improvement (R^2 = 0.18, $F_{(1, 98)}$ = 21.15, p < 0.001). However, this came at a cost, with

originally well-learned categories being replayed less often and a drop in their generalisation accuracy.

We present the idea that such a reinforcement learning process may underlie the "rebalancing" of

experience in the brain, and that replay may therefore help to compensate for the fact that some

categories are more difficult to learn than others.

Fig 3. Replay as a reinforcement learning process simulates the brain's tendency to consolidate

weaker knowledge. (A) Replay in a model which approximates the visual system is controlled by a

reinforcement learning (RL) network which aims to assume the role of the hippocampus. The RL

network selects one of 10 categories to replay through the visual system and receives a reward

based on the improved performance, learning through trial and error which categories to replay. (B)

Overall generalisation performance on new category exemplars was similar for both generative

replay and generative replay controlled by a reinforcement learning network. Generalisation

performance represents mean accuracy (+/- S.E.M) on test images across 10 models which each

learned 10 new categories. (C) The difference between generative replay and generative RL replay

performance for each day. (D) The RL network learns to replay categories which were originally more

difficult for the model of the visual system, and improves their accuracy. This effectively

"rebalanced" memory such that category knowledge was more evenly distributed, and offers a

candidate mechanism as to how the brain chooses weakly learned information for replay. Plotted

517 values represent the 100 categories across 10 models. A proportion of the generalisation

518 performance values are overlapping.

4. Discussion

We simulated the consolidation of category knowledge in a large-scale neural network model which

approximates functional aspects of the human ventral visual system, by replaying prototypical

representations thought to be formed and initiated by the hippocampus. The notion that replay of

visual experiences might be generative in nature has been suggested by limited-capacity models which

have been trained on low-resolution photographic images (van de Ven et al. 2020). However, our

results using a model of the visual brain whose representations has compared favourably with actual

brain data, represent more persuasive evidence that humans are unlikely to replay experiences

verbatim during rest and sleep to improve category knowledge, and might be more likely to replay

novel, imagined instances instead. In addition, the large number (117,000) of high-resolution complex

naturalistic images we used for training in this experiment more closely reflected real-world learning

and facilitated the extraction of gist-like features. While empirical evidence exists that humans replay

novel sequences of stimuli (Liu et al. 2019), our work suggests that the brain might go further and uses

learned features of objects to construct entirely fictive experiences to replay. We speculate that this

creative process is particularly important for the consolidation of category knowledge as opposed to

the replay of episodic memory (Deuker et al. 2013; Schapiro et al. 2018; Zhang et al. 2018), because

of the requirement to abstract prototypical features and use these to generalise to new examples of

a category. We propose that generative replay confers additional advantages such as constituting less

of a burden on memory resources, as not all experiences need to be remembered. Further, our replay

representations were highly effective in consolidating category knowledge despite being down-

sampled, and these compressed, low-resolution samples would reduce storage requirements further.

Perhaps the simulation that most favourably supported the hypothesis that category replay in the

brain likely adopts this compressed, prototypical format is that it aided generalisation to a similar

degree as the exact veridical replay of experience in boosting generalisation performance. Therefore,

the main advantage to generative replay over veridical replay is that it represents a feasible, efficient

solution to memory consolidation without compromising effectiveness. In addition, generative replay

can add to events which have been experienced. Our findings therefore encourage a

reconceptualization of the nature of consolidation-related replay in humans, that it is not only

generative, but also low resolution or "blurry", as is the case with internally generated imagery in

humans (Giusberti et al. 1992; Lee et al. 2012). In fact, the kind of replay we propose here may be the

driving force behind the transformation of memory into a more schematic, generalised form which

preserves regularities across experiences while allowing unique elements of experience to fade (Love

and Medin 1998; Winocur and Moscovitch 2011; Sweegers and Talamini 2014). The challenge for

future empirical studies in humans to confirm our hypothesis, will be to decode prototypical replay

representations during rest and sleep. In addition, future modelling and empirical work should address

the sequential nature of learning and replay, as life experience does not consist of still snapshots of

experience, such as those used in these experiments. Prior modelling work has shown that a video

game-playing agent can improve its performance by learning inside its own generated environment

(Ha and Schmidhuber 2018), which is more akin to an unfolding dream during sleep, and may provide

inspiration for modelling the generative replay of video-like events to support category learning.

Simulating replay in a human-like network also allowed us to answer a question not currently

tractable in neuroimaging studies: where in the visual stream is replay functionally relevant to

consolidation? In a prior simulation of replay in a neural network, van de Ven et al. (2020)

demonstrated generative replay could attenuate forgetting when performed after the final

convolutional layer, but its effectiveness was not compared to earlier layers, and the network

employed, consisting of five convolutional layers, had not been compared with the human visual

system. Deeper networks, such as the one used here, consisting of 23 layers in total, organised into

five blocks of convolutional layers, not only extract useful category features from naturalistic images,

but representations in network layers have demonstrated a degree of representational

correspondence with specific brain regions along the ventral visual stream (Khaligh-Razavi and

Kriegeskorte 2014; Güçlü and van Gerven 2015; Devereux et al. 2018), albeit not capturing all

observable variance (Xu and Vaziri-Pashkam 2021). In keeping with our observation that low-

resolution, coarse, schematic replay was effective in helping the network to generalise, we found the

most effective location for replay to be in the most advanced layers of the network, layers which are

less granular in their representations. This region shares some functional similarities with the lateral

occipital cortex in humans, a region which represents more complex, high-level features (Güçlü and

van Gerven 2015). In contrast, generative replay from the earliest layers corresponding to early visual

cortex was less effective. These layers are sensitive to low-level visual features such as contrast, edges

and colour, therefore generating samples from these layers will yield rudimentary-level category-

specific information, which are of limited utility for replay and generalisation. High-level

representations on the other hand, may contain more unique combinations and abstractions of these

lower-level features. We also found replay from the penultimate layer was more effective than the

final layer, suggesting the optimal replay location represents a balance between the presence of

sufficiently complex category information and the number of downstream neuronal weights available

to be updated based on replaying these features. These findings may encourage a re-evaluation of the

functional relevance of replay in early visual cortices in both animals and humans, and generate

specific hypotheses for potential perturbation studies to investigate the effects of disruptive

stimulation at different stages of the ventral stream during offline consolidation.

Our simulations also revealed a phenomenon never before tested in humans, that the

effectiveness of replay depends on the stage of learning. We acquire factual information about the

world sporadically over time across contexts, for example we may encounter a new species at a zoo

one day, and subsequently see the same animal on a wildlife documentary, and so on. Ultimately the

consolidation of semantic information in the neocortex can take up to years to complete (Manns et

al. 2003). However, our simulations suggest that replay may be most beneficial during the initial

encounters with a novel category, when we are still working out its identifiable features and have not

yet learned to generalise perfectly to unseen instances. It is therefore possible humans replay a

category less and less with increasing familiarity, and there is some support for this idea in the animal

literature (Giri et al. 2019). We speculate that if this is the case, the enhanced effectiveness for recent

memories may have an adaptive function, allowing us to generalise quickly with limited information.

In fact, our simulations showed that after a single learning episode, replay can compensate

substantially for an absence of subsequent experience. Our results provide novel hypotheses for

human experiments, testing for an interaction between the stage of category learning and the extent

of replay. The fact that replay early in the learning process was more effective provides further support

for our proposal that vague, imprecise replay events are useful for generalisation, as the networks

imaginary representations at that stage would be an imperfect approximation of the category in

question. We acknowledge there may be a "ceiling effect", whereby later in training there is no further

room for improvement, however we would posit that over the human lifespan, we are operating in

the non-converged portion of the learning curve that we display here.

Our results also represent the first mechanistic account of how the brain selects weakly-

learned information for replay and consolidation (Kuriyama et al. 2004; Drosopoulos et al. 2007;

McDevitt et al. 2015; Schapiro et al. 2018). The hippocampus triggers replay events in the neocortex

(Zhang et al. 2018), with a loop of information back and forth between the two brain areas (Rothschild

et al. 2017), although the content of this neural dialogue is not known. Our simulations suggest that

the hippocampus may learn the optimal categories to replay based on feedback from the neocortex.

Our results showed that such a process resulted in the "rebalancing" of experience in an artificial

neural network, where generalisation performance was improved for weakly learned items, and

attenuated for items which were strongly learned. A reorganisation of knowledge of this kind has been

observed in electrophysiological investigations in rodents, where the neural representations of novel

environments are strengthened through reactivation at the peak of the theta cycle, while those

corresponding to familiar environments are weakened through replay during the trough (Poe et al.

2000). This more even distribution of knowledge could be adaptive in both ensuring adequate

recognition performance across all categories and forming a more general foundation on top of which

future conceptual knowledge can be built. There have been recent theoretical and empirical

demonstrations of how items get selected for replay within a reinforcement learning framework, such

as the "tagging" of items that elicit a large prediction error during the learning phase (Momennejad

et al. 2018), and the replay of events that are more likely to be encountered in future and which lead

to the highest reward (Mattar and Daw 2018; Liu et al. 2021). However, these accounts do not explain

why even in the absence of such prediction errors, or without knowing the likelihood of future events,

knowledge which has been weakly-learned during waking periods is consistently targeted for replay

and consolidation during sleep (Kuriyama et al. 2004; Drosopoulos et al. 2007; McDevitt et al. 2015;

Schapiro et al. 2018). Our interactive networks suggest that offline reinforcement learning could

account for the selection of weakly-learned knowledge during the replay process itself, and future

experiments could assess whether our models choose the same categories for replay as humans when

trained on the same stimuli.

In summary, our simulations provide supportive evidence that category replay in humans is a

generative process and make the prediction that it is functionally relevant at advanced stages of the

ventral stream. We have generated hypotheses about when during learning replay is likely to be

effective and offer a novel account of replay as a learning process in and of itself between the

hippocampus and neocortex. We hope these findings encourage a closer dialogue between theoretical

models and empirical experiments. These findings also add credence to the emerging perspective that

deep learning networks are powerful tools which are becoming increasingly well-positioned to resolve

challenging neuroscientific questions (Richards et al. 2019).

Acknowledgements: We thank the Love Lab for helpful discussions on this project. This work was

supported by the Royal Society (grant number 183029) and the Wellcome Trust (grant number

WT106931MA) to B.C.L. The funders had no role in study design, data collection and analysis,

decision to publish, or preparation of the manuscript.

Conflicts of Interests: The authors have declared that no conflicts of interests exist.

Author Contributions: D.N.B: Conceptualization, methodology, software, data curation,

investigation, formal analysis, visualization, writing-original draft preparation, writing-review &

editing. B.C.L.: Conceptualization, methodology, resources, funding acquisition, supervision, writing-

review & editing.

Data and Code Availability: The code, environment, and additional information required to run the

simulations is available at https://github.com/danielbarry1/replay.git and in the supplementary

information. All relevant data in the paper is available at

https://doi.org/10.6084/m9.figshare.14208470.

5. References

Bowman CR, Iwashita T, Zeithamova D. 2020. Tracking prototype and exemplar representations in
the brain across learning. Elife. 9:e59360.
de Voogd LD, Fernández G, Hermans EJ. 2016. Awake reactivation of emotional memory traces
through hippocampal–neocortical interactions. NeuroImage. 134:563-572.
Deng J, Dong W, Socher R, Li L-J, Li K, Fei-Fei L. 2009. Imagenet: A large-scale hierarchical image
database. 2009 IEEE conference on computer vision and pattern recognition. 248-255.
Deuker L, Olligs J, Fell J, Kranz TA, Mormann F, Montag C, Reuter M, Elger CE, Axmacher N. 2013.
Memory consolidation by replay of stimulus-specific neural activity. J Neurosci. 33:19373-19383.
Devereux BJ, Clarke A, Tyler LK. 2018. Integrated deep visual and semantic attractor neural networks
predict fMRI pattern-information along the ventral object processing pathway. Sci Rep. 8:10636.
Drosopoulos S, Windau E, Wagner U, Born J. 2007. Sleep enforces the temporal order in memory.
PLoS One. 2:e376.
Dudai Y. 2012. The restless engram: consolidations never end. Annu Rev Neurosci. 35:227-247.
Eichenlaub J-B, Jarosiewicz B, Saab J, Franco B, Kelemen J, Halgren E, Hochberg LR, Cash SS. 2020.
Replay of learned neural firing sequences during rest in human motor cortex. Cell Rep. 31:107581.
Ekman M, Kok P, de Lange FP. 2017. Time-compressed preplay of anticipated events in human
primary visual cortex. Nat Commun. 8:15276.
Fan Y, Tian F, Qin T, Li X-Y, Liu T-Y. 2018. Learning to teach. arXiv preprint arXiv:180503643.
Fenn KM, Nusbaum HC, Margoliash D. 2003. Consolidation during sleep of perceptual learning of
spoken language. Nature. 425:614-616.
French RM. 1999. Catastrophic forgetting in connectionist networks. Trends Cogn Sci. 3:128-135.

Friedrich M, Wilhelm I, Born J, Friederici AD. 2015. Generalization of word meanings during infant
sleep. Nat Commun. 6:6004.
Girardeau G, Inema I, Buzsáki G. 2017. Reactivations of emotional memory in the hippocampus–
amygdala system during sleep. Nat Neurosci. 20:1634.
Giri B, Miyawaki H, Mizuseki K, Cheng S, Diba K. 2019. Hippocampal reactivation extends for several
hours following novel experience. J Neurosci. 39:866-875.
Giusberti F, Cornoldi C, De Beni R, Massironi M. 1992. Differences in vividness ratings of perceived
and imagined patterns. Br J Psychol. 83:533-547.
Gómez RL, Bootzin RR, Nadel L. 2006. Naps Promote Abstraction in Language-Learning Infants.
Psychol Sci. 17:670-674.
Graveline YM, Wamsley EJ. 2017. The impact of sleep on novel concept learning. Neurobiol Learn
Mem. 141:19-26.
Grossberg S. 2013. Adaptive Resonance Theory: How a brain learns to consciously attend, learn, and
recognize a changing world. Neural Netw. 37:1-47.
Güçlü U, van Gerven MA. 2015. Deep neural networks reveal a gradient in the complexity of neural
representations across the ventral stream. J Neurosci. 35:10005-10014.
Gupta AS, van der Meer MA, Touretzky DS, Redish AD. 2010. Hippocampal replay is not a simple
function of experience. Neuron. 65:695-705.
Ha D, Schmidhuber J. 2018. Recurrent World Models Facilitate Policy Evolution. Adv Neural Inf
Process Syst. 31.
Hassabis D, Kumaran D, Vann SD, Maguire EA. 2007. Patients with hippocampal amnesia cannot
imagine new experiences. Proc Natl Acad Sci USA. 104:1726-1731.
Hayes TL, Krishnan GP, Bazhenov M, Siegelmann HT, Sejnowski TJ, Kanan C. 2021. Replay in Deep
Learning: Current Approaches and Missing Biological Elements. arXiv preprint arXiv:2104.04132.
He K, Zhang X, Ren S, Sun J. Delving deep into rectifiers: Surpassing human-level performance on
imagenet classification. Proc IEEE Int Conf Comput Vis; 2015. 1026-1034.
Hermans EJ, Kanen JW, Tambini A, Fernández G, Davachi L, Phelps EA. 2017. Persistence of
amygdala–hippocampal connectivity and multi-voxel correlation structures during awake rest after
fear learning predicts long-term expression of fear. Cereb Cortex. 27:3028-3041.
Horváth K, Liu S, Plunkett K. 2016. A daytime nap facilitates generalization of word meanings in
young toddlers. Sleep. 39:203-207.
Jafarpour A, Fuentemilla L, Horner AJ, Penny W, Duzel E. 2014. Replay of very early encoding
representations during recollection. J Neurosci. 34:242-248.
Ji D, Wilson MA. 2007. Coordinated memory replay in the visual cortex and hippocampus during
sleep. Nat Neurosci. 10:100-107.
Kemker R, Kanan C. 2017. Fearnet: Brain-inspired model for incremental learning. arXiv preprint
arXiv:171110563.
Khaligh-Razavi SM, Kriegeskorte N. 2014. Deep supervised, but not unsupervised, models may
explain IT cortical representation. PLoS Comput Biol. 10:e1003915.
Kingma DP, Ba J. 2014. Adam: A method for stochastic optimization. arXiv preprint arXiv:14126980.
Kirkpatrick J, Pascanu R, Rabinowitz N, Veness J, Desjardins G, Rusu AA, Milan K, Quan J, Ramalho T,
Grabska-Barwinska A, Hassabis D, Clopath C, Kumaran D, Hadsell R. 2017. Overcoming catastrophic
forgetting in neural networks. Proc Natl Acad Sci USA. 114:3521-3526.
Kuriyama K, Stickgold R, Walker MP. 2004. Sleep-dependent learning and motor-skill complexity.
Learn Mem. 11:705-713.
Lau H, Alger SE, Fishbein W. 2011. Relational memory: A daytime nap facilitates the abstraction of
general concepts. PLoS One. 6:e27139.
Lee SH, Kravitz DJ, Baker CI. 2012. Disentangling visual imagery and perception of real-world objects.
Neuroimage. 59:4064-4073.
Liu Y, Dolan RJ, Kurth-Nelson Z, Behrens TEJ. 2019. Human replay spontaneously reorganizes
experience. Cell. 178:640-652.

Liu Y, Mattar MG, Behrens TEJ, Daw ND, Dolan RJ. 2021. Experience replay is associated with
efficient nonlocal learning. Science. 372:6544.
Love BC, Medin DL. 1998. SUSTAIN: A model of human category learning. Aaai/iaai. 671-676.
Lutz ND, Diekelmann S, Hinse-Stern P, Born J, Rauss K. 2017. Sleep supports the slow abstraction of
gist from visual perceptual memories. Sci Rep. 7:42950.
Manns JR, Hopkins RO, Squire LR. 2003. Semantic memory and the human hippocampus. Neuron.
38:127-133.
Mattar MG, Daw ND. 2018. Prioritized memory access explains planning and hippocampal replay.
Nat Neurosci. 21:1609-1617.
McDevitt EA, Duggan KA, Mednick SC. 2015. REM sleep rescues learning from interference. Learn
Mem. 122:51-62.
McGaugh JL. 2000. Memory- a century of consolidation. Science. 287:248-251.
Michelmann S, Staresina BP, Bowman H, Hanslmayr S. 2019. Speed of time-compressed forward
replay flexibly changes in human episodic memory. Nat Hum Behav. 3:143-154.
Momennejad I, Otto AR, Daw ND, Norman KA. 2018. Offline replay supports planning in human
reinforcement learning. Elife. 7:e32548.
Peyrache A, Khamassi M, Benchenane K, Wiener SI, Battaglia FP. 2009. Replay of rule-learning
related neural patterns in the prefrontal cortex during sleep. Nat Neurosci. 12:919-926.
Poe GR, Nitz DA, McNaughton BL, Barnes CA. 2000. Experience-dependent phase-reversal of
hippocampal neuron firing during REM sleep. Brain Res. 855:176-180.
Remy P. 2020. Keract: A library for visualizing activations and gradients. GitHub repository.
Richards BA, Lillicrap TP, Beaudoin P, Bengio Y, Bogacz R, Christensen A, Clopath C, Costa RP, de
Berker A, Ganguli S, Gillon CJ, Hafner D, Kepecs A, Kriegeskorte N, Latham P, Lindsay GW, Miller KD,
Naud R, Pack CC, Poirazi P, Roelfsema P, Sacramento J, Saxe A, Scellier B, Schapiro AC, Senn W,
Wayne G, Yamins D, Zenke F, Zylberberg J, Therien D, Kording KP. 2019. A deep learning framework
for neuroscience. Nat Neurosci. 22:1761-1770.
Robins A. 1995. Catastrophic Forgetting, Rehearsal and Pseudorehearsal. Connect Sci. 7:123-146.
Rothschild G, Eban E, Frank LM. 2017. A cortical-hippocampal-cortical loop of information processing
during memory consolidation. Nat Neurosci. 20:251-259.
Russakovsky O, Deng J, Su H, Krause J, Satheesh S, Ma S, Huang Z, Karpathy A, Khosla A, Bernstein M,
Berg AC, Fei-Fei L. 2015. ImageNet large scale visual recognition challenge. Int J Comput Vis.
115:211-252.
Schapiro AC, McDevitt EA, Chen L, Norman KA, Mednick SC, Rogers TT. 2017. Sleep benefits memory
for semantic category structure while preserving exemplar-specific information. Sci Rep. 7:14869.
Schapiro AC, McDevitt EA, Rogers TT, Mednick SC, Norman KA. 2018. Human hippocampal replay
during rest prioritizes weakly learned information and predicts memory performance. Nat Commun.
9:3920.
Schönauer M, Alizadeh S, Jamalabadi H, Abraham A, Pawlizki A, Gais S. 2017. Decoding material-
specific memory reprocessing during sleep in humans. Nat Commun. 8:15404.
Schrimpf M, Kubilius J, Hong H, Majaj NJ, Rajalingham R, Issa EB, Kar K, Bashivan P, Prescott-Roy J,
Schmidt K, Yamins DLK, DiCarlo JJ. 2018. Brain-Score: Which artificial neural network for object
recognition is most brain-like? bioRxiv.407007.
Schwartenbeck P, Baram A, Liu Y, Mark S, Muller T, Dolan R, Botvinick M, Kurth-Nelson Z, Behrens T.
2021. Generative replay for compositional visual understanding in the prefrontal-hippocampal
circuit. bioRxiv.2021.2006.2006.447249.
Simonyan K, Zisserman A. 2014. Very deep convolutional networks for large-scale image recognition.
arXiv preprint arXiv:14091556.
Squire LR, Alvarez P. 1995. Retrograde amnesia and memory consolidation: a neurobiological
perspective. Curr Opin Neurobiol. 5:169-177.
Srivastava N, Hinton G, Krizhevsky A, Sutskever I, Salakhutdinov R. 2014. Dropout: a simple way to
prevent neural networks from overfitting. J Mach Learn Res. 15:1929-1958.

Staresina BP, Alink A, Kriegeskorte N, Henson RN. 2013. Awake reactivation predicts memory in
humans. Proc Natl Acad Sci U S A. 110:21159-21164.
Sweegers CCG, Talamini LM. 2014. Generalization from episodic memories across time: A route for
semantic knowledge acquisition. Cortex. 59:49-61.
Tambini A, Davachi L. 2013. Persistence of hippocampal multivoxel patterns into postencoding rest is
related to memory. Proc Natl Acad Sci USA. 110:19591-19596.
Tambini A, Ketz N, Davachi L. 2010. Enhanced brain correlations during rest are related to memory
for recent experiences. Neuron. 65:280-290.
van de Ven GM, Siegelmann HT, Tolias AS. 2020. Brain-inspired replay for continual learning with
artificial neural networks. Nat Commun. 11:4069.
Wilson MA, McNaughton BL. 1994. Reactivation of hippocampal ensemble memories during sleep.
Science. 265:676-679.
Wimmer GE, Liu Y, Vehar N, Behrens TEJ, Dolan RJ. 2020. Episodic memory retrieval success is
associated with rapid replay of episode content. Nat Neurosci. 23:1025-1033.
Winocur G, Moscovitch M. 2011. Memory transformation and systems consolidation. J Int
Neuropsychol Soc. 17:766-780.
Wittkuhn L, Schuck NW. 2021. Dynamics of fMRI patterns reflect sub-second activation sequences
and reveal replay in human visual cortex. Nat Commun. 12:1795.
Xu Y, Vaziri-Pashkam M. 2021. Limits to visual representational correspondence between
convolutional neural networks and the human brain. Nat Commun. 12:2065.
Zhang H, Fell J, Axmacher N. 2018. Electrophysiological mechanisms of human memory
consolidation. Nat Commun. 9:4103.

Supplementary Fig 1. Samples of real and generated activations from different layers in the network, displayed as greyscale images. The first filters where information was visible is displayed.

Supplementary Fig 2. Generalisation performance improvement over baseline for replay from layer four when downsampled by a factor of seven.

827   Supplementary table 1: List of ImageNet classes by model

Model 1	n12360108 begonia
	n02822579 bedstead bedframe
	n02427724 waterbuck
	n03098688 control room
	n02944075 camisole
	n01603600 waxwing
	n03196598 digital display alphanumeric display
	n02848216 blade
	n07712856 tortilla chip
	n03592669 jalousie
Model 2	n11853356 Christmas cactus Schlumbergera buckleyi Schlumbergera baridgesii
	n04177820 settle settee
	n03904183 pedestrian crossing zebra crossing
	n04355511 sundress
	n03487444 hand lotion
	n12899752 angel's trumpet Brugmansia suaveolens Datura suaveolens
	n12655869 raspberry raspberry bush
	n12948053 common European dogwood red dogwood blood-twig pedwood Cornus sanguinea
	n02869737 bongo bongo drum
	n02415253 Dall sheep Dall's sheep white sheep Ovis montana dalli
Model 3	n03375575 foil
	n03082807 compressor
	n03262932 easy chair lounge chair overstuffed chair
	n02047614 puffin
	n03317788 faience
	n09475044 wasp's nest wasps' nest hornet's nest hornets' nest
	n11784497 jack-in-the-pulpit Indian turnip wake-robin Arisaema triphyllum Arisaema atrorubens
	n03941231 pinata
	n02813399 bay window bow window
	n04544325 wainscoting wainscotting
Model 4	n03993053 potty seat potty chair
	n04082886 reticle reticule graticule
	n03421324 garter belt suspender belt
	n03766044 miller milling machine
	n03505504 headscarf
	n12384839 love-in-a-mist running pop wild water lemon Passiflora foetida
	n03619793 kitbag kit bag
	n07600696 candied apple candy apple taffy apple caramel apple toffee apple
	n02068974 dolphin
	n03237992 dressing gown robe-de-chambre lounging robe
Model 5	n02918964 bumper car Dodgem
	n02392824 white rhinoceros Ceratotherium simum Diceros simus

	n01806364 blue peafowl Pavo cristatus
	n02956699 capitol
	n04290079 spun yarn
	n08596076 littoral litoral littoral zone sands
	n02887970 bracelet bangle
	n10635788 sphinx
	n07901457 muscat muscatel muscadel muscadelle
	n07870167 lasagna lasagne
Model 6	n04324387 stockroom stock room
	n04591517 wind turbine
	n02988486 CD-R compact disc recordable CD-WO compact disc write-once
	n04568069 weathervane weather vane vane wind vane
	n04514241 uplift
	n03207835 dishtowel dish towel tea towel
	n13206817 maidenhair maidenhair fern
	n03307792 external drive
	n12666965 cape jasmine cape jessamine Gardenia jasminoides Gardenia augusta
	n12950126 valerian
Model 7	n03986355 portfolio
	n11848479 night-blooming cereus
	n04439712 tinfoil tin foil
	n03160740 damask
	n01612122 sparrow hawk American kestrel kestrel Falco sparverius
	n09206896 arroyo
	n12392549 stinging nettle Urtica dioica
	n02343772 gerbil gerbille
	n07875436 risotto Italian rice
	n02060133 fulmar fulmar petrel Fulmarus glacialis
Model 8	n03655072 legging leging leg covering
	n10738111 unicyclist
	n09270735 dune sand dune
	n03409393 gable gable end gable wall
	n02331046 rat
	n03452267 gramophone acoustic gramophone
	n10105733 forward
	n07911677 cocktail
	n03797182 muffler
	n01563128 warbler
Model 9	n04197110 shipwreck
	n10470779 priest
	n02769290 backhoe
	n03478756 hall
	n04519153 valve
	n04289027 sprinkler
	n02782778 ballpark park

	n03558404 ice skate
	n04138261 satin
	n02700064 alternator
Model 10	n03524150 hockey stick
	n03716966 mandolin
	n02962200 carburetor carburettor
	n03237340 dresser
	n04004210 printed circuit
	n02917377 bullhorn loud hailer loud-hailer
	n07879953 tempura
	n04087826 ribbing
	n02404432 longhorn Texas longhorn
	n07830593 hot sauce

828
829

847 Supplementary table 2: Conceptually similar classes (plants)

Model 1 (1)	n12360108 begonia
Model 2 (1)	n11853356 Christmas cactus Schlumbergera buckleyi Schlumbergera baridgesii
Model 2 (6)	n12899752 angel's trumpet Brugmansia suaveolens Datura suaveolens
Model 2 (8)	n12948053 common European dogwood red dogwood blood-twig pedwood Cornus sanguinea
Model 4 (6)	n12384839 love-in-a-mist running pop wild water lemon Passiflora foetida
Model 6 (7)	n13206817 maidenhair maidenhair fern
Model 6 (9)	n12666965 cape jasmine cape jessamine Gardenia jasminoides Gardenia augusta
Model 6 (10)	n12950126 valerian
Model 7 (2)	n11848479 night-blooming cereus
Model 7 (7)	n12392549 stinging nettle Urtica dioica

848
849