Perceptual clustering in auditory streaming

Nathanael Larigaldie[1,2], Tim Yates[3], Ulrik R. Beierholm[1*]

*For correspondence:
ulrik.beierholm@durham.ac.uk (URB)

[1]Durham University, UK; [2]Aarhus University, DK; [3]University of Birmingham, UK

Abstract

Perception is dependent on the ability to separate stimuli from different objects and causes in order to perform inference and further processing. We have models of how the human brain can perform such causal inference for simple binary stimuli (e.g., auditory and visual), but the complexity of the models increases dramatically with more than two stimuli. To characterize human perception with more complex stimuli, we developed a Bayesian inference model that takes into account a potentially unlimited number of stimulus sources: it is general enough to factor in any discrete sequential cues from any modality. Because the model employs a non-parametric prior, increased signal complexity does not necessitate the addition of more parameters. The model not only predicts the number of possible sources, but also specifies the source with which each signal is associated. As a test case, we demonstrate that such a model can explain several phenomena in the auditory stream perception literature, that it provides an excellent fit to experimental data, and that it makes novel predictions that we experimentally confirm. These findings have implications not just for human auditory temporal perception, but for a wide range of perceptual phenomena across unisensory and multisensory stimuli.

Introduction

Ambiguity in perceptual systems is a blight for inference. When we hear two sounds sequentially, we may infer that they came from two different sources, e.g. birds A and B, or the same source repeated. A third sound is heard: Are the generating sources AAA, AAB, ABA, ABB, or ABC (see Fig. 1 for the possible generative models)? By the time four, five and six sounds are heard the number of possible combinations reaches 15, 52, and 858. The ambiguity breeds to generate a combinatorial explosion, and yet the human auditory system is able to reliably allocate multiple sources of sound in complex, real-world situations. The characteristics of the signal are consistently associated with different sources, allowing us to keep track of a speaker's voice and the wail of an ambulance siren, separate from the noise of background traffic and falling rain.

Inferring the generative model that caused the observed stimuli is a general problem faced by the perceptual system. To perform such a task for simple stimuli the brain relies on causal inference (*Körding et al., 2007*; *Shams and Beierholm, 2010*), probabilistically estimating the most likely cause of the stimuli in the environment. This has been shown to be a good model of perceptual inference for ambiguous stimuli, when they are in small numbers, i.e. two. However, increasing the number of stimuli causes the complexity of possible generative structures to rapidly increase (Fig. 1), rendering a causal inference strategy that relies on enumerating all possible structures impossible.

However, an important realisation is that, given a specific set of a large number of stimuli, this process is essentially one of *clustering*, combining together stimuli that are similar while keeping separate from those dissimilar. This idea that perception involves clustering has a long history in the literature of Gestalt psychology, although not always expressed in those terms (*Wagemans et al., 2012*). However, the brain would need to choose the right number of clusters and have a way to specify the prior expectations over clusters, which is difficult before even knowing the number of stimuli.

Figure 1. a) Graphical illustration of clustering problem in causal inference. As the number of stimuli increases $(1, 2, 3, 4, ...)$ the number (C) of potential causes increases at the same rate, while the number of combinations of causes that could have generated the stimuli increases according to the number of ways to partition a set of n objects into k nonempty subsets. It is easy to differentiate between the two potential generative structures when there are only two stimuli, but much harder when four stimuli can be created from fifteen different generative structures. b) Example of auditory tones being segregated into one or two streams, using 'galloping' stimuli similar to (**van Noorden, 1975**). c) Example of a series of potential stimuli with a representative assignment of tones to the streams below. As each tone is presented, the observer reassigns the entire set of tones to streams $(1-> 12-> 123$ etc.). The brain has to decide how to assign each tone into an unknown number of streams, a type of clustering problem.

The key proposal in this paper is that the brain can perform this clustering process using a modern version of 'Occam's Razor', *non-parametric Bayesian clustering*. With this approach the numbers of clusters do not have to be pre-specified, instead the algorithm adapts the number of clusters to the data. Likewise, there is no need for a large number of parameters to specify the prior expectations, instead a single meta-parameter specifies the degree of clustering. Individual data points (stimuli) are assigned to different groups (or clusters) based on the other existing data points. This type of algorithm is renown for allowing the complexity of the model to grow with the data set (*Aldous, 1985*; *Ghahramani, 2013*) as a larger number of clusters can emerge as the number of data points increases.

Non-parametric Bayesian inference has previously been used in cognitive and perceptual studies (*Froyen et al., 2015*; *Gershman and Niv, 2013*), but not to study the segmentation of perceptual cues.

To exemplify how human perception of large number of sources can be modeled by non-parametric Bayesian inference, we will present modeling and experimental results on auditory stream segregation.

Auditory stream segregation

For several decades, the human ability to segregate sequential sounds into streams corresponding to sources has been investigated using simple sequences of either pure tones or more complex sounds (reviewed in *Moore and Gockel* (*2012*)). The time interval between tones, their pitch difference and the duration of a sequence are among the factors that play an important role (*Anstis and Saida, 1985*; *Bregman and Campbell, 1971*; *van Noorden, 1975*): explanations of how the factors are used based on principles such as Gestalt laws and Occam's razor have been incorporated into the conceptual model of Bregman (*Bregman, 1994*).

Descriptive models based on peripheral excitation (*Beauvois and Meddis, 1997*), coherence of coupled oscillators (*Wang, 1996*) and cortical streaming modules (*McCabe and Denham, 1997*) provide mechanisms to estimate the number of streams, but do not specify which sound is associated with which source. While some of the models are expandable to allow more sources to be inferred, it is not known if they would cope with the combinatorial explosion. Furthermore, Moore and Gockel (*Moore and Gockel, 2002*) conclude from an extensive review of the literature that any sufficiently salient factor can induce stream segregation. This indicates that a more general model of inference is needed, that can incorporate any auditory perceptual cue and multiple sounds with different sources.

If ambiguity is a blight for inference, regularities in natural signals are the cure. Not all combinations of signal sources are equally likely – when perceptual systems generate a model of the world, we assume that they infer the most likely interpretation because the perceptual systems are optimized to the statistics of natural signals (*Barlow, 1961*; *McDermott and Simoncelli, 2011*). Bayesian inference has had considerable success in modeling many visual and multi-sensory percepts as a generative, probabilistic process (*Shams et al., 2005*; *Weiss et al., 2002*; *Beierholm, 2015*). Despite these successes, we still have no general, principled model of how the auditory system solves the source inference problem.

A Bayesian approach to auditory stream segregation (based on sequential sampling) has been used to model the dynamics of perceptual bistability (*Lee and Habibi, 2009*) but assumes that only two percepts are possible. Turner (*Turner, 2010*) has developed methods of analyzing statistics of sounds based on Bayesian inference, and constructed a model to synthesize realistic auditory textures. While inference in the model can qualitatively replicate many known auditory grouping rules, the expected number of sources in the environment has to be specified. In a natural scenario an observer would have to infer the number of sources that are present in the environment due to the inherent uncertainty.

In our model the probability of many alternative stream configurations (given the input signal) are calculated and the percept generated corresponds to the most probable configuration. The

probabilities are calculated using Bayes' rule to combine the likelihood of generating a signal given a postulated stream configuration, with the prior probability of sounds being associated with different sources. The likelihood and prior probability distributions are iteratively updated in a principled manner as information accumulates.

The forms of the distributions are presumably optimized to natural signal statistics: the likelihood distribution we use is based on consideration of the physical limitations of oscillators. However, the framework of the model allows formulations of multiple explanatory factors, such as those determined by Bregman (*Bregman, 1994*) from psychophysics experiments, to be simply incorporated in the distributions. Furthermore, while the current study uses simple pure tones (replicating work by Bregman), the framework allows more complex cues from audition and other modalities to be used as long as their perceptual difference can be quantified.

Model

Pure tones are the indivisible atoms of input to the model – each being assigned to just one sound source, or stream. Inspired by the work done on non-parametric priors (*Froyen et al., 2015*; *Orbanz and Teh, 2010*; *Wood et al., 2006*) we assume the existence of an infinite number of potential sources, leading to a sequence of *tones* with pitch f_1, f_2..., onset time t_1^{on}, t_2^{on}... and an offset time, t_1^{off}, t_2^{off} ... and the sound sources/streams that generated the tones are denoted by positive integers S_1, S_2... We rename the sources when necessary so that the first tone heard will always be generated by source 1 (i.e. $S_1 = 1$), and a subsequent ith tone can be associated with source $[1 : max(S_1...S_{i-1}) + 1]$.

Generative model

Given a source S_i we assume that the frequency of tone i is governed by physical constraints and statistical regularities of the source. If two sequential sounds with the frequencies f_{i-1} and f_i are produced by the same source, $S_i = S_{i-1}$, the pitch cannot change at an infinitely fast rate: to make an oscillator change its frequency discontinuously would require an infinite impulse of energy. We assume that, all things being equal, a pure tone sound source is most likely to continue oscillating at the same frequency as it has in the past, and the probability decreases with $\Delta f = f_i - f_{i-1}$ but increases with $\Delta t = (t_i^{on} - t_{i-1}^{off})$. More specifically we assume a normal probability distribution:

$$p(f_i, t_i^{on}|S_i = S_{i-1}, f_{i-1}, t_{i-1}^{off}) = \frac{1}{\sqrt{2\pi\sigma^2}} exp^{-\frac{\left(\frac{\Delta f}{\Delta t}\right)^2}{2\sigma^2}} \tag{1}$$

where σ is a constant. We here assume that the observer has a perfect noise free access to the generated auditory frequencies.

For successive sources, we assume that sources that have been active previously are more likely to be active again, but do not provide a limit to the number of sources that N tones can be generated from. Concretely we assign the probability of a source j generating the ith tone according to a Chinese Restaurant Process (CRP; *Aldous* (*1985*)), which can be considered as an extension of Occam's rule. If the number of tones previously assigned to source $j = S_i$ is given by $n_i = \sum_{k=1}^{i-1} \delta(S_i - S_k)$ then

$$p(S_i = j|S_1...S_{i-1}) = \frac{n_i}{(i-1+\alpha)} \qquad\qquad \text{if } n_i > 0 \tag{2}$$

$$p(S_i = j|S_1...S_{i-1}) = \frac{\alpha}{(i-1+\alpha)} \qquad\qquad \text{if } n_i = 0 \tag{3}$$

and where δ is the discrete Kronecker delta function ($\delta(0) = 1$, but 0 elsewhere). Intuitively, the more tones have already been assigned to a source, the more likely that tone i will also be assigned to it ("rich-get-richer" scheme).

134 **Inference**

The task of the observer is to infer the sources generating each of the tones, i.e. to find the se-
quence $S_1 S_2 S_3 ...$ that maximize $p(S_1 S_2 S_3 ... | f_1 f_2 f_3 ..., t_1^{on} t_2^{on} t_3^{on} ..., t_1^{off} t_2^{off} t_3^{off} ...)$, as illustrated in Fig-
ure 1. For simplicity of writing we will refer to the properties of tone i as t_i in place of the set
$(f_i, t_i^{on}, t_i^{off})$

As an example, we use a sequence of three tones t_1, t_2, t_3, for which the observer wishes to
infer the likely sources S_1, S_2, S_3. Thus the probability $p(S_1, S_2, S_3 | t_1, t_2, t_3)$ that a sequence of three
tones was generated by sources S_1, S_2, S_3, has to be calculated over the five possible combinations:
$[S_1 = 1, S_2 = 1, S_3 = 1]$, $[S_1 = 1, S_2 = 1, S_3 = 2]$, $[S_1 = 1, S_2 = 2, S_3 = 1]$, $[S_1 = 1, S_2 = 2, S_3 = 2]$,
$[S_1 = 1, S_2 = 2, S_3 = 3]$ corresponding to the five unique configurations of sources generating
three sounds. Note that the first source is always assigned the value 1, the next different source
is assigned 2, etc.

Bayes' rule relates each conditional probability (posterior distribution) to the likelihood
$p(t_1, t_2, t_3 | S_1, S_2, S_3)$ of each configuration of sound sources generating the sequence of tones, by

$$p(S_1, S_2, S_3 | t_1, t_2, t_3) = \frac{p(t_1, t_2, t_3 | S_1, S_2, S_3) * p(S_1, S_2, S_3)}{Z} \tag{4}$$

where Z is a normalization constant, and $p(S_1, S_2, S_3)$ is the prior probability of the particular config-
uration of sound sources, regardless of the frequency, etc. of the tones. In this form the equation
states that the posterior depends on the joint likelihood of all the tones, multiplied by the joint prior
over all sources. This is not always the most convenient way to formulate it, and we can instead
write it in a manner that updates posteriors as each new tone arrives.

Assuming conditional independence of the tones and tone-source causality, the posterior can
be rewritten as

$$
\begin{aligned}
p(S_1, S_2, S_3 | t_1, t_2, t_3) =& p(S_3 | S_2, S_3, t_1, t_2, t_3) * p(S_1, S_2 | t_1, t_2, t_3) \\
=& \frac{p(t_3 | S_1, S_2, S_3, t_1, t_2)}{p(t_3)} * p(S_3 | S_2, S_3, t_1, t_2) * p(S_1, S_2 | t_1, t_2, t_3) \\
=& \frac{p(t_3 | S_1, S_2, S_3, t_1, t_2)}{p(t_3)} * p(S_3 | S_1, S_2) * p(S_1, S_2 | t_1, t_2)
\end{aligned} \tag{5}
$$

The final term is the posterior generated from the first two tones. The latter two terms can be
considered together as the prior for the third source, allowing us to use an iterative approach to the
inference. After each tone we grow the tree of possible source sequence (e.g. $11 \rightarrow 111$ and 112), by
multiplying the previous posterior $p(S_1, S_2 | t_1, t_2)$ with two terms; the likelihood $p(t_3 | S_1, S_2, S_3, t_1, t_2)$
and a prior for how likely the next 'branch' is, $p(S_3 | S_1, S_2)$., which is the CRP presented above.

We now consider how to determine the likelihood and prior probabilities. The first source can
only be associated with one source, so $p(S_1 = 1) = 1$. The principle of Occam's razor would suggest
that $p(S_1 = 1, S_2 = 1) > p(S_1 = 1, S_2 = 2)$, i.e. if we haven't heard any of the sounds, the most
probable acoustic scene is the simplest one: all sounds come from the same source. The value
of $p(S_1 = 1, S_2 = 1)$ for an individual can be determined from fitting their data, and the value
$p(S_1 = 1, S_2 = 2)$ is simply $1 - p(S_1 = 1, S_2 = 1)$. The values may depend on factors such as the
environment, which are not considered in the model: natural signal statistics may provide guidance
for how the prior probabilities are assigned.

Regarding the likelihood function, for new tone i the observer assumes the generative proba-
bility $p(t_i | S_i, t_{i-k}, S_i = S_{i-k})$, where tone $i - k$ was the latest tone inside stream S_i. Note that this
applies even when the sounds generated by the same source are separated by one or more sounds
associated with different sources (e.g., $(S_1 = 1, S_2 = 2, S_3 = 1)$). The only transition that matters
is that between the most recent tone and the last tone in the same stream, so if three tones t_1,
t_2 and t_3 had all been associated with the same stream (e.g. $(S_1 = 1, S_2 = 1, S_3 = 1)$), we would
only consider the transition from t_2 to t_3, whereas if t_2 was associated with a different stream (e.g.
$(S_1 = 1, S_2 = 2, S_3 = 1)$), we would only consider the transition from t_1 to t_3.

If a sound comes from a new source, then we assume that the likelihood is independent of previous tones:

$$p(t_i | S_1 \neq S_i, S_2 \neq S_i, \ldots S_{i-1} \neq S_i) = \frac{1}{\sqrt{2\pi\sigma^2}} exp^{-\frac{(f_i - f_0)^2}{2\sigma^2}} \tag{6}$$

where f_0 is the midpoint of the range of auditory tones presented for the trial (the model is insensitive as to whether the mean is chosen instead).

Figure 2 summarizes the main properties of the model. The final model has two parameters, α and σ, plus a parameter for the steepness of the response variability (given by softmax function) for each subject β. For details of implementation of the model, see the Methods section.

Figure 2. Examples of the likelihood function and CRP prior for a 4th tone given that previous tones $[t_1, t_2, t_3]$ were generated by sources $[S_1 = 1, S_2 = 1, S_3 = 2]$. This figure illustrates how $\Delta t = (t_i^{on} - t_{i-1}^{off})$ influences the probability of a tone being generated by different sources (as time distance increases, so does the capacity of the source to significantly change its oscillation frequency). It also shows how the CRP prior implements Occam's Razor by penalizing the probability of a new cluster, and has a "rich gets richer" property by favouring more populated clusters.

Results

To evaluate the performance of the model, we made qualitative comparisons with studies in the literature and quantitative comparison with experimental data. We furthermore tested a prediction from the model using a novel experimental paradigm.

Modeling

Time and frequency

A well-known basic stream segregation phenomena (e.g. *Bregman and Campbell* (*1971*)) shows that increasing the speed at which auditory tones increases the probability that tones are perceived as coming from separate streams. To examine this in the model we recreate the second experiment of Bregman and Campbell (*Bregman and Campbell, 1971*), showing in Fig. 3a-b that while a sequence of six slowly presented tones is assigned a low posterior probability of originating from different sources (and should therefore be assigned the same stream), as the speed of presentation is increased the probability of originating from two sources increases drastically (implying subjects should segregate the streams). Likewise, separation by frequency causes the clustering of tones to be more difficult. As an example, in *van Noorden* (*1975*) tones close together in frequency are perceived as one stream, whereas tones farther apart are split in two. This is replicated by the model (Fig. 3c-d) which assigns a high probability to the lower and higher tones coming from separate sources, and thus assigns them to separate streams (see also Galloping below).

Figure 3. a-d) Stimuli used in experiments from (*Bregman and Campbell, 1971*) (second experiment), highlighting how the speed of presentation affects perception of streams of tones. Stimuli are shown at the top, bottom are dendrogram tree-plots based on the posterior distribution over clustering. A unique colour is assigned to clusters with more than 50 percent distance from other clusters. a) Slow sequence, ISI 100 ms, tone duration 500 ms, pitch difference [0 4 8 26 30 34] semi-tones, tone sequence repeated twice. The posterior mode (the sequence combination with the highest posterior probability) was 111111, i.e. all tones assigned to the same stream. b) Fast sequence, ISI 100ms, tone duration 100 ms (posterior mode 121212). c-d) Example of a galloping stream, from (*van Noorden, 1975*), highlighting effect of frequency differences. c) ISI 26.6ms, pitch difference 6 semi-tones (posterior mode 111) d) ISI 26.6ms, pitch difference 20 semi-tones (posterior mode 121). Parameters for this figure (and subsequent figures) were $\alpha = 1.44$, $\sigma = 40$.

Cumulative

The galloping sequence Low-High-Low has also been used to highlight the effect of the accumulation of information (Fig. 4). Bregman (*Bregman, 1978b*) showed that a short sequence of tones tends to lead to the percept of a single stream, whereas the accumulation of information causes the tones to segregate into two streams. For the model, this effect is due to the non-parametric

prior initially assigning a low probability to the possibility of two streams, before more information is gathered.

Figure 4. a-b) Stimuli used in experiments from Bregman (***Bregman, 1978b***), highlighting the cumulative effect of tones. Stimuli are shown at the top, and at the bottom are dendrogram tree-plots based on the posterior distribution over clustering. A unique colour is assigned to clusters with more than 50 percent distance from other clusters. a) Short sequence ISI 26.6ms, pitch difference 7 semi-tones, tone sequence repeated twice (posterior mode 111). b) Long sequence ISI 26.6ms, pitch difference 7 semi-tones, tone sequence repeated eight times (posterior mode 121). c-d) Context matters for the clustering of tones. c) Two low tones , two high tones, leading to low tones segregated from high tones (posterior mode 1122); d) While the two low tones have been kept constant, the context of the two other tones now causes them to be clustered separately with the other tones (posterior mode 1212). Long sequence ISI 26.6ms, tone sequence repeated eight times. The modeling parameters were the same as in Fig. 3

Context

An aspect of auditory perception that especially received attention from the Gestalt movement was the role of context in auditory clustering. Experiments done by (***Bregman, 1978a***) showed that modifying the context in which tones were presented modified the segregation of unmodified tones. Figure 4 shows an example, based on (***Bregman, 1978a***), where two low tones will be clustered together while two distractor tones are far off in frequency, but will be clustered separately as the distractor tones are placed around them. The model replicates this phenomena, showing a separation of the first two tones in Fig 4c-d.

Crossing

As shown by Tougas and Bregman (***Tougas and Bregman, 1985***) interleaving a decreasing and increasing series of tones gives the illusory percept of the two streams 'bouncing' i.e. the lower set of tones are clustered and segregated from the higher set of tones. Figure 5 recreates this experiment with 2 x 10 interleaved decreasing and increasing tones. The model recreates the perceptual phenomenon, with the lower frequency tones grouped together, separate from the higher frequency tones, thus implying a perceived 'bounce'.

Figure 5. Interleaved increasing (uneven numbered tones) and decreasing (even numbered tones) series of tones, ISI 26.6ms. Same as for human observer the model assigns higher value to a 'bouncing' percept, where tones [2 4 6 8 10] are clustered together with [13 15 17 19].Modeling parameters were the same as in Fig 3

Galloping effect

Several studies have shown how the effect of frequency and time can interact. Van Norden (***van Noorden, 1975***) found that in a repeating low-high-low sequence of tones (see Fig. 3), subjects would report one or two streams as a function of both the difference in auditory frequency and the speed of presentation (interstimulus interval). In our computational model (see Fig. 2) the likelihood term directly depends on both of these factors, and the prior probability again constrains the observer from segregating tones into more streams. We replicate the results of this study in Experiment 1 below.

Overall, the model is able to recreate several phenomena in the experimental literature.

Experiment 1

To quantitatively compare the model with human performance, we conducted a psychophysics experiment, in which 15 participants with normal hearing listened to simple auditory sequences and performed a subjective judgment task (a variant of the galloping experiment (***van Noorden, 1975***), see Figure 3). Given a sequence of Low-High-Low tones, subjects would respond whether they perceived one or two streams. Across trials, the separation between low and high tones, and the inter-stimulus-interval, were varied (see Methods for details).

Model performance and comparison

As an example, response data from six subjects is shown in Figure 6b. As expected, when the ISI was short or when the difference in frequency was large, subjects were more likely to report two streams than one. Figure 6 also shows the fit of the model for one participant.

Figure 6. a) Model fit, based on fitted parameters from subject 8, giving the fraction of trials in which the participant responded '2' for the number of streams perceived. Axes give the pitch difference for the middle tone and the inter stimulus interval (ISI): the time between the offset of one tone and the onset of the next. b) The behavioural results from 6 subjects. c) Model performance on experiment 1 in terms of Evidence Lower Bound (ELBO) for each subject with the CRP model (dark blue), alternative A (red), alternative B (yellow), and alternative C (purple). The black dotted line indicates the performance of a purely random model that assigns 0.5 probability to either response for every condition. Subjects are ordered based on CRP model ELBO values.

While visually the model approximates the subject behaviour, we used model-comparison to rule out other hypotheses.

The model with the non-parametric prior was compared against three alternatives that used different priors to constrain the number of possible streams:

A. When the stream combination comprised only one stream (repeated), the prior probability of the next stream being 1 or 2 was allocated according to the CRP, but if the combination already contained two streams, the prior probability of allocating stream 1 or 2 was simply the fraction of previous tones that were allocated to stream 1 or 2 respectively.

B. The prior probabilities of a new tone being allocated to stream 1 or stream 2 were given by P1 and 1-P1, respectively, where P1 is a fixed parameter.

C. Prior probabilities that a new tone was assigned to stream 1 or 2 were fixed at 0.5.

For model comparison (and fitting) we used the Evidence Lower Bound, as implemented in the
VBMC package (*Acerbi, 2020*). The Bayesian model with the non-parametric process prior gives
a better fit (larger ELBO) than all the alternatives considered for every subject, with a protected
exceedance probability (*Rigoux et al., 2014*) of $p < 0.001$ for the other three models. The mean $\pm$
SEM of the optimised parameters for the unconstrained model are $\alpha = 4.68 \pm 0.23$ (equivalently
$P(11) = 0.184 \pm 0.010$) and $\sigma = 107.4 \pm 6.8$ [semitones/sec].

Experiment 2

While the model above theoretically allows an unlimited number of tones to be segregated into an
unrestricted number of streams, Experiment 1 (presented above) only allows a repeated sequence
of 3 tones to be separated into 1 or 2 streams. However, both the model and the ASA literature
predict that subjects should generally segregate based on the frequency and temporal distance
between tones with a possibly infinite number of streams. To test this further, we performed
a novel follow-up experiment in a broader auditory environment. The experimental setting was
inspired by Barsz (*Barsz, 1988*) and was specifically designed to allow three streams to emerge and
to replace the explicit measure of stream segregation by an implicit one (see Methods for details).
Participants were asked to judge if two consecutive melodies comprised of 4 repeated tones
were similar or different. In every condition, 1 tone was considered to be in the low frequency
range, 2 tones in the medium range, and 1 tone in the high range. According to previous exper-
iments showing that order information is intact when tones are inside the same stream but lost
when segregated into different streams (*Bregman and Campbell, 1971*; *Demany, 1982*; *Barsz, 1988*),
if medium tones were to be part of a stream excluding low and high tones, participants should be
unable to detect the difference between two sequences if only medium tones were inverted. Thus,
subjects should only be able to detect the inversion of the middle tones if the tones are placed
in the same stream as the upper or lower stream (hence all tones clustered into 1 or 2 groups).
Conditions were created with varying discrepancies between frequency ranges (ISIs were kept con-
stant for this experiment). See Figure 9 for a schematic representation of a typical stimulus with
inversion.
As our model predicts that the probability of being assigned to different streams is dependent
on the frequency difference, our first prediction is that participants should have a reasonable de-
gree of performance in detecting a difference between two melodies when the medium tones are
inverted and there is only a small frequency difference between those medium tones and at least
one of the high and low tones. This would reflect the fact that medium tones are in a stream that
also includes other tones. Conversely, our other prediction is that as the frequency difference in-
creases, participants should perform significantly worse at detecting the medium tone inversion.
This would reflect the fact that medium tones are in a stream that does not include other tones.
This is in contrast to any model that only allows two streams (such as models B and C above),
according to which large frequency difference should not lead to any decrement in performance.

Analysis preparation

Individual responses for perceived differences between sequences were transformed into D-prime
scores ($d' = Z(HR) - Z(FA)$ where Z is the inverse of the normal cumulative distribution function,
HR is the hit rate and FA the false alarm rate) to obtain a single measure of signal detection for each
pair of frequency differences, while taking into account possible response biases. Two participants
with a negative D-prime score in the easiest condition (*3-3*) were considered unable to perform the
task correctly and were therefore excluded from further analysis, leaving a total of 24 participants.
No data was missing from the data set. A one-way repeated measures ANOVA was conducted on
these D-prime scores, with frequency differences (*3-3* vs. *3-9* vs. *3-15* vs. *9-9* vs. *9-15* vs. *15-15*) as
the only within-subject factor, along with seven subsequent paired-sample t-tests in line with our
hypotheses.

Data analysis

Although inferential statistical tests were conducted only on D-prime scores, table 1 also includes the summary statistics of the proportions of "similar" responses in every experimental condition.

One-way repeated measures ANOVA (frequency differences) showed that D-prime scores differed as a function of this factor [F(5,115)=6.659, p<.001]. This is in accordance with our CRP model, but against predictions from any model that only allows 2 potential streams.

Seven subsequent paired-sample t-tests were performed to decompose the main effect of frequency differences over D-prime scores. Three paired-sample t-tests revealed that D-prime scores were significantly higher in the *3-3* condition than in the *9-9* condition [t(23)=3.003, p=.006, d=0.613], in the *9-15* condition [t(23)=2.556, p=.018, d=0.522] and in the *15-15* condition [t(23)=2.535, p=0.019, d=0.517]. Two other paired-samples t-tests revealed no significant difference between the *3-3* and the *3-9* conditions [t(23)=0.681, p=.503, d=0.139] and between the *3-3* and the *3-15* conditions [t(23)=-1.568, p=.131, d=-0.32]. Another two paired-samples t-tests revealed no significant differences between the *9-9* and the *9-15* conditions [t(23)=-1.02, p=.318, d=-0.208] and between the *9-9* and the *15-15* conditions [t(23)=-0.949, p=.353, d=-0.194]. These results are summarized in Figure 7.

	3-3	3-9	3-15	9-9	9-15	15-15
Different	0.271 ± 0.209	0.288 ± 0.292	0.240 ± 0.258	0.486 ± 0.253	0.497 ± 0.284	0.538 ± 0.317
Similar	0.799 ± 0.230	0.771 ± 0.240	0.833 ± 0.197	0.771 ± 0.202	0.854 ± 0.199	0.896 ± 0.176
D-prime	1.476 ± 0.765	1.371 ± 1.016	1.713 ± 0.863	0.748 ± 0.843	0.976 ± 0.777	0.960 ± 0.940

Table 1. Mean proportions of "similar" responses, and mean D-prime scores across all conditions. Reported errors are ± 1 standard deviation

Figure 7. D-prime scores as a function of frequency difference. Red bars indicate conditions with a small minimum frequency difference, blue bars indicate conditions with an intermediate minimum frequency difference and green bars indicate conditions with a large minimum frequency difference. Error bars are ± 1 standard error

₃₁₈ Model performance

₃₁₉ While the results above support the ability of the model to explain to qualitatively predict the per-
₃₂₀ formance of subjects on a novel experiment we also wanted to verify this quantitatively. We fitted
₃₂₁ the model (see Methods) to the data for each subject, with the same model variants as for Exper-
₃₂₂ iment 1. We again found that the model with a CRP prior was best able to explain the data with
₃₂₃ an average advantage of ELBO for the CRP of (-1.9204 -3.6681 -1.5003) relative to the other three
₃₂₄ models. Furthermore the protected exceedance probability (*Rigoux et al., 2014*) was respectively
₃₂₅ (0.9993 0.0003 0.0002 0.0003) indicating a strong preference for the CRP model.

₃₂₆ It is worth noting that the behavior of the subjects on this task is more noisy and even the
₃₂₇ best-performing model is at chance level for 6 of the subjects.

Figure 8. Model performance on experiment 2 in terms of Evidence Lower Bound (ELBO) for each subject
with the CRP model (blue), alternative A (red), alternative B (yellow), and alternative C (purple). The black
horizontal dotted line indicates the performance of a purely random model that assigns 0.5 probability to
either response for every condition. Subjects are ordered based on CRP model ELBO values. Large negative
values indicate poor performance of a model.

Discussion

₃₂₉ We have presented a simple Bayesian perceptual model that is capable of assigning stimuli to an
₃₃₀ unrestricted number of sources, by clustering of stimuli. We have applied the model to the specific
₃₃₁ case of auditory stream segregation, an area where Gestalt psychology has long emphasized the
₃₃₂ need for grouping. Utilizing a non-parametric Bayesian prior, the model iteratively updates the pos-
₃₃₃ terior distribution over the assigned group of each stimulus and provides an excellent description
₃₃₄ of the perceptual interpretation of simple auditory sequences by human observers.

₃₃₅ With just two parameters, the model gives a good account of the basic characteristics of audi-
₃₃₆ tory stream segregation – the variation in the probability of perceiving a single sound source as a
₃₃₇ function of the repetition rate and pitch difference of the sounds. The basic model (with a softmax
₃₃₈ decision function) gave a better fit to experimental data (Exp. 1) than alternative models that were
₃₃₉ constrained to interpret the sounds as being produced from just one or two streams. Predictions
₃₄₀ from the model were also in accordance with results from a novel experiment with a larger number
₃₄₁ of tones (Exp. 2).

₃₄₂ Importantly, the model goes beyond giving just the number of sources, but says which sounds
₃₄₃ are produced by each source. While the combinatorial space of the posterior distribution in exper-

iment 1 was collapsed to give a marginal distribution in a continuous 1-d response space (leading to an estimate of response probability), the maximum a posterior (MAP) for all participants was always located at either 111-111... or 121-121..., depending on the stimulus condition (Figure 3). This is reassuring as it is consistent with the anecdotal evidence that participants always perceive either a galloping rhythm (streams 111-111...) or a high-pitch and a low pitch stream (121-121...), i.e. the percept is always at the MAP. Indeed, the percept cannot in general be at the mean because the space of possible percepts is discrete: there is no percept in between 111 and 121.

One consequence of the inference model that is not addressed by mechanistic models of stream segregation is that when a percept changes from, say 111-111 to 121-121, the source allocation of previous sounds is changed. Ironically, this 'non-causal' effect is essentially a feature of causal inference – when an observer decides that the percept has changed to 121-121, this is based on previous evidence, and yet at the time that the previous tones were heard, they were all associated with one source. A similar effect is commonly encountered when mis-interpreted speech (perhaps mis-heard due to background noise) suddenly makes sense when an essential word is heard – the previous words are reinterpreted, similar to the letters in predictive text message systems.

In the current implementation, we had to make numerical approximations in order to handle the complexity of the model. As an alternative to calculating our results analytically (but with approximations), we could use Monte Carlo techniques (e.g. Markov Chain Monte Carlo sampling, i.e. MCMC, a different type of approximation), which have become a standard tool for solving complex statistical models. While not presented here, we have also implemented a MCMC version of the model with similar results. In future work this might be useful in explaining bistable behavioral phenomena, where an observer will seemingly randomly switch between incongruous interpretations of stimuli (*Barniv and Nelken, 2015*; *Pressnitzer and Hupé, 2006*), a phenomenon not explained by the current model.

The framework of the model is very general and allows for the incorporation of other factors into the likelihood to describe other aspects of auditory stream segregation. Adding terms in the likelihood function may be able to explain other effects seen in the literature, such as segregation based on bandwidth (*Cusack and Roberts, 2000*), or build-up and resetting of segregation (*Roberts et al., 2008*). Furthermore, in the current study we assume that there is no ambiguity in the percept of the pure tones, the uncertainty arises from the lack of knowledge about the underlying generative structure of the data. In a realistic situation perceptual ambiguity would have to be taken into account using an approach such as suggested by Turner and Sahani (*Turner and Sahani, 2011*). Nevertheless, we should emphasize that even though we are dealing with a Markov property (each tone within a stream only depends on the previous tone within the stream), the mixture of streams makes the problem very different from the work on e.g. Hidden Markov Models (or even Infinite Hidden Markov Models) for which the goal is to infer the underlying states despite noisy signal (*Fox et al., 2011*).

Our approach is an example of a predictive coding model (*Denham and Winkler, 2020*) that uses a generative model to make predictions about the relationships between stimuli and subsequently update these relationships. The model shares similarities with work by Barniv and Neike (*Barniv and Nelken, 2015*), who used Gaussian mixture models to describe the integration and segregation of auditory objects, and assumed that a new object could be introduced with a small fixed probability. The model implemented by Chambers et al. (*Chambers et al., 2017*) also used a similar probabilistic framework and Gaussian likelihood to explain the perceived continuity of pure tones with octave relationships ('Shepard tones'). In contrast to such probabilistic models, there have also been proposals for mechanistic models, such as neural network models simulating the abstract processing of the cochlea and auditory cortex (*Krishnan et al., 2014*), as well as models explaining behavioural phenomena through interactions between different neural populations (*McCabe and Denham, 1997*; *Nguyen et al., 2020*).

The proposed model of auditory stream segregation is a specific instantiation of an iterative

probabilistic approach towards inference of perceptual information. A major issue for this approach is the problem of dealing with multiple sources, as represented by the work done on causal inference (*Shams and Beierholm, 2010*; *Körding et al., 2007*; *Shams and Beierholm, 2022*). Until now, models of causal inference have been unable to handle more than two sources, due to the increasing number of parameters needed for parametric priors. The use of a non-parametric prior allows a complex of many stimuli to be interpreted without running into this problem, potentially allowing for an arbitrary number of causes in the world. This approach is very general - it can be applied to any set of discrete sequential cues involving multiple sources - and it gives a simple, principled way to incorporate signal constraints into the generative model.

While frequency and time are the most studied dimensions in the Auditory Scene Analysis literature (*Bregman, 1994*; *Moore and Gockel, 2012*), the general idea of explaining perceptual clustering through the use of a Bayesian non-parametric prior can potentially be applied to other auditory variables, such as harmonic complex tones (*Moore and Gockel, 2011*) or multiple speakers, i.e. the cocktail party problem (*Mcdermott, 2010*). It is also possible to add other features in addition to time and frequency, to the existing model, such as spatial discrepancy and saliency, topics we plan to explore in the future. The auditory streaming model currently also does not consider attentional mechanisms. As presented here, it assumes that our perceptual system automatically groups or segregates cues into a potentially infinite number of streams based on stimulus characteristics, and that attention only has the role of selecting one or several clusters of interest in a given situation, or is being driven by the posterior probability of the different clusters. In either case, attentional processes would be entirely independent of the mechanisms simulated by the model. Nevertheless, it has already been proposed that attention could interact with the cluster formation process itself and therefore affect their overall configuration (*Sussman, 2017*). If that is the case, the model's responses could significantly differ from behavioural results in situations where top-down attention is being manipulated.

Auditory stream segregation is considered a typical example of the Gestalt principle of Pragnanz (*Wagemans et al., 2012*), according to which properties of a set of stimuli are interpreted in a manner that simplifies the interpretation. We would propose that another way to interpret this is by the principle of clustering, with stimuli that are similar (in auditory frequency, visual continuity etc.) being combined into a single simple interpretation. The simplification principle is naturally interpreted in our framework through a non-parametric Bayesian process that naturally restricts the complexity of the interpretation, such as the number of possible objects or sources in a scene.

Ultimately, the processing of auditory stimuli in an organism must be for the goal of survival and procreation. Simplicity, as encapsulated in this model, is not a goal in itself but can be thought of as a heuristic towards improved detection, tracking and processing of auditory sources. Further work in this area can expand on under what conditions this is indeed a useful heuristic.

In conclusion, we have shown that auditory scene perception of streams of single frequency tones can be explained by a simple Bayesian model utilizing a non-parametric prior. This highlights the importance of clustering in auditory perception, although the approach is applicable to any combination of stimuli and perceptual cues. Together with advances in visual perception (*Froyen et al., 2015*) this hints at clustering being a general property of perception.

Materials and Methods

Modelling

Model response and fitting, Exp 1

For experiment 1, to determine the response (1 or 2 streams) of the model to a tone sequence, the posterior for each possible sequence, $S_{1:n}$, is calculated tone-by-tone until all 30 tones (maximum) have been presented. To relate the final posterior over sequences to response r_k of subject k, ('1 or 2 streams') $P_{model}(r_k|tones)$, we assume that subjects maximise the expected utility

$$\operatorname*{argmax}_{r_k} <U> = \operatorname*{argmax}_{r_k} \sum_{i,j} U(r_k, S_i, S_j) * P(S_i = S_j | f, t) \tag{7}$$

where the utility of a response given two tones in same stream is counted as 1 if they are in the same stream, and zero otherwise. Note that the absolute values of S_i do not matter, just whether they are in the same stream or not.

$$U(r_k, S_i, S_j) = 1 \quad \text{if } (r_k = 1, S_i = S_j) \text{ or } (r_k = 0, S_i \neq S_j) \tag{8}$$
$$U(r_k, S_i, S_j) = 0 \quad \text{if } (r_k = 0, S_i = S_j) \text{ or } (r_k = 1, S_i \neq S_j) \tag{9}$$

The best response is then to choose 1 (single stream) if

$$\sum_{i,j} P(S_i = S_j | f, t) > \sum_{i,j} (1 - P(S_i = S_j | f, t)) \tag{10}$$

If the observer believes all tones came from the same stream they should choose $r_k = 1$, if they are convinced half the tones are from one stream, half from another they should choose $r_k = 2$.

We assume soft-max, a variant of probability matching similar to Luce's law (*Luce, 1959*), to explain the variability in data and allow us to fit our models.

$$P(r_k | f, t) = \frac{exp(\beta * \sum P(S_i = S_j | f, t))}{exp(\beta * \sum P(S_i = S_j | f, t)) + exp(\beta * \sum (1 - P(S_i = S_j | f, t)))} \tag{11}$$

The parameters of the model (as well as for the alternative models) were optimised independently for each subject k using the BADS and VBMC toolboxes (as a more robust alternative to MATLAB's fminsearch routine (*Acerbi and Ma, 2017*; *Acerbi, 2018*, *2020*), to maximise the Evidence Lower Bound (ELBO) based on the likelihood log $P_{model}(r_k | tones, par)$ combined with a weak prior. During each iteration of the search, a sequence of 30 tones was presented to the model for each condition, and the probability of response '1' was calculated per condition.

We performed six initialisations of the VBMC algorithm for each subject (to avoid fitting to a local minimum), and assessed the convergence using the build-in diagnostic function. When reporting values from VBMC (parameters or ELBO) we always report the mean values.

Model posterior approximation

Using the iterative scheme above, we can calculate analytically the possible combinations of tones, but as the tone sequence progresses the number of possible source combinations - and hence the size of the posterior distribution - increases exponentially. To prevent combinatorial explosion two methods were used to generate an approximation of the full posterior distribution. The first limits the number of tones that are retained when using the previous posterior as the next prior, i.e. the algorithm only retains the last 30 tones and their potential allocations to sources

Limiting the number of tones eases the computational load and can also be seen as a crude model of a limited memory capacity. Although the iteratively constructed prior retains some stream information of all previous tones, when a very short memory is used, this may not be sufficient to generate stable stream allocation as the CRP prior probabilities fluctuate greatly when the number of previous tones is small. Furthermore, if the structure of the sequence is an important cue for streaming, a larger memory may be necessary to determine regularities in the sequence.

Even when the memory is limited to (e.g.) the previous six tones, allocating a stream to the seventh tone requires a posterior distribution taking 858 values, most of which must necessarily have very small probabilities. A second method to limit the size of the posterior is simply to select only the most probable stream combinations by imposing a probability threshold, hence we only propagated stream combinations with $P(S_{1:n} | tones_{1:n}) > 0.001$. Together, these approximation methods allow a reasonable memory length of 30 tones (to avoid instability), while avoiding combinatorial explosion.

 Model response and fitting, Exp 2

The qualitative and quantitative predictions for Experiment 2 rest on the assumptions that subjects will be unable to differentiate the order of the middles tones (M1 and M2) if the tones are in a stream only with themselves, i.e. if L and H are in separate streams from M1 and M2. Similar to methods for Exp 1 we marginalise over all the probabilities where

$$P(S_{M1} = S_L \& S_{M1} = S_H \& S_{M2} = S_L \& S_{M2} = S_H | f, t) = 1 - \sum_{n,o} P(S_n = S_o)$$

where $n \in (M1, M2)$ and $o \in (L, H)$.

Same as for Experiment 1 we assumed a soft-max distribution of responses to explain variability
of responses and help us fit our models.

In contrast to Experiment we did not fit the prior probability of a single stream to the data
($P(11) = 1/(\alpha + 1)$), but instead assumed a fixed value across subjects of 0.18 (mean fitted value
from Exp 1). The reason for this was that while in Exp 1 we varied both the tone differences and
the tone timing gap, allowing us to examine effect of parameters for prior probability $P(11)$ and the
variance σ, in Exp 2 we only varied the tone differences thus giving us less dimensions of variability
and thus need to restrict the number of parameters.

Otherwise the fitting worked in a similar manner using the VBMC toolbox to find the distribution
of ELBO.

Experimental setup

Two experiments were conducted to test different aspects of the model. Experiment 1 was a replica
of the 'galloping' stimuli experiment (*van Noorden, 1975*) performed to test the quantitative per-
formance of the model, while the second experiment was a novel task designed to test one of the
predictions of the model.

Subjects for both experiments were under-graduate students and received course credits for
their participation, except for one of the authors who participated in Experiment 1. Each subject
was fully briefed, provided informed consent and was given brief training on the task they per-
formed. Experiments were completed by different subjects. No personal data was kept, ensuring
participants' anonymity. The two experiments were approved by University of Birmingham and
Durham University's Ethics Committees respectively.

Stimuli were dynamically programmed using Matlab (*MathWorks, 2018*) on a PC desktop com-
puter. Both experiments used the Psychtoolbox extension to ensure timings were accurate
(*Kleiner et al., 2007*). Stimuli were played through Sennheiser 280 headphones at a comfortable
supra-threshold level plugged into an external sound card. The experiment was carried out in a
special sound-attenuated room.

Experiment 1

This experiment replicated the study from (*van Noorden, 1975*), using fifteen participants. Figure
3 shows a schematic of the stimuli used – each sequence comprised 30 tones in repeated LHL-
triplets, where the dash represents a silent gap. Each tone was 50 ms in duration, including 10 ms
raised cosine onset and offset ramps. A 4x5 factorial design was used: the pitch of the high tones
took values of 3, 6, 9, 12, and 15 semitones above the low tone, which had a fixed frequency of 1000
Hz, and the offset to onset interval took values 17, 33, 50, and 67 ms. The duration of the silent gap
was equal to the tone duration plus the offset-onset interval. Conditions were ordered randomly
– each condition was tested 20 times over 4-6 runs, each run lasting approximately 7 minutes. At
the end of the sequence participants pressed a key to report whether the percept at the end of
the sequence was most like a single stream (a galloping rhythm) or two separate streams of notes.
The whole experiment lasted about 50 minutes.

₅₂₀ Experiment 2

₅₂₁ Twenty-six participants were enrolled for this study. No personal data was kept, ensuring partici-
₅₂₂ pants' anonymity.

Material and stimuli

₅₂₄ Each testing trial consisted in 2 sequences of 4 pure tones in repeated Low-Medium-High-Medium
₅₂₅ (L-M1-H-M2 or L-M2-H-M1) quadruplets. The first sequence was always repeated 22 times for a
₅₂₆ total of 88 tones presented. The second one was always repeated a total of 11 times for a total of
₅₂₇ 44 tones presented. Tones between sequences within a same trial were always the same and only
₅₂₈ their order of presentation could differ. Each tone was 100ms in duration, including 10ms raised
₅₂₉ cosine onset and offset ramps. The offset to onset interval between tones inside a sequence was
₅₃₀ 16.67ms. Each sequence also had general 500ms long raised cosine onset and offset ramps. The
₅₃₁ offset to onset interval between sequences inside a trial was 2s. The lowest tone had a fixed fre-
₅₃₂ quency of 440Hz across trials. The highest possible tone had a frequency of 2960Hz. The lowest
₅₃₃ frequency was specifically chosen to correspond to a common tone, and to control for differences
₅₃₄ in perceived loudness as much as possible across the range of played frequencies. Indeed, the
₅₃₅ 440-2960Hz range presents a low variability in equal-loudness (*ISO Central Secretary, 2003*) The
₅₃₆ frequency of M1 was calculated in semitone increases from the lowest tone, according to experi-
₅₃₇ mental conditions. M2 was always 3 semitones higher than M1. As was the case for the difference
₅₃₈ between L and M1, the frequency of H was calculated in semitone increases from M2, in relation
₅₃₉ to experimental conditions (see Figure 9 for a representation of a typical trial).

Figure 9. Visual representation of a trial with inversion in a 9-9 frequency difference condition

₅₄₀ Training trials were similarly designed and consisted in 2 sequences of 3 pure tones in repeated
₅₄₁ Low-Medium-Medium (L-M1-M2 or L-M2-M1) triplets.

Design

₅₄₃ A 2x6 within-subjects factorial design was used. The first independent variable was the medium
₅₄₄ tones inversion, which could be either present or absent between the 2 sequences of a trial. This
₅₄₅ resulted respectively in trials objectively comprised of a pair of different sequences, and trials ob-
₅₄₆ jectively comprised of a pair of twin sequences. The second independent variable was pairs of
₅₄₇ frequency differences between L and M1, and between M2 and H, counted in semitones. Possible
₅₄₈ values were 3-3, 3-9, 3-15, 9-9, 9-15, and 15-15. Conditions were presented randomly, and the
₅₄₉ order in which baseline and inverted tone sequences were presented was counterbalanced. Each
₅₅₀ identical pair of sequences was presented 6 times, while each different pair of sequences was pre-
₅₅₁ sented 12 times for a total of 108 trials. Training trials consisted in 3 identical pairs and 3 different
₅₅₂ pairs repeated twice, for a total of 12 training trials.

The first dependent variable was the perceived difference between sequences (different vs. similar). The second dependent variable was the level of confidence in this judgement (on a scale from 1 to 4, 4 being "very confident"). We did not analyse the confidence judgments here.

Procedure

Participants were greeted in a small sound-attenuated room and were asked to sit at a desk, approximately 60cm from a computer screen. They were handed an information and a privacy notice sheet, stating the general aims of the experiment, their rights as a subject, and how their data would be handled. After reading and asking any questions they may have to the experimenter, they were asked to sign a consent form. They were then asked to put the headphones on once they confirmed they understood the task instructions.

Participants were asked to listen to pairs of melodies presented sequentially, and judge after each pair if the melodies were similar or different by pressing the right key on a keypad ("1" for different, "2" for similar). They were also asked to rate their confidence about the judgement they just made, by pressing a key from 1 to 4 on the same keypad. Participants were warned that tones between sequences had the same frequency, and that they should focus on the order of tones within the melody. On each trial, a white dot was displayed in the middle of the screen for a brief period to signify a new trial was about to start. A grey dot was then displayed in place of the white one along with the instruction "listen" while melodies were being played. A black dot, along with a reminder of the response keys, replaced them as soon as the melodies were finished, meaning that subjects could enter their response. Participants had no time limit to respond, as the next trial would only start after they did.

Once the experiment was over, the experimenter gave an oral feedback explaining the aims, design, and experimental background of the study. The whole experiment lasted about 55 minutes.

Appendix 1

When fitting parameters of a model to a data set it is important to first ensure that the model is specific enough that it is possible to recover its generating parameters when fitting to simulated data sampled from the model.

Parameter recovery for Experiment 1 fitting

Parameter values were sampled from prior distributions over the generating parameters $P(onesource)$, σ and β. Based on this parameter set, subject responses were simulated from the model in accordance with how subject were recorded (i.e. same number of trials, same number of conditions). Given this simulated data set (for which we know the true generating parameters) the model was fit unto, using the same method as for fitting to the real subject data. The fitting on simulated data reveals a set of fitting parameters that can then be compared with the generating parameters. Figure 10 shows the recovered parameters for $P(onesource)$, σ, and β, plotted against the original generating parameters. The fitted parameters are reasonably close, implying that the model is correctly specified. Obviously more trials per condition would decrease noise and therefore lead to better fits of the parameters.

Parameter recovery for Experiment 2 fitting

Methods of parameter recovery were similar to those for Exp 1. Figure 11Left shows that for the σ variable the original parameter is quite well recovered. For the β parameter in Figure 11Right the recovery is not quite as good (points are further from diagonal) although it is not too surprising given the natural variability of the data when only doing 18 binary choices per condition.

Figure 10. Parameter recovery for Experiment 1. Left) True value for $P(11)$ on horizontal axis, estimated value on the vertical axis. Middle) True value for σ on horizontal axis, estimated value on the vertical axis. Right) True value for β on horizontal axis, estimated value on the vertical axis.

Figure 11. Parameter recovery for Experiment 2. Left) True value for sigma on horizontal axis, estimated value on the vertical axis. Right) True value for beta on horizontal axis, estimated value on the vertical axis.

Acknowledgements

We are very grateful for discussions and helpful comments by Uta Noppeney as well as colleagues at Durham University Psychology department. NL was funded through a Durham University Postgraduate grant.

Data and code availability

The human behavioral raw data are available for both experiments. Code, stimuli and data wrangling and analyses scripts for experiment 2 are also provided. Computational model predictions as well as the code for computational modelling and analyses scripts are also available. All can be found in the OSF repository: https://osf.io/ys94d/

References

Acerbi L. Variational Bayesian Monte Carlo. Advances in Neural Information Processing Systems. 2018; 31(NeurIPS 2018):8222–8232. http://arxiv.org/abs/1810.05558.

Acerbi L. Variational Bayesian Monte Carlo with Noisy Likelihoods. Advances in Neural Information Processing Systems. 2020 Oct; 33:8211–8222. http://arxiv.org/abs/2006.08655, arXiv: 2006.08655.

Acerbi L, Ma WJ. Practical Bayesian Optimization for Model Fitting with Bayesian Adaptive Direct Search. Advances in Neural Information Processing Systems. 2017; 30:1834–1844.

Aldous DJ. Exchangeability and Related Topics. Lecture notes in mathematics. 1985; 1117:1–198.

Anstis SM, Saida S. Adaptation to Auditory Streaming of Frequency-Modulated Tones. Journal of Experimental Psychology: Human Perception and Performance,. 1985; 11(3):257–271.

Barlow H. Possible Principles Underlying the Transformation of Sensory Messages. Sensory Communication. 1961; p. 217 – 234.

Barniv D, Nelken I. Auditory Streaming as an Online Classification Process with Evidence Accumulation. PLOS ONE. 2015; 10(12):e0144788. https://dx.plos.org/10.1371/journal.pone.0144788, doi: 10.1371/journal.pone.0144788.

Barsz K. Auditory Pattern Perception: The Effect of Tonal Frequency Range on the Perception of Temporal Order. Perception & Psychophysics. 1988 May; 43(3):293–303. https://link.springer.com/article/10.3758/BF03207873, doi: 10.3758/BF03207873.

Beauvois MW, Meddis R. Time Decay of Auditory Stream Biasing. Perception & psychophysics. 1997; 59(1):81–86. doi: 10.3758/BF03206850.

Beierholm UR. Bayesian Models of Perception. In: *Encyclopedia of Computational Neuroscience* Springer Verlag; 2015.p. 1–5. doi: https://doi.org/10.1007/978-1-4614-6675-8$_4$51.

Bregman AS, Campbell J. Primary Auditory Stream Segregation and Perception of Order in Rapid Sequences of Tones. Journal of experimental psychology. 1971 Aug; 89(2):244–9.

Bregman AS. Auditory streaming: Competition among alternative organizations. Perception & Psychophysics. 1978 Sep; 23(5):391–398. http://www.springerlink.com/index/10.3758/BF03204141, doi: 10.3758/BF03204141.

Bregman AS. Auditory Streaming Is Cumulative. Journal of Experimental Psychology: Human Perception and Performance. 1978; 4(3):380–387. doi: 10.1037/0096-1523.4.3.380.

Bregman AS. Auditory Scene Analysis the Perceptual Organization of Sound. MIT Press; 1994.

Chambers C, Akram S, Adam V, Pelofi C, Sahani M, Shamma S, Pressnitzer D. Prior context in audition informs binding and shapes simple features. Nature Communications. 2017; 8:15027.

Cusack R, Roberts B. Effects of Differences in Timbre on Sequential Grouping. Perception & Psychophysics. 2000; 62:1112–1120. http://link.springer.com/article/10.3758/BF03212092.

Demany L. Auditory stream segregation in infancy. Infant Behavior and Development. 1982 jan; 5(2-4):261–276. https://www.sciencedirect.com/science/article/pii/S0163638382800362, doi: 10.1016/S0163-6383(82)80036-2.

Denham SL, Winkler I. Predictive coding in auditory perception: challenges and unresolved questions. European Journal of Neuroscience. 2020 Mar; 51(5):1151–1160. https://onlinelibrary.wiley.com/doi/abs/10.1111/ejn.13802, doi: 10.1111/ejn.13802.

Fox EB, Sudderth EB, Jordan MI, Willsky AS. A sticky HDP-HMM with application to speaker diarization. The Annals of Applied Statistics. 2011 Jun; 5(2 A):1020–1056. http://projecteuclid.org/euclid.aoas/1310562215, doi: 10.1214/10-AOAS395.

Froyen V, Feldman J, Singh M. Bayesian Hierarchical Grouping: Perceptual Grouping as Mixture Estimation. Psychological Review. 2015; 122(4):575–597.

Gershman SJ, Niv Y. Perceptual estimation obeys Occam's razor. Frontiers in psychology. 2013 jan; 4(September):623. http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=3780620{&}tool=pmcentrez{&}rendertype=abstract, doi: 10.3389/fpsyg.2013.00623.

Ghahramani Z. Bayesian non-parametrics and the probabilistic approach to modelling. Phil Trans R Soc A. 2013; 371(1984):20110553. http://www.ncbi.nlm.nih.gov/pubmed/23277609, doi: 10.1098/rsta.2011.0553.

ISO Central Secretary. Acoustics – Normal Equal-Loudness-Level Contours. International Organization for Standardization; 2003.

Kleiner M, Brainard D, Pelli D, Ingling A, Murray R, Broussard C. What's new in psychtoolbox-3. Perception. 2007; 36(14):1–16. https://nyuscholars.nyu.edu/en/publications/whats-new-in-psychtoolbox-3.

Körding KP, Beierholm U, Ma WJ, Quartz S, Tenenbaum JB, Shams L. Causal inference in multisensory perception. Plos One. 2007; 2(9):e943. https://www.ncbi.nlm.nih.gov/pmc/articles/PMC1978520, doi: 10.1371/journal.pone.0000943.

Krishnan L, Elhilali M, Shamma S. Segregating Complex Sound Sources through Temporal Coherence. PLoS Computational Biology. 2014 Dec; 10(12):e1003985. http://dx.plos.org/10.1371/journal.pcbi.1003985, doi: 10.1371/journal.pcbi.1003985.

Lee MD, Habibi A. A Cyclic Sequential Sampling Model of Bistable Auditory Perception. In: Taatgen N, van Rijn H, Nerbonne J, Shonmaker L, editors. *Proceedings of the 31st Annual Conference of the Cognitive Science Society*; 2009. p. 2669–2674.

Luce RD. On the possible psychophysical laws. Psychological Review. 1959; 66(2):81–95. http://content.apa.org/journals/rev/66/2/81, doi: 10.1037/h0043178.

MathWorks. MATLAB version: 9.5.0 (R2018b). Natick, Massachusetts, United States; 2018, https://www.mathworks.com.

McCabe SL, Denham MJ. A Model of Auditory Streaming. The Journal of the Acoustical Society of America. 1997 Mar; 101(3):1611. http://scitation.aip.org/content/asa/journal/jasa/101/3/10.1121/1.418176, doi: 10.1121/1.418176.

Mcdermott JH. The cocktail party problem. Current Biology. 2010; 19(22):1024–1027.

McDermott JH, Simoncelli EP. Sound Texture Perception via Statistics of the Auditory Periphery: Evidence from Sound Synthesis. Neuron. 2011 Sep; 71(5):926–40. doi: 10.1016/j.neuron.2011.06.032.

Moore B, Gockel H. Factors Influencing Sequential Stream Segregation. Acta Acustica. 2002; 88(3):320–333. http://www.ingentaconnect.com/content/dav/aaua/2002/00000088/00000003/art00004.

Moore BCJ, Gockel HE. Resolvability of components in complex tones and implications for theories of pitch perception. Hearing Research. 2011; 276(1-2):88–97.

Moore BCJ, Gockel HE. Properties of Auditory Stream Formation. Philosophical transactions of the Royal Society of London Series B, Biological sciences. 2012 Apr; 367(1591):919–31. http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=3282308&tool=pmcentrez&rendertype=abstract, doi: 10.1098/rstb.2011.0355.

Nguyen QA, Rinzel J, Curtu R. Buildup and bistability in auditory streaming as an evidence accumulation process with saturation. PLOS Computational Biology. 2020 Aug; 16(8):e1008152. https://dx.plos.org/10.1371/journal.pcbi.1008152, doi: 10.1371/journal.pcbi.1008152.

van Noorden L. Temporal coherence in the perception of tone sequences. PhD thesis, Technische Hogeschool Eindhoven; 1975.

Orbanz P, Teh YW. Bayesian Nonparametric Models. In: *Encyclopedia of Machine Learning*; 2010. p. 81–89. https://api.semanticscholar.org/CorpusID:622754.

Pressnitzer D, Hupé JM. Temporal Dynamics of Auditory and Visual Bistability Reveal Common Principles of Perceptual Organization. Current Biology. 2006 Jul; 16(13):1351–1357. https://www.sciencedirect.com/science/article/pii/S096098220601637X, doi: 10.1016/j.cub.2006.05.054.

Rigoux L, Stephan KE, Friston KJ, Daunizeau J. Bayesian model selection for group studies - Revisited. NeuroImage. 2014; 84:971–985. http://dx.doi.org/10.1016/j.neuroimage.2013.08.065, doi: 10.1016/j.neuroimage.2013.08.065.

Roberts B, Glasberg BR, Moore BCJ. Effects of the Build-up and Resetting of Auditory Stream Segregation on Temporal Discrimination. Journal of experimental psychology Human perception and performance. 2008 Aug; 34(4):992–1006. doi: 10.1037/0096-1523.34.4.992.

Shams L, Beierholm U. Bayesian causal inference: A unifying neuroscience theory. Neuroscience & Biobehavioral Reviews. 2022 Jun; 137:104619. https://linkinghub.elsevier.com/retrieve/pii/S0149763422001087, doi: 10.1016/j.neubiorev.2022.104619.

Shams L, Beierholm UR. Causal Inference in Perception. Trends in Cognitive Sciences. 2010 Aug; 14(9):1–8. http://dx.doi.org/10.1016/j.tics.2010.07.001, doi: 10.1016/j.tics.2010.07.001.

Shams L, Ma WJ, Beierholm U. Sound-Induced Flash Illusion as an Optimal Percept. Neuroreport. 2005 Nov; 16(17):1923–7. http://www.ncbi.nlm.nih.gov/pubmed/16272880.

Sussman ES. Auditory Scene Analysis: An Attention Perspective. Journal of speech, language, and hearing research: JSLHR. 2017 Oct; 60(10):2989–3000.

Tougas Y, Bregman AS. Crossing of Auditory Streams. Journal of Experimental Psychology: Human Perception and Performance. 1985; 11(6):788–798. doi: 10.1037/0096-1523.11.6.788.

Turner RE. Statistical Models for Natural Sounds. PhD thesis, Gatsby Computational Neuroscience Unit, UCL; 2010.

Turner RE, Sahani M. Probabilistic Amplitude and Frequency Demodulation. In: Shawe-Taylor J, Zemel RS, Bartlett P, Pereira F, Weinberger KQ, editors. *Advances in Neural Information Processing* Red Hook; 2011. p. 981–989.

Wagemans J, Elder JH, Kubovy M, Palmer SE, Peterson Ma, Singh M, von der Heydt R. A century of Gestalt psychology in visual perception: II Conceptual and theoretical foundations. Psychological Bulletin. 2012; 138(6):1218–1252.

Wang D. Primitive Auditory Segregation Based on Oscillatory Correlation. Cognitive Science. 1996 Sep; 20(3):409–456. http://www.sciencedirect.com/science/article/pii/S0364021399800111, doi: 10.1016/S0364-0213(99)80011-1.

Weiss Y, Simoncelli EP, Adelson EH. Motion Illusions as Optimal Percepts. Nat Neurosci. 2002; 5:598–604. http://dx.doi.org/10.1038/nn858.

Wood F, Goldwater S, Black MJ. A Non-Parametric Bayesian Approach to Spike Sorting. Conference proceedings : Annual International Conference of the IEEE Engineering in Medicine and Biology Society IEEE Engineering in Medicine and Biology Society Conference. 2006 Jan; 1:1165–8. doi: 10.1109/IEMBS.2006.260700.