1   **Using top-down gating to optimally balance shared versus separated task representations**

3   *Authors: Pieter Verbeke[1] & Tom Verguts[1]*

4   *Affiliations:* [1] Department of experimental psychology; Ghent University

5   ORCID IDs: Pieter Verbeke: 0000-0003-2919-1528

6   Tom Verguts: 0000-0002-7783-4754

7   Corresponding author email: pjverbek.verbeke@ugent.be

9   Keywords: Cognitive control, gating, neural representations, learning

11   **Declarations**

Acknowledgements: PV was supported by grant 1102519N from Research Foundation Flanders. TV

was supported by grant BOF17/GOA/004 from the Ghent University Research Council. We thank

Sebastian Musslick, Senne Braem, Cristian Buc Calderon and Pieter Huycke for valuable comments

on this work. We also thank Michael J. Frank and his lab members for interesting input.

Conflict of interests: The authors declare no competing financial interests.

Data availability statement: Code to simulate the model and analyze the resulting data is provided

in our GitHub repository: https://github.com/CogComNeuroSci/PieterV_public/tree/master/Gating

Abstract

Human adaptive behavior requires continually learning and performing a wide variety of tasks, often with very little practice. To accomplish this, it is crucial to separate neural representations of different tasks in order to avoid interference. At the same time, sharing neural representations supports generalization and allows faster learning. Therefore, a crucial challenge is to find an optimal balance between shared versus separated representations. Typically, models of human cognition employ top-down gating signals to separate task representations, but there exist surprisingly little systematic computational investigations of how such gating is best implemented. We identify and systematically evaluate two crucial features of gating signals. First, top-down input can be processed in an additive or multiplicative manner. Second, the gating signals can be adaptive (learned) or non-adaptive (random). We cross these two features, resulting in four gating models which are tested on a variety of input datasets and tasks with different degrees of stimulus-action mapping overlap. The multiplicative adaptive gating model outperforms all other models in terms of accuracy. Moreover, this model develops hidden units that optimally share representations between tasks. Specifically, different than the binary approach of currently popular latent state models, it exploits partial overlap between tasks.

Introduction

Humans and other rational agents need to continually learn and perform an enormous number of complex tasks. Sometimes very similar contexts require totally different actions (e.g., soccer and handball). In such contexts, it is important to separate stimulus-action representations between the two tasks as much as possible in order to avoid interference. However, at other times, two different contexts nevertheless require partially similar actions (e.g., tennis and badminton). In these cases, an agent can significantly benefit from partially sharing knowledge between the two tasks.

Previous research (Baxter, 2019; Franklin & Frank, 2018; Musslick et al., 2017; Vaidya, Jones, Castillo, & Badre, 2020; Zambaldi et al., 2018) indeed illustrated that sharing task representations significantly improves learning and generalization across tasks, two hallmarks of human flexibility. However, sharing task representations in a neural network severely impacts the network's ability to perform more than one task at the same time (i.e., to multi-task; Alon et al., 2017; Musslick et al., 2017; Musslick, Saxe, Novick, Reichman, & Cohen, 2020). Moreover, shared task representations leave a network very vulnerable to overwriting previously learned information. This problem is known as catastrophic interference (French, 1999). In contrast, a network that develops separated task representations experiences less problems in multi-tasking (Musslick et al., 2020; Tsai, Saxe, & Cox, 2016) and can continually learn without forgetting (Kirkpatrick et al., 2017; Masse, Grant, & Freedman, 2018; McClelland, McNaughton, & O'Reilly, 1995; Verbeke & Verguts, 2019). However, such networks are less able to generalize and as a consequence must learn even very similar tasks (like tennis and badminton) from scratch. In sum, there exists a trade-off between sharing and separating task representations in neural networks (Musslick et al., 2017; Musslick & Cohen, 2020; Sagiv, Musslick, Niv, & Cohen, 2020).

How to separate task representations received considerable interest in human empirical and theoretical research. Here, the ability to perform one task while eliminating interference from other tasks, is known as cognitive control. Influential theoretical work (Miller & Cohen, 2001), suggests that cognitive control is implemented as a top-down gating signal that prioritizes relevant information processing in other processing areas. Specifically, it has been suggested that the human prefrontal cortex sends gating signals to more posterior processing areas; such gating signals excite (gates open) task-

relevant processing pathways and inhibit (gates closed) task-irrelevant processing pathways (Aben, Calderon, Van den Bussche, & Verguts, 2020). Hence, the prefrontal cortex can separate information by closing the gates for all processing that might interfere with the current task. This approach has proven fruitful to explain human behavior in cognitively demanding tasks (Abrahamse, Braem, Notebaert, & Verguts, 2016; Botvinick, Braver, Barch, Carter, & Cohen, 2001; Cohen, Dunbar, & McClelland, 1990; Verbeke & Verguts, 2019). However, as noted above, a complete separation between task representations would be inefficient and in some cases the network might benefit from opening the gates to allow for information transfer between similar tasks.

To study the balance between sharing and separation, we consider the nature of top-down signals. Interestingly, there exist some crucial differences in the literature with respect to how top-down gating signals are implemented. For instance, while some research treats the top-down signal as any other input signal and adds all inputs together (Cohen et al., 1990), other research has treated the top-down signal as multiplicative (Masse et al., 2018; O'Reilly & Frank, 2006), which allows to effectively shut down (multiply by zero) activity for irrelevant neurons. Additionally, while in most research the gating signal is adapted to the needs of the current task (Botvinick et al., 2001; Cohen et al., 1990; Verguts & Notebaert, 2008), other work (Bouchacourt & Buschman, 2019; Masse et al., 2018) illustrated that also random, non-adaptive gating signals can be sufficient to allow optimal performance on complex tasks. Hence, random signals can often meet performance of learned signals, while requiring far less computational constraints. Moreover, because less parameters need to be learned, these random gating signals are often faster in learning to process novel inputs. More generally, random signals have proven to be useful in constructing powerful neural networks (Lillicrap, Cownden, Tweed, & Akerman, 2016; Maass, Natschläger, & Markram, 2002). Thus, gating signals differ in whether they are additive or multiplicative and whether they are adaptive or non-adaptive.

The current work provides a systematic investigation of different types of gating signals in balancing the trade-off between shared and separated representations. Specifically, we propose four approaches for gating. In a first approach, non-adaptive additive gating (N+ network) is applied. Here, for each task, a different random top-down signal contributes to the activity patterns in an additive manner. Second, in adaptive additive gating (A+ network), top-down input is also added to the network.

However, in this approach, the top-down input is treated like any other task-processing input in the

sense that top-down weights are susceptible to the same (backpropagation) learning rules as the regular

task-processing weights. Third, in non-adaptive multiplicative gating (Nx network), the network

inhibits and/or excites a random proportion of pathways in every task context by multiplying activation

with zero (inhibition) or a random positive value (excitation). Fourth, in adaptive multiplicative gating

(Ax network), the network learns which processing pathways to excite or inhibit.

Since previous work illustrated that the impact of shared representations depends on the nature

of the task environment (Musslick et al., 2017), networks are tested on three different types of input

(discrete low-dimensional, continuous low-dimensional, and continuous high-dimensional; see also

Figure 1). For each input type, we consider a number of tasks that differ in the amount of overlap of

their stimulus-action mappings. Interestingly, for artificial agents, there is more catastrophic

interference when trained in a blocked fashion. In contrast, blockwise training appears beneficial for

human agents (Flesch, Balaguer, Dekker, Nili, & Summerfield, 2018). To evaluate each network's

ability to overcome interference, we thus trained our artificial networks in a blocked fashion. In sum,

we test the four gating signals on a task that requires them to optimally balance the transfer (sharing)

and avoidance of interference (separating) between tasks. Network performance is evaluated in terms

of accuracy and the ability to find the optimal amount of sharing between task representations.

111   **Methods**

The network

Our network (Figure 1a) consists of an Input, Hidden, and Output layer. Information flows in

a feedforward manner from Input to Hidden to Output layer. All neurons in each layer are fully

connected to all neurons in the next layer. Neurons in the Input layer are divided in a Stimulus group

and a Task group. Activation at the Hidden layer is a combination of input from the Stimulus group and

a gating signal from the Task group. For an additive gating signal we use:

$$H = f(SW_{s,h} + TW_{t,h}) \qquad (1)$$

120   For multiplicative gating, we use

$$\boldsymbol{H} = f(\boldsymbol{SW_{s,h}}) \otimes g(\boldsymbol{TW_{t,h}}) \qquad (2)$$

122   In these equations, $\boldsymbol{H}$, $\boldsymbol{S}$ and $\boldsymbol{T}$ are vectors representing activation in the Hidden, Stimulus and Task

123   group respectively. A weight matrix between layers is represented by $\boldsymbol{W}$. The symbol $\otimes$ represents

124   elementwise multiplication. The functions $f()$ and $g()$ represent (elementwise) nonlinear activation

125   functions. In the main text we consider simulations in which $f()$ represents a sigmoid activation function:

$$sig(\boldsymbol{XW_{x,j}}) = \frac{1}{1 + e^{-(XW_{x,j})}} \qquad (3)$$

128   and $g()$ represents a RELU activation function:

$$RELU(\boldsymbol{XW_{x,j}}) = \max{(0, (\boldsymbol{XW_{x,j}}))} \qquad (4)$$

In these equations, X is a (row) vector representing activity in the sending layer and $\boldsymbol{W_{x,j}}$ represents a

weight matrix between the sending (x) and receiving (j) layer. Thus, Hidden neurons with a negative

weight from the active Task neuron are gated out (activation multiplied by 0), while activation of

Hidden neurons with a positive weight, are multiplied by a positive value. The supplementary materials

present additional simulations in which different combinations of sigmoid and RELU functions are

explored. Activation at the Output layer ($\boldsymbol{O}$) simply follows $\boldsymbol{O} = sig(\boldsymbol{HW_{h,o}})$. After each trial, weights

are adapted by the backpropagation learning rule (Rumelhart, Hinton, & Williams, 1986):

$$\Delta \boldsymbol{W_{x,j}} = -\alpha \times \frac{dE}{d\boldsymbol{W_{x,j}}} \qquad (5)$$

in which again *x* represents the sending layer and *j* represents the receiving layer. The parameter $\alpha > 0$

represents a learning rate, and $\frac{dE}{dW_{x,j}}$ is the (partial) derivative of the error (E) with respect to the weights

(***W***).

Figure 1. Network architecture and simulations. *a: General network architecture.* The network

consists of three layers. Information flows in a feedforward manner from Input to Hidden to Output

layer. The Input layer is divided in a Stimulus and Task group. The Task group sends a gating signal

(red arrow). We evaluate four different types of gating and test the network on three types of stimulus

datasets (b-d). *b: Stroop (discrete) dataset.* Stimuli are a combination of a cue, a color and a word. The

cue indicates which other dimension (word or color) is relevant for responding. Five tasks are defined

in which the mapping between three response options and three values for color and word are changed.

Mappings are represented in the panel. *c: Trees (continuous low-dimensional) dataset.* The stimulus

figure is adopted from Flesch et al (2018). Current work has coded this dataset with two neurons that

can take on any value between 0 and 1. Four tasks are defined in which the network needs to give a yes

or no judgement (one response neuron). *d: MNIST (continuous high-dimensional) dataset.* Here, stimuli

are 28 x 28 pixel images of handwritten digits from 0 to 9. Examples are taken from

https://www.tensorflow.org/datasets/catalog/mnist. We defined six possible tasks in which again the

network needs to give a yes/no judgement.

Datasets

The network was tested on three datasets (Figure 1b-d), allowing us to evaluate several

combinations of input and task type. The first dataset had discrete (binary) low-dimensional input

patterns. Specifically, we consider the classic cognitive control Stroop task. See Figure 1b for an

illustration of the network specifics for this dataset. In this Stroop dataset, on each trial a word is

presented ("red", "green" or "blue") in a particular color (red, green or blue). Additionally, a cue is

provided telling the network to respond either to the word or to the color dimension. Thus, each stimulus

consists of the activation (input value = 1) of 3 out of 8 Stimulus neurons, resulting in 18 (2 instructions

× 3 colors × 3 words) possible stimuli. Additionally, we activate one Task neuron on every trial, which

determines the appropriate mappings between stimuli and responses. In this task, the Output layer

consists of 3 neurons. On each trial, the Output neuron with the highest activation (argmax(O)) is

considered to be the network response. Depending on the task, each color value (red, green or blue) was

linked to one of the neurons in the Output layer. Specifically, we define five tasks (see also Figure 1b).

Here, tasks A, B and C share no stimulus-action mappings. Task D represents a mix of tasks A, B and

C. Specifically, D shares exactly 1/3 of stimulus-action mappings with all three other tasks. The last

task E shared all stimulus-action mappings with A but activated a different neuron in the Task group

(in a sense, A and E are synonyms). Note that we call this a Stroop task because the input consists of

color and word input where one dimension was relevant; we did not mimic the imbalance between color

and word reading that appears in typical Stroop tasks.

The second dataset is the Trees dataset (see also Flesch et al., 2018). Specifics for this dataset

are presented in Figure 1c. In the Trees dataset, there are two Stimulus neurons which can take on any

value in a range of 0 to 1 (continuous low-dimensional input). One Stimulus neuron represents the

'leafiness' of a tree and the other Stimulus neuron represents the 'branchiness' of the tree. The Output

layer contained only one neuron. For this dataset, the network has to make a yes (output = 1) or no

(output = 0) judgement. We defined four different tasks for this input type. One task was to respond yes

to leafy trees, a second task was to respond to branchy trees, a third task required the network to respond

to trees that were both leafy and branchy (AND task), and the fourth task consisted of responding to

trees that were either leafy or branchy (but not both; XOR task). Note that for this dataset there were no

completely (100%) dissimilar tasks. The Leafy and Branchy task share 50% of stimulus-action

mappings with each other but also with the AND and XOR taks. The AND and XOR task share 25%

of mappings with each other.

The third dataset consisted of images (continuous, high-dimensional input). More specifically,

we used the MNIST data set (LeCun, Cortes, & Burges, 2010) which contains grey-scaled images (28

x 28 pixels) of handwritten digits from 0 to 9. Again, the Output layer consisted of one neuron. For this

input type, 6 different tasks were provided. One task was to respond to odd digits (i.e., output = 1 for

odd digits; output = 0 for even digits); another task required a response to even digits. A third and fourth

task required the network to respond to digits that were respectively larger or smaller than 5. The fifth

task consisted of responding to digits larger than 3 and the sixth task was to respond to digits smaller

than 7. This resulted in a complex pattern of overlap between the different tasks. Tasks vary from 100%

dissimilar (odd and even), to only 20% dissimilar (>3 and >5; <5 and <7).

Simulations

As described before, four versions of the network were simulated. Activation at the Hidden

layer follows Equation (1) for additive gating networks (N+ and A+), and Equation (2) for

multiplicative gating networks (Nx and Ax). In adaptive gating networks (A+ and Ax), the weights

between the Task group and Hidden layer are learned by the backpropagation rule (Equation (5)), just

like the other weights. In non-adaptive gating networks (N+ and Nx), the weights between the Task

group and Hidden layer are fixed at their initial (random) values. All weights are initialized with a

random value drawn from the normal distribution N(0, 1). Only for the Ax network, gating weights

(between Task and Hidden layer) had an initial random value drawn from the uniform distribution U(0,

1), such that RELU(T) > 0 (all gates open) at the first trial. Results were similar when gating weights

were also initialized via the normal distribution in the Ax network.

All four versions of the network were tested on all three data sets. Additionally, we explored

different learning rates (α) and shapes of Hidden layer. For the Stroop and Trees input datasets, α took

on 11 values ranging from 0 to 1 in steps of .1. We explored the network with one Hidden layer of either

12 or 24 neurons. For the MNIST dataset we used lower learning rates. Here, α took on 11 values

ranging from 0 to .1 in steps of .01. For this data set, we explored performance with one Hidden layer

of 400 neurons; and also with two Hidden layers, one with 300 and a second one with 100 neurons (see

also LeCun, Bottou, Bengio, & Haffner, 1998). Note that for this dataset, the total number of Hidden

neurons did not differ. Activation at the first Hidden layer (H_1) followed Equation (1) or (2) for additive

or multiplicative networks respectively. Activation at the second Hidden layer followed: $H_2 =$

$sig(H_1 W_{H1,H2})$. Hence, the Task gating signal was not sent directly to the second Hidden layer.

For every combination of α and shape of the Hidden layer, 50 simulations ($N = 50$) were

performed for each dataset. For each simulation, 1200 or 12000 inputs were randomly sampled for the

Trees and MNIST datasets respectively. Since there were only 18 stimuli (input patterns) for the Stroop

dataset, we chose to repeat these 18 stimuli 75 times in each simulation, resulting in 1350 trials.

Additionally, we randomly shuffled the order of tasks before a simulation. In a next step, we divided

the sampled input patterns over 3 repetitions (450, 400 or 4000 trials per block for the Stroop, Trees

and MNIST dataset respectively). In every repetition, the network was trained (training phase)

blockwise on each task, using the predetermined input sample and order of tasks. Thus, each task was

repeated 3 times in a blocked fashion. At the end of the third block, weights were frozen, and the

network was tested (test phase). For this test phase a new order of tasks was generated. Each task was

tested for one block of trials. For this purpose, 100 or 500 new inputs were randomly sampled from the

Trees and MNIST datasets respectively. For the Stroop dataset, no new inputs could be generated so

we repeated the 18 possible inputs 5 times, resulting in 90 trials.

Analyses

Accuracy

To investigate whether networks suffered from catastrophic interference during learning, we

computed accuracy for each task repetition (averaged over all tasks). Networks that suffer from

catastrophic interference would need to relearn a task on every repetition because they would learn

other tasks in between. Hence, such a network would not improve over task repetitions.

Next, we investigated the network's ability to balance separating representations with sharing

representations. More specifically, we computed accuracy for each task during the test phase. For this

analysis we mainly focus on the Stroop dataset but we present results for the other datasets as well. The

Stroop dataset is optimally suited for this analysis since there is a larger variation in (dis)similarities

between tasks (see also the objective dissimilarity table in Figure 2) than is the case for the other

datasets. More specifically, five tasks were proposed for the Stroop dataset. As described in the Methods

section, three of them (A, B and C) did not share any stimulus-action mappings and thus can be totally

separated. Tasks A and E however, share all stimulus-action mappings and can be fully shared.

Additionally, task D shares 1/3 of its stimulus-action mappings with all other tasks. On the one hand, a

full sharing of task representations would allow the network to exploit the shared mappings between A,

D and E but lead to catastrophic interference in tasks B and C, illustrated by a strong decrease of

accuracy in tasks B and C compared to A, D and E. On the other hand, a full separation of tasks would

improve accuracy of tasks B and C (by less interference), but would also eliminate the advantage of the

full overlap between A and E and the partial overlap between D and the other tasks. Hence, accuracy

would be the same for all tasks. Importantly, when the network is only able to fully share or separate

information it would benefit from the full overlap between A and E but would not benefit from the

partial overlap between task D and the other tasks. In sum, an optimal network would find a balance

between sharing and separating, resulting in an improved accuracy for tasks A, D and E while

minimizing the dip in accuracy for tasks B and C.

To evaluate overall performance of the networks we also computed accuracy during the test

phase for all learning rates and all tasks.

Representational dissimilarity

In order to analyze to what extent the networks shared or separated stimulus-action mappings

across tasks, we computed how dissimilarity between tasks in terms of stimulus-action mappings was

represented in the network. This analysis considers several steps. An overview of these steps in the

context of the Stroop dataset is provided in Figure 2.

In a first step, we computed for each simulation the objective dissimilarity between stimulus-

action mappings across tasks. Specifically, we computed a matrix where rows and columns represent

the tasks, and each cell contains the proportion of stimuli that were matched with a different action

across the two respective tasks (row and column).

A second step was to compute the representational dissimilarity within the network. For this

purpose, we first computed the mean activation at Hidden layer for each stimulus (18 Stroop stimuli, 4

quadrants of branchy-leafy space and 10 digits in MNIST dataset) in each task across trials. Then the

difference between task representations was extracted by computing the mean Euclidean distance for

two tasks T1 and T2. Here,

$$Dissimilarity_{T1,T2} = \sum_{S}^{nStim} \left\| \boldsymbol{H}_{T1}^{S} - \boldsymbol{H}_{T2}^{S} \right\| / nStim \qquad (6)$$

in which $\boldsymbol{H}_{T1}^{S}$ and $\boldsymbol{H}_{T2}^{S}$ are vectors of length *nHidden*, representing the average activity for all Hidden

neurons when stimulus S was presented to the network. Hence, we compute the Euclidean distance

(indicated by $\left\| \ldots \right\|$) for each stimulus (S) and each task pair (T_1, T_2). This distance is then averaged

over all possible stimuli (*nStim*) to obtain one dissimilarity matrix of Hidden representations between

tasks.

In a third and last step we compared the objective dissimilarity to the representational

dissimilarity. Specifically, we reshaped both matrices to vectors and computed the Spearman rank

correlation coefficient between these vectors. This resulted in one value of the dissimilarity correlation

between objective task dissimilarity and a network's representational task dissimilarity.

Figure 2. Methods. Illustration of the different steps in the representational dissimilarity analyses.

Examples are shown for one simulations of the Stroop dataset with a learning rate of .5 and 12 Hidden

neurons.

Neural activation analyses

We performed two additional analyses to gain more insight into how the different gating

signals organize Hidden layer activity. For this purpose, we again computed for each task the mean

activation at Hidden layer for each stimulus, resulting in a matrix with size (*nStim*, *nTask*, *nHidden*).

First, we investigated the distribution of activation for all stimuli and tasks across the Hidden neurons.

Second, in order to visualize the network representations for each task, we reduced Hidden layer

dimensionality via principal component analysis. For this purpose, we entered the activation matrix

with size (*nStim*, *nTask*, *nHidden*) into the principal component analysis and approximated it by a matrix

of size (nStim, *nTask*, 2). As a result, we could plot the representation of each stimulus in each task in

a two-dimensional space.

300   **Results**

Accuracy

First, we evaluated the networks' ability to separate task representations. For this purpose, we

investigated whether average accuracy (during the training phase) increased over task repetitions.

Networks that do not separate task sets suffer from catastrophic interference because they overwrite

mappings of one task by the mappings of another task. As a result, such networks need to relearn the

original task when it is presented again, and not show any improvement over task repetitions. In Figure

3, it is observed that accuracy hardly improves for the additive networks (A+ and N+). Thus, these

networks severely suffered from catastrophic interference. In contrast, for multiplicative gating

networks, in particular for the Ax network, there was a significant improvement over task repetitions.

Thus, multiplicative gating signals seem more efficient in separating task representations, rendering

them less vulnerable to catastrophic interference during learning.

Figure 3. Accuracy in training phase per task repetition. Lines illustrate mean accuracy for each

task repetition during the training phase averaged across all learning rates (α), all tasks and all

simulations. Bars indicate standard deviations over 50 simulations. Results are shown for different

datasets (rows) and different shapes of Hidden layer (columns).

Second, we zoomed in on accuracy for each task during the test phase. Here, we focus mainly

on the Stroop dataset (see Methods) because the Stroop dataset has a broader range of dissimilarities

between tasks. Specifically, tasks A, B and C have completely dissimilar mappings, task D has a partial

overlap of 1/3 mappings with all other tasks and task E shares all mappings with task A. An optimal

network would find a balance between sharing and separating, resulting in an improved accuracy for

tasks A, D and E while minimizing the dip in accuracy for tasks B and C (see also Methods). In Figure

4a,b we observe a strong dip in accuracy for tasks B and C when the gating signal was additive. This

suggests that additive gating signals are well suited for sharing task representations, but less so for

separating task representations. This dip in accuracy for tasks B and C is less strong for the

multiplicative gating networks. Importantly, the Nx network has an approximately equal accuracy for

all tasks, especially when there were only 12 hidden neurons (Figure 4a). This suggests that the Nx

network has strongly separated task representations, which did not allow that network to benefit from

overlap between task mappings across the different tasks. The Ax network is clearly the network that

was able to optimally balance the separation and sharing of task representations, showing an advantage

in accuracy for all tasks compared to the other networks, and only a very small dip for tasks A and B.

Note that although task D only had a partial overlap with other tasks, accuracy is equally high as for

tasks A and E which fully overlapped. Hence, the Ax network does not treat sharing or separation as an

all-or-none process, but also captures partial overlap.

Figure 4. Accuracy in test phase per task. Lines illustrate mean accuracy during the test phase for each task, averaged across all learning rates (α) and all simulations. Bars indicate standard deviations over 50 simulations. Results are shown for different datasets (rows) and different shapes of Hidden layer (columns).

We also show results for the other datasets but these are less informative in this respect, because there is no strong variability in objective task dissimilarity (see Methods and Figure 2). For the Trees dataset (Figure 4 c,d) there was an average objective dissimilarity of 50% for the leafy and branchy task, and an average dissimilarity of 41.5% for the AND and XOR tasks. Note that also this small imbalance is visible by a small decrease in accuracy for the AND and XOR tasks. For the MNIST

dataset (Figure 4e, f) there was a strong variability of dissimilarity between tasks themselves (20-100%), but when averaged over all tasks, the range of dissimilarity between one task and all other tasks was rather small (between 56 and 64%). Despite the absence of variability in overall dissimilarity between tasks, it is also clear for the Trees (Figure 4c, d) and MNIST (Figure 4e, f) dataset that the Ax network performs best.

This suggestion that the Ax network is best able to find a balance between sharing and separating task representations, is supported by the fact that this network reaches a higher accuracy overall when we analyze accuracy over all tasks during the test phase. In Figure 5, it is observed that the Ax network outperforms all other networks for all learning rates, all shapes of Hidden layer and all datasets. The non-adaptive additive (N+) network performs worst. The non-adaptive multiplicative gating (Nx) network and the adaptive additive (A+) network perform in between these other networks. Here, the Nx gating network seems to obtain an advantage over the A+ network when there are more Hidden neurons (Figure 5b,d) and for high-dimensional (MNIST; Figure 5e,f) input datasets. In sum, multiplicative gating outperforms additive gating, and adaptive gating outperforms non-adaptive gating.

Figure 5. Accuracy in test phase per learning rate (α). Lines illustrate mean accuracy during the test phase for each value of α, averaged across all tasks and all simulations. Bars indicate standard deviations over 50 simulations. Results are shown for different datasets (rows) and different shapes of Hidden layer (columns).

Representational dissimilarity

We next investigate whether objective dissimilarity of stimulus-action mappings between tasks was represented in the network. For this purpose, we computed for each network simulation a representational dissimilarity matrix and correlated this matrix element-wise with an objective dissimilarity matrix of stimulus-action mappings between tasks (see Methods and Figure 2 for details).

Results of this analysis are shown in Figure 6. As was already suggested by the accuracy results, the

Ax network was clearly better at extracting the objective dissimilarity between tasks. Interestingly, the

A+ network was also (although less strongly) able to capture the objective overlap between tasks for

the Stroop and Trees input datasets, but not for the MNIST dataset (Figure 6e,f).

For the MNIST dataset, we simulated a network with one Hidden layer (Figure 6e) and a

network with 2 Hidden layers (Figure 6f). Here, the network shows a small benefit from dividing the

(same number of) Hidden neurons across 2 layers. However, only the first Hidden layer received a

gating signal. To provide more insight into this benefit for the 2-layer network, we provide results of

the representational dissimilarity analyses in each layer separately (Figure 6g,h). Remarkably, while the

gating signal is only delivered to the first Hidden layer (Figure 6g), it is actually the second (but not the

first) Hidden layer that represents the dissimilarity between tasks (Figure 6h).

Figure 6. Correlation of objective and representational dissimilarity between tasks. Lines illustrate the mean task dissimilarity correlation for each value of α across all simulations. Bars indicate standard deviations over 50 simulations. In a-f, results are shown for different datasets (rows) and different shapes of Hidden layer (columns). In the last row (g and h), results are presented separately for the first and second Hidden layer of the MNIST dataset network with two hidden layers.

Neural activation analysis

To provide additional insight into how the different gating signals organize Hidden layer activity, Figure 7 shows the distribution of activation at Hidden layer for all networks and datasets. Here, it is observed that activation distributions are strongly bimodal with peaks around 0 and 1. Note that, because of the RELU gating signal (see Equations (2) and (4)), activation in the multiplicative gating networks was theoretically not bound to 1. Nevertheless, also these multiplicative gating networks shows a clear activation asymptote of 1 after learning. Interestingly, the multiplicative gating networks illustrate a strong asymmetrical distribution with a higher peak of activity around zero. Especially the Nx network has a high zero-centered peak. This suggests that the Nx network is learning more sparse representations and potentially creates different groups or modules of neurons where each module learns one task. Hence, in line with what was described before, the Nx network is well suited for separating task representations. The activity distribution of the additive networks is clearly more symmetrical with a higher number of neurons that exhibit strong activity for each stimulus and task. As a result, the additive networks will probably share more neurons for representing stimuli and/or tasks. In line with what we described before, the Ax network illustrates a mixture between the properties of the Nx and additive networks and is therefore optimally suited to balance shared and separated representations. Intriguingly, when the networks use multiple Hidden layers, we observe in Figure 7g, h that the differences between the gating networks are more pronounced at the first layer than at the second layer. This contrasts with the previous result (Figure 6g,h) that differences in task representations across networks are more pronounced in the second Hidden layer.

Figure 7. Distribution of activity at Hidden layer. The distribution of activation at the Hidden layer(s) of the different gating networks is shown. In a-f, results are shown for different datasets (rows) and different shapes of Hidden layer (columns). In the last row (g and h), results are presented separately for the first and second Hidden layer of the MNIST dataset network with two hidden layers.

415   For the next analyses, we reduced Hidden layer dimensionality into two principal components

416 with the highest eigenvalues. For the Stroop dataset these components explained on average over all

417 simulations, networks, learning rates and shapes of Hidden layer, 54.2% of the variance (SD = 6.3%).

418 For the Trees dataset, two components explained 71.53% of the variance (SD = 7.6%) and for the

419 MNIST dataset, two components explained 44.52% of the variance (SD = 4.33%). In Figure 8, we show

420 neural representations in the Hidden layer for each stimulus (dots) and each task (colors) on 2

421 dimensions. Notice that this analysis does not allow us to average over simulations. Hence, results are

422 shown for one representative simulation of the network with an intermediate learning rate of α=.5 for

423 the Stroop and Trees dataset and α=.05 for the MNIST dataset.

424   Generally, results are in line with our previous findings in accuracy and representational

425 dissimilarity analyses. For the Stroop dataset, we observe that the additive gating networks show a

426 tendency to share neural representations across tasks (Figure 8c,d,g,h). In contrast, the Nx network

427 (Figure 8b,f) effectively separates the different tasks but fails to share tasks A and E (blue and green

428 dots) which have no dissimilarities in their stimulus-action mappings. The Ax network however, shows

429 a remarkable ability in discovering the overall relational structure between tasks. The network finds

430 three orthogonal axes for the three orthogonal tasks A, B and C. Task D which shares stimulus-action

431 mappings with all previous tasks, is placed in between the representations of A, B and C. Additionally,

432 the network discovered that task E fully overlaps with task A.

433   For the Trees dataset (Figure 8 i-p), all networks were able to separate task representations.

434 Thus, in contrast to the Stroop input datasets, the additive networks were able to separate task

435 representations for the Trees dataset. This explains why the difference in accuracy between networks

436 was much smaller for the Trees dataset in comparison to other datasets (Figure 5). Note that in this

437 dataset the inputs were significantly less complex (only 2 dimensions) than for the other datasets (18 or

438 784 (28^2) dimensions for the Stroop and MNIST dataset respectively). Remarkably, again the Ax

439 network was best able to capture the overall relational structure. Specifically, the Ax network placed

440 the Leafy and Branchy tasks (yellow and blue dots) far away from each other; the other two tasks, which

required to make a combination of leafy and branchy mappings, were placed in between. The other

networks seemed to just separate four tasks without representing an additional relational structure.

For the MNIST dataset, the additive networks again fail to separate task representations

(Figure 8s,t,w,x). Notice that the networks extracted separate representations for the 10 digits (0-9), but

shared the digit representations across all tasks. The Nx network was able to separate task

representations but did not extract a clear relational structure. Again, only the Ax network was able to

extract the full relational structure of the tasks. Here, two dimensions were extracted by the network.

One dimension (Dimension 2) was used to separate the odd from the even tasks, the other dimension

(Dimension 1) was used to separate the larger than (>5 and >3) tasks from the smaller than (<5 and <7)

tasks.

Figure 7. Task representations after principal component analysis. The neural representation for

each stimulus (dots) and each task (colors) are shown along the first two principal components. This is

454 shown for a representative simulation and an intermediate learning rate, for all gating networks

455 (columns) and all shapes of Hidden layer.

457   **Discussion**

Current work investigated how neural networks can optimally balance the trade-off between

avoiding interference via separating task representations and generalizing information via sharing

representations. For this purpose, we identified and systematically investigated two crucial features of

gating signals. First, the gating signals can be additive or multiplicative. Multiplicative signals were

better suited for separating task representations. The multiplicative networks were less vulnerable to

catastrophic interference than the additive networks. Second, the gating signals could be adaptive

(learned) or non-adaptive (random). Adaptive gating signals provided a clear advantage over non-

adaptive gating signals in terms of both accuracy and balancing representations. As a result, the adaptive

multiplicative (Ax) model was able to optimally balance the trade-off between sharing and separating

task representations. This Ax network can avoid interference but also generalize across tasks which

resulted in an overall better accuracy compared to the other networks.

Crucially, multiplicative signals modulated task-specific input more strongly. A Hidden

neuron that receives input from many bottom-up Stimulus neurons, needs a strong (negative) additive

gating signal in order to be inhibited. In contrast, our multiplicative signal followed a RELU activation

function (Equation (4); see Supplementary materials for an investigation of activation functions), which

means that a small negative weight was sufficient to shut down (multiply by zero) a Hidden neuron

activation. As a result, multiplicative signals developed sparser representations (Figure 7) which is

optimal for separating task representations. This advantage was especially present when there were

many Stimulus neurons (i.e., the MNIST task). When there were only 2 Stimulus neurons, as in the

Trees task (see Figure 1c), the additive network was also able to separate task representations (see

Figure 8k,l,o,p). Thus, multiplicative gating signals are more efficient than additive signals, especially

for separating high-dimensional inputs. Specifically, the Ax network warped the representational space

in order to effectively organize tasks that obey similar mappings as well as tasks that obey dissimilar

mappings within one neural architecture. In this representational space, dissimilar tasks were placed at

the edges of a regular grid (see Figure 8q,u) and tasks that were similar were placed closer together. Such a geometrical organization of task rules is optimally suited for generalizing task rules (Bernardi et al., 2020; Kim, Pitt, & Myung, 2013). Consistent with the current analysis, Kim et al., (2013) demonstrated how backpropagation shapes hidden space to accommodate quasi-regularities in language processing, thus to accommodate both regular and irregular stimuli (e.g., orthography-phonology mappings). They demonstrated that after training by backpropagation, both regular and irregular stimuli could be placed in hidden neuron space at the edges of a slightly deformed grid; sufficiently grid-like to process the regular stimuli (and profit from generalization), but sufficiently deformed to cope with irregular mappings as well. Moreover, previous work has illustrated a similar systematicity of task representations in neural activation of prefrontal areas and hippocampus of monkeys (Bernardi et al., 2020).

An extensive amount of work describes how humans share or separate representations by extracting latent states in the environment (Collins & Frank, 2016; Franklin & Frank, 2018; Gershman & Niv, 2012; Wilson, Takahashi, Schoenbaum, & Niv, 2014; Yu, Wilson, & Nassar, 2020). Here, the agent decides on every new experience whether to categorize it as belonging to a new state or as belonging to a state that it has experienced before. Each latent state would then develop its own representations. An important disadvantage of the latent state approach is that it uses a dichotomous decision on whether an object belongs to the state or not. Such an approach is less suited to capture partial overlap between tasks. In the example of the Stroop dataset, a latent state approach would correctly assign tasks A, B and C to three different states because the mappings are completely dissimilar. The latent state approach would also correctly assign task E to the same latent state as A because they fully share the stimulus-action mappings. However, task D shares 1/3 of the mappings with all four other tasks. In this case, D would be optimally handled as a combination of the other mappings that are already learned. This is problematic for a latent state approach since it can only decide to assign D to a new latent state or to one of the previous ones. Alternatively, the latent state approach could allow mixed overlap between tasks by representing a task as multiple states, each representing a subset of mappings (Franklin & Frank, 2020). Nevertheless, this approach could significantly increase the number of possible states, which can be problematic in very complex task environments. As we

have shown in Figure 4a,b, the current Ax network could benefit equally from the partial overlap in D

and the full overlap between A and E without the need of extracting latent states. An important avenue

for future research is to further compare both approaches in explaining behavioral and neural data

(Palminteri, Wyart, & Koechlin, 2017).

A crucial question that remains is how multiplicative signals are mechanistically implemented

in the human brain. In this respect, we point to recent work that described an important role for neural

oscillations in organizing functional networks. For example, it has been proposed that neural

oscillations at alpha frequency (8-12 Hz) reflect gating by inhibition (Jensen & Mazaheri, 2010). Here,

GABAergic inhibition provided by the task-irrelevant areas would be reflected by stronger alpha

activity in those areas. Another oscillatory frequency that is known to organize functional networks in

the brain is the theta frequency (4-8 Hz). More specifically, recent theoretical and empirical work

(Helfrich & Knight, 2016; Lisman & Jensen, 2013; Verbeke et al., 2021; Verbeke & Verguts, 2019;

Verguts, 2017) has proposed that prefrontal theta activity functions to (de)synchronize gamma (>40

Hz) activity in posterior processing areas. Here, synchronization leads to effective communication

(gates open) between processing areas while desynchronization eliminates effective communication

(gates closed) between processing areas (Fries, 2005, 2015). Thus, previous work has described how

oscillatory interactions within and between different frequency bands (theta, alpha and gamma) reflect

gating processes that could biologically implement the multiplicative gating signals that were used in

the current networks.

Previous work has also described how neurotransmitters such as dopamine and catecholamine

can modulate neural activation in a way that mimics multiplicative gating (O'Reilly & Frank, 2006;

Servan-Schreiber, Printz, & Cohen, 1990). Moreover, current work observed that additive gating can

reach similar performance as multiplicative gating when stimulus dimensionality was low (Trees

dataset). Hence, combining additive gating with weight regularization approaches between Stimulus

and Hidden layer but not between Task and Hidden layer would allow the additive gating networks to

overcome high-dimensional inputs and reach similar performance as the multiplicative gating networks.

Future work should further explore biologically plausible implementations of multiplicative gating.

In analogy to previous work (e.g., Cohen et al., 1990), the current networks used a low-

dimensional Task layer which sent gating signals to modulate a higher-dimensional Hidden layer.

Typically, information in the Task layer has been considered to correspond to dorsolateral prefrontal

cortex (DLPFC) and the Hidden layer to posterior task-related (e.g., visual and motor) processing

pathways (Miller & Cohen, 2001). Hence, we propose that gating signals are implemented by DLPFC.

A detailed investigation of activation at Hidden layer (Figure 7) illustrated that

(multiplicative) networks separate tasks by developing sparse representations (see also Bowers,

Vankov, Damian, & Davis, 2014). Here, for every task, only a small subset of neurons is active. In the

current context, this suggests that the network develops groups or modules of neurons that each become

specialized for a given task. Developing specialized modules might be beneficial for cognition in

various ways (Bullinaria, 2007; Clune, Mouret, & Lipson, 2013; Coltheart, 1999; Fodor, 1983;

Meunier, Lambiotte, Fornito, Ersche, & Bullmore, 2009). Moreover, recent work in reinforcement

learning has also described hierarchical forms of modularity (Botvinick, Niv, & Barto, 2009; Dietterich,

2000; Holroyd & Verguts, 2021; Krueger & Dayan, 2009). Here, it is proposed that the dorsal part of

the anterior cingulate cortex processes prediction errors related to specific events while the rostral part

processes prediction errors related to the context in which these events occur (Alexander & Brown,

2015). However, modularity of processes in a single task requires integration of information across

stages of processing. Hence, exploring the trade-off between sharing and separating representations at

different levels of processing is an important avenue for future research.

In the current work, gating signals are employed to guide learning over trials. Here, (for the

adaptive networks) weights between the Task and Hidden layer are adapted to learn representations of

different tasks. In contrast, a lot of previous work considered how gating is adapted to guide online

performance. Here, the intensity of the gating signal is typically increased in response to some

evaluation of the cost-benefit structure of the task context (Shenhav, Botvinick, & Cohen, 2013). These

networks typically adapt the intensity of the gating signal by changing activity in the Task layer instead

of changing the weights (Botvinick et al., 2001; Verbeke & Verguts, 2020; Verguts, 2017). Consistent

with this approach, research on visual attention has proposed that activity can be modulated (in a

multiplicative manner) at the level of the Stimulus layer (Martinez-Trujillo & Treue, 2004; Treue &

Martínez Trujillo, 1999). Alternatively, previous work (Cheadle et al., 2014) suggested that decisions

can be guided via adaptive (multiplicative) gain functions in the transfer from input to output. Hence,

there is a potentially important functional distinction between gating in learning versus performance

(see also Lindsay & Miller, 2017).

The trade-off between shared and separated representation also impacts performance

(Mussllick et al., 2020). Specifically, a wide range of empirical observations of interference during

multi-tasking (performing multiple tasks at the same time) can be explained by a tendency to share task

representations. Musslick et al. (2020) suggest that for generalization purposes, representations of novel

tasks should strongly overlap with other task representations; unfortunately, such overlap leads to strong

interference when these tasks need to be performed at the same time. However, with extensive training,

the networks will gradually separate task representations, which leads to less interference. Hence, future

work should consider a more extensive exploration of gating signals in performance as well.

We evaluated the ability of different gating signals to balance shared and separated

representations by investigating how the networks could overcome catastrophic interference.

Importantly, while gating has proven to be efficient (Masse et al., 2018; Verbeke & Verguts, 2019),

previous work also described other methods to avoid catastrophic interference. For instance, sharing or

separation of task sets might be implemented in complementary learning systems (O'Reilly & Norman,

2002). Alternatively, machine learning literature has introduced methods such as synaptic intelligence

(Kirkpatrick et al., 2017) in which weights learn whether they should be specific for one task and hence

not change during further learning or whether they can be shared across all tasks. Future work should

further address the differences between these approaches.

Several additional tests and extensions can be made to the network. First, previous work

(Flesch et al., 2018) has pointed to an important distinction between interference in artificial and human

agents. While artificial agents show more interference when they learn in a blocked fashion, human

agents exhibit more interference when they learn in an interleaved fashion. The current work trained

artificial agents in a blocked fashion. However, the different types of gating signals should also be

evaluated for interleaved learning. Potentially this approach could yield more insight in the existing

distinction of learning benefits for artificial compared to human agents. Second, the current networks

did not learn which task features were relevant for gating. Here, the input layer was divided a-priori in

a Stimulus group and a Task group. Hence, an important next step for the network would be to learn a

hierarchical structure in input features in order to extract which inputs are relevant for gating and which

are relevant for basic stimulus-action mappings (Rougier, Noelle, Braver, Cohen, & O'Reilly, 2005).

Fourth, although we illustrated that the Ax network was able to significantly benefit (in terms of

accuracy) from shared mappings between tasks (Figure 4a,b), we did not perform a direct test of

generalization. That is, we did not evaluate whether newly learned mappings in Task A of the Stroop

task were transferred to task E without further training in task E. For this purpose, the weight matrix

between Task neuron A and the Hidden layer should be exactly the same as the weight matrix between

Task neuron E and the Hidden layer, which seems a strong requirement. Yet, it is not clear either

whether two contexts that require the same stimulus-action mappings would also function in exactly

the same way at behavioral and neural levels. Nor is this computationally desirable: In the natural

environment, two labels that lead to the same stimulus-action contingencies, may still suggest (subtle)

differences. Consider looking for lunch and seeing a "restaurant" versus a "snack bar" in the distance:

Both tell you that you will be able to eat there, but expectations will differ at least slightly. As we

discussed before, extracting a relational structure between contexts that allows for partial generalization

might be more optimal than using a dichotomous same or different decision.

In sum, efficient human learning and performance requires to balance a trade-off between

sharing representations to allow generalization and separating representations to avoid interference. We

evaluated four different gating signals and found that an adaptive multiplicative gating signal was best

suited to balance the sharing/separation trade-off. This gating signal allowed the Hidden layer of the

network to make a geometrical abstraction of the relational structure between tasks. Importantly, our

work opens several avenues for future work to increase the understanding of the sharing/separation

trade-off in both artificial and human agents.

References

Aben, B., Calderon, C. B., Van den Bussche, E., & Verguts, T. (2020). Cognitive Effort Modulates

Connectivity between Dorsal Anterior Cingulate Cortex and Task-Relevant Cortical Areas. *The*

Journal of Neuroscience, *40*(19). https://doi.org/10.1523/jneurosci.2948-19.2020

Abrahamse, E., Braem, S., Notebaert, W., & Verguts, T. (2016). Grounding Cognitive Control in

Associative Learning. *Psychological Bulletin*, *142*(7), 693–728.

https://doi.org/10.1037/bul0000047

Alexander, W. H., & Brown, J. W. (2015). Hierarchical error representation: A computational model

of anterior cingulate and dorsolateral prefrontal cortex. *Neural Computation*, *27*(11), 2354–

2410. https://doi.org/10.1162/NECO

Alon, N., Reichman, D., Shinkar, I., Wagner, T., Musslick, S., Cohen, J. D., … Ozcimder, K. (2017).

A graph-theoretic approach to multitasking. In *Advances in Neural Information Processing*

Systems (pp. 2097–2106).

Baxter, J. (2019). Learning Internal Representations. In *Proceedings of the eigth annual conference*

on computational learning theory (pp. 311–320).

https://doi.org/10.7551/mitpress/2906.003.0006

Bernardi, S., Benna, M. K., Rigotti, M., Munuera, J., Fusi, S., & Salzman, C. D. (2020). The

Geometry of Abstraction in the Hippocampus and Prefrontal Cortex. *Cell*, *183*(4), 954–967.

https://doi.org/10.1016/j.cell.2020.09.031

Botvinick, M. M., Braver, T. S., Barch, D. M., Carter, C. S., & Cohen, J. D. (2001). Conflict

monitoring and cognitive control. *Psychological Review*, *108*(3), 624–652.

https://doi.org/10.1037/0033-295X.108.3.624

Botvinick, M. M., Niv, Y., & Barto, A. C. (2009). Hierarchically organized behavior and its neural

foundations : A reinforcement learning perspective. *Cognition*, *113*(3), 262–280.

https://doi.org/10.1016/j.cognition.2008.08.011

Bouchacourt, F., & Buschman, T. J. (2019). A Flexible Model of Working Memory. *Neuron*, *103*(1),

147–160. https://doi.org/10.1016/j.neuron.2019.04.020

Bowers, J. S., Vankov, I. I., Damian, M. F., & Davis, C. J. (2014). Neural networks learn highly

selective representations in order to overcome the superposition catastrophe. *Psychological*

Review, *121*(2), 248–261. https://doi.org/10.1037/a0035943

Bullinaria, J. A. (2007). Understanding the emergence of modularity in neural systems. *Cognitive*

Science, *31*(4), 673–695. https://doi.org/10.1080/15326900701399939

Cheadle, S., Wyart, V., Tsetsos, K., Myers, N., deGardelle, V., HerceCastañón, S., & Summerfield, C.

(2014). Adaptive gain control during human perceptual choice. *Neuron*, *81*(6), 1429–1441.

https://doi.org/10.1016/j.neuron.2014.01.020

Clune, J., Mouret, J. B., & Lipson, H. (2013). The evolutionary origins of modularity. *Proceedings of*

the Royal Society B: Biological Sciences, *280*(1755). https://doi.org/10.1098/rspb.2012.2863

Cohen, J. D., Dunbar, K., & McClelland, J. L. (1990). On the control of automatic processes: a

parallel distributed processing account of the Stroop effect. *Psychological Review*, *97*(3), 332–

361. https://doi.org/10.1037/0033-295X.97.3.332

Collins, A. G. E., & Frank, M. J. (2016). Neural signature of hierarchically structured expectations

predicts clustering and transfer of rule sets in reinforcement learning. *Cognition*, *152*, 160–169.

https://doi.org/10.1016/j.cognition.2016.04.002

Coltheart, M. (1999). Modularity and cognition. *Trends in Cognitive Sciences*, *3*(3), 115–120.

https://doi.org/10.1016/S1364-6613(99)01289-9

Dietterich, T. G. (2000). Hierarchical reinforcement learning with the MAXQ value function

decomposition. *Journal of Artificial Intelligence Research*, *13*, 227–303.

https://doi.org/10.1613/jair.639

Flesch, T., Balaguer, J., Dekker, R., Nili, H., & Summerfield, C. (2018). Comparing continual task

learning in minds and machines. *Proceedings of the National Academy of Sciences of the United*

States of America, *115*(44). https://doi.org/10.1073/pnas.1800755115

Fodor, J. A. (1983). *The modularity of mind*. MIT Press/Bradford Books.

Franklin, N. T., & Frank, M. J. (2018). Compositional clustering in task structure learning. *PLoS*

Computational Biology, *14*(4), 1–25. https://doi.org/10.1371/journal.pcbi.1006116

Franklin, N. T., & Frank, M. J. (2020). Generalizing to generalize: Humans flexibly switch between

compositional and conjunctive structures during reinforcement learning. *PLoS Computational*

Biology, *16*(4), 1–33. https://doi.org/10.1371/journal.pcbi.1007720

French, R. M. (1999). Catastrophic forgetting in connectionist networks. *Trends in Cognitive*

Sciences, *3*(4), 128–135.

Fries, P. (2005). A mechanism for cognitive dynamics: neuronal communication through neuronal

coherence. *Trends in Cognitive Sciences*, *9*(10), 474–480.

https://doi.org/10.1016/j.tics.2005.08.011

Fries, P. (2015). Rhythms for Cognition: Communication through Coherence. *Neuron*, *88*(1), 220–

235. https://doi.org/10.1016/j.neuron.2015.09.034

Gershman, S. J., & Niv, Y. (2012). Exploring a latent cause theory of classical conditioning. *Learning*

and Behavior, *40*(3), 255–268. https://doi.org/10.3758/s13420-012-0080-8

Helfrich, R. F., & Knight, R. T. (2016). Oscillatory Dynamics of Prefrontal Cognitive Control. *Trends*

in Cognitive Sciences, *20*(12), 916–930. https://doi.org/10.1016/j.tics.2016.09.007

Holroyd, C. B., & Verguts, T. (2021). The best laid plans: Computational principles of ACC. *Trends*

in Cognitive Sciences, *25*(4), 316–329. https://doi.org/10.1016/j.tics.2021.01.008

Jensen, O., & Mazaheri, A. (2010). Shaping functional architecture by oscillatory alpha activity:

Gating by inhibition. *Frontiers in Human Neuroscience*, *4*, 1–8.

https://doi.org/10.3389/fnhum.2010.00186

Kim, W., Pitt, M. A., & Myung, J. I. (2013). How Do PDP Models Learn Quasiregularity?

Psychological Review, *120*(4), 903–916. https://doi.org/10.1037/a0034195

Kirkpatrick, J., Pascanu, R., Rabinowitz, N., Veness, J., Desjardins, G., Rusu, A. A., … Hadsell, R.

(2017). Overcoming Catastrophic Forgetting in Neural Networks. *Proceedings of the National*

Academy of Sciences, *114*(13), 3521–3526. https://doi.org/10.1073/pnas.1611835114

Krueger, K. A., & Dayan, P. (2009). Flexible shaping: How learning in small steps helps. *Cognition*,

110(3), 380–394. https://doi.org/10.1016/j.cognition.2008.11.014

LeCun, Y., Bottou, L., Bengio, Y., & Haffner, P. (1998). Gradient-based learning applied to

document recognition. *Proceedings of the IEEE*, *86*(11), 2278–2323.

https://doi.org/10.1109/5.726791

LeCun, Y., Cortes, C., & Burges, C. J. (2010). MNIST handwritten digit database.

Lillicrap, T. P., Cownden, D., Tweed, D. B., & Akerman, C. J. (2016). Random synaptic feedback

weights support error backpropagation for deep learning. *Nature Communications*, *7*, 1–10.

https://doi.org/10.1038/ncomms13276

Lindsay, G. W., & Miller, K. D. (2018). How biological attention mechanisms improve task

performance in a large-scale visual system model. *ELife*, *7*, 1–29.

https://doi.org/10.7554/eLife.38105.001

Lisman, J. E., & Jensen, O. (2013). The Theta-Gamma Neural Code. *Neuron*, *77*(6), 1002–1016.

https://doi.org/10.1016/j.neuron.2013.03.007

Maass, W., Natschläger, T., & Markram, H. (2002). Real-time computing without stable states: A

new framework for neural computation based on perturbations. *Neural Computation*, *14*(11),

2531–2560. https://doi.org/10.1162/089976602760407955

Martinez-Trujillo, J. C., & Treue, S. (2004). Feature-Based Attention Increases the Selectivity of

Population Responses in Primate Visual Cortex. *Current Biology*, *14*, 744–751.

https://doi.org/10.1016/j.cub.2004.04.028

Masse, N. Y., Grant, G. D., & Freedman, D. J. (2018). Alleviating catastrophic forgetting using

context-dependent gating and synaptic stabilization. *Proceedings of the National Academy of*

Sciences, *115*(44), 1–12. https://doi.org/10.1073/pnas.1803839115

McClelland, J. L., McNaughton, B. L., & O'Reilly, R. C. (1995). Why There Are Complementary

Learning Systems in the Hippocampus and Neo-cortex: Insights from the Successes and Failures

of Connectionists Models of Learning and Memory. *Psychological Review.*, *102*(3), 419–457.

https://doi.org/10.1037/0033-295X.102.3.419

Meunier, D., Lambiotte, R., Fornito, A., Ersche, K. D., & Bullmore, E. T. (2009). Hierarchical

modularity in human brain functional networks. *Frontiers in Neuroinformatics*, *3*, 1–12.

https://doi.org/10.3389/neuro.11.037.2009

Miller, E. K., & Cohen, J. D. (2001). An Integrative Theory of Prefrontal Cortex Function. *Annual*

Review of Neuroscience, *24*, 167–202. https://doi.org/10.1146/annurev.neuro.24.1.167

Musslick, S., & Cohen, J. D. (2020). Rationalizing constraints on the capacity for cognitive control.

PsyArxiv, 45. https://doi.org/10.31234/osf.io/vtknh

Musslick, S., Saxe, A. M., Ozcimder, K., Dey, B., Henselman, G., & Cohen, J. D. (2017).

Multitasking Capability Versus Learning Efficiency in Neural Network Architectures. In *Annual*

meeting of the Cognitive Science Society (pp. 829–834).

Musslick, S., Saxe, A., Novick, A., Reichman, D., & Cohen, J. D. (2020). On the rational

boundedness of cognitive control: Shared versus separated representations. *PsyArXiv*.

https://doi.org/10.31234/osf.io/jkhdf

O'Reilly, R. C., & Frank, M. J. (2006). Making Working Memory Work : A Computational Model of

Learning in the Prefrontal Cortex and Basal Ganglia. *Neural Computation*, *18*(2), 283–328.

https://doi.org/10.1162/089976606775093909

O'Reilly, R. C., & Norman, K. A. (2002). Hippocampal and neocortical contributions to memory:

Advances in the complementary learning systems framework. *Trends in Cognitive Sciences*,

6(12), 505–510. https://doi.org/10.1016/S1364-6613(02)02005-3

Palminteri, S., Wyart, V., & Koechlin, E. (2017). The Importance of Falsification in Computational

Cognitive Modeling. *Trends in Cognitive Sciences*, *21*(6), 425–433.

https://doi.org/10.1016/j.tics.2017.03.011

Rougier, N. P., Noelle, D. C., Braver, T. S., Cohen, J. D., & O'Reilly, R. C. (2005). Prefrontal cortex

and flexible cognitive control: Rules without symbols. *Proceedings of the National Academy of*

Sciences of the United States of America, *102*(20), 7338–7343.

https://doi.org/10.1073/pnas.0502455102

Rumelhart, D. E., Hinton, G. E., & Williams, R. J. (1986). Learning representations by back-

propagating errors. *Nature*, *323*, 533–536. https://doi.org/10.1038/323533a0

Sagiv, Y., Musslick, S., Niv, Y., & Cohen, J. D. (2020). Efficiency of learning vs. processing:

Towards a normative theory of multitasking. In *Proceedings of the 40th Annual Meeting of the*

Cognitive Science Society, (p. 1004—1009).

Servan-Schreiber, D., Printz, H., & Cohen, J. D. (1990). A network model of catecholamiine effects:

Gain, signal-to-noise ratio, and behavior. *Science*, *249*(4971), 892–895.

https://doi.org/10.1126/science.2392679

Shenhav, A., Botvinick, M. M., & Cohen, J. D. (2013). The expected value of control: An integrative

theory of anterior cingulate cortex function. *Neuron*, *79*(2), 217–240.

https://doi.org/10.1016/j.neuron.2013.07.007

Treue, S., & Martínez Trujillo, J. C. (1999). Feature-based attention influences motion processing

gain in macaque visual cortex. *Nature*, *399*, 575–579. https://doi.org/10.1038/21176

Tsai, C. Y., Saxe, A., & Cox, D. (2016). Tensor switching networks. *Advances in Neural Information*

Processing Systems, (Nips), 2046–2054.

Vaidya, A. R., Jones, H. M., Castillo, J., & Badre, D. (2020). Neural representation of abstract task

structure during generalization. *BioRxiv*, 2020.07.21.213009.

https://doi.org/10.1101/2020.07.21.213009

Verbeke, P., Ergo, K., De Loof, E., Verguts, T., Loof, E. De, & Verguts, T. (2021). Learning to

synchronize: Midfrontal theta dynamics during reversal learning. *Journal of Neuroscience*,

41(7), 1–13. https://doi.org/10.1523/JNEUROSCI.1874-20.2020

Verbeke, P., & Verguts, T. (2019). Learning to synchronize: How biological agents can couple neural

task modules for dealing with the stability-plasticity dilemma. *PLoS Computational Biology*,

15(8). https://doi.org/10.1371/journal.pcbi.1006604

Verbeke, P., & Verguts, T. (2020). Neural synchrony for adaptive control. *Psyarxiv*, 1–37.

https://doi.org/10.31234/osf.io/523x9

Verguts, T. (2017). Binding by random bursts: A computational model of cognitive control. *Journal*

of Cognitive Neuroscience, *29*(6), 1103–1118. https://doi.org/10.1162/jocn

Verguts, T., & Notebaert, W. (2008). Hebbian Learning of Cognitive Control : Dealing With Specific

and Nonspecific Adaptation. *Psychological Review*, *115*(2), 518–525.

https://doi.org/10.1037/0033-295X.115.2.518

Wilson, R. C., Takahashi, Y. K., Schoenbaum, G., & Niv, Y. (2014). Orbitofrontal cortex as a

cognitive map of task space. *Neuron*, *81*(2), 267–279.

https://doi.org/10.1016/j.neuron.2013.11.005

Yu, L. Q., Wilson, R. C., & Nassar, M. R. (2020). Adaptive learning is structure learning in time.

Psyarxiv, 1–27. https://doi.org/10.31234/osf.io/r637c

Zambaldi, V., Raposo, D., Santoro, A., Bapst, V., Li, Y., Babuschkin, I., … Battaglia, P. (2018).

Relational Deep Reinforcement Learning, (2), 1–15. Retrieved from

http://arxiv.org/abs/1806.01830

Supplementary materials:

Exploration of activation functions

In the main text, multiplicative gating was established by $H = \text{sig}(\boldsymbol{SW_{s,h}}) \otimes \text{RELU}(\boldsymbol{TW_{t,h}})$ (see Equation (2)). Here, we did not present a clear reason why we chose to use a sigmoid activation function for lower-level processing and a RELU activation function for top-down gating signals. In order to provide some more information on the effect of the different activation functions, we present additional network simulations. As in the main text, four networks were simulated. However, for this additional test, all networks used adaptive multiplicative gating but we crossed the activation functions. Thus, a first network used a sigmoid activation function for both types of processing (S-S network), a second network used a RELU activation function for both types of processing (R-R) network. The third network corresponded to the network in the main text and used a sigmoid activation function for the lower-level processing and a RELU function for the gating signal (S-R network). The fourth network used the RELU activation function for lower-level processing and the sigmoid activation for gating purposes (R-S network).

For these additional simulations, the networks were only simulated on the Stroop dataset with 12 Hidden neurons. In line with the main text, weights that used RELU activation were initialized by sampling from the uniform distribution while weights that used sigmoid activation were initialized by sampling from the normal distribution. We did explore different values of α going from 0 to 1 in steps of .1. Again, 50 simulations were performed in which we shuffled task contexts and trained networks for three context repetitions after which weights were frozen and the networks were tested again on each context.

Accuracy was analysed during the test phase. As can be observed (Figure S1a), the R-S network performed significantly worse than the three other networks which illustrated approximately equal performance. Also the correlation between objective and representational dissimilarity across task sets was clearly lower for the R-S network. Additionally, at lower learning rate (α) values, there was a lower correlation for the S-S network compared to the networks that used a RELU function for gating purposes.

Principal component analyses revealed that indeed the R-S network illustrated similar problems as the additive networks of the main text in which task set representations were not separated. The other three networks were clearly able to capture the relational structure of the different task sets. All networks clearly separated task sets A, B and C, discovered a full overlap between task set A and E and a partial overlap between D and all other task sets. Notice however that although the structure of representations of the S-S network is similar to the R-R and S-R network, task sets are less strongly separated in the S-S network. This is probably the result of the fact that the RELU function provides a wider range of activation levels. Specifically, in contrast to the sigmoid activation function it has no upper bound (of 1). Additionally, sigmoid activation functions have a lower asymptote of zero but can never reach an activation of exactly zero. In contrast, RELU gating signals can fully inhibit neurons by sending a zero signal.

Figure S1. Results of activation exploration. *a:* shows accuracy for all networks (colors) and all values of α . *b*: shows the correlation between objective and representational differences across task sets for all networks (colors) and all values of α. Lines represent means and bars illustrate standard deviations across 50 replications.

Figure S2. Task set representations after principal component analysis. The neural representation for each stimulus (dots) and each task (colors) are shown along two dimensions after a principal component analysis. This is shown for a random replication and a learning rate (α) of .5 but for all four networks.