Modelling brain representations of abstract concepts

Daniel Kaiser[1,*], Arthur M. Jacobs[2,3], Radoslaw M. Cichy[2,4,5]

[1]Department of Psychology, University of York

[2]Department of Education and Psychology, Freie Universität Berlin

[3]Center for Cognitive Neuroscience Berlin, Freie Universität Berlin

[4]Berlin School of Mind and Brain, Humboldt-Universität zu Berlin

[5]Bernstein Center for Computational Neuroscience Berlin

*Correspondence:

danielkaiser.net@gmail.com

Abstract

Abstract conceptual representations are critical for human cognition. Despite their

importance, key properties of these representations remain poorly understood. Here,

we used computational models of distributional semantics to predict multivariate fMRI

activity patterns during the activation and contextualization of abstract concepts. We

devised a task in which participants had to embed abstract nouns into a story that

they developed around a given background context. We found that representations

in inferior parietal cortex were predicted by concept similarities emerging in models

of distributional semantics. By constructing different model families, we reveal the

models' learning trajectories and delineate how abstract and concrete training

materials contribute to the formation of brain-like representations. These results

inform theories about the format and emergence of abstract conceptual

representations in the human brain.

Introduction

The use of conceptual knowledge is one of the foundations of human intelligence. On the neural level, concepts are represented in a complex network of brain regions (Binder et al., 2009). Fueled by novel computational models of distributional semantics, researchers have recently started to unravel the format of concept representations in this neural network. By harnessing linguistic co-occurrence statistics, these models not only capture representations of concepts from written and spoken language (Deniz et al., 2019; Huth et al., 2016; Just et al., 2010; Mitchell et al., 2008), but also predict representations of novel concepts (Pereira et al., 2019).

However, these recent advances in understanding the representations of conceptual knowledge largely hinge on the study of concrete concepts. Only few studies have investigated how abstract concept representations are organized (Anderson et al., 2014; Vargas & Just, 2020; Wang et al., 2018). To date, key questions about the emergence and the format of these representations remain heavily debated (Borghi et al., 2017).

Here, we model brain representations that support the activation and contextualization of abstract concepts. We recorded fMRI while participants were tasked with embedding abstract words into a background context. By relating brain activations during this task to targeted models of distributional semantics, we shine a new light on the format of abstract concept representations in the human brain.

Results and Discussion

In an fMRI experiment, we visually presented 61 abstract German nouns (see Materials and Methods). Participants (n=19) read these words and silently embedded them into a coherent story that they were developing around a prespecified contextual background (Figure 1a).

Cortical responses were modelled in a representational similarity searchlight analysis (Figure 1b), in which we extracted similarity relations among the words across the whole cortex (see Materials and Methods). We modelled these similarities using a word2vec model of distributional semantics (Mikolov et al., 2013), trained on a 45-million sentence corpus (SdeWaC; Faaß & Eckhart, 2013).

This model predicted brain activations in the left inferior parietal cortex (IPC; Figure 1c), most prominently covering the angular gyrus, but extending into the superior parietal and middle occipital cortices (158 voxels, peak: -36/-58/46, t[18]=6.16), and in right IPC, with an anterior cluster primarily in the supramarginal gyrus (91 voxels, peak: 45/-46/58, t[18]=4.91), and a posterior cluster in the angular gyrus (35 voxels, peak: 36/-73/40, t[18]=4.80). These results show that bilateral IPC represents semantic similarities of abstract concepts. They further suggest IPC as a cortical hub for the activation and contextualization of abstract concepts.

Figure 1. Representation of abstract concepts in parietal cortex. a) Participants
completed 10 runs of fMRI recordings. Before each run, they established a unique
background context in their mind and were then asked to silently narrate a story of
their own making that included the subsequently presented 61 abstract words, in
random order (all German word stimuli in Supplementary Information). b) In a
searchlight analysis, representational dissimilarity matrices (RDMs) were extracted (i)
from the brain data, by pairwise correlations among localized activity patterns, and (ii)
from a word2vec model of distributional semantics, by pairwise correlations among
hidden-layer activations. c) Correlating the neural and model RDMs revealed clusters
in bilateral inferior parietal cortex (IPC), primarily covering the angular gyrus. Brain
maps are thresholded at $p_{voxel}<0.001$ (uncorrected) and $p_{cluster}<0.05$ (FWE-corrected).
d) These clusters persisted when repeating the analyses while partialing out the effects
of emotional word content (using affect grids), visual wordform (using a visual-
categorization DNN), and auditory properties of the spoken words (using a speech-
recognition DNN). e) Within the IPC cluster defined on the full 45-million sentence
model (marked by an arrow), we compared model families trained on different corpus
sizes and on only abstract or concrete words, respectively. Brain-like representations
emerged in models that were trained on as little as 100,000 sentences and on either
abstract or concrete embeddings. Dots show individual-participant data, error bars
denote SEM, asterisks represent p<0.05 (FDR-corrected).
95
96 **Controlling for emotional and sensory word properties**
97
Some researchers have argued that abstract concepts are represented through their
grounding in the emotional domain (Kousta et al., 2011; Vigliocco et al., 2011). To test
whether IPC representations are indeed driven by the words' emotional content, we
re-performed the analysis while partialing out valence and arousal ratings (see
Materials and Methods). We still found clusters in left (36 voxels, peak: -33/-64/31,
t[18]=4.73), and right (108 voxels, peak: 63/-40/31, t[18]=7.30) IPC, suggesting that
the emotional content is insufficient to explain abstract concept representation in
parietal cortex.
106

IPC is also sensitive to sensory properties, such as visual form (Freud et al., 2018) and

phonological speech attributes (Hartwigsen et al., 2010). However, when repeating

the analysis while partialing out early activations in a visual-categorization deep neural

network (DNN; see Materials and Methods), we still found clusters in the left (157

voxels, peak: -36/-58/46, t[18]=6.07) and right (anterior: 76 voxels, peak: 51/-49/52,

t[18]=4.70; posterior: 32 voxels, peak: 39/-76/40, t[18]=4.82) IPC. Similarly, when

controlling for activations obtained from a speech-recognition DNN (see Materials and

Methods), we still found clusters in left (113 voxels, peak: -33/-64/31, t[18]=5.43,

$p_{cluster}$<0.001), and right (53 voxels, peak: 48/-46/55, t[18]=4.68) IPC. These results

show that sensory properties are unrelated to IPC representations of abstract

concepts.

Trajectories towards brain-like representations

Our observation that the word2vec model and IPC share abstract concept

representations led us to ask how the model acquires this property. To test whether

co-occurrence statistics are acquired incrementally over increasing experience with

human language, we devised a word2vec model family whose members were trained

on staggered amounts of data, from the full 45-million sentence corpus down to

fragments as small as 1,000 sentences. We then evaluated how well models trained

on less data could still predict representations in the IPC cluster that yielded the best

correspondence with the full 45-million sentence model (see Materials and Methods).

This analysis revealed decreasing correspondence with decreasing training data

(mean r=0.74, t[18]=5.89, p<0.001). Nonetheless, a model trained on only 100,000

sentences (~0.2% of the corpus) still predicted IPC representations well (t[18]=3.46,

p_{FDR}=0.002; comparison to full model: t[18]=2.15, p=0.045), whereas models trained

on smaller training sets did not (Figure 1d). These results show that brain-like

representations are learned through linguistic co-occurrence statistics, which can

emerge already from a (relatively) modest degree of training experience.

Extracting meaning from abstract and concrete embeddings

Some theorists argue that the meaning of abstract concepts needs to be derived

through the activation of related concrete concepts, which are in turn grounded in

sensory experiences (Kiefer & Pulvermüller, 2012; Lakoff, 2008). This view prompts

the hypothesis that representations of abstract concepts originate primarily from co-

occurrence statistics between abstract and concrete words, rather than among

abstract words alone. To test this hypothesis, we trained word2vec models on

subsets of the 45-million sentence corpus that we devised to consist of abstract or

concrete words only (see Materials and Methods).

Models trained on abstract-only and concrete-only corpora both predicted

representations in IPC (Figure 1e). Reproducing the previous pattern of results, we

found that models trained on larger fractions of the corpus predicted representations

better (abstract only: mean r=0.36, t[18]=2.55, p=0.010; concrete-only: mean r=0.73,

t[18]=4.32, p<0.001). Interestingly, representations were modelled equally well by the

most extensively trained abstract-only (t[18]=3.09, p_{FDR}=0.010) and concrete-only

models (t[18]=2.60, p_{FDR}=0.018; comparison: t[18]=0.50, p=0.62), suggesting that

brain-like representations of abstract concepts can emerge from either abstract or

concrete semantic embeddings.

Conclusions

Our findings yield multiple key insights into abstract concept representation:

First, our findings provide novel evidence for IPC as a core area for concept coding

(Binder et al., 2009). Using a task that required participants to activate and

contextualize abstract concepts, we identify the angular gyrus as a critical hub for the

dynamic use of abstract knowledge, consistent with the view that this region plays a

key role in combinatory linguistic processing (Graessner et al., 2021; Price et al., 2015;

Pylkkänen, 2019). Such combinatory processing is critical in real-life situations that

require applying abstract knowledge in a situational and meaningful way.

Second, our study informs theories of abstract knowledge representation (Borghi et

al., 2017). We show that the meaning of abstract concepts can be derived from

distributional word embeddings in natural language (Wang et al., 2018). Interestingly,

the organization of abstract concepts, as found in our brains, can be derived from

linguistic embeddings in both abstract and concrete realms of knowledge. This result

shows that despite their representational dissimilarities (Binder et al., 2005; Wang et

al., 2010), abstract and concrete concepts may derive their meaning through shared

principles. By contrast, our data do not provide evidence for theories suggesting that

abstract concepts are coded solely through emotional associations (Vigliocco et al.,

2011) or the activation of related concrete concepts (Harpaintner et al., 2020; Lakoff,

2008). They rather suggest that abstract knowledge is represented through concept

relationships in the language processing system.

Third, our results establish that computational models of distributional semantics

acquire brain-like abstract concept representations by harnessing co-occurrence

statistics from linguistic experience. Although massive corpora are immensely popular

for modelling language organization, our analyses of model learning trajectories show

that brain-like representations can emerge from much smaller training sets of only

100,000 sentences. Future work could map out the emergence of more fine-grained

information along these model learning trajectories to predict human concept learning

and development (Vigliocco et al., 2018).

Finally, our study highlights that computational models – through systematic

manipulation of model training regimes – can yield targeted insights into the

emergence and format of concept representations. Moving ahead, future studies

could not only refine training regimes but also comprehensively manipulate

fundamental model parameters such as architecture, learning material and learning

procedure (Cichy & Kaiser, 2019). Such model-based analyses may yield further fine-

grained insights into how our brain represents abstract knowledge.

Materials and Methods

Participants

Nineteen healthy adults (mean age 28.8 years, SD=6.1; 10 female) with normal or corrected-to-normal vision completed the experiment. All of them were right-handed and native German speakers. Participants provided informed consent and received monetary reimbursement or course credits for participation. Participants were recruited from the online participant database of the Berlin School of Mind and Brain (Greiner, 2015). All procedures were approved by the local ethical committee and were in accordance with the Declaration of Helsinki.

Stimuli and Paradigm

The stimulus set consisted of 61 abstract German nouns. All words and their English translations can be found in the Supplementary Information (Table S1).

During the fMRI experiment, participants completed 10 runs. Before each run, participants read through one of 10 contextual background stories. All texts and their English translations can be found in the Supplementary Information (Table S2). Participants were asked to mentally image themselves being in the scenario outlined in the text. After reading through the text, participants were instructed to use the subsequently presented words in the upcoming run to mentally narrate a story that incorporates the words as they are shown on the screen. They were instructed that it is completely up to them how the story unfolds as long as they use all the words in their story. Stories were chosen to be emotionally engaging to increase participants' immersion into the task. The order of the 10 stories was randomized for every participant.

Each run contained 61 experimental trials. On each trial, one of the abstract words was shown for 3 seconds, in black Arial font on a gray background. Trials were separated by an inter-trial interval of 1.5 seconds, during which a fixation cross was shown. In addition to the experimental trials, each run included 14 fixation trials, where

only the fixation cross was shown throughout the trial. Trial order was randomized
within each run.

To ensure that participants paid attention to the words, we introduced a simple
manual task: In each run, 7 of the word were shown in pink color and participants had
to press a button whenever they saw one them.

Runs started and ended with brief fixation periods; each run lasted 5:48 minutes. The
stimulation was back-projected onto a translucent screen at the end of the MRI
scanner bore and controlled using the Psychtoolbox (Brainard, 1997).

Additionally, prior to the experiment, each participant completed a practice run (using
a background text different from the ones used in the experiment).

Two participants completed a version of the experiment that differed in two aspects:
the inter-trial interval was 1s instead of 1.5s and no behavioral task was included.

MRI acquisition and preprocessing

MRI data was acquired using a 3T Siemens Tim Trio Scanner equipped with a 12-
channel head coil. T2*-weighted gradient-echo echo-planar images were collected as
functional volumes (TR=2s, TE=30ms, 70° flip angle, $3mm^3$ voxel size, 37 slices, 20%
gap, 192mm FOV, 64×64 matrix size, interleaved acquisition). Additionally, a T1-
weighted image (MPRAGE; $1mm^3$ voxel size) was obtained as a high-resolution
anatomical reference. Preprocessing was done in MATLAB using SPM12
(www.fil.ion.ucl.ac.uk/spm/). The functional volumes were realigned and coregistered
to the T1 image. The T1 image was normalized to MNI-305 standard space to obtain
transformation parameters used to normalize participant-specific results maps (see
below).

Representational similarity analysis

To quantify neural representations, we used multivariate representational similarity
analysis (RSA) (Kriegeskorte et al., 2008). In RSA, neural representations are first
characterized by means of their pairwise similarity structure (i.e., how similarly each
stimulus is represented with each other stimulus). The pairwise dissimilarities between
neural representations are organized in neural representational dissimilarity matrices
(RDMs) indexed in rows and columns by the experimental conditions compared.
Then, the neural similarity structure (i.e., the neural RDMs) are correlated to model
RDMs, which capture different aspects of the conditions' similarity. Significant
correlations between the neural RDMs and these model RDMs indicate that the
aspect of similarity conveyed by the model is represented in the brain.

Extracting neural dissimilarity

Separately for each participant and each run, we first modeled the functional MRI data
in a general linear model (GLM) with 67 predictors (61 predictors for the 61 words,
and 6 predictors for the 6 movement regressors obtained during realignment). From
these GLMs, we obtained 610 beta weights of interest for every voxel, which
quantified the voxel's activation to each of the 61 words in each of the 10 runs. All
further analyses were carried out using a searchlight approach (Kriegeskorte et al.,
2006), that is, analyses were done repeatedly for a spherical neighborhood (3-voxel
radius) centered on each voxel across the brain. This approach allowed us to quantify
and model neural representations in a continuous and unconstrained way across
brain space.

For each searchlight neighborhood, neural RDMs were created based on the similarity
of multi-voxel response patterns, using the CoSMoMVPA toolbox (Oosterhof et al.,
2016). Within each neighborhood, we extracted the response pattern across voxels
evoked by each word in each run. We then performed a cross-validated correlation
analysis (Haxby et al., 2001). For this analysis, the data were repeatedly split into two
halves (all possible 50/50 splits; results were later averaged across these splits) and
the response patterns for each word were averaged within each half. For each pair of
words, we then computed two correlations: (i) within-condition correlations were
computed by correlating the response patterns evoked by each of the two words in

one half of the data with the response patterns evoked by the same word in the other

half of the data, and (ii) between-condition correlations were computed by correlating

the response patterns evoked by each of the two words in one half of the data with

the response patterns evoked by the other word in the other half of the data. By

subtracting the between-correlations from the within-correlations for each pair of

words, we obtained an index of how dissimilar two words are based on the response

patterns they evoked in the current searchlight neighborhood. Repeating this analysis

for each pair of words yielded a 61×61 neural RDM for each searchlight.

Modelling neural dissimilarity

To model the semantic representation of the abstract words, we used a word2vec

computational model of distributional semantics (Mikolov et al., 2013). The model was

trained on the SdeWaC corpus, which contains 45 million German sentences (Faaß &

Eckhart, 2013) using the gensim library (https://github.com/RaRe-

Technologies/gensim). The model hyperparameters were the following: dimensions =

300, model type = skipgram, windowsize = 5, minimum count = 1, iterations = 50. For

each word in the corpus, this model yields a vector representation that indicates its

position in a 300-dimensional vector space. Distances in this vector space reflect

similarities in contextual embeddings. We then created a 61×61 RDM based on the

pairwise correlations of the 300 vector-space features for each of the words used in

the experiment.

To establish correspondences between the model and the brain data, the model

RDMs were correlated with the neural RDMs for each searchlight. These correlations

were then Fisher-transformed and mapped back to the searchlight center. We thereby

obtained brain maps of correspondence between each model and the neural data.

For each participant, these maps were warped into standard space by using the

normalization parameters obtained during preprocessing.

Controlling for emotional, visual, and auditory word properties

As an emotional content model, we used participants' responses in an affect grid task, where 20 participants (partly including the participants in the current experiment) concurrently rated each word's valence and arousal by selecting one compartment of a 9×9 grid (Russell et al., 1989). From these data, we created two RDMs: (i) a valence RDM, whose entries reflected pairwise absolute difference in the words' valence ratings and (ii) an arousal RDM, whose entries reflected pairwise absolute difference in the words' arousal ratings. The valence and arousal RDMs were mildly correlated with each other (r=0.19) and with the different word2vec model RDMs (all r<0.24). The words' similarity in valence an arousal did not significantly predict brain activations in a searchlight analysis.

As a visual word form model, we used activations in the three earliest convolutional layers an AlexNet DNN pre-trained on object recognition (Krizhevsky et al., 2012; Vedaldi & Lenc, 2015), which have been shown to capture representations of simple visual attributes in visual cortex (Cichy et al., 2016). We printed the 61 words as they appeared in the experiment on a 225×225 pixel gray image background and fed the resulting images to the background. The resulting network activations were used to construct model RDMs. For each of the first three convolutional layers of the network, the RDM was constructed by computing pairwise distances (1-correlation) between layer-specific activation vectors. The visual DNN RDMs were only very weakly correlated with the word2vec model RDMs (all r<0.1). Searchlight analyses revealed that the first three layers of the visual DNN predicted activations in bilateral posterior visual cortex, including fusiform cortex (see Supplementary Information, Figure S1).

As a model of auditory, phonetic word similarity, we used activations in a DNN model of auditory speech recognition (Kell et al., 2018). We obtained spoken versions of the 61 words from the ttsmp3 webpage (https://ttsmp3.com/text-to-speech/German/). The sound files were resized to a length of 2 seconds by right-padding them with zeros, transformed into a cochleagram representation, and then passed through the speech recognition branch of the DNN. The resulting network activations were used to construct model RDMs. For each of the seven layers of the network, the RDM was constructed by computing pairwise distances (1-correlation) between layer-specific activation vectors. The auditory DNN RDMs were only weakly correlated with the

word2vec model RDMs (all r<0.16). Searchlight analyses revealed that the early layers

of the auditory DNN, because of the correlation between word length and speech

duration, also predicted activations in bilateral posterior visual cortex. By contrast,

the last layer of the network specifically predicted activations in left middle temporal

gyrus (see Supplementary Information, Figure S1).

To control for emotional and sensory properties, we performed searchlight analyses

relating the neural RDMs and the word2vec model RDMs as before, while we partialed

out the two emotion predictor RDMs, the three visual DNN predictor RDMs, or the

seven auditory DNN predictor RDMs, respectively. All other aspects of the analyses

remained identical.

Region of interest analyses

For further dissecting the representations in left parietal cortex, we specifically

focused on this area in a region-of-interest (ROI) analysis. The IPC clusters that

showed significant correspondence with the word2vec model in the main analysis

were chosen as the ROI. Neural RDMs were generated from pairwise correlations of

activity patterns across all voxels in the ROI; the procedure was otherwise identical

to the procedure applied in the searchlight analysis (see above).

As ROI definition was done on the basis of the model that was trained on the full 45-

million sentences SDeWaC corpus, we never evaluated this model statistically in our

ROI analysis. We instead probed the correspondence between neural RDMs in the

ROI and RDMs built from a set of different word2vec model families whose training

regimes differed in important aspects.

To probe the behavior of our word2vec model with changes in training set, we created

a model family whose members were trained on different amounts of data. Models

were trained on different fragments of the corpus (containing 45m, 10m, 1m, 100k,

10k, or 1k sentences). Each of these fragments corresponded to the first *n* sentences

in the corpus (e.g., the 1k model comprised the first 1,000 sentences). We thereby

ensured that the smaller fragments were always completely included in the larger
ones.
397
Additionally, we constructed a model family whose members were trained on abstract
words and a model family whose members were trained on concrete words. Members
in each family differed by the amount of data they were trained on (as outlined above).
Abstract and concrete words were defined on the basis of the abstractness-
concreteness scale of the IMS norms (https://www.ims.uni-
stuttgart.de/en/research/resources/experiment-data/affective-norms) (Köper & im
Walde, 2017). For the abstract-only models, we chose words that had a z-value of <0
on the on this scale and removed all other words from the corpus; this left us with ~65
million words (~4% of the corpus). For the concrete-only models, we chose words
that had a z-value of >0 and removed all other words from the corpus; this left us with
~280 million words (~18% of the corpus). Note that for the concrete-only model, the
61 abstract words were also left in the corpus, so that relationships between them
and the concrete words could be obtained. For all models of each model family, we
extracted a 61×61 RDM, which was then correlated with the neural RDM extracted for
the ROI; these correlations were Fisher-transformed before statistical analysis.
413
414 ***Statistical testing***
415
For the searchlight analyses, to detect spatial clusters in which the neural data were
explained by the different representational models, we performed one-sided t-tests
against zero across participants, separately for each voxel in the correlation maps.
The resulting statistical maps were thresholded at the voxel level at $p_{voxel} < 0.001$
(uncorrected) and at the cluster level at $p_{cluster} < 0.05$ (family-wise error corrected, as
implemented in SPM12).
422
For the cross-validated ROI analyses, ROIs were repeatedly defined in 18
participants, using the same statistical thresholding as in the full searchlight analysis
($p_{voxel} < 0.001$, $p_{cluster} < 0.05$ FWE-corrected). Correlations between neural RDMs
extracted from the ROIs and model RDMs were then evaluated using one-sided t-

tests against zero across participants. Results were corrected for multiple

comparisons across the different training corpus sizes using FDR corrections.

Data availability

Data are publicly available on OSF (https://doi.org/10.17605/OSF.IO/FTBJQ). For

other materials, please contact the corresponding author.

Acknowledgements

Thanks to Raphael Leuner and Kshitij Dwivedi for help with the computational

analyses. D.K. and R.M.C. are supported by DFG grants (KA4683/2-1, CI241/1-1,

CI241/3-1, CI241/7-1). R.M.C. is supported by an ERC Starting Grant (ERC-2018-StG

803370).

References

Anderson AJ, Murphy B, Poesio M. (2014). Discriminating taxonomic categories and

domains in mental simulations of concepts of varying concreteness. J Cogn

Neurosci, 26, 658-681.

Binder JR, Westbury CF, McKiernan KA, Possing ET, Medler DA. (2005). Distinct

brain systems for processing concrete and abstract concepts. J Cogn

Neurosci, 17, 905-917.

Binder JR, Desai RH, Graves WW, Conant LL. (2009). Where is the semantic

system? A critical review and meta-analysis of 120 functional neuroimaging

studies. Cereb Cortex, 19, 2767-2797.

Borghi AM, et al. (2017). The challenge of abstract concepts. Psychol Bull, 143, 263-

292.

Brainard DH. (1997). The psychophysics toolbox. Spat Vis, 10, 433-436.

Cichy RM, Kaiser D. (2019). Deep neural networks as scientific models. Trends Cogn

Sci, 23, 305-317.

Cichy RM, Khosla A, Pantazis D, Torralba A, Oliva A. (2016). Comparison of deep
neural networks to spatio-temporal cortical dynamics of human visual object
recognition reveals hierarchical correspondence. Sci Rep, 6, 27755.

Deniz F, Nunez-Elizalde AO, Huth AG, Gallant JL. (2019). The representation of
semantic information across human cerebral cortex during listening versus
reading is invariant to stimulus modality. J Neurosci, 39, 7722-7736.

Faaß G, Eckhart K. (2013). SdeWaC – a corpus of parsable sentences from the web.
In: Gurevych I, Biemann C, Zesch T (eds). Language processing and
knowledge in the web. Lecture notes in computer science, vol. 8105.
Springer, Berlin, Heidelberg.

Freud E, Culham JC, Plaut DC, Behrmann M. (2018). The large-scale organization of
shape processing in the ventral and dorsal pathways. eLife, 6, e27576.

Graessner A, Zaccarella E, Hartwigsen G. (2021). Differential contributions of left-
hemispheric language regions to basic semantic composition. Brain Struct
Funct, 226, 501-518.

Greiner B. (2015). Subject pool recruitment procedures: organizing experiments with
ORSEE. JESA, 1, 114-125.

Hartwigsen G, et al. (2010). Phonological decisions require both the left and right
supramarginal gyri. Proc Natl Acad Sci USA, 107, 16494-16499.

Harpaintner M, Sim E-J, Trumpp NM, Ulrich M, Kiefer M. (2020). The grounding of
abstract concepts in the motor and visual system: an fMRI study. Cortex,
124, 1-22.

Haxby JV, et al. (2001). Distributed and overlapping representations of faces and
objects in ventral temporal cortex. Science, 293, 2425-2430.

Huth AG, de Heer WA, Griffiths TL, Theunissen FE, Gallant JL. (2016). Human
natural speech reveals the semantic maps that tile human cerebral cortex.
Nature, 532, 453-458.

Just MA, Cherkassky VL, Aryal S, Mitchell TM. (2010). A neurosemantic theory of
concrete noun representation based on the underlying brain codes. PLoS
One, 5, e8622.

Kell AJ, Yamins DL, Shook EN, Norman-Haignere SV, McDermott JH. (2018). A
task-optimized neural network replicates human auditory behavior, predicts

brain responses, and reveals a cortical processing hierarchy. Neuron, 98,
630-644.

Kiefer M, Pulvermüller F. (2012). Conceptual representations in mind and brain:
Theoretical developments, current evidence and future directions. Cortex, 48,
805-825.

Köper M, im Walde SS. (2017). Improving verb metaphor detection by propagating
abstractness to words, phrases and individual senses. Proceedings of the 1st
workshop on sense, concept and entity representations and their
applications, 24-30.

Kousta ST, Vigliocco G, Vinson DP, Andrews M, Del Campo E. (2011). The
representation of abstract words: why emotion matters. J Exp Psychol Gen,
140, 14.

Kriegeskorte N, Goebel R, Bandettini P. (2006). Information-based functional brain
mapping. Proc Natl Acad Sci USA, 103, 3863-3868.

Kriegeskorte N, Mur M, Bandettini P. (2008). Representational similarity analysis –
connecting the branches of systems neuroscience. Front Syst Neurosci, 2, 4.

Krizhevsky A, Sutskever I, Hinton GE. (2012). ImageNet classification with deep
convolutional neural networks. Advances in Neural Information Processing
Systems, 1097–1105.

Lakoff G. (2008). The neural theory of metaphor. In: Gibbs Jr, WR (ed). The
Cambridge handbook of metaphor and thought. Cambridge University Press,
Cambridge.

Mikolov T, Chen K, Corrado G, Dean J. (2013). Efficient estimation of word
representations in vector space. arXiv, arXiv:1301.3781.

Mitchell TM, et al. (2008). Predicting human brain activity associated with the
meanings of nouns. Science, 320, 1191-1195.

Oosterhof NN, Connolly AC, Haxby JV. (2016). CoSMoMVPA: Multi-modal
multivariate pattern analysis of neuroimaging data in Matlab/GNU Octave.
Front Neuroinform, 10, 20.

Pereira F, et al. (2019). Toward a universal decoder of linguistic meaning from brain
activation. Nat Commun, 9, 1-13.

Price AR, Bonner MF, Peelle JE, Grossman M. (2015). Converging evidence for the
neuroanatomic basis of combinatorial semantics in the angular gyrus. J
Neurosci, 35, 3276-3284.

Pylkkänen L. (2019). The neural basis of combinatory syntax and semantics.
Science, 355, 62-66.

Russell JA, Weiss A, Mendelsohn GA. (1989). Affect grid: a single-item scale of
pleasure and arousal. J Personal Soc Psychol, 57, 493.

Vargas R, Just MA. (2020). Neural representations of abstract concepts: identifying
underlying neurosemantic dimensions. Cereb Cortex, 30, 2157-2166.

Vedaldi A, Lenc K. (2015). MatConvNet – convolutional neural networks for Matlab.
ACM International Conference on Multimedia.

Vigliocco G, et al. (2011). The neural representation of abstract words: the role of
emotion. Cereb Cortex, 24, 1767-1777.

Vigliocco G, Ponari M, Norbury C. (2018). Learning and processing abstract words
and concepts: insights from typical and atypical development. Top Cogn Sci,
10, 533-549.

Wang J, Conder JA, Blitzer DN, Shinkareva SV. (2010). Neural representation of
abstract and concrete concepts: a meta-analysis of neuroimaging studies.
Hum Brain Mapp, 31, 1459-1468.

Wang X, et al. (2018). Organizational principles of abstract words in the human
brain. Cereb Cortex, 28, 4305-4318.