An image reconstruction framework for characterizing initial visual encoding

Ling-Qi Zhang[1]*, Nicolas P. Cottaris[1], and David H. Brainard[1]
[1]Department of Psychology, University of Pennsylvania
*lingqiz@sas.upenn.edu

Abstract

We developed an image-computable observer model of the initial visual encoding that operates on natural image input, based on the framework of Bayesian image reconstruction from the excitations of the retinal cone mosaic. Our model extends previous work on ideal observer analysis and evaluation of performance beyond psychophysical discrimination, takes into account the statistical regularities of the visual environment, and provides a unifying framework for answering a wide range of questions regarding the visual front end. Using the error in the reconstructions as a metric, we analyzed variations of the number of different photoreceptor types on human retina as an optimal design problem. In addition, the reconstructions allow both visualization and quantification of information loss due to physiological optics and cone mosaic sampling, and how these vary with eccentricity. Furthermore, in simulations of color deficiencies and interferometric experiments, we found that the reconstructed images provide a reasonable proxy for modeling subjects' percepts. Lastly, we used the reconstruction-based observer for the analysis of psychophysical threshold, and found notable interactions between spatial frequency and chromatic direction in the resulting spatial contrast sensitivity function. Our method is widely applicable to experiments and applications in which the initial visual encoding plays an important role.

Introduction

Visual perception begins at the retina, which takes sensory measurements of the light incident at the eyes. This initial representation is then transformed by computations that support perceptual inferences about the external world. Even these earliest sensory measurements, however, do not preserve all of the information available in the light signal. Factors such as optical aberrations, spatial and spectral sampling by the cone mosaic, and noise in the cone excitations all limit the information available downstream.

One approach to understanding the implications of such information loss is ideal observer analysis, which evaluates the optimal performance on psychophysical discrimination tasks. This allows for quantification of the limits imposed by features of the initial visual encoding, as well as predictions of the effect of variation in these features (Geisler 1989, 2011). Ideal observer analysis separates effects due to the visual representation from inefficiencies in the processes that mediate the discrimination decisions themselves. Such analyses have often been applied to analyze performance for simple artificial stimuli, assuming that the stimuli to be discriminated are known exactly (Banks, Geisler, and Bennett 1987; Davila and Geisler 1991) or known statistically with some uncertainty (Pelli 1985; Geisler 2018). The ideal observer approach has been extended to consider decision processes that learn aspects of the stimuli being discriminated, rather than being provided with these a priori, and extended to handle discrimination and estimation tasks with naturalistic stimuli (Burge and Geisler 2011, 2014; Singh et al. 2018; Chin and Burge 2020; Kim and Burge 2020). For a recent review see Burge (2020); also see Tjan and Legge (1998) and Cottaris et al. (2019, 2020).

It is generally accepted that the visual system has internalized the statistical regularities of natural scenes, so as to take advantage of these regularities for making perceptual inferences (Attneave 1954; Field 1987; Shepard 1987; Knill, Kersten, and Yuille 1996). This motivates interest in extending ideal observer analysis to apply to fully naturalistic input, while incorporating the statistical regularities of natural scenes (Burge 2020). Here we pursue an approach to this goal that, in addition, extends the evaluation of performance to a diverse set of objectives.

We developed a method that, under certain assumptions, optimally reconstructs images from noisy cone excitations, with the excitations generated from an accurate image-computable[1] model of the front end of the visual system (Cottaris et al. 2019, 2020). The image reconstruction approach provides us with a unified framework for characterizing the information loss due to various factors in the initial encoding. In the next sections, we show analyses that: 1) use image reconstruction error as an information metric to understand the retinal mosaic "design" problem, with one example examining the implications of different allocations of retinal cone types; 2) allow both visualization and

---

[1] We use the term "image-computable" here in contrast with observer models that operate on abstract and/or hypothetical internal representations.

69 quantification of information loss due to physiological optics and cone mosaic sampling
70 and how this varies with eccentricity, as well as with different types of color deficiency;
71 3) combine the image reconstruction approach with analysis of psychophysical
72 discrimination, providing an way to incorporate into such analyses the assumption that
73 our visual system takes into account the statistical regularities of natural images.
74
75 **Results**
76
We developed a Bayesian method to reconstruct images from sensory measurements,
which we describe briefly here (see *Methods* for details). We begin with a forward model
that expresses the relation between an image and its visual representation at a well-
defined stage in the visual pathway. Here that stage is the excitations of the
photoreceptors of the retinal cone mosaic, so that our model accounts for blur in retinal
image formation, spatial and spectral sampling by the cone mosaic, and the noise in the
cone excitations. The approach is general, however, and may be applied to other sites
in the visual pathways (see e.g., Naselaris et al. 2009; Parthasarathy et al. 2017). Our
forward model is implemented within the open-source software package ISETBio
(isetbio.org; **Fig. 1A-C**) which encapsulates the probabilistic relationship between the
stimulus (i.e., pixel values of a displayed RGB image) and the cone excitations (i.e.,
trial-by-trial photopigment isomerizations). ISETBio simulates the process of displaying
an image on a monitor (**Fig. 1A**), the wavelength-dependent optical blur of the human
eye and spectral transmission through the lens and the macular pigment (**Fig. 1B**), as
well as the interleaved spatial and chromatic sampling of the retinal image by the L, M
and S cones (**Fig. 1C**). Noise in the cone signals is characterized by a Poisson process.
The forward model allows us to compute the *likelihood* function. The likelihood function
represents the probability that an observed pattern of cone excitations was produced by
any given image.
96
97 To obtain a *prior* over natural images, we applied independent components analysis
98 (ICA, see *Methods*) to a large dataset of natural images (Russakovsky et al. 2015), and
99 fit an exponential probability density function to the individual component weights (**Fig.**
100 **1D**). The prior serves as our description of the statistical structure of natural images.
101
102 Given the likelihood function, prior distribution, and an observed pattern of cone
103 excitations, we can then obtain a reconstruction of the original image stimulus by
104 applying Bayes rule to find the posterior probability of any image given that pattern. We
105 take the reconstructed image as the one that maximizes the *a posteriori* probability
106 (MAP estimate, see *Methods*) (**Fig. 1D**).
107
108
109
110

111
112
Figure 1: Model of the Initial Visual Encoding and Bayesian Reconstruction from Cone
Mosaic Excitation. (A) The visual stimulus, in our case a natural image in RGB format, is
displayed on a simulated monitor, which generates a hyperspectral scene representation of that
image. **(B)** The hyperspectral image is blurred with a set of wavelength-dependent point-spread
functions typical of human optics. We also account for spectral transmission through the lens
and the macular pigment. This process produces the retinal image at the photoreceptor plane.
(C) The retinal image is then sampled by a realistic cone mosaic, which generates cone
excitations (isomerizations) for each cone. The trial-by-trial variability in the cone excitations is
modeled as a Poisson process. **(D)** Our Bayesian reconstruction method takes the pattern of
cone excitations as input and estimates the original stimulus (RGB image) based on the
likelihood function and a statistical model (prior distribution) of natural images (See *Methods*).
124

Basic Properties of the Reconstructions:
To understand the consequences of initial visual encoding, we need to study the
interaction between the likelihood function (i.e., our model of the initial encoding) and
the statistics of natural images (i.e., the image prior). There are strong constraints on
the statistical structure of natural images, such that natural images occupy only a small
manifold within the space of all possible images. The properties of the initial encoding
produce ambiguities with respect to what image is displayed when only the likelihood
function is considered, but if these can be resolved by taking advantage of the statistical
regularities of the visual environment, they should in principle, not prohibit effective
visual perception. To illustrate this point, consider the simple example of discrete signal
sampling: Based on the sampled signal, one cannot distinguish between the original
signal from all its possible aliases (Bracewell 1986). However, with the prior knowledge
that the original signal contains only frequencies below the Nyquist frequency of the
sampling array, this ambiguity is resolved. In the context of our current study, the role of
the natural image prior comes in several forms, as we will demonstrate in Results. First,
since the reconstruction problem is underdetermined, the prior is a regularizer, providing
a unique MAP estimate; Second, the prior acts as a denoiser, counteracting the Poisson
noise in the cone excitation; Lastly, the prior guides the spatial and spectral
demosaicing of the signals provided via the discrete sampling of the retinal image by the
cone mosaic.
145
To highlight the importance of prior information while holding the likelihood function
fixed, we can vary a parameter γ that adjusts the weight of the log-prior term in the
reconstruction objective function (see *Methods*). Explicitly manipulating γ reveals the
effect of the prior on the reconstruction (**Fig. 2**). When γ is small, the reconstruction is
corrupted by the noise and the ambiguity of the initial visual encoding (**Fig. 2A, 2B**).
When γ is large, the prior leads to desaturation and over-smoothing (**Fig. 2E**) in the
reconstruction. For the rest of our simulations, the value of γ is determined on the
training set by a cross-validation procedure that minimizes the reconstruction error,
unless specified otherwise (**Fig. 2C**).
155

156
157
Figure 2: Effect of Prior Weight on Reconstructed Image. Reconstruction error for an
example natural image using a 1-deg foveal mosaic and root sum of squared distance (RSS, y-
axis) in the pixel space as the error metric, as a function of weight γ on the log-prior term (x-
axis, see *Methods*) in the reconstruction objective function. The reconstructed image obtained
with each particular γ value is shown alongside each corresponding point. Image **C** corresponds
to the value of γ obtained through the cross-validation procedure (see *Methods*). The images at
the bottom are magnified versions of a subset of the images for representative γ values, as
indicated by the solid dots in the plot.
166

To further elucidate properties of the Bayesian reconstruction, especially the interaction
between the likelihood and prior, we plotted a few representative images in a log-prior,
log-likelihood coordinate system, given a particular instance of cone excitations (**Fig. 3**).
The optimal reconstruction, taken as the MAP estimate, has both a high prior probability
and likelihood value as expected (**Fig. 3A**). In fact, for our reconstruction algorithm,
there should not exist any image above the $\gamma x + y = c$ line that goes through **A** (solid
line, **Fig. 3**), otherwise the optimization routine has failed to find the global optimum.
The original image stimulus (ground truth) has a slightly lower likelihood value, mainly
due to noise present in the cone excitations, and also a slightly lower prior probability,
possibly due to the fact that our prior is only an approximation to the true natural image
distribution (**Fig. 3B**). The detrimental effect of noise becomes prominent in a maximum
likelihood estimate (MLE, **Fig. 3C**): Noise in the cone excitations is interpreted as true
variation in the original image stimulus, thus slightly increasing the likelihood value but
also creating artifacts. Such artifacts are penalized by the prior in other reconstructions.
Furthermore, even without the presence of noise, other features of the initial visual
encoding (e.g., **Fig. 1B, C**) cause loss of information and ambiguity for the
reconstruction. This is illustrated by a set of images that lie on the equal likelihood line
with the MAP reconstruction (**Fig. 3D**): There exist an infinite set of variations in the
image (stimulus) that have no effect on the value of the likelihood function[2] (i.e.,
variations within the null space of the linear likelihood render matrix, see *Methods*).
Thus, the cone excitations provide no information to distinguish between images that
differ by such variations. However, as with the case of noise, variations inconsistent with
natural images are discouraged by the prior. Other corruptions of the image, such as
addition of white noise in the RGB pixel space, are countered by both the likelihood and
prior (**Fig. 3E**). Lastly, for illustrative purposes, we can increase the prior probability of
the reconstruction relative to the optimal by making it spatially or chromatically more
uniform (**Fig. 3F**), but doing so decreases the likelihood.
194

---

[2] One implication of the existence of the null space is that the MLE solution to the reconstruction problem
is actually underdetermined, as an entire subspace of images can have the same likelihood value. In the
figure we show one arbitrarily chosen MLE estimate.

Figure 3: Solution Space of Image Reconstruction. Given a particular instance of cone excitations, we can evaluate the (log-)prior probability (x-axis) and (log-)likelihood value (y-axis) for arbitrary images. Here, a few representative images are shown together with their corresponding location in a log-prior, log-likelihood coordinate system. **(A)** The optimal MAP reconstruction obtained via the reconstruction algorithm. The solid line shows $\gamma x + y = c$, with the value of c evaluated at the optimal reconstruction and with the value of γ matched to that obtained through cross-validation. **(B)** Original input image (ground truth). **(C)** A reconstruction generated by maximum likelihood estimation (MLE, set $\gamma = 0$). Note that the maximum likelihood reconstruction shown is not unique, since adding any pattern from the null space of the likelihood matrix leads to a different reconstruction with the same maximum likelihood. Here one arbitrarily chosen MLE reconstruction is shown. **(D)** Optimal reconstruction, corrupted by patterns randomly sampled from the null space of the likelihood render matrix (see *Methods*). These have the same likelihood as the optimal reconstruction, but lower prior probability **(E)** Optimal reconstruction, corrupted by white noise in RGB space. **(F)** Grayscale version of the optimal reconstruction.

Optimal Allocation of Retinal Photoreceptors:

Within the Bayesian reconstruction framework, the goal of the visual front end can be characterized as minimizing the average error in reconstruction across the set of natural images. In this context, we can ask how to choose various elements of the initial encoding, subject to constraints, to minimize the expected reconstruction error under the natural image prior (Levin, Freeman, and Durand 2008; Manning and Brainard 2009). More formally, we seek the "design" parameters θ of a visual system:

$$\theta = argmin_\theta \quad E_{p(x)}\left(E_{p(m|x;\theta)}\, L(\hat{x}(m;\theta),x)\right),$$

where $\hat{x}(m;\theta) = argmax_x \quad p(m|x;\theta)p(x)$. Here x represents individual samples of natural images, m represents instances of cone excitation (i.e., sensory measurements), and $p(m|x;\theta)$ is our model of the initial encoding (i.e., likelihood function). The particular features under consideration of the modeled visual system are indicated explicitly by the parameter vector θ. The MAP image reconstruction is indicated by $\hat{x}(m;\theta)$, and $L(\cdot,\cdot)$ is a loss function that assesses reconstruction error. In practice, the expectations are approximated by taking the average over large samples of natural images and cone excitations.[3]

One intriguing design problem is the allocation of cone photoreceptor types: The maximum number of photoreceptors (cones) per unit area is bounded due to biological constraints. How should the visual system assign this limited resource across the three different types of cones? It has been observed in human subjects that there is a relatively sparse population of S cones, while large individual variability exists in the L/M cone ratio (Hofer et al. 2005). Previous research has used information-theoretical measures combined with approximations to address this question (Garrigan et al. 2010). Here, we empirically evaluated a loss function (i.e., we used root sum of squares distance in the RGB pixel space as well as the S-CIELAB space) on the reconstructed images, while systematically changing the allocation of retinal cone types (**Fig. 4**).

Interestingly, we found that large variations (nearly a 10-fold range) in the assignment of L and M cones have little impact on the average reconstruction error (**Fig. 4A**). Only when the proportion of L or M cones becomes very low is there a substantial increase in reconstruction error, as the modeled visual system approaches dichromacy. On the other hand, the average reconstruction error as a function of the proportion of S cones shows a clear optimum at a small S-cone proportion (~10%; **Fig. 4B**).

Our results are in agreement with a previous analysis in showing that the empirically observed allocation of retinal photoreceptor type is consistent with the principle of

---

[3] For simplicity in the development here, we did not include the parameter γ that we incorporated into our reconstruction algorithm in the equations above. It was included, however, in the actual computations that investigated the effect of the parameters of the initial encoding on reconstruction performance. Also note that the MAP estimate is not in general the one that minimizes the expected loss. We use the MAP estimate as a computationally tractable proxy for the loss-minimizing estimate.

optimal design (Garrigan et al. 2010; also see Levin et al. 2008; Manning and Brainard
2009; Tian et al. 2015; Jiang et al. 2017). The indifference to L/M ratio can be explained
by the large spatial and chromatic correlations present in natural images, together with
the high overlap in L- and M-cone spectral sensitivities. This leads to a high correlation
in the excitations of neighboring L and M cones in response to natural images, allowing
cones of one type to be substituted for cones of the other type with little effect on
reconstruction error (see the next section for additional analysis on this point).
Additional analysis (**Fig. 4-S1**) revealed that the sensitivity to S cone proportion is due
to a combination of two main factors: 1) chromatic aberrations, which blur the retinal
image at short wavelengths and reduce the value of dense spatial sampling at these
wavelengths; and 2) S cones mainly contribute to the estimation of pixel values in the B-
pixel plane, whereas L and M cone contribute to both the R- and G-pixel planes (see
Fig. 4-S1). This makes L and M cones more informative than S cones, given the
particular loss functions we employ to evaluate reconstruction error. To further validate
our conclusion, we have also replicated our analysis with a dataset of hyperspectral (as
opposed to RGB) images (Nascimento, Ferreira, and Foster 2002; Chakrabarti and
Zickler 2011), with a loss function applied directly to the whole spectrum, and have
obtained similar results (**Fig. 4-S2**, also see *Methods*).
269

270
271
Figure 4: Effect of the Allocation of Retinal Cone Types on Reconstruction. Average
image reconstruction error from a 1-deg foveal mosaic on a set of natural images from the
evaluation set, computed as root sum of squares (RSS) distance in the RGB pixel space (y-axis,
left panels) and the S-CIELAB space (y-axis, right panels), as a function of different allocations
of retinal photoreceptor (cone) types in the mosaic. **(A)** Average (over evaluation images)
reconstruction error as a function of %L cone (top x-axis), or L:M cone ratio (bottom x-axis).
Example mosaics with different %L values are shown below the plot. Error bars indicate +/- 1
SEM. **(B)** Average reconstruction error as a function of %S cone (top x-axis), or S:(L+M) cone
ratio (bottom x-axis). Example mosaics with different %S values are shown below the plot. Error
bars indicate +/- 1 SEM across sampled images. See **Fig. 4-S2** for a replication of the same
analysis with hyperspectral images.

To further study the role of statistical regularities in the optimal allocation of
photoreceptor type, we repeated the L-cone proportion analysis above, but on different
sets of synthetic image datasets for which the spatial and chromatic correlations in the
images were manipulated explicitly (see *Methods*). The dependence of the average
reconstruction error on the L-cone proportion decreases as the chromatic correlation in
the signal increases (**Fig. 5**). A decrease of spatial correlation has little impact on the
shape of the curves, but increases the overall magnitude of reconstruction error (**Fig. 5**;
to highlight the shape, the scale of the y-axis is different across rows and columns. See
Fig. 5-S1 for the same plot with matched y-axis scale). When both the chromatic and
spatial correlation are high, there is a large margin of L-cone proportion within which the
reconstruction error is close to the optimal (minimal) point (**Fig. 5**, shaded area). This
analysis highlights the importance of considering visual system design in context of the
statistical properties (prior distribution) of natural images, as it shows that the
conclusions drawn can vary with these properties (Barlow 1961; Derrico and
Buchsbaum 1991; Barlow and Földiàgk 1989; Atick, Li, and Redlich 1992; Lewis and Li
2006; Levin et al. 2008; Borghuis et al. 2008; Garrigan et al. 2010; Tkačik et al. 2010;
Atick 2011; Burge 2020). Natural images are thought to have both high spatial and high
chromatic correlation (Webster and Mollon 1997; Nascimento et al. 2002; Garrigan et al.
2010), making the results shown in **Fig. 5** consistent with those in **Fig. 4**.
302

303
304
Figure 5: Effect of Spatial and Chromatic Correlation on the Optimal Allocation of
Photoreceptors. Average image reconstruction error from a half-degree square foveal mosaic
on different sets of synthetic images, computed as root sum of squares (RSS) distance in the
RGB pixel space, as a function of %L cone (L:M cone ratio) of the mosaic (i.e., similar to **Fig.**
4A, left column). The shaded areas represent %L values that correspond to RSS values within a
$+0.1$ RSS margin of the optimal (minimum RSS) point. Within each panel, synthetic images
were sampled from a Gaussian distribution with specified spatial and chromatic correlation, as
indicated by example images on the top row and rightmost column, and reconstruction was
performed with the corresponding Gaussian prior (see *Methods*). The overall RSS is reduced
compared to **Fig. 4** due to the smaller image size used and the fact that the images were drawn
from a different prior, as well as because the prior used in reconstruction exactly describes the
images for this case. In addition, reconstruction error bars are negligible due to the large image
sample size used.

Visualization of Color Deficiency with Image Reconstruction:
In addition to quantification, the reconstruction framework also provides a method for
visualizing the effect of information loss in the initial visual encoding. We know that
extreme values of L:M cone ratio create essentially dichromatic retinal mosaics, and
from the analysis above we observed that these lead to high reconstruction error. To
understand the nature of this error, we can directly visualize the reconstructed images.
325
Fig. 6A shows reconstructions of a set of example images from different dichromatic
retinal mosaics. While the spatial structure of the original images is largely retained in
the reconstructions, each type of dichromacy creates a distinct pattern of color
confusions and shifts in the reconstructed color. Note that in the case where there is no
simulated cone noise (as in **Fig. 6**), the original image has a likelihood at least as high
as the reconstruction obtained via our method. Thus, the difference between the original
images and each of the corresponding dichromatic reconstructions is driven by the
image prior. On the other hand, the difference in the reconstructions across the three
types of dichromacy illustrates how the different dichromatic likelihood functions interact
with the prior.
336
One might speculate as to whether the reconstructions predict color appearance as
experienced by dichromats. To approach this, we compare the reconstructions with two
other methods that have been proposed to predict the color appearance for dichromats
(Brettel, Viénot, and Mollon 1997; Jiang, Farrell, and Wandell 2016). To determine an
image based on the excitations of only two classes of cones, any method will need to
rely on a set of regularizing assumptions to resolve the ambiguity introduced by the
dichromatic retinas. Brettel et al. (1997) started with the trichromatic cone excitations of
each image pixel, and projected these onto a biplanar surface, with each plane defined
by the neutral color axis and an anchoring stimulus identified through color appearance
judgments made across the two eyes of unilateral dichromats. The resulting trichromatic
excitations were then used to determine the rendered RGB values (**Fig. 6B**). Jiang et al.
(2016) also adopted a reconstruction approach, but one that reconstructed the incident
spectrum from the dichromatic cone excitations at each pixel. They then projected the
estimated spectra onto trichromatic cone excitations, and used these to render the RGB
values (**Fig. 6C**). In their method, a spectral smoothness constraint was introduced to
regularize the spectral estimates, which favors desaturated spectra. In this sense, their
prior is similar to ours: The sparse prior we used is centered on the average image,
which is desaturated, and also encourages achromatic content due to the high
correlations across color channels. One noticeable difference between our method and
the other two is that ours takes into account the spatial structure of the image.
357
358 Interestingly, although there are differences in detail between the images obtained, in
359 many cases the different methods produce visualizations that are quite similar. We find
360 the general agreement between the reconstruction-based methods and the one based
361 subject reports an encouraging sign that the reconstruction approach can be used to
362 predict aspects of appearance.

363
364
Figure 6: Visualization of Effect of Dichromacy. Reconstructions of a set of example images
in the evaluation set from different types of 1-degree foveal dichromatic retinal mosaics
(protanopia, deuteranopia, tritanopia) together with other previously proposed methods for
predicting color appearance for dichromats. **(A)** Our method; **(B)** Brettel, Viénot, and Mollon
(1997); **(C)** Jiang, Farrell, and Wandell (2016). Cone noise was not simulated for the images
shown in this figure, since the comparison methods operate directly on the input images. See
Methods for a brief description of the implantation of the two other methods.
372

Anomalous trichromacy is another form of color deficiency that is commonly found in
human observers. For example, in deuteranomaly, the spectral sensitivity of the M
cones is shifted towards that of the L cones (**Fig. 7B**). Since the three cone spectral
sensitivity functions are linearly independent of each other, in the absence of noise we
should be able to obtain a trichromatic reconstruction from the excitations of the
deuteranomalous mosaic. However, in the presence of noise, we expect that the high
degree of overlap between M and L spectral sensitivities will result in a lower signal-to-
noise ratio (SNR) in the difference between M- and L-cone excitations, compared to that
of a normal trichromatic observer, and thus to worse reconstructions. We performed
image reconstructions for a normal trichromatic (with a peak spectral sensitivity of M
cone at 530 nm) and a deuteranomalous (with a peak spectral sensitivity of M cone at
550 nm) 1-deg foveal mosaic at different overall light intensity levels (**Fig. 7**). Due to the
nature of Poisson noise, the higher the light intensity, the higher the SNR of the cone
excitations. At high light intensities, the reconstructions are similar for the normal and
deuteranomalous mosaics (first row). At lower intensities, however, the
deuteranomalous reconstruction lacks chromatic content still present in the normal
reconstruction (second and third row). The increase in noise also reduces the amount of
spatial detail in the reconstructed images, due to the denoising effect driven by the
image prior. Furthermore, a loss of chromatic content is also seen for the reconstruction
from the normal mosaic at the lowest light level (last row). This observation may be
connected to the fact that biological visual systems that operate at low light levels are
typically monochromatic, potentially to increase the SNR of spatial vision at the cost of
completely disregarding color (e.g., the monochromatic human rod system; see
Manning and Brainard 2009 for a related and more detailed treatment; also see Walls
1942; Rushton 1962; Van Hateren 1993; Land and Osorio 2003).
398

399
400
Figure 7: Comparison of Normal and Deuteranomalous Observers at Varying Light Intensities. Image reconstructions for a set of example images in the evaluation set from 1-degree, foveal **(A)** normal trichromatic and **(B)** deuteranomalous trichromatic mosaics at four different overall light intensity levels that lead to different Poisson signal-to-noise ratios in the cone excitations. The average excitations (photo-isomerizations) per cone per 50 ms integration time is chosen to be approximately 10^4 for *Outdoor Daylight*, 10^3 for *LCD Monitor*, 10^2 for *Dim Light*, and 10^1 for *Twilight* (Lewis and Li 2006; Stockman and Sharpe 2006). The prior weight parameter in these set of simulations was set based on a cross-validation procedure that minimizes RMSE ($\lambda = 0.05$). To highlight interaction between noise and the prior, we have also included a set of reconstructions with the prior weight set to a much lower level ($\lambda = 0.001$), see **Fig. 7-S1**.

Effect of Physiological Optics and Mosaic Spatial Sampling:

So far, our visualizations have focused on chromatic information loss due to a reduced number of cone types or a shift in cone spectral sensitivity. However, imperfection in the physiological optics, combined with the spatial sampling of retinal mosaic, also introduces significant loss of information. Furthermore, the interleaved nature of the mosaic means that color and pattern are entangled at the very initial stage of visual processing (Brainard 2019). To highlight these effects, we reconstructed natural images from 1-deg patches of mosaics at different retinal eccentricities across the visual field, with 1) changes in optical aberrations (Polans et al. 2015); 2) increases in size and decreases in density of the photoreceptors (Curcio et al. 1990); and 3) decreases in the density of the macular pigment (Nolan et al. 2008; Putnam and Bland 2014). The degradation in the quality of the reconstructed images can be clearly observed as we move from the fovea to the periphery (**Fig. 8**; See **Fig. 8-S1** for an enlarged view of the mosaic and optics). For some retinal locations, the elongated point-spread function (PSF) also introduces a salient directional blur (**Fig. 8E, F**). For a simple quantification of the average reconstruction error as a function of visual eccentricity, see **Fig. 8-S2**.

The consequences of irregular spatial sampling by the cone mosaic have been previously studied with the framework of signal processing (Snyder, Laughlin, and Stavenga 1977; Yellott 1983). Our results highlight that optimizing the initial visual encoding depends in rich ways on the interplay between the cone sampling and the optics. While less information (i.e., at more eccentric locations) does lead to overall lower quality reconstructions (**Fig. 8-S2**), exactly which aspects of the reconstructions are incorrect can vary in subtle ways. Concretely, in **Fig. 8**, we observe a trade-off across visual eccentricity between spatial and chromatic vision. In the image of the dragonfly, for example, the reconstructed colors are desaturated at intermediate eccentricities (e.g., **Fig. 8C, D**), compared with the fovea (**Fig. 8A**) and more eccentric locations (**Fig. 8E, F**). The desaturation is qualitatively consistent with the literature that indicates a decrease in chromatic sensitivity at peripheral visual eccentricities, at least for the red-green axis of color perception and for some stimulus spatial configurations (Virsu and Rovamo 1979; Mullen and Kingdom 1996; but see Hansen, Pracejus, and Gegenfurtner 2009). To further elucidate this richness, in an additional analysis, we systematically varied the size of the PSF for a fixed peripheral retinal mosaic. This revealed that (**Fig. 8-S3**): 1) A larger PSF does lead to better estimate of chromatic content, albeit eventually at the cost of spatial content. 2) In general, an appropriate amount of optical blur is required to achieve the best overall image reconstruction performance, presumably due to its prevention of aliasing. We will treat the issue of spatial aliasing further in the next section.

Lastly, to emphasize the importance of the natural image prior, we performed a set of maximum likelihood reconstructions with no explicit prior constraint, which resulted in images with less coherent spatial structure and lower fidelity color appearance (**Fig. 8-S4**). Thus, the prior here is critical for the proper demosaicing and interpolation of the information provided by the sparse cone sampling at these peripheral locations.

457
458
Figure 8: Image Reconstruction with Optics/Mosaic at Different Retinal Eccentricities.
Image reconstructions for a set of example images in the evaluation set from 1-degree patches
of mosaic at different retinal eccentricities. The coordinates at the top of each column indicate
the horizontal and vertical eccentricity of the patch used for that column. The image at the top
left of each column shows a contour plot of the point-spread function relative to an expanded
view of the cone mosaic used for that column, while the image at the top right of each column
shows the full 1-degree mosaic (see **Fig. 8-S1** for an enlarged view of the mosaic and optics).

Spatial Aliasing:

As we have alluded to above, the retinal mosaic and physiological optics can also interact in other important ways: Both in humans and other species, it has been noted that the optical cut-off of the eye is reasonably matched to the spacing of the photoreceptors (i.e., the mosaic Nyquist frequency), enabling good spatial resolution while minimizing spatial aliasing due to discrete sampling (Williams 1985; Snyder, Bossomaier, and Hughes 1986; Land and Nilsson 2012). In contrast to our work, these analyses did not take into account the fact that the cone mosaic interleaves multiple spectral classes of cones (but see Williams et al. 1991; Brainard 2015), and here we revisit classic experiments on spatial aliasing for a trichromatic mosaic using our reconstruction framework.

Experimentally, it has been demonstrated that with instruments that *bypass* the physiological optics and present high contrast grating stimuli directly on the retina, human subjects can detect spatial frequencies up to 200 cyc/deg (Williams 1985). For foveal viewing, subjects also report having a percept resembling a pattern of "two-dimensional noise" and/or "zebra stripes" when viewing those high spatial frequency stimuli (Williams 1985). For peripheral viewing, high frequency vertical gratings can be perceived as horizontal (and vice-versa; Coletta and Williams 1987). We explored these effects within our framework as follows: We reconstructed a set of vertical chromatic grating stimuli from the cone excitations of a foveal and a peripheral mosaic. To simulate the interferometric experimental conditions of Williams (1985), we used diffraction-limited optics with no longitudinal chromatic aberration (LCA), allowing high-frequency stimuli to reach the cone mosaic directly. For gratings that are above the typical optical cut-off frequency, we obtained reconstructions that 1) are quite distinct from a uniform field, which would allow them to be reliably detected in a discrimination protocol; and 2) lack the coherent vertical structure of the original stimulus (**Fig. 9**). Concretely, the reconstructions recapitulate the "zebra stripe" percept reported at approximately 120 cyc/deg in the fovea (**Fig. 9A**); as well as the orientation-reversal effect at an appropriate spatial frequency in the periphery (**Fig. 9B**). Both results corroborate pervious theoretical analysis and psychophysical measurements (Williams 1985; Coletta and Williams 1987), but now taking the trichromatic nature of the mosaic into account. On the other hand, with full optical aberrations, the reconstructed images became mostly uniform at these high spatial frequencies (**Fig. 9-S1**). Since our method accounts for trichromacy, we have also made the prediction that for achromatic grating stimuli viewed under similar diffraction-limited conditions, while the spatial aliasing pattern will be comparable, additional chromatic aliasing should be visible (**Fig. 9-S2**; also see Williams et al. 1991; Brainard 2015).

Figure 9: Reconstruction of Chromatic Grating Stimuli without Optical Aberrations. Image reconstruction of chromatic grating stimuli with increasing spatial frequency from **(A)** a 0.2-deg foveal mosaic and **(B)** a 1-deg peripheral mosaic at (18, 18) degree retinal eccentricity, using diffraction-limited optics without LCA. The leftmost images show an expanded view of the cone mosaic relative to a contour plot of a typical point-spread function at that eccentricity. Images were modulations of the red channel of the simulated monitor, to mimic the 633 nm laser used in the interferometric experiments. The exact frequency of the stimuli being used for each condition is as denoted in the figure. For a more extended comparison between reconstructions with and without optical aberrations, see **Fig. 9-S1 and Fig. 9-S2**.

Contrast Sensitivity Function:
Our framework can also be adapted to perform ideal observer analysis for
psychophysical discrimination (threshold) tasks, which have been used previously to
evaluate the information available in the initial encoding. Here we use the reconstructed
images as the basis for discrimination decisions. This is potentially important since even
the early post-receptoral visual representation (e.g., retinal ganglion cells), on which
downstream decisions must be based, is likely shaped by the regularities of our visual
environment (Atick et al. 1992; Borghuis et al. 2008; Karklin and Simoncelli 2011; Atick
2011). Our method provides a way to extend ideal observer analysis to incorporate
these statistical regularities.
528
Concretely, we predicted and compared the diffraction-limited spatial contrast sensitivity
function (CSF) for gratings with a half-degree spatial extent (see *Methods*). First, we
applied the classic signal-known-exactly ideal observer to the Poisson distributed
excitations of the simulated cone mosaic. We computed CSFs for both achromatic
(L+M) and chromatic (L-M) grating modulations, with matched cone contrast measured
as the vector length of the cone contrast vector. As expected, the ideal observer at the
cone excitations produces nearly identical CSFs for the contrast-matched L+M and L-M
modulations; also, as expected, these fall off with spatial frequency, primarily because
of optical blur (**Fig. 10A**).
538
Next, we reconstructed images from the cone excitations produced by the grating
stimuli. A template-matching observer based on the noise-free reconstructions was then
applied to the noisy reconstructions (see *Methods*). The image-reconstruction observer
shows significant interactions between spatial frequency and chromatic direction.
Sensitivity in the L+M direction is relatively constant with spatial frequency. Sensitivity in
the L-M direction starts out higher than L+M at low spatial frequencies, but drops
significantly and is lower than L+M at high spatial frequencies (**Fig. 10B**). We attribute
these effects to the role of the image prior in the reconstructions, which leads to
selective enhancement/attenuation of different image components. In support of this
idea, we also found that an observer based on maximum likelihood reconstruction
without the explicit prior term produced CSFs similar in shape to the Poisson ideal
observer (**Fig. 10-S1**).
551
It is intriguing that the CSFs from the reconstruction-based observer show substantially
higher sensitivity for L-M than for L+M modulations at low spatial frequencies (with
equated RMS cone contrast), but with a more rapid falloff such that the sensitivity for
L+M modulations is higher at high spatial frequencies. Both of these features are
characteristic of the CSFs of human vision (Mullen 1985; Anderson, Mullen, and Hess
1991; Chaparro et al. 1993; Sekiguchi, Williams, and Brainard 1993). A more
comprehensive exploration of this effect and its potential interaction with other decision
rule used in the calculation awaits future research.
560

561
562
563 **Figure 10: Contrast Sensitivity Functions.** Contrast sensitivity, defined as the inverse of
564 threshold contrast, for **(A)** a Poisson 2AFC ideal observer, and **(B)** an image reconstruction-
565 based observer (see *Methods*), as a function of the spatial frequency of stimulus in either the
566 L+M direction (black) and L-M cone contrast direction (red). Contrast was measured as the
567 vector length of the cone contrast vector, which is matched across two color directions.
568

Discussion:

We developed a Bayesian image reconstruction framework for characterizing the initial visual encoding, by combining an accurate image-computable forward model together with a sparse coding model of natural image statistics. Our method enables both quantification and visualization of information loss due to various factors in the initial encoding, and unifies the treatment of a diverse set of issues that have been studied in separate, albeit related, ways. In several cases, we were able to extend previous studies by eliminating simplifying assumptions (e.g., by the use of realistic, large cone mosaics that operate on high-dimensional, naturalistic image input). To summarize succinctly, we highlight here the following novel results and substantial extensions of previous findings: 1) When considering the allocation of different cone types on the human retina, we demonstrated the importance of the spatial and spectral correlation structure of the image prior; 2) As we examined reconstructions as a way to visualize information loss, we observed rich interactions in how the appearances of the reconstruction vary with mosaic sampling, physiological optics, and the SNR of the cone excitations; 3) We found that the reconstructions are consistent with empirical reports of retinal spatial aliasing obtained with interferometric stimuli, adding an explicit image prior component and extending consideration of the interleaved nature of the trichromatic retinal cone mosaic relative to the previous treatment of these phenomena; 4) We linked image reconstructions to spatio-chromatic contrast sensitivity functions by applying a computational observer for psychophysical discrimination to the reconstructions. Below, we provide an extended discussion of key findings, as well as of some interesting open questions and future directions.

First, we cast retinal mosaic design as a "likelihood design" problem. We found that the large natural variations of L- and M-cone proportion, and the relatively stable but small S-cone proportion, can both be explained as an optimal design that minimizes the expected image reconstruction loss. This is closely related to an alternative formalism, often termed "efficient coding", which seeks to maximize the amount of information transmission (Barlow 1961; Karklin and Simoncelli 2011; Wei and Stocker 2015; Sims 2018). In both cases, the optimization problem is subject to realistic biological constraints and incorporates natural scene statistics. Previous work (Garrigan et al. 2010) conducted a similar analysis with consideration of natural scene statistics, physiological optics, and cone spectral sensitivity, using an information maximization criterion. One advance enabled by our work is that we are able to fully simulate a 1-deg mosaic with naturalistic input, as opposed to the information-theoretical measures used by Garrigan et al., which became intractable as the size of the mosaic and the dimensionality of the input increased. In fact, Garrigan et al. (2010) approximated by estimating the exact mutual information for small mosaic size ($N = 1 \ldots 6$ cones) and then extrapolated to larger cone mosaics using a scaling law (Borghuis et al. 2008). The fact that the two theories corroborate each other well is reassuring and suggests that the results are robust to the details of the analysis.

Our approach could be applied to analyzing the retinal mosaic characteristics of
different animals. Adult zebrafish, for example, feature a highly regular mosaic with fixed
2:2:1:1 R:G:B:U cone ratios (Engström 1960). Since our analysis has highlighted the
importance of prior statistics in determining the optimal design, one might speculate
whether this regularity results from the particular visual world of zebrafish (i.e.,
underwater, low signal-to-noise ratio), which perhaps demands a more balanced ratio of
different cone types to achieve the maximum amount of information transmission.
Further study that characterizes in detail the natural scene statistics of the zebrafish's
environment might help us to better understand this question (Zimmermann et al. 2018;
Cai et al. 2020). It would also be interesting to incorporate into the formulation an
explicit specification of how the goal of vision might vary across species. One extension
to the current approach to incorporate this would be to specify an explicit loss function
for each species and find the reconstruction that minimizes the expected (over the
posterior of images) loss (Berger 1985), although implementing this approach would be
computationally challenging. Related is the task-specific accuracy maximization
analysis formulation (Burge and Geisler 2011; see Burge 2020 for a review).
629
Second, we applied our framework to cone excitations of retinal mosaics with varying
degrees of optical quality, photoreceptor size, density, and cone spectral sensitivity. The
reconstructed images reflect accurately the information loss in the initial encoding,
including spatial blur due to optical aberration and mosaic sampling, pixel noise due to
Poisson variability in the cone excitations, and reduction of chromatic contrast in
anomalous trichromacy. Although we have mainly focused on visualization of these
effects in our current paper, it would be possible to perform quantitative analyses. In
fact, our reconstruction algorithm could provide a natural "front-end" extension to many
image-based perceptual quality metrics, such as spatial CIELAB (Zhang and Wandell
1997; Lian 2020), structural similarity (Wang et al. 2004), low-level feature similarity
(FSIM; Zhang et al. 2011), or neural network-based approaches (Bosse et al. 2018).
Doing so would incorporate factors related to the initial visual encoding explicitly into the
resulting image quality metrics.
643
In addition, when SNR is high, we found that we are able to fully recover color
information even from an anomalous trichromatic mosaic. As SNR drops, this becomes
less feasible. Although our analysis does underestimate the amount of total noise in the
visual system (i.e., we only consider noise at cone excitations, but see Ala-Laurila et al.
2011 for a detailed treatment of noise in the retinal), this nonetheless suggests that a
downstream circuit that properly compensates for the shift in cone spectral sensitivity
can, in principle, maintain relatively normal color perception in the low noise regime
(Tregillus et al. 2021). This may potentially be related to some reports of less than
expected difference in color perception between anomalous trichromats and color
normal observers (Bosten 2019; Lindsey, Hutchinson, and Brown 2020).
654
Third, we speculate that image reconstruction could provide a reasonable proxy for
modeling percepts in various psychophysical experiments. We found that images

reconstructed from dichromatic mosaics resemble results generated by previously
proposed methods for visualizing dichromacy, including one that uses explicit
knowledge of dichromatic subjects' color appearance reports (Brettel et al. 1997). We
have also reproduced the "zebra stripes" and "orientation reversal" aliasing patterns
when reconstructing images from cone excitations to spatial frequencies above the
mosaic Nyquist limit, similar to what has been documented experimentally in human
subjects (Williams 1985; Coletta and Williams 1987). In a similar vein, previous work
has used a simpler image reconstruction method to model the color appearance of
small spots light stimulus presented to single cones using adaptive optics (Brainard,
Williams, and Hofer 2008). Our method could also be applied to such questions, and
also to a wider range of adaptive optics (AO) experiments (e.g., Schmidt et al. 2019;
Neitz et al. 2020), to help understand the extent to which image reconstruction can
capture perceptual behavior. More speculatively, it may be possible to use calculations
performed within the image reconstruction framework to synthesize stimuli that will
maximally discriminate between different hypothesis about how the excitations of sets of
cones are combined to form percepts, particularly with the emergence of technology
that enables precise experimental control over the stimulation of individual cones in
human subjects (Harmening et al. 2014; Sabesan et al. 2016; Schmidt et al. 2019).
675
Last, we showed that our method can be used in conjunction with analysis of
psychophysical discrimination performance, bringing to this analysis the role of
statistical regularities of natural images. In our initial exploration, we found that the
image-reconstruction based observer exhibits significant interaction between spatial
frequency and chromatic direction in its contrast sensitivity function, a behavior distinct
from its Poisson ideal observer counterpart, and is more similar to the human observer.
Future computations will be needed to understand in more detail whether the
reconstruction approach can account for other features of human psychophysical
discrimination performance that are not readily explained by ideal-observer calculations
applied to the cone excitations.
686
Our current model only considers the representation up to and including the excitations
of the cone mosaic. Post-excitation factors (e.g., retinal ganglion cells), especially in the
peripheral visual field, are likely to lead to additional information loss. In this regard, we
are eager to incorporate realistic models of retinal ganglion cells into the ISETBio
pipeline. Nevertheless, the value of the analysis we have presented is to elucidate
exactly what phenomena can or cannot be attributed to factors up to the cone
excitations, thus helping to dissect the role of different stages of processing in
determining behavior. For example, we found there is desaturation of chromatic content
in reconstructed images in the periphery, with the details depending on interactions
between the physiological optics, cone mosaic sampling, macular pigment density, and
the model of natural image statistics. This is in contrast to more traditional explanations
of the decrease in peripheral chromatic sensitivity, which often consider it in the context
of models of how different cone types are wired to retinal ganglion cells (e.g., Lennie,
Haake, and Williams 1991; Mullen and Kingdom 1996; Hansen et al. 2009; Field et al.

2010; Wool et al. 2018). Whether the early vision factors are sufficient to account for the
full variation in chromatic sensitivity awaits a more detailed future study, but the fact that
early vision factors can play a role through their effect on the available chromatic
information is a novel insight that should be incorporated into thinking about the role of
post-excitation mechanisms.
706
More generally, we can consider the locus of the signals analyzed in the context of the
encoding-decoding dichotomy of sensory perception (Stocker and Simoncelli 2006;
Rust and Stocker 2010). Here we reconstruct images from cone excitations, thus post-
excitation processing may be viewed as part of the brain's implementation of the
reconstruction algorithm. When we apply such an algorithm to, for example, the output
of retinal ganglion cells, we shift the division. Our view is that analyses at multiple
stages are of interest, and eventual comparisons between them are likely to shed light
on the role of each stage.
715
Our current model also does not take into account fixational eye movements, which
displace the retinal image at a time scale shorter than the integration period we have
used here (Martinez-Conde, Macknik, and Hubel 2004; Burak et al. 2010). It has been
shown that these small eye movements can increase psychophysically-measured visual
acuity relative to that obtained with retinally-stabilized stimuli (Rucci et al. 2007; Ratnam
et al. 2017). An intuition behind this is that fixational eye movements can increase the
effective cone sampling density, if the visual system can sensibly combine information
obtained across multiple fixation locations. This intuition is supported by computational
analyses that integrate information across fixations while simultaneously estimating the
eye movement path (Burak et al. 2010; Anderson et al. 2020). In their analysis, Burak et
al. (2010) showed the effectiveness of their algorithm depended both on the integration
time of the sensory units whose excitations were processed, and also on the receptive
field properties of those units. In addition, consideration of the effects of fixational eye
movement might also benefit from an accurate model of the temporal integration that
occurs within each cone, as a consequence of the temporal dynamics of the
phototransduction cascade (Angueyra and Rieke 2013). ISETBio in its current form
implements a model of the phototransduction cascade as well as of fixational eye
movements (see Cottaris et al. 2020). Future work should be able to extend our current
results through the study of dynamic reconstruction algorithms within ISETBio.
735
Since our framework is centered on image reconstruction, one may naturally wonder
whether we should have applied the more "modern" technique of convolutional neural
networks (CNNs), which have become the standard for image processing-related tasks
(Krizhevsky, Sutskever, and Hinton 2012). For our scientific purposes, the Bayesian
framework offers an important advantage in its *modularity*, namely, the likelihood and
prior are two separate components that can be built independently. This allows us to
easily isolate and manipulate one of them (e.g., likelihood) while holding the other
constant (e.g., prior), something we have done throughout this paper. In addition,
building the likelihood function (i.e., render matrix R, see *Methods*) is a forward process

that is computationally very efficient. Performing a similar analysis with the neural
network approach (or supervised learning in general) would require re-training of the
network with a newly generated dataset (i.e., cone excitations paired with the
corresponding images) for *every* condition in our analysis.
749
However, the ability of neural networks to represent more complex natural image priors
(Ulyanov, Vedaldi, and Lempitsky 2018; Kadkhodaie and Simoncelli 2021) is of great
interest. Currently, we have chosen a rather simple, parametric description of natural
image statistics, which leads to a numerical MAP solution. Previous work has proposed
methods that alternate, within each iteration, between regularized reconstruction and
denoising, which effectively allow for transfer of the prior implicit in an image denoiser
(e.g., a deep neural network denoiser) to be applied to any other domain with a known
likelihood model (Venkatakrishnan, Bouman, and Wohlberg 2013; Romano, Elad, and
Milanfar 2017). More recently, Kadkhodaie and Simoncelli (2021) developed a related
but more explicit and direct technique to extract the image prior (a close approximation
to the gradient of the log-prior density, to be precise) from a denoising deep neural
network, which could be applied to our image reconstruction problem. We think this
represents a promising direction, and in the future plan to incorporate more
sophisticated priors, to evaluate the robustness of our conclusions to variations and
improvements in the image prior.
765
766 To conclude, we believe our method is widely applicable to many experiments (e.g.,
767 adaptive optics psychophysics) designed for studying the initial visual encoding, for
768 modeling the effect of changes of various components in the encoding process (e.g., in
769 clinical conditions), and for practical applications (e.g., perceptual quality metric) in
770 which the initial visual encoding plays an important role.

Materials and Methods:

771
772
The problem of reconstructing images from neural signals can be considered in the
general framework of estimating a signal x, given an (often lower-dimensional and
noisy) measurement m. We take a Bayesian approach. Specifically, we model the
generative process of measurement as the conditional probability $p(m|x)$ and the prior
distribution of the signal as the probability density $p(x)$. We then take the estimate of the
signal, $\hat{x}$, as the maximum a posteriori estimate $argmax\ p(m|\hat{x})p(\hat{x})$. We next explain
in detail how each part of the Bayesian estimate is constructed.
780
Likelihood Function:
In our particular problem, x is a column vector containing the (vectorized) RGB pixel
values of an input image of dimension $N*N*3$, where N is the linear pixel size of the
display. Below we will generalize from RGB images to hyperspectral images. The
column vector m contains the excitations of the M cone photoreceptors. The
relationship between x and m is modeled by the ISETBio software (Cottaris et al. 2019,
2020; **Fig. 1**). ISETBio simulates in detail the process of displaying an image on the
monitor, the wavelength-dependent optical blur of the human eye and spectral
transmission through the lens and the macular pigment, as well as the interleaved
sampling of the retinal image by the L, M and S cone mosaic. For the majority of
simulations presented in our paper, we simulate a 1-deg foveal retina mosaic, which
contains approximately 11,000 cone photoreceptors. A stochastic procedure was used
to generate approximately hexagonal mosaics with eccentricity-varying cone density
matched to that of the human retina (Curcio et al. 1990). See Cottaris et al. (2019) for a
detailed description of the algorithm. We use a wavelength-dependent point spread
function empirically measured in human subjects (Marimont and Wandell 1994; Cottaris
et al. 2019), with a pupil size of 3-mm. We took the cone integration time to be 50 ms.
The input images of size $128*128*3$ were displayed on a simulated typical CRT
monitor (simulated with a 12 bit-depth in each of the RGB channels to avoid
quantization artifacts).
801
Once the RGB pixel values in the original image are linearized, all the processes
involved in the relation between x and m, including image formation by the optics of the
eye and the relation between retinal irradiance and cone excitations, are well described
as linear operations. Furthermore, the instance-to-instance variability in cone excitations
is described by a Poisson process acting independently in each cone. Thus $p(m|x)$ is
the product of Poisson probability mass functions, one for each cone, with the Poisson
mean parameter λ_i for each cone determined by a linear transformation of the input
image x. We describe the linear transformation between x and the vector of Poisson
mean parameters λ by a matrix R, and thus obtain:

811
$$p(m|x) = \prod_{i=1}^{M} Poisson(m_i \mid \lambda_i = [Rx]_i).$$

812
813   We refer to the matrix R as the *render matrix*. This matrix together with the Poisson
814   variability encapsulates the properties of the initial visual encoding through to the level

815 of the cone excitations. In cases where we parameterize properties of the initial visual
816 encoding (parameters denoted by θ in the text above), the render matrix is a function of
817 these parameters.
818
Although ISETBio can compute the relation between the linearized RGB image values
at each pixel and the mean excitation of each cone, it does so in a general way that
does not exploit the linearity of the relation. To speed the computations, we use
ISETBio to precompute R. Each column of R is a vector of mean cone excitations r_j to a
basis image x_j with one entry set to one and the remaining entry set to zero. To
determine R, we use ISETBio to compute explicitly each of its columns r_j. We verified
that calculating mean cone excitations from an image via Rx yields the same result as
applying the ISETBio pipeline directly to the image.
827
828 See *Code and Data Availability* for parameters used in the simulation including display
829 specifications (i.e., RGB channel spectra, display gamma function) and cone mosaic
830 setup (i.e., cone spectral sensitivities, lens pigment and macular pigment density and
831 absorption spectra), as well as some of the pre-computed render matrices.
832
Null Space of Render Matrix:
To understand the information lost between an original RGB image and the mean cone
excitations, we can take advantage of the linearity property of the render matrix.
Variations in the image space that are within the null space of the (low-rank) render
matrix R will have no effect on the likelihood. That is, the cone excitation pattern
provides no information to disambiguate between image variants that differ only by
vectors within the null space of R. To obtain the null space of R, we used MATLAB
function *null*, which computes the singular value decomposition of R. The set of right
singular vectors whose associated singular values are 0 form a basis for the null space.
842
843 As an illustration, we generated random samples of images from the null space by
844 taking linear combinations of its orthonormal basis vectors, where the weights are
845 sampled independently from a Gaussian distribution with a mean of 0 and a standard
846 deviation of 0.3. As shown in **Fig. 3D**, altering an image by adding to it samples from the
847 null space has no effect on the likelihood.
848
Prior Distribution:
We also need to specify a prior distribution $p(x)$. The problem of developing statistical
models of natural images has been studied extensively using numerous approaches,
and remains challenging (Simoncelli 2005). The high-dimensionality and complex
structure of natural images makes it difficult to determine a high-dimensional joint
distribution that properly captures the various forms of correlation and higher-order
dependencies of natural images. Here, we have implemented two relatively simple
forms of $p(x)$.
857

We first introduce a simple Gaussian prior $p(x)$ to set up the basic concepts and
notations for image prior based on basis vectors. In particular, for the Gaussian prior,
we assume $p(x) = \mathcal{N}(x|\mu, \Sigma)$. For convenience, we zero-centered our images when
building priors, making $\mu = 0$. The actual mean value of each pixel is added back to
each image when computing the likelihood and at the end of the reconstruction
procedure. The covariance matrix Σ can be estimated empirically, from a large dataset
of natural images. Note that we can write the covariance matrix as its eigen-
decomposition: $\Sigma = Q\Lambda Q^{-1}$. Defining $\beta = \Lambda^{-1/2}Q^{-1}x$, we have:

$$p(\beta) = \mathcal{N}(\beta \mid 0, I).$$

This derivation provides a convenient way of expressing our image prior: We can
project images onto an appropriate set of basis vectors, and impose a prior distribution
on the projected coefficients. In the case above, if we choose the basis vectors as the
column vectors of $\Lambda^{-1/2}Q^{-1}$, we obtain an image prior by assuming that the entries of β
are each independently distributed as a univariant standard Gaussian (Simoncelli
2005). Such a Gaussian prior can describe the first and second order statistics of
natural images, but fails to capture important higher-order structure (Portilla et al. 2003).

Our second model of $p(x)$ emerges from the basis set formulation. Rather than
choosing the basis vectors from the eigen-decomposition as above and using a
Gaussian distribution over the weights β, we instead choose an over-complete set of
basis vectors using independent components analysis, and model the distribution of the
entries of weight vector β using the long-tailed distribution Laplace distribution. This
leads to a sparse coding model of natural images (Olshausen and Field 1996;
Simoncelli and Olshausen 2001). More specifically, we learned a set of K ($K \geq 3N^2$)
basis vectors that lead to a sparse representation of our image dataset, through the
reconstruction independent component analysis (RICA) algorithm (Le et al. 2011)
applied to whitened images, and took these as the columns of the basis matrix E. Our
image prior in this case can be written as $p(\beta)$, with $\beta = E^+x$. Here E^+ represents the
pseudoinverse of matrix E, and

$$p(\beta) = \prod_{k=1}^{K} \frac{1}{2b} \, exp(-|\beta_k|/b).$$

Note that we further scaled each column of E to equalize the variance across β_k's.

Both methods outlined above can be applied directly to small image patches. They are
computationally intractable for larger images, however, since the calculation of basis
vectors will involve either an eigen-decomposition of a large covariance matrix or
independent component analysis of a set of high-dimensional image vectors. To
address this limitation, we iteratively apply the prior distributions we have constructed
above to overlapping small patches of the same size within a large image (Guleryuz
2006).

To illustrate the idea, consider the following example: Assume we have constructed a
prior distribution $p(y)$, for small image patches y of size $N_{patch} * N_{patch}$. To model a

larger image x of size $pN_{patch} * pN_{patch}$, we could consider viewing x as composed of
$p * p$ independent patches of non-overlapping y's . Under this assumption, the prior on x
could be expressed as the product:

$$p(x) \propto \prod_{j=1}^{p*p} p(y_j),$$

where y_j's describe individual patches of size $N_{patch} * N_{patch}$ within x. The
independence assumption is problematic, however, since y_j's are far from
independently sampled natural images: they need to be combined into a single coherent
large image. Using this approach to approximate a prior would create block artifacts at
the patch boundaries.

The basic idea above, however, can be extended heuristically to solve the block artifact
problem by allowing y_j's to overlap with each other. The degree of overlap can be
viewed as an additional parameter of the prior, which we refer to here as the stride. This
effectively implements a convolutional form of the sparse coding prior (Gu et al. 2015).
Again, for example, consider a large image x of size $pN_{patch} * pN_{patch}$. A stride of 1 will
tile through all $(pN_{patch} - N_{patch} + 1) * (pN_{patch} - N_{patch} + 1)$ possible patches of size
$N_{patch} * N_{patch}$ within x, yielding a prior distribution of the form:

$$p(x) \propto \prod_{j=1}^{(pN_{patch}-N_{patch}+1)*(pN_{patch}-N_{patch}+1)} p(y_j).$$

Although this form of prior is still an approximation, we have found it to work well in
practice, and using it does not lead to visible block artifacts as long as the stride
parameter is sufficiently smaller than N_{patch}.

Maximum a Posteriori Estimation:
To reconstruct the image $\hat{x}$ given a pattern of cone excitation m, we find the maximum a
posteriori estimate: $\hat{x} = argmax \ p(m|\hat{x})p(\hat{x})$. In practice, this optimization is usually
expressed in terms of its logarithmic counterpart: $\hat{x} = argmax \ [log \ p(m|\hat{x}) + log \ p(\hat{x})]$.

For the Poisson likelihood and sparse coding prior, the equation above becomes:

$$\hat{x} = argmax \ \left[\sum_{i=1}^{M}\left(-\lambda_i + m_i * log(\lambda_i)\right) + \gamma * \sum_{j=1}^{J}\sum_{k=1}^{K}\left|\beta_{jk}\right| + c\right],$$

where $\lambda = R\hat{x}$, $\beta_j = E^+ y_j$, y_j's are individual patches of size $N_{patch} * N_{patch}$ within x.
Each β_j is of length K and there are a total of J (overlapping) patches. Lastly, c is a
constant that does not depend on $\hat{x}$.

In principle, the value of γ can be analytically derived based on the parametric form of
the prior. However, due to the approximate nature of our prior, introduced especially by
the aggregation over patches, we left γ as a free parameter. Treating γ as a free
parameter also provides some level of robustness against misspecification of the prior
more generally. For most of the reconstruction results presented in this paper, the value
of γ was determined by maximizing reconstruction performance with a cross-validation
procedure (see **Fig. 2**). We also found that the optimal γ values were similar across the

two loss functions we considered. Note that the additional flexibility provided by this γ
parameter also provides us with a parametric way to manipulate and isolate the relative
contribution of the log-likelihood and log-prior terms to the reconstruction (e.g., **Fig. 2**;
also compare **Fig. 7** and **Fig. 7S-1**).

The optimization problem required to obtain $\hat{x}$ can be solved efficiently using the
MATLAB function *fmincon* by providing the analytical gradient to the minimization
function:

$$\frac{\partial \log p(m|x)}{\partial x} = \left(-1 + m \circ \frac{1}{\lambda}\right)^T * R,$$

$$\frac{\partial \log p(y)}{\partial y} = sign(\beta)^T * E^+.$$

956 where $\lambda = Rx, \beta = E^+ y$, $\circ$ denotes element-wise product between two vectors, $\frac{1}{\lambda}$ is the
957 element-wise inverse of vector λ, and

$$sign(\beta_i) = \begin{cases} -1, & \beta_i < 0 \\ 1, & \beta_i > 0 \end{cases}.$$

RGB Image Dataset:
We used the ImageNet ILSVRC (Russakovsky et al. 2015) as our dataset for natural
RGB images. Fifty randomly sampled images were reserved as the evaluation set, and
the rest of the images were used for learning the prior and for cross-validation. For the
sparse prior, we constructed a basis set size of $K = 768$, on image patches of size $16 *$
16 sampled from the training set, and used a stride of 4 when tiling larger images. We
randomly sampled 20 patches from each one of the $5,000$ images in the training set for
learning the prior (ICA analysis), and 500 images for the cross-validation procedure to
determine the γ parameter.

In our work, we simulate display of the RGB images on idealized monitor to generate
spectral radiance as a linear combination of the monitor's RGB channel spectra. Thus, a
prior over the linear RGB pixels values induces a full spatial-spectral prior. To make
sure the constraints introduced by RGB images together with the monitor do not
influence our results, we also conducted a control analysis using hyperspectral images
directly, as described in the following section.

Hyperspectral Images:
As a control analysis, we developed priors and reconstructed images directly on small
patches of hyperspectral images. The development is essentially the same as above,
with the generalization being to increase the number of channels in the images from 3
to N. In addition, since our algorithm treats images as high-dimensional vectors, it can
be directly applied to reconstruct hyperspectral images. Here, we used images from
Nascimento et al. (2002) and Chakrabarti and Zickler (2011). The dataset of
Nascimento et al. (2002) was pre-processed following the instructions provided by the
authors, and the images of Chakrabarti and Zickler (2011) were converted to spectral
radiance using the hyperspectral camera calibration data provided in that work. We

further resampled the combined image dataset with a patch size of $18 * 18$ and 15
uniformly spaced wavelengths between 420 nm and 700 nm for a dataset of ~ 5000
patches. We retained 300 of them as the evaluation set, and the rest for prior learning
and cross-validation. The remaining of the analysis (i.e., prior and reconstruction
algorithm) followed the same procedures as those used for the RGB images, using
number of basis functions $K = 4860$ and applied directly to each small image without
the patchwise procedure.
994
995   See *Code and Data Availability* for the curated RGB and hyperspectral image dataset,
996   as well learned basis functions for each sparse prior.
997
Gaussian Prior for Synthetic Images:
We also reconstructed multivariate Gaussian distributed synthetic images with known
chromatic and spatial correlations that we can explicitly manipulate (**Fig. 5**). To
construct these signals $x \sim \mathcal{N}(\mu, \Sigma)$, where x is RGB image of size $N * N * 3$ ($N = 36$ in
our current analysis), we set $\mu = 0.5$, and used a separable Σ along its two spatial
dimensions and one chromatic dimension. That is:
1004
$$\Sigma = \Sigma_c \otimes \Sigma_s \otimes \Sigma_s,$$
1005
1006   where Σ_c is the chromatic covariance matrix of size $(3 * 3)$
1007
$$\Sigma_c(i, j) = \sigma_c^2 * \rho_c^{|i-j|},$$
1008
1009   and Σ_s is the spatial covariance matrix of size $(N * N)$
1010
$$\Sigma_s(i, j) = \sigma_s^2 * \rho_s^{|i-j|}.$$
1011
1012   In the covariance matrix constructions, i, j index into entries of Σ_c and Σ_s at i-th row and
1013 j-th column. Here $\otimes$ represents the Kronecker product, thus producing the signal
1014   covariance matrix Σ of size $(3N^2 * 3N^2)$ (Brainard et al. 2008; Manning and Brainard
1015   2009).
1016
1017   The parameters σ_c^2 and σ_s^2 determine the overall variance of the signal, which are fixed
1018   across all simulations, whereas by changing the value of ρ_c and ρ_s, we manipulate the
1019   degree of spatial and chromatic correlation presented in the synthetic images (**Fig. 5**).
1020
1021   We introduce an additional simplification for the case of reconstructions with respect to
1022   the synthetic Gaussian prior: We approximated the Poisson likelihood function with a
1023   Gaussian distribution with fixed variance. Thus, the reconstruction problem can be
1024   written as:
1025
$$p(\beta) = \mathcal{N}(\beta \mid 0, \, I),$$
1026
$$p(m|\beta) = \mathcal{N}\left(m; \, RQ\Lambda^{1/2}\beta, \, \sigma^2 I\right).$$
1027
1028   Where R is the render matrix, and $\Sigma = Q\Lambda Q^{-1}$.
1029

1030 The reconstruction problem with Gaussian prior and Gaussian noise matches the ridge
1031 regression formulation, and can be solved analytically by the regularized normal
1032 equations, applied directly to each small image without the patchwise procedure.
1033 Denote the design matrix $D = RQ\Lambda^{1/2}$:

$$\hat{\beta} = (D^T D + \gamma I)^{-1} D^T m,$$
$$\hat{x} = Q\Lambda^{1/2}\hat{\beta}.$$

Note that the γ parameter here is also determined through a cross-validation routine.
We adopted this simplification (using Gaussian noise) for the simulation results in **Fig.
5**, in order to make it computationally feasible to evaluate the average reconstruction
error across a large number of synthetic image datasets.

Variations in Retinal Cone Mosaic:
To simulate a dichromatic observer, we constructed retinal mosaics with only two
classes of cones but with similar spatial configuration. To simulate the deuteranomalous
observer, we shifted the M cone spectral sensitivity function, setting its peak at 550 nm
instead of the typical 530 nm. In both cases, the likelihood function (i.e., render matrix
R) was computed using the procedure described above and the same Bayesian
algorithm was applied to obtain the reconstructed images.

In **Fig. 6** we also present the results of two comparison methods for visualizing
dichromacy, those of Brettel et al. (1997) and Jiang et al. (2016), both are implemented
as part of ISETBio routine. To determine the corresponding dichromatic images, we first
computed the LMS trichromatic stimulus coordinates of the linear RGB value of each
pixel of the input image, based on the parameters of the simulated CRT display. LMS
coordinates were computed with respect to the Stockman-Sharpe 2-deg cone
fundamentals (Stockman and Sharpe 2000). The ISETBio function *lms2lmsDichromat*
was then used to transform these LMS coordinates according to the two methods (see a
brief description in the main text). Lastly, the transformed LMS coordinates were
converted back to linear RGB values, and gamma corrected before rendering.

To simulate retinal mosaics at different eccentricities, we constructed retinal mosaics
with the appropriate photoreceptor size, density (Curcio et al. 1990), and physiological
optics (Polans et al. 2015), and computed their corresponding render matrices. The
same Bayesian algorithm was applied to obtain the reconstructed images.

To simulate the interferometric experimental conditions of Williams (1985), we used
diffraction-limited optics without longitudinal chromatic aberration (LCA) for the
computation of the cone excitations, but used the likelihood function with normal optics
for the reconstruction. This models subjects whose perceptual systems are matched to
their normal optics and assumes there is no substantial adaptation within the short time
span of the experiment.

Contrast Sensitivity Function:

We compared the spatial Contrast Sensitivity Function (CSF) between a standard,
Poisson 2AFC ideal observer, and an image reconstruction-based observer.

1076

1077 We simulated stimulus modulations in two chromatic contrast directions, L+M and L-M.
1078 Contrast was measured as the vector length in the L and M cone contrast plane at 5
1079 spatial frequencies, $[2, 4, 8, 16, 32]$ cycles per degree. For each chromatic direction and
1080 spatial frequency combination, the sensitivity is defined as the inverse of threshold
1081 contrast.

1082

We used the QUEST+ procedure (Watson 2017) as implemented in MATLAB by
Brainard (mQUESTPlus; https://github.com/BrainardLab/mQUESTPlus) for estimating
the simulated threshold efficiently as follows: We initialized the procedure with the
contrast near the middle of a pre-defined possible stimulus range. For each contrast, we
first generated a null template T_{null}, which is the noise-free, average excitations of a 0.5
deg foveal mosaic with N_{cones} cones to a uniform background stimulus; and a target
template T_{targ}, which is the noise-free, average cone excitations to a grating stimulus at
that contrast level. We then simulated 128 two alternative forced choice (TAFC) trials at
this contrast. For each trial, two Poisson-noise corrupted observed sets of cone
excitations r_{null} and r_{targ}, are generated based on T_{null} and T_{targ}, respectively. We
determine the accuracy of for TAFC trials with the target in the first interval. Based on
the observer responses, the QUEST+ procedure chooses the next test contrast
according to an information-maximization criterion (Watson 2017). The process is
repeated 15 times, for a total of $15 \times 128 = 1920$ trials.

1097

1098 For the Poisson TAFC observer, we directly compute the likelihood ratio for the two
1099 possible orderings of the null and target stimulus:

1100
$$\Lambda = \frac{Poisson(r_{\text{targ}}|T_{\text{targ}}) \, Poisson(r_{\text{null}}|T_{\text{null}})}{Poisson(r_{\text{targ}}|T_{\text{null}}) \, Poisson(r_{\text{null}}|T_{\text{targ}})}.$$

1101

1102 Taking the logarithm of the equation above, the decision rule simplifies to the following:
1103
$$d = \sum_{i=1}^{N_{\text{cones}}} \{(r_{\text{targ}} \circ \log T_{\text{targ}} + r_{\text{null}} \circ \log T_{\text{null}}) - (r_{\text{null}} \circ \log T_{\text{targ}} + r_{\text{targ}} \circ \log T_{\text{null}})\}_{\text{i}}$$

1104

1105 where $\circ$ denotes element-wise product between two vectors. The simulated observer
1106 correctly chooses target in first interval when $d > 0$, and incorrectly test in second when
1107 $d < 0$. Because of symmetry, we only need to simulated one of the two TAFC orders.

1108

1109 For the image reconstruction-based observer, given the cone responses, it first applies
1110 the reconstruction algorithm to obtain the image template $\hat{T}_{\text{null}}$ and $\hat{T}_{\text{targ}}$ from T_{null} and
1111 T_{targ}, and also noisy image instances $\hat{r}_{\text{null}}$ and $\hat{r}_{\text{targ}}$ by applying the same algorithm to
1112 r_{null} and r_{targ}. We then perform a template-matching decision rule as follows:

1113
$$d = \sqrt{||\hat{r}_{\text{targ}} - \hat{T}_{\text{targ}}||_2^2 + ||\hat{r}_{\text{null}} - \hat{T}_{\text{null}}||_2^2} - \sqrt{||\hat{r}_{\text{null}} - \hat{T}_{\text{targ}}||_2^2 + ||\hat{r}_{\text{targ}} - \hat{T}_{\text{null}}||_2^2}$$

1114

1115   where $|| \cdot ||_2$ represents the L_2 norm of a vector. The template observer correctly
1116   chooses target in first interval when $d < 0$, and incorrectly target in second interval
1117   when $d > 0$. We choose the template matching procedure for computational
1118   convenience. Note that because the variability in the reconstructed images is not
1119   independent across pixels, this procedure is not ideal.
1120
1121   *Code and Data Availability:*
1122   The MATLAB code used for this paper is available at:
1123   https://github.com/isetbio/ISETImagePipeline
1124
1125   In addition, the curated RGB and hyperspectral image datasets, parameters used in the
1126   simulation including display and cone mosaic setup, as well as the intermediate results
1127   such as the learned sparse priors, likelihood functions (i.e., render matrices), are
1128   available through: https://tinyurl.com/26r92c8y
1129

References:

Ala-Laurila, Petri, Martin Greschner, E. J. Chichilnisky, and Fred Rieke. 2011. "Cone Photoreceptor Contributions to Noise and Correlations in the Retinal Output." *Nature Neuroscience* 14(10):1309–16. doi: 10.1038/nn.2927.

Anderson, Alexander G., Kavitha Ratnam, Austin Roorda, and Bruno A. Olshausen. 2020. "High-Acuity Vision from Retinal Image Motion." *Journal of Vision* 20(7):34. doi: 10.1167/jov.20.7.34.

Anderson, S. J., K. T. Mullen, and R. F. Hess. 1991. "Human Peripheral Spatial Resolution for Achromatic and Chromatic Stimuli: Limits Imposed by Optical and Retinal Factors." *The Journal of Physiology* 442:47–64. doi: 10.1113/jphysiol.1991.sp018781.

Angueyra, Juan M., and Fred Rieke. 2013. "Origin and Effect of Phototransduction Noise in Primate Cone Photoreceptors." *Nature Neuroscience* 16(11):1692–1700. doi: 10.1038/nn.3534.

Atick, Joseph J. 2011. "Could Information Theory Provide an Ecological Theory of Sensory Processing?" *Network: Computation in Neural Systems* 22(1–4):4–44. doi: 10.3109/0954898X.2011.638888.

Atick, Joseph J., Zhaoping Li, and A. Norman Redlich. 1992. "Understanding Retinal Color Coding from First Principles." *Neural Computation* 4(4):559–72. doi: 10.1162/neco.1992.4.4.559.

Attneave, Fred. 1954. "Some Informational Aspects of Visual Perception." *Psychological Review* 61(3):183.

Banks, Martin S., Wilson S. Geisler, and Patrick J. Bennett. 1987. "The Physical Limits of Grating Visibility." *Vision Research* 27(11):1915–24.

Barlow, Horace B. 1961. "Possible Principles Underlying the Transformation of Sensory Messages." *Sensory Communication* 1(01).

Barlow, Horace, and Peter Földiàgk. 1989. "Adaptation and Decorrelation in the Cortex."

Berger, James O. 1985. *Statistical Decision Theory and Bayesian Analysis*. Springer Science & Business Media.

Borghuis, Bart G., Charles P. Ratliff, Robert G. Smith, Peter Sterling, and Vijay Balasubramanian. 2008. "Design of a Neuronal Array." *Journal of Neuroscience* 28(12):3178–89. doi: 10.1523/JNEUROSCI.5259-07.2008.

Bosse, S., D. Maniry, K. Müller, T. Wiegand, and W. Samek. 2018. "Deep Neural Networks for
No-Reference and Full-Reference Image Quality Assessment." *IEEE Transactions on*
Image Processing 27(1):206–19. doi: 10.1109/TIP.2017.2760518.

Bosten, Jenny. 2019. "The Known Unknowns of Anomalous Trichromacy." *Current Opinion in*
Behavioral Sciences 30:228–37.

Bracewell, Ronald Newbold. 1986. *The Fourier Transform and Its Applications*. Vol. 31999.
McGraw-Hill New York.

Brainard, David H. 2015. "Color and the Cone Mosaic." *Annual Review of Vision Science* 1:519–
46. doi: 10.1146/annurev-vision-082114-035341.

Brainard, David H. 2019. "Color, Pattern, and the Retinal Cone Mosaic." *Current Opinion in*
Behavioral Sciences 30:41–47. doi: 10.1016/j.cobeha.2019.05.005.

Brainard, David H., David R. Williams, and Heidi Hofer. 2008. "Trichromatic Reconstruction from
the Interleaved Cone Mosaic: Bayesian Model and the Color Appearance of Small
Spots." *Journal of Vision* 8(5):15–15. doi: 10.1167/8.5.15.

Brettel, Hans, Françoise Viénot, and John D. Mollon. 1997. "Computerized Simulation of Color
Appearance for Dichromats." *JOSA A* 14(10):2647–55. doi: 10.1364/JOSAA.14.002647.

Burak, Yoram, Uri Rokni, Markus Meister, and Haim Sompolinsky. 2010. "Bayesian Model of
Dynamic Image Stabilization in the Visual System." *Proceedings of the National Academy*
of Sciences 107(45):19525–30. doi: 10.1073/pnas.1006076107.

Burge, Johannes. 2020. "Image-Computable Ideal Observers for Tasks with Natural Stimuli."
Annual Review of Vision Science 6:491–517.

Burge, Johannes, and Wilson S. Geisler. 2011. "Optimal Defocus Estimation in Individual Natural
Images." *Proceedings of the National Academy of Sciences* 108(40):16849–54.

Burge, Johannes, and Wilson S. Geisler. 2014. "Optimal Disparity Estimation in Natural Stereo
Images." *Journal of Vision* 14(2):1–1. doi: 10.1167/14.2.1.

Cai, Lanya T., Venkatesh Krishna, Tim C. Hladnik, Nicholas C. Guilbeault, Scott A. Juntti, Tod R.
Thiele, Aristides B. Arrenberg, and Emily A. Cooper. 2020. "Visual Statistics of Aquatic
Environments in the Natural Habitats of Zebrafish." *Journal of Vision* 20(11):433–433.
doi: 10.1167/jov.20.11.433.

Chakrabarti, Ayan, and Todd Zickler. 2011. "Statistics of Real-World Hyperspectral Images." Pp.
193–200 in *CVPR 2011*. IEEE.

Chaparro, A., C. F. Stromeyer, E. P. Huang, R. E. Kronauer, and R. T. Eskew. 1993. "Colour Is
What the Eye Sees Best." *Nature* 361(6410):348–50. doi: 10.1038/361348a0.

Chin, Benjamin M., and Johannes Burge. 2020. "Predicting the Partition of Behavioral Variability
in Speed Perception with Naturalistic Stimuli." *Journal of Neuroscience* 40(4):864–79.

Coletta, Nancy J., and David R. Williams. 1987. "Psychophysical Estimate of Extrafoveal Cone
Spacing." *JOSA A* 4(8):1503–13.

Cottaris, Nicolas P., Haomiao Jiang, Xiaomao Ding, Brian A. Wandell, and David H. Brainard.
2019. "A Computational-Observer Model of Spatial Contrast Sensitivity: Effects of Wave-
Front-Based Optics, Cone-Mosaic Structure, and Inference Engine." *Journal of Vision*
19(4):8–8.

Cottaris, Nicolas P., Brian A. Wandell, Fred Rieke, and David H. Brainard. 2020. "A
Computational Observer Model of Spatial Contrast Sensitivity: Effects of Photocurrent
Encoding, Fixational Eye Movements, and Inference Engine." *Journal of Vision* 20(7):17–
17. doi: 10.1167/jov.20.7.17.

Curcio, Christine A., Kenneth R. Sloan, Robert E. Kalina, and Anita E. Hendrickson. 1990.
"Human Photoreceptor Topography." *Journal of Comparative Neurology* 292(4):497–
523. doi: https://doi.org/10.1002/cne.902920402.

Davila, Karen D., and Wilson S. Geisler. 1991. "The Relative Contributions of Pre-Neural and
Neural Factors to Areal Summation in the Fovea." *Vision Research* 31(7–8):1369–80.

Derrico, Joel B., and Gershon Buchsbaum. 1991. "A Computational Model of Spatiochromatic
Image Coding in Early Vision." *Journal of Visual Communication and Image
Representation* 2(1):31–38. doi: 10.1016/1047-3203(91)90033-C.

Engström, Kjell. 1960. "Cone Types and Cone Arrangement in the Retina of Some Cyprinids."
Acta Zoologica 41(3):277–95. doi: https://doi.org/10.1111/j.1463-6395.1960.tb00481.x.

Field, David J. 1987. "Relations between the Statistics of Natural Images and the Response
Properties of Cortical Cells." *Josa a* 4(12):2379–94.

Field, Greg D., Jeffrey L. Gauthier, Alexander Sher, Martin Greschner, Timothy A. Machado,
Lauren H. Jepson, Jonathon Shlens, Deborah E. Gunning, Keith Mathieson, Wladyslaw
Dabrowski, Liam Paninski, Alan M. Litke, and E. J. Chichilnisky. 2010. "Functional
Connectivity in the Retina at the Resolution of Photoreceptors." *Nature* 467(7316):673–
77. doi: 10.1038/nature09424.

Garrigan, Patrick, Charles P. Ratliff, Jennifer M. Klein, Peter Sterling, David H. Brainard, and Vijay
Balasubramanian. 2010. "Design of a Trichromatic Cone Array." *PLOS Computational
Biology* 6(2):e1000677. doi: 10.1371/journal.pcbi.1000677.

Geisler, Wilson S. 1989. "Sequential Ideal-Observer Analysis of Visual Discriminations."
Psychological Review 96(2):267.

Geisler, Wilson S. 2011. "Contributions of Ideal Observer Theory to Vision Research." *Vision*
Research 51(7):771–81.

Geisler, Wilson S. 2018. "Psychometric Functions of Uncertain Template Matching Observers."
Journal of Vision 18(2):1–1.

Gu, Shuhang, Wangmeng Zuo, Qi Xie, Deyu Meng, Xiangchu Feng, and Lei Zhang. 2015.
"Convolutional Sparse Coding for Image Super-Resolution." Pp. 1823–31 in *Proceedings*
of the IEEE International Conference on Computer Vision.

Guleryuz, O. G. 2006. "Nonlinear Approximation Based Image Recovery Using Adaptive Sparse
Reconstructions and Iterated Denoising-Part I: Theory." *IEEE Transactions on Image*
Processing 15(3):539–54. doi: 10.1109/TIP.2005.863057.

Hansen, Thorsten, Lars Pracejus, and Karl R. Gegenfurtner. 2009. "Color Perception in the
Intermediate Periphery of the Visual Field." *Journal of Vision* 9(4):26. doi:
10.1167/9.4.26.

Harmening, Wolf M., William S. Tuten, Austin Roorda, and Lawrence C. Sincich. 2014. "Mapping
the Perceptual Grain of the Human Retina." *The Journal of Neuroscience: The Official*
Journal of the Society for Neuroscience 34(16):5667–77. doi: 10.1523/JNEUROSCI.5191-
13.2014.

Hofer, Heidi, Joseph Carroll, Jay Neitz, Maureen Neitz, and David R. Williams. 2005.
"Organization of the Human Trichromatic Cone Mosaic." *The Journal of Neuroscience:*
The Official Journal of the Society for Neuroscience 25(42):9669–79. doi:
10.1523/JNEUROSCI.2414-05.2005.

Jiang, Haomiao, Joyce Farrell, and Brian Wandell. 2016. "A Spectral Estimation Theory for Color
Appearance Matching." *Electronic Imaging* 2016(20):1–4. doi: 10.2352/ISSN.2470-
1173.2016.20.COLOR-329.

Jiang, Haomiao, Qiyuan Tian, Joyce Farrell, and Brian A. Wandell. 2017. "Learning the Image
Processing Pipeline." *IEEE Transactions on Image Processing* 26(10):5032–42. doi:
10.1109/TIP.2017.2713942.

Kadkhodaie, Zahra, and Eero Simoncelli. 2021. "Stochastic Solutions for Linear Inverse Problems
Using the Prior Implicit in a Denoiser." *Advances in Neural Information Processing*
Systems 34.

Karklin, Yan, and Eero P. Simoncelli. 2011. "Efficient Coding of Natural Images with a Population
of Noisy Linear-Nonlinear Neurons." *Advances in Neural Information Processing Systems*
24:999–1007.

Kim, Seha, and Johannes Burge. 2020. "Natural Scene Statistics Predict How Humans Pool
Information across Space in Surface Tilt Estimation." *PLoS Computational Biology*
16(6):e1007947.

Knill, David C., Daniel Kersten, and Alan Yuille. 1996. "Introduction: A Bayesian Formulation of
Visual Perception." *Perception as Bayesian Inference* 1:1–21.

Krizhevsky, Alex, Ilya Sutskever, and Geoffrey E. Hinton. 2012. "Imagenet Classification with
Deep Convolutional Neural Networks." *Advances in Neural Information Processing*
Systems 25:1097–1105.

Land, Michael F., and Dan-Eric Nilsson. 2012. *Animal Eyes*. 2nd edition. Oxford ; New York:
Oxford University Press.

Land, Michael F., and Daniel C. Osorio. 2003. "Colour Vision: Colouring the Dark." *Current*
Biology 13(3):R83–85. doi: 10.1016/S0960-9822(03)00031-9.

Le, Quoc, Alexandre Karpenko, Jiquan Ngiam, and Andrew Ng. 2011. "ICA with Reconstruction
Cost for Efficient Overcomplete Feature Learning." *Advances in Neural Information*
Processing Systems 24.

Lennie, Peter, P. William Haake, and David R. Williams. 1991. "The Design of Chromatically
Opponent Receptive Fields." Pp. 71–82 in *Computational models of visual processing*.
Cambridge, MA, US: The MIT Press.

Levin, Anat, William T. Freeman, and Frédo Durand. 2008. "Understanding Camera Trade-Offs
through a Bayesian Analysis of Light Field Projections." Pp. 88–101 in *Computer Vision –*
ECCV 2008, *Lecture Notes in Computer Science*, edited by D. Forsyth, P. Torr, and A.
Zisserman. Berlin, Heidelberg: Springer.

Lewis, Alex, and Zhaoping Li. 2006. "Are Cone Sensitivities Determined by Natural Color
Statistics?" *Journal of Vision* 6(3):285–302. doi: 10.1167/6.3.8.

Lian, Trisha. 2020. *Vision Modeling Tools for Evaluating Next-Generation Displays*. PhD Thesis,
Stanford University.

Lindsey, Delwin, Lindsey Hutchinson, and Angela Brown. 2020. "Unique Yellow and Other
Special Colors Seen by Deuteranomalous Trichromats." *Journal of Vision* 20(11):1249–
1249. doi: 10.1167/jov.20.11.1249.

Manning, Jeremy R., and David H. Brainard. 2009. "Optimal Design of Photoreceptor Mosaics:
Why We Do Not See Color at Night." *Visual Neuroscience* 26(1):5.

Marimont, David H., and Brian A. Wandell. 1994. "Matching Color Images: The Effects of Axial
Chromatic Aberration." *JOSA A* 11(12):3113–22. doi: 10.1364/JOSAA.11.003113.

Martinez-Conde, Susana, Stephen L. Macknik, and David H. Hubel. 2004. "The Role of Fixational Eye Movements in Visual Perception." *Nature Reviews Neuroscience* 5(3):229–40. doi: 10.1038/nrn1348.

Mullen, K. T. 1985. "The Contrast Sensitivity of Human Colour Vision to Red-Green and Blue-Yellow Chromatic Gratings." *The Journal of Physiology* 359:381–400.

Mullen, Kathy T., and Frederick A. A. Kingdom. 1996. "Losses in Peripheral Colour Sensitivity Predicted from 'Hit and Miss' Post-Receptoral Cone Connections." *Vision Research* 36(13):1995–2000. doi: 10.1016/0042-6989(95)00261-8.

Nascimento, Sérgio MC, Flávio P. Ferreira, and David H. Foster. 2002. "Statistics of Spatial Cone-Excitation Ratios in Natural Scenes." *JOSA A* 19(8):1484–90.

Naselaris, Thomas, Ryan J. Prenger, Kendrick N. Kay, Michael Oliver, and Jack L. Gallant. 2009. "Bayesian Reconstruction of Natural Images from Human Brain Activity." *Neuron* 63(6):902–15.

Neitz, Alexandra, Xiaoyun Jiang, James A. Kuchenbecker, Niklas Domdei, Wolf Harmening, Hongyi Yan, Jihyun Yeonan-Kim, Sara S. Patterson, Maureen Neitz, Jay Neitz, Daniel R. Coates, and Ramkumar Sabesan. 2020. "Effect of Cone Spectral Topography on Chromatic Detection Sensitivity." *JOSA A* 37(4):A244–54. doi: 10.1364/JOSAA.382384.

Nolan, John M., James M. Stringham, Stephen Beatty, and D. Max Snodderly. 2008. "Spatial Profile of Macular Pigment and Its Relationship to Foveal Architecture." *Investigative Ophthalmology & Visual Science* 49(5):2134–42. doi: 10.1167/iovs.07-0933.

Olshausen, Bruno A., and David J. Field. 1996. "Emergence of Simple-Cell Receptive Field Properties by Learning a Sparse Code for Natural Images." *Nature* 381(6583):607–9.

Parthasarathy, Nikhil, Eleanor Batty, William Falcon, Thomas Rutten, Mohit Rajpal, E. J. Chichilnisky, and Liam Paninski. 2017. "Neural Networks for Efficient Bayesian Decoding of Natural Images from Retinal Neurons." *Advances in Neural Information Processing Systems* 30.

Pelli, Denis G. 1985. "Uncertainty Explains Many Aspects of Visual Contrast Detection and Discrimination." *JOSA A* 2(9):1508–32.

Polans, James, Bart Jaeken, Ryan P. McNabb, Pablo Artal, and Joseph A. Izatt. 2015. "Wide-Field Optical Model of the Human Eye with Asymmetrically Tilted and Decentered Lens That Reproduces Measured Ocular Aberrations." *Optica* 2(2):124–34. doi: 10.1364/OPTICA.2.000124.

Portilla, Javier, Vasily Strela, Martin J. Wainwright, and Eero P. Simoncelli. 2003. "Image Denoising Using Scale Mixtures of Gaussians in the Wavelet Domain." *IEEE Transactions on Image Processing* 12(11):1338–51.

Putnam, Christopher M., and Pauline J. Bland. 2014. "Macular Pigment Optical Density Spatial
Distribution Measured in a Subject with Oculocutaneous Albinism." *Journal of*
Optometry 7(4):241–45. doi: 10.1016/j.optom.2014.03.001.

Ratnam, Kavitha, Niklas Domdei, Wolf M. Harmening, and Austin Roorda. 2017. "Benefits of
Retinal Image Motion at the Limits of Spatial Vision." *Journal of Vision* 17(1):30. doi:
10.1167/17.1.30.

Romano, Yaniv, Michael Elad, and Peyman Milanfar. 2017. "The Little Engine That Could:
Regularization by Denoising (RED)." *SIAM Journal on Imaging Sciences* 10(4):1804–44.
doi: 10.1137/16M1102884.

Rucci, Michele, Ramon Iovin, Martina Poletti, and Fabrizio Santini. 2007. "Miniature Eye
Movements Enhance Fine Spatial Detail." *Nature* 447(7146):852–55. doi:
10.1038/nature05866.

Rushton, W. A. 1962. "Visual Pigments in Man." *Scientific American* 207:120–32. doi:
10.1038/scientificamerican1162-120.

Russakovsky, Olga, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng
Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-
Fei. 2015. "ImageNet Large Scale Visual Recognition Challenge." *ArXiv:1409.0575 [Cs]*.

Rust, Nicole C., and Alan A. Stocker. 2010. "Ambiguity and Invariance: Two Fundamental
Challenges for Visual Processing." *Current Opinion in Neurobiology* 20(3):382–88. doi:
10.1016/j.conb.2010.04.013.

Sabesan, Ramkumar, Brian P. Schmidt, William S. Tuten, and Austin Roorda. 2016. "The
Elementary Representation of Spatial and Color Vision in the Human Retina." *Science*
Advances 2(9):e1600797. doi: 10.1126/sciadv.1600797.

Schmidt, Brian P., Alexandra E. Boehm, William S. Tuten, and Austin Roorda. 2019. "Spatial
Summation of Individual Cones in Human Color Vision." *PLOS ONE* 14(7):e0211397. doi:
10.1371/journal.pone.0211397.

Sekiguchi, N., D. R. Williams, and D. H. Brainard. 1993. "Efficiency in Detection of Isoluminant
and Isochromatic Interference Fringes." *Journal of the Optical Society of America. A,*
Optics, Image Science, and Vision 10(10):2118–33. doi: 10.1364/josaa.10.002118.

Shepard, Roger N. 1987. "Toward a Universal Law of Generalization for Psychological Science."
Science 237(4820):1317–23.

Simoncelli, Eero P. 2005. "4.7 Statistical Modeling of Photographic Images." *Handbook of Video*
and Image Processing 9.

Simoncelli, Eero P., and Bruno A. Olshausen. 2001. "Natural Image Statistics and Neural
Representation." *Annual Review of Neuroscience* 24(1):1193–1216.

Sims, Chris R. 2018. "Efficient Coding Explains the Universal Law of Generalization in Human
Perception." *Science* 360(6389):652–56. doi: 10.1126/science.aaq1118.

Singh, Vijay, Nicolas P. Cottaris, Benjamin S. Heasly, David H. Brainard, and Johannes Burge.
2018. "Computational Luminance Constancy from Naturalistic Images." *Journal of Vision*
18(13):19–19. doi: 10.1167/18.13.19.

Snyder, A. W., T. R. Bossomaier, and A. Hughes. 1986. "Optical Image Quality and the Cone
Mosaic." *Science (New York, N.Y.)* 231(4737):499–501. doi: 10.1126/science.3941914.

Snyder, A. W., S. B. Laughlin, and D. G. Stavenga. 1977. "Information Capacity of Eyes." *Vision*
Research 17(10):1163–75. doi: 10.1016/0042-6989(77)90151-1.

Stocker, Alan A., and Eero P. Simoncelli. 2006. "Noise Characteristics and Prior Expectations in
Human Visual Speed Perception." *Nature Neuroscience* 9(4):578–85. doi:
10.1038/nn1669.

Stockman, Andrew, and Lindsay T. Sharpe. 2000. "The Spectral Sensitivities of the Middle- and
Long-Wavelength-Sensitive Cones Derived from Measurements in Observers of Known
Genotype." *Vision Research* 40(13):1711–37. doi: 10.1016/S0042-6989(00)00021-3.

Stockman, Andrew, and Lindsay T. Sharpe. 2006. "Into the Twilight Zone: The Complexities of
Mesopic Vision and Luminous Efficiency." *Ophthalmic & Physiological Optics: The*
Journal of the British College of Ophthalmic Opticians (Optometrists) 26(3):225–39. doi:
10.1111/j.1475-1313.2006.00325.x.

Tian, Qiyuan, Henryk Blasinski, Steven Lansel, Haomiao Jiang, Munenori Fukunishi, Joyce E.
Farrell, and Brian A. Wandell. 2015. "Automatically Designing an Image Processing
Pipeline for a Five-Band Camera Prototype Using the Local, Linear, Learned (L ^{3})
Method." P. 940403 in, edited by N. Sampat, R. Tezaur, and D. Wüller. San Francisco,
California, United States.

Tjan, Bosco S., and Gordon E. Legge. 1998. "The Viewpoint Complexity of an Object-Recognition
Task." *Vision Research* 38(15):2335–50. doi: 10.1016/S0042-6989(97)00255-1.

Tkačik, Gašper, Jason S. Prentice, Jonathan D. Victor, and Vijay Balasubramanian. 2010. "Local
Statistics in Natural Scenes Predict the Saliency of Synthetic Textures." *Proceedings of*
the National Academy of Sciences 107(42):18149–54. doi: 10.1073/pnas.0914916107.

Tregillus, Katherine E. M., Zoey J. Isherwood, John E. Vanston, Stephen A. Engel, Donald I. A.
MacLeod, Ichiro Kuriki, and Michael A. Webster. 2021. "Color Compensation in
Anomalous Trichromats Assessed with FMRI." *Current Biology* 31(5):936-942.e4. doi:
10.1016/j.cub.2020.11.039.

Ulyanov, Dmitry, Andrea Vedaldi, and Victor Lempitsky. 2018. "Deep Image Prior." Pp. 9446–54
in *Proceedings of the IEEE conference on computer vision and pattern recognition*.

Van Hateren, J. H. 1993. "Spatial, Temporal and Spectral Pre-Processing for Colour Vision."
Proceedings of the Royal Society of London. Series B: Biological Sciences 251(1330):61–
68. doi: 10.1098/rspb.1993.0009.

Venkatakrishnan, Singanallur V., Charles A. Bouman, and Brendt Wohlberg. 2013. "Plug-and-
Play Priors for Model Based Reconstruction." Pp. 945–48 in *2013 IEEE Global Conference
on Signal and Information Processing*. Austin, TX, USA: IEEE.

Virsu, V., and J. Rovamo. 1979. "Visual Resolution, Contrast Sensitivity, and the Cortical
Magnification Factor." *Experimental Brain Research* 37(3):475–94. doi:
10.1007/BF00236818.

Walls, G. L. 1942. *The Vertebrate Eye and Its Adaptive Radiation*. Oxford, England: Cranbrook
Institute of Science.

Wang, Zhou, Alan C. Bovik, Hamid R. Sheikh, and Eero P. Simoncelli. 2004. "Image Quality
Assessment: From Error Visibility to Structural Similarity." *IEEE Transactions on Image
Processing* 13(4):600–612.

Watson, Andrew B. 2017. "QUEST: A General Multidimensional Bayesian Adaptive Psychometric
Method." *Journal of Vision* 17(3):1–27. doi: 10.1167/17.3.10.

Webster, Michael A., and J. D. Mollon. 1997. "Adaptation and the Color Statistics of Natural
Images." *Vision Research* 37(23):3283–98. doi: 10.1016/S0042-6989(97)00125-9.

Wei, Xue-Xin, and Alan A. Stocker. 2015. "A Bayesian Observer Model Constrained by Efficient
Coding Can Explain 'anti-Bayesian' Percepts." *Nature Neuroscience* 18(10):1509–17. doi:
10.1038/nn.4105.

Williams, David R. 1985. "Aliasing in Human Foveal Vision." *Vision Research* 25(2):195–205. doi:
10.1016/0042-6989(85)90113-0.

Williams, David R., Nobutoshi Sekiguchi, William Haake, David Brainard, and Orin Packer. 1991.
"The Cost of Trichromacy for Spatial Vision." Pp. 11–22 in *From Pigments to Perception:
Advances in Understanding Visual Processes*, *NATO ASI Series*, edited by A. Valberg and
B. B. Lee. Boston, MA: Springer US.

Wool, Lauren E., Joanna D. Crook, John B. Troy, Orin S. Packer, Qasim Zaidi, and Dennis M.
Dacey. 2018. "Nonselective Wiring Accounts for Red-Green Opponency in Midget
Ganglion Cells of the Primate Retina." *Journal of Neuroscience* 38(6):1520–40. doi:
10.1523/JNEUROSCI.1688-17.2017.

Yellott, J. I. 1983. "Spectral Consequences of Photoreceptor Sampling in the Rhesus Retina."
Science 221(4608):382–85. doi: 10.1126/science.6867716.

Zhang, L., L. Zhang, X. Mou, and D. Zhang. 2011. "FSIM: A Feature Similarity Index for Image
Quality Assessment." *IEEE Transactions on Image Processing* 20(8):2378–86. doi:
10.1109/TIP.2011.2109730.

Zhang, Xuemei, and Brian A. Wandell. 1997. "A Spatial Extension of CIELAB for Digital Color-
Image Reproduction." *Journal of the Society for Information Display* 5(1):61–63.

Zimmermann, Maxime J. Y., Noora E. Nevala, Takeshi Yoshimatsu, Daniel Osorio, Dan-Eric
Nilsson, Philipp Berens, and Tom Baden. 2018. "Zebrafish Differentially Process Color
across Visual Space to Match Natural Scenes." *Current Biology* 28(13):2018-2032.e5. doi:
10.1016/j.cub.2018.04.075.

1442

 Supplementary Figures:

1445
1446
Figure 4, Supplementary Figure 1: Factors that Contribute to Optimal S Cone Proportion.
Average reconstruction error as a function of S-cone proportion, computed as RSS of pixel
values for the R- (left), G- (middle), and B-planes (right) respectively. Under typical conditions
(red), a low S-cone ratio is optimal for all three planes. Removing lens pigment and macular
pigment from the simulations (blue) increases the SNR of the S cones by increasing their
average quantum catch, but has little effect on the optimal S-cone proportion for any of the
image planes. Correcting chromatic aberration (green) while retaining lens pigment and macular
pigment greatly improves the information provided by the S cones for the B-plane, but not for
the R- and G- planes. Error bars indicate $\pm$ 1 SEM.
1456

1457
1458
Figure 4, Supplementary Figure 2: Effect of the Allocation of Retinal Cone Types on
Reconstruction of Hyperspectral Images. Average reconstruction error as a function of L-
cone proportion (top) and S-cone proportion (bottom), computed as RSS of pixel values over
space and wavelength, for a set of evaluation hyperspectral images of size of $18 * 18$ and 15
uniform wavelength sample between 420 nm and 700 nm (see *Methods*). Error bars indicate $\pm$
1 SEM. The results corroborated our main conclusion obtained with RGB images, shown in **Fig.**
4.
1466

1467
1468
Figure 5, Supplementary Figure 1: Effect of Spatial and Chromatic Correlation on the
Optimal Allocation of Photoreceptors (matched y-axis). Same as **Figure 5** but with matched
y-axis to highlight the overall magnitude of errors across the different conditions. Average image
reconstruction error from a half-degree square foveal mosaic on different sets of synthetic
images, computed as root sum of squares (RSS) distance in the RGB pixel space, as a function
of %L cone (L:M cone ratio) of the mosaic The shaded areas represent %L values that
correspond to RSS values within a +0.1 RSS margin from the optimal (minimum RSS) point.
1476

1477
1478
Figure 7, Supplementary Figure 1: Reconstruction with a Weak Prior Across SNR Levels.
Image reconstructions for a set of example images in the evaluation set from 1-degree, foveal
(A) normal trichromatic and **(B)** deuteranomalous trichromatic mosaics at five different overall
light intensity levels that lead to different Poisson signal-to-noise ratios in the cone excitations.
The average excitations (photo-isomerizations) per cone per 50 ms integration time is chosen to
be approximately 10^4 for *Outdoor Daylight*, 10^3 for *LCD Monitor*, 10^2 for *Dim Light*, and 10^1 for
Twilight (Lewis and Li 2006; Stockman and Sharpe 2006). To highlight the effect of noise and
prior, the prior weight was set to a much lower level ($\lambda = 0.001$) than the optimal value
($\lambda = 0.05$) used for the results shown in **Fig. 7**.
1488

1489
1490
Figure 8, Supplementary Figure 1: Optics and Cone Mosaic at Different Retinal
Eccentricities. Enlarged view of the top panels of **Fig. 8**. The coordinates at the top of each
pair indicate the horizontal and vertical eccentricity of the retinal patch. The left image of each
pair shows a contour plot of the point-spread function relative to an expanded view of the cone
mosaic, while the right image of each pair shows the full 1-degree mosaic used in the
simulation.
1497

1498
1499
Figure 8, Supplementary Figure 2: Reconstruction Error at Different Visual Eccentricities.
Average image reconstruction error, computed as RSS of pixel values for both the RGB images
(left y-axis), and corresponding gray scale images to measure the spatial error, define as the
first PC based on a PCA analysis of our image dataset (i.e., $0.57R + 0.59G + 0.56B$, right y-
axis), as a function of the visual eccentricity location of a 1-deg retinal mosaic. Error bars
indicate +/- 1 SEM.
1506

1507
1508
Figure 8, Supplementary Figure 3: Image Reconstruction with Different Point Spread
Functions. (A) Image reconstructions for a set of example images in the evaluation set from 1-
degree patches of mosaic at (10, 10) degree eccentricity, but with PSFs sampled from different
visual eccentricities as indicated by the top panel. **(B)** The average differential reconstruction
error (i.e., difference in RSS compared to the lowest value obtained among the simulations) as
a function of the eccentricity of the PSFs used. Error bars represent +/- 1 SEM. To separate the
spatial and chromatic error, we perform a PCA analysis on the RGB images. The RSS along the
first PC ($0.57R + 0.59G + 0.56B$) corresponds to the spatial error (left axis), while the RSS along
the second and third PCs ($0.76R - 0.13G - 0.64B;\ -0.31R + 0.80G - 0.52B$) quantify the
chromatic error (right axis). With the range of PSFs in our simulation, the minimal spatial error is
obtained with the PSF at (10, 10) deg (i.e., the PSF that matched to the mosaic), and the
minimal chromatic error is obtained with the largest PSF, corresponding to (18, 18) deg.
1521

1522
1523
Figure 8, Supplementary Figure 4: Image Reconstruction at Peripheral Eccentricities with
Maximum Likelihood Estimation (MLE). Image reconstructions obtained using maximum
likelihood estimation for a few example images in the evaluation set from 1-degree patches of
mosaic at different retinal eccentricities, as indicated at the top of each column. Note that
simulation of cone excitation noise is turned off for these reconstructions. Note also that the
MLE reconstructions are not unique (see **Fig. 3**). The MLE reconstructions shown here were
chosen arbitrarily as the ones converged upon by our particular numerical search algorithm.
1531

1532
1533
Figure 9, Supplementary Figure 1: Reconstruction of Chromatic Grating Stimuli
with/without Optical Aberrations. Image reconstruction of chromatic grating stimuli with
increasing spatial frequency from **(A)** a 0.2-deg foveal mosaic and **(B)** a 1-deg peripheral
mosaic at (18, 18) degrees retinal eccentricity with full optical aberrations (left columns) and with
diffraction-limited optics (right columns). The top left images show a contour plot of the point-
spread function relative to an expanded view of the cone mosaic, while the top right images
show the full mosaic. Images were modulations of the red channel of the simulated monitor, to
mimic the 633 nm laser used in the interferometric experiments. The exact frequency of the
stimuli being used for each condition is as denoted in the figure. Note that the mottle observed
in the reconstructions with full optical aberrations at high spatial frequencies match the
reconstruction of a uniform field of saturated red stimulus.
1545
1546
1547
1548

1549
1550
Figure 9, Supplementary Figure 2: Reconstruction of Achromatic Grating Stimuli
with/without Optical Aberrations. Image reconstructions of achromatic grating stimuli with
increasing spatial frequency from **(A)** a 0.2-deg foveal mosaic and **(B)** a 1-deg peripheral
mosaic at (18, 18) degree retinal eccentricity with full optical aberration (left columns) and with
diffraction-limited optics (right columns). The top left images show a contour plot of the point-
spread function relative to an expanded view of the cone mosaic, while the top right images
show the full mosaic. The exact frequency of the stimuli being used for each condition is as
denoted in the figure. The reconstruction shows similar spatial aliasing as in **Fig. 9** and **Fig. S6**,
but shows an additional pattern of chromatic aliasing that arises because of the interleaved
sampling by a mosaic of different cone types (Williams et al. 1991; Brainard et al. 2008).
Whether such chromatic aliasing would actually be observed if a subject viewed achromatic
gratings under diffraction-limited conditions is to our knowledge, an open question.
1563

1564
1565
Figure 10, Supplementary Figure 1: Contrast Sensitivity Function of a MLE
Reconstruction Observer. Contrast sensitivity, defined as the inverse of threshold contrast, for
an image reconstruction-based observer *without* the prior term ($\lambda = 0$) as a function of the
spatial frequency of stimulus in either L+M direction (black) and L-M direction (red) with equal
RMS cone contrast. Note that the MLE reconstructions are not unique (see **Fig. 3**). In the
computations whose results are shown here, the MLE reconstructions were chosen arbitrarily as
the ones converged upon by our particular numerical search algorithm.