Rostral Anterior Cingulate Activations inversely relate to Reward Payoff Maximation & predict Depressed Mood

Pragathi Priyadharsini Balasubramani[1*], Juan Diaz-Delgado[1], Gillian Grennan[1], Fahad Alim[1],

Mariam Zafar-Khan[1], Vojislav Maric[1], Dhakshin Ramanathan[1,2], Jyoti Mishra[1*]

[1]Neural Engineering and Translation Labs, Department of Psychiatry, University of California,

San Diego, La Jolla, CA, USA

[2]Department of Mental Health, VA San Diego Medical Center, San Diego, CA

[*]Correspondence should be addressed to:

Pragathi Priyadharsini Balasubramani & Jyoti Mishra

University of California, San Diego

Neural Engineering & Translation Labs (NEAT Labs)

9500 Gilman Drive Mail Code 0875

La Jolla, CA 92037

pbalasubramani@health.ucsd.edu & jymishra@health.ucsd.edu

Keywords: reward prediction; risk sensitivity; reinforcement learning; anterior cingulate cortex;;

depression

Conflict of Interest. The authors declare no conflict of interest.

Abstract

Choice selection strategies and decision making are typically investigated using multiple-

choice gambling paradigms that require participants to maximize reward payoff. However,

research shows that performance in such paradigms suffers from individual biases towards the

frequency of gains to choose smaller local gains over larger longer term gain, also referred to as

melioration. Here, we developed a simple two-choice reward task, implemented in 186 healthy

human adult subjects across the adult lifespan to understand the behavioral, computational, and

neural bases of payoff maximization versus melioration. The observed reward choice behavior on

this task was best explained by a reinforcement learning model of differential future reward

prediction. Simultaneously recorded and source-localized electroencephalography (EEG) showed

that diminished theta-band activations in the right rostral anterior cingulate cortex (rACC)

correspond to greater reward payoff maximization, specifically during the presentation of

cumulative reward information at the end of each task trial. Notably, these activations (greater

rACC theta) predicted depressed mood symptoms, thereby showcasing a reward processing

marker of potential clinical utility.

Significance Statement

This study presents cognitive, computational and neural (EEG-based) analyses of a rapid reward-based decision-making task. The research has the following three highlights. 1) It teases apart two core aspects of reward processing, i.e. long term expected value maximization versus immediate gain frequency melioration based choice behavior. 2) It models reinforcement learning based behavioral differences between individuals showing that observed performance is best explained by differential extents of reward prediction. 3) It investigates neural correlates in 186 healthy human subjects across the adult lifespan, revealing specific theta band cortical source activations in right rostral anterior cingulate as correlates for maximization that further predict depressed mood across subjects.

Introduction

Cognitive and neural responses to reward and risk are quintessential to understanding human behavior. Gambling tasks predominantly form the experimental test beds for measuring reward and risk processing abilities in humans (Bechara et al., 1997; Brevers et al., 2013). However, it is widely debated how well these tasks can separate decision-making based on frequency of gains/losses versus expected value of payoff for different choice-sets (Bechara et al., 1997, 2000, 2000; Bembich et al., 2014; Christakou et al., 2009; Garon et al., 2006; R. Gupta et al., 2011; Mueller et al., 2010; Must et al., 2013; Oberg et al., 2011; Roca et al., 2008; Woodrow et al., 2019).

For instance, studies that have controlled for gain frequency in the Iowa Gambling Task (IGT) show that subject choices reflect their inherent gain frequency preferences in the task, which

portray relatively immediate reinforcement based choice behavior rather than a behavior that

maximizes expected value or long-term payoff (Chiu et al., 2008; Chiu & Lin, 2007; Lin et al.,

2009; Napoli & Fum, 2010; Singh & Khan, 2012). In contrast, some researchers suggest such local

minima choices also referred to as melioration may be the rational solution in the face of

uncertainty (Sims et al., 2013). Additionally, task related performance measures for long-term

payoff versus immediate gain frequency bias may reflect distinct reinforcement learning and

decision making strategies, e.g. sensitivity to rewards and risks, learning rate, and other behavioral

execution strategies (Franken & Muris, 2005; Furl, 2010; Harman, 2011; Newman et al., 2008;

Weller et al., 2010), which prior neural studies of reward payoff maximization have not accounted

for.

In this study, we uniquely separate immediate gain frequency bias driven decision-making

from advantageous longer term payoff-based decision making. Specifically, we designed a two-

choice paradigm with two distinct blocks – a $\Delta_0$payoff (baseline) block where two reward choice

options have equal payoffs and reward variance suitable for measuring the immediate gain

frequency bias, and a Δpayoff (difference) block where the two-choice options have unequal

payoffs suitable for measuring payoff influences. We thereby, tease apart measurements of

immediate gain frequency biased response from expected value or long-term payoff based

response, to understand the distinct cognitive and neural mechanisms underlying payoff decisions.

Second, we capitalize on computational reinforcement learning (RL) models to understand

the basis of individual differences in reward and risk based learning across subjects

(Balasubramani et al., 2014; Balasubramani & Chakravarthy, 2019; Chakravarthy et al., 2018; A.

Gupta et al., 2013; Muralidharan et al., 2014). The RL framework provides the ability to simulate

the observed behavior and estimate the hidden parameters forming the basis for individual

differences in learning and performance. Specifically in this study, we checked whether the

observed subject behavior for reward payoff maximization versus gain frequency bias melioration

can be explained by extent of future reward prediction (Doya, 2002), or differential risk seeking

towards gains versus losses (Balasubramani et al., 2014).

Neurally, earlier studies have suggested the significant role of frontal executive regions,

particularly the medial prefrontal cortex (mPFC) in reward and risk based performance

(Balasubramani & Hayden, 2018; Bechara et al., 1997, 2000; Brevers et al., 2013; Kennerley et

al., 2011; Moccia et al., 2017). Uniquely, in this study, we estimate the neural correlates for payoff

relevant decisions while accounting for significant RL parameters and individual differences in

immediate gain frequency biases. Finally, we understand the relationship between the identified

neural correlates for reward maximization to individual's self-reported mood symptom variations.

We show that reward payoff maximization correlates within mPFC are sensitive to depressed

mood, and hence our experimental and computational framework for identifying the regions of

interest in mPFC may serve future clinical utility as a biomarker for depression.

Methods

Participants. 198 adult human subjects (age mean ± standard deviation 35.44 ± 20.30 years, range 18-80 years, 115 females) participated in the study. All participants provided written informed consent for the study protocol approved by the University of California San Diego institutional review board (UCSD IRB #180140). Twelve of these participants were excluded from the study as they had a current diagnosis for a psychiatric disorder and current/recent history of psychotropic medications for a final sample of 186 healthy adult participants. All participants reported normal/corrected-to-normal vision and hearing and no participant reported color blindness. For older adults >60 years of age, participants were confirmed to have a Mini-Mental State Examination (MMSE) score >26 to verify absence of apparent cognitive impairment (Arevalo-Rodriguez et al. 2015). All data was collected prior to the COVID-19 period of restricted human subjects research.

Surveys. All participants provided demographic information by self-report including age, gender, race (in a scale of 1 to 7: Caucasian; Black/African American; Native Hawaiian / Other Pacific Islander; Asian; American Indian / Alaska Native; More than one race; Unknown or not reported) and ethnicity; socio-economic status (SES) was measured on the Family Affluence Scale from 1 to 9 (Boudreau and Poulin, 2008), and any current/past history of clinical diagnoses and medications were reported. For older adults >60 years of age, participants completed the Mini-Mental State Examination (MMSE) and scored >26 to verify absence of apparent cognitive impairment (Arevalo-Rodriguez et al., 2015). All participants completed subjective mental health self-reports using standard instruments, ratings of inattention and hyperactivity obtained on the Adult ADHD Rating Scale (New York University and Massachusetts General Hospital. Adult ADHD-RS-IV with Adult Prompts. 2003; : 9–10), Generalized Anxiety Disorder 7-item scale GAD-7 (Spitzer et al., 2006) and depression symptoms reported on the 9-item Patient Health Questionnaire, PHQ-9 (Kroenke et al., 2001). Symptoms for these psychiatric conditions were measured because they have been related to changes in reward processing (Admon & Pizzagalli, 2015; Dillon et al., 2014; Luman et al., 2010).

Task Design. We investigated a two-choice decision-making task that enabled a rapid assessment and was easy to understand across the adult lifespan. In this task that we refer to as *Lucky Door*, participants chose between one of two doors, either a rare gain door (RareG, probability for gains p=0.3, for losses p=0.7) or a rare loss door (RareL, probability for losses p=0.3, for gains p=0.7). Participants used the left and right arrow keys on the keyboard to make their door choice. Door choice was monitored throughout the task. In two separate blocks, we investigated whether the overall expected value (payoff) of the choice door can influence individual behavior. In the baseline block with $\Delta_0$payoff (no-payoff difference), the two choice doors did not differ in payoff (RareL door, p=0.3 for -70 coins and p=0.7 for +30 coins, payoff=0; RareG door, p=0.3 for +70 coins and p=0.7 for -30 coins, payoff=0). In the experimental difference block with Δpayoff (payoff difference), expected value or payoff was greater for the RareG door (p=0.3 for +60 coins, p=0.7 for -20 coins, payoff=+40) than for the RareL door (p=0.3 for -60 coins, p=0.7 for +20 coins; payoff=-40). Manipulation of payoff, with greater expected value tied to the RareG door, allowed for investigating individual propensities to prioritize long-term (or cumulative) vs. short-term (or immediate) rewards. The RareG door was assigned greater payoff because selecting this door suggests payoff-based decision processing in subjects as opposed to simply choosing based on

frequency of gains, in which case the RareL choice should be preferred. 40 trials were presented
per block and block order was randomized across participants; two practice trials preceded the
main Δpayoff or Δ₀payoff blocks. **Figure 1A** shows a schematic of the task stimulus sequence and
Supplementary table 1 shows the reward distribution that was shuffled and updated after every
10 trials had been sampled from that set.
The *Lucky Door* task was deployed in Unity as part of the assessment suite on the *BrainE*
(short for Brain Engagement) platform (Balasubramani et al., 2020). The Lab Streaming Layer
(LSL (Kothe et al., 2019)) protocol was used to time-stamp each stimulus/response event during
the task. Study participants engaged with the assessment on a Windows 10 laptop sitting at a
comfortable viewing distance.
158
159 **Electroencephalography (EEG).** EEG data was collected simultaneous to the *Lucky Door* task
160 using a 24-channel Smarting device with a semi-dry and wireless electrode layout (Next EEG—
161 new human interface, MBT). Data were acquired at 500 Hz sampling frequency at 24-bit
162 resolution. Cognitive event markers were integrated using LSL and data files were stored in xdf
163 format.
164
Behavioral analyses. Task speeds were calculated as log(1/RT), where RT is response time in
seconds. We computed the payoff sensitive performance response (*Perf*) as the difference in
proportion selection of the RareG door between the Δpayoff and the Δ₀payoff blocks; RareG vs.
RareL EVs differed only in the Δpayoff block. We computed gain frequency bias (*Bias*) as the
difference in selected proportion of RareL and RareG doors in the Δ₀payoff block where the payoff
for both the doors was the same. While *Perf* is indicative of subjective payoff maximization based
selection of advantageous choices, *Bias* informs the choice bias and melioration for higher
immediate gain frequencies. For N fraction of responses in each block, we calculated:
173

174
$$Perf = N_{exptRareG} - N_{baseRareG}$$
$$Bias = N_{baseRareL} - N_{baseRareG}$$
(1)

175
176 We also calculated Win-Stay and Lose-Shift performance on both Δpayoff and Δ₀payoff blocks.
177 Win-Stay was computed as the proportion of times the subject repeated the same choice option in
178 the next trial after obtaining a gain for choosing that option in the current trial. Lose-Shift was
179 computed as the proportion of times the subject would shift away from the current choice option
180 in the next trial, on obtaining a loss in the current trial.
181
Reinforcement Learning (RL) Model. We simulated three parsimonious RL models with up to
two free parameters, which have a key role in reward-based decision-making, to explain the
observed individual subject behavior; see **Figure 2A** for model schematic (Balasubramani et al.,
2014; Sutton & Barto, 1998):
1) Model A optimized the time scale of reward prediction (γ) for every subject;
2) Model B optimized risk sensitivity (α) for every subject; and
3) Model C optimized both γ and α to for every subject.
The time scale of reward prediction parameter (γ) represents whether reward prediction is myopic
or long-sighted, lower values $\gamma \in (0\ 1)$, $\gamma \to 0$ suggest myopic reward prediction leading to

impulsive decisions while higher values, $\gamma \to 1$ suggest long-sighted integration of rewards for
decisions.
The risk sensitivity parameter (α) measures the extent to which expected uncertainty associated
with the door influences the decision utility, the smaller the parameter value $\alpha \in (-1\ 1)$, $\alpha \to -1$ the
higher is risk seeking, while a larger value, $\alpha \to 1$ indicates high risk aversiveness.
The simulation agent had reward distributions as in the real experiment but scaled down
by multiplying with a parameter 0.1, and varying with blocks (Δpayoff, $\Delta_0$payoff) that were
randomly ordered. There were as high as 50,000 trials in each block for letting model performance
converge.
200
201 The agent has to choose between two doors each of which (stimulus, s) was represented by a radial
202 basis function (Φ_i) as below:

203
$$\Phi_s = \exp\frac{-(x - \mu_s)^2}{\sigma^2} \tag{2}$$

204 Here, the μ_s and σ denotes the mean ($s \in [1\ 2]$; door1 = 1; door2 = 2) and standard deviation of the
205 inverse attention parameter, respectively. σ is set to 1 in our models.
206
207 The door stimulus is multiplied with the weight matrix wv for computing its value function, Q, and
208 wr for constructing its risk function, $\sqrt{h}$.
209
210 Utility associated with any state at a trial, t, is the combination of value and risk function(Bell,
211 1995; d'Acremont et al., 2009), where the risk function is modulated by a risk sensitivity parameter
212 α. Higher the α, higher the risk aversiveness of the subject.
213
214
$$U(s,t) = Q(s,t) - \alpha\sqrt{h(s,t)}$$

Where
215
$$Q(s,t) = wv(s,t)\Phi(s)$$
$$h(s,t) = wr(s,t)\Phi(s) \tag{3}$$

216 The door choice selection is performed using the SoftMax principle defined as below. According
217 to SoftMax, the probability for choosing a door at trial, t, is $P(s,t)$:

218
$$P(s,t) = \frac{exp(\beta U(s,t))}{\sum_{i=1}^{n} exp(\beta U(i,t))} \tag{4}$$

219 Here, n is the total number of doors available, and β is the exploration index. β is set to 1 in our
220 models.
221 After choice selection, the weight functions are updated using the below principles. The choice
222 value function Q at trial $t+1$ for door, s, may be expressed as,
223
$$Q_{t+1}(s,t) = Q_t(s,t) + \eta_Q \delta\Phi(s) \tag{5}$$

224 where ηQ is the learning rate of the value function ($0 < \eta Q < 1$) for the stimulus variable, $\Phi(s)$. δ
225 is the temporal difference error represented as
226
$$\delta = r + \gamma\ max_{s'}\ Q(s',t) - Q_t(s,t) \tag{6}$$

where r is the reward associated with taking an action, a, for stimulus, s, at time, t, and γ is the

time scale of reward prediction. Similar to the value function, the risk function h has an incremental
update as defined by the below equation. Optimizing the risk function in addition to the value
function is shown to capture human behavior well in a variety of cognitive tasks involving rewards,
punishments and risk (Balasubramani, Chakravarthy, Ravindran, et al., 2015; Balasubramani et
al., 2014).

$$h_{t+1}(s,t) = h_t(s,t) + \eta_h \xi \Phi(s)$$

(7)

233 where ηh is the learning rate of the risk function ($0 < \eta h < 1$), and ξ is the risk prediction error
234 expressed by the below equation.

235
$$\xi = \delta^2 - h_t(s,t)$$

(8)

236 For simplicity, we model as $\eta_h = \eta_Q = 0.1$ as an initial optimization for our subjects for η provided
237 a median of 0.1. The weights *wv* and *wr* are set to a small random number from set [-0.0005 0.0005]
238 at trial = 1. The weights are normalized by dividing by their norm.
239
The cost function optimizes the frequency of selections of rare gain and rare loss options in
$\Delta_0$payoff and Δpayoff blocks for every subject after running the simulation agent for 10 instances
of 100,000 each, and inferring the optimal parameters for every participant in our study using
fmincon function in MATLAB. Cost function = sum of squares of the difference for observed
actual (Proportion# RareG$_{expt}$ + Proportion# RareL$_{expt}$ + Proportion# RareG$_{base}$ + Proportion#
RareL$_{base}$) – simulated actual (Proportion# RareG$_{expt}$ + Proportion# RareL$_{expt}$ + Proportion#
RareG$_{base}$ + Proportion# RareL$_{base}$). Optimization is carried out for either one (Models A,B) or two
(Model C) parameters, using *fmincon*(). We ran fmincon() 100 times to choose the parameter set
with least cost for any subject.
249
250 The AIC (Akaike Information Criteria) for these models were built using the likelihood function,
251 which was estimated as the average correlation coefficient between the simulated and the observed
252 key task behaviors - 1) payoff performance or *Perf* measure (eqn. 1); 2) gain frequency *Bias*
253 measure (eqn. 1); and 3) the block differences between Δpayoff and Δ0payoff blocks in Win-Stay
254 results for the RareG door.
255
256 **Neural data processing.** We applied a uniform processing pipeline to all EEG data acquired
257 simultaneous to the reward task. This included: 1) data pre-processing, 2) computing event related
258 spectral perturbations (ERSP) for all channels, and 3) cortical source localization of the EEG data
259 filtered within relevant theta, alpha and beta frequency bands.
260
1) Data preprocessing was conducted using the EEGLAB toolbox in MATLAB(Delorme &
Makeig, 2004). EEG data was resampled at 250 Hz, and filtered in the 1-45 Hz range to exclude
ultraslow DC drifts at <1Hz and high-frequency noise produced by muscle movements and
external electrical sources at >45Hz. EEG data were average referenced and epoched to the chosen
door presentation during the task, in the -.5 sec to +1.5 sec time window (**Figure 1**). Any missing
channel data (one channel each in 6 participants) was spherically interpolated to nearest neighbors.
Epoched data were cleaned using the autorej function in EEGLAB to remove noisy trials (>5sd
outliers rejected over max 8 iterations; 0.91± 2.65% of trials rejected per participant). EEG data

were further cleaned by excluding signals estimated to be originating from non-brain sources, such
as electrooculographic, electromyographic or unknown sources, using the Sparse Bayesian
learning (SBL) algorithm(Ojeda et al., 2018, 2021), https://github.com/aojeda/PEB) explained
below in the cortical source localization section.
273
2) For ERSP calculations, we performed time-frequency decomposition of the epoched data using
the continuous wavelet transform (cwt) function in MATLAB's signal processing toolbox.
Baseline time-frequency (TF) data in the -250 ms to -50 ms time window prior to chosen door
presentation were subtracted from the epoched trials (at each frequency) to observe the event-
related synchronization (ERS) and event-related desynchronization (ERD) modulations
(Pfurtscheller, 1999)..
280
3) Cortical source localization was performed to map the underlying neural source activations for
the ERSPs using the block-Sparse Bayesian learning (SBL) algorithm (Ojeda et al., 2018, 2021)
implemented in a recursive fashion. This is a two-step algorithm in which the first-step is
equivalent to low-resolution electromagnetic tomography (LORETA) (Pascual-Marqui et al.,
1994). LORETA estimates sources subject to smoothness constraints, i.e. nearby sources tend to
be co-activated, which may produce source estimates with a high number of false positives that
are not biologically plausible. To guard against this, SBL applies sparsity constraints in the
second step wherein blocks of irrelevant sources are pruned. This data-driven sparsity constraint
of the SBL method reduces the effective number of sources considered at any given time as a
solution, thereby reducing the ill-posed nature of the inverse mapping. In other words, one can
either increase the number of channels used to solve the ill-posed inverse problem or impose
more aggressive constraints on the solution to converge on the source model. The two-stage SBL
produces evidence-optimized inverse source models at 0.95AUC relative to the ground truth
while without the second stage <0.9AUC is obtained (Ojeda et al., 2018, 2021). Prior research
has also shown that sparse source imaging constraints can be soundly applied to low channel
density data (Ding & He, 2008; Stopczynski et al., 2014). Furthermore in Balasubramani et al.
(42) we have shown that the ROI estimates resulting from this cortical source mapping have high
test-retest reliability (Cronbach's alpha = 0.77, p<0.0001).
299
Source space activity signals were estimated and their root mean squares were partitioned into
(1) regions of interest (ROIs) based on the standard 68 brain region Desikan-Killiany atlas
(Desikan et al., 2006), using the Colin-27 head model (Holmes et al., 1998) and (2) artifact
sources contributing to EEG noise from non-brain sources such as electrooculographic,
electromyographic or unknown sources; activations from non-brain sources were removed to
clean the EEG data. Cleaned subject-wise trial-averaged EEG data were then specifically filtered
in theta (3-7 Hz), alpha (8-12 Hz), and beta (13-30 Hz) bands and separately source localized in
each of these bands to estimate their cortical ROI source signals. The source signal envelopes
were computed in MatLab (envelop function) by a spline interpolation over the local maxima
separated by at least one time sample; we used this *spectral amplitude* signal for all neural
analyses presented here. For analyses, we focused on theta, alpha and beta signals in the relevant
selected choice period (0-500 ms after selected choice presentation), trial reward period (500-
1000 ms after selected choice presentation), and the cumulative reward period (1000-1500 ms
after selected choice presentation).
314

Statistical Analyses. We fit robust multivariate linear regression models in MATLAB to
investigate the behavioral relationships between the *Perf* measure and demographic variables (age,
sex, race, ethnicity and SES), while controlling for *Bias* and order of block presentation. For any
linear regression model, the response variable was log-transformed for normality and we identified
significant factors contributing to the main effects. For regression models, we report the overall
model R^2 and p-value, and individual variable β coefficients, t-statistic, degrees of freedom, and
p-values.
322
Channel-wise theta, alpha, beta ERS and ERD modulations for significant spectral activity were
computed relative to baseline by first processing for any outliers; any activations greater than
5MAD from the median were removed from further analyses. The significant average activity
across all trials were found by performing t-tests ($p<0.05$) across subjects, followed by false
discovery rate (FDR, alpha = 0.05) corrections applied across the three dimensions of time,
frequency, and channels (Genovese et al., 2002).
329
For computing source level activity correlates of the behavioral *Perf* measure, we first found the
difference in RareG door specific neural activations between Δpayoff and $\Delta_0$payoff blocks in three
frequency bands – theta, alpha and beta and in three relevant trial periods: selected choice
presentation, trial reward and cumulative reward period. We again used robust linear regression
fits for identifying individual ROIs that relate to the *Perf* measure, while also accounting for
individual *Bias* and variations in RL as predicted by the best fitting RL model. The results were
family-wise error rate corrected for multiple comparisons for 3 trial periods and 3 frequency bands
(FWER correction, $p<0.0055$). The independently identified ROIs were further factored in a
unified multivariate linear regression model to account for comparisons across ROIs; significant
ROIs in this final multivariate model were reported after controlling for *Bias*, and the RL model-
fit parameter ($p<0.05$).
341
342 Finally, we used robust multivariate linear regressions to model the self-reported mood symptoms
343 of Anxiety, Depression, Inattention, Hyperactivity using predictors of demographic variables,
344 *Perf*, *Bias*, RL model-fit parameter along with the identified neural correlates of *Perf*. Adjusted
345 responses from robust multivariate models were plotted using the plotAdjustedResponse function
346 in MATLAB.
347
348

Results

Options associated with larger payoff show win-stay behavior and their choice fraction is proportional to individual gain frequency bias.

Healthy adult subjects (N = 186, ages 18-80 years, 115 females) performed a two-choice gambling task, *Lucky Door*, which implemented two distinct blocks of choices; the $\Delta_0$payoff block delivered choice-sets with different gain frequencies but no differences in payoff, while the Δpayoff block delivered choice-sets with same gain frequencies as the $\Delta_0$payoff block yet with long-term payoff (i.e. expected value) differences (**Figure 1A**; **Supplementary Table 1**). Specifically, the $\Delta_0$payoff block only varied the gain frequency associated with the choice doors, with one door leading to 70% positive reward outcomes (Rare Loss or RareL door) while the other resulting in 70% negative reward outcomes (Rare Gain or RareG door), yet maintaining the same reward average or long-term expected value/payoff. The Δpayoff block, presented in a random sequence order relative to the $\Delta_0$payoff block across subjects, had the same gain and loss frequency setup as the $\Delta_0$payoff block, but the rewards associated with the RareG door resulted in a larger long-term payoff than the RareL door. Participants executed 40 trials per block. Thus, we calculated the payoff related performance measure, *Perf* as the difference in probability of RareG selections on Δpayoff vs. $\Delta_0$payoff blocks. Gain frequency *Bias* was measured as the difference in proportion of RareL vs. RareG choices on the $\Delta_0$payoff block.

In terms of subject behavior, the actual proportion of RareG choices between the two blocks did not differ (paired Wilcoxon signed-rank test: N_{RareG} Δpayoff:17.74 ± 0.39; $\Delta_0$payoff:18.47 ± 0.40; p=0.07). But, we found that Win-Stay behavior for the RareG choices distinguished performance on the two blocks (mean$\pm$SEM Win-Stay RareG, Δpayoff:0.61 ± 0.02;

372 $\Delta_0$payoff:0.55±0.02; block difference: 0.06± 0.03, p=0.02, **Figure 1B**). Corresponding lose-shift

373 behavior did not differ between blocks (p=0.33).

374  Additionally, we found that the payoff-based responses, *Perf* were significantly correlated

375 to individual gain frequency *Bias* (r=0.65, p<0.0001, **Figure 1C**).

376  Next, we implemented multivariate regression to model the payoff-related performance,

377 *Perf*, based on all self-reported demographic (age, gender, race, ethnicity, socio-economic status

378 SES) and mental health (anxiety, depression, inattention and hyperactivity) predictors as per **Table**

379 **1**. This model also included individual gain frequency *Bias* and order of block presentation. The

380 overall *Perf* model was significant (R^2=0.43, p<0.0001). Interestingly the only variable that

381 significantly predicted *Perf* was Gain frequency *Bias* (β=0.37 ±0.04, t(151)=9.18, p<0.0001).

382 Thus, hereafter, we control for *Bias* in all payoff-relevant analyses below.

384
385 **Figure 1. Reward task and associated behavior A)** As per the task schematic, participants
386 fixated for 0.5 sec, then chose from one of two choice doors. Post-response, fixation reappeared
387 for 0.5 sec, followed by presentation of the chosen door for 0.5 sec, then immediate gain or loss
388 feedback provided for 0.5 sec, and finally, cumulative feedback of all gains/losses up to the
389 present trial shown for 0.5 sec. Reward distributions for the door choices are presented in
390 Supplementary Table 1. **B)** Win-Stay behavior for the rare gain RareG door is significantly
391 greater on the ΔPayoff versus Δ_0Payoff block. *:p<.05. **C)** Gain frequency *Bias* significantly
392 predicts payoff performance, *Perf* (r=0.65, p<0.0001).
393

Demographics	Median ± MAD
Age	25.00 ± 14.87
Gender n (%)	
Male	71 (38.17)
Female	115 (61.83)
Ethnicity n (%)	
Caucasian	116 (62.37)
Black or African American	4 (2.15)
Native Hawaiian, Pacific Islander	0 (0)
Asian	37 (19.89)
American Indian, Alaska Native	4 (2.15)
Multi-racial	12 (6.45)
Others	12 (6.45)
Race n (%)	
Hispanic or Latino	25 (13.51)
Not Hispanic or Latino	155 (83.78)
Unknown	5 (2.70)
SES	5.00 ± 1.34
Mental Health	**Median ± MAD**
Anxiety	3 ± 2.88
Depression	3 ± 2.76
Inattention	4 ± 3.99
Hyperactivity	3 ± 2.96
Behavior	**Median ± MAD**
Perf	-0.02±0.13
Bias	0.10±0.21
Model γ	0.99± 0.07

Table 1. Subject characteristics. Median ± MAD for subjects demographics variables, mental health self-report scores, and parameter γ from the preferred reinforcement learning model. MAD: median absolute deviation, SES: socioeconomic status score.

Individual differences in reward prediction explain task behavior.

Prior RL modeling studies have suggested that task behavior can be explained with greater accuracy when both the long term expected value or payoff and the expected risk are accounted for during decision-making (Balasubramani, Chakravarthy, Ravindran, et al., 2015; Balasubramani et al., 2014). The major advantages of building these RL models are that the models can characterize the individual differences in each participant in terms of computational

parameters that manifest in learning and executive control. Secondly, they can explain the

converged behavioral dynamics in each participant sans experimental trial limitations.

Using this RL framework, we were interested in investigating how are choice decisions

affected by 1) extent of integration of rewards over time i.e. time scale of reward prediction, and

2) differential risk sensitivity to gains and losses affecting the choices, where risk is the variance

in reward outcomes. In order to find whether the observed subjective behavioral differences are

driven by one of the two or both of the above decision making measures, we built three separate

reinforcement learning models (RL, **Figure 2A**) that simulate behavior by optimizing time scale

of reward prediction (γ: model A), risk sensitivity (α: model B) or both γ and α parameters (model

C). In model A, higher γ parameter values represent long-sightedness; risk sensitivity α is set to 0

in this model. In model B, higher α parameter values indicate risk aversiveness and lower values

indicate risk seeking; the reward prediction γ parameter is set to 0 in this model. All models were

optimized using robust solvers in MATLAB (see Methods to find global minima with multiple

random initial conditions) to match to the observed choice selection behavior observed in each

block.

Next, we computed the likelihood of any Model A, B, C to explain the significantly

observed behavioral measures: which are *Perf, Bias* and the block differences in proportion of

Win-Stay to the RareG door. The likelihood, taken as correlations between the simulated and

actually observed, was used to construct model AIC (Akaike Information Criterion). The AIC

values for Models A, B and C were 2.94, 3.70 and 5.45, respectively (**Figure 2B**), suggesting that

Model A can preferably explain the observed behavior (**Figure 2C**). This means the individual

differences in the time scale of reward prediction can preferably explain the reward maximization

(*Perf*) as well as melioration (*Bias*) behavior. On parameter recovery analysis for this model, the

simulated model solutions were significantly correlated with the recovered solutions, implying that

our model can reliably explain the subjective behaviors (Wilson & Collins, 2019).

432
433
Figure 2. Reinforcement Learning Model (A) Schematic representing the stimulus, value
function and choice selection modules. The model results for number of selections associated with
each of the choice door stimuli in each task block are compared against the actual selections made
by each subject, for purposes of model optimization. The model uses the utility, U, associated with
each choice response for making the decision, where the utility is a function of reward average and
reward variance associated with choices. The decision in the model is taken using the SoftMax
probability, P, of making the choices. Model parameters are highlighted as α (model agent's
differential risk sensitivity to gain and loss outcome uncertainties), and γ (time scale of reward
prediction). **(B)** AIC values for three models, Model A (γ optimized), B (α optimized), C (γ and α
optimized), show that the γ model was best performing. **(C)** The γ optimized model showed strong
correlations between simulated and actual *Perf* ($\rho(185)=0.81$, $p<0.0001$), *Bias* ($\rho(185)=0.89$,
$p<0.0001$) and RareG Win-Stay difference between blocks ($\rho(185)=0.17$ $p=0.004$).
446

Right rostral anterior cingulate cortex encodes reward payoff maximization.

Participants performed the reward task with simultaneous EEG, which we analyzed in the theta (3-7 Hz), alpha (8-12 Hz), and beta (13-30 Hz) frequency bands in cortical source space parcellated as per the Desikan-Killiany regions of interest (Desikan et al., 2006). To identify the neural correlates underlying reward payoff maximization (*Perf*), we modeled the neural variables as predictors of *Perf* using robust multivariate linear regression, while accounting for gain frequency *Bias* that was significantly related to *Perf* (**Figure 1**), and the optimal RL model parameter (γ).

We investigated neural activations from three relevant trial periods: immediately post-presentation of selected choice but prior to reward (0-500 ms selected choice period), during presentation of trial reward (0-500 ms reward period), and during presentation of the cumulative reward up to that trial in the trial sequence (0-500 ms cumulative reward period). *Perf* neural activations were the relative difference in activity on Δpayoff vs. $\Delta_0$payoff block RareG trials. Taking the relative block difference allowed non-task related individual EEG differences to cancel out. Relative responses to the RareG door were important for analysis because this door choice resulted in a larger long-term payoff than the other (RareL) door in the Δpayoff block. We applied family-wise error-rate (fwer) corrections to the *Perf* source-space neural correlates to account for multiple comparisons across three frequency bands (theta, alpha, beta) and three time periods (choice, reward, cumulative reward). **Figure 3A** shows the *Perf* source-space neural correlates found to be significant in this analysis; all neural activations inversely related to *Perf*.

We further accounted for the multiple independently significant cortical ROI predictors (Figure 3A) within a unified multivariate model for *Perf* that also included the significant *Bias* and RL model parameter γ as covariates. This overall multivariate model for *Perf* was significant

(R^2=0.69, df=126, p<0.0001). The results of this model showed alpha activity in the bilateral

rostral anterior cingulate cortex (rACC) during the reward period (left: β=-394.32 $\pm$ 125.56,

t(177)=-3.14, p=0.002; right: β=-634.89 $\pm$ 220.51, t(176)=-2.88, p=0.004) and theta activity in the

right rACC during the cumulative reward period (β=-56.98 $\pm$ 17.93, t(177)=-3.17, p=0.002) as the

most significant predictors of payoff-based decisions; activity in the selected choice presentation

period did not survive the multivariate model. We then investigated whether these specific

theta/alpha rACC activations also related to gain frequency *Bias*, while controlling for the *Perf*

payoff. The bilateral alpha band rACC activations were significantly related to *Bias* (left: β=-

514.67$\pm$205.05, t(178)=-2.51, p=0.01; right: β=-886.15$\pm$348.74, t(179)=-2.54, p=0.01) but not

right rACC theta (p>0.05). Thus, right rACC theta activity during the cumulative reward period

was the distinct neural correlate of reward payoff **(Figure 3B)**; corresponding scalp theta activity

and topography are shown in **Figure 3C**.

Additionally, we checked whether the distinct Perf correlate of right rACC theta activation

during the cumulative reward period showed any interactions with age and gender, but no

significant interactions were found (p>0.1).

Distinct neural correlates of reward maximization in right rACC predict depressed mood.

Finally, we investigated whether the neural correlates of payoff decisions are relevant to

subjective mental health by modeling anxiety, depression, inattention and hyperactivity self-

reported mood symptoms scores as dependent variables in robust multivariate regression models.

All demographic variables (age, gender, race, ethnicity, SES), task performance variables of *Perf*

and *Bias*, the relevant RL model parameter γ, as well as the reward-processing neural correlates

(bilateral rostral ACC alpha; right rostral ACC theta) were included in each model as independent

predictors. Models were fwer-corrected for multiple comparisons.

Only the models for anxiety (R^2=0.24, p=0.0002) and depression (R^2=0.21, p=0.002) were

significant after multiple comparisons correction. Amongst demographics, age negatively

predicted both anxiety (β=-0.02±0.004, t(152)=-4.95, p<0.0001) and depression (β=-0.01±0.004,

t(152)=-3.42, p=0.0007); no other demographics, RL model parameter γ, Perf or Bias were

significant in these models. Notably, neural correlates of payoff performance, specifically right

rACC theta during the cumulative reward period positively predicted depressed mood

(β=301.41±150.34, t(152)=2.00, p=0.046, **Figure 3D**); payoff neural correlates did not predict

anxiety.

503
Figure 3: Neural correlates of payoff-based decision making in humans. (A) Independent
neural correlates in theta (blue), alpha (brown), and beta (cyan) bands found to be inversely
related to *Perf* in the choice selection, reward and cumulative reward epochs (p<0.0055). **(B)**
Only right rostral anterior cingulate cortex (rACC) theta activity in the cumulative reward period
uniquely relates to *Perf* after controlling for *Bias* and time scale of reward prediction. **(C)**
Corresponding theta band temporal activity on RareG trials at mid-frontal scalp channel AFz
showing differences between payoff blocks (top), and scalp topography of RareG theta band trial
difference across Δpayoff and $\Delta_0$payoff blocks in the significant cumulative reward period
(bottom). **(D)** *Perf* related rACC theta positively predicts depressed mood symptoms. The scatter
plots in (B) and (D) are presented on an adjusted axis as obtained from the multivariate robust
regression models; the x-axes for these plots are 10^{-3} source activity units.

Discussion

Reinforcement learning models suggest healthy human choices ideally tend to maximize

long-term beneficial outcomes (Balasubramani, Chakravarthy, Ali, et al., 2015a; Balasubramani

et al., 2014; Balasubramani, Moreno-Bote, et al., 2018; Balasubramani & Chakravarthy, 2019; A.

Gupta et al., 2013). However, many existing neuropsychological measures of decision-making that

optimize for long-term payoffs don't reliably estimate the participant's ability to integrate rewards

and make foresighted decisions, and instead suffer from biased predispositions (Furl, 2010;

Gansler et al., 2011; Napoli & Fum, 2010; Stocco et al., 2009); this tendency to choose lesser local

minima based gain over long-term gain is also referred to as melioration (Sims et al., 2013). In our

paradigm, we study gain frequency driven bias separate from payoff-based decision-making by

introducing a $\Delta_0$payoff block with no payoff difference between choice options wherein decisions

are purely based on gain frequency (Lin et al., 2009). Comparing choices within the Δpayoff

experimental block, designed to have similar reward distribution structure as the $\Delta_0$payoff block

but differing only on the long-term outcome between options, allows measurement of long-term

payoff maximization strategy. Therefore, our study design is able to distinguish reward

maximization from melioration and further leverages these measures to inform mental health

behaviors.

The behavioral outcomes of our experiment varied based on individual subject

characteristics. We found that payoff-based performance was significantly related to individual

bias for observed frequency of gains; this is in line with prior studies of decision-making but

wherein gain frequency decisions are often conflated with expected value (Bechara et al., 1997;

Lin et al., 2009). We further modeled subjective differences in reinforcement learning based

decision making and by using RL modeling framework, we extracted subjective sensitivity to risks

(α) and time scale of reward prediction (γ) to explain each subject's behavior. The parsimonious

RL models suggested that the observed behavior is preferably explained by the differences in the

extent of reward prediction over time (γ) between individuals.

Uniquely, we then investigated the neural correlates of payoff performance while

accounting for individual differences in gain frequency bias and extent of reward prediction.

Earlier studies have suggested complex dynamics mediated by dopamine and serotonin

neuromodulation in the cortico-basal ganglia circuit to underlie reward and risk based decision

making (Balasubramani, Chakravarthy, Ali, et al., 2015b; Balasubramani, Chakravarthy, et al.,

2018; Balasubramani et al., 2014; Chakravarthy et al., 2018; Doya, 2002; Schultz, 2000; Sutton &

Barto, 1998; Tobler et al., 2009). In our study, we focused on three different time periods of the

task, the first associated with processing of the selected choice, the ensuing reward presentation

period and the cumulative reward period to understand how neural dynamics in these periods affect

payoff-based performance. The selected choice period captures the processing associated with

presentation of the chosen door after the actual decision period. We did not analyze the actual

decision period since two different choice options are shown on the screen during this time and

the signal associated with every choice option was difficult to explicitly assess. These analyses

showed distinct neural correlates of payoff based performance in the core frontal executive region

of the right rACC during the cumulative reward period. Relatedly, most prior studies on

probabilistic reward processing have suggested this medial prefrontal cortex (mPFC) region to be

critical for mediating decision performance (Balasubramani & Hayden, 2018; Bechara et al., 1997,

2000; Brevers et al., 2013; Kennerley et al., 2011; Moccia et al., 2017).

More specifically, analyses showed theta activity in right rACC negatively associated with

payoff-based performance. This finding is aligned with prior evidence for reward-based theta

processing and its widely studied relationship to long-term risk or uncertainty (Cavanagh et al.,

2010; Christie & Tata, 2009; Zavala et al., 2018). This may be one reason why we observe a

negative relationship between cumulative reward period rACC theta and effective payoff, *Perf*,

because long-term payoff magnitude has been shown to inversely relate to uncertainty but

positively to choice utility (Behrens et al., 2007; Krain et al., 2006; Paulus & Frank, 2006;

Preuschoff et al., 2006). Notably, reward period bilateral rACC alpha also related to payoff

maximization, but this was not a distinct correlate of payoff as it also significantly explained gain

frequency bias or melioration in our task.

Translational neuroscience studies show that reward based decision processing deficits are

found in depression and in attention disorders, leading to difficulty in reward integration and

foresighted choice-behaviors (Balasubramani, Chakravarthy, Ali, et al., 2015b; Balasubramani &

Chakravarthy, 2019; Gradin et al., 2011; Groen et al., 2013; Miller & Seligman, 1973; Silvetti et

al., 2013; Ziegler et al., 2016). Such individuals then focus on the immediate reward outcome in

the short-term, characterized by a prolonged attenuation of temporal discounting of rewards (Eshel

& Roiser, 2010; Pizzagalli et al., 2005). Interestingly, rACC theta activity in our paradigm during

the cumulative reward period, which negatively correlated with payoff performance, was a positive

predictor of depressed mood. This result is aligned with prior research using fMRI showing that

the volume and activation patterns of rACC correlates with depressed mood (Boes et al., 2008;

Yoshimura et al., 2010). Related research also suggests that rACC theta activity is a significant

baseline marker for depression treatment outcomes (Pizzagalli et al., 2018). These results are still

limited by our study in healthy adults and need to be replicated in clinical populations, and with

greater channel density electrophysiology recordings.

Altogether, our study presents the importance of controlling for melioration biases for

immediate reward frequency and individual differences in learning while assessing advantageous,

i.e. foresighted, decision-making ability in humans. Our findings of payoff-relevant right rostral

ACC theta activity in the cumulative reward feedback period, could be important for clinical

translational application, particularly for depression, suggesting a plausible neural target for

interventions that engage reward processing.

Supplementary Data

	Δpayoff		$\Delta_0$payoff	
	RareL	RareG	RareL	RareG
1	20	-20	30	-30
2	20	-20	30	-30
3	20	-20	30	-30
4	20	-20	30	-30
5	20	-20	30	-30
6	20	-20	30	-30
7	20	-20	30	-30
8	-60	60	-70	70
9	-60	60	-70	70
10	-60	60	-70	70
sum	-40	40	0	0
average	-4	4	0	0
variance	1493.33	1493.33	2333.33	2333.33

Supplementary Table 1. **Reward distributions for the door choices in the Δpayoff and**
$\Delta_0$payoff blocks. The two door choices in either block were RareG (rare gains and frequent losses)
and RareL (rare losses and frequent gains). Payoff (expected value) for RareG and RareL were the
same in the $\Delta_0$payoff block and greater for RareG relative to RareL in the Δpayoff block. RareG
and RareL distributions had the same sum, average and variance in the $\Delta_0$payoff block, and
different sum and averages but same variance in the Δpayoff block.

Acknowledgements

This work was supported by University of California San Diego (UCSD) lab start-up funds (DR, JM), the Interdisciplinary Research Fellowship in NeuroAIDS (PB: R25MH081482), the Brain & Behavior Research Fund (PB), the Kavli Foundation (PB, JM), and the Sanford Institute for Empathy and Compassion (JM, PB). We thank Alankar Misra for software development of the *BrainE* software and several UCSD undergraduate students who assisted with data collection. The *BrainE* software is copyrighted for commercial use (Regents of the University of California Copyright #SD2018-816) and free for research and educational purposes. We thank Sabyasachi Shivkumar and Vignesh Muralidharan for their helpful feedback on the study analysis.

Data Availability

A part of the dataset with 96 of the 186 participants data used in this study is available on the open-access repository link: 10.5281/zenodo.4088951

References

Admon, R., & Pizzagalli, D. A. (2015). Dysfunctional reward processing in depression. *Current Opinion in Psychology*, *4*, 114–118. https://doi.org/10.1016/j.copsyc.2014.12.011

Arevalo-Rodriguez, I., Smailagic, N., i Figuls, M. R., Ciapponi, A., Sanchez-Perez, E., Giannakou, A., Pedraza, O. L., Cosp, X. B., & Cullum, S. (2015). Mini-Mental State Examination (MMSE) for the detection of Alzheimer's disease and other dementias in people with mild cognitive impairment (MCI). *Cochrane Database of Systematic Reviews*, *3*.

Aron, A. R., Durston, S., Eagle, D. M., Logan, G. D., Stinear, C. M., & Stuphorn, V. (2007). Converging Evidence for a Fronto-Basal-Ganglia Network for Inhibitory Control of Action and Cognition. *Journal of Neuroscience*, *27*(44), 11860–11864. https://doi.org/10.1523/JNEUROSCI.3644-07.2007

Balasubramani, P. P., Chakravarthy, S., Ravindran, B., & Moustafa, A. A. (2014). An extended reinforcement learning model of basal ganglia to understand the contributions of serotonin and dopamine in risk-based decision making, reward prediction, and punishment learning. *Frontiers in Computational Neuroscience*, *8*, 47.

Balasubramani, P. P., Chakravarthy, S., Ravindran, B., & Moustafa, A. A. (2015). A network model of basal ganglia for understanding the roles of dopamine and serotonin in reward-punishment-risk based decision making. *Name: Frontiers in Computational Neuroscience*, *9*, 76.

Balasubramani, P. P., & Chakravarthy, V. S. (2019). Bipolar oscillations between positive and negative mood states in a computational model of Basal Ganglia. *Cognitive Neurodynamics*. https://doi.org/10.1007/s11571-019-09564-7

Balasubramani, P. P., Chakravarthy, V. S., Ali, M., Ravindran, B., & Moustafa, A. A. (2015a).

Identifying the Basal Ganglia Network Model Markers for Medication-Induced

Impulsivity in Parkinson's Disease Patients. *PLoS One*, *10*(6), e0127542.

Balasubramani, P. P., Chakravarthy, V. S., Ali, M., Ravindran, B., & Moustafa, A. A. (2015b).

Identifying the Basal Ganglia Network Model Markers for Medication-Induced

Impulsivity in Parkinson's Disease Patients. *PLoS ONE*, *10*(6).

https://doi.org/10.1371/journal.pone.0127542

Balasubramani, P. P., Chakravarthy, V. S., Ravindran, B., & Moustafa, A. A. (2018). Modeling

Serotonin's Contributions to Basal Ganglia Dynamics. In *Computational Neuroscience*

Models of the Basal Ganglia (pp. 215–243). Springer.

Balasubramani, P. P., & Hayden, B. (2018). Overlapping neural processes for stopping and

economic choice in orbitofrontal cortex. *BioRxiv*, 304709.

Balasubramani, P. P., Moreno-Bote, R., & Hayden, B. Y. (2018). Using a Simple Neural

Network to Delineate Some Principles of Distributed Economic Choice. *Frontiers in*

Computational Neuroscience, *12*, 22.

Balasubramani, P. P., Ojeda, A., Grennan, G., Maric, V., Le, H., Alim, F., Zafar-Khan, M., Diaz-

Delgado, J., Silveira, S., & Ramanathan, D. (2020). Mapping Cognitive Brain Functions

at Scale. *NeuroImage*, 117641.

Bechara, A., Damasio, H., Tranel, D., & Damasio, A. R. (1997). Deciding advantageously before

knowing the advantageous strategy. *Science*, *275*(5304), 1293–1295.

Bechara, A., Tranel, D., & Damasio, H. (2000). Characterization of the decision-making deficit

of patients with ventromedial prefrontal cortex lesions. *Brain*, *123*(11), 2189–2202.

https://doi.org/10.1093/brain/123.11.2189

Behrens, T. E. J., Woolrich, M. W., Walton, M. E., & Rushworth, M. F. S. (2007). Learning the

value of information in an uncertain world. *Nature Neuroscience*, *10*(9), 1214–1221.

https://doi.org/10.1038/nn1954

Bell, D. E. (1995). Risk, return, and utility. *Management Science*, *41*(1), 23–30.

Bembich, S., Clarici, A., Vecchiet, C., Baldassi, G., Cont, G., & Demarini, S. (2014).

Differences in time course activation of dorsolateral prefrontal cortex associated with low

or high risk choices in a gambling task. *Frontiers in Human Neuroscience*, *8*, 464.

Boes, A. D., McCormick, L. M., Coryell, W. H., & Nopoulos, P. (2008). Rostral Anterior

Cingulate Cortex Volume Correlates with Depressed Mood in Normal Healthy Children.

Biological Psychiatry, *63*(4), 391–397. https://doi.org/10.1016/j.biopsych.2007.07.018

Brevers, D., Bechara, A., Cleeremans, A., & Noel, X. (2013). Iowa Gambling Task (IGT):

Twenty years after – gambling disorder and IGT. *Frontiers in Psychology*, *4*.

https://doi.org/10.3389/fpsyg.2013.00665

Cavanagh, J. F., Frank, M. J., Klein, T. J., & Allen, J. J. (2010). Frontal theta links prediction

errors to behavioral adaptation in reinforcement learning. *Neuroimage*, *49*(4), 3198–

3209.

Chakravarthy, V. S., Balasubramani, P. P., Mandali, A., Jahanshahi, M., & Moustafa, A. A.

(2018). The many facets of dopamine: Toward an integrative theory of the role of

dopamine in managing the body's energy resources. *Physiology & Behavior*.

Chiu, Y.-C., & Lin, C.-H. (2007). Is deck C an advantageous deck in the Iowa Gambling Task?

Behavioral and Brain Functions, *3*(1), 37.

Chiu, Y.-C., Lin, C.-H., Huang, J.-T., Lin, S., Lee, P.-L., & Hsieh, J.-C. (2008). Immediate gain

is long-term loss: Are there foresighted decision makers in the Iowa Gambling Task?

Behavioral and Brain Functions, *4*(1), 13.

Christakou, A., Brammer, M., Giampietro, V., & Rubia, K. (2009). Right ventromedial and

dorsolateral prefrontal cortices mediate adaptive decisions under ambiguity by integrating

choice utility and outcome evaluation. *Journal of Neuroscience*, *29*(35), 11020–11028.

Christie, G. J., & Tata, M. S. (2009). Right frontal cortex generates reward-related theta-band

oscillatory activity. *Neuroimage*, *48*(2), 415–422.

d'Acremont, M., Lu, Z.-L., Li, X., Van der Linden, M., & Bechara, A. (2009). Neural correlates

of risk prediction error during reinforcement learning in humans. *Neuroimage*, *47*(4),

1929–1939.

Delorme, A., & Makeig, S. (2004). EEGLAB: An open source toolbox for analysis of single-trial

EEG dynamics including independent component analysis. *Journal of Neuroscience*

Methods, *134*(1), 9–21. https://doi.org/10.1016/j.jneumeth.2003.10.009

Denison, R. N., Adler, W. T., Carrasco, M., & Ma, W. J. (2018). Humans incorporate attention-

dependent uncertainty into perceptual decisions and confidence. *Proceedings of the*

National Academy of Sciences, *115*(43), 11090–11095.

https://doi.org/10.1073/pnas.1717720115

Desikan, R. S., Ségonne, F., Fischl, B., Quinn, B. T., Dickerson, B. C., Blacker, D., Buckner, R.

L., Dale, A. M., Maguire, R. P., Hyman, B. T., Albert, M. S., & Killiany, R. J. (2006). An

automated labeling system for subdividing the human cerebral cortex on MRI scans into

gyral based regions of interest. *NeuroImage*, *31*(3), 968–980.

https://doi.org/10.1016/j.neuroimage.2006.01.021

Dillon, D. G., Rosso, I. M., Pechtel, P., Killgore, W. D., Rauch, S. L., & Pizzagalli, D. A. (2014).

711   Peril and pleasure: An RDOC-inspired examination of threat responses and reward

712   processing in anxiety and depression. *Depression and Anxiety*, *31*(3), 233–249.

713   Ding, L., & He, B. (2008). Sparse source imaging in electroencephalography with accurate field

714   modeling. *Human Brain Mapping*, *29*(9), 1053–1067.

715   Doya, K. (2002). Metalearning and neuromodulation. *Neural Networks*, *15*(4–6), 495–506.

716   Eshel, N., & Roiser, J. P. (2010). Reward and punishment processing in depression. *Biological*

717   *Psychiatry*, *68*(2), 118–124.

718   Franken, I. H., & Muris, P. (2005). Individual differences in decision-making. *Personality and*

719   *Individual Differences*, *39*(5), 991–998.

720   Furl, B. A. (2010). *The influence of individual differences on the Iowa Gambling Task and real-*

721   *world decision making* [PhD Thesis]. Wake Forest University.

722   Gansler, D. A., Jerram, M. W., Vannorsdall, T. D., & Schretlen, D. J. (2011). Comparing

723   alternative metrics to assess performance on the Iowa Gambling Task. *Journal of Clinical*

724   *and Experimental Neuropsychology*, *33*(9), 1040–1048.

725   https://doi.org/10.1080/13803395.2011.596820

726   Garon, N., Moore, C., & Waschbusch, D. A. (2006). Decision Making in Children With ADHD

727   Only, ADHD-Anxious/Depressed, and Control Children Using a Child Version of the

728   Iowa Gambling Task. *Journal of Attention Disorders*, *9*(4), 607–619.

729   https://doi.org/10.1177/1087054705284501

730   Genovese, C. R., Lazar, N. A., & Nichols, T. (2002). Thresholding of Statistical Maps in

731   Functional Neuroimaging Using the False Discovery Rate. *NeuroImage*, *15*(4), 870–878.

732   https://doi.org/10.1006/nimg.2001.1037

Gradin, V. B., Kumar, P., Waiter, G., Ahearn, T., Stickle, C., Milders, M., Reid, I., Hall, J., &

Steele, J. D. (2011). Expected value and prediction error abnormalities in depression and

schizophrenia. *Brain*, *134*(6), 1751–1764. https://doi.org/10.1093/brain/awr059

Groen, Y., Gaastra, G. F., Lewis-Evans, B., & Tucha, O. (2013). Risky behavior in gambling

tasks in individuals with ADHD–a systematic literature review. *PLoS One*, *8*(9), e74909.

Gupta, A., Balasubramani, P. P., & Chakravarthy, S. (2013). Computational model of precision

grip in Parkinson's disease: A Utility based approach. *Frontiers in Computational*

Neuroscience, *7*. https://doi.org/10.3389/fncom.2013.00172

Gupta, R., Koscik, T. R., Bechara, A., & Tranel, D. (2011). The amygdala and decision-making.

Neuropsychologia, *49*(4), 760–766.

Hampshire, A., Chamberlain, S. R., Monti, M. M., Duncan, J., & Owen, A. M. (2010). The role

of the right inferior frontal gyrus: Inhibition and attentional control. *NeuroImage*, *50*(3).

https://ora.ox.ac.uk/objects/uuid:df04571a-0bb2-4088-bc43-2249062b5db0

Harman, J. L. (2011). Individual differences in need for cognition and decision making in the

Iowa Gambling Task. *Personality and Individual Differences*, *51*(2), 112–116.

Holmes, C. J., Hoge, R., Collins, L., Woods, R., Toga, A. W., & Evans, A. C. (1998).

Enhancement of MR Images Using Registration for Signal Averaging. *Journal of*

Computer Assisted Tomography, *22*(2), 324–333.

Kennerley, S. W., Behrens, T. E., & Wallis, J. D. (2011). Double dissociation of value

computations in orbitofrontal and anterior cingulate neurons. *Nature Neuroscience*,

14(12), 1581.

Kothe, C., Medine, D., Boulay, C., Grivich, M., & Stenner, T. (2019). *"Lab Streaming Layer"*

Copyright. https://labstreaminglayer.readthedocs.io/

Krain, A. L., Wilson, A. M., Arbuckle, R., Castellanos, F. X., & Milham, M. P. (2006). Distinct

neural mechanisms of risk and ambiguity: A meta-analysis of decision-making.

NeuroImage, *32*(1), 477–484. https://doi.org/10.1016/j.neuroimage.2006.02.047

Kroenke, K., Spitzer, R. L., & Williams, J. B. W. (2001). The PHQ-9: Validity of a Brief

Depression Severity Measure. *Journal of General Internal Medicine*, *16*, 606–613.

Lin, C., Chiu, Y., & Huang, J. (2009). Gain-loss frequency and final outcome in the Soochow

Gambling Task: A Reassessment. *Behavioral and Brain Functions*, *5*, 1–9.

https://doi.org/10.1186/1744-9081-5-45

Luman, M., Tripp, G., & Scheres, A. (2010). Identifying the neurobiology of altered

reinforcement sensitivity in ADHD: A review and research agenda. *Neuroscience &*

Biobehavioral Reviews, *34*(5), 744–754. https://doi.org/10.1016/j.neubiorev.2009.11.021

Miller, W. R., & Seligman, M. E. (1973). Depression and the perception of reinforcement.

Journal of Abnormal Psychology, *82*(1), 62–73. https://doi.org/10.1037/h0034954

Moccia, L., Pettorruso, M., Crescenzo, F. D., Risio, L. D., Martinotti, G., Bifone, A., Janiri, L.,

& Di, M. (2017). Neural correlates of cognitive control in gambling disorder: A

systematic review of fMRI studies. *Neuroscience and Biobehavioral Reviews*, *78*, 104–

116. https://doi.org/10.1016/j.neubiorev.2017.04.025

Mueller, E. M., Nguyen, J., Ray, W. J., & Borkovec, T. D. (2010). Future-oriented decision-

making in Generalized Anxiety Disorder is evident across different versions of the Iowa

Gambling Task. *Journal of Behavior Therapy and Experimental Psychiatry*, *41*(2), 165–

171.

Muralidharan, V., Balasubramani, P. P., Chakravarthy, V. S., Lewis, S. J., & Moustafa, A. A.

(2014). A computational model of altered gait patterns in parkinson's disease patients

negotiating narrow doorways. *Frontiers in Computational Neuroscience*, *7*, 190.

https://doi.org/10.3389/fncom.2013.00190

Muralidharan, V., Yu, X., Cohen, M. X., & Aron, A. R. (2019). Preparing to stop action

increases beta band power in contralateral sensorimotor cortex. *Journal of Cognitive*

Neuroscience, *31*(5), 657–668.

Must, A., Horvath, S., Nemeth, V. L., & Janka, Z. (2013). The Iowa GamblingTask in depression

– what have we learned about sub-optimal decision-making strategies? *Frontiers in*

Psychology, *4*, 1–6. https://doi.org/10.3389/fpsyg.2013.00732

Napoli, A., & Fum, D. (2010). Rewards and punishments in iterated decision making: An

explanation for the frequency of the contingent event effect. *10th International*

Conference on Cognitive Modeling. Philadelphia, PA.

Newman, L. I., Polk, T. A., & Preston, S. D. (2008). *Revealing individual differences in the Iowa*

Gambling Task. 1067–1072.

Oberg, S. A., Christie, G. J., & Tata, M. S. (2011). Problem gamblers exhibit reward

hypersensitivity in medial frontal cortex during gambling. *Neuropsychologia*, *49*(13),

3768–3775.

Ojeda, A., Kreutz-Delgado, K., & Mishra, J. (2021). Bridging M/EEG Source Imaging and

Independent Component Analysis Frameworks Using Biologically Inspired Sparsity

Priors. *Neural Computation*, *33*, 1–31. https://doi.org/10.1162/NECO_A_01415

Ojeda, A., Kreutz-Delgado, K., & Mullen, T. (2018). Fast and robust Block-Sparse Bayesian

learning for EEG source imaging. *Neuroimage*, *174*, 449–462.

Pascual-Marqui, R. D., Michel, C. M., & Lehmann, D. (1994). Low resolution electromagnetic

tomography: A new method for localizing electrical activity in the brain. *International*

Journal of Psychophysiology, *18*(1), 49–65. https://doi.org/10.1016/0167-

8760(84)90014-X

Paulus, M. P., & Frank, L. R. (2006). Anterior cingulate activity modulates nonlinear decision

weight function of uncertain prospects. *Neuroimage*, *30*(2), 668–677.

Pfurtscheller, G. (1999). EEG event—Related desynchronization (ERD) and event—Releated

synchronization (ERS). *Electroencephalography: Basic Principles, Clinical Applications*

and Related Fields, 958–967.

Picazio, S., Veniero, D., Ponzo, V., Caltagirone, C., Gross, J., Thut, G., & Koch, G. (2014).

Prefrontal Control over Motor Cortex Cycles at Beta Frequency during Movement

Inhibition. *Current Biology*, *24*(24), 2940–2945.

https://doi.org/10.1016/j.cub.2014.10.043

Pizzagalli, D. A., Sherwood, R. J., Henriques, J. B., & Davidson, R. J. (2005). Frontal brain

asymmetry and reward responsiveness: A source-localization study. *Psychological*

Science, *16*(10), 805–813.

Pizzagalli, D. A., Webb, C. A., Dillon, D. G., Tenke, C. E., Kayser, J., Goer, F., Fava, M.,

McGrath, P., Weissman, M., Parsey, R., Adams, P., Trombello, J., Cooper, C., Deldin, P.,

Oquendo, M. A., McInnis, M. G., Carmody, T., Bruder, G., & Trivedi, M. H. (2018).

Pretreatment Rostral Anterior Cingulate Cortex Theta Activity in Relation to Symptom

Improvement in Depression: A Randomized Clinical Trial. *JAMA Psychiatry*, *75*(6),

547–554. https://doi.org/10.1001/jamapsychiatry.2018.0252

Preuschoff, K., Bossaerts, P., & Quartz, S. R. (2006). Neural differentiation of expected reward

and risk in human subcortical structures. *Neuron*, *51*(3), 381–390.

https://doi.org/10.1016/j.neuron.2006.06.024

Roca, M., Torralva, T., López, P., Cetkovich, M., Clark, L., & Manes, F. (2008). Executive

Functions in Pathologic Gamblers Selected in an Ecologic Setting. *Cognitive and*

Behavioral Neurology, *21*(1), 1–4. https://doi.org/10.1097/WNN.0b013e3181684358

Roelfsema, P. R., & Ooyen, A. van. (2005). Attention-gated reinforcement learning of internal

representations for classification. *Neural Computation*, *17*(10), 2176–2214.

Schultz, W. (2000). Multiple reward signals in the brain. *Nature Reviews. Neuroscience*, *1*(3),

199.

Silvetti, M., Wiersema, J. R., Sonuga-Barke, E., & Verguts, T. (2013). Deficient reinforcement

learning in medial frontal cortex as a model of dopamine-related motivational deficits in

ADHD. *Neural Networks*, *46*, 199–209.

Sims, C. R., Neth, H., Jacobs, R. A., & Gray, W. D. (2013). Melioration as rational choice:

Sequential decision making in uncertain environments. *Psychological Review*, *120*(1),

139–154. https://doi.org/10.1037/a0030850

Singh, V., & Khan, A. (2012). Decision making in the reward and punishment variants of the

Iowa gambling task: Evidence of "foresight" or "framing"? *Frontiers in Neuroscience*, *6*,

107.

Spitzer, R. L., Kroenke, K., Williams, J. B. W., & Loewe, B. (2006). A Brief Measure for

Assessing Generalized Anxiety Disorder: The GAD-7. *Archives of Internal Medicine*,

166, 1092–1097.

Stocco, A., Fum, D., & Napoli, A. (2009). Dissociable processes underlying decisions in the

Iowa Gambling Task: A new integrative framework. *Behavioral and Brain Functions*,

5(1), 1–12.

Stopczynski, A., Stahlhut, C., Larsen, J. E., Petersen, M. K., & Hansen, L. K. (2014). The

smartphone brain scanner: A portable real-time neuroimaging system. *PloS One*, *9*(2),

e86733.

Sutton, R. S., & Barto, A. G. (1998). *Reinforcement Learning: An Introduction. Adaptive*

Computations and Machine Learning. MIT Press/Bradford.

Tobler, P. N., Christopoulos, G. I., O'Doherty, J. P., Dolan, R. J., & Schultz, W. (2009). Risk-

dependent reward value signal in human prefrontal cortex. *Proceedings of the National*

Academy of Sciences, *106*(17), 7185–7190.

Tops, M., & Boksem, M. A. S. (2011). *A potential role of the inferior frontal gyrus and anterior*

insula in cognitive control, brain rhythms, and event-related potentials. Front. Psychol. 2

(330).

Weller, J. A., Levin, I. P., & Bechara, A. (2010). Do individual differences in Iowa Gambling

Task performance predict adaptive decision making for risky gains and losses? *Journal of*

Clinical and Experimental Neuropsychology, *32*(2), 141–150.

Wilson, R. C., & Collins, A. G. (2019). Ten simple rules for the computational modeling of

behavioral data. *ELife*, *8*, e49547. https://doi.org/10.7554/eLife.49547

Woodrow, A., Sparks, S., Bobrovskaia, V., Paterson, C., Murphy, P., & Hutton, P. (2019).

Decision-making ability in psychosis: A systematic review and meta-analysis of the

magnitude, specificity and correlates of impaired performance on the Iowa and

Cambridge Gambling Tasks. *Psychological Medicine*, *49*, 32–48.

Yoshimura, S., Okamoto, Y., Onoda, K., Matsunaga, M., Ueda, K., Suzuki, S., &

ShigetoYamawaki. (2010). Rostral anterior cingulate cortex activity mediates the

relationship between the depressive symptoms and the medial prefrontal cortex activity.

Journal of Affective Disorders, *122*(1), 76–85. https://doi.org/10.1016/j.jad.2009.06.017

Zavala, B., Jang, A., Trotta, M., Lungu, C. I., Brown, P., & Zaghloul, K. A. (2018). Cognitive

control involves theta power within trials and beta power across trials in the prefrontal-

subthalamic network. *Brain: A Journal of Neurology*, *141*(12), 3361–3376.

https://doi.org/10.1093/brain/awy266

Ziegler, S., Pedersen, M. L., Mowinckel, A. M., & Biele, G. (2016). Modelling ADHD: A

review of ADHD theories through their predictions for computational models of

decision-making and reinforcement learning. *Neuroscience & Biobehavioral Reviews*, *71*,

633–656. https://doi.org/10.1016/j.neubiorev.2016.09.002