Recirculation of H_2, CO_2, and ethylene improves carbon fixation and carboxylate yields in anaerobic fermentation

Flávio C. F. Baleeiro[†‡], Sabine Kleinsteuber[†], Heike Sträuber[†]*

[†]Department of Environmental Microbiology, Helmholtz Centre for Environmental Research – UFZ, Leipzig, Germany

[‡]Technical Biology, Institute of Process Engineering in Life Science, Karlsruhe Institute of Technology – KIT, Karlsruhe, Germany

ABSTRACT. Anaerobic fermentation with mixed cultures has gained momentum as a bioprocess for its promise to produce platform carboxylates from low-value biomass feedstocks. Anaerobic fermenters are net carbon emitters and their carboxylate yields are limited by electron donor availability. In a new approach to tackle these two disadvantages, we operated two bioreactors fed with acetate and lactate as a model feedstock while recirculating H_2/CO_2 to stimulate concomitant autotrophic activity. After 42 days of operation, hydrogenotrophic methanogenesis was predominant and ethylene ($\geq$1.3 kPa) was added to one of the reactors, inhibiting methanogenesis completely and recovering net carbon fixation (0.20 g CO_2 L^{-1} d^{-1}). When methanogenesis was inhibited, exogenous H_2 accounted for 17% of the consumed electron donors. Lactate-to-butyrate selectivity was 101% (88% in the control without ethylene) and lactate-to-caproate selectivity was

17% (2.3% in the control). Community analysis revealed that ethylene caused *Methanobacterium*

to be washed out, giving room to acetogenic bacteria. In contrast to 2-bromoethanosulfonate,

ethylene is a scalable methanogenesis inhibition strategy that did not collaterally block *i*-butyrate

formation. By favoring the bacterial share of the community to become mixotrophic, the concept

offers a way to simultaneously increase selectivity to medium-chain carboxylates and to develop

a carbon-fixing chain elongation process.

KEYWORDS. Mixotrophy; Volatile fatty acids; Medium-chain carboxylic acids; Carbon capture;

Methanogenesis inhibition; Syngas fermentation; Acetogenesis; Wood-Ljungdahl pathway.

INTRODUCTION

Carboxylate production via anaerobic fermentation of complex biomass feedstocks, such as

lignocellulose or food waste, recovers value-added products from low value waste streams[1].

Among the most common carboxylates produced, medium-chain carboxylates (MCC, e.g.

caproate and caprylate) have received particular attention. MCC stand out as promising platform

chemicals and sustainable energy carriers compared to short-chain carboxylates (SCC) and ethanol

due to their higher energy density and low water solubility enabling an easier separation from

fermentation broths[2-3].

MCC production by mixed cultures results from the process of chain elongation in which linear

carboxylate carbon chains are extended by two carbon atoms in each cycle. Chain elongation

requires an electron donor and an electron acceptor (typically an SCC). Conventional electron

donors (i.e. lactate, sugars, or ethanol) and SCC are produced by hydrolysis and fermentation of

biomass[4].

As a drawback, anaerobic fermenters are commonly net carbon emitters because some carbon from the feedstock is released in form of CO_2 and CH_4 via various metabolic pathways. CO_2 is formed during fermentation of substrates such as carbohydrates and lactate into SCC via pyruvate (shown in Equation 1 for acetate); H_2/CO_2 is formed by syntrophic bacteria during SCC oxidation (shown in Equation 2 for acetate); CH_4 and CO_2 are produced from acetate by acetoclastic methanogens (Equation 3); and CH_4 is formed from H_2/CO_2 by hydrogenotrophic methanogens (Equation 4).

$$CH_3COCOO^- + H_2O \rightarrow CH_3COO^- + CO_2 + H_2 \tag{1}$$

$$CH_3COO^- + H^+ + 2H_2O \rightarrow 4H_2 + 2CO_2 \tag{2}$$

$$CH_3COO^- + H^+ \rightarrow CH_4 + CO_2 \tag{3}$$

$$4H_2 + CO_2 \rightarrow CH_4 + 2H_2O \tag{4}$$

The pathways described by Equations 2, 3, and 4 are counterproductive to carboxylate production and chain elongation[5] whereas CO_2 emission in Equation 1 is a consequence of the stoichiometry in the production of carboxylates with even carbon numbers. If additional H_2 is provided to the mixed culture, carbon emission can be compensated by homoacetogenic activity with reincorporation of CO_2 into acetate (Equation 5).

$$4H_2 + 2CO_2 \rightarrow CH_3COO^- + H^+ + 2H_2O \tag{5}$$

If H_2 can be kept abundant and accessible to the microorganisms, multiple positive effects can be achieved by i) stimulating autotrophic activity in the community[6] to the point that fermentation can become a net carbon-fixing process (with exogenous CO_2); ii) disfavoring the oxidation of SCC (Equation 2)[5]; and iii) providing substrates for chain elongation. To take profit from these possibilities, the concept of an anaerobic fermenter with recirculation of exogenous H_2/CO_2 or syngas (H_2, CO_2, CO) was proposed Baleeiro, et al. [5].

To avoid carbon emission by methanogenesis (Equations 3 and 4), the use of chemical inhibitors

is a popular alternative. Among methanogenesis inhibitors considered to be selective, 2-

bromoethanesulfonate (2-BES) is the most used chemical in lab-scale fermentations[7]. However,

the selectivity of 2-BES comes with caveats. Recent studies indicated collateral effects of 2-BES

addition on carboxylate production, such as inhibition of *i*-butyrate formation[6, 8] and an increase

of sulfate-reducing bacterial populations, suggesting 2-BES degradation in the long term[9-11].

Moreover, application of 2-BES at the high concentrations (50 mM[12]) needed to inhibit

hydrogenotrophic methanogenesis (Equation 4) might be economically unfeasible in industrial

scale.

Alternatively, ethylene and acetylene are commodity gases that can inhibit methanogenesis

completely even at partial pressures as low as 0.5 kPa[13]. Up to 5 kPa of ethylene showed no

inhibitory effect on pure cultures of the acetogenic bacterium *Acetobacterium woodii*[14], yet, studies

on the use of these gases in anaerobic fermentation are rare, possibly because the gas phase of

many reactors is simply vented out. In a few concept demonstrations, acetylene has been proposed

as a cost-effective methanogenesis inhibitor in H_2 production[15-17]. To the best of the author's

knowledge, there are no reports testing the cost-effectiveness of ethylene in the literature.

In this study, a gas recirculation system was developed with the aims of achieving net carbon

fixation and enhancing carboxylate production with exogenous H_2/CO_2 without increasing the

supply of conventional electron donors. To deal with the resilient methanogenic activity, the use

of ethylene as a methanogenesis inhibitor was tested in culture bottles and scaled up to a H_2/CO_2

recirculation reactor.

MATERIAL AND METHODS

BATCH EXPERIMENTS IN CULTURE BOTTLES. Two different culture bottle experiments

were realized with duplicates to test the use of ethylene as methanogenesis inhibitor. The first

batch lasted 48 days with H_2 (160 kPa) as electron donor and under conditions with and without

ethylene. The second batch with addition of H_2 (160 kPa) and ethanol (1.7 g L^{-1}) as electron donors

lasted 63 days, and conditions with ethylene, with 2-BES, and without methanogenesis inhibitor

were tested. Table S1 summarizes the tested conditions and the types of controls used in each batch

experiment.

The inoculum for the batch experiments originated from a previous study, in which microbial

communities were enriched on organic substrates and H_2/CO_2[6]. From this study, "community C"

was used for inoculation. Prior to their use, the inoculum sources were stored in serum bottles

initially with 200 kPa H_2:CO_2 (80:20) in the dark and at room temperature. The basal medium

containing yeast extract and 200 mM acetate was described by Baleeiro et al.[6]. The cultures were

set up with 10 vol% inoculum, whereas the abiotic control bottles received 10 vol% sterile anoxic

water instead. Preparation procedures for the fermentation and gas purging/pressurization cycles

were done as described by Baleeiro et al.[6]. When applicable, 4.5 kPa ethylene was added to the

pressurized culture bottles. For comparison of ethylene and 2-BES, every bottle received 1.7 g L^{-1}

^{1} (37 mM) of ethanol in the beginning of the fermentation. 50 mM of 2-BES (sodium salt) was

used in one set of duplicates, whereas all bottles without 2-BES received additionally 50 mM NaCl

to achieve a similar salinity level. The culture bottles were incubated in a rotary shaker at 37°C

and 200 rpm. The pH value was adjusted manually to 5.5 with 4 M KOH or 4 M HCl.

The headspace of the bottles was sampled once or twice per week (depending on methanogenic

activity) for monitoring of pressure, gas composition, and gas production. Culture bottles were

refilled when their pressure was 130 kPa or lower. The liquid phase was sampled weekly for

analysis of organic acids and alcohols. Cell pellets were collected at the end of each batch for

microbial community analysis.

GAS RECIRCULATION REACTORS. Two identical gas recirculation reactor systems were

assembled for this study. Each system (Figure 1) consisted of a bioreactor Biostat A plus (Sartorius

AG, Göttingen, Germany) with 1.0 L working volume, an 11 L (maximum volume) gas reservoir

made of gas-tight, flexible multilayered aluminum-plastic composite material, a condenser, and

Hei-Flow Precision peristaltic pumps (Heidolph Instruments GmbH, Schwabach, Germany). The

whole system was connected with PVC tubes Tygon® R-3603 or LMT-55 and checked regularly

for gas leakages with a gas leak detector GLD-100 (Coy Laboratory Products, Grass Lake, USA).

A peristaltic pump ensured a continuous gas flow of ca. 20 mL min^{-1} with injection in the liquid

phase through a microsparger. The reactor was operated at 32°C with stirring speed of 300 rpm

and 7 kPa overpressure on average. Temperature and pH were monitored and controlled, and

oxidation reduction potential (ORP) was monitored.

 Figure 1. Scheme of the gas recirculation reactor.

The basal medium used in the reactor was similar to the medium used in the culture bottles

experiment with the following modifications: it contained 1.61 g L^{-1} NH_4Cl, did not contain yeast

extract, and was prepared with glacial acetic acid instead of a sodium acetate/acetic acid mixture.

The basal medium was made anoxic and was sterilized and then stored at room temperature at pH

4.5. The inoculum for the reactor experiment, derived from a biogas reactor, was the same as the

one used for "community C" described by Baleeiro et al.[6], and it was stored under anoxic

conditions at room temperature in the dark before its use. For startup, each reactor received 14

vol% of inoculum plus 86 vol% of basal medium with pH adjusted to 6.0. Anoxic, concentrated

cysteine and vitamin solution were added to the basal medium immediately before its addition to

the vessel or its connection to the feed pump. 4 M NaOH was used to maintain the pH value

between 5.9 and 6.0 and as sodium source. Depending on the amount of NaOH added, salinity of

the broth was estimated to be in the range of 16 to 28 g L^{-1} NaCl equivalents. Feeding and

harvesting were done with peristaltic pumps programmed to operate 10 times per day in pulses

lasting 90 s each. Flows were set to a hydraulic retention time (HRT) of 14 days. On day 9 of

operation, DL-lactic acid (90% purity) started to be fed with a syringe once a week in order to

reach a lactate concentration of 6.0 g L^{-1} (67 mM) after each injection.

Before startup, the gas reservoirs of the assembled dry reactor systems were vacuumed and filled

several times with 10 L N_2 to remove all O_2. A defined amount of helium was injected in the

system and recirculated to estimate the rigid volume of the system (volume of the system without

the gas reservoir). After inoculation and for every gas purging/replenishment cycle, the gas

reservoir was emptied with a vacuum pump Laboport$^®$ N810FT (KNF Neuberger GmbH,

Freiburg, Germany) and refilled with 10 L of H_2:CO_2 (80:20). Furthermore, 120 mL helium was

injected with a syringe to act as an inert tracer gas to quantify volume variations due to microbial

activity. Concentration of N_2 was monitored to identify and quantify possible air contamination in

the system. For inhibition of methanogenesis, ethylene was added after gas replenishment to one

of the reactors ensuring a minimum ethylene share of 1.3% in the recirculating gas. Once

methanogenic activity was established, gas reservoirs were refilled once a week or when the H_2

share was below 60%, whichever came first. Gas purging and replenishment cycles were always

preceded and succeeded by gas sampling in order to keep track of the volume of the system.

The reactor broth was sampled three times per week and before and after each lactate addition.

The sampled broth was used for collection of cell pellets for microbial community analysis and

for biomass concentration and chemical composition analysis.

Assumptions and calculation steps for the gas recirculation experiment as well as conversion

factors used for the electron and carbon balances (Table S2) are described in the Supporting

Information.

ANALYTICAL METHODS. Biomass concentration was determined by measuring the optical density at 600 nm (spectrophotometer Genesys 10 S, Thermo Scientific Inc., Waltham, USA). Concentration of linear monocarboxylates C1-C8, normal alcohols C2-C6, *i*-butyrate, *i*-valerate, *i*-caproate, and lactate was measured by high performance liquid chromatography with a refractive index detector (HPLC Prominence-i RID, Shimadzu Europa GmbH, Duisburg, Germany). H_2, CO_2, CH_4, He, N_2, and ethylene in the gas phase were analyzed by gas chromatography with a thermal conductivity detector (Light Gas Analyzer ARNL4159 model 4016, PerkinElmer Inc., Shelton, USA). Details of the chromatographic techniques were described previously[6, 18].

MICROBIAL COMMUNITY ANALYSIS. Cell pellets collected from serum bottles and from the gas recirculation reactors were washed with phosphate-buffered saline (PBS, 12 mM PO_4^{-3}) solution and stored at -20°C until their use for amplicon sequencing of the 16S rRNA genes. Detailed description of DNA extraction, PCR, Illumina library preparation, and sequencing on the MiSeq platform can be found in the study of Logroño, et al.[19]. The used primers targeted the V3 and V4 regions of the 16S rRNA gene and were described by Klindworth, et al.[20]. The bioinformatics workflow used for sample inference from amplicon data was described previously[6]. Taxonomic assignment of amplicon sequence variants (ASVs) was done using the SILVA 138 reference database[21-22]. For the most abundant ASVs, MegaBLAST[23] was used to find the most similar sequences of cultured species within the NCBI 16S ribosomal RNA sequences database[24]. Phyloseq package for R[25] was used for filtering, agglomeration, normalization, subsetting, and visualization of the microbiome census data. All samples were rarefied to an equal sequencing depth of 44,017 counts. Raw sequence data for this study was deposited at the European Nucleotide Archive (ENA) under the study accession number PRJEB41050 (http://www.ebi.ac.uk/ena/data/view/PRJEB41050).

ASSUMPTIONS FOR ECONOMIC ANALYSIS. Assumptions adopted for the economic

analysis are described in detail in the Supporting Information.

RESULTS AND DISCUSSION

The study was divided in two main experiments, namely batch tests in culture bottles and the

operation of gas recirculation semi-continuous reactors. First, two batch tests were performed in

serum bottles to understand the effectiveness of ethylene as an inhibitor, its stability, its effect on

the carboxylate production, and to compare it with 2-BES. Afterwards, the gas recirculation reactor

system was assembled and operated for 84 days.

To consider chemicals in the gaseous and aqueous phases simultaneously, results are presented

in terms of electron equivalents. When relevant, reference is made to results in terms of chemicals

concentrations in the Supporting Information.

INHIBITION OF METHANOGENESIS IN BATCH CULTURES. The electron balances for

the first test are shown in Figure S1. Regardless of ethylene presence, more acetate was consumed

when H_2 was present. The presence of H_2 with ethylene allowed a 3.7-fold higher butyrate and a

4.1-fold higher i-butyrate production, as well as a 56% higher caproate production in comparison

to cultures with the presence of H_2 alone (Figure S1-A). 243 ± 2 mmol e⁻ H_2 was consumed and

249 ± 3 mmol e⁻ CH_4 was produced when ethylene was not present (Figure S1-B). The presence

of ethylene inhibited virtually all methane production (0.1 ± 0.1 mmol e⁻ CH_4 produced),

nevertheless 22 ± 4 mmol e⁻ H_2 was consumed. Caproate production in this batch experiment was

low. Cultures with H_2 produced slightly more caproate on average (uninhibited: 2.0 ± 2.4 mmol e,

with ethylene: 3.2 ± 2.3 mmol e⁻) than H_2-free controls (uninhibited: 1.4 ± 1.7 mmol e⁻, with

ethylene: 1.2 ± 0.9 mmol e⁻) (Figure S1-A). Abiotic controls showed no changes in chemical

concentration (data not shown). CH_4 was not produced in cultures that did not receive exogenous H_2, indicating that acetoclastic methanogenesis did not play a role.

Afterwards, ethylene and 2-BES were compared in the presence of H_2, CO_2, and ethanol in different culture bottles (Figure S2). When H_2 was present but no inhibitor was used, CH_4 was the most common product. Both 2-BES and ethylene completely inhibited methanogenesis (Figure S2-B). The use of inhibitors did not strongly affect butyrate or caproate formation (Figure S2-A), however, 2-BES inhibited *i*-butyrate production (0.51 ± 0.07 mmol e$^-$).

To account for the possibility of ethylene consumption by the community, the amount of ethylene in the headspace of the bottles was monitored throughout the two batch experiments (Figure S3). No sign of ethylene consumption was found during the periods of the batch experiments. The observed stability of ethylene in the anaerobic cultures is in agreement with a previous study[14], in which ethylene was not consumed over the whole period of the study (more than 3 months).

A comparison of the microbial community compositions of the inoculum and the inhibited cultures showed that *Methanobacterium* and *Methanobrevibacter* were the methanogens inhibited by ethylene and 2-BES (Figure S4). Being a closed batch system, a complete disappearance of methanogens could not be observed. In the presence of H_2/CO_2 and ethylene, the relative abundance of *Clostridium* sensu stricto 12 increased (Figure S4-A). When ethanol was also available, an *Anaerovoracaceae* bacterium had the biggest increase in relative abundance (Figure S4-B). Similar observations were found in a previous study[6], where *Clostridium* sensu stricto 12 grew most when H_2 was the only electron donor, but *Anaerovoracaceae* bacteria were most abundant when ethanol was co-fed. The patterns of the community inhibited by 2-BES or ethylene

were similar (Figure S4-B). A detailed discussion of the batch experiment results can be found in

the Supporting Information.

COMPONENT BALANCES IN THE GAS RECIRCULATION REACTORS. The operation of

the two H_2/CO_2 recirculation reactors was divided in two phases lasting 42 days each. The first

phase was used for reactor startup and process stabilization. By the end of the start-up phase,

hydrogenotrophic methanogenesis was well established in both reactors and ethylene was added

to one of the reactors, starting the inhibition phase.

Figure 2 summarizes the results of the two reactor experiments with the profiles of the

accumulated compounds during the 84 days of fermentation. Figure S5 presents the concentration

profiles of compounds in the aqueous phase. Both reactors were fed with the same amount of

lactate, however, the control reactor started lactate consumption later and some lactate was washed

out in the beginning (Figure 2).

Butyrate was the main carboxylate produced. Weekly spikes of the substrates were reflected by

the curves of lactate, butyrate (Figure 2 and Figure S5), and acetate (Figure S5) suggesting that

butyrate production was directly coupled with simultaneous consumption of lactate and acetate.

Moreover, net consumption of acetate occurred regardless of whether methanogenesis was

inhibited or not.

Figure 2. Accumulated substrate consumption and formation of compounds in the reactor with ethylene (Test reactor) and in the reactor without ethylene (Control reactor) shown in electron equivalents. Negative values mean consumption of the compound.

Butyrate production started earlier (day 14) than methanogenesis (between days 21 and 28). CH_4 formation rates were 216 and 262 mmol e^- L^{-1} d^{-1} in the control and in the test reactor, respectively, in the last seven days of the startup phase. CH_4 production stopped immediately after ethylene addition in the test reactor and H_2 consumption slowed down from 269 to 23 mmol e^- L^{-1} d^{-1}. Regarding H_2 availability, the partial pressure of H_2 in the control reactor often reached zero and fluctuated strongly in the range of 0 - 80 kPa (Figure S6). In the test reactor, partial pressures of H_2 and ethylene were within the range of 68 - 80 kPa and 1.3 - 4.8 kPa, respectively. Caproate and

propionate production was not clearly related to lactate consumption (Figures 2 and S5). An onset

of propionate production, peaking at about 1 g L^{-1}, was observed in a late stage in the control

reactor despite unchanged operating conditions. *i*-Butyrate production was not inhibited by the use

of ethylene and its accumulation remained steady in both the control and the test reactor (Figure

2). In the control reactor, variations of *i*-butyrate concentration followed variations of butyrate

concentration (Figure S5-A) while this relation was less clear in the test reactor (Figure S5-B). A

discussion on the possible role of metabolic intermediates can be found in the Supporting

Information.

The reactor with ethylene showed 55.7% less net consumption of acetate and higher

accumulation of electrons in the butyrate and caproate pools (Figure S7-A). Electron selectivity in

the test reactor was 101% lactate-to-butyrate (88.2% in the control reactor), 16.9% lactate-to-

caproate (2.3% in the control reactor), and 1.4% lactate-to-propionate (6.3% in the control reactor).

Channeling of H_2 to CH_4 was mainly responsible for the consumption of 10.9 moles e$^-$ H_2 in the

control reactor and less than 10% of this consumption (0.93 mol e$^-$ H_2) was observed in the reactor

that received ethylene (Figure S7-B). Despite being a small amount of electrons in comparison to

the methanogenic process, the H_2 consumption in the reactor with ethylene accounted for 17% of

the total electron donor consumption. In contrast, the non-methanogenic H_2 consumption

accounted for 6.6% of the total electron donors consumed in the control reactor.

NET CARBON FIXATION. Both reactors started with net carbon fixation, but there was a trend

in the long run for loss of carbon fixation capacity (Figure S8). The test reactor became a net

carbon emitter by the 3rd HRT period, whereas the control reactor became a net carbon emitter in

the 5th HRT. The use of ethylene, injected for the first time in the beginning of the 4th HRT, reverted

the trend for the test reactor (Figure S8). A maximum carbon fixation rate of 62.2 mmol C per 14-

days period was observed, which was equivalent to 0.20 g CO_2 L^{-1} d^{-1}. CO_2 dissolution in the broth

had only a small impact in the carbon fixation estimation.

MICROBIAL COMMUNITY DEVELOPMENT. The development of the microbial

communities in the gas recirculation reactors is shown in Figure 3. By the end of the startup phase

(day 42), the acidogenic genera *Clostridium, Caproiciproducens, Eubacterium,* and *Oscillibacter*,

together with the methanogenic genus *Methanobacterium*, were the main settlers in both reactors.

Bacteroides settled in both reactors from the middle until the end phase of the experiment.

Rummeliibacillus, *Sutterella*, *Defluviitoga*, *Fastidiosipila*, and unclassified *Actinomycetaceae*

were only transiently detected during the startup phase.

Figure 3. Microbial community profiles for the control and the test reactors. The latter received ethylene after day 42. Hydrogenotrophic methanogens of the genus *Methanobacterium* were washed out during the period in which ethylene was used.

In the control reactor, an additional methanogenic genus, *Methanobrevibacter*, ascended in the later experimental phase while *Eubacterium* and other less abundant genera were washed out from the reactor. With the use of ethylene in the test reactor, the washout of *Methanobacterium* gave room for higher relative abundances of *Clostridium*, *Eubacterium*, and *Colidextribacter*, genera that harbor acetogenic and acidogenic species. A slow but steady increase of *Acidipropionibacterium* was observed in the late fermentation stages in particular in the control reactor (Figure 3), which temporally corresponds to the profile of propionate concentration in the same period (Figure S5-A).

Butyrate formation was positively correlated with the relative abundances of *Clostridium* sensu stricto 12 while caproate correlated positively with abundances of *Eubacterium*, *Oscillibacter*, *Caproiciproducens*, *Erysipelatoclostridiaceae* UCG-004, and *Colidextribacter* ($p<0.01$, Figure S9). Production of CH_4 correlated positively with relative abundances of *Methanobacterium* and *Methanobrevibacter* (Figure S9), known as hydrogenotrophic methanogens. *i*-Butyrate production correlated with abundances of *Oscillibacter*, *Caproiciproducens*, *Bacteroides*, and *Erysipelatoclostridiaceae* UCG-004 (Figure S9). Presence of ethylene correlated with higher relative abundances of *Clostridium* sensu stricto 12, *Eubacterium*, *Caproiciproducens*, *Colidextribacter*. It is worth notice that the analysis shows no distinctions between direct and indirect correlations. This is exemplified in the cases that are clearly indirect: correlations between abundances of some bacterial genera and CH_4 formation and between methanogens and formation

of propionate and *i*-butyrate. Some of the ASVs within the acidogenic and acetogenic genera which

had high similarities with isolates are presented in the Supporting Information.

Although the planktonic methanogens were observed to be almost completely washed out with

the use of ethylene in the test reactor, biofilms attached to the vessel walls and other inner reactor

surfaces still contained methanogens at the end of the experiment (Figure S10).

ETHYLENE AS A SCALABLE INHIBITOR. While 2-BES can be considered a specialty

chemical (41 US\$/kg), ethylene is a commodity with a relatively low price (1 US\$/kg) and widely

available on the chemical market. Moreover, ethylene (as well as acetylene) is a common

constituent of syngas from biomass gasification in the concentrations used in this study[26-27]. With

gas recirculation, ethylene could be used as a recyclable methanogenesis inhibitor, which is not

the case for 2-BES, as the latter is soluble in water and would be washed out from the aqueous

phase. On the other hand, recirculation of gas increases the auxiliary power requirement of the

process. Figure 4 presents an order of magnitude estimate of the operating costs per m^3 of broth

for gas recirculation (depending on the compression pressure) and for the use of 2-BES (depending

on its concentration). As a reference for economic feasibility, the potential value that can be

obtained by selling the carboxylates present in the fermenter broth is estimated to be between 8

US\$ m^{-3} and 40 US\$ m^{-3} (Figure 4). This value depends on the extractable carboxylate composition

and the selling price of the carboxylates. Assumptions adopted for the economic analysis are

described in detail in the Supporting Information. Four alternatives were compared: i)

H_2/CO_2/ethylene recirculation at the flow used in this study (1.2 L h^{-1} L^{-1}); ii) H_2/CO_2/ethylene

recirculation at a flow at optimized conditions with ten times the microbial gas consumption

observed in the test reactor with ethylene (0.14 L h^{-1} L^{-1}); iii) recirculation of ethylene (0.018 L h^{-1}

^{1} L^{-1}); and iv) use of 2-BES for methanogenesis inhibition at concentrations up to 50 mM (10.5 g

L^{-1} sodium 2-BES). The gas recirculation alternatives i)-iii) cost between 0.02 US$ m^{-3} and 2 US$

m^{-3}, which is well below the value range of the carboxylate broth. The use of 2-BES for inhibiting

methanogenesis (option iv)) costs at least 43 US$ m^{-3} and is thus not economically feasible even

at concentrations below those required for inhibition of hydrogenotrophic methanogens. For a

more detailed economic analysis in the future, the supply of H$_2$ and CO$_2$ as well as the pay-offs of

gas recirculation (in terms of increased selectivity to MCC, higher carboxylate production, and net

carbon fixation) would have to be considered. As a reference, an encompassing economic analysis

considering downstream processing and capital costs (but excluding gas recirculation and

methanogenesis inhibition costs) was done previously by Scarborough, et al.[28] for an integrated

lignocellulosic biorefinery producing MCC, ethanol, and electricity.

Figure 4. Estimated operating costs of 2-BES addition or H$_2$, CO$_2$, and ethylene (C$_2$H$_4$)

recirculation depending on the pressure. The value of the carboxylate-containing broth is

estimated to be between 8 US$ m^{-3} and 40 US$ m^{-3}.

Another difference between ethylene and 2-BES found in the batch experiments was that 2-BES

showed inhibitory effects on *i*-butyrate formation, whereas ethylene did not. This fact could prove

useful if the production of branched carboxylates is desired, in particular considering that *i*-

butyrate and *i*-caproate have been recognized as potential bio-product platforms[29-30].

As a cautionary tale, it was shown that the biofilm formed in inner reactor parts contained

methanogens from previous reactor operation phases (Figure S10). Since ethylene is a reversible

inhibitor[14], the planktonic community may be easily re-inoculated with methanogens from the

biofilm or unsterile substrate if the use of ethylene ceases.

MECHANISM OF ETHYLENE INHIBITION. Research on the mechanism of ethylene

inhibition of methanogens and its effects on acidogenic bacteria has been not as encompassing as

research with acetylene. Arguably, the mechanism of inhibition by ethylene may be comparable

to that of acetylene, since ethylene also has a π C-C bond[31]. The specific inhibition by ethylene

may be explained by its effect on some types of hydrogenases, specifically those which

methanogens most depend on[31]. Acetylene was shown to strongly inhibit [NiFe] hydrogenases of

a methanogen (*Methanosarcina* sp. MST-AI DSM 2905) and of a sulfate-reducing bacterium

(*Desulfovibrio gigas*) while presenting no effect on the nickel-free hydrogenase of another sulfate-

reducing bacterium (*Desulfovibrio vulgaris*)[32]. Methanogenic archaea depend on [NiFe]

hydrogenases for fast H_2 oxidation[33] whereas fermentative bacteria (in particular *Firmicutes*) have

a vast diversity of [FeFe] hydrogenases[34]. Whether ethylene has a differential effect on these two

types of hydrogenases needs to be tested in future studies, in particular because alternative

inhibition mechanisms have been proposed[35-36]. It is worth noticing that the effects of acetylene

and ethylene on anaerobic cultures are not identical. Acetylene is a less selective inhibitor than

ethylene since acetylene inhibits sulfate-reducing and nitrogen-fixing bacteria whereas ethylene

does not[14,37]. Ethylene also seems to be more stable in anaerobic systems than acetylene, since a

rare metabolic pathway has been found that degrades acetylene in the absence of strong electron

acceptors (e.g. sulfate)[38-39] while to the best of our knowledge no similar pathway is known for

ethylene degradation.

POSSIBILITIES FOR PROCESS OPTIMIZATION. Developing, controlling, and optimizing a

mixotrophic acidogenic community is not trivial because homoacetogens typically prefer higher

ATP-yielding substrates (e.g. carbohydrates, ethanol, lactate) before switching to autotrophic

metabolism, as seen in the case of *C. ljungdahlii* in the presence of fructose[40]. Under lactate

starvation, homoacetogens are forced to put their substrate flexibility into use[41]. Here, the reactor

system was operated in such a way that H_2 and CO_2 were always available, basal medium (with

acetate) was fed ten times per day, and lactate was fed once a week. It is possible that this feeding

strategy, which had a longer intermittency for lactate, may have helped favor autotrophy over

heterotrophy. Another possible consequence of longer intervals of substrate feeding is the

maintenance of high diversity in the community[42]. High community diversity is a factor that can

help couple non-methanogenic H_2 consumption with MCC formation[6].

Acetate and lactate were used as a simplified model of an ensiled feedstock or the organic

fraction of municipal solid waste. The exploration of the concept with complex biomass is the next

step to start assessing the economic feasibility of the H_2, CO_2, and ethylene gas recirculation

approach. Future studies should also aim to increase caproate concentration, since in this study the

maximum caproate concentration achieved (up to 1.2 g L^{-1}, Figure S5) fell short in comparison to

state-of-the-art chain elongation processes. Furthermore, increase of non-methanogenic gas

consumption rates is highly desirable, since the non-methanogenic H_2 consumption achieved here

was only 17% of the total electron donor consumption. In this direction, operation with CO or

syngas mixtures may help improve gas consumption, chain elongation, solventogenesis, and

volumetric rates[43]. Besides, the presence of CO can help inhibit methanogens[44].

Depending on the desired products (SCC, MCC, alcohols, *i*-butyrate, etc.), the operation of the

system may be optimized by adjusting gas-liquid feeding strategies, together with other operational

parameters such as pH and temperature. Nevertheless, a better knowledge of the relation between

process parameters and production of SCC, MCC, and alcohols is still needed.

ASSOCIATED CONTENT

Supporting Information.

The following files are available free of charge.

Table S1 and S2, Figures S1 to S10, calculations for component balances, assumptions for

economic analysis, further discussion of the results from the batch experiments, possible

metabolic intermediates, and ASV similarities to species level. (PDF)

AUTHOR INFORMATION

Corresponding Author

* heike.straeuber@ufz.de.

Author Contributions

FCFB, SK, and HS conceptualized the study and reviewed the manuscript. FCFB developed the

methodology, performed the experiments, analyzed the data, and prepared the original draft. HS

and SK supervised the project and supported the data analysis. All authors have given approval to

the final version of the manuscript.

Funding Sources

This study was funded by the Helmholtz Association, Research Program Renewable Energies.

Financial support was also received from the CAPES – Brazilian Federal Agency for Support

and Evaluation of Graduate Education within the Ministry of Education of Brazil (No.

88887.163504/2018-00) and from the BMBF - German Federal Ministry of Education and

Research (No. 01DQ17016).

ACKNOWLEDGEMENT

We thank Ute Lohse for technical assistance in library preparation for MiSeq amplicon

sequencing as well as Carolin Köbe and Felix Kaufmann for helping with the batch experiments.

The DBFZ Department Biorefineries is acknowledged for providing the reactors.

REFERENCES

1.   Wu, Q.; Bao, X.; Guo, W.; Wang, B.; Li, Y.; Luo, H.; Wang, H.; Ren, N., Medium chain
carboxylic acids production from waste biomass: Current advances and perspectives. *Biotechnol*
Adv **2019,** *37* (5), 599-615.
2.   De Groof, V.; Coma, M.; Arnot, T.; Leak, D. J.; Lanham, A. B., Medium Chain
Carboxylic Acids from Complex Organic Feedstocks by Mixed Culture Fermentation. *Molecules*
2019, *24* (3), 398.
3.   Angenent, L. T.; Richter, H.; Buckel, W.; Spirito, C. M.; Steinbusch, K. J.; Plugge, C.
M.; Strik, D. P.; Grootscholten, T. I.; Buisman, C. J.; Hamelers, H. V., Chain Elongation with
Reactor Microbiomes: Open-Culture Biotechnology To Produce Biochemicals. *Environ Sci*
Technol **2016,** *50* (6), 2796-810.
4.   Stamatopoulou, P.; Malkowski, J.; Conrado, L.; Brown, K.; Scarborough, M.,
Fermentation of Organic Residues to Beneficial Chemicals: A Review of Medium-Chain Fatty
Acid Production. *Processes* **2020,** *8* (12), 1571.
5.   Baleeiro, F. C. F.; Kleinsteuber, S.; Neumann, A.; Sträuber, H., Syngas-aided anaerobic
fermentation for medium-chain carboxylate and alcohol production: the case for microbial
communities. *Appl Microbiol Biotechnol* **2019,** *103* (21-22), 8689-8709.

6.   Baleeiro, F. C. F.; Kleinsteuber, S.; Sträuber, H., Hydrogen as a Co-electron Donor for

Chain Elongation With Complex Communities. *Frontiers in Bioengineering and Biotechnology*

2021, *9*, 650631.

7.   Webster, T. M.; Smith, A. L.; Reddy, R. R.; Pinto, A. J.; Hayes, K. F.; Raskin, L.,

Anaerobic microbial community response to methanogenic inhibitors 2-bromoethanesulfonate

and propynoic acid. *Microbiologyopen* **2016,** *5* (4), 537-550.

8.   Huang, S.; Kleerebezem, R.; Rabaey, K.; Ganigue, R., Open microbiome dominated by

Clostridium and *Eubacterium* converts methanol into *i*-butyrate and *n*-butyrate. *Appl Microbiol*

Biotechnol **2020,** *104* (11), 5119-5131.

9.   Candry, P.; Huang, S.; Carvajal-Arroyo, J. M.; Rabaey, K.; Ganigue, R., Enrichment and

characterisation of ethanol chain elongating communities from natural and engineered

environments. *Sci Rep* **2020,** *10* (1), 3682.

10.   Hu, J. L.; Hu, Z. Y.; Cui, X. C.; Li, J.; Xia, X.; Yin, R.; Lin, X. G., 2-

bromoethanesulfonate (BES) Enhances Sulfate-reducing Bacterial Population and

Dichlorodiphenyltrichloroethane (DDT) Dechlorination in an Anaerobic Paddy Soil. *Soil &*

Sediment Contamination **2012,** *21* (6), 732-738.

11.   Rago, L.; Guerrero, J.; Baeza, J. A.; Guisasola, A., 2-Bromoethanesulfonate degradation

in bioelectrochemical systems. *Bioelectrochemistry* **2015,** *105*, 44-49.

12.   Zinder, S. H.; Anguish, T.; Cardwell, S. C., Selective inhibition by 2-

bromoethanesulfonate of methanogenesis from acetate in a thermophilic anaerobic digestor. *Appl*

Environ Microbiol **1984,** *47* (6), 1343-1345.

13.   Liu, H.; Wang, J.; Wang, A.; Chen, J., Chemical inhibitors of methanogenesis and

putative applications. *Appl Microbiol Biotechnol* **2011,** *89* (5), 1333-40.

14.   Schink, B., Inhibition of Methanogenesis by Ethylene and Other Unsaturated-

Hydrocarbons. *Fems Microbiology Ecology* **1985,** *31* (2), 63-68.

15.   Sparling, R.; Risbey, D.; PoggiVaraldo, H. M., Hydrogen production from inhibited

anaerobic composters. *International Journal of Hydrogen Energy* **1997,** *22* (6), 563-566.

16.   Wang, L.; Trujillo, S.; Liu, H., Selective inhibition of methanogenesis by acetylene in

single chamber microbial electrolysis cells. *Bioresour Technol* **2019,** *274*, 557-560.

17.   Trujillo, S. Using Acetylene as a Low-cost and Effective Methanogenesis Inhibitor in

Single Chamber Microbial Electrolysis Cells. Undergraduate Thesis, Oregon State University.

18.   Apelt, M., Examination of samples of solids (substrates) and digestates with HPLC for

aliphatic and aromatic acids, alcohols and aldehydes. In *Series "Biomass Energy Use":*

Collection of Methods for Biogas: Methods to determine parameters for analysis purposes and

parameters that describe processes in the biogas sector, 2[nd] ed.; Liebetrau, J.; Pfeiffer, D.;

Thrän, D., Eds. DBFZ: Leipzig, 2020; Vol. 7.

19.   Logroño, W.; Popp, D.; Kleinsteuber, S.; Sträuber, H.; Harms, H.; Nikolausz, M.,

Microbial Resource Management for Ex Situ Biomethanation of Hydrogen at Alkaline pH.

Microorganisms **2020,** *8* (4).

20.   Klindworth, A.; Pruesse, E.; Schweer, T.; Peplies, J.; Quast, C.; Horn, M.; Glockner, F.

O., Evaluation of general 16S ribosomal RNA gene PCR primers for classical and next-

generation sequencing-based diversity studies. *Nucleic Acids Res* **2013,** *41* (1), e1.

21.   Yilmaz, P.; Parfrey, L. W.; Yarza, P.; Gerken, J.; Pruesse, E.; Quast, C.; Schweer, T.;

Peplies, J.; Ludwig, W.; Glockner, F. O., The SILVA and "All-species Living Tree Project

(LTP)" taxonomic frameworks. *Nucleic Acids Res* **2014,** *42* (Database issue), D643-8.

22.   Callahan, B., Silva taxonomic training data formatted for DADA2 (Silva version 132).

Zenodo: 2018.

23.   Morgulis, A.; Coulouris, G.; Raytselis, Y.; Madden, T. L.; Agarwala, R.; Schaffer, A. A.,

Database indexing for production MegaBLAST searches. *Bioinformatics* **2008,** *24* (16), 1757-64.

24.   NCBI, Database resources of the National Center for Biotechnology Information. In

Nucleic Acids Res, 2017/11/16 ed.; 2018; Vol. 46, pp D8-D13.

25.   McMurdie, P. J.; Holmes, S., phyloseq: an R package for reproducible interactive

analysis and graphics of microbiome census data. *PLoS One* **2013,** *8* (4), e61217.

26.   Abdoulmoumine, N.; Kulkarni, A.; Adhikari, S., Effects of Temperature and Equivalence

Ratio on Pine Syngas Primary Gases and Contaminants in a Bench-Scale Fluidized Bed Gasifier.

Industrial & Engineering Chemistry Research **2014,** *53* (14), 5767-5777.

27.   Karthikeyan, D. R.; Dimple, K. K.; Ashokkumar, M. S.; Ajay, K.; Hasan, K. A.;

Raymond, L. H.; Mark, R. W., Critical factors affecting the integration of biomass gasification

and syngas fermentation technology. *AIMS Bioengineering* **2016,** *3* (2), 188-210.

28.   Scarborough, M. J.; Lynch, G.; Dickson, M.; McGee, M.; Donohue, T. J.; Noguera, D.

R., Increasing the economic value of lignocellulosic stillage through medium-chain fatty acid

production. *Biotechnol Biofuels* **2018,** *11*, 200.

29. de Leeuw, K. D.; de Smit, S. M.; van Oossanen, S.; Moerland, M. J.; Buisman, C. J. N.;
Strik, D. P. B. T. B., Methanol-Based Chain Elongation with Acetate to *n*-Butyrate and
Isobutyrate at Varying Selectivities Dependent on pH. *ACS Sustainable Chemistry &*
Engineering **2020,** *8* (22), 8184-8194.

30. de Leeuw, K. D.; Buisman, C. J. N.; Strik, D., Branched Medium Chain Fatty Acids: Iso-
Caproate Formation from Iso-Butyrate Broadens the Product Spectrum for Microbial Chain
Elongation. *Environ Sci Technol* **2019,** *53* (13), 7704-7713.

31. Hyman, M. R.; Arp, D. J., Acetylene inhibition of metalloenzymes. *Anal Biochem* **1988,**
173 (2), 207-20.

32. He, S. H.; Woo, S. B.; DerVartanian, D. V.; Le Gall, J.; Peck, H. D., Jr., Effects of
acetylene on hydrogenases from the sulfate reducing and methanogenic bacteria. *Biochem*
Biophys Res Commun **1989,** *161* (1), 127-33.

33. Thauer, R. K.; Kaster, A. K.; Goenrich, M.; Schick, M.; Hiromoto, T.; Shima, S.,
Hydrogenases from methanogenic archaea, nickel, a novel cofactor, and H_2 storage. *Annu Rev*
Biochem **2010,** *79*, 507-36.

34. Peters, J. W.; Schut, G. J.; Boyd, E. S.; Mulder, D. W.; Shepard, E. M.; Broderick, J. B.;
King, P. W.; Adams, M. W., [FeFe]- and [NiFe]-hydrogenase diversity, mechanism, and
maturation. *Biochim Biophys Acta* **2015,** *1853* (6), 1350-69.

35. Menon, A.; Lyng, J. G., Circular bioeconomy solutions: driving anaerobic digestion of
waste streams towards production of high value medium chain fatty acids. *Reviews in*
Environmental Science and Bio-Technology **2021,** *20* (1), 189-208.

36. Sprott, G. D.; Jarrell, K. F.; Shaw, K. M.; Knowles, R., Acetylene as an Inhibitor of
Methanogenic Bacteria. *Journal of General Microbiology* **1982,** *128* (Oct), 2453-2462.

37. Brouzes, R.; Knowles, R., Inhibition of growth of Clostridium pasteurianum by
acetylene: implication for nitrogen fixation assay. *Can J Microbiol* **1971,** *17* (12), 1483-9.

38. Schink, B., Fermentation of Acetylene by an Obligate Anaerobe, Pelobacter-Acetylenicus
Sp-Nov. *Archives of Microbiology* **1985,** *142* (3), 295-301.

39. Sutton, J. M.; Baesman, S. M.; Fierst, J. L.; Poret-Peterson, A. T.; Oremland, R. S.;
Dunlap, D. S.; Akob, D. M., Complete Genome Sequences of Two Acetylene-Fermenting
Pelobacter acetylenicus Strains. *Genome Announc* **2017,** *5* (6), e01572-16.

40.   Infantes-López, A. Advancing towards biomass-derived syngas fermentation - Evaluation

of process parameters and gas composition effects. Ph.D. thesis, Karlsruher Institut für

Technologie (KIT), 2020.

41.   Schuchmann, K.; Muller, V., Energetics and Application of Heterotrophy in Acetogenic

Bacteria. *Appl Environ Microbiol* **2016,** *82* (14), 4056-4069.

42.   Bonk, F.; Popp, D.; Weinrich, S.; Sträuber, H.; Kleinsteuber, S.; Harms, H.; Centler, F.,

Intermittent fasting for microbes: how discontinuous feeding increases functional stability in

anaerobic digestion. *Biotechnol Biofuels* **2018,** *11*, 274.

43.   Takors, R.; Kopf, M.; Mampel, J.; Bluemke, W.; Blombach, B.; Eikmanns, B.;

Bengelsdorf, F. R.; Weuster-Botz, D.; Durre, P., Using gas mixtures of CO, CO_2 and H_2 as

microbial substrates: the do's and don'ts of successful technology transfer from laboratory to

production scale. *Microb Biotechnol* **2018,** *11* (4), 606-625.

44.   Esquivel-Elizondo, S.; Miceli, J., 3rd; Torres, C. I.; Krajmalnik-Brown, R., Impact of

carbon monoxide partial pressures on methanogenesis and medium chain fatty acids production

during ethanol fermentation. *Biotechnol Bioeng* **2018,** *115* (2), 341-350.

SYNOPSIS. Anaerobic fermentation with continuous recirculation of H_2, CO_2, and ethylene

increases selectivity to carboxylates while allowing net carbon fixation.

552   **For Table of Contents Only**