Unsupervised Models of Mouse Visual Cortex

Aran Nayebi[*]   Nathan C. L. Kong[*]
Chengxu Zhuang   Justin L. Gardner
Anthony M. Norcia   Daniel L. K. Yamins

Stanford University

Abstract

Task-optimized deep convolutional neural networks are the most quantitatively accurate models of the primate ventral visual stream. However, such networks are implausible as a model of the mouse visual system because mouse visual cortex has a known shallower hierarchy and the supervised objectives these networks are typically trained with are likely neither ethologically relevant in content nor in quantity. Here we develop shallow network architectures that are more consistent with anatomical and physiological studies of mouse visual cortex than current models. We demonstrate that hierarchically shallow architectures trained using contrastive objective functions applied to visual-acuity-adapted images achieve neural prediction performance that exceed those of the same architectures trained in a supervised manner and result in the most quantitatively accurate models of the mouse visual system. Moreover, these models' neural predictivity significantly surpasses those of supervised, deep architectures that are known to correspond well to the primate ventral visual stream. Finally, we derive a novel measure of inter-animal consistency, and show that the best models closely match this quantity across visual areas. Taken together, our results suggest that contrastive objectives operating on shallow architectures with ethologically-motivated image transformations may be a biologically-plausible computational theory of visual coding in mice.

1 Introduction

In systems neuroscience, the rodent has become an indispensable model organism, allowing unprecedented genetic and experimental control at the level of cell-type specificity in individual circuits (Huberman and Niell, 2011). Beyond fine-grained control, studies of mouse visual behavior have revealed a multitude of abilities, ranging from stimuli and reward associations, to goal-directed navigation, and object-centric discriminations. These behaviors suggest that the mouse visual system is capable of supporting higher-order functions, and prior physiological studies provide evidence that higher visual cortical areas might subserve such behaviors (Glickfeld and Olsen, 2017). Given the range of hypotheses, a natural question therefore is what these populations of neurons code for during visually-guided behaviors. Formal computational models are needed to test these hypotheses: if optimizing a model for a certain task leads to accurate predictions of neural responses, then that task may provide a unified, normative account for why those population responses occur in the brain.

Deep convolutional neural networks (CNNs) are a class of models that have had immense success as predictive models of the human and non-human primate ventral visual stream (e.g.,

---

[*]Equal contribution. Correspondence: {`anayebi`;`nclkong`}@stanford.edu.

Yamins et al., 2014; Khaligh-Razavi and Kriegeskorte, 2014; Güçlü and van Gerven, 2015; Cichy et al., 2016; Cadena et al., 2019a). While the shallow, middle, and deeper layers of these models are anatomically consistent with the primate ventral stream, in that they best match lower, intermediate, and higher visual areas of primates, it is known that the rodent visual cortex exhibits a more parallel and much shallower sequential hierarchy (Harris et al., 2019; Siegle et al., 2021). In contrast with the above correspondence in primates, early visual cortical responses in rodents are best matched by deeper layers in deep CNNs (Shi et al., 2019; Cadena et al., 2019b). In fact, a fundamental problem confronting this approach is that the current best models of visual cortex are trained on ImageNet (Conwell et al., 2020), which has over one million images belonging to one thousand, mostly human-relevant, semantic categories (Deng et al., 2009). While such a dataset is an important technical tool for machine learning, it is highly implausible as a biological model particularly for rodents, who do not receive such category labels over development. These observations suggest that: (i) there is a potential architectural mismatch between deep CNN models and the rodent visual system and (ii) the representations learned from supervised image categorization may not appropriately encapsulate the constraints of the rodent visual system during natural image viewing.

We addressed these two mismatches by turning to shallower CNN architectures and by training them on unsupervised objective functions operating on lower-resolution images that more closely mimic the inputs mice receive. First, we found a gap between current supervised, deep CNNs (VGG16 and ResNet-18) used in prior comparisons to mouse visual data (Cadena et al., 2019b; Shi et al., 2019; de Vries et al., 2020; Conwell et al., 2020) as well architectures based on more detailed anatomical considerations (Shi et al., 2020), when compared to the inter-animal consistency noise ceiling. We found that adjusting the image resolution during supervised task training to better match mouse visual acuity provided a neural predictivity improvement for the resultant models, suggesting strong constraints even at the level of input transformations.

We next developed a class of novel shallow architectures with multiple streams ("StreamNets") that mimic the intermediate and higher visual areas identified in mice, informed by empirical work on the mouse visual hierarchy (Harris et al., 2019; Siegle et al., 2021). Even when *untrained*, these shallow architectures matched the improved prior, deep CNN architectures optimized on the visual acuity-adjusted supervision task, and further training of these shallow architectures outperformed them. We then addressed the strong supervision signals used in the standard ImageNet categorization task by considering supervised tasks with less category labels (CIFAR-10) or ethologically relevant labels that might be available to the mouse (e.g., depth information provided by whiskers; Quist et al., 2014; Huet and Hartmann, 2016; Zhuang et al., 2017). These tasks did not improve neural predictivity of the shallow architectures over their counterparts trained with supervision on ImageNet. Therefore, we removed these labels completely and turned to a spectrum of unsupervised objectives including sparse autoencoding (Olshausen and Field, 1996), image-rotation prediction (Gidaris et al., 2018), and contrastive embedding objectives (Wu et al., 2018; Chen et al., 2020a,b; Chen and He, 2020), all while operating on lower-resolution images.

Overall, shallow architectures (our StreamNet variants and AlexNet) trained on contrastive objectives yielded the best match to mouse neural response patterns, improving the matches on any of the supervised tasks we considered, and closely matching the inter-animal consistency noise ceiling. Taken together, our results suggest that contrastive objectives operating on shallow architectures with ethologically-motivated image transformations provide the best correspondence to all mouse visual areas, thus providing quantitative evidence for a biologically-plausible computational theory of visual coding in mice.

2   Reliability of responses throughout mouse visual cortex

What firing patterns of mouse visual areas are common across multiple animals, and thus worthy of computational explanation? This question is comparatively straightforward for more stereotypical early visual areas (e.g., VISp), because the very presence of stereotypical tuning properties allows the definition and measurement of observables that arise reliably across trials and animals. However, how can this be done generally for populations in which one does not have a prior characterization of what each cell encodes, especially those in higher visual areas? We took inspiration from methods that have proven useful in modeling primate and human visual, auditory, and motor cortex (Yamins and DiCarlo, 2016; Kell et al., 2018; Michaels et al., 2020; Nayebi et al., 2021). Specifically, we aimed to identify the best performing class of similarity transforms needed to map the firing patterns of one animal's neural population to that of another (Figure 1A). As with other cortical areas, this transform class likely cannot be so strict as to require fixed neuron-to-neuron mappings between cells. However, the transform class for each visual area also cannot be so loose as to allow a completely unconstrained linear mapping, since the highly structured response patterns of stereotypical VISp cell types may not be guaranteed to be preserved under arbitrary linear transforms.

We explored a variety of mapping transform classes between the population responses for each mouse visual area. For all methods, mapping fit was performed on 50% of natural scene images, and evaluated on a remaining held-out set of images (Figure 1B, see supplement for more details). We also included representational similarity analysis (RSA, Kriegeskorte et al., 2008) as a baseline measure of population-wide similarity across animals, corresponding to no selection of individual units, unlike the other mapping transforms. For the strictest (One-to-One) mapping transform, each target unit was mapped to the single most correlated unit in the source animal. Linear regression with sparseness priors (Lasso and ElasticNet) tended to yield the lowest inter-animal consistency among the maps considered, and in some cases could have large error bars in some visual areas, implying an inconsistent fit. However, One-to-One mapping, Ridge (L2-regularized) and PLS (Partial Least Squares) regression were more effective at the inter-animal mapping, yielding the most consistent fits across visual areas, with PLS regression providing the highest inter-animal consistency.

3   Shallow architectures trained on contrastive objectives capture neural responses throughout mouse visual cortex

Having established a consistent similarity transform class between animals across visual areas (PLS regression), we proceeded to map artificial neural responses to real neural response patterns under this transform class. While training network models on 1000-way ImageNet categorization is a popular dataset for obtaining visual representations that are well-matched to primate responses and seems to be better than other supervised alternatives for rodent neural responses (Conwell et al., 2020), it is unclear that rodents can perform well on large-scale object recognition tasks when trained (attaining approximately 70% on a two-alternative forced-choice object classification task, Froudarakis et al., 2020), such as those where there are hundreds of labels. Furthermore, the categories of the ImageNet dataset are rather human-centric and therefore not entirely ethologically relevant for rodents to begin with.

While the top-down goal of the supervised image categorization task might not be entirely appropriate given this intuition, it seems that the inputs (i.e., images), as provided by the ImageNet dataset, are a reasonable starting place, particularly given the general observation that ImageNet

Figure 1: **Evaluating the inter-animal consistency of the neural data. A**. Calcium imaging and Neuropixels data were collected by the Allen Institute for six mouse visual areas: VISp, VISl, VISal, VISrl, VISam, VISpm. We assessed the neural data for their internal consistency (split-half reliability) and their inter-animal consistency, which tells us how well one animal corresponds to a pseudo-population of pooled source animals. Obtaining these metrics further allows us to determine how well *any* model can be expected to match the neural data, whereby each animal's visual responses are mapped onto other animal's visual responses. **B**. Inter-animal consistency was computed using different linear maps, showing that PLS regression provides the highest consistency. Horizontal bars at the top are the median and s.e.m. of the internal consistencies of the neurons in each visual area. Refer to Table S1 for N units per visual area.

pre-training leads to a good representational basis set for other visual recognition tasks such as semantic segmentation and action recognition (e.g., Simonyan and Zisserman, 2014; Long et al., 2015). A change in the loss function entirely was motivated by the fact that object recognition tasks with less categories (e.g., 10 categories in CIFAR-10, Krizhevsky et al., 2009) did not improve neural predictivity for the *same* architecture trained on ImageNet (turquoise bars in Figure 2B). Therefore, we turned to the consideration of unsupervised losses, as these may provide more general goals for the models beyond the specifics of (human-centric) object categorization. Advances in computer vision have yielded algorithms that are powerful unsupervised representation learners, and these have yielded quantitatively accurate models of the primate ventral visual stream (Zhuang et al., 2021).

Reducing the image size during task training based on rodent visual acuity, which we show in Section 4 to be important to provide good neural predictivity when controlling for task and architecture, further set a constraint on the type of unsupervised algorithms we considered. Specifically, algorithms that involved crops were unlikely candidates, as the resultant crop would be too small to be effective or too small to have non-trivial features downstream of the network due to the architecture (e.g., relative location prediction or contrastive predictive coding (CPC) for static images, Doersch et al., 2015; Oord et al., 2018). We therefore considered objective functions that use image statistics from the *entire* image. As control models, we used relatively less powerful unsupervised algorithms including the sparse autoencoder (Olshausen and Field, 1996), depth-map prediction, and image-rotation prediction (RotNet, Gidaris et al., 2018). Recent advances in unsupervised learning have shown that training models on contrastive objective functions yields representations that can support strong performance on downstream categorization tasks. Thus, the remaining four algorithms we used were from the family of contrastive objective functions: instance recognition (IR, Wu et al., 2018), simple framework for contrastive learning (SimCLR, Chen et al., 2020a), momentum contrast (MoCov2, Chen et al., 2020b), and simple siamese representation learning (SimSiam, Chen and He, 2020). At a high-level, the goal of these contrastive objectives is to learn a representational space where embeddings of augmentations for one image (i.e., embeddings for two transformations of the *same* image) are more "similar" to each other than to embeddings of other images.

With these loss functions, we next turned to the development of shallower architectures (Figure 2A), called "StreamNets", that have a closer physical correspondence to mouse visual cortex than deeper models used before to compare to rodent visual responses (VGG16 and ResNet-18) The number of model layers of the StreamNet variants was informed by the shallow temporal hierarchy observed in previous studies and the timing of the reliability of the responses in the Neuropixels dataset. The design decisions of these StreamNets, which are based on the AlexNet architecture, is discussed in Section 5. We found that AlexNet and our ImageNet-supervised and unsupervised StreamNet model variants outperformed all the other models (Figure 2B). Furthermore, when those models were trained with contrastive objectives, they had the highest neural predictivity, as shown by the red and brown bars on the left of Figure 2B, attaining approximately 90% of the inter-animal noise ceiling in each dataset. However, there was no clear separation in neural predictivity among the different contrastive objectives. Among the unsupervised algorithms, contrastive objectives had the highest 64×64 pixels ImageNet transfer performance (red vs. blue/orange/purple in Figures 2C and S1B), indicating that powerful unsupervised loss functions are crucial for explaining the variance in the neural responses.

Higher ImageNet categorization performance also did not correspond to higher neural predictivity, in contrast to findings in models of the primate ventral visual stream (Yamins et al., 2014; Schrimpf et al., 2018). Specifically, deeper, purely supervised models that attain greater than 40% accuracy had, on average, the least match to the neural data (black dots in Figures 2C and S1B). As

a positive control, we optimized ResNet-18 on a contrastive objective function (pink in Figure 2) and found that although changing the objective function improved neural predictivity for ResNet-18 over its supervised counterpart, it was still worse than the shallower AlexNet trained using a contrastive objective (compare pink and brown points in Figures 2B and 2C). This indicates that having an appropriately shallow architecture contributes to neural predictivity, but even with a less physical, deep architecture such as ResNet-18, you can greatly improve neural predictivity with a contrastive embedding loss function. These findings are consistent with the idea that appropriate combinations of objective functions and architectures are necessary to build quantitatively accurate models of neural systems, with the objective function providing a strong constraint especially when coupled with a shallow architecture (Yamins and DiCarlo, 2016).

4   Task-optimization on images of lower resolution leads to improved neural predictivity

Before developing new models, we started by examining the common ImageNet models (VGG16 and ResNet-18) that have been benchmarked before on neural recordings from the primate ventral stream (Schrimpf et al., 2018; Zhuang et al., 2021; Nayebi et al., 2021) and from the mouse visual system (Cadena et al., 2019b; Shi et al., 2019; Conwell et al., 2020). Cadena et al. (2019b) specifically found that training these architectures on the ImageNet categorization task did not always yield better (and in some cases worse) neural predictivity than their untrained counterparts. Our observation that an ImageNet-supervised AlexNet (on 224×224 pixels images) is as good as an untrained AlexNet at predicting mouse visual responses corroborates their finding (Figure S5).

We reasoned that some of these problems may be related to the input resolution ("visual acuity") of these models. These models were trained using 224×224 pixels images and assuming that they span approximately 7 degrees of visual angle, which is reasonable for the primate visual system (Kiorpes, 2019; Cadena et al., 2019a; Yamins et al., 2014). As observed by Prusky et al. (2000), the upper bound on mouse visual acuity is 0.5 cycles / degree, corresponding to 2 pixels / cycle $\times$ 0.5 cycles / degree = 1 pixel / degree. A simplified correction for the appropriate visual acuity would correspond to 64×64 pixels, as in Shi et al. (2019, 2020), though more investigation into the appropriate transformation may be needed.

We retrained the models on the (supervised) object categorization task using this smaller image size (Figure 3A) and found that it generally improved the neural predictivity compared to the same task on the larger image size (left vs. right bars in Figures 3B and 3C for each architecture; see Figure S3 for the same comparisons using the RSA metric and Figure S4 for the comparison of AlexNet, VGG-16, ResNet18 also using the RSA metric). These observations suggest that a change in the task via a simple change in the image statistics is crucial to obtain an appropriate model of mouse visual encoding, suggesting that mouse visual encoding is the result of task-optimization at a lower "visual acuity" than is typically used for primate ventral stream models.

5   Task-optimized shallow models yield a physical model with competitive neural predictivity

It was observed that the mouse visual system has a shallow hierarchy, in contrast to the primate ventral visual stream (Harris et al., 2019; Siegle et al., 2021; Felleman and Van Essen, 1991). By examining neural predictivity of the best performing model (AlexNet) as a function of model layer, we found that peak neural predictivity did not occur past the fourth convolutional layer, suggesting

Figure 2: **Shallow architectures trained with contrastive objective functions yield the best matches to the neural data. A**. We developed shallow, multi-stream architectures ("StreamNets") and trained them on various objective functions. For each model architecture, we map each layer's units via a linear transform (denoted by L) to the neural population of each animal, mimicking the procedure used for computing the inter-animal consistency. **B**. The median and s.e.m. neural predictivity, using PLS regression, across six mouse visual areas. $N = 1731$ units (Neuropixels) and $N = 5167$ units (calcium imaging). Red denotes our StreamNet models trained on contrastive objective functions, blue denotes our StreamNet models trained on RotNet, turquoise denotes our StreamNet models trained in a supervised manner on ImageNet and on CIFAR-10, green denotes untrained models (random weights), orange denotes our StreamNet models trained depth prediction, purple denotes our StreamNet models trained on autoencoding, brown denotes contrastive AlexNet, pink denotes contrastive ResNet-18 (both trained on instance recognition), black denotes the remaining ImageNet supervised models (primate ventral stream models), and grey denotes the MouseNet of Shi et al. (2020) and our variant of this architecture. Actual neural predictivity performance can be found in Table S3. **C**. Each model's performance on 64×64 pixels ImageNet is plotted against its median neural predictivity across all units from each visual area. All ImageNet performance numbers can be found in Table S3. Color scheme as in **B**.

Figure 3: **Lower image resolution during model training improves task-optimized neural predictivity.** **A**. Models with lower "visual acuity" were trained using lower-resolution ImageNet images. Each image was downsampled from 224×224 pixels to 64×64 pixels. **B**. Light blue bars indicate the maximum noise-corrected neural predictivity, obtained via PLS regression, on the Neuropixels dataset across model layers for models trained on 224×224 pixels images. Dark blue bars indicate the maximum noise-corrected neural predictivity for models trained on 64×64 pixels images. The median and s.e.m. across neurons in each visual area is reported. **C**. As in **B**, but for the calcium imaging dataset. Refer to Table S1 for N units per visual area.

that an even shallower network architecture might be more appropriate (Figures 4B and 4C).

This hypothesis was further corroborated by examining the internal consistencies of the neurons in each visual area from the Neuropixels dataset at each 10-ms time bin, shown in the right panel of Figure 4A. The peak internal consistencies occurred in quick succession from 100-130 ms, starting from VISp (hierarchically the lowest visual area), suggesting an overall three to four level architecture. Recent work by Shi et al. (2020) investigated the construction of a shallow, parallel pathway model based on information provided by large-scale tract tracing data, though this model was neither task-optimized nor compared to neural responses. We trained this network on (64×64 pixels) ImageNet categorization, and conducted a hyperparameter sweep to identify the learning parameters that yielded the best performance on the task. We also trained a variant of this network where the task readout was at the final model layer ("VISpor"), and found that this yielded an approximately 2% improvement in ImageNet categorization performance over the original model with its best hyperparameters. The neural predictivity of MouseNet and this variant was comparable on both datasets (see Figure 4D for neural predictivity on the Neuropixels dataset and Figure S2B for neural predictivity on the calcium imaging dataset).

For each visual area, the maximum neural predictivity of these models was worse than that of AlexNet (trained on 64×64 pixels images), which was the best (and shallowest) model among these architectures (Figure 4D). This result motivated the consideration of an architecture that is shallower than AlexNet (which we call "StreamNet"), that is more physically matched to the known shallower hierarchy of the mouse visual system, and yields comparable neural predictivity with *no* model layers that are unassigned to any visual area. We therefore adapted the AlexNet architecture up to the model layer of maximum predictivity across all visual areas (fourth convolutional layer; Figures 4B and 4C, and Figure S2A), but allowed for potentially multiple parallel pathways with three levels based on the peak internal consistency timing observations (right panel of Figure 4A). This yielded an architecture of four convolutional layers, divided into three levels. The first level consisted of one convolutional layer and the intermediate level consisted of two convolutional layers. The final level has two "areas" in parallel (where each area consists of one convolutional layer), inspired by the observation that VISpor and VISam comprise the top-most levels of the mouse visual hierarchy (left panel of Figure 4A; Harris et al., 2019; Siegle et al., 2021). We additionally included dense skip connections from shallow levels to deeper levels, known from the feedforward connectivity of the mouse connectome (Harris et al., 2016; Knox et al., 2018). Taking into consideration the observation of Conwell et al. (2020) that thinner task-optimized networks yielded better fits to mouse visual data[1], we allowed the number of parallel streams N to be an architectural variable. We set the number of parallel streams to be one (as a control; denoted "single-stream"), two (to mimic a potential ventral/dorsal stream distinction; denoted "dual-stream"), and six (to more closely match the known number of intermediate visual areas: VISl, VISli, VISal, VISrl, VISpl, and VISpm; denoted "six-stream"). A schematic of each of these StreamNet variants is shown in Figure 2A. We found that our StreamNet model variants were always more predictive of the neural data across all the visual areas than the MouseNet of Shi et al. (2020) and attain comparable predictivity as AlexNet, when trained with the same supervised or unsupervised loss function (Figures 2B and S1A).

---

[1]We note, however, that this conclusion was made without using models that were trained on images with the adjusted size.

Figure 4: **StreamNet model derivation (Neuropixels dataset). A**. Left: Normalized hierarchy scores for each mouse visual area from Figure 2a of Siegle et al. (2021). Higher score indicates that the visual area is higher in the mouse visual hierarchy. Right: Fraction of maximum split-half reliability for each visual area as a function of time computed from the Neuropixels dataset. **B**. We found that the first four convolutional layers of AlexNet best corresponded to all the mouse visual areas (panel C). These convolutional layers were used as the basis for our StreamNet architecture variants (shown in Figure 2A). **C**. Neural predictivity, using PLS regression, on the Neuropixels dataset across AlexNet architectures trained in two different ways (supervised [orange] and unsupervised [green]). We observe that the first four convolutional layers provide the best fits to the neural data while the latter three layers are not very predictive for any visual area, suggesting that an even shallower architecture may be suitable. **D**. Supervised AlexNet provides the best neural predictivity on the Neuropixels dataset across all six visual areas compared to deeper architectures (to the left of the purple bar). Refer to Table S1 for N units per visual area. See Figure S2B for predictivity on the calcium imaging dataset.

6 Contrastive embedding methods yield high performing neural networks

Given the strong correspondence between unsupervised models trained with contrastive embedding objectives, especially relative to their supervised and untrained counterparts (the latter being an objective-function-independent control), here we delve into why this might be the case. In other words, given that improvement on ImageNet categorization was *not* related to improved neural predictivity (Figure 2C), are the representations in these unsupervised networks better serving a downstream ethological niche compared to alternative supervised and unsupervised objectives?

We examined the effectiveness of these unsupervised representations for supporting a variety of visual tasks on image sets distinct from the images under which training took place. Specifically, we explored whether contrastive models provided visual representations useful for different downstream tasks that rodents *might* perform, such as object-centric visual behaviors (Zoccolan et al., 2009) and non-object-centric behaviors that may be useful for guiding navigation, typically attributed to dorsal areas (Wang and Burkhalter, 2013). We considered two primary datasets for these tasks. The first image set was previously used to assess both neural and behavioral consistency of supervised and unsupervised neural networks (Yamins et al., 2014; Rajalingham et al., 2018; Schrimpf et al., 2018; Zhuang et al., 2021), on which we evaluated transfer performance on object categorization and other object-centric visual tasks independent of object category, including object position localization, size estimation, and pose estimation. The second dataset was focused on texture discrimination (Cimpoi et al., 2014), which we used as a proxy for the subset of non-object-centric visual behaviors which may be relevant to navigation and the exploration of novel environments.

We assessed the transfer performance of the unsupervised models by adding a single fully connected linear readout layer to each layer of the three StreamNet variants, trained with the supervised categorization and unsupervised loss functions. Because different tasks could in theory be best supported by different layers of the unsupervised networks, we report cross-validated performance values for the best model layer. Note that these are all on held-out images not used during training of any of the original networks.

Shown in Figure 5, we found that, across all evaluated objective functions and StreamNet architectural variants, the contrastive embedding objectives (red bars) showed substantially better linear task transfer performance than other unsupervised methods (purple and blue bars), as well as ethologically-relevant supervision such as depth prediction (orange bars). Furthermore, the contrastive embedding objectives either approached or exceeded, the performance of networks trained on supervised ImageNet categorization (turquoise bars). Taken together, these results suggest that contrastive embedding methods have achieved a generalized improvement in the quality of the visual representations they create, enabling a diverse range of visual behaviors, providing evidence for their potential as computational models of mouse visual cortex, across ventral and dorsal areas.

7 Discussion

We have shown that shallow contrastive embedding methods operating on visual-acuity-adapted images most accurately predict image-evoked neural responses across early and higher visual areas in mice, surpassing the predictive power of supervised methods. Specifically, we found that deep CNNs supervised on ImageNet categorization, which are quantitatively the best models of the *primate* ventral stream, were poor predictors of neural responses throughout mouse visual cortex, corroborating previous findings (Cadena et al., 2019b; Shi et al., 2019; Conwell et al., 2020).

Figure 5: **Evaluating visual representations of StreamNet variants learned in an unsupervised manner on object-centric and non-object-centric visual tasks.** Red denotes our StreamNet variants trained on contrastive objective functions. Blue denotes our models trained on rotation prediction (RotNet), orange denotes our depth prediction models, purple denotes autoencoding models, green are the untrained model. The average performance and its standard deviation (mean and s.t.d.) across 10 train-test image splits is reported for each transfer task. **A.** Maximum linear transfer performance across model layers on the categorization of objects that are highly varied in terms of their rotation, sizes, and positions in the image. **B.** Object pose estimation accuracy. **C.** Object position estimation accuracy. **D.** Object size estimation accuracy. **E.** Maximum linear transfer performance on 47-way texture classification (a non-object-centric task).

However, we found that training CNNs on modified image statistics that were somewhat more consistent with those received by the mouse visual system, led to models that better correspond to neural responses in all mouse visual areas. In particular, we found that the shallow AlexNet architecture, when trained on reduced size images, had the best predictive performance, even when compared to recent models (and variants of them that we considered), whose architecture was constrained by mouse neuroanatomical data (Shi et al., 2020). Given that the higher layers of AlexNet were not good predictors of any rodent visual areas, this observation motivated us to develop shallower, multi-stream architectural variants ("StreamNets"), containing at most four sequential convolutional layers, based on the known functional hierarchy of the mouse visual system and on the peak internal consistency timings we computed on the Neuropixels dataset. We showed that training these novel architectures in a supervised manner on ImageNet resulted in competitive neural predictivity with AlexNet, the architecture it was based on. Finally, we removed the dependency on supervised categorization labels, by training architectures on unsupervised objectives and found that AlexNet and our StreamNet model variants trained with contrastive objectives had the best neural predictivity across visual areas. In fact, these architectures approached the computed inter-animal consistency of all measured units on both neural datasets, a novel quantity that we introduce. Taken together with recent work done in primates (Zhuang et al., 2021), these results indicate that contrastive objectives appear to best explain responses across both rodent and primate species, suggesting that these objectives may be part of a species-general toolkit. However, unlike the situation in the primate ventral stream, contrastive objectives *surpassed* the neural predictivity of their supervised counterparts, as increased categorization performance lead to overall *worse* correspondence to mouse visual areas. We observe that the advantage of these contrastive objectives is that they provide representations that are generally improved over those obtained by supervised methods in order to enable a diverse range of visual behaviors.

Although we have made progress in improving model correspondence to the mouse visual system by approaching the inter-animal consistency on this data, we suggest several future directions. Specifically, on the neural dataset front, we believe that future datasets collected from all putative rodent visual areas, with more natural images may result in a stronger separation of model architectures and candidate loss functions. It would be of interest to see if specific choices of contrastive embedding objectives and StreamNet variants are more differentiated, in order to narrow the family of candidate objective functions that provide the best correspondence to mouse visual responses.

In terms of future modeling directions, we consider three main components of task-driven neural network models: the data stream, the architecture class, and the objective function; noting that each of these components can be further refined in future work.

We first modified the input data via a modification in the image statistics so that they are closer to those received by the mouse visual system, by resizing the images to be smaller during as a proxy for low-pass filtering. As a result of a reduced image size, certain algorithms became less applicable. We believe that future work could improve on this by investigating the appropriate low-pass filters and ethologically relevant pixel-level transformations to apply to the original image (i.e., removing the need to downsample the images), so that a wider range of candidate objective functions can be used and evaluated. Another issue with the current set of algorithms is that the input data are static images, whereas visual development and learning occurs within dynamic environments. Moreover, the neural responses by which we assessed our models were evoked by static images and a complete model of the visual system should be able to match the neural responses to arbitrary visual stimuli (e.g., video streams). Thus, to develop a complete model of the visual system, it is imperative that models are trained on dynamic inputs of the kind rodents naturally receive so that neural responses under natural behaviors (e.g., navigation, which we used

texture recognition as a proxy of) could potentially be modeled.

On the architectural front, we introduced StreamNets, a novel shallow and multi-stream model, which we think is a reasonable starting point for building more accurate mouse vision models, but is incomplete. Specifically, a major limitation in our modeling efforts is due to our simplification of visual cortex to a set of parallel, feedforward computations. However, as observed by Harris et al. (2019), there are many feedback connections from higher visual areas to lower visual areas. Incorporating these architectural motifs into our models and training these models using dynamic inputs may be useful for modeling temporal dynamics in mouse visual cortex, as has been recently done in primates (Nayebi et al., 2018; Kubilius et al., 2019; Nayebi et al., 2021). In addition, we can probe the functionality of, and test hypotheses for the utility of these feedback connections between visual areas using models that incorporate these features.

Models of the rodent and the primate visual system can also be used to develop and to test computational hypotheses aiming to understand the organizational principles of visual cortex that are common or uncommon across species. For example, it is known that neurons in primary visual cortex are selective to the orientation of an edge (Hubel and Wiesel, 1962). In particular, neurons selective for the *same* orientation are organized in columns in primary visual cortex of higher-order species such as cats and macaques (Hubel and Wiesel, 1963; Hubel et al., 1977, 1978). Furthermore, the preferred orientation for a column varies smoothly along the cortical surface, creating pinwheel-like patterns (Bonhoeffer and Grinvald, 1991). These highly organized maps of orientation preference, however, are not present in rodents (Ohki et al., 2005; Van Hooser et al., 2005). What are the constraints imposed on the *development* of visual cortex of higher- or lower-order species that result in the presence or the absence of these orientation maps? Are there multiple objective functions present during development at different stages, or are they best explained by one? Computational models of rodent and of macaque visual systems will be useful tools to test theories for the development of this phenomenon and are a starting point for the comparison of computational goals (i.e., behaviors), constraints, and visual experience driving the organization of visual cortex across different species.

Acknowledgements

We thank Shahab Bakhtiari, Katherine L. Hermann, and Akshay Jagadeesh for helpful discussions, and Eshed Margalit for helpful feedback on the manuscript. N.C.L.K. is supported by the Stanford University Ric Weiland Graduate Fellowship. J.L.G. acknowledges the generous support of Research to Prevent Blindness and Lions Club International Foundation (`https://www.rpbusa.org/rpb/low-vision/`). A.M.N. is supported by the Stanford Institute for Human Centered Artificial Intelligence. D.L.K.Y. is supported by the James S. McDonnell Foundation (Understanding Human Cognition Award Grant No. 220020469), the Simons Foundation (Collaboration on the Global Brain Grant No. 543061), the Sloan Foundation (Fellowship FG-2018-10963), the National Science Foundation (RI 1703161 and CAREER Award 1844724), the DARPA Machine Common Sense program, and hardware donation from the NVIDIA Corporation.

References

Tobias Bonhoeffer and Amiram Grinvald. Iso-orientation domains in cat visual cortex are arranged in pinwheel-like patterns. *Nature*, 353(6343):429–431, 1991.

Léon Bottou. Large-scale machine learning with stochastic gradient descent. In *Proceedings of COMPSTAT'2010*, pages 177–186. Springer, 2010.

Santiago A Cadena, George H Denfield, Edgar Y Walker, Leon A Gatys, Andreas S Tolias, Matthias Bethge, and Alexander S Ecker. Deep convolutional models improve predictions of macaque v1 responses to natural images. *PLoS Computational Biology*, 15(4):e1006897, 2019a.

Santiago A Cadena, Fabian H Sinz, Taliah Muhammad, Emmanouil Froudarakis, Erick Cobos, Edgar Y Walker, Jacob Reimer, Matthias Bethge, Andreas Tolias, and Alexander S Ecker. How well do deep neural networks trained on object recognition characterize the mouse visual system? *NeurIPS Neuro AI Workshop*, 2019b.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning*, pages 1597–1607, 2020a.

Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. *arXiv preprint arXiv:2011.10566*, 2020.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020b.

Radoslaw Martin Cichy, Aditya Khosla, Dimitrios Pantazis, Antonio Torralba, and Aude Oliva. Comparison of deep neural networks to spatio-temporal cortical dynamics of human visual object recognition reveals hierarchical correspondence. *Scientific Reports*, 6(1):1–13, 2016.

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2014.

Colin Conwell, Michael Buice, Andrei Barbu, and George Alvarez. Model zoology and neural taskonomy for better characterizing mouse visual cortex. *ICLR Bridging AI and Cognitive Science (BAICS) Workshop*, 2020.

Saskia EJ de Vries, Jerome A Lecoq, Michael A Buice, Peter A Groblewski, Gabriel K Ocker, Michael Oliver, David Feng, Nicholas Cain, Peter Ledochowitsch, Daniel Millman, et al. A large-scale standardized physiological survey reveals functional organization of the mouse visual cortex. *Nature Neuroscience*, 23(1):138–151, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009.

Carl Doersch, Abhinav Gupta, and Alexei A Efros. Unsupervised visual representation learning by context prediction. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1422–1430, 2015.

Daniel J Felleman and David C Van Essen. Distributed hierarchical processing in the primate cerebral cortex. *Cerebral Cortex*, 1(1):1–47, 1991.

Emmanouil Froudarakis, Uri Cohen, Maria Diamantaki, Edgar Y Walker, Jacob Reimer, Philipp Berens, Haim Sompolinsky, and Andreas S Tolias. Object manifold geometry across the mouse cortical visual hierarchy. *bioRxiv*, 2020.

Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised representation learning by predicting image rotations. In *International Conference on Learning Representations*, 2018.

Lindsey L Glickfeld and Shawn R Olsen. Higher-order areas of the mouse visual cortex. *Annual Review of Vision Science*, 3:251–273, 2017.

Umut Güçlü and Marcel AJ van Gerven. Deep neural networks reveal a gradient in the complexity of neural representations across the ventral stream. *Journal of Neuroscience*, 35(27):10005–10014, 2015.

Julie A Harris, Stefan Mihalas, Karla E Hirokawa, Jennifer D Whitesell, Hannah Choi, Amy Bernard, Phillip Bohn, Shiella Caldejon, Linzy Casal, Andrew Cho, et al. Hierarchical organization of cortical and thalamic connectivity. *Nature*, 575(7781):195–202, 2019.

Kameron D Harris, Stefan Mihalas, and Eric Shea-Brown. High resolution neural connectivity from incomplete tracing data using nonnegative spline regression. In *Advances in Neural Information Processing Systems*, volume 29, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 9729–9738, 2020.

Ha Hong, Daniel LK Yamins, Najib J Majaj, and James J DiCarlo. Explicit information for category-orthogonal object properties increases along the ventral stream. *Nature neuroscience*, 19(4):613, 2016.

David H Hubel and TN Wiesel. Shape and arrangement of columns in cat's striate cortex. *The Journal of Physiology*, 165(3):559–568, 1963.

David H Hubel and Torsten N Wiesel. Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. *The Journal of Physiology*, 160(1):106–154, 1962.

David H Hubel, Torsten N Wiesel, and Michael P Stryker. Orientation columns in macaque monkey visual cortex demonstrated by the 2-deoxyglucose autoradiographic technique. *Nature*, 269 (5626):328–330, 1977.

David H Hubel, Torsten N Wiesel, and Michael P Stryker. Anatomical demonstration of orientation columns in macaque monkey. *Journal of Comparative Neurology*, 177(3):361–379, 1978.

Andrew D Huberman and Cristopher M Niell. What can mice tell us about how vision works? *Trends in Neurosciences*, 34(9):464–473, 2011.

Lucie A Huet and Mitra JZ Hartmann. Simulations of a vibrissa slipping along a straight edge and an analysis of frictional effects during whisking. *IEEE transactions on haptics*, 9(2):158–169, 2016.

Alexander JE Kell, Daniel LK Yamins, Erica N Shook, Sam V Norman-Haignere, and Josh H McDermott. A task-optimized neural network replicates human auditory behavior, predicts brain responses, and reveals a cortical processing hierarchy. *Neuron*, 98(3):630–644, 2018.

Seyed-Mahdi Khaligh-Razavi and Nikolaus Kriegeskorte. Deep supervised, but not unsupervised, models may explain it cortical representation. *PLoS Computational Biology*, 10(11):e1003915, 2014.

Lynne Kiorpes. Understanding the development of amblyopia using macaque monkey models. *Proceedings of the National Academy of Sciences*, 116(52):26217–26223, 2019.

Joseph E Knox, Kameron Decker Harris, Nile Graddis, Jennifer D Whitesell, Hongkui Zeng, Julie A Harris, Eric Shea-Brown, and Stefan Mihalas. High-resolution data-driven model of the mouse connectome. *Network Neuroscience*, 3(1):217–236, 2018.

Nikolaus Kriegeskorte, Marieke Mur, and Peter A Bandettini. Representational similarity analysis-connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, 2:4, 2008.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Jonas Kubilius, Martin Schrimpf, Kohitij Kar, Rishi Rajalingham, Ha Hong, Najib Majaj, Elias Issa, Pouya Bashivan, Jonathan Prescott-Roy, Kailyn Schmidt, et al. Brain-like object recognition with high-performing shallow recurrent anns. *Advances in Neural Information Processing Systems*, 32:12805–12816, 2019.

Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3431–3440, 2015.

Najib J Majaj, Ha Hong, Ethan A Solomon, and James J DiCarlo. Simple learned weighted sums of inferior temporal neuronal firing rates accurately predict human core object recognition performance. *Journal of Neuroscience*, 35(39):13402–13418, 2015.

Jonathan A Michaels, Stefan Schaffelhofer, Andres Agudelo-Toro, and Hansjörg Scherberger. A goal-driven modular neural network predicts parietofrontal neural dynamics during grasping. *Proceedings of the National Academy of Sciences*, 117(50):32124–32135, 2020.

Aran Nayebi, Daniel M Bear, Jonas Kubilius, Kohitij Kar, Surya Ganguli, David Sussillo, James J DiCarlo, and Daniel LK Yamins. Task-driven convolutional recurrent models of the visual system. *Advances in Neural Information Processing Systems*, 31:5295—5306, 2018.

Aran Nayebi, Javier Sagastuy-Brena, Daniel M Bear, Kohitij Kar, Jonas Kubilius, Surya Ganguli, David Sussillo, James J DiCarlo, and Daniel LK Yamins. Goal-driven recurrent neural network models of the ventral visual stream. *bioRxiv*, 2021.

Kenichi Ohki, Sooyoung Chung, Yeang H Ch'ng, Prakash Kara, and R Clay Reid. Functional imaging with cellular resolution reveals precise micro-architecture in visual cortex. *Nature*, 433(7026):597–603, 2005.

Bruno A Olshausen and David J Field. Emergence of simple-cell receptive field properties by learning a sparse code for natural images. *Nature*, 381(6583):607–609, 1996.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Glen T Prusky, Paul WR West, and Robert M Douglas. Behavioral assessment of visual acuity in mice and rats. *Vision Research*, 40(16):2201–2209, 2000.

Brian W Quist, Vlad Seghete, Lucie A Huet, Todd D Murphey, and Mitra JZ Hartmann. Modeling forces and moments at the base of a rat vibrissa during noncontact whisking and whisking against an object. *Journal of Neuroscience*, 34(30):9828–9844, 2014.

Rishi Rajalingham, Elias B Issa, Pouya Bashivan, Kohitij Kar, Kailyn Schmidt, and James J DiCarlo. Large-scale, high-resolution comparison of the core visual object recognition behavior of humans, monkeys, and state-of-the-art deep artificial neural networks. *Journal of Neuroscience*, 38 (33):7255–7269, 2018.

J. Brendan Ritchie, Stefania Bracci, and Hans Op de Beeck. Avoiding illusory effects in representational similarity analysis: What (not) to do with the diagonal. *NeuroImage*, 148:197–200, 2017.

Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J Majaj, Rishi Rajalingham, Elias B Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Kailyn Schmidt, et al. Brain-score: Which artificial neural network for object recognition is most brain-like? *bioRxiv*, page 407007, 2018.

Jianghong Shi, Eric Shea-Brown, and Michael Buice. Comparison against task driven artificial neural networks reveals functional properties in mouse visual cortex. *Advances in Neural Information Processing Systems*, 32:5764–5774, 2019.

Jianghong Shi, Michael A Buice, Eric Shea-Brown, Stefan Mihalas, and Bryan Tripp. A convolutional network architecture driven by mouse neuroanatomical data. *bioRxiv*, 2020.

Joshua H Siegle, Xiaoxuan Jia, Séverine Durand, Sam Gale, Corbett Bennett, Nile Graddis, Greggory Heller, Tamina K Ramirez, Hannah Choi, Jennifer A Luviano, et al. Survey of spiking in the mouse visual system reveals functional hierarchy. *Nature*, pages 1–7, 2021.

Karen Simonyan and Andrew Zisserman. Two-stream convolutional networks for action recognition in videos. In *Advances in Neural Information Processing Systems*, 2014.

Stephen D Van Hooser, J Alexander F Heimel, Sooyoung Chung, Sacha B Nelson, and Louis J Toth. Orientation selectivity without orientation maps in visual cortex of a highly visual mammal. *Journal of Neuroscience*, 25(1):19–28, 2005.

Quanxin Wang and Andreas Burkhalter. Stream-related preferences of inputs to the superior colliculus from areas of dorsal and ventral streams of mouse visual cortex. *Journal of Neuroscience*, 33(4):1696–1705, 2013.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via nonparametric instance discrimination. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3733–3742, 2018.

Daniel LK Yamins and James J DiCarlo. Using goal-driven deep learning models to understand sensory cortex. *Nature Neuroscience*, 19(3):356–365, 2016.

Daniel LK Yamins, Ha Hong, Charles F Cadieu, Ethan A Solomon, Darren Seibert, and James J DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences*, 111(23):8619–8624, 2014.

Yang You, Igor Gitman, and Boris Ginsburg. Large batch training of convolutional networks. *arXiv preprint arXiv:1708.03888*, 2017.

Yinda Zhang, Shuran Song, Ersin Yumer, Manolis Savva, Joon-Young Lee, Hailin Jin, and Thomas Funkhouser. Physically-based rendering for indoor scene understanding using convolutional neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5287–5295, 2017.

Chengxu Zhuang, Jonas Kubilius, Mitra JZ Hartmann, and Daniel Yamins. Toward goal-driven neural network models for the rodent whisker-trigeminal system. *Advances in Neural Information Processing Systems*, 2017:2556–2566, 2017.

Chengxu Zhuang, Siming Yan, Aran Nayebi, Martin Schrimpf, Michael C Frank, James J DiCarlo, and Daniel LK Yamins. Unsupervised neural network models of the ventral visual stream. *Proceedings of the National Academy of Sciences*, 118(3), 2021.

Davide Zoccolan, Nadja Oertelt, James J DiCarlo, and David D Cox. A rodent model for the study of invariant visual object recognition. *Proceedings of the National Academy of Sciences*, 106(21): 8748–8753, 2009.

8 Methods

8.1 Neural Response Datasets

We used the Allen Brain Observatory Visual Coding dataset (de Vries et al., 2020; Siegle et al., 2021) collected using both two-photon calcium imaging and Neuropixels from areas VISp (V1), VISl (LM), VISal (AL), VISrl (RL), VISam (AM), and VISpm (PM) in mouse visual cortex. We focused on the natural scene stimuli, consisting of 118 images, each presented 50 times (i.e., 50 trials per image).

We list the number of units and specimens for each dataset in Table S1, after units are selected, according to the following procedure: For the calcium imaging data, we used a similar unit selection criterion as in Conwell et al. (2020), where we subselected units that attain a Spearman-Brown corrected split-half consistency of at least 0.75 (averaged across 100 bootstrapped trials), and whose peak responses to their preferred images are not significantly modulated by the mouse's running speed during stimulus presentation ($p > 0.05$).

For the Neuropixels dataset, we separately averaged, for each specimen and each visual area, the temporal response (at the level of 10-ms bins up to 250 ms) on the largest contiguous time interval when the median (across the population of units in that specimen) split-half consistency reached at least 0.3. This procedure helps to select the most internally-consistent units in their temporally-averaged response, and accounts for the fact that different specimens have different time courses along which their population response becomes reliable.

Finally, after subselecting units according to the above criteria for both datasets, we only keep specimens that have at least the 75th percentile number of units among all specimens for that given visual area. This final step helped to ensure we have enough internally-consistent units per specimen for the inter-animal consistency estimation (derived in Section 8.3).

Dataset Type	Visual Area	Total Units	Total Specimens
Calcium Imaging	VISp	2149	29
	VISl	1425	24
	VISal	583	10
	VISrl	249	9
	VISam	200	9
	VISpm	561	19
Neuropixels	VISp	442	8
	VISl	162	6
	VISal	396	6
	VISrl	299	7
	VISam	257	7
	VISpm	175	5

Table S1: **Descriptive statistics of the neural datasets.** Total number of units and specimens for each visual area for the calcium imaging and Neuropixels datasets.

8.2 Noise Corrected Neural Predictivity

8.2.1 Linear Regression

When we perform neural fits, we choose a random 50% set of natural scene images (59) to train the regression, and the remaining 50% to use as a test set (59), across ten train-test splits total. For Ridge, Lasso, and ElasticNet regression, we use an $\alpha = 1$, following the `sklearn.linear_model` convention. For ElasticNet, we use an `l1_ratio=0.5`. PLS regression was performed with 25 components, as is done by others, such as Yamins et al. (2014); Schrimpf et al. (2018); Zhuang et al. (2021). When we perform regression with the One-to-One mapping, as in Figure 1B, we identify the top correlated (via Pearson correlation on the training images) unit in the source population for each target unit. Once that source unit has been identified, we then fix it for that particular train-test split, evaluated on the remaining 50% of images.

Motivated by the justification given in Section 8.3 for the noise correction in the inter-animal consistency, the noise correction of the model to neural response regression is a special case of the quantity defined in Section 8.3.2, where now the source animal is replaced by model features, separately fit to each target animal (from the set of available animals $\mathcal{A}$). Namely, let L be the set of model layers, let r^ℓ be the set of model responses at model layer $\ell \in L$, and let s be the trial-averaged pseudo-population response.

$$\max_{\ell \in L} \text{median} \bigoplus_{\mathsf{B} \in \mathcal{A}} \left\langle \frac{\text{Corr}\left(M\left(r^\ell_{\text{train}}; \text{s}^{\mathsf{B}}_{1,\text{train}} \right)_{\text{test}}, \text{s}^{\mathsf{B}}_{2,\text{test}} \right)}{\sqrt{\widetilde{\text{Corr}}\left(M\left(r^\ell_{\text{train}}; \text{s}^{\mathsf{B}}_{1,\text{train}} \right)_{\text{test}}, M\left(r^\ell_{\text{train}}; \text{s}^{\mathsf{B}}_{2,\text{train}} \right)_{\text{test}} \right) \times \widetilde{\text{Corr}}\left(\text{s}^{\mathsf{B}}_{1,\text{test}}, \text{s}^{\mathsf{B}}_{2,\text{test}} \right)}} \right\rangle,$$

where the average is taken over 100 bootstrapped split-half trials, $\oplus$ denotes concatenation of units across animals $\mathsf{B} \in \mathcal{A}$ followed by the median value across units.

8.2.2 Representational Similarity Analysis (RSA)

In line with prior work (Shi et al., 2019; Conwell et al., 2020), we also used representational similarity analysis (RSA, Kriegeskorte et al., 2008) to compare models to neural responses, as well as to compare animals to each other. Specifically, we compared (via Pearson correlation) only the upper-right triangles of the representational dissimilarity matrices (RDMs), excluding the diagonals to avoid illusory effects (Ritchie et al., 2017).

For each visual area and a given model, we defined the predictivity of the model for that area to be the maximum RSA score across model layers after the suitable noise correction is applied, which is defined as follows. Let r^ℓ be the model responses at model layer ℓ and let s be the trial-averaged pseudo-population response (i.e., responses aggregated across specimens). The metric used here is a specific instance of Equation (10), where the single source animal A is the trial-wise, deterministic model features (which have a mapping consistency of 1 as a result) and a single target animal B, which is the pseudo-population response:

$$\max_{\ell \in L} \left\langle \frac{\text{RSA}\left(r^\ell, \text{s}_2 \right)}{\sqrt{\widetilde{\text{RSA}}\left(\text{s}_1, \text{s}_2 \right)}} \right\rangle,$$

$$\widetilde{\text{RSA}}\left(\text{s}_1, \text{s}_2 \right) := \frac{2\,\text{RSA}\left(\text{s}_1, \text{s}_2 \right)}{1 + \text{RSA}\left(\text{s}_1, \text{s}_2 \right)},$$

(1)

where L is the set of model layers, $\{s_i\}_{i=1}^2$ are the animal's responses for two halves of the trials (and averaged across the trials dimension), the average is computed over 100 bootstrapped split-half trials, and $\widetilde{\text{RSA}}(s_1, s_2)$ denotes Spearman-Brown correction applied to the internal consistency quantity, $\text{RSA}(s_1, s_2)$, defined in Section 8.3.5.

If the fits are performed separately for each animal, then B corresponds to each animal among those for a given visual area (defined by the set $\mathcal{A}$), and we compute the median across animals $B \in \mathcal{A}$:

$$\max_{\ell \in L} \operatorname*{median}_{B \in \mathcal{A}} \left\langle \frac{\text{RSA}\left(r^\ell, s_2^B\right)}{\sqrt{\widetilde{\text{RSA}}\left(s_1^B, s_2^B\right)}} \right\rangle. \tag{2}$$

Similar to the above, Spearman-Brown correction is applied to the internal consistency quantity, $\text{RSA}\left(s_1^B, s_2^B\right)$.

8.3 Inter-Animal Consistency Derivation

8.3.1 Single Animal Pair

Suppose we have neural responses from two animals A and B. Let t_i^p be the vector of true responses (either at a given time bin or averaged across a set of time bins) of animal $p \in \mathcal{A} = \{A, B, \dots\}$ on stimulus set $i \in \{\text{train}, \text{test}\}$. Of course, we only receive noisy observations of t_i^p, so let $s_{j,i}^p$ be the jth set of n trials of t_i^p. Finally, let $M(x; y)_i$ be the predictions of a mapping M (e.g., PLS) when trained on input x to match output y and tested on stimulus set i. For example, $M\left(t_{\text{train}}^A; t_{\text{train}}^B\right)_{\text{test}}$ is the prediction of mapping M on the test set stimuli trained to match the true neural responses of animal B given, as input, the true neural responses of animal A on the train set stimuli. Similarly, $M\left(s_{1,\text{train}}^A; s_{1,\text{train}}^B\right)_{\text{test}}$ is the prediction of mapping M on the test set stimuli trained to match the trial-average of noisy sample 1 on the train set stimuli of animal B given, as input, the trial-average of noisy sample 1 on the train set stimuli of animal A.

With these definitions in hand, the inter-animal mapping consistency from animal A to animal B corresponds to the following true quantity to be estimated:

$$\text{Corr}\left(M\left(t_{\text{train}}^A; t_{\text{train}}^B\right)_{\text{test}}, t_{\text{test}}^B\right), \tag{3}$$

where $\text{Corr}(\cdot, \cdot)$ is the Pearson correlation across a stimulus set. In what follows, we will argue that Equation (3) can be approximated with the following ratio of measurable quantities, where we split in half and average the noisy trial observations, indexed by 1 and by 2:

$$\text{Corr}\left(M\left(t_{\text{train}}^A; t_{\text{train}}^B\right)_{\text{test}}, t_{\text{test}}^B\right)$$
$$\sim \frac{\text{Corr}\left(M\left(s_{1,\text{train}}^A; s_{1,\text{train}}^B\right)_{\text{test}}, s_{2,\text{test}}^B\right)}{\sqrt{\text{Corr}\left(M\left(s_{1,\text{train}}^A; s_{1,\text{train}}^B\right)_{\text{test}}, M\left(s_{2,\text{train}}^A; s_{2,\text{train}}^B\right)_{\text{test}}\right) \times \text{Corr}\left(s_{1,\text{test}}^B, s_{2,\text{test}}^B\right)}}. \tag{4}$$

In words, the inter-animal consistency (i.e., the quantity on the left side of Equation (4)) corresponds to the predictivity of the mapping on the test set stimuli from animal A to animal B on two different (averaged) halves of noisy trials (i.e., the numerator on the right side of Equation (4)), corrected by the square root of the mapping reliability on animal A's responses to the test set stimuli on two different halves of noisy trials multiplied by the internal consistency of animal B.

We justify the approximation in Equation (4) by gradually replacing the true quantities (t) by their measurable estimates (s), starting from the original quantity in Equation (3). First, we make the approximation that:

$$\text{Corr}\left(M\left(t^A_{\text{train}}; t^B_{\text{train}}\right)_{\text{test}}, s^B_{2,\text{test}}\right) \sim \text{Corr}\left(M\left(t^A_{\text{train}}; t^B_{\text{train}}\right)_{\text{test}}, t^B_{\text{test}}\right) \times \text{Corr}\left(t^B_{\text{test}}, s^B_{2,\text{test}}\right), \quad (5)$$

by the transitivity of positive correlations (which is a reasonable assumption when the number of stimuli is large). Next, by transitivity and normality assumptions in the structure of the noisy estimates and since the number of trials (n) between the two sets is the same, we have that:

$$\text{Corr}\left(s^B_{1,\text{test}}, s^B_{2,\text{test}}\right) \sim \text{Corr}\left(s^B_{1,\text{test}}, t^B_{\text{test}}\right) \times \text{Corr}\left(t^B_{\text{test}}, s^B_{2,\text{test}}\right)$$

$$\sim \text{Corr}\left(t^B_{\text{test}}, s^B_{2,\text{test}}\right)^2. \quad (6)$$

In words, Equation (6) states that the correlation between the average of two sets of noisy observations of n trials each is approximately the square of the correlation between the true value and average of one set of n noisy trials. Therefore, combining Equations (5) and (6), it follows that:

$$\text{Corr}\left(M\left(t^A_{\text{train}}; t^B_{\text{train}}\right)_{\text{test}}, t^B_{\text{test}}\right) \sim \frac{\text{Corr}\left(M\left(t^A_{\text{train}}; t^B_{\text{train}}\right)_{\text{test}}, s^B_{2,\text{test}}\right)}{\sqrt{\text{Corr}\left(s^B_{1,\text{test}}, s^B_{2,\text{test}}\right)}}. \quad (7)$$

From the right side of Equation (7), we can see that we have removed t^B_{test}, but we still need to remove the $M\left(t^A_{\text{train}}; t^B_{\text{train}}\right)_{\text{test}}$ term, as this term still contains unmeasurable (i.e., true) quantities. We apply the same two steps, described above, by analogy, though these approximations may not always be true (they are, however, true for Gaussian noise):

$$\text{Corr}\left(M\left(s^A_{1,\text{train}}; s^B_{1,\text{train}}\right)_{\text{test}}, s^B_{2,\text{test}}\right) \sim \text{Corr}\left(s^B_{2,\text{test}}, M\left(t^A_{\text{train}}; t^B_{\text{train}}\right)_{\text{test}}\right)$$

$$\times \text{Corr}\left(M\left(t^A_{\text{train}}; t^B_{\text{train}}\right)_{\text{test}}, M\left(s^A_{1,\text{train}}; s^B_{1,\text{train}}\right)_{\text{test}}\right)$$

$$\text{Corr}\left(M\left(s^A_{1,\text{train}}; s^B_{1,\text{train}}\right)_{\text{test}}, M\left(s^A_{2,\text{train}}; s^B_{2,\text{train}}\right)_{\text{test}}\right)$$

$$\sim \text{Corr}\left(M\left(s^A_{1,\text{train}}; s^B_{1,\text{train}}\right)_{\text{test}}, M\left(t^A_{\text{train}}; t^B_{\text{train}}\right)_{\text{test}}\right)^2,$$

which taken together implies the following:

$$\text{Corr}\left(M\left(t^A_{\text{train}}; t^B_{\text{train}}\right)_{\text{test}}, s^B_{2,\text{test}}\right) \sim \frac{\text{Corr}\left(M\left(s^A_{1,\text{train}}; s^B_{1,\text{train}}\right)_{\text{test}}, s^B_{2,\text{test}}\right)}{\sqrt{\text{Corr}\left(M\left(s^A_{1,\text{train}}; s^B_{1,\text{train}}\right)_{\text{test}}, M\left(s^A_{2,\text{train}}; s^B_{2,\text{train}}\right)_{\text{test}}\right)}}. \quad (8)$$

Equations (7) and (8) together imply the final estimated quantity given in Equation (4).

8.3.2 Multiple Animals

For multiple animals, we consider the average of the true quantity for each target in B in Equation (3) across source animals A in the ordered pair (A, B) of animals A and B:

$$\left\langle \text{Corr}\left(M\left(t^A_{\text{train}}; t^B_{\text{train}}\right)_{\text{test}}, t^B_{\text{test}}\right)\right\rangle_{A\in\mathcal{A}:(A,B)\in\mathcal{A}\times\mathcal{A}}$$

$$\sim \left\langle \frac{\text{Corr}\left(M\left(s^A_{1,\text{train}}; s^B_{1,\text{train}}\right)_{\text{test}}, s^B_{2,\text{test}}\right)}{\sqrt{\widetilde{\text{Corr}}\left(M\left(s^A_{1,\text{train}}; s^B_{1,\text{train}}\right)_{\text{test}}, M\left(s^A_{2,\text{train}}; s^B_{2,\text{train}}\right)_{\text{test}}\right) \times \widetilde{\text{Corr}}\left(s^B_{1,\text{test}}, s^B_{2,\text{test}}\right)}} \right\rangle_{A\in\mathcal{A}:(A,B)\in\mathcal{A}\times\mathcal{A}}.$$

We also bootstrap across trials, and have multiple train/test splits, in which case the average on the right hand side of the equation includes averages across these as well.

Note that each neuron in our analysis will have this single average value associated with it when *it* was a target animal (B), averaged over source animals/subsampled source neurons, bootstrapped trials, and train/test splits. This yields a vector of these average values, which we can take median and standard error of the mean (s.e.m.) over, as we do with standard explained variance metrics.

8.3.3 RSA

We can extend the above derivations to other commonly used metrics for comparing representations that involve correlation. Since $\mathsf{RSA}(x, y) := \mathsf{Corr}(\mathsf{RDM}(x), \mathsf{RDM}(y))$, then the corresponding quantity in Equation (4) analogously (by transitivity of positive correlations) becomes:

$$
\left\langle \mathsf{RSA}\left(M\left(t^{\mathsf{A}}_{\text{train}}; t^{\mathsf{B}}_{\text{train}} \right)_{\text{test}}, t^{\mathsf{B}}_{\text{test}} \right) \right\rangle_{\mathsf{A}\in\mathcal{A}:(\mathsf{A},\mathsf{B})\in\mathcal{A}\times\mathcal{A}}
$$

$$
\sim \left\langle \frac{\mathsf{RSA}\left(M\left(s^{\mathsf{A}}_{1,\text{train}}; s^{\mathsf{B}}_{1,\text{train}} \right)_{\text{test}}, s^{\mathsf{B}}_{2,\text{test}} \right)}{\sqrt{\widetilde{\mathsf{RSA}}\left(M\left(s^{\mathsf{A}}_{1,\text{train}}; s^{\mathsf{B}}_{1,\text{train}} \right)_{\text{test}}, M\left(s^{\mathsf{A}}_{2,\text{train}}; s^{\mathsf{B}}_{2,\text{train}} \right)_{\text{test}} \right) \times \widetilde{\mathsf{RSA}}\left(s^{\mathsf{B}}_{1,\text{test}}, s^{\mathsf{B}}_{2,\text{test}} \right)}} \right\rangle_{\mathsf{A}\in\mathcal{A}:(\mathsf{A},\mathsf{B})\in\mathcal{A}\times\mathcal{A}}.
$$

$$(9)$$

Note that in this case, each *animal* (rather than neuron) in our analysis will have this single average value associated with it when *it* was a target animal (B) (since RSA is computed over images and neurons), where the average is over source animals/subsampled source neurons, bootstrapped trials, and train/test splits. This yields a vector of these average values, which we can take median and s.e.m. over, across animals $\mathsf{B} \in \mathcal{A}$.

For RSA, we can use the identity mapping (since RSA is computed over neurons as well, the number of neurons between source and target animal can be different to compare them with the identity mapping). As parameters are not fit, we can choose train = test, so that Equation (9) becomes:

$$
\left\langle \mathsf{RSA}\left(t^{\mathsf{A}}, t^{\mathsf{B}} \right) \right\rangle_{\mathsf{A}\in\mathcal{A}:(\mathsf{A},\mathsf{B})\in\mathcal{A}\times\mathcal{A}} \sim \left\langle \frac{\mathsf{RSA}\left(s^{\mathsf{A}}_1, s^{\mathsf{B}}_2 \right)}{\sqrt{\widetilde{\mathsf{RSA}}\left(s^{\mathsf{A}}_1, s^{\mathsf{A}}_2 \right) \times \widetilde{\mathsf{RSA}}\left(s^{\mathsf{B}}_1, s^{\mathsf{B}}_2 \right)}} \right\rangle_{\mathsf{A}\in\mathcal{A}:(\mathsf{A},\mathsf{B})\in\mathcal{A}\times\mathcal{A}}. \qquad (10)
$$

8.3.4 Pooled Source Animal

Often times, we may not have enough neurons per animal to ensure that the estimated inter-animal consistency in our data closely matches the "true" inter-animal consistency. In order to address this issue, we holdout one animal at a time and compare it to the pseudo-population aggregated across units from the remaining animals, as opposed to computing the consistencies in a pairwise fashion. Thus, B is still the target heldout animal as in the pairwise case, but now the average over A is over a sole "pooled" source animal constructed from the pseudo-population of the remaining animals.

8.3.5 Spearman-Brown Correction

The Spearman-Brown correction can be applied to each of the terms in the denominator individually, as they are each correlations of observations from half the trials of the *same* underlying process

to itself (unlike the numerator). Namely,

$$\widetilde{\mathsf{Corr}}\,(X, Y) := \frac{2\,\mathsf{Corr}\,(X, Y)}{1 + \mathsf{Corr}\,(X, Y)}.$$

Analogously, since $\mathsf{RSA}(X, Y) := \mathsf{Corr}(\mathsf{RDM}(x), \mathsf{RDM}(y))$, then we define

$$\widetilde{\mathsf{RSA}}\,(X, Y) := \widetilde{\mathsf{Corr}}(\mathsf{RDM}(x), \mathsf{RDM}(y))$$
$$= \frac{2\,\mathsf{RSA}\,(X, Y)}{1 + \mathsf{RSA}\,(X, Y)}.$$

8.4   StreamNet Architecture Variants

We developed shallow, multiple-streamed architectures for mouse visual cortex, shown in Figure 2A. There are three main modules in our architecture: shallow, intermediate, and deep. The shallow and deep modules each consist of one convolutional layer and the intermediate module consists of a block of two convolutional layers. Thus, the longest length of the computational graph, excluding the readout module, is four (i.e., $1+2+1$). Depending on the number of parallel streams in the model, the intermediate module would contain multiple branches (in parallel), each receiving input from the shallow module. The outputs of the intermediate modules are then passed through one convolutional operation (deep module). Finally, the outputs of each parallel branch would be summed together, concatenated across the channels dimension, and used as input for the readout module. Table S2 describes the parameters of three model variants, each containing one ($N = 1$), two ($N = 2$), or six ($N = 6$) parallel branches.

Module Name	Output Size	Single ($N = 1$)	Dual ($N = 2$)	Six ($N = 6$)
Input	64×64	N/A	N/A	N/A
Shallow	7×7	$(64, 11, 4, 2)$	$(64, 11, 4, 2)$	$(64, 11, 4, 2)$
Intermediate	3×3	$\begin{bmatrix}(192, 5, 1, 2)\\(384, 3, 1, 1)\end{bmatrix}$	$\begin{bmatrix}(192, 5, 1, 2)\\(384, 3, 1, 1)\end{bmatrix} \times 2$	$\begin{bmatrix}(192, 5, 1, 2)\\(384, 3, 1, 1)\end{bmatrix} \times 6$
Deep	3×3	If inputs are from intermediate: $(256, 3, 1, 1)$, otherwise: $(256, 3, 2, 0)$	If inputs are from intermediate: $(256, 3, 1, 1)$, otherwise: $(256, 3, 2, 0)$	If inputs are from intermediate: $(256, 3, 1, 1)$, otherwise: $(256, 3, 2, 0)$

Table S2: **Neural network parameters and output sizes for the convolutional layers of our StreamNet model variants containing one, two, and six parallel branches in the intermediate module.** One convolutional layer is denoted by a tuple: (number of filters, filter size, stride, padding). A block of convolutional layers is denoted by a list of tuples, where each tuple in the list corresponds to a single convolutional layer. When a list of tuples is followed by "$\times N$", this means that the convolutional parameters for each of the N parallel branches are the same.

8.5   Neural Network Training Objectives

In this section, we briefly describe the supervised and unsupervised objectives that were used to train our models.

8.5.1 Supervised Training Objective

The loss function $\mathcal{L}$ used in supervised training is the cross-entropy loss, defined as follows:

$$\mathcal{L}(\boldsymbol{X}; \boldsymbol{\theta}) = -\frac{1}{N} \sum_{i=1}^{N} \log \left(\frac{\exp(\boldsymbol{X}_i[\boldsymbol{c}_i])}{\sum_{j=0}^{C-1} \exp(\boldsymbol{X}_i[j])} \right), \tag{11}$$

where N is the batch size, C is the number of categories for the dataset, $\boldsymbol{X} \in \mathbb{R}^{N \times C}$ are the model outputs (i.e., logits) for the N images, $\boldsymbol{X}_i \in \mathbb{R}^C$ are the logits for the ith image, $\boldsymbol{c}_i \in [0, C-1]$ is the category index of the ith image (zero-indexed), and $\boldsymbol{\theta}$ are the model parameters. Equation (11) was minimized using stochastic gradient descent (SGD) with momentum (Bottou, 2010).

ImageNet (Deng et al., 2009)   This dataset contains approximately 1.3 million images in the training set and 50 000 images in the validation set. Each image was previously labeled into $C = 1000$ distinct categories.

CIFAR-10 (Krizhevsky et al., 2009)   This dataset contains 50 000 images in the training set and 10 000 images in the validation set. Each image was previously labeled into $C = 10$ distinct categories.

8.5.2 Unsupervised Training Objectives

Sparse Autoencoder (Olshausen and Field, 1996)   The goal of this objective is to reconstruct an image from a sparse image embedding. In order to generate an image reconstruction, we used a mirrored version of each of our StreamNet variants. Concretely, the loss function was defined as follows:

$$\mathcal{L}(\boldsymbol{x}; \boldsymbol{\theta}) = \frac{1}{2 \cdot 64^2} \|f(\boldsymbol{x}) - \boldsymbol{x}\|_2^2 + \frac{\lambda}{128} \|\boldsymbol{v}\|_1, \tag{12}$$

where $\boldsymbol{v} \in \mathbb{R}^{128}$ is the image embedding, f is the (mirrored) model, $f(\boldsymbol{x})$ is the image reconstruction, $\boldsymbol{x}$ is a 64×64 pixels image, λ is the regularization coefficient, and $\boldsymbol{\theta}$ are the model parameters.

Our single-, dual-, and six-stream variants were trained using a batch size of 256 for 100 epochs using SGD with momentum of 0.9 and weight decay of 0.0005. The initial learning rate was set to 0.01 for the single- and dual-stream variants and was set to 0.001 for the six-stream variant. The learning rate was decayed by a factor of 10 at epochs 30, 60, and 90. For all the StreamNet variants, the embedding dimension was set to 128 and the regularization coefficient was set to 0.0005.

Depth Prediction (Zhang et al., 2017)   The goal of this objective is to predict the depth map of an image. We used a synthetically generated dataset of images known as PBRNet (Zhang et al., 2017). It contains approximately 500 000 images and their associated depth maps. Similar to the loss function used in the sparse autoencoder objective, we used a mean-squared loss to train the models. The output (i.e., depth map prediction) was generated using a mirrored version of each of our StreamNet variants. In order to generate the depth map, we appended one final convolutional layer onto the output of the mirrored architecture in order to downsample the three image channels to one image channel. During training, random crops of size 224×224 pixels were applied to the image and depth map (which were both subsequently resized to 64×64 pixels). In addition, both the image and depth map were flipped horizontally with probability 0.5. Finally, prior to the application of the loss function, each depth map was normalized such that the mean and standard deviation across pixels were zero and one respectively.

Each of our single-, dual-, and six-stream variants were trained using a batch size of 256 for 50 epochs using SGD with momentum of 0.9, and weight decay of 0.0001. The initial learning rate was set to 10^{-4} and was decayed by a factor of 10 at epochs 15, 30, and 45.

RotNet (Gidaris et al., 2018)   The goal of this objective is to predict the rotation of an image. Each image of the ImageNet dataset was rotated four ways ($0°$, $90°$, $180°$, $270°$) and the four rotation angles were used as "pseudo-labels" or "categories". The cross-entropy loss was used with these pseudo-labels as the training objective (i.e., Equation (11) with $C = 4$).

Our single-, dual-, and six-stream variants were trained using a batch size of 192 (which is effectively a batch size of $192 \times 4 = 768$ due to the four rotations for each image) for 50 epochs using SGD with nesterov momentum of 0.9, and weight decay of 0.0005. An initial learning rate of 0.01 was decayed by a factor of 10 at epochs 15, 30, and 45.

Instance Recognition (Wu et al., 2018)   The goal of this objective is to be able to differentiate between embeddings of augmentations of one image from embeddings of augmentations of other images. Thus, this objective function is an instance of the class of contrastive objective functions.

A random image augmentation is first performed on each image of the ImageNet dataset (random resized cropping, random grayscale, color jitter, and random horizontal flip). Let $\boldsymbol{x}$ be an image augmentation, and $f(\cdot)$ be the model backbone composed with a one-layer linear multi-layer perceptron (MLP) of size 128. The image is then embedded onto a 128-dimensional unit-sphere as follows:

$$\boldsymbol{z} = f(\boldsymbol{x})/\|f(\boldsymbol{x})\|_2, \qquad \boldsymbol{z} \in \mathbb{R}^{128}.$$

Throughout model training, a memory bank containing embeddings for each image in the training set is maintained (i.e., the size of the memory bank is the same as the size of the training set). The embedding $\boldsymbol{z}$ will be "compared" to a subsample of these embeddings. Concretely, the loss function $\mathcal{L}$ for one image $\boldsymbol{x}$ is defined as follows:

$$h(\boldsymbol{u}) = \frac{\exp(\boldsymbol{u} \cdot \boldsymbol{z}/\tau)/Z}{\exp(\boldsymbol{u} \cdot \boldsymbol{z}/\tau)/Z + (m/N)},$$

$$\mathcal{L}(\boldsymbol{x}; \boldsymbol{\theta}) = -\log h(\boldsymbol{v}) - \sum_{j=1}^{m} \log\left(1 - h(\boldsymbol{v}_j)\right), \tag{13}$$

where $\boldsymbol{v} \in \mathbb{R}^{128}$ is the embedding for image $\boldsymbol{x}$ that is currently stored in the memory bank, N is the size of the memory bank, $m = 4096$ is the number of "negative" samples used, $\{\boldsymbol{v}_j\}_{j=1}^{m}$ are the negative embeddings sampled from the memory bank uniformly, Z is some normalization constant, $\tau = 0.07$ is a temperature hyperparameter, and $\boldsymbol{\theta}$ are the parameters of f. From Equation (13), we see that we want to maximize $h(\boldsymbol{v})$, which corresponds to maximizing the similarity between $\boldsymbol{v}$ and $\boldsymbol{z}$ (recall that $\boldsymbol{z}$ is the embedding for $\boldsymbol{x}$ obtained using f). We can also see that we want to maximize $1 - h(\boldsymbol{v}_j)$ (or minimize $h(\boldsymbol{v}_j)$). This would correspond to minimizing the similarity between $\boldsymbol{v}_j$ and $\boldsymbol{z}$ (recall that $\boldsymbol{v}_j$ are the negative embeddings).

After each iteration of training, the embeddings for the current batch are used to update the memory bank (at their corresponding positions in the memory bank) via a momentum update. Concretely, for image $\boldsymbol{x}$, its embedding in the memory bank $\boldsymbol{v}$ is updated using its current embedding $\boldsymbol{z}$ as follows:

$$\boldsymbol{v} \leftarrow \lambda \boldsymbol{v} + (1 - \lambda)\boldsymbol{z},$$
$$\boldsymbol{v} \leftarrow \boldsymbol{v}/\|\boldsymbol{v}\|_2,$$

where $\lambda = 0.5$ is the momentum coefficient. The second operation on $\boldsymbol{v}$ is used to project $\boldsymbol{v}$ back onto the 128-dimensional unit sphere.

Our single-, dual-, and six-stream variants were trained using a batch size of 256 for 200 epochs using SGD with momentum of 0.9, and weight decay of 0.0005. An initial learning rate of 0.03 was decayed by a factor of 10 at epochs 120 and 160.

SimSiam (Chen and He, 2020) The goal of this objective is to maximize the similarity between the embeddings of two augmentations of the same image. Thus, SimSiam is another instance of the class of contrastive objective functions.

Two random image augmentations (e.g., random resized crop, random horizontal flip, color jitter, random grayscale, and random Gaussian blur) are first generated for each image in the ImageNet dataset. Let $\boldsymbol{x}_1$ and $\boldsymbol{x}_2$ be the two augmentations of the same image, $f(\cdot)$ be the model backbone, $g(\cdot)$ be a three-layer non-linear MLP, and $h(\cdot)$ be a two-layer non-linear MLP. The three-layer MLP has hidden dimensions of 2048, 2048, and 2048. The two-layer MLP has hidden dimensions of 512 and 2048 respectively. Let $\boldsymbol{\theta}$ be the parameters for f, g, and h. The loss function $\mathcal{L}$ for one image $\boldsymbol{x}$ of a batch is defined as follows (recall that $\boldsymbol{x}_1$ and $\boldsymbol{x}_2$ are two augmentations of one image):

$$\boldsymbol{p}_1 = h \circ g \circ f(\boldsymbol{x}_1), \qquad \boldsymbol{p}_2 = h \circ g \circ f(\boldsymbol{x}_2), \qquad \boldsymbol{z}_1 = g \circ f(\boldsymbol{x}_1), \qquad \boldsymbol{z}_2 = g \circ f(\boldsymbol{x}_2),$$

$$\mathcal{L}(\boldsymbol{x}_1, \boldsymbol{x}_2; \boldsymbol{\theta}) = -\frac{1}{2} \left(\frac{\boldsymbol{z}_1 \cdot \boldsymbol{p}_2}{\|\boldsymbol{z}_1\|_2 \|\boldsymbol{p}_2\|_2} + \frac{\boldsymbol{z}_2 \cdot \boldsymbol{p}_1}{\|\boldsymbol{z}_2\|_2 \|\boldsymbol{p}_1\|_2} \right), \tag{14}$$

where $\boldsymbol{z}_1, \boldsymbol{z}_2, \boldsymbol{p}_1, \boldsymbol{p}_2 \in \mathbb{R}^{2048}$. Note that $\boldsymbol{z}_1$ and $\boldsymbol{z}_2$ are treated as constants in this loss function (i.e., the gradients are not back-propagated through $\boldsymbol{z}_1$ and $\boldsymbol{z}_2$). This "stop-gradient" method was key to the success of this objective function.

Our single-, dual-, and six-stream variants were trained using a batch size of 512 for 100 epochs using SGD with momentum of 0.9, and weight decay of 0.0001. An initial learning rate of 0.1 was used, and the learning rate was decayed to 0.0 using a cosine schedule (with no warm-up).

MoCov2 (He et al., 2020; Chen et al., 2020b) The goal of this objective is to be able to distinguish augmentations of one image (i.e., by labeling them as "positive") from augmentations of other images (i.e., by labeling them as "negative"). Intuitively, embeddings of different augmentations of the same image should be more "similar" to each other than to embeddings of augmentations of other images. Thus, this algorithm is another instance of the class of contrastive objective functions and is similar conceptually to instance recognition.

Two image augmentations are first generated for each image in the ImageNet dataset by applying random resized cropping, color jitter, random grayscale, random Gaussian blur, and random horizontal flips. Let $\boldsymbol{x}_1$ and $\boldsymbol{x}_2$ be the two augmentations for one image. Let $f_q(\cdot)$ be a query encoder, which is a model backbone composed with a two-layer non-linear MLP of dimensions 2048 and 128 respectively and let $f_k(\cdot)$ be a key encoder, which has the same architecture as f_q. $\boldsymbol{x}_1$ is encoded by f_q and $\boldsymbol{x}_2$ is encoded by f_k as follows:

$$\boldsymbol{v} = f_q(\boldsymbol{x}_1), \qquad \boldsymbol{k}_0 = f_k(\boldsymbol{x}_2), \qquad \boldsymbol{v}, \boldsymbol{k}_0 \in \mathbb{R}^{128}.$$

During each iteration of training, a dictionary of size K of image embeddings obtained from previous iterations is maintained (i.e., the dimensions of the dictionary are $K \times 128$). The image embeddings in this dictionary are used as "negative" samples. The loss function $\mathcal{L}$ for one image of a batch is defined as follows:

$$\mathcal{L}(\boldsymbol{x}_1, \boldsymbol{x}_2; \boldsymbol{\theta}_q) = -\log \frac{\exp(\boldsymbol{v} \cdot \boldsymbol{k}_0 / \tau)}{\sum_{i=0}^{K} \exp(\boldsymbol{v} \cdot \boldsymbol{k}_i / \tau)}, \tag{15}$$

where $\boldsymbol{\theta}_q$ are the parameters of f_q, $\tau = 0.2$ is a temperature hyperparameter, $K = 65\,536$ is the number of "negative" samples, and $\{\boldsymbol{k}_i\}_{i=1}^{K}$ are the embeddings of the negative samples (i.e., the augmentations for other images which are encoded using f_k, and are stored in the dictionary). From Equation (15), we see that we want to maximize $\boldsymbol{v} \cdot \boldsymbol{k}_0$, which corresponds to maximizing the similarity between the embeddings of the two augmentations of an image.

After each iteration of training, the dictionary of negative samples is enqueued with the embeddings from the most recent iteration, while embeddings that have been in the dictionary for the longest are dequeued. Finally, the parameters $\boldsymbol{\theta}_k$ of f_k are updated via a momentum update, as follows:

$$\boldsymbol{\theta}_k \leftarrow \lambda \boldsymbol{\theta}_k + (1 - \lambda)\boldsymbol{\theta}_q,$$

where $\lambda = 0.999$ is the momentum coefficient. Note that only $\boldsymbol{\theta}_q$ are updated with back-propagation.

Our single-, dual-, and six-stream variants were trained using a batch size of 512 for 200 epochs using SGD with momentum of 0.9, and weight decay of 0.0005. An initial learning rate of 0.06 was used, and the learning rate was decayed to 0.0 using a cosine schedule (with no warm-up).

SimCLR (Chen et al., 2020a) The goal of this objective is conceptually similar to that of Mo-Cov2, where the embeddings of augmentations of one image should be distinguishable from the embeddings of augmentations of other images. Thus, SimCLR is another instance of the class of contrastive objective functions.

Similar to other contrastive objective functions, two image augmentations are first generated for each image in the ImageNet dataset (by using random cropping, random horizontal flips, random color jittering, random grayscaling and random Gaussian blurring). Let $f(\cdot)$ be the model backbone composed with a two-layer non-linear MLP of dimensions 2048 and 128 respectively. The two image augmentations are first embedded into a 128-dimensional space and normalized:

$$\boldsymbol{z}_1 = f(\boldsymbol{x}_1)/\|f(\boldsymbol{x}_1)\|_2, \qquad \boldsymbol{z}_2 = f(\boldsymbol{x}_2)/\|f(\boldsymbol{x}_2)\|_2, \qquad \boldsymbol{z}_1, \boldsymbol{z}_2 \in \mathbb{R}^{128}.$$

The loss function $\mathcal{L}$ for a single pair of augmentations of an image is defined as follows:

$$\mathcal{L}(\boldsymbol{x}_1, \boldsymbol{x}_2; \boldsymbol{\theta}) = -\log \frac{\exp(\boldsymbol{z}_1 \cdot \boldsymbol{z}_2/\tau)}{\sum_{i=1}^{2N} \mathbb{1}[i \neq 1] \exp(\boldsymbol{z}_1 \cdot \boldsymbol{z}_i/\tau)}, \tag{16}$$

where $\tau = 0.1$ is a temperature hyperparameter, N is the batch size, $\mathbb{1}[i \neq 1]$ is equal to 1 if $i \neq 1$ and 0 otherwise, and $\boldsymbol{\theta}$ are the parameters of f. The loss defined in Equation (16) is computed for every pair of images in the batch (including their augmentations) and subsequently averaged.

Our single-, dual-, and six-stream variants were trained using a batch size of 4096 for 200 epochs using layer-wise adaptive rate scaling (LARS, You et al., 2017) with momentum of 0.9, and weight decay of 10^{-6}. An initial learning rate of 4.8 was used and decayed to 0.0 using a cosine schedule. A linear warm-up of 10 epochs was used for the learning rate with warm-up ratio of 0.0001.

8.6 Top-1 Validation Set Performance

8.6.1 Performance of primate models on 224×224 **pixels and** 64×64 **pixels ImageNet**

Here we report the top-1 validation set accuracy of models trained in a supervised manner on 64×64 pixels and 224×224 pixels ImageNet.

Model	Image Size	Objective Function	Top-1 Accuracy
AlexNet	224×224	Supervised (ImageNet)	56.52%
	64×64		36.22%
VGG16	224×224		71.59%
	64×64		58.32%
ResNet-18	224×224		69.76%
	64×64		53.31%

8.6.2 Performance of StreamNet Variants on 64×64 pixels CIFAR-10 and 64×64 pixels ImageNet

Here we report the top-1 validation set accuracy of our model variants trained in a supervised manner on 64×64 pixels CIFAR-10 and ImageNet.

Model	Dataset	Objective Function	Top-1 Accuracy
Single Stream	CIFAR-10	Supervised	76.52%
	ImageNet		34.87%
Dual Stream	CIFAR-10		81.13%
	ImageNet		38.68%
Six Stream	CIFAR-10		78.73%
	ImageNet		34.15%

8.6.3 Transfer Performance of StreamNet Variants on 64×64 pixels ImageNet Under Linear Evaluation for Models Trained with Unsupervised Objectives

In this subsection, we report the top-1 ImageNet validation set performance under linear evaluation for models trained with unsupervised objectives. After training each model on a unsupervised objective, the model backbone weights are then held fixed and a linear readout head is trained on top of the fixed model backbone. In the case where the objective function is "untrained", model parameters were randomly initialized and held fixed while the linear readout head was trained. The image augmentations used during transfer learning were random cropping and random horizontal flipping. The linear readout for every unsupervised model was trained with the cross-entropy loss function (i.e., Equation (11) with $C = 1000$) for 100 epochs, which was minimized using SGD with momentum of 0.9, and weight decay of 10^{-9}. The initial learning rate was set to 0.1 and reduced by a factor of 10 at epochs 30, 60, and 90.

8.7 Evaluating Model Performance on Downstream Visual Tasks

To evaluate transfer performance on downstream visual tasks, we used the activations from the outputs of the shallow, intermediate, and deep modules of our StreamNet variants. We also included the average-pooling layer in all the variants (the model layer prior to the fully-connected readout layer). The dimensionality of the activations was then reduced to 1000 dimensions using principal components analysis (PCA), if the number of features exceeded 1000. PCA was not used if the number of features was less than or equal to 1000. A linear readout on these features was then used to perform five transfer visual tasks.

For the first four object-centric visual tasks (object categorization, pose estimation, position estimation, and size estimation), we used a stimulus set that was used previously in the evaluation of neural network models of the primate visual system (Schrimpf et al., 2018; Rajalingham et al.,

Model	Objective Function	ImageNet Transfer Top-1 Accuracy	Neural Predictivity Neuropixels; Calcium Imaging
Single Stream	Untrained	9.28%	32.76%; 27.49%
	Supervised	34.87%	36.21%; 29.14%
	Autoencoder	10.37%	35.99%; 28.54%
	Depth Prediction	18.04%	33.89%; 27.53%
	RotNet	19.72%	35.63%; 29.13%
	Instance Recognition	21.22%	38.01%; 30.91%
	SimSiam	26.48%	39.19%; 30.05%
	MoCov2	27.63%	39.17%; 29.98%
	SimCLR	22.84%	39.45%; 29.74%
Dual Stream	Untrained	10.85%	33.58%; 28.14%
	Supervised	38.68%	36.07%; 29.24%
	Autoencoder	10.26%	34.97%; 28.27%
	Depth Prediction	19.81%	32.81%; 27.13%
	RotNet	23.29%	35.37%; 28.83%
	Instance Recognition	22.55%	40.06%; 30.84%
	SimSiam	29.21%	40.20%; 30.67%
	MoCov2	31.00%	38.64%; 30.03%
	SimCLR	26.25%	38.03%; 29.75%
Six Stream	Untrained	11.12%	33.74%; 28.29%
	Supervised	34.15%	36.64%; 29.33%
	Autoencoder	9.27%	37.34%; 30.73%
	Depth Prediction	18.27%	33.12%; 27.54%
	RotNet	22.78%	35.49%; 29.00%
	Instance Recognition	26.49%	37.67%; 31.08%
	SimSiam	30.52%	38.17%; 29.88%
	MoCov2	32.70%	37.96%; 29.94%
	SimCLR	28.42%	38.91%; 29.90%
AlexNet	Supervised	36.22%	37.28%; 30.32%
AlexNet	Instance Recognition	16.09%	41.33%; 31.50%
ResNet-18	Supervised	53.31%	35.82%; 28.05%
ResNet-18	Instance Recognition	30.75%	38.99%; 30.02%
VGG16	Supervised	58.32%	31.92%; 26.05%
MouseNet of Shi et al. (2020)	Supervised	37.14%	31.05%; 25.37%
MouseNet Variant	Supervised	39.37%	33.02%; 25.37%

Table S3: **ImageNet top-1 validation set accuracy via linear transfer or via supervised training and neural predictivity.** We summarize here the top-1 accuracy for each unsupervised and supervised model on 64×64 pixels ImageNet as well as their noise-corrected neural predictivity under the PLS map (aggregated across all visual areas). The numbers are plotted in Figure 2C.

2018; Zhuang et al., 2021). The stimulus set consists of objects in various poses (object rotations about the x, y, and z axes), positions (vertical and horizontal coordinates of the object), and sizes, each from eight categories. We then performed five-fold cross-validation on the training split of the low variation image subset ("Var0" and "Var3", defined in Majaj et al., 2015) consisting of 3200 images, and computed the performance (metrics defined below) on the test split of the high variation set ("Var6") consisting of 1280 images. Ten different category-balanced train-test splits were randomly selected, and the performance of the best model layer (averaged across train-test splits) was reported for each model. All images were resized to 64×64 pixels prior to fitting, to account for the visual acuity adjustment. The final non-object-centric task was texture recognition, using the Describable Textures Dataset (Cimpoi et al., 2014).

Object Categorization   We fit a linear support vector classifier to each model layer activations that were transformed via PCA. The regularization parameter,

$$C \in [5 \times 10^{-2}, 5 \times 10^{-1}, 1, 5, 5 \times 10^2, 5 \times 10^3, 5 \times 10^4], \tag{17}$$

was chosen by five-fold cross validation. The categories are Animals, Boats, Cars, Chairs, Faces, Fruits, Planes, and Tables. We reported the classification accuracy average across the ten train-test splits.

Position Estimation   We predicted both the vertical and the horizontal locations of the object center in the image. We used Ridge regression where the regularization parameter

$$\alpha \in [0.01, 0.1, 1, 10]. \tag{18}$$

For each network, we reported the correlation averaged across both locations for the best model layer.

Pose Estimation   This task was similar to the position prediction task except that the prediction target were the z-axis (vertical axis) and the y-axis (horizontal axis) rotations, both of which ranged between -90 degrees and 90 degrees. The $(0, 0, 0)$ angle was defined in a per-category basis and was chosen to make the $(0, 0, 0)$ angle "semantically" consistent across different categories. See Hong et al. (2016) for more details. We used Ridge regression with α chosen from the range in (18).

Size Estimation   The prediction target was the three-dimensional object scale, which was used to generate the image in the rendering process. This target varied between 0.625 to 1.6, which was a relative measure to a fixed canonical size of 1. When objects were at the canonical size, they occluded around 40% of the image on the longest axis. We used Ridge regression with α chosen from the range in (18).

Texture Recognition   We trained linear readouts of the model layers on texture recognition using the Describable Textures Dataset (Cimpoi et al., 2014), which consists of 5640 images organized according to 47 categories, with 120 images per category. We used ten category-balanced train-test splits, provided by their benchmark. Each split consists of 3760 train-set images and 1880 test-set images. A linear support vector classifier was then fit with C chosen in the range (17). We reported the classification accuracy average across the ten train-test splits.

9 Supplemental Figures

Figure S1: **Shallow architectures trained with contrastive objective functions yield the best matches to the neural data (RSA). A**. The median and s.e.m. noise-corrected neural predictivity, using RSA, across $N = 39$ and $N = 100$ animals for the Neuropixels and calcium imaging dataset respectively (across all visual areas). Red denotes our StreamNet models trained on contrastive objective functions, blue denotes our StreamNet models trained on RotNet, turquoise denotes our StreamNet models trained in a supervised manner on ImageNet and on CIFAR-10, green denotes untrained models (random weights), orange denotes our StreamNet models trained depth prediction, purple denotes our StreamNet models trained on autoencoding, brown denotes contrastive AlexNet, pink denotes contrastive ResNet-18 (both trained on instance recognition), black denotes the remaining ImageNet supervised models (primate ventral stream models), and grey denotes the MouseNet of Shi et al. (2020) and our variant of this architecture. **B**. We plot each model's performance on 64×64 pixels ImageNet against its median neural predictivity, using RSA, across visual areas. All ImageNet performance numbers can be found in Table S3. Color scheme as in **A**.

Figure S2: **StreamNet model derivation (calcium imaging dataset). A**. Neural predictivity, using PLS regression, on the calcium imaging dataset across AlexNet architectures trained in two different ways (supervised [orange] and unsupervised [green]). We observe that the first four convolutional layers provide the best fits to the neural data while the latter three layers are not very predictive for any visual area, suggesting that an even shallower architecture may be suitable. **B**. Supervised AlexNet provides the best neural predictivity on the Neuropixels dataset across all six visual areas compared to deeper architectures (to the left of the purple bar). The median and s.e.m. across neurons is reported. Refer to Table S1 for N units per visual area.

Figure S3: **Lower image resolution during model training improves task-optimized neural predictivity.** Light blue bars indicate the maximum noise-corrected neural predictivity, using RSA, on the Neuropixels (top two rows) and calcium imaging (bottom two rows) datasets across model layers for models trained on 224×224 pixels ImageNet images. Dark blue bars indicate the maximum noise-corrected neural predictivity for models trained on 64×64 pixels ImageNet images. The median and s.e.m. across animals in each visual area is reported. Refer to Table S1 for N animals per visual area.

Figure S4: **Lower image resolution during model training improves task-optimized neural predictivity for supervised primate ventral stream models (AlexNet, VGG16, and ResNet-18).** Light blue bars indicate the maximum noise-corrected neural predictivity, using RSA, on the Neuropixels (top two rows) and calcium imaging (bottom two rows) datasets across model layers for models supervised on ImageNet categorization with 224×224 pixels images. Dark blue bars indicate the maximum noise-corrected neural predictivity for models supervised on ImageNet categorization with 64×64 pixels images. The median and s.e.m. across animals in each visual area is reported. Refer to Table S1 for N animals per visual area.

Figure S5: **Comparing AlexNets trained using various image sizes.** When AlexNet is supervised on ImageNet categorization with 224×224 pixels images, its neural predictivity, obtained via PLS regression is equal to or worse than the untrained model (compare blue with green). Supervising AlexNet on ImageNet categorization with 64×64 pixels images improves neural predictivity and surpasses that of the untrained network (compare blue with orange). The top two rows show neural predictivity of the models on the Neuropixels dataset and the bottom two rows show the neural predictivity for the calcium imaging dataset. The median and s.e.m. across neurons is reported. Refer to Table S1 for N units per visual area.