Mouse visual cortex as a limited resource system that self-learns an ecologically-general representation

Aran Nayebi[*]   Nathan C. L. Kong[*]
Chengxu Zhuang   Justin L. Gardner
Anthony M. Norcia   Daniel L. K. Yamins

Stanford University

Abstract

Studies of the mouse visual system have revealed a variety of visual brain areas in a roughly hierarchical arrangement, together with a multitude of behavioral capacities, ranging from stimulus-reward associations, to goal-directed navigation, and object-centric discriminations. However, an overall understanding of the mouse's visual cortex organization, and how this organization supports visual behaviors, remains unknown. Here, we take a computational approach to help address these questions, providing a high-fidelity quantitative model of mouse visual cortex. By analyzing factors contributing to model fidelity, we identified key principles underlying the organization of mouse visual cortex. Structurally, we find that comparatively low-resolution and shallow structure were both important for model correctness. Functionally, we find that models trained with task-agnostic, unsupervised objective functions, based on the concept of contrastive embeddings were substantially better than models trained with supervised objectives. Finally, the unsupervised objective builds a general-purpose visual representation that enables the system to achieve better transfer on out-of-distribution visual, scene understanding and reward-based navigation tasks. Our results suggest that mouse visual cortex is a low-resolution, shallow network that makes best use of the mouse's limited resources to create a light-weight, general-purpose visual system – in contrast to the deep, high-resolution, and more task-specific visual system of primates.

1 Introduction

The mouse has become an indispensable model organism in systems neuroscience, allowing unprecedented genetic and experimental control at the level of cell-type specificity in individual circuits (Huberman and Niell, 2011). Beyond fine-grained control, studies of mouse visual behavior have revealed a multitude of abilities, ranging from stimulus-reward associations, to goal-directed navigation, and object-centric discriminations (Glickfeld and Olsen, 2017). These behaviors suggest that the mouse visual system is capable of supporting higher-order functions, and providing evidence that higher visual cortical areas might subserve such behaviors. A natural question, therefore, is what these populations of neurons code for during visually-guided behaviors. Formal computational models are needed to test these hypotheses: if optimizing a model for a certain task leads to accurate predictions of neural responses, then that task may provide a unified, normative account for why those population responses occur in the brain. Moreover, with a stimulus-computable model, we can assess the *functional* similarities and differences between rodent and

---

[*]Equal contribution. Correspondence: {`anayebi;nclkong`}@stanford.edu.

primate visual cortex, which otherwise would be hard to capture in the absence of a model from prior literature, beyond failures to be homologous in higher visual areas past V1. Finally, in addition to a normative account of rodent vision, the experimental tractability of this animal model naturally leads to the consideration of "integrated" studies of higher-level processing downstream of visual processing, such as in memory and its role in navigation (O'Keefe and Dostrovsky, 1971; Hafting et al., 2005; Kropff et al., 2015; Solstad et al., 2008; Sargolini et al., 2006). Studying higher cognition and motor control in rodents will therefore critically depend on an understanding of the upstream sensory areas that they depend on.

Deep convolutional neural networks (CNNs) are a class of models that have had immense success as predictive models of the human and non-human primate ventral visual stream, even when animals were merely fixating (e.g., Yamins et al., 2014; Khaligh-Razavi and Kriegeskorte, 2014; Güçlü and van Gerven, 2015; Cichy et al., 2016; Cadena et al., 2019a; Bashivan et al., 2019). In contrast with the strong correspondence between task-optimized CNNs and the primate visual system, these CNNs are poor predictors of neural responses in mouse visual cortex (Cadena et al., 2019b).

Three fundamental problems, each grounded in the goal-driven modeling approach (Yamins and DiCarlo, 2016), confront these primate ventral stream models as potential models of the mouse visual system. Firstly, they are trained in a supervised manner on ImageNet (Schrimpf et al., 2018; Conwell et al., 2020), which is an image set containing over one million images belonging to one thousand, mostly human-relevant, semantic categories (Deng et al., 2009). While such a dataset is an important technical tool for machine learning, it is highly implausible as a biological model particularly for rodents, who do not receive such category labels over development. Secondly, these models are too deep to be plausible models of the mouse visual system, since mouse visual cortex is known to be more parallel and much shallower than primate visual cortex (Harris et al., 2019; Siegle et al., 2021; Felleman and Van Essen, 1991; Gămănuţ and Shimaoka, 2021). Finally, mice are known to have lower visual acuity than that of primates (Prusky et al., 2000; Kiorpes, 2019), suggesting that the resolution of the inputs to mouse models should be lower than that of the inputs to primate models. Given these three differences between the visual system of primates and of mice, one cannot simply use current supervised primate ventral stream models as models of the mouse visual system.

The failure of these current models may therefore be tied to a failure in the application of the principles of goal-driven modeling to mouse vision, having to do with a mismatch between the model's architecture and task and those of the system being investigated. We addressed these three differences between the primate and mouse visual system by training shallower CNN architectures in an unsupervised manner using lower-resolution images. We also "implant" this model as the visual front-end of a bio-mechanically realistic virtual rodent operating in an environment that supports spatially-extended reward-based navigation, finding improved transfer performance across environments, illustrating the congruence between the task-transfer performance and improved neural fidelity of the computational model.

Taken together, our best models of the mouse visual system suggest that it is a shallower, general-purpose system operating on comparatively low-resolution inputs. These identified factors therefore provide interpretable insight into the confluence of constraints that may have given rise to the system in the first place, suggesting that these factors were crucially important given the ecological niche in which the mouse is situated, and the resource limitations to which it is subject.

2 Determining the animal-to-animal mapping transform

How should artificial neural network responses be mapped to biological neural responses? What firing patterns of mouse visual areas are common across multiple animals, and thus worthy of computational explanation? A natural approach would be to map artificial neural network features to mouse neural responses in the same manner that different animals can be mapped to each other. Specifically, we aimed to identify the best performing class of similarity transforms needed to map the firing patterns of one animal's neural population to that of another, which we denote as the "inter-animal consistency". We took inspiration from methods that have proven useful in modeling human and non-human primate visual, auditory, and motor cortices (Yamins and DiCarlo, 2016; Kell et al., 2018; Michaels et al., 2020; Nayebi et al., 2022). As with other cortical areas, this transform class likely cannot be so strict as to require fixed neuron-to-neuron mappings between cells. However, the transform class for each visual area also cannot be so loose as to allow an unconstrained nonlinear mapping, since the model already yields an image-computable nonlinear response.

We explored a variety of linear mapping transform classes (fit with different constraints) between the population responses for each mouse visual area (Figure 1A). The mouse visual responses to natural scenes were collected previously using both two-photon calcium imaging and Neuropixels by the Allen Institute (de Vries et al., 2020; Siegle et al., 2021). For all methods, the corresponding mapping was trained on 50% of all the natural scene images, and evaluated on the remaining held-out set of images. We also included representational similarity analyses (RSA, Kriegeskorte et al., 2008) as a baseline measure of population-wide similarity across animals, corresponding to no selection of individual units, unlike the other mapping transforms. For the strictest mapping transform (One-to-One), each target unit was mapped to the single most correlated unit in the source animal. Overall, the One-to-One mapping tended to yield the lowest inter-animal consistency among the maps considered. However, Ridge regression (L2-regularized) and Partial Least Squares (PLS) regression were more effective at the inter-animal mapping, yielding the most consistent fits across visual areas, with PLS regression providing the highest inter-animal consistency. We therefore used PLS regression in the evaluation of a candidate model's ability to predict neural responses.

Under all mapping transforms, a log-linear extrapolation analysis (Figure S6) reveals that as the number of units increases, the inter-animal consistency approaches 1.0 more rapidly for the Neuropixels dataset, than the calcium imaging dataset, indicating the higher reliability of the Neuropixels data. We further noticed a large difference between the inter-animal consistency obtained via RSA and the consistencies achieved by any of the other mapping transforms for the responses in RL of the calcium imaging dataset (green in Figure 1A). This difference, however, was not observed for responses in RL in the Neuropixels dataset. This discrepancy suggested that there was a high degree of population-level heterogeneity in the responses collected from the calcium imaging dataset, which may be attributed to the fact that the two-photon field-of-view for RL spanned the boundary between the visual and somatosensory cortex, as originally noted by de Vries et al. (2020). We therefore excluded it from further analyses, following Siegle et al. (2020), who systematically compared these two datasets. Thus, this analysis provided insight into the experiments from which the data were collected.

We next sought to describe the *functional* hierarchical grouping of the visual areas in the data by computing how well responses in one visual area can be predicted, via a linear transform (PLS regression), by responses in other visual areas. The intuition is that if responses in one visual area are well approximated, after a linear transform, by responses in another visual area, then the two visual areas can be considered functionally similar. Based on the analysis of the split-half reliability

over time (using the Neuropixels dataset) for each visual area, we expected that there should be roughly three to four groups of visual areas (Figure 1B). This was corroborated by the groupings observed in a matrix that summarized how well neural responses in a target visual area could be predicted by neural responses in a source visual area (Figure 1C). Each visual area was predicted well by the corresponding visual area in the other animals, but AL, PM, and AM were similarly predicted by each other. Thus, the visual areas could be qualitatively grouped as: V1, LM, RL, and (AL, PM, AM). This is largely consistent with the grouping of visual areas obtained using other measures of a visual area's hierarchical level (c.f. Figure 4e in D'Souza et al., 2022).

To quantify this intuition, we visualized the relationships between the visual areas via a two-dimensional multi-dimensional scaling (MDS) embedding of the matrix in Figure 1C, where we observed that the visual areas clustered into roughly four groups (Figure 1D). The two-dimensional MDS embedding also implicitly encodes a hierarchy, which can be extracted via a one-dimensional principal component analysis (PCA) embedding. We found that the one-dimensional embedding obtained via PCA correlates with the hierarchy scores described by Siegle et al. (2021) (Figure 1E). Thus, the two-dimensional MDS embedding of the visual areas can be used as a metric of hierarchical consistency by which candidate models can be evaluated.

The three- to four-level hierarchy motivated our development of a novel class of architectures, denoted as "StreamNet", that consists of four convolutional layers. We set the number of parallel streams, N, to be one ("single-stream"), two ("dual-stream"), and six ("six-stream", treating each intermediate visual area as roughly its own stream). We additionally included dense skip connections from shallow levels to deeper levels, known from the feedforward connectivity of the mouse connectome (Harris et al., 2016; Knox et al., 2018). A schematic of the StreamNet architecture is shown in Figure S1.

Overall, the animal-to-animal mapping analyses of the neural data allow us to: (i) ascertain the level of neural response variance that is common across animals and that therefore should be "explained" by candidate models and (ii) assess the hierarchical consistency of candidate models by evaluating their two-dimensional MDS embedding of the visual areas with respect to that of the data.

3   Modeling mouse visual cortex

3.1   Quantitatively accurate models

Building on the idea that prior models of mouse visual cortex can be improved in three primary ways, we proceeded to better match these ingredients to the structure and function of mouse visual cortex. Having established a consistent similarity transform class between animals across visual areas (PLS regression), we mapped artificial neural network responses, which varied in these three factors, to mouse neural response patterns under this transform class. The overall conclusion that the mouse visual system is most consistent with an artificial neural network model that is unsupervised, low-resolution, and comparatively shallow. This model (AlexNet, trained using a powerful contrastive[1], unsupervised algorithm) approaches 90% of the inter-animal consistency, significantly improving over the prior high-resolution, deep, and task-specific models (VGG16) which attained only 56.27% of this ceiling (Figure 2). In the subsequent subsections, we distill the three factors that contributed to the improved correspondence between models and the mouse visual areas: input resolution, objective function, and architecture.

---

[1]Unless otherwise noted, "contrastive" will refer specifically to the instance recognition algorithm (Wu et al., 2018), for simplicity.

Figure 1: **Quantifying neural response consistency and functional hierarchy in mouse visual cortex. A**. Inter-animal consistency was computed using different linear maps, showing that PLS regression provides the highest consistency. Horizontal bars at the top are the median and s.e.m. of the internal consistencies of the neurons in each visual area. Refer to Table S1 for N units per visual area. **B**. The fraction of maximum split-half reliability is plotted as a function of time (in 10-ms time bins) for each visual area. The time-series show that the visual areas can be grouped into roughly three to four modules based on the timing of the responses. **C**. Each entry in the matrix denotes the median neural predictivity across units for the pairwise mapping performed between a source and a target visual area of the Neuropixels dataset (and between animals, as in panel **A**). **D**. A two-dimensional projection was computed on the neural predictivity values in the matrix shown in panel **B** using multi-dimensional scaling (MDS). The MDS embedding suggests that the visual areas can be functionally grouped into roughly three to four modules. **E**. The two-dimensional MDS embedding can then be projected onto a line using principal components analysis. Using the values on this line (in arbitrary units), one can compute the Pearson's correlation between the implicit (functional) hierarchy scores from the MDS embeddings and the hierarchy scores from Figure 2A of Siegle et al. (2021).

Figure 2: **Substantially improving neural response predictivity of models of mouse visual cortex.** The median and s.e.m. neural predictivity, using PLS regression, across units in all mouse visual areas. $N = 1731$ units in total. Red denotes our StreamNet models trained on contrastive objective functions, blue denotes these models trained on RotNet, turquoise denotes these models trained in a supervised manner on ImageNet and on CIFAR-10, green denotes untrained models (random weights), orange denotes our StreamNet models trained depth prediction, purple denotes these models trained on autoencoding, brown denotes contrastive AlexNet, pink denotes contrastive primate models (VGG16, ResNets; all of which are trained using instance recognition), black denotes the remaining ImageNet supervised models (primate ventral stream models), and grey denotes the MouseNet of Shi et al. (2020) and our variant of this architecture. Absolute neural predictivity can be found in Table S3.

3.2 Data stream: Training models on images of lower resolution improves correspondence to mouse visual areas

The visual acuity of mice is known to be lower than the visual acuity of primates (Prusky et al., 2000; Kiorpes, 2019). Here we investigated how neural predictivity of two of the best models (Contrastive AlexNet and Contrastive StreamNet; see Figure 2) varied as a function of the image resolution at which they were trained. The Contrastive StreamNet model was trained using a contrastive objective function (instance recognition) at image resolutions that varied from 32×32 pixels to 224×224 pixels. Similarly, we trained AlexNet on instance recognition using image resolutions that varied from 64×64 pixels to 224×224 pixels. 64×64 pixels was the minimum image size for AlexNet due to its final max-pooling layer. In both cases, 224×224 pixels is the image resolution that is typically used to train neural network models of the primate ventral visual stream.

Training models using resolutions lower than what is used for primate vision models improves neural predictivity across all visual areas (Figure 3A). Furthermore, this led to functional differences in the convolutional operations of the models, in terms of spatial frequency and orientation tuning preferences (Figure S7). Although the input resolution of 64×64 pixels may not be optimal for different architectures, it is the resolution that we used to train all the models. This was motivated by the observation that the upper bound on mouse visual acuity is 0.5 cycles / degree (Prusky et al., 2000), corresponding to 2 pixels / cycle $\times$ 0.5 cycles / degree = 1 pixel / degree, so that a simplified correction for the appropriate visual acuity would correspond to 64×64 pixels, which was also used in Shi et al. (2019) and in the MouseNet of Shi et al. (2020). A more thorough investigation into the appropriate image transformations, however, may be needed.

Overall, these results show that objective function optimization using a simple change in the image statistics (i.e., data stream) is crucial to obtain an improved models of mouse visual encoding. This further suggests that mouse visual encoding is the result of task-optimization at a lower "visual acuity" than what is typically used for primate ventral stream models.

3.3 Objective function: Training models on unsupervised, contrastive objectives, instead of supervised objectives, improves correspondence to mouse visual areas

Training neural network models on 1000-way ImageNet categorization is useful for obtaining visual representations that are well-matched to those of the primate ventral visual stream (Schrimpf et al., 2018; Zhuang et al., 2021) and seems to result in the best *supervised* models for mouse visual cortex (Conwell et al., 2020). However, it is unclear that rodents can perform well on large-scale object recognition tasks when trained (attaining approximately 70% on a two-alternative forced-choice object classification task, Froudarakis et al., 2020), such as those where there are hundreds of labels. Furthermore, the categories of the ImageNet dataset are rather human-centric and therefore not entirely ecologically relevant for rodents to begin with.

We therefore considered unsupervised objective functions instead, as these may provide more general goals for the models beyond the specifics of (human-centric) object categorization. Advances in computer vision have yielded algorithms that are powerful unsupervised visual representation learners, and models trained in those ways have been shown to be quantitatively accurate models of the primate ventral visual stream (Zhuang et al., 2021). Reducing the image size during task training based on rodent visual acuity, which we show in Section 3.2 to be important to provide good neural predictivity when controlling for task and architecture, further set a constraint on the type of unsupervised algorithms we considered. Specifically, algorithms that involved crops were unlikely candidates, as the resultant crop would be too small to be effective or too small to have non-trivial features downstream of the network due to the architecture (e.g., relative location

Figure 3: **Structural and functional factors leading to improved neural response predictivity (Neuropixels dataset).** **A**. Contrastive AlexNet and Contrastive StreamNet (Dual Stream) were trained using images of increasing resolutions. For AlexNet, the minimum resolution was 64×64 pixels. For Dual StreamNet, the minimum resolution was 32×32 pixels. The median and s.e.m. neural predictivity across all units of all visual areas is plotted against the image resolution at which the models were trained. Reducing the image resolution (but not beyond a certain point) during representation learning improves the match to all the visual areas. **B**. For each visual area, the neural predictivity values are plotted across all model layers for an untrained AlexNet, supervised (ImageNet) AlexNet and contrastive AlexNet (ImageNet, instance recognition). Training a model on a contrastive objective improves neural predictivity across all visual areas. Note that these models were trained on images of size 64×64 pixels. Shaded regions denote mean and s.e.m. across units.

prediction or contrastive predictive coding (CPC) for static images, Doersch et al., 2015; Oord et al., 2018). We instead considered objective functions that use image statistics from the *entire* image. As control models, we used relatively less powerful unsupervised algorithms including the sparse autoencoder (Olshausen and Field, 1996), depth-map prediction, and image-rotation prediction (RotNet, Gidaris et al., 2018). Advances in unsupervised learning have shown that training models on contrastive objective functions yields representations that can support strong performance on downstream object categorization tasks. Thus, the remaining four algorithms we used were from the family of contrastive objective functions: instance recognition (IR, Wu et al., 2018), simple framework for contrastive learning (SimCLR, Chen et al., 2020a), momentum contrast (MoCov2, Chen et al., 2020b), and simple siamese representation learning (SimSiam, Chen and He, 2020).

At a high-level, the goal of these contrastive objectives is to learn a representational space where embeddings of augmentations for one image (i.e., embeddings for two transformations of the *same* image) are more "similar" to each other than to embeddings of other images. Models trained with these contrastive objectives resulted in higher neural predictivity across all the visual areas than a model trained on supervised object categorization and weaker unsupervised algorithms (compare red vs. blue, purple, turquoise, and orange in Figure 2).

We hone in on the contribution of the contrastive objective function (over a supervised objective) to neural predictivity by fixing the architecture to be AlexNet (the best model in terms of neural predictivity shown in Figure 2), while varying the objective function. Across all the visual areas, there is an improvement in neural predictivity simply by using a powerful contrastive algorithm (brown vs. black in Figure 3B).

3.4 Architecture: Very deep models perform poorly on the hierarchical consistency metric

The mouse visual system has a shallower hierarchy relative to that of the primate visual system (Harris et al., 2019; Siegle et al., 2021; Felleman and Van Essen, 1991; Gămănuţ and Shimaoka, 2021). For each candidate model, we performed an MDS analysis on the median neural predictivity (across units) of each visual area across model layers, similar to the analysis performed on the data itself, presented in Figure 1D. Each model is therefore associated with a two-dimensional embedding of the six visual areas. Using the two-dimensional MDS embedding of the data itself, we defined the hierarchical consistency metric as follows: first, the squared Euclidean distance between the model's embedding of the visual area and the data's embedding of the visual area is computed. Next, the hierarchical consistency metric is calculated by taking the square-root of the sum of the distances for all six visual areas and subtracting it from one. Thus, higher values of the hierarchical consistency metric indicate better consistency of the model to the data.

Hierarchical consistency for all the models are shown in Figure 4A, capturing the intuition that models with many linear-nonlinear operations should not be used as a proxy of (a comparatively hierarchically shallow) mouse visual cortex. Specifically, we found that models with over 50 linear-nonlinear operations (ResNet-50, ResNet-101, and ResNet-152) performed poorly on this metric, whereas models with an order of magnitude less operations perform better on this metric (e.g., AlexNet and StreamNets). Intriguingly, the MouseNet of Shi et al. (2020) (gray in Figure 4A), which is a model with multiple parallel pathways based on information provided by large-scale tract tracing data, performs the best on the hierarchical consistency metric This shows that performing well on our metric for hierarchical consistency is captured by models that are appropriately (biologically) constrained architecturally.

By plotting a model's neural predictivity against its hierarchical consistency, we found that the two metrics were not strongly correlated ($R = -0.17$, $p = 0.27$), suggesting that they each cap-

ture different aspects of the neural data: functional response variance and hierarchical consistency (Figure 4B). Further evident from Figure 4B is the fact that the contrastive AlexNet model (brown) is roughly optimal on both metrics, as it lies in the upper-right portion of the plot. Altogether, although models with a comparatively large number of linear-nonlinear computations perform well on the neural predictivity metric, the hierarchical consistency metric is able to penalize those models for having too many of those sequential computations.

Figure 4: **Quantifying hierarchical consistency of models with functional hierarchy of mouse visual cortex. A**. Larger hierarchical consistency scores (models to the left) indicate better matches between the functional grouping of the visual areas obtained from model predictions and the functional grouping obtained from the animal-to-animal predictions. The deepest (supervised and unsupervised) models (e.g., ResNet-50, ResNet-101, and ResNet-152) perform the worst on this metric (rightmost bars). Error bars denote the standard deviation of the hierarchical consistency score across the train-test image splits. **B**. A model's hierarchical consistency score is plotted against its neural predictivity, showing that the two metrics are uncorrelated and are therefore capturing different variance in the data. The sizes of the dots indicate (relative) model depth (i.e., larger dots indicate deeper models). Models that perform the best on both metrics lie in the upper-right corner of the scatter plot, showing that contrastive AlexNet (brown dot) is roughly optimal on both metrics. Although the deepest models perform relatively well on the neural predictivity metric, they fail to capture the two-dimensional MDS projection of the visual areas (pink and black dots in the upper-left corner).

4 Mouse visual cortex as a general-purpose visual system

Our results show that optimizing for a contrastive unsupervised objective generates representations with substantially better quantitative match to the mouse visual system than a wide variety of alternatives. However, unlike supervised object categorization or other more-classical forms of unsupervised learning such as sparse autoencoding, whose ecological function is directly encoded in the loss function (e.g., predator recognition or metabolically-efficient dimension reduction), the functional utility of contrastive self-supervision is not as readily apparent. This naturally raises the question of what behavioral function(s) optimizing a contrastive self-supervision objective might enable for the mouse from an ecological fitness viewpoint.

Analyzing the spectrum of models described in the above section, we first observed that performance on ImageNet categorization is uncorrelated with improved neural predictivity for mouse

visual cortex (Figure 5A). In seeking an interpretation of the biological function of the contrastive unsupervised objective, we were thus prompted to consider behaviors beyond object-centric categorization tasks. We hypothesized that since unsupervised loss functions are typically most effective in task-agnostic stimulus domains where goal-specific labels are unavailable, optimizing for such an objective might enable the rodent to *transfer* well to complex multi-faceted ecological tasks in novel domains affording few targeted opportunities for hyper-specialization.

To test this hypothesis, we utilized a recently-developed "virtual rodent" framework (adapted from Merel et al., 2020), in which a biomechanically-validated mouse model is placed in a simulated 3D maze-like environment (Figure 5B). We used the optimally neurally-consistent low-resolution shallow model architecture (64px AlexNet) as the visual system of the simulated mouse, coupled to a simple actor-critic reinforcement-learning architecture (Figure 5C). We then trained the simulated mouse in several visual contexts with varying objective functions, and evaluated those models' ability to *transfer* to a variety of tasks in novel environments, including both a reward-based navigation task, as well as several object-centric visual categorization and estimation tasks (Figure 5D).

We first evaluated a simulated mouse whose visual system was pretrained with ImageNet images in terms of its ability to transfer to reward-based navigation in the "DM Locomotion Rodent Mazes" environment, training just the reinforcement learning portion of the network on the navigation task with the pretrained visual system held constant. As a supervised control, we performed the same transfer training procedure using a visual front-end created using supervised (ImageNet) object categorization pretraining. We found that the simulated mouse with the contrastive unsupervised visual representation was able to reliably obtain substantially higher navigation rewards than its counterpart with category-supervised visual representation (Figure 5D; top left panel).

Conversely, we then trained the simulated mouse directly in the "Rodent Mazes" environment. In one variant, we trained the visual system on the contrastive unsupervised objective (but on the images of the "Rodent Mazes" environment). In a second variant, we trained the agent end-to-end on the reward navigation task itself – the equivalent of "supervision" in the "Rodent Mazes" environment. We then tested both models on their ability to transfer to out-of-sample visual categorization and estimation tasks. Again, we found that the unsupervised variant transfers significantly better than its "supervised" counterpart (blue vs. purple bars in Figure 5D).

Returning to analyses of neural predictivity, we found that both unsupervised models (trained in either environment) were better matches to mouse visual cortex neurons than the supervised counterparts in their respective environments (brown vs. black and blue vs. purple in Figure 5E). This results illustrates the congruence between the task-transfer performance and improved neural fidelity of the computational model. It is also noteworthy that, comparing models by training environment rather than objective function, the ImageNet-trained models produce more neurally-consistent models than the "Rodent Mazes"-trained models, both for supervised and unsupervised objectives. Using the contrastive unsupervised objective function is by itself enough to raise the "Rodent Mazes"-trained model to the predictivity level of the ImageNet-trained supervised model, but the training environment makes an independent significant contribution. This suggests that while the task domain and biomechanical model of the "Rodent Mazes" environment are realistic, future work will likely need to improve the realism of the the simulated image distribution.

Overall, these results suggest that contrastive embedding methods have achieved a generalized improvement in the quality of the visual representations they create, enabling a diverse range of visual behaviors, providing evidence for their potential as computational models of mouse visual cortex.

Figure 5: **Unsupervised, contrastive visual representations better support transfer performance on downstream, out-of-distribution tasks.** **A**. Each model's (transfer or supervised) performance on ImageNet is plotted against its median neural predictivity across all units from each visual area. All ImageNet performance values can be found in Table S3. Color scheme as in Figure 2A. See Figure S2 for neural predictivity on the calcium imaging dataset. **B**. Each row shows an example of an episode used to train the reinforcement learning (RL) policy in an offline fashion (Wang et al., 2020). The episodes used to train the virtual rodent (adapted from Merel et al., 2020) were previously generated and are part of a larger suite of RL tasks for benchmarking algorithms (Gulcehre et al., 2020). In this task, the goal of the agent is to navigate the maze to collect as many rewards as possible (blue orbs shown in the first row). **C**. A schematic of the RL agent. The egocentric visual input is fed into the visual backbone of the model, which is fixed to be the first four convolutional layers of either the contrastive or the supervised variants of AlexNet. The output of the visual encoder is then concatenated with the virtual rodent's proprioceptive inputs before being fed into the (recurrent) critic and policy heads. The parameters of the visual encoder are *not* trained, while the parameters of the critic head and the policy head are trained. **D**. Models trained in a contrastive manner (using either ImageNet or the egocentric maze inputs) lead to better transfer on out-of-distribution downstream tasks (i.e., trained on ImageNet, tested on reward-based navigation; trained on reward-based navigation inputs, tested on object-centric tasks) than models trained in a supervised manner (i.e., models supervised on labels or on rewards). **E**. Median and s.e.m. neural predictivity across units in the Neuropixels dataset.

5 Discussion

In this work, we showed that shallower architectures trained with contrastive embedding methods operating on lower-resolution images most accurately predict image-evoked neural responses across visual areas in mice, surpassing the predictive power of supervised methods. Our best models approached the computed inter-animal consistency of all measured units on both neural datasets. The fact that these goal-driven constraints lead to a better match, even in "behaviorally-free" data, suggests that these constraints may be better descriptions of the evolutionary and the developmental drivers of mouse visual cortical structure and function. While the primate ventral visual stream is well-modeled by a deep hierarchical system and category learning, mouse as a model visual system has not had such a coherent account heretofore. Our results demonstrate that both primate and rodent visual systems are highly constrained, although for different functional purposes.

Unlike the situation in the primate ventral visual stream (Zhuang et al., 2021), contrastive objectives *surpassed* the neural predictivity of their supervised counterparts, as increased categorization performance lead to overall *worse* correspondence to mouse visual areas. We observe that the advantage of these contrastive objectives is that they provide representations that are generally improved over those obtained by supervised methods, enabling transfer to a diverse range of downstream behaviors in novel environments, such as reward-based navigation and scene understanding. These results suggest that the mouse visual cortex is a light-weight, shallower, low-resolution, and general-purpose visual system in contrast to the deep, high-resolution, and more task-specific visual system of primates. Our improved models of the mouse visual system therefore provide a different view of its goals and constraints than that provided by (comparatively) high-resolution, deep feedforward categorization models. Furthermore, the generic nature of these unsupervised contrastive objective functions suggests the intriguing possibility that they might be used by other sensory systems, such as in barrel cortex or the olfactory system.

These results, coupled with the fact that much deeper networks (which are relatively better models of primate ventral visual responses than shallow networks) are among the worst models of mouse visual cortex, demonstrates a kind of "double dissociation" between the mouse-like architectures and tasks and the primate-like architectures and tasks. Thus, the failure of the "blind application" of deep networks to capture mouse data well – and the subsequent success of our more structurally-and-functionally tuned approach – illustrates not a weakness of the goal-driven neural network approach, but instead a strength of this methodology's ability to be appropriately sensitive to salient biological differences.

Although we have made progress in modeling the mouse visual system in three core ways (the choice of objective function, data stream, and architecture class), some limitations remain.

On the architectural front, our focus in this work was on feedforward models, but there are many feedback connections from higher visual areas to lower visual areas (Harris et al., 2019), which appear to play a functional role in the data as PM/AM are lower than AL in the functional hierarchy (Figures 1D and 1E), despite being more reliable later in time (Figure 1B). Incorporating these architectural motifs into our models and training these models using dynamic inputs may be useful for modeling temporal dynamics in mouse visual cortex, as has been recently done in primates (Nayebi et al., 2018; Kubilius et al., 2019; Nayebi et al., 2022).

Towards incorporating recurrent connections in the architecture, we would also like to probe the functionality of these feedback connections using unsupervised loss functions in scenarios with temporally-varying, dynamic inputs. Concurrent work of Bakhtiari et al. (2021) used the unsupervised predictive objective of CPC (Oord et al., 2018) to model neural responses of mouse visual cortex to natural movies. Given that our best performing unsupervised methods obtained good

representations on static images by way of contrastive learning, it would be interesting to explore a larger spectrum of more object-centric unsupervised signals operating on dynamic inputs, such as in the context of forward prediction (e.g., Mrowca et al., 2018; Haber et al., 2018; Lingelbach et al., 2020).

Moreover, we found that constraining the input data so that they are closer to those received by the mouse visual system, was important for improved correspondence – specifically, resizing the images to be smaller during training as a proxy for low-pass filtering. We believe that future work could investigate other appropriate low-pass filters and ecologically relevant pixel-level transformations to apply to the original image or video stream. These additional types of input transformations will likely also constrain the types of unsupervised objective functions that can be effectively deployed in temporally-varying contexts, as it did in our case for static images.

Finally, our inter-animal consistency measurements make a clear recommendation for the type of future neural datasets that are likely to be helpful in more sharply differentiating future candidate models. In Figure S5A, we observed that when fitting linear maps between animals to assess inter-animal consistency, fitting values are significantly higher in training than on the evaluation (test) set, indicating that the number of stimuli could be enlarged to close this gap. In fact, as a function of the number of stimuli, the test set inter-animal consistencies steadily increases (see Figure S5B), and likely would continue to increase substantially if the dataset had more stimuli. Thus, while much focus in methods has been on increasing the number of neurons contained in a given dataset (Steinmetz et al., 2021), our analysis indicates that the main limiting factor in model identification is *number of stimuli* in the dataset, rather than the number of neurons. In our view, future experiments should preferentially focus more resources on increasing stimulus count. Doing so would likely raise the inter-animal consistency, providing substantially more dynamic range for separating models in terms of their ability to match the data, and thereby increasing the likelihood that more specific conclusions about precisely which circuit structure(s) (Collins et al., 2017; Bergstra et al., 2015) and which specific (combinations of) objectives (e.g., Wu et al., 2018; Chen and He, 2020; Chen et al., 2020a) best describe mouse visual cortex.

Acknowledgements

We thank Shahab Bakhtiari, Katherine L. Hermann, and Akshay Jagadeesh for helpful discussions, and Eshed Margalit and Xiaoxuan Jia for helpful feedback on the manuscript. N.C.L.K. is supported by the Stanford University Ric Weiland Graduate Fellowship. J.L.G. acknowledges the generous support of Research to Prevent Blindness and Lions Club International Foundation (`https://www.rpbusa.org/rpb/low-vision/`). A.M.N. is supported by the Stanford Institute for Human Centered Artificial Intelligence. D.L.K.Y. is supported by the James S. McDonnell Foundation (Understanding Human Cognition Award Grant No. 220020469), the Simons Foundation (Collaboration on the Global Brain Grant No. 543061), the Sloan Foundation (Fellowship FG-2018-10963), the National Science Foundation (RI 1703161 and CAREER Award 1844724), the DARPA Machine Common Sense program, and hardware donation from the NVIDIA Corporation.

References

Shahab Bakhtiari, Patrick Mineault, Timothy Lillicrap, Christopher Pack, and Blake Richards. The functional specialization of visual cortex emerges from training parallel pathways with self-supervised predictive learning. *bioRxiv*, 2021.

Pouya Bashivan, Kohitij Kar, and James J DiCarlo. Neural population control via deep image synthesis. *Science*, 364(6439), 2019.

James Bergstra, Brent Komer, Chris Eliasmith, Daniel Yamins, and David D Cox. Hyperopt: a python library for model selection and hyperparameter optimization. *Computational Science & Discovery*, 8(1), 2015.

Léon Bottou. Large-scale machine learning with stochastic gradient descent. In *Proceedings of COMPSTAT'2010*, pages 177–186. Springer, 2010.

Santiago A Cadena, George H Denfield, Edgar Y Walker, Leon A Gatys, Andreas S Tolias, Matthias Bethge, and Alexander S Ecker. Deep convolutional models improve predictions of macaque v1 responses to natural images. *PLoS Computational Biology*, 15(4):e1006897, 2019a.

Santiago A Cadena, Fabian H Sinz, Taliah Muhammad, Emmanouil Froudarakis, Erick Cobos, Edgar Y Walker, Jacob Reimer, Matthias Bethge, Andreas Tolias, and Alexander S Ecker. How well do deep neural networks trained on object recognition characterize the mouse visual system? *NeurIPS Neuro AI Workshop*, 2019b.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning*, pages 1597–1607, 2020a.

Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. *arXiv preprint arXiv:2011.10566*, 2020.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020b.

Radoslaw Martin Cichy, Aditya Khosla, Dimitrios Pantazis, Antonio Torralba, and Aude Oliva. Comparison of deep neural networks to spatio-temporal cortical dynamics of human visual object recognition reveals hierarchical correspondence. *Scientific Reports*, 6(1):1–13, 2016.

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2014.

Jasmine Collins, Jascha Sohl-Dickstein, and David Sussillo. Capacity and trainability in recurrent neural networks. In *ICLR*, 2017.

Colin Conwell, Michael Buice, Andrei Barbu, and George Alvarez. Model zoology and neural taskonomy for better characterizing mouse visual cortex. *ICLR Bridging AI and Cognitive Science (BAICS) Workshop*, 2020.

Saskia EJ de Vries, Jerome A Lecoq, Michael A Buice, Peter A Groblewski, Gabriel K Ocker, Michael Oliver, David Feng, Nicholas Cain, Peter Ledochowitsch, Daniel Millman, et al. A large-scale standardized physiological survey reveals functional organization of the mouse visual cortex. *Nature Neuroscience*, 23(1):138–151, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009.

Carl Doersch, Abhinav Gupta, and Alexei A Efros. Unsupervised visual representation learning by context prediction. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1422–1430, 2015.

Rinaldo D D'Souza, Quanxin Wang, Weiqing Ji, Andrew M Meier, Henry Kennedy, Kenneth Knoblauch, and Andreas Burkhalter. Hierarchical and nonhierarchical features of the mouse visual cortical network. *Nature Communications*, 13(1):1–14, 2022.

Daniel J Felleman and David C Van Essen. Distributed hierarchical processing in the primate cerebral cortex. *Cerebral Cortex*, 1(1):1–47, 1991.

Emmanouil Froudarakis, Uri Cohen, Maria Diamantaki, Edgar Y Walker, Jacob Reimer, Philipp Berens, Haim Sompolinsky, and Andreas S Tolias. Object manifold geometry across the mouse cortical visual hierarchy. *bioRxiv*, 2020.

Răzvan Gămănuţ and Daisuke Shimaoka. Anatomical and functional connectomes underlying hierarchical visual processing in mouse visual system. *Brain Structure and Function*, pages 1–19, 2021.

Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised representation learning by predicting image rotations. In *International Conference on Learning Representations*, 2018.

Lindsey L Glickfeld and Shawn R Olsen. Higher-order areas of the mouse visual cortex. *Annual Review of Vision Science*, 3:251–273, 2017.

Umut Güçlü and Marcel AJ van Gerven. Deep neural networks reveal a gradient in the complexity of neural representations across the ventral stream. *Journal of Neuroscience*, 35(27):10005–10014, 2015.

Caglar Gulcehre, Ziyu Wang, Alexander Novikov, Thomas Paine, Sergio Gómez, Konrad Zolna, Rishabh Agarwal, Josh S Merel, Daniel J Mankowitz, Cosmin Paduraru, Gabriel Dulac-Arnold, Jerry Li, Mohammad Norouzi, Matthew Hoffman, Nicolas Heess, and Nando de Freitas. RL unplugged: A suite of benchmarks for offline reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 33, pages 7248–7259, 2020.

Nick Haber, Damian Mrowca, Stephanie Wang, Li Fei-Fei, and Daniel LK Yamins. Learning to play with intrinsically-motivated, self-aware agents. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pages 8398–8409, 2018.

Torkel Hafting, Marianne Fyhn, Sturla Molden, May-Britt Moser, and Edvard I Moser. Microstructure of a spatial map in the entorhinal cortex. *Nature*, 436(7052):801–806, 2005.

Julie A Harris, Stefan Mihalas, Karla E Hirokawa, Jennifer D Whitesell, Hannah Choi, Amy Bernard, Phillip Bohn, Shiella Caldejon, Linzy Casal, Andrew Cho, et al. Hierarchical organization of cortical and thalamic connectivity. *Nature*, 575(7781):195–202, 2019.

Kameron D Harris, Stefan Mihalas, and Eric Shea-Brown. High resolution neural connectivity from incomplete tracing data using nonnegative spline regression. In *Advances in Neural Information Processing Systems*, volume 29, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 9729–9738, 2020.

Ha Hong, Daniel LK Yamins, Najib J Majaj, and James J DiCarlo. Explicit information for category-orthogonal object properties increases along the ventral stream. *Nature Neuroscience*, 19(4):613, 2016.

Andrew D Huberman and Cristopher M Niell. What can mice tell us about how vision works? *Trends in Neurosciences*, 34(9):464–473, 2011.

Alexander JE Kell, Daniel LK Yamins, Erica N Shook, Sam V Norman-Haignere, and Josh H McDermott. A task-optimized neural network replicates human auditory behavior, predicts brain responses, and reveals a cortical processing hierarchy. *Neuron*, 98(3):630–644, 2018.

Seyed-Mahdi Khaligh-Razavi and Nikolaus Kriegeskorte. Deep supervised, but not unsupervised, models may explain it cortical representation. *PLoS Computational Biology*, 10(11):e1003915, 2014.

Lynne Kiorpes. Understanding the development of amblyopia using macaque monkey models. *Proceedings of the National Academy of Sciences*, 116(52):26217–26223, 2019.

Joseph E Knox, Kameron Decker Harris, Nile Graddis, Jennifer D Whitesell, Hongkui Zeng, Julie A Harris, Eric Shea-Brown, and Stefan Mihalas. High-resolution data-driven model of the mouse connectome. *Network Neuroscience*, 3(1):217–236, 2018.

Nikolaus Kriegeskorte, Marieke Mur, and Peter A Bandettini. Representational similarity analysis-connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, 2:4, 2008.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Emilio Kropff, James E Carmichael, May-Britt Moser, and Edvard I Moser. Speed cells in the medial entorhinal cortex. *Nature*, 523(7561):419–424, 2015.

Jonas Kubilius, Martin Schrimpf, Kohitij Kar, Rishi Rajalingham, Ha Hong, Najib Majaj, Elias Issa, Pouya Bashivan, Jonathan Prescott-Roy, Kailyn Schmidt, et al. Brain-like object recognition with high-performing shallow recurrent anns. *Advances in Neural Information Processing Systems*, 32: 12805–12816, 2019.

Michael Lingelbach, Damian Mrowca, Nick Haber, Li Fei-Fei, and Daniel LK Yamins. Towards curiosity-driven learning of physical dynamics. *ICLR Bridging AI and Cognitive Science (BAICS) Workshop*, 2020.

Najib J Majaj, Ha Hong, Ethan A Solomon, and James J DiCarlo. Simple learned weighted sums of inferior temporal neuronal firing rates accurately predict human core object recognition performance. *Journal of Neuroscience*, 35(39):13402–13418, 2015.

Josh Merel, Diego Aldarondo, Jesse Marshall, Yuval Tassa, Greg Wayne, and Bence Ölveczky. Deep neuroethology of a virtual rodent. *International Conference on Learning Representations*, 2020.

Jonathan A Michaels, Stefan Schaffelhofer, Andres Agudelo-Toro, and Hansjörg Scherberger. A goal-driven modular neural network predicts parietofrontal neural dynamics during grasping. *Proceedings of the National Academy of Sciences*, 117(50):32124–32135, 2020.

Damian Mrowca, Chengxu Zhuang, Elias Wang, Nick Haber, Li Fei-Fei, Joshua B Tenenbaum, and Daniel LK Yamins. Flexible neural representation for physics prediction. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pages 8813–8824, 2018.

Aran Nayebi, Daniel M Bear, Jonas Kubilius, Kohitij Kar, Surya Ganguli, David Sussillo, James J DiCarlo, and Daniel LK Yamins. Task-driven convolutional recurrent models of the visual system. *Advances in Neural Information Processing Systems*, 31:5295—5306, 2018.

Aran Nayebi, Javier Sagastuy-Brena, Daniel M Bear, Kohitij Kar, Jonas Kubilius, Surya Ganguli, David Sussillo, James J DiCarlo, and Daniel LK Yamins. Recurrent connections in the primate ventral visual stream mediate a tradeoff between task performance and network size during core object recognition. *Neural Computation*, 2022.

John O'Keefe and Jonathan Dostrovsky. The hippocampus as a spatial map: Preliminary evidence from unit activity in the freely-moving rat. *Brain research*, 1971.

Bruno A Olshausen and David J Field. Emergence of simple-cell receptive field properties by learning a sparse code for natural images. *Nature*, 381(6583):607–609, 1996.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Glen T Prusky, Paul WR West, and Robert M Douglas. Behavioral assessment of visual acuity in mice and rats. *Vision Research*, 40(16):2201–2209, 2000.

Rishi Rajalingham, Elias B Issa, Pouya Bashivan, Kohitij Kar, Kailyn Schmidt, and James J DiCarlo. Large-scale, high-resolution comparison of the core visual object recognition behavior of humans, monkeys, and state-of-the-art deep artificial neural networks. *Journal of Neuroscience*, 38 (33):7255–7269, 2018.

J. Brendan Ritchie, Stefania Bracci, and Hans Op de Beeck. Avoiding illusory effects in representational similarity analysis: What (not) to do with the diagonal. *NeuroImage*, 148:197–200, 2017.

Francesca Sargolini, Marianne Fyhn, Torkel Hafting, Bruce L McNaughton, Menno P Witter, May-Britt Moser, and Edvard I Moser. Conjunctive representation of position, direction, and velocity in entorhinal cortex. *Science*, 312(5774):758–762, 2006.

Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J Majaj, Rishi Rajalingham, Elias B Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Kailyn Schmidt, et al. Brain-score: Which artificial neural network for object recognition is most brain-like? *bioRxiv*, page 407007, 2018.

Jianghong Shi, Eric Shea-Brown, and Michael Buice. Comparison against task driven artificial neural networks reveals functional properties in mouse visual cortex. *Advances in Neural Information Processing Systems*, 32:5764–5774, 2019.

Jianghong Shi, Michael A Buice, Eric Shea-Brown, Stefan Mihalas, and Bryan Tripp. A convolutional network architecture driven by mouse neuroanatomical data. *bioRxiv*, 2020.

Joshua H Siegle, Peter Ledochowitsch, Xiaoxuan Jia, Daniel Millman, Gabriel K Ocker, Shiella Caldejon, Linzy Casal, Andrew Cho, Daniel J Denman, Séverine Durand, et al. Reconciling functional differences in populations of neurons recorded with two-photon imaging and electrophysiology. *BioRxiv*, 2020.

Joshua H Siegle, Xiaoxuan Jia, Séverine Durand, Sam Gale, Corbett Bennett, Nile Graddis, Greggory Heller, Tamina K Ramirez, Hannah Choi, Jennifer A Luviano, et al. Survey of spiking in the mouse visual system reveals functional hierarchy. *Nature*, pages 1–7, 2021.

Trygve Solstad, Charlotte N Boccara, Emilio Kropff, May-Britt Moser, and Edvard I Moser. Representation of geometric borders in the entorhinal cortex. *Science*, 322(5909):1865–1868, 2008.

Nicholas A Steinmetz, Cagatay Aydin, Anna Lebedeva, Michael Okun, Marius Pachitariu, Marius Bauza, Maxime Beau, Jai Bhagat, Claudia Böhm, Martijn Broux, et al. Neuropixels 2.0: A miniaturized high-density probe for stable, long-term brain recordings. *Science*, 372(6539), 2021.

Ziyu Wang, Alexander Novikov, Konrad Zolna, Josh S Merel, Jost Tobias Springenberg, Scott E Reed, Bobak Shahriari, Noah Siegel, Caglar Gulcehre, Nicolas Heess, et al. Critic regularized regression. *Advances in Neural Information Processing Systems*, 33:7768–7778, 2020.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via nonparametric instance discrimination. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3733–3742, 2018.

Daniel LK Yamins and James J DiCarlo. Using goal-driven deep learning models to understand sensory cortex. *Nature Neuroscience*, 19(3):356–365, 2016.

Daniel LK Yamins, Ha Hong, Charles F Cadieu, Ethan A Solomon, Darren Seibert, and James J DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences*, 111(23):8619–8624, 2014.

Yang You, Igor Gitman, and Boris Ginsburg. Large batch training of convolutional networks. *arXiv preprint arXiv:1708.03888*, 2017.

Yinda Zhang, Shuran Song, Ersin Yumer, Manolis Savva, Joon-Young Lee, Hailin Jin, and Thomas Funkhouser. Physically-based rendering for indoor scene understanding using convolutional neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5287–5295, 2017.

Chengxu Zhuang, Siming Yan, Aran Nayebi, Martin Schrimpf, Michael C Frank, James J DiCarlo, and Daniel LK Yamins. Unsupervised neural network models of the ventral visual stream. *Proceedings of the National Academy of Sciences*, 118(3), 2021.

6 Methods

6.1 Neural Response Datasets

We used the Allen Brain Observatory Visual Coding dataset (de Vries et al., 2020; Siegle et al., 2021) collected using both two-photon calcium imaging and Neuropixels from areas V1 (VISp), LM (VISl), AL (VISal), RL (VISrl), AM (VISam), and PM (VISpm) in mouse visual cortex. We focused on the natural scene stimuli, consisting of 118 images, each presented 50 times (i.e., 50 trials per image).

We list the number of units and specimens for each dataset in Table S1, after units are selected, according to the following procedure: For the calcium imaging data, we used a similar unit selection criterion as in Conwell et al. (2020), where we sub-selected units that attain a Spearman-Brown corrected split-half consistency of at least 0.3 (averaged across 100 bootstrapped trials), and whose peak responses to their preferred images are not significantly modulated by the mouse's running speed during stimulus presentation ($p > 0.05$).

For the Neuropixels dataset, we separately averaged, for each specimen and each visual area, the temporal response (at the level of 10-ms bins up to 250 ms) on the largest contiguous time interval when the median (across the population of units in that specimen) split-half consistency reached at least 0.3. This procedure helps to select the most internally-consistent units in their temporally-averaged response, and accounts for the fact that different specimens have different time courses along which their population response becomes reliable.

Finally, after subselecting units according to the above criteria for both datasets, we only keep specimens that have at least the 75th percentile number of units among all specimens for that given visual area. This final step helped to ensure we have enough internally-consistent units per specimen for the inter-animal consistency estimation (derived in Section 6.3).

Dataset Type	Visual Area	Total Units	Total Specimens
Calcium Imaging	V1	7080	29
	LM	4393	24
	AL	2064	9
	RL	1116	8
	AM	847	9
	PM	1844	19
Neuropixels	V1	442	8
	LM	162	6
	AL	396	6
	RL	299	7
	AM	257	7
	PM	175	5

Table S1: **Descriptive statistics of the neural datasets.** Total number of units and specimens for each visual area for the calcium imaging and Neuropixels datasets.

6.2 Noise-Corrected Neural Predictivity

6.2.1 Linear Regression

When we perform neural fits, we choose a random 50% set of natural scene images (59 images in total) to train the regression, and the remaining 50% to use as a test set (59 images in total), across ten train-test splits total. For Ridge regression, we use an $\alpha = 1$, following the `sklearn.linear_model` convention. PLS regression was performed with 25 components, as in prior work (e.g., Yamins et al., 2014; Schrimpf et al., 2018). When we perform regression with the One-to-One mapping, as in Figure 1B, we identify the top correlated (via Pearson correlation on the training images) unit in the source population for each target unit. Once that source unit has been identified, we then fix it for that particular train-test split, evaluated on the remaining 50% of images.

Motivated by the justification given in Section 6.3 for the noise correction in the inter-animal consistency, the noise correction of the model to neural response regression is a special case of the quantity defined in Section 6.3.2, where now the source animal is replaced by model features, separately fit to each target animal (from the set of available animals $\mathcal{A}$). Let L be the set of model layers, let r^ℓ be the set of model responses at model layer $\ell \in L$, M be the mapping, and let s be the trial-averaged pseudo-population response.

$$
\max_{\ell \in L} \operatorname{median} \bigoplus_{\mathsf{B} \in \mathcal{A}} \left\langle \frac{\mathsf{Corr}\left(M\left(r^\ell_{\text{train}}; \mathsf{s}^\mathsf{B}_{1,\text{train}} \right)_{\text{test}}, \mathsf{s}^\mathsf{B}_{2,\text{test}} \right)}{\sqrt{\widetilde{\mathsf{Corr}}\left(M\left(r^\ell_{\text{train}}; \mathsf{s}^\mathsf{B}_{1,\text{train}} \right)_{\text{test}}, M\left(r^\ell_{\text{train}}; \mathsf{s}^\mathsf{B}_{2,\text{train}} \right)_{\text{test}} \right) \times \widetilde{\mathsf{Corr}}\left(\mathsf{s}^\mathsf{B}_{1,\text{test}}, \mathsf{s}^\mathsf{B}_{2,\text{test}} \right)}} \right\rangle,
$$

where the average is taken over 100 bootstrapped split-half trials, $\oplus$ denotes concatenation of units across animals $\mathsf{B} \in \mathcal{A}$ followed by the median value across units, and $\mathsf{Corr}(\cdot, \cdot)$ denotes the Pearson correlation of the two quantities. $\widetilde{\mathsf{Corr}}(\cdot, \cdot)$ denotes the Spearman-Brown corrected value of the original quantity (see Section 6.3.5).

Prior to obtaining the model features of the stimuli for linear regression, we preprocessed each stimulus using the image transforms used on the validation set during model training, resizing the shortest edge of the stimulus in both cases to 64 pixels, preserving the aspect ratio of the input stimulus. Specifically, for models trained using the ImageNet dataset, we first resized the shortest edge of the stimulus to 256 pixels, center-cropped the image to 224×224 pixels, and finally resized the stimulus to 64×64 pixels. For models trained using the CIFAR-10 dataset, this resizing yielded a 64×81 pixels stimulus.

6.2.2 Representational Similarity Analysis (RSA)

In line with prior work (Shi et al., 2019; Conwell et al., 2020), we also used representational similarity analysis (RSA, Kriegeskorte et al., 2008) to compare models to neural responses, as well as to compare animals to each other. Specifically, we compared (via Pearson correlation) only the upper-right triangles of the representational dissimilarity matrices (RDMs), excluding the diagonals to avoid illusory effects (Ritchie et al., 2017).

For each visual area and a given model, we defined the predictivity of the model for that area to be the maximum RSA score across model layers after the suitable noise correction is applied, which is defined as follows. Let r^ℓ be the model responses at model layer ℓ and let s be the trial-averaged pseudo-population response (i.e., responses aggregated across specimens). The metric used here is a specific instance of Equation (10), where the single source animal A is the trial-wise,

deterministic model features (which have a mapping consistency of 1 as a result) and a single target animal B, which is the pseudo-population response:

$$\max_{\ell \in L} \left\langle \frac{\mathsf{RSA}\left(r^\ell, \mathrm{s}_2\right)}{\sqrt{\widetilde{\mathsf{RSA}}\left(\mathrm{s}_1, \mathrm{s}_2\right)}} \right\rangle,$$

$$\widetilde{\mathsf{RSA}}\left(\mathrm{s}_1, \mathrm{s}_2\right) := \frac{2\,\mathsf{RSA}\left(\mathrm{s}_1, \mathrm{s}_2\right)}{1 + \mathsf{RSA}\left(\mathrm{s}_1, \mathrm{s}_2\right)}, \tag{1}$$

where L is the set of model layers, $\{\mathrm{s}_i\}_{i=1}^2$ are the animal's responses for two halves of the trials (and averaged across the trials dimension), the average is computed over 100 bootstrapped split-half trials, and $\widetilde{\mathsf{RSA}}\left(\mathrm{s}_1, \mathrm{s}_2\right)$ denotes Spearman-Brown correction applied to the internal consistency quantity, $\mathsf{RSA}\left(\mathrm{s}_1, \mathrm{s}_2\right)$, defined in Section 6.3.5.

If the fits are performed separately for each animal, then B corresponds to each animal among those for a given visual area (defined by the set $\mathcal{A}$), and we compute the median across animals $\mathrm{B} \in \mathcal{A}$:

$$\max_{\ell \in L} \operatorname*{median}_{\mathrm{B} \in \mathcal{A}} \left\langle \frac{\mathsf{RSA}\left(r^\ell, \mathrm{s}_2^{\mathsf{B}}\right)}{\sqrt{\widetilde{\mathsf{RSA}}\left(\mathrm{s}_1^{\mathsf{B}}, \mathrm{s}_2^{\mathsf{B}}\right)}} \right\rangle. \tag{2}$$

Similar to the above, Spearman-Brown correction is applied to the internal consistency quantity, $\mathsf{RSA}\left(\mathrm{s}_1^{\mathsf{B}}, \mathrm{s}_2^{\mathsf{B}}\right)$.

6.3 Inter-Animal Consistency Derivation

6.3.1 Single Animal Pair

Suppose we have neural responses from two animals A and B. Let t_i^p be the vector of true responses (either at a given time bin or averaged across a set of time bins) of animal $p \in \mathcal{A} = \{\mathsf{A}, \mathsf{B}, \dots\}$ on stimulus set $i \in \{\text{train}, \text{test}\}$. Of course, we only receive noisy observations of t_i^p, so let $\mathrm{s}_{j,i}^p$ be the jth set of n trials of t_i^p. Finally, let $M(x; y)_i$ be the predictions of a mapping M (e.g., PLS) when trained on input x to match output y and tested on stimulus set i. For example, $M\left(\mathrm{t}_{\text{train}}^{\mathsf{A}}; \mathrm{t}_{\text{train}}^{\mathsf{B}}\right)_{\text{test}}$ is the prediction of mapping M on the test set stimuli trained to match the true neural responses of animal B given, as input, the true neural responses of animal A on the train set stimuli. Similarly, $M\left(\mathrm{s}_{1,\text{train}}^{\mathsf{A}}; \mathrm{s}_{1,\text{train}}^{\mathsf{B}}\right)_{\text{test}}$ is the prediction of mapping M on the test set stimuli trained to match the trial-average of noisy sample 1 on the train set stimuli of animal B given, as input, the trial-average of noisy sample 1 on the train set stimuli of animal A.

With these definitions in hand, the inter-animal mapping consistency from animal A to animal B corresponds to the following true quantity to be estimated:

$$\mathsf{Corr}\left(M\left(\mathrm{t}_{\text{train}}^{\mathsf{A}}; \mathrm{t}_{\text{train}}^{\mathsf{B}}\right)_{\text{test}}, \mathrm{t}_{\text{test}}^{\mathsf{B}}\right), \tag{3}$$

where $\mathsf{Corr}(\cdot, \cdot)$ is the Pearson correlation across a stimulus set. In what follows, we will argue that Equation (3) can be approximated with the following ratio of measurable quantities, where we split in half and average the noisy trial observations, indexed by 1 and by 2:

$$\mathsf{Corr}\left(M\left(\mathrm{t}_{\text{train}}^{\mathsf{A}}; \mathrm{t}_{\text{train}}^{\mathsf{B}}\right)_{\text{test}}, \mathrm{t}_{\text{test}}^{\mathsf{B}}\right)$$

$$\sim \frac{\mathsf{Corr}\left(M\left(\mathrm{s}_{1,\text{train}}^{\mathsf{A}}; \mathrm{s}_{1,\text{train}}^{\mathsf{B}}\right)_{\text{test}}, \mathrm{s}_{2,\text{test}}^{\mathsf{B}}\right)}{\sqrt{\mathsf{Corr}\left(M\left(\mathrm{s}_{1,\text{train}}^{\mathsf{A}}; \mathrm{s}_{1,\text{train}}^{\mathsf{B}}\right)_{\text{test}}, M\left(\mathrm{s}_{2,\text{train}}^{\mathsf{A}}; \mathrm{s}_{2,\text{train}}^{\mathsf{B}}\right)_{\text{test}}\right) \times \mathsf{Corr}\left(\mathrm{s}_{1,\text{test}}^{\mathsf{B}}, \mathrm{s}_{2,\text{test}}^{\mathsf{B}}\right)}}. \tag{4}$$

In words, the inter-animal consistency (i.e., the quantity on the left side of Equation (4)) corresponds to the predictivity of the mapping on the test set stimuli from animal A to animal B on two different (averaged) halves of noisy trials (i.e., the numerator on the right side of Equation (4)), corrected by the square root of the mapping reliability on animal A's responses to the test set stimuli on two different halves of noisy trials multiplied by the internal consistency of animal B.

We justify the approximation in Equation (4) by gradually replacing the true quantities (t) by their measurable estimates (s), starting from the original quantity in Equation (3). First, we make the approximation that:

$$\text{Corr}\left(M\left(t_{\text{train}}^{A};t_{\text{train}}^{B}\right)_{\text{test}},s_{2,\text{test}}^{B}\right) \sim \text{Corr}\left(M\left(t_{\text{train}}^{A};t_{\text{train}}^{B}\right)_{\text{test}},t_{\text{test}}^{B}\right) \times \text{Corr}\left(t_{\text{test}}^{B},s_{2,\text{test}}^{B}\right), \qquad (5)$$

by the transitivity of positive correlations (which is a reasonable assumption when the number of stimuli is large). Next, by transitivity and normality assumptions in the structure of the noisy estimates and since the number of trials (n) between the two sets is the same, we have that:

$$\text{Corr}\left(s_{1,\text{test}}^{B},s_{2,\text{test}}^{B}\right) \sim \text{Corr}\left(s_{1,\text{test}}^{B},t_{\text{test}}^{B}\right) \times \text{Corr}\left(t_{\text{test}}^{B},s_{2,\text{test}}^{B}\right)$$
$$\sim \text{Corr}\left(t_{\text{test}}^{B},s_{2,\text{test}}^{B}\right)^{2}. \qquad (6)$$

In words, Equation (6) states that the correlation between the average of two sets of noisy observations of n trials each is approximately the square of the correlation between the true value and average of one set of n noisy trials. Therefore, combining Equations (5) and (6), it follows that:

$$\text{Corr}\left(M\left(t_{\text{train}}^{A};t_{\text{train}}^{B}\right)_{\text{test}},t_{\text{test}}^{B}\right) \sim \frac{\text{Corr}\left(M\left(t_{\text{train}}^{A};t_{\text{train}}^{B}\right)_{\text{test}},s_{2,\text{test}}^{B}\right)}{\sqrt{\text{Corr}\left(s_{1,\text{test}}^{B},s_{2,\text{test}}^{B}\right)}}. \qquad (7)$$

From the right side of Equation (7), we can see that we have removed t_{test}^{B}, but we still need to remove the $M\left(t_{\text{train}}^{A};t_{\text{train}}^{B}\right)_{\text{test}}$ term, as this term still contains unmeasurable (i.e., true) quantities. We apply the same two steps, described above, by analogy, though these approximations may not always be true (they are, however, true for Gaussian noise):

$$\text{Corr}\left(M\left(s_{1,\text{train}}^{A};s_{1,\text{train}}^{B}\right)_{\text{test}},s_{2,\text{test}}^{B}\right) \sim \text{Corr}\left(s_{2,\text{test}}^{B},M\left(t_{\text{train}}^{A};t_{\text{train}}^{B}\right)_{\text{test}}\right)$$
$$\times \text{Corr}\left(M\left(t_{\text{train}}^{A};t_{\text{train}}^{B}\right)_{\text{test}},M\left(s_{1,\text{train}}^{A};s_{1,\text{train}}^{B}\right)_{\text{test}}\right)$$

$$\text{Corr}\left(M\left(s_{1,\text{train}}^{A};s_{1,\text{train}}^{B}\right)_{\text{test}},M\left(s_{2,\text{train}}^{A};s_{2,\text{train}}^{B}\right)_{\text{test}}\right)$$
$$\sim \text{Corr}\left(M\left(s_{1,\text{train}}^{A};s_{1,\text{train}}^{B}\right)_{\text{test}},M\left(t_{\text{train}}^{A};t_{\text{train}}^{B}\right)_{\text{test}}\right)^{2},$$

which taken together implies the following:

$$\text{Corr}\left(M\left(t_{\text{train}}^{A};t_{\text{train}}^{B}\right)_{\text{test}},s_{2,\text{test}}^{B}\right) \sim \frac{\text{Corr}\left(M\left(s_{1,\text{train}}^{A};s_{1,\text{train}}^{B}\right)_{\text{test}},s_{2,\text{test}}^{B}\right)}{\sqrt{\text{Corr}\left(M\left(s_{1,\text{train}}^{A};s_{1,\text{train}}^{B}\right)_{\text{test}},M\left(s_{2,\text{train}}^{A};s_{2,\text{train}}^{B}\right)_{\text{test}}\right)}}. \qquad (8)$$

Equations (7) and (8) together imply the final estimated quantity given in Equation (4).

6.3.2 Multiple Animals

For multiple animals, we consider the average of the true quantity for each target in B in Equation (3) across source animals A in the ordered pair (A, B) of animals A and B:

$$\left\langle \mathsf{Corr}\left(M\left(\mathrm{t}^A_{\mathrm{train}}; \mathrm{t}^B_{\mathrm{train}}\right)_{\mathrm{test}}, \mathrm{t}^B_{\mathrm{test}}\right)\right\rangle_{A\in\mathcal{A}:(A,B)\in\mathcal{A}\times\mathcal{A}}$$

$$\sim \left\langle \frac{\mathsf{Corr}\left(M\left(\mathrm{s}^A_{1,\mathrm{train}}; \mathrm{s}^B_{1,\mathrm{train}}\right)_{\mathrm{test}}, \mathrm{s}^B_{2,\mathrm{test}}\right)}{\sqrt{\widetilde{\mathsf{Corr}}\left(M\left(\mathrm{s}^A_{1,\mathrm{train}}; \mathrm{s}^B_{1,\mathrm{train}}\right)_{\mathrm{test}}, M\left(\mathrm{s}^A_{2,\mathrm{train}}; \mathrm{s}^B_{2,\mathrm{train}}\right)_{\mathrm{test}}\right) \times \widetilde{\mathsf{Corr}}\left(\mathrm{s}^B_{1,\mathrm{test}}, \mathrm{s}^B_{2,\mathrm{test}}\right)}} \right\rangle_{A\in\mathcal{A}:(A,B)\in\mathcal{A}\times\mathcal{A}}.$$

We also bootstrap across trials, and have multiple train/test splits, in which case the average on the right hand side of the equation includes averages across these as well.

Note that each neuron in our analysis will have this single average value associated with it when *it* was a target animal (B), averaged over source animals/subsampled source neurons, bootstrapped trials, and train/test splits. This yields a vector of these average values, which we can take median and standard error of the mean (s.e.m.) over, as we do with standard explained variance metrics.

6.3.3 RSA

We can extend the above derivations to other commonly used metrics for comparing representations that involve correlation. Since $\mathsf{RSA}(x, y) := \mathsf{Corr}(\mathsf{RDM}(x), \mathsf{RDM}(y))$, then the corresponding quantity in Equation (4) analogously (by transitivity of positive correlations) becomes:

$$\left\langle \mathsf{RSA}\left(M\left(\mathrm{t}^A_{\mathrm{train}}; \mathrm{t}^B_{\mathrm{train}}\right)_{\mathrm{test}}, \mathrm{t}^B_{\mathrm{test}}\right)\right\rangle_{A\in\mathcal{A}:(A,B)\in\mathcal{A}\times\mathcal{A}}$$

$$\sim \left\langle \frac{\mathsf{RSA}\left(M\left(\mathrm{s}^A_{1,\mathrm{train}}; \mathrm{s}^B_{1,\mathrm{train}}\right)_{\mathrm{test}}, \mathrm{s}^B_{2,\mathrm{test}}\right)}{\sqrt{\widetilde{\mathsf{RSA}}\left(M\left(\mathrm{s}^A_{1,\mathrm{train}}; \mathrm{s}^B_{1,\mathrm{train}}\right)_{\mathrm{test}}, M\left(\mathrm{s}^A_{2,\mathrm{train}}; \mathrm{s}^B_{2,\mathrm{train}}\right)_{\mathrm{test}}\right) \times \widetilde{\mathsf{RSA}}\left(\mathrm{s}^B_{1,\mathrm{test}}, \mathrm{s}^B_{2,\mathrm{test}}\right)}} \right\rangle_{A\in\mathcal{A}:(A,B)\in\mathcal{A}\times\mathcal{A}}. \tag{9}$$

Note that in this case, each *animal* (rather than neuron) in our analysis will have this single average value associated with it when *it* was a target animal (B) (since RSA is computed over images and neurons), where the average is over source animals/subsampled source neurons, bootstrapped trials, and train/test splits. This yields a vector of these average values, which we can take median and s.e.m. over, across animals $B \in \mathcal{A}$.

For RSA, we can use the identity mapping (since RSA is computed over neurons as well, the number of neurons between source and target animal can be different to compare them with the identity mapping). As parameters are not fit, we can choose train = test, so that Equation (9) becomes:

$$\left\langle \mathsf{RSA}\left(\mathrm{t}^A, \mathrm{t}^B\right)\right\rangle_{A\in\mathcal{A}:(A,B)\in\mathcal{A}\times\mathcal{A}} \sim \left\langle \frac{\mathsf{RSA}\left(\mathrm{s}^A_1, \mathrm{s}^B_2\right)}{\sqrt{\widetilde{\mathsf{RSA}}\left(\mathrm{s}^A_1, \mathrm{s}^A_2\right) \times \widetilde{\mathsf{RSA}}\left(\mathrm{s}^B_1, \mathrm{s}^B_2\right)}} \right\rangle_{A\in\mathcal{A}:(A,B)\in\mathcal{A}\times\mathcal{A}}. \tag{10}$$

6.3.4 Pooled Source Animal

Often times, we may not have enough neurons per animal to ensure that the estimated inter-animal consistency in our data closely matches the "true" inter-animal consistency. In order to address this

issue, we holdout one animal at a time and compare it to the pseudo-population aggregated across units from the remaining animals, as opposed to computing the consistencies in a pairwise fashion. Thus, B is still the target heldout animal as in the pairwise case, but now the average over A is over a sole "pooled" source animal constructed from the pseudo-population of the remaining animals.

6.3.5 Spearman-Brown Correction

The Spearman-Brown correction can be applied to each of the terms in the denominator individually, as they are each correlations of observations from half the trials of the *same* underlying process to itself (unlike the numerator). Namely,

$$\widetilde{\mathsf{Corr}}\left(X, Y\right) := \frac{2\,\mathsf{Corr}\left(X, Y\right)}{1 + \mathsf{Corr}\left(X, Y\right)}.$$

Analogously, since $\mathsf{RSA}(X, Y) := \mathsf{Corr}(\mathsf{RDM}(x), \mathsf{RDM}(y))$, then we define

$$
\begin{aligned}
\widetilde{\mathsf{RSA}}\left(X, Y\right) &:= \widetilde{\mathsf{Corr}}(\mathsf{RDM}(x), \mathsf{RDM}(y)) \\
&= \frac{2\,\mathsf{RSA}\left(X, Y\right)}{1 + \mathsf{RSA}\left(X, Y\right)}.
\end{aligned}
$$

6.4 StreamNet Architecture Variants

We developed shallower, multiple-streamed architectures for mouse visual cortex, shown in Figure 2A. There are three main modules in our architecture: shallow, intermediate, and deep. The shallow and deep modules each consist of one convolutional layer and the intermediate module consists of a block of two convolutional layers. Thus, the longest length of the computational graph, excluding the readout module, is four (i.e., $1+2+1$). Depending on the number of parallel streams in the model, the intermediate module would contain multiple branches (in parallel), each receiving input from the shallow module. The outputs of the intermediate modules are then passed through one convolutional operation (deep module). Finally, the outputs of each parallel branch would be summed together, concatenated across the channels dimension, and used as input for the readout module. Table S2 describes the parameters of three model variants, each containing one ($N = 1$), two ($N = 2$), or six ($N = 6$) parallel branches.

6.5 Neural Network Training Objectives

In this section, we briefly describe the supervised and unsupervised objectives that were used to train our models.

6.5.1 Supervised Training Objective

The loss function $\mathcal{L}$ used in supervised training is the cross-entropy loss, defined as follows:

$$\mathcal{L}(\boldsymbol{X}; \boldsymbol{\theta}) = -\frac{1}{N}\sum_{i=1}^{N}\log\left(\frac{\exp(\boldsymbol{X}_i[\boldsymbol{c}_i])}{\sum_{j=0}^{C-1}\exp(\boldsymbol{X}_i[j])}\right), \tag{11}$$

where N is the batch size, C is the number of categories for the dataset, $\boldsymbol{X} \in \mathbb{R}^{N \times C}$ are the model outputs (i.e., logits) for the N images, $\boldsymbol{X}_i \in \mathbb{R}^C$ are the logits for the ith image, $\boldsymbol{c}_i \in [0, C-1]$ is the category index of the ith image (zero-indexed), and $\boldsymbol{\theta}$ are the model parameters. Equation (11) was minimized using stochastic gradient descent (SGD) with momentum (Bottou, 2010).

Module Name	Output Size	Single ($N = 1$)	Dual ($N = 2$)	Six ($N = 6$)
Input	64×64	N/A	N/A	N/A
Shallow	7×7	$(64, 11, 4, 2)$	$(64, 11, 4, 2)$	$(64, 11, 4, 2)$
Intermediate	3×3	$\begin{bmatrix}(192, 5, 1, 2)\\(384, 3, 1, 1)\end{bmatrix}$	$\begin{bmatrix}(192, 5, 1, 2)\\(384, 3, 1, 1)\end{bmatrix} \times 2$	$\begin{bmatrix}(192, 5, 1, 2)\\(384, 3, 1, 1)\end{bmatrix} \times 6$
Deep	3×3	If inputs are from intermediate: $(256, 3, 1, 1)$, otherwise: $(256, 3, 2, 0)$	If inputs are from intermediate: $(256, 3, 1, 1)$, otherwise: $(256, 3, 2, 0)$	If inputs are from intermediate: $(256, 3, 1, 1)$, otherwise: $(256, 3, 2, 0)$

Table S2: **Neural network parameters and output sizes for the convolutional layers of our StreamNet model variants containing one, two, and six parallel branches in the intermediate module.** One convolutional layer is denoted by a tuple: (number of filters, filter size, stride, padding). A block of convolutional layers is denoted by a list of tuples, where each tuple in the list corresponds to a single convolutional layer. When a list of tuples is followed by "$\times N$", this means that the convolutional parameters for each of the N parallel branches are the same.

ImageNet (Deng et al., 2009)   This dataset contains approximately 1.3 million images in the train set and $50\,000$ images in the validation set. Each image was previously labeled into $C = 1000$ distinct categories.

CIFAR-10 (Krizhevsky et al., 2009)   This dataset contains $50\,000$ images in the train set and $10\,000$ images in the validation set. Each image was previously labeled into $C = 10$ distinct categories.

6.5.2   Unsupervised Training Objectives

Sparse Autoencoder (Olshausen and Field, 1996)   The goal of this objective is to reconstruct an image from a sparse image embedding. In order to generate an image reconstruction, we used a mirrored version of each of our StreamNet variants. Concretely, the loss function was defined as follows:

$$\mathcal{L}(\boldsymbol{x}; \boldsymbol{\theta}) = \frac{1}{2 \cdot 64^2} \|f(\boldsymbol{x}) - \boldsymbol{x}\|_2^2 + \frac{\lambda}{128} \|\boldsymbol{v}\|_1, \tag{12}$$

where $\boldsymbol{v} \in \mathbb{R}^{128}$ is the image embedding, f is the (mirrored) model, $f(\boldsymbol{x})$ is the image reconstruction, $\boldsymbol{x}$ is a 64×64 pixels image, λ is the regularization coefficient, and $\boldsymbol{\theta}$ are the model parameters.

Our single-, dual-, and six-stream variants were trained using a batch size of 256 for 100 epochs using SGD with momentum of 0.9 and weight decay of 0.0005. The initial learning rate was set to 0.01 for the single- and dual-stream variants and was set to 0.001 for the six-stream variant. The learning rate was decayed by a factor of 10 at epochs $30, 60$, and 90. For all the StreamNet variants, the embedding dimension was set to 128 and the regularization coefficient was set to 0.0005.

Depth Prediction (Zhang et al., 2017)   The goal of this objective is to predict the depth map of an image. We used a synthetically generated dataset of images known as PBRNet (Zhang et al., 2017). It contains approximately $500\,000$ images and their associated depth maps. Similar to the loss function used in the sparse autoencoder objective, we used a mean-squared loss to train the

models. The output (i.e., depth map prediction) was generated using a mirrored version of each of our StreamNet variants. In order to generate the depth map, we appended one final convolutional layer onto the output of the mirrored architecture in order to downsample the three image channels to one image channel. During training, random crops of size 224×224 pixels were applied to the image and depth map (which were both subsequently resized to 64×64 pixels). In addition, both the image and depth map were flipped horizontally with probability 0.5. Finally, prior to the application of the loss function, each depth map was normalized such that the mean and standard deviation across pixels were zero and one respectively.

Each of our single-, dual-, and six-stream variants were trained using a batch size of 256 for 50 epochs using SGD with momentum of 0.9, and weight decay of 0.0001. The initial learning rate was set to 10^{-4} and was decayed by a factor of 10 at epochs 15, 30, and 45.

RotNet (Gidaris et al., 2018) The goal of this objective is to predict the rotation of an image. Each image of the ImageNet dataset was rotated four ways ($0°$, $90°$, $180°$, $270°$) and the four rotation angles were used as "pseudo-labels" or "categories". The cross-entropy loss was used with these pseudo-labels as the training objective (i.e., Equation (11) with $C = 4$).

Our single-, dual-, and six-stream variants were trained using a batch size of 192 (which is effectively a batch size of $192 \times 4 = 768$ due to the four rotations for each image) for 50 epochs using SGD with Nesterov momentum of 0.9, and weight decay of 0.0005. An initial learning rate of 0.01 was decayed by a factor of 10 at epochs 15, 30, and 45.

Instance Recognition (Wu et al., 2018) The goal of this objective is to be able to differentiate between embeddings of augmentations of one image from embeddings of augmentations of other images. Thus, this objective function is an instance of the class of contrastive objective functions.

A random image augmentation is first performed on each image of the ImageNet dataset (random resized cropping, random grayscale, color jitter, and random horizontal flip). Let $\boldsymbol{x}$ be an image augmentation, and $f(\cdot)$ be the model backbone composed with a one-layer linear multi-layer perceptron (MLP) of size 128. The image is then embedded onto a 128-dimensional unit-sphere as follows:

$$\boldsymbol{z} = f(\boldsymbol{x})/\|f(\boldsymbol{x})\|_2, \qquad \boldsymbol{z} \in \mathbb{R}^{128}.$$

Throughout model training, a memory bank containing embeddings for each image in the train set is maintained (i.e., the size of the memory bank is the same as the size of the train set). The embedding $\boldsymbol{z}$ will be "compared" to a subsample of these embeddings. Concretely, the loss function $\mathcal{L}$ for one image $\boldsymbol{x}$ is defined as follows:

$$h(\boldsymbol{u}) = \frac{\exp(\boldsymbol{u} \cdot \boldsymbol{z}/\tau)/Z}{\exp(\boldsymbol{u} \cdot \boldsymbol{z}/\tau)/Z + (m/N)},$$

$$\mathcal{L}(\boldsymbol{x}; \boldsymbol{\theta}) = -\log h(\boldsymbol{v}) - \sum_{j=1}^{m} \log\left(1 - h(\boldsymbol{v}_j)\right), \tag{13}$$

where $\boldsymbol{v} \in \mathbb{R}^{128}$ is the embedding for image $\boldsymbol{x}$ that is currently stored in the memory bank, N is the size of the memory bank, $m = 4096$ is the number of "negative" samples used, $\{\boldsymbol{v}_j\}_{j=1}^{m}$ are the negative embeddings sampled from the memory bank uniformly, Z is some normalization constant, $\tau = 0.07$ is a temperature hyperparameter, and $\boldsymbol{\theta}$ are the parameters of f. From Equation (13), we see that we want to maximize $h(\boldsymbol{v})$, which corresponds to maximizing the similarity between $\boldsymbol{v}$ and $\boldsymbol{z}$ (recall that $\boldsymbol{z}$ is the embedding for $\boldsymbol{x}$ obtained using f). We can also see that we want

to maximize $1 - h(\boldsymbol{v}_j)$ (or minimize $h(\boldsymbol{v}_j)$). This would correspond to minimizing the similarity between $\boldsymbol{v}_j$ and $\boldsymbol{z}$ (recall that $\boldsymbol{v}_j$ are the negative embeddings).

After each iteration of training, the embeddings for the current batch are used to update the memory bank (at their corresponding positions in the memory bank) via a momentum update. Concretely, for image $\boldsymbol{x}$, its embedding in the memory bank $\boldsymbol{v}$ is updated using its current embedding $\boldsymbol{z}$ as follows:

$$\boldsymbol{v} \leftarrow \lambda \boldsymbol{v} + (1 - \lambda) \boldsymbol{z},$$
$$\boldsymbol{v} \leftarrow \boldsymbol{v} / \|\boldsymbol{v}\|_2,$$

where $\lambda = 0.5$ is the momentum coefficient. The second operation on $\boldsymbol{v}$ is used to project $\boldsymbol{v}$ back onto the 128-dimensional unit sphere.

Our single-, dual-, and six-stream variants were trained using a batch size of 256 for 200 epochs using SGD with momentum of 0.9, and weight decay of 0.0005. An initial learning rate of 0.03 was decayed by a factor of 10 at epochs 120 and 160.

SimSiam (Chen and He, 2020)   The goal of this objective is to maximize the similarity between the embeddings of two augmentations of the same image. Thus, SimSiam is another instance of the class of contrastive objective functions.

Two random image augmentations (e.g., random resized crop, random horizontal flip, color jitter, random grayscale, and random Gaussian blur) are first generated for each image in the ImageNet dataset. Let $\boldsymbol{x}_1$ and $\boldsymbol{x}_2$ be the two augmentations of the same image, $f(\cdot)$ be the model backbone, $g(\cdot)$ be a three-layer non-linear MLP, and $h(\cdot)$ be a two-layer non-linear MLP. The three-layer MLP has hidden dimensions of 2048, 2048, and 2048. The two-layer MLP has hidden dimensions of 512 and 2048 respectively. Let $\boldsymbol{\theta}$ be the parameters for f, g, and h. The loss function $\mathcal{L}$ for one image $\boldsymbol{x}$ of a batch is defined as follows (recall that $\boldsymbol{x}_1$ and $\boldsymbol{x}_2$ are two augmentations of one image):

$$\boldsymbol{p}_1 = h \circ g \circ f(\boldsymbol{x}_1), \qquad \boldsymbol{p}_2 = h \circ g \circ f(\boldsymbol{x}_2), \qquad \boldsymbol{z}_1 = g \circ f(\boldsymbol{x}_1), \qquad \boldsymbol{z}_2 = g \circ f(\boldsymbol{x}_2),$$

$$\mathcal{L}(\boldsymbol{x}_1, \boldsymbol{x}_2; \boldsymbol{\theta}) = -\frac{1}{2} \left(\frac{\boldsymbol{z}_1 \cdot \boldsymbol{p}_2}{\|\boldsymbol{z}_1\|_2 \|\boldsymbol{p}_2\|_2} + \frac{\boldsymbol{z}_2 \cdot \boldsymbol{p}_1}{\|\boldsymbol{z}_2\|_2 \|\boldsymbol{p}_1\|_2} \right), \tag{14}$$

where $\boldsymbol{z}_1, \boldsymbol{z}_2, \boldsymbol{p}_1, \boldsymbol{p}_2 \in \mathbb{R}^{2048}$. Note that $\boldsymbol{z}_1$ and $\boldsymbol{z}_2$ are treated as constants in this loss function (i.e., the gradients are not back-propagated through $\boldsymbol{z}_1$ and $\boldsymbol{z}_2$). This "stop-gradient" method was key to the success of this objective function.

Our single-, dual-, and six-stream variants were trained using a batch size of 512 for 100 epochs using SGD with momentum of 0.9, and weight decay of 0.0001. An initial learning rate of 0.1 was used, and the learning rate was decayed to 0.0 using a cosine schedule (with no warm-up).

MoCov2 (He et al., 2020; Chen et al., 2020b)   The goal of this objective is to be able to distinguish augmentations of one image (i.e., by labeling them as "positive") from augmentations of other images (i.e., by labeling them as "negative"). Intuitively, embeddings of different augmentations of the same image should be more "similar" to each other than to embeddings of augmentations of other images. Thus, this algorithm is another instance of the class of contrastive objective functions and is similar conceptually to instance recognition.

Two image augmentations are first generated for each image in the ImageNet dataset by applying random resized cropping, color jitter, random grayscale, random Gaussian blur, and random horizontal flips. Let $\boldsymbol{x}_1$ and $\boldsymbol{x}_2$ be the two augmentations for one image. Let $f_q(\cdot)$ be a query encoder, which is a model backbone composed with a two-layer non-linear MLP of dimensions 2048

and 128 respectively and let $f_k(\cdot)$ be a key encoder, which has the same architecture as f_q. $\boldsymbol{x}_1$ is encoded by f_q and $\boldsymbol{x}_2$ is encoded by f_k as follows:

$$\boldsymbol{v} = f_q(\boldsymbol{x}_1), \qquad \boldsymbol{k}_0 = f_k(\boldsymbol{x}_2), \qquad \boldsymbol{v}, \boldsymbol{k}_0 \in \mathbb{R}^{128}.$$

During each iteration of training, a dictionary of size K of image embeddings obtained from previous iterations is maintained (i.e., the dimensions of the dictionary are $K \times 128$). The image embeddings in this dictionary are used as "negative" samples. The loss function $\mathcal{L}$ for one image of a batch is defined as follows:

$$\mathcal{L}(\boldsymbol{x}_1, \boldsymbol{x}_2; \boldsymbol{\theta}_q) = -\log \frac{\exp(\boldsymbol{v} \cdot \boldsymbol{k}_0 / \tau)}{\sum_{i=0}^{K} \exp(\boldsymbol{v} \cdot \boldsymbol{k}_i / \tau)}, \tag{15}$$

where $\boldsymbol{\theta}_q$ are the parameters of f_q, $\tau = 0.2$ is a temperature hyperparameter, $K = 65\,536$ is the number of "negative" samples, and $\{\boldsymbol{k}_i\}_{i=1}^{K}$ are the embeddings of the negative samples (i.e., the augmentations for other images which are encoded using f_k, and are stored in the dictionary). From Equation (15), we see that we want to maximize $\boldsymbol{v} \cdot \boldsymbol{k}_0$, which corresponds to maximizing the similarity between the embeddings of the two augmentations of an image.

After each iteration of training, the dictionary of negative samples is enqueued with the embeddings from the most recent iteration, while embeddings that have been in the dictionary for the longest are dequeued. Finally, the parameters $\boldsymbol{\theta}_k$ of f_k are updated via a momentum update, as follows:

$$\boldsymbol{\theta}_k \leftarrow \lambda \boldsymbol{\theta}_k + (1 - \lambda) \boldsymbol{\theta}_q,$$

where $\lambda = 0.999$ is the momentum coefficient. Note that only $\boldsymbol{\theta}_q$ are updated with back-propagation.

Our single-, dual-, and six-stream variants were trained using a batch size of 512 for 200 epochs using SGD with momentum of 0.9, and weight decay of 0.0005. An initial learning rate of 0.06 was used, and the learning rate was decayed to 0.0 using a cosine schedule (with no warm-up).

SimCLR (Chen et al., 2020a) The goal of this objective is conceptually similar to that of Mo-Cov2, where the embeddings of augmentations of one image should be distinguishable from the embeddings of augmentations of other images. Thus, SimCLR is another instance of the class of contrastive objective functions.

Similar to other contrastive objective functions, two image augmentations are first generated for each image in the ImageNet dataset (by using random cropping, random horizontal flips, random color jittering, random grayscaling and random Gaussian blurring). Let $f(\cdot)$ be the model backbone composed with a two-layer non-linear MLP of dimensions 2048 and 128 respectively. The two image augmentations are first embedded into a 128-dimensional space and normalized:

$$\boldsymbol{z}_1 = f(\boldsymbol{x}_1) / \|f(\boldsymbol{x}_1)\|_2, \qquad \boldsymbol{z}_2 = f(\boldsymbol{x}_2) / \|f(\boldsymbol{x}_2)\|_2, \qquad \boldsymbol{z}_1, \boldsymbol{z}_2 \in \mathbb{R}^{128}.$$

The loss function $\mathcal{L}$ for a single pair of augmentations of an image is defined as follows:

$$\mathcal{L}(\boldsymbol{x}_1, \boldsymbol{x}_2; \boldsymbol{\theta}) = -\log \frac{\exp(\boldsymbol{z}_1 \cdot \boldsymbol{z}_2 / \tau)}{\sum_{i=1}^{2N} \mathbb{1}[i \neq 1] \exp(\boldsymbol{z}_1 \cdot \boldsymbol{z}_i / \tau)}, \tag{16}$$

where $\tau = 0.1$ is a temperature hyperparameter, N is the batch size, $\mathbb{1}[i \neq 1]$ is equal to 1 if $i \neq 1$ and 0 otherwise, and $\boldsymbol{\theta}$ are the parameters of f. The loss defined in Equation (16) is computed for every pair of images in the batch (including their augmentations) and subsequently averaged.

Our single-, dual-, and six-stream variants were trained using a batch size of 4096 for 200 epochs using layer-wise adaptive rate scaling (LARS, You et al., 2017) with momentum of 0.9, and weight decay of 10^{-6}. An initial learning rate of 4.8 was used and decayed to 0.0 using a cosine schedule. A linear warm-up of 10 epochs was used for the learning rate with warm-up ratio of 0.0001.

6.6 Top-1 Validation Set Performance

6.6.1 Performance of primate models on 224×224 pixels and 64×64 pixels ImageNet

Here we report the top-1 validation set accuracy of models trained in a supervised manner on 64×64 pixels and 224×224 pixels ImageNet.

Architecture	Image Size	Objective Function	Top-1 Accuracy
AlexNet	224×224	Supervised (ImageNet)	56.52%
	64×64		36.22%
VGG16	224×224		71.59%
	64×64		58.32%
ResNet-18	224×224		69.76%
	64×64		53.31%
ResNet-34	224×224		73.31%
	64×64		58.24%
ResNet-50	224×224		76.13%
	64×64		63.57%
ResNet-101	224×224		77.37%
	64×64		64.53%
ResNet-152	224×224		78.31%
	64×64		65.21%

6.6.2 Performance of StreamNet Variants on 64×64 pixels CIFAR-10 and 64×64 pixels ImageNet

Here we report the top-1 validation set accuracy of our model variants trained in a supervised manner on 64×64 pixels CIFAR-10 and ImageNet.

Architecture	Dataset	Objective Function	Top-1 Accuracy
Single Stream	CIFAR-10	Supervised	76.52%
	ImageNet		34.87%
Dual Stream	CIFAR-10		81.13%
	ImageNet		38.68%
Six Stream	CIFAR-10		78.73%
	ImageNet		34.15%

6.6.3 Transfer Performance of StreamNet Variants on 64×64 pixels ImageNet Under Linear Evaluation for Models Trained with Unsupervised Objectives

In this subsection, we report the top-1 ImageNet validation set performance under linear evaluation for models trained with unsupervised objectives. After training each model on a unsupervised objective, the model backbone weights are then held fixed and a linear readout head is trained on top of the fixed model backbone. In the case where the objective function is "untrained", model parameters were randomly initialized and held fixed while the linear readout head was trained. The image augmentations used during transfer learning were random cropping and random horizontal flipping. The linear readout for every unsupervised model was trained with the cross-entropy loss function (i.e., Equation (11) with $C = 1000$) for 100 epochs, which was minimized using SGD with momentum of 0.9, and weight decay of 10^{-9}. The initial learning rate was set to 0.1 and reduced by a factor of 10 at epochs 30, 60, and 90.

Architecture	Objective Function	ImageNet Transfer Top-1 Accuracy	Neural Predictivity Neuropixels; Calcium Imaging
Single Stream	Untrained	9.28%	32.76%; 28.65%
	Supervised	34.87%	36.21%; 29.73%
	Autoencoder	10.37%	35.99%; 28.69%
	Depth Prediction	18.04%	33.79%; 27.54%
	RotNet	19.72%	35.63%; 29.27%
	Instance Recognition	21.22%	38.01%; 30.88%
	SimSiam	26.48%	39.19%; 30.48%
	MoCov2	27.63%	39.17%; 30.30%
	SimCLR	22.84%	39.45%; 29.50%
Dual Stream	Untrained	10.85%	33.58%; 29.24%
	Supervised	38.68%	36.07%; 29.43%
	Autoencoder	10.26%	34.97%; 28.74%
	Depth Prediction	19.81%	32.81%; 27.20%
	RotNet	23.29%	35.37%; 29.15%
	Instance Recognition	22.55%	40.07%; 30.64%
	SimSiam	29.21%	40.20%; 30.60%
	MoCov2	31.00%	38.64%; 30.33%
	SimCLR	26.25%	38.03%; 29.08%
Six Stream	Untrained	11.12%	33.74%; 29.26%
	Supervised	34.15%	36.64%; 29.79%
	Autoencoder	9.27%	37.34%; 31.12%
	Depth Prediction	18.27%	33.12%; 27.63%
	RotNet	22.78%	35.49%; 28.97%
	Instance Recognition	26.49%	37.67%; 31.18%
	SimSiam	30.52%	38.17%; 30.46%
	MoCov2	32.70%	37.96%; 30.44%
	SimCLR	28.42%	38.92%; 29.19%
AlexNet	Supervised	36.22%	37.28%; 30.34%
AlexNet	Instance Recognition	16.09%	41.33%; 31.60%
AlexNet	SimSiam	6.84%	39.68%; 30.95%
AlexNet	MoCov2	15.67%	39.83%; 31.20%
AlexNet	SimCLR	26.85%	39.39%; 30.27%
ResNet-18	Supervised	53.31%	35.82%; 28.93%
ResNet-18	Instance Recognition	30.75%	38.99%; 30.11%
ResNet-34	Supervised	58.24%	36.38%; 28.42%
ResNet-34	Instance Recognition	32.91%	39.26%; 30.93%
ResNet-50	Supervised	63.57%	37.72%; 30.70%
ResNet-50	Instance Recognition	38.49%	39.45%; 31.12%
ResNet-101	Supervised	64.53%	38.15%; 31.05%
ResNet-101	Instance Recognition	39.43%	39.94%; 31.60%
ResNet-152	Supervised	65.21%	37.74%; 30.67%
ResNet-152	Instance Recognition	40.08%	39.07%; 31.30%
VGG16	Supervised	58.32%	33.19%; 27.09%
VGG16 (224 px)	Supervised	71.59%	26.03%; 20.40%
VGG16	Instance Recognition	25.33%	37.78%; 28.66%
MouseNet of Shi et al. (2020)	Supervised	37.14%	31.05%; 25.89%
MouseNet Variant	Supervised	39.37%	33.02%; 26.53%

Table S3: **ImageNet top-1 validation set accuracy via linear transfer or via supervised training and neural predictivity for each model.** We summarize here the top-1 accuracy for each unsupervised and supervised model on ImageNet as well as their noise-corrected neural predictivity obtained via the PLS map (aggregated across all visual areas). These values are plotted in Figures 2C and S2. Unless otherwise stated, each model is trained and validated on 64×64 pixels images.

6.7 Reinforcement Learning Task

A set of state-action-reward-state tuples (i.e., (s_t, a_t, r_t, s_{t+1})) were generated in prior work (Merel et al., 2020) and were used to train (in an offline fashion) the reinforcement learning (RL) agent. We used an offline RL algorithm known as critic-regularized regression (Wang et al., 2020). Except for the visual encoder, the architecture of the RL agent was identical to that used by Wang et al. (2020) (c.f. Figure 3 in Wang et al., 2020). Four different visual encoders based on the AlexNet architecture were used:

- Contrastive ImageNet: AlexNet trained using ImageNet in a contrastive manner. Its weights were held fixed during training of the RL agent. This visual encoder is the best model of mouse visual cortex (Figure 2).

- Supervised ImageNet: AlexNet trained using ImageNet in a supervised manner. Its weights were held fixed during training of the RL agent.

- Contrastive Maze: AlexNet trained using the egocentric maze inputs from the virtual rodent reward-based navigation task. Its weights were then held fixed during training of the RL agent.

- Supervised Maze: Truncated AlexNet (first four convolutional layers of AlexNet) trained end-to-end on the virtual rodent reward-based navigation task.

After training the agent until policy loss convergence by $10\,000$ steps (once), the agent was evaluated on 300 episodes. Each model was trained twice (i.e., two different random seeds), so each model was evaluated on $300 \times 2 = 600$ episodes in total and we report the average reward across all 600 episodes.

6.8 Evaluating Model Performance on Downstream Visual Tasks

To evaluate transfer performance on downstream visual tasks, we used the activations from the outputs of the shallow, intermediate, and deep modules of our StreamNet variants. We also included the average-pooling layer in all the variants (the model layer prior to the fully-connected readout layer). The dimensionality of the activations was then reduced to 1000 dimensions using principal components analysis (PCA), if the number of features exceeded 1000. PCA was not used if the number of features was less than or equal to 1000. A linear readout on these features was then used to perform five transfer visual tasks.

For the first four object-centric visual tasks (object categorization, pose estimation, position estimation, and size estimation), we used a stimulus set that was used previously in the evaluation of neural network models of the primate visual system (Schrimpf et al., 2018; Rajalingham et al., 2018; Zhuang et al., 2021). The stimulus set consists of objects in various poses (object rotations about the x, y, and z axes), positions (vertical and horizontal coordinates of the object), and sizes, each from eight categories. We then performed five-fold cross-validation on the training split of the medium and high variation image subsets ("Var3" and "Var6", defined in Majaj et al., 2015) consisting of 3840 images, and computed the performance (metrics defined below) on the test split of the medium and high variation sets ("Var3" and "Var6") consisting of 1280 images. Ten different category-balanced train-test splits were randomly selected, and the performance of the best model layer (averaged across train-test splits) was reported for each model. All images were resized to 64×64 pixels prior to fitting, to account for the visual acuity adjustment. The final non-object-centric task was texture recognition, using the Describable Textures Dataset (Cimpoi et al., 2014).

Object Categorization We fit a linear support vector classifier to each model layer activations that were transformed via PCA. The regularization parameter,

$$C \in [10^{-8}, 5 \times 10^{-8}, 10^{-7}, 5 \times 10^{-7}, 10^{-6}, 5 \times 10^{-6}, 10^{-5}, 5 \times 10^{-5},$$
$$10^{-4}, 5 \times 10^{-4}, 10^{-3}, 5 \times 10^{-3}, 10^{-2}, 5 \times 10^{-2}, 10^{-1}, 5 \times 10^{-1},$$
$$1, 5, 10^2, 5 \times 10^2, 10^3, 5 \times 10^3, 10^4, 5 \times 10^4,$$
$$10^5, 5 \times 10^5, 10^6, 5 \times 10^6, 10^7, 5 \times 10^7, 10^8, 5 \times 10^8], \quad (17)$$

was chosen by five-fold cross validation. The categories are Animals, Boats, Cars, Chairs, Faces, Fruits, Planes, and Tables. We reported the classification accuracy average across the ten train-test splits.

Position Estimation We predicted both the vertical and the horizontal locations of the object center in the image. We used Ridge regression where the regularization parameter was selected from:
$$\alpha = 1/C, \quad (18)$$
where C was selected from the list defined in (17). For each network, we reported the correlation averaged across both locations for the best model layer.

Pose Estimation This task was similar to the position prediction task except that the prediction target were the z-axis (vertical axis) and the y-axis (horizontal axis) rotations, both of which ranged between -90 degrees and 90 degrees. The $(0, 0, 0)$ angle was defined in a per-category basis and was chosen to make the $(0, 0, 0)$ angle "semantically" consistent across different categories. We refer the reader to Hong et al. (2016) for more details. We used Ridge regression with α chosen from the range in (18).

Size Estimation The prediction target was the three-dimensional object scale, which was used to generate the image in the rendering process. This target varied between 0.625 to 1.6, which was a relative measure to a fixed canonical size of 1. When objects were at the canonical size, they occluded around 40% of the image on the longest axis. We used Ridge regression with α chosen from the range in (18).

Texture Classification We trained linear readouts of the model layers on texture recognition using the Describable Textures Dataset (Cimpoi et al., 2014), which consists of 5640 images organized according to 47 categories, with 120 images per category. We used ten category-balanced train-test splits, provided by their benchmark. Each split consisted of 3760 train-set images and 1880 test-set images. A linear support vector classifier was then fit with C chosen in the range (17). We reported the classification accuracy average across the ten train-test splits.

Data Availability

The calcium imaging and Neuropixels datasets were both obtained from the Allen Brain Atlas using the AllenSDK package (`https://allensdk.readthedocs.io/en/latest/index.html`).

Code Availability

All code can be accessed by emailing the corresponding authors.

7 Supplemental Figures

Figure S1: **StreamNet architecture schematic.** The first four convolutional layers of AlexNet best corresponded to all the mouse visual areas) These convolutional layers were used as the basis for our StreamNet architecture variants. The number of parallel streams, N, was varied to be one (single-stream), two (dual-stream) or six (six-stream).

Figure S2: **Shallow architectures trained with contrastive objective functions yield the best matches to the neural data (calcium imaging dataset).** As in Figure 2, but for the calcium imaging dataset. **A**. The median and s.e.m. neural predictivity, using PLS regression, across neurons in all mouse visual areas except RL. $N = 16228$ units in total (RL is excluded, as mentioned in Section 2). Red denotes our StreamNet models trained on contrastive objective functions, blue denotes our StreamNet models trained on RotNet, turquoise denotes our StreamNet models trained in a supervised manner on ImageNet and on CIFAR-10, green denotes untrained models (random weights), orange denotes our StreamNet models trained depth prediction, purple denotes our StreamNet models trained on autoencoding, brown denotes contrastive AlexNet, pink denotes contrastive ResNet-18 (both trained on instance recognition), black denotes the remaining ImageNet supervised models (primate ventral stream models), and grey denotes the MouseNet of Shi et al. (2020) and our variant of this architecture. Actual neural predictivity performance can be found in Table S3. **B**. Each model's performance on ImageNet is plotted against its median neural predictivity across all units from each visual area. All ImageNet performance numbers can be found in Table S3. Color scheme as in **A**.

Figure S3: **Shallow architectures trained with contrastive objective functions yield the best matches to the neural data (RSA). A**. The median and s.e.m. noise-corrected neural predictivity, using RSA, across $N = 39$ and $N = 90$ animals for the Neuropixels and calcium imaging dataset respectively (across all visual areas, with RL excluded for the calcium imaging dataset, as mentioned in Section 2). Red denotes our StreamNet models trained on contrastive objective functions, blue denotes our StreamNet models trained on RotNet, turquoise denotes our StreamNet models trained in a supervised manner on ImageNet and on CIFAR-10, green denotes untrained models (random weights), orange denotes our StreamNet models trained depth prediction, purple denotes our StreamNet models trained on autoencoding, brown denotes contrastive AlexNet, pink denotes contrastive ResNet-18 (both trained on instance recognition), black denotes the remaining ImageNet supervised models (primate ventral stream models), and grey denotes the MouseNet of Shi et al. (2020) and our variant of this architecture. **B**. We plot each model's performance on ImageNet against its median neural predictivity, using RSA, across visual areas. All ImageNet performance numbers can be found in Table S3. Color scheme as in **A**.

Figure S4: **Structural and functional factors leading to improved neural response predictivity (calcium imaging dataset).** **A**. As in Figure 3A, our dual stream variant (red) and AlexNet (brown) were trained using lower resolution ImageNet images and in a contrastive manner. Each image was downsampled from 224×224 pixels, the image size typically used to train primate ventral stream models, to various image sizes. Training models on resolutions lower than 224×224 pixels generally led to improved neural predictivity. The median and s.e.m. across neurons in each visual area is reported. As mentioned in Section 2, visual area RL was removed from the calcium imaging neural predictivity results. Refer to Table S1 for N units per visual area. **B**. As in Figure 3B, AlexNet was either untrained, trained in a supervised manner (ImageNet) or trained in an unsupervised manner (instance recognition). We observe that the first four convolutional layers provide the best fits to the neural responses for all the visual areas while the latter three layers are not very predictive for any visual area. As mentioned in Section 2, visual area RL was removed from the calcium imaging neural predictivity results.

Figure S5: **Inter-animal consistency can increase with more stimuli. A**. Inter-animal consistency under PLS regression evaluated on the train set (left bars for each visual area) and test set (right bars for each visual area), for both Neuropixels and calcium imaging datasets. The horizontal lines are the internal consistency (split-half reliability). **B**. Inter-animal consistency under PLS regression on the train set (dotted lines) and test set (straight lines), aggregated across visual areas. Each dot corresponds to the inter-animal consistency evaluated across 10 train-test splits, where each split is a sample of the natural scene image set corresponding to the percentage (x-axis). Note that RL is excluded for calcium imaging, as explained in the text. The median and s.e.m. across neurons is reported for both panels. Refer to Table S1 for N units per visual area.

Figure S6: **Inter-animal consistency as a function of the number of units in the datasets for different mapping transforms.** Inter-animal consistency was extrapolated across the number of units in each dataset using a log-linear function ($f(n) = a \log_{10}(n) + b$, where a and b are fit as parameters via least squares, and n is the sample size factor). This analysis reveals that inter-animal consistency of the Neuropixels dataset approaches 1.0 more rapidly than it does for the calcium imaging dataset. Inter-animal consistency evaluated at a sample size factor of one indicates the consistency when all the existing units in the datasets are used (i.e., inter-animal consistency values reported in Figure 1A).

Figure S7: **Spatial frequency and orientation tuning preferences are different for Contrastive AlexNet models that were trained on images of dimensions** 64×64 **or** 224×224 **pixels.** The first convolutional layers of both Contrastive AlexNet models were evaluated for their spatial frequency and their orientation tuning preferences. A set of fixed-size Gabor patches (each of size 224×224 pixels) were presented to each model and each artificial neuron's spatial frequency or orientation tuning curves was computed. Since the model layer is convolutional, we do not need to compute tuning curves for every neuron in the convolutional output. Instead, we obtain a set of representative neurons that are each associated with each convolutional filter. Concretely, if there are 64 convolutional filters, we will obtain tuning curves for 64 representative neurons. From this set of representative neurons, we sample, with replacement, 1000 artificial neurons and record each neuron's spatial frequency and orientation tuning preference. Each artificial neuron's spatial frequency preference was defined to be the spatial frequency at which the tuning curve achieved its maximum value (similarly for the neuron's orientation tuning preference). We find that the mean spatial frequency tuning preference (dotted red lines in the top row) and the mean orientation tuning preference (dotted red lines in the bottom row) are significantly different between the two models, quantified via a two-tailed t-test, where the null hypothesis is that there is no difference between the means of the distributions (spatial frequency: $p = 1.5 \times 10^{-30}$; orientation: $p = 0.0001$).